

Service systems modelling and simulation: the SERGENT distributed approach

Thècle Alix, Grégory Zacharewicz, Bruno Vallespir

▶ To cite this version:

Thècle Alix, Grégory Zacharewicz, Bruno Vallespir. Service systems modelling and simulation: the SERGENT distributed approach. Enterprise interoperability VI, Springer International Publishing, pp.357-367, 2014, 10.1007/978-3-319-04948-9_30. hal-01004812

HAL Id: hal-01004812 https://hal.science/hal-01004812

Submitted on 15 Apr 2021

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Service Systems Modeling

- and Simulation: The Sergent Distributed
- ³ Approach
- ⁴ Thècle Alix, Gregory Zacharewicz and Bruno Vallespir

Abstract The economy is dominated by the service sector. Citizens see services 5 as a way to have access to basic or complex commodities, to address environmental problems while manufacturers consider them as a way to differentiate themselves from the competition, to be closer to their customers and to improve the shopper experience. Services are of a huge importance in the national and international economy and are discussed in many domains: human and social 10 science, manufacturing science, business domain, IT domain, etc. Several concepts 11 related to service have merged as well as new scientific disciplines. General issues 12 linked to service design, service implementation, service operation management, 13 service quality, service modeling and simulation, product-service system design 14 are still under consideration and the multiplicity of the domains concerned failed 15 to come up with unanimous answer. This paper proposes a contribution to service 16 modeling and simulation that can potentially be used in any area. The proposed 17 model is based on the most relevant concepts coming from a specialized literature 18 review on services. A distributed simulation model of service is then proposed. 19

Keywords Service system Conceptual modelling Distributed simulation
 G-DEVS

22

G. Zacharewicz

B. Vallespir e-mail: bruno.vallespir@ims-bordeaux.fr

T. Alix (&) G. Zacharewicz B. Vallespir University of Bordeaux, IMS, UMR 5218, 351 cours de la Libération 33400 Talence, France e-mail: thecle.alix@ims-bordeaux.fr

e-mail: gregory.zacharewicz@ims-bordeaux.fr

²³ 1 Introduction

The service sector is particularly important in the current economy and is now between 70 and 80 % of the gross national product of the developed and developing countries. The tertiary sector drove the recent job creation, contributing to more than 4 million of "full-time equivalents" between 1990 and 2009 in France while the other business sectors lost 1.4 millions over the same period. In 2009, it represented about three quarters of the value added and employed 89 % of the working population.

Today, the proportion of unsatisfied services demand lead to the creation of new 31 companies belonging to the service sector and de facto to the increase in the 32 number of employed persons in this sector. As a result is an increase of the 33 competition in both market and non-market-services which rises many questions 34 such as the management of the service production process, the service productivity 35 measurement, the quality measurement of the services supplied and of the activ-36 ities contributing to provide them, as well as the measurement of the real service 37 value-added for customers. Accordingly, it becomes imperative for those com-38 panies producing services to rationalize and to industrialize their practices and to position themselves clearly in the competition regarding their value-added. 40

To prepare this shift, obviously approaches from the secondary sector of production could be reuse. Unfortunately, optimization models stemming from industry do not allow to analyse the service value chains because of its specific characteristics: a fuzzy border between production and distribution, a context dependent value, a customer participation to the production even to the design of the service, only few physical movement of material and finally the impossibility to reduce the hand of work.

Before focusing on the rationalisation of service production activities, it is of 48 vital importance to define the production ins and outs and to clarify upstream what 49 a service is. On the later point, it must be noted that each domain interested in 50 services proposes its own definition and characterization of the concept. Accord-51 ingly, the paper proposes a conceptual model of services as broad as possible, 52 based on a multidisciplinary literature review on the service concept and on the 53 service production as well as some approaches that directly or indirectly address 54 service production. At the end, the model is simulated to verify dynamically the 55 correctnesss of its behavior regarding a temporal sequence chaining. 56

⁵⁷ 2 A Multidisciplinary State of the Art of the Service ⁵⁸ Concepts

59 Some disciplines such as the Management Sciences are being interested for a long

time in services. Its contribution is multiple. Regarding definition, a service is

defined at the same time by opposition to goods [1, 2], as an activity [3, 4] and as a

result [5, 6]. Each point of view leads to introduce specific notions: some works aims at characterizing the system producing the service often called service delivery system [7]; while others propose specific service characteristics called IHIP characteristics standing for immateriality, heterogeneity, inseparability, and perishability [8–11].

Computer sciences address the concept of service through the service oriented 67 architectures (SOA) or the IT services. A functionality is decomposed into a set of 68 functions or of services supplied by components. A business service is a company 69 functionality that seems to be atomic from the service consumer point of view. In 70 this frame, a service is a connection to an application offering an access to some of 71 its functionalities [12]. It appoints an action executed by a "service provider" 72 component to the attention of a "service consumer" component, possibly based on 73 another system. A Service Broker enables to choose the service that fits the best 74 the requirements among the available ones. 75

The functional analysis or value engineering method used in product design 76 does not evoke directly the concept of service but focuses on the concept of 77 function that is similar to a certain extent to the concept of service. The functional 78 analysis was firstly used to identify the needs within the frame of new products 79 design [13]. The most known approach that joins the functional analysis into this 80 frame is the value engineering method. It is characterized by a functional approach 81 proposing to formulate the problem in terms of objectives rather than in terms of 82 solutions. For that concern, the value engineering method rests on several fun-83 damental concepts: the value [14], the need [15] and the function [16]. The 84 functions of a product define what the product (or product subset) is doing or what 85 it is going to do. That perspective is very close to the service concept.

The service science, management and engineering (SSME) addresses several concepts relative to services. It aims at a better understanding of design, evolution, and emergent properties of service systems and also how the innovation leads to productivity gains in this sector [17]. The SSME consider the services as processes, performances or else results that a person (company, organization) realizes for the profit of another company/organization. Several approaches such as "the triptych of technical criteria" [18] or the "triangle of services" are proposed [19].

₉₄ 3 Service System Modelling

This section presents a conceptual model of service based on the above-presented contributions. The objective is to embrace the main part of these contributions to be as generic as possible. The result is a conceptual model based on the fundamental concepts related to services [20–22].



Fig. 1 Basic principle and representation of a sergent

⁹⁹ 3.1 Basic Principles: The Sergent

The basic principle of the proposed approach is that a service is an interaction within a service provider/consumer couple oriented from the provider towards the consumer. The intensity of the service delivered grows in the same way than a parameter that characterises the provider/consumer coupling. A provider is identified with regard to its function and is noted P. A consumer is characterized by its need and is noted C (Fig. 1, left part).

Of course, an object cannot be limited to be a provider or a consumer. That is 106 why objects are generally considered to be able to behave simultaneously as both. 107 The initial principle presents an object as a one service provider or consumer. 108 Obviously, a complex object is able to provide several services and/or to consume 109 several ones. Accordingly, an object can be a provider/consumer of several ser-110 vices (Fig. 1, right part). Service delivery relations become then more complex i.e. 111 each relation is defined for a given service. An object is then part of a service 112 delivery series, linked to another upstream object as service consumer and a 113 downstream object as service provider. 114

The "object" talked about up to now will be called an "agent of service" or a service agent" or, in short, a "sergent".

117 3.2 Service Delivery Process Dynamics

For realizing the service delivery process, a consumer and a provider require to be coupled. The coupling steps are illustrated in Fig. 2.

The abovementioned situations suppose that the service delivery process can only be led during the coupling. Obviously, the interaction between the service supplier/consumer is the main part of the service delivery process. However, in more complex cases both actors can require to be prepared in an upstream phase (pre-process) and to get free in a downstream phase (post-process) (Fig. 3).

¹²⁵ The corresponding phases are the following ones:

• Initialization: this phase does not require the coupling to be established but requires to know that the service must be provided. Information on the service need is necessary to activate the phase.



Fig. 3 The whole service delivery process

• Customization and contextualisation: in case the service is not standard, a phase of customization based on information coming from the consumer is to be envisaged. The contextualisation focuses on the adaptation to the context (consumer, surrounding conditions, etc.) of the service to be provided and of the service delivery process.

• Closing and de-contextualisation: phases exist when both actors require a process to close the activity. This process is similar to the initialization phase one but occurs after the service delivery.

¹³⁷ 3.3 Function Capacity and Need Load

A sergent may use its function in different ways: possibility to implement a function one or several times, in a successive or simultaneous way. These operational situations differ according to the sergent capacity to implement a function.
 Conversely, a sergent need can lead to different load levels.

Valuation of capacity and load: the capacity is a variable belonging to an interval [0, Max_c]. When the capacity is lower than Max_c, the sergent is able to implement the function but not with its maximum potential. The function capacity and need load are time variables. In particular, the provider capacity can be low or non-existent because the sergent is occupied or not operational for example.

¹⁴⁷ Capacity variability: several phenomena can lead to a temporary or long-¹⁴⁸ lasting capacity variation of a sergent to provide a service. When a sergent pro-¹⁴⁹ vides a service, its capacity decreases. Once the service provided and the service ¹⁵⁰ delivery process ended, two situations can occur: either the capacity provides to its ¹⁵¹ initial value (long-lasting function) or the capacity maintains its new value (con-¹⁵² sumable function). The first case corresponds to non-perishable sergents while the ¹⁵³ second one corresponds to the consumption of not renewable resources.

In the case of long-lasting functions, several phenomena can appear: wear (capacity decreases each time the process is launched), learning (capacity increases each time the process is launched) and unlearning phenomenon (capacity decreases because the process is not launched as often as it should).

158 3.4 Provider/Consumer Matching

¹⁵⁹ The provider/consumer matching is based on the following mechanism.

Function statement. A provider declares his functions in a "service directory" that indicates the precise nature of the proposed functions. The function statement is to be made according to a standard expressed in a "service repository". The nature of the function is the static part of the statement while the capacity that can be used at a moment corresponds to the dynamic part (Fig. 4, left part).

Matching. The dynamic is the following (Fig. 4, right part): (1) expression of needs by the consumer, (2) comparison to functions reported in the service repository, (request), (3) choice among providers able to fulfil the need, (4) provider selection.

¹⁶⁹ 4 Service System Simulation

Indeed, the service modelling requires also the modelling of the interactions
 between multiple services; this process can lead very quickly to a significant level
 of complexity from a static point of view and even more in a dynamic view. We



Fig. 4 Provider/consumer matching

proposed in previous works [23, 24] a first tentative to represent service in sim-173 ulation. We therefore focus in this paper on the establishing operations for a single 174 service coupling in the G-DEVS formalism [25]. This discrete formalism is 175 selected because of its formal property and its time management capability. We 176 propose to model each service component through a G-DEVS model based on 177 attributes. The model attributes are described from a qualitative and quantitative 178 point of view and all elements (actors and material) that interact within its envi-179 ronment are required. Once the description is complete, the described component 180 can integrate a G-DEVS based library of service components: the service repos-181 itory. The prospect of a break in service into four subsets then seemed obvious. 182 These four models are: 183

- The sergent requesting the service (here sergent B is the consumer),
- The service provider (here sergent A),
- The coupling as the association between two sergents that will achieve the service delivery process, and
- The service delivery process 'service providing').

¹⁸⁹ 4.1 Coupled model

The coupled model (Fig. 5 shows the global architecture) presents the G-DEVS component required for the global simulation of the process. The components 1 and 2 are the A and B models. The component 3 is a coupling model used to connect the models paired for the service. The component 4 is used to orchestrate the process steps defined Sect. 3.2.

¹⁹⁵ 4.2 The Service Requester: Sergent B

The G-DEVS atomic model corresponding to the sergent B is an applicant for a service and its operations are detailed. This model describes the sergent behavior during the process of service delivery coupling.



Fig. 5 Architecture of the coupled model of service delivery

The G-DEVS model follows the coupling steps described in §3. It communicates with the service delivery model. To assume the simulation execution, the states, event and temporal information have been added. These data are not related in this example to any information coming from a real system. The goal of the simulation is the verification of different correct communication sequences. Operations are as follow:

- Every five time units (again: arbitrary chosen), the model B launches the
 comparison of its P/S potential intensity over a threshold value. This comparison is expressed as a condition on the internal transition.
- 208 2. The model function sends a request (DFb1) to the service provider (sergent A).
- ²⁰⁹ 3. Positive response is received when sergent A is able to achieve this service.
- 4. Negative response is received when A is not available or not competent for this
 service achievement, a request will be send to another sergent.
- 5. Sending an acknowledgment to sergent A to tell them that the service can be achieved and to lock between them a delivery process.
- 6. Sending "ok_coupling" to external produce model.
- 7. Pending the external event "end_SD" meaning that the production of the
 service is completed.
- 8. Back to the waiting phase, the service was rendered, the intensity of sergent B
 to decrease the capacitance value function of sergent A demand. We note that
 some strategy can keep the value of the sergent B since some service potential
- is infinite.

221 4.3 The service provider: Sergent A

- This section is introducing the G-DEVS atomic model of the service provider
- sergent A. An explanation of the model and its operations is detailed here.

- 1. The model A is expecting a request from sergent B. 224
- 2. A tests the ability to get the function (FC1a) and the load required by sergent B 225
- (NL1b). If the ability and capacity of A is greater than or equal to the need and 226 load of B then the service is feasible. 227
- 3. Same as step 2; if the capacity is lower than the load of B then the service will 228 not be feasible. 229
- 4. The service is not feasible, the supplier is informed the consumer via a message 230 object "NOK". 231
- 5. The service can be done, A sends to B "OK". 232
- 6. The model waits for the acquittal of sergent B to produce the service. 233
- The model awaits a response from an external "process" models and indicating 234 that the service is in progress. 235
- 8. The model pends an external event "end_SD_OK" from the "process" model. 236
- 9. The process is over and the ability to provide the function of the particular 237 service A can be reduced (consumption) or increased (experience).
- 238
- 10. The service is completed. The ability of A can stay decreased or can recover 239 its initial value with a gain of experience that increases its ability (the 240 241
 - hypothesis can be to gain 10 % capacity acquired for each service delivery).

4.4 Coupling and Decoupling 242

This atomic model enables the coupling orchestration of two sergents before the 243 service delivery process and manages the notion of decoupling at the end of the 244 service. This model is labelled 3 in Fig. 5. Its main operations are the followings. 245 It starts by waiting an event from the sergent A informing that it is ready and 246 looking for a delivery process coupling. Then it is waiting for an event from the 247 sergent B answering that it is available and capable regarding the load and com-248 petence required by A. Then the coupling can be realized. Gathering the infor-249 mation, the model is informing both participants. Then it is waiting for an event 250 informing of the end of the service delivery to return to the standby state. This last 251 step is producing the end of the coupling. 252

4.5 The Service Delivery Process 253

A last G-DEVS atomic model is required to define the characteristics and simulate 254 the service delivery process behaviour (service delivery model 4 in Fig. 5). 255

This model starts by waiting an event to be in-formed that a coupling is ok. At 256 this time, it computes the characteristics of this service delivery including cou-257 pling, duration, quantity of load and experience acquired at the end. It informs by 258 output sending the "SD" settings to the model participants and set them in pro-259 gress. When the service is ended, it informs the participants by sending to output 260 "end_SD". 261

The simulation concludes and illustrates the choreography between the supplier 262 sergent and the receiver sergent. It shows clearly the communication steps during 263 the service delivery. Nevertheless, the question is still on quantities and values 264 used to define the potential of the sergent and the duration of the steps. 265

5 Conclusion 266

The paper presents a conceptual model of service and service delivery which takes 267 into account notions and concepts stemming from disciplines initially remote but 268 which become integrated rather naturally into a coherent set. The proposed con-269 cepts contribute to a first level of model that requires nevertheless to be completed. 270 Others concepts need to be explored and some questions need to find response. For 271 example, how to select a provider when the function capacity is similar from one 272 to another? or else, in the case of service composition, how to decide the com-273 position? and how to ensure its coherency? 274

Considering perspectives to that work, three concepts need to be explored.

At first, considering the fact that a way to approach the concept of service is to 276 make the difference between buying a service and buying a product providing a 277 service, it is necessary to take into account into the model all the elements focusing 278 the transactional aspect around the sergent or around its functions. 279

Then, the sergent life cycle was not envisaged. Nevertheless, knowing in which 280 phases of its life cycle a sergent is really able to implement its functions, or 281 knowing what it becomes in the other phases or identifying the phases when it will 282 consumes a service are so many questions which have to find an answer within the 283 framework of a model of life cycle. 284

On the simulation aspect, the paper has provided a preliminary work to define 285 the root concepts that can be modelled and simulated. It has focused on splitting 286 the service delivery into different steps used to couple a service provider and a 287 consumer. It opens the research in this domain where few works considering 288 quantitative and dynamic aspects already exist. As perspective the authors are 289 considering the definition of a simulation platform running an open space popu-290 lated by autonomous sergents entities. Once a sergent needs a service, it will try to 291 connect to a service supplier in its neighbourhood (that needs to be defined). 292

Finally, the measure of a service remains a huge problem. In equal function, can 293 the service of a provider be considered as upper to that of another one? This 294 problem of the measure is certainly the most difficult to be settled. Nevertheless, it 295 would enable to clear up some other aspects presented here. 296

Finally, this model has started to be tested on academic cases [20]. The tests on 297 real cases have to be processed I the near future. 298

275

299 References

317

- 1. Rathmell, J. M. (1966). What is meant by services? Journal of Marketing, 30, 32–36.
- 2. Judd, V. C. (1964). The case for redefining services. Journal of Marketing, 28, 58–59.
- 302 3. Berry, L. L. (1980). Services marketing is different. Business Journal, 30, 24–29.
- 4. Lovelock, C., Wirtz, J., & Lapert, D. (2004). Marketing des services. London: Pearson
 Education.
- 5. Hill, T. P. (1977). On goods and services. Review of Income and Wealth, 23(4), 315–338.
- 6. Zarifian, P. (2001). Valeur de service et compétence, in: La relation de service: regards croisés, 28, L'Harmattan.
- ³⁰⁸ 7. Eiglier, P., & Langeard, E. (1987). Servuction, le marketing des services. Mc Graw Hill.
- 8. Rosengren, W. R. (1968). Organisational age structure and orientation toward clients. Social
 Forces, 47(1), 1–11.
- 9. Issac, J. (1996). Les codes de déontologie: outils de gestion de la qualité dans les activités de services. PhD thesis, univ. Paris Dauphine.
- 10. Dumoulin, C., & Flipo, J. P. (1991). Entreprises de services: 7 facteurs clés de réussite. Ed.
 d'organisation.
- ³¹⁵ 11. Shostack, G. L. (1977). Breaking free from product marketing. Journal of Marketing, 41,
 ³¹⁶ 73–80.
 - 12. Raymond, G. (2007). SOA: Architecture logique, principes, structures et bonnes pratiques.
- Miles, L. D. (1963). Definitions. Lawrence D. Miles value Engineering Reference Center,
 Wendt Library.
- I4. Grandhaye, J. P., & Soltan, E. (2002). Value management project: Processing unforeseen
 events in design and production activities; a methodology and a case study. In 5th European
 Project Management Conference.
- 15. Perrin, J. (2004). Valeurs et développement durable : questionnement sur la valeur
 économique. L'harmattan.
- I6. Grandhaye, J. P., & Poisson, P. (2001). Le Management par Valeur pour Concevoir et Rédiger un Projet d'Etablissement. International Congress AFAV.
- I7. Zhao, G., Perros, H. G., & Xin, Z. (2009). How service science management and engineering
 (SSME) can evolve to an academic discipline? International Journal of Web Engineering and
 Technology, 5(4), 459–467.
- 18. Spohrer, J., Maglio, P., Bailey, J., & Gruhl, D. (2007). Steps toward a science of service
 systems. IEEE Computer, 40(1), 71–77.
- 19. Tabas, L. (2007). Designing for service systems. ISD Symposium, UCB I School Report.
- 20. Touzi, W. (2001). Conceptualisation et modélisation de la production de service: application
 aux domaines de la santé et de l'enseignement. PhD thesis, Univ. Bordeaux 1.
- Touzi, W., Alix, T., & Vallespir, B. (2012). Contribution au développement d'un modèle
 conceptuel du service et de la production de service. MOSIM, Bordeaux, France, 6-8 June
 2012.
- Touzi, W., Alix, T., & Vallespir, B. (2012). Contribution to the development of a conceptual
 model of service and service delivery. APMS, Rhodes, Greece, 24–26 September 2012.
- Zacharewicz, G., Alix, T., & Vallespir, B. (2009) .Services modeling and distributed
 simulation DEVS/HLA supported. In Winter Simulation Conference, Austin, Texas, 13–16
 December 2009.
- 24. Alix, T., & Zacharewicz, G. (2012). Product-service systems scenarios simulation based on
 G-DEVS/HLA: Generalized discrete event specification/high level architecture. Computers
 in Industry, 63(4), 370–378.
- 25. Giambiasi, N., Escude, B., & Ghosh, S. (2000). GDEVS: A generalized discrete event
 specification for accurate modeling of dynamic systems. Transactions of the Society for
 Computer Simulation International, 17(3), 120–134.
- 26. Do Manh, H. (2005). Modélisation des services dans le cadre de la mobilité, training period
 report, Institut de la francophonie pour l'informatique, Hanoi, Vietnam.