

See discussions, stats, and author profiles for this publication at: <https://www.researchgate.net/publication/260083798>

Cost-effectiveness of Climate Change Adaptation Strategies for RC Structures Exposed to Chloride Ingress: Application to E....

Conference Paper · January 2013

CITATIONS

0

READS

7

5 authors, including:



Emilio Bastidas-Arteaga

University of Nantes

108 PUBLICATIONS 481 CITATIONS

SEE PROFILE



Mark G. Stewart

University of Newcastle

255 PUBLICATIONS 4,576 CITATIONS

SEE PROFILE



Franck Schoefs

University of Nantes

319 PUBLICATIONS 1,046 CITATIONS

SEE PROFILE



Xiaoming Wang

Monash University / Swinburne University of ...

148 PUBLICATIONS 2,032 CITATIONS

SEE PROFILE

Some of the authors of this publication are also working on these related projects:



Effects of climatic and mechanical variations on the durability of timber structures [View project](#)



MRGenCi - French Network for Risk Management in Civil Engineering [View project](#)

Cost-effectiveness of Climate Change Adaptation Strategies for RC Structures Exposed to Chloride Ingress: Application to Existing Structures in France

Emilio Bastidas-Arteaga^{1a}, Mark G. Stewart^b, Franck Schoefs^a, Stacey Dravitzki^c, Xiaoming Wang^c

^aLUNAM Université, Université de Nantes-Ecole Centrale Nantes, GeM, Institute for Research in Civil and Mechanical Engineering/Sea and Littoral Research Institute, CNRS UMR 6183/FR 3473, Nantes, France.

^bAustralian Research Council Professorial Fellow Director, Centre for Infrastructure Performance and Reliability, The University of Newcastle, New South Wales, 2308, Australia

^cCSIRO Climate Adaptation Flagship and CSIRO Ecosystem Sciences, Highett, Vic, Australia

Abstract

Reinforced concrete (RC) structures are subjected to environmental actions that affect their performance, serviceability and safety. Among these actions, chloride ingress leads to corrosion initiation and its interaction with service loading could reduce its operational life. Experimental evidence indicates that chloride ingress is highly influenced by weather conditions in the surrounding environment. On the other hand, studies on global warming announce several changes in climate that could affect RC durability. Therefore, both structural design and maintenance should be adapted to these new environmental conditions.

This work focuses on the assessment of the costs and benefits of two climate adaptation strategies for existing RC structures subjected to chloride ingress and climate change. RC structures built in France at different periods under different construction codes (CCBA, BAEL, EUROCODE) will be studied in this work. Concerning environmental actions, historic weather records are used to estimate the current deterioration state and several climate change scenarios will be considered for the assessment of climate change effects. The adaptation strategies aim to reduce the impact of chloride-induced corrosion damage increasing the corrosion initiation time. It is supposed herein that adaptation strategies will take place after a repair action in which the chloride-polluted concrete cover is rebuilt. These adaptation strategies are: (i) increase in concrete cover, and (ii) increase in strength grade of concrete. Their cost-effectiveness will be measured in terms of Benefit to Cost Ratio (BCR) and the probability that BCR exceeds unity –i.e., $\Pr(\text{BCR}>1)$. BCR is selected because it seems to be a metric that government and policy makers are familiar with. The results of the paper will provide practical advice to policy makers to improve the management of RC structures under a changing climate.

Keywords: chloride ingress, climate change, climate adaptation, reinforced concrete, corrosion, cost-benefit ratio, reliability, existing structures.

¹ Corresponding Author: phone: +33 2 51 12 55 24, email: emilio.bastidas@univ-nantes.fr