

**This document must be cited according to its final version
which is published in a conference proceeding as:**

**J. Qian¹²³, P. Dufour¹ , M. Nadri¹
`Observer and model predictive control for on-line parameter
identification in nonlinear systems",
Proceedings of the 10th IFAC International Symposium
on Dynamics and Control of Process Systems (DYCOPS),
Mumbai, India, pp. 571-576, 2013.**

**All open archive documents of Pascal Dufour are available at:
<http://hal.archives-ouvertes.fr/DUFOUR-PASCAL-C-3926-2008>**

**The professional web page (Fr/En) of Pascal Dufour is:
<http://www.lagep.univ-lyon1.fr/signatures/dufour.pascal>**

**The web page of this research group is:
<http://hal.archives-ouvertes.fr/SNLEP>**

1

Université de Lyon, Lyon, F-69003, France; Université Lyon 1;
CNRS UMR 5007 LAGEP (Laboratoire d'Automatique et de GEnie des Procédés),
43 bd du 11 novembre, 69100 Villeurbanne, France
Tel +33 (0) 4 72 43 18 45 - Fax +33 (0) 4 72 43 16 99
<http://www.lagep.univ-lyon1.fr/> <http://www.univ-lyon1.fr> <http://www.cnrs.fr>

2

Acsysteme
Company Acsystème, 4 rue René Dumont, 35000 Rennes, France.
Emails: jun.qian@acsysteme.com

3 This PhD thesis is between the LAGEP and the french company Acsystème which is gratefully acknowledged for the funding. The french ministry of higher education and research, for the financial support of this CIFRE PhD thesis 2011/0876, is also acknowledged.

Observer and model predictive control for on-line parameter identification in nonlinear systems

Jun QIAN^{1,2}, Pascal DUFOUR^{1,3}, Madiha NADRI¹

¹Université de Lyon, Lyon F-69003, Université Lyon 1, CNRS UMR 5007, Laboratory of Process Control and Chemical Engineering (LAGEP), Villeurbanne 69100, France

²Acystème company (IT and Control engineering), Rennes, France

^{1,2}Emails: jun.qian@acsyste.com or qian@lagep.univ-lyon1.fr;
dufour@lagep.univ-lyon1.fr; nadri@lagep.univ-lyon1.fr;

³Project leader and contact. Software website: <http://odoe4ope.univ-lyon1.fr>

10th International Symposium on Dynamics and Control of Process Systems
18-20 December, Mumbai, India



Table of contents

- 1 Context and motivations
- 2 Outline of the proposed approach
- 3 Proposed closed-loop optimal identification approach
 - Closed loop control structure
 - The components
 - Model Predictive Control (MPC): general framework
 - Optimal control law design
- 4 Case study: Delta Wing
 - The unstable nonlinear model of delta wing
 - Review of Jain et al. [2005]
 - Simulation results
- 5 Conclusion
- 6 Contacts, acknowledgements and time for discussion

Context and motivations

- All **model parameters** need to be numerically known for simulation, control or optimization of dynamic processes.
- The optimal experiment design (**OED**) is a classic technique for **parameter estimation**. (Goodwin and Payne [1979], Ljung [1999])
- The OED usually separates parameter identification from the optimal input design (**offline identification**).
- Most applications of OED are reliable on **linear** or **approximated linearized** models.
- Recently, the coupled online OED techniques and parameter estimation has been developed for **open loop stable systems without input/output process constraint**. (Jayasankar et al. [2010], Zhu and Huang [2011])

Context and motivations

- All **model parameters** need to be numerically known for simulation, control or optimization of dynamic processes.
- The optimal experiment design (**OED**) is a classic technique for **parameter estimation**. (Goodwin and Payne [1979], Ljung [1999])
- The OED usually separates parameter identification from the optimal input design (**offline identification**).
- Most applications of OED are reliable on **linear** or **approximated linearized** models.
- Recently, the coupled online OED techniques and parameter estimation has been developed for **open loop stable systems without input/output process constraint**. (Jayasankar et al. [2010], Zhu and Huang [2011])

Context and motivations

- All **model parameters** need to be numerically known for simulation, control or optimization of dynamic processes.
- The optimal experiment design (**OED**) is a classic technique for **parameter estimation**. (Goodwin and Payne [1979], Ljung [1999])
- The OED usually separates parameter identification from the optimal input design (**offline identification**).
- Most applications of OED are reliable on **linear** or **approximated linearized** models.
- Recently, the coupled online OED techniques and parameter estimation has been developed for **open loop stable systems without input/output process constraint**. (Jayasankar et al. [2010], Zhu and Huang [2011])

Context and motivations

- All **model parameters** need to be numerically known for simulation, control or optimization of dynamic processes.
- The optimal experiment design (**OED**) is a classic technique for **parameter estimation**. (Goodwin and Payne [1979], Ljung [1999])
- The OED usually separates parameter identification from the optimal input design (**offline identification**).
- Most applications of OED are reliable on **linear** or **approximated linearized** models.
- Recently, the coupled online OED techniques and parameter estimation has been developed for **open loop stable systems without input/output process constraint**. (Jayasankar et al. [2010], Zhu and Huang [2011])

Context and motivations

- All **model parameters** need to be numerically known for simulation, control or optimization of dynamic processes.
- The optimal experiment design (**OED**) is a classic technique for **parameter estimation**. (Goodwin and Payne [1979], Ljung [1999])
- The OED usually separates parameter identification from the optimal input design (**offline identification**).
- Most applications of OED are reliable on **linear** or **approximated linearized** models.
- Recently, the coupled online OED techniques and parameter estimation has been developed for **open loop stable systems without input/output process constraint**. (Jayasankar et al. [2010], Zhu and Huang [2011])

Outline of the proposed approach

- Our proposed approach of closed-loop OED for online parameter identification has been initially proposed in [Flila et al. \[2008\]](#) for the **mono-variable case** (SISOSP).
- Synthesize the **online OED** and **online closed-loop parameter identification**.
- For **linear** and **nonlinear** dynamic model based systems.
- Online optimal input design which **optimizes the sensitivities** of the measurements with respect to the unknown constant model parameters.
- Combine **observer design theory** and an on-line predictive controller (**MPC**).
- **Input and output constraints** may be specified to keep the process in a desired operating zone.
- Extend to an **open-loop unstable, nonlinear, and multivariable** case: a delta wing.

Outline of the proposed approach

- Our proposed approach of closed-loop OED for online parameter identification has been initially proposed in [Flila et al. \[2008\]](#) for the **mono-variable case** (SISOSP).
- Synthesize the **online OED** and **online closed-loop parameter identification**.
 - For **linear** and **nonlinear** dynamic model based systems.
 - Online optimal input design which **optimizes the sensitivities** of the measurements with respect to the unknown constant model parameters.
 - Combine **observer design theory** and an on-line predictive controller (**MPC**).
 - **Input and output constraints** may be specified to keep the process in a desired operating zone.
 - Extend to an **open-loop unstable, nonlinear, and multivariable** case: a delta wing.

Outline of the proposed approach

- Our proposed approach of closed-loop OED for online parameter identification has been initially proposed in [Flila et al. \[2008\]](#) for the **mono-variable case** (SISOSP).
- Synthesize the **online OED** and **online closed-loop parameter identification**.
- For **linear** and **nonlinear** dynamic model based systems.
- Online optimal input design which **optimizes the sensitivities** of the measurements with respect to the unknown constant model parameters.
- Combine **observer design theory** and an on-line predictive controller (**MPC**).
- **Input and output constraints** may be specified to keep the process in a desired operating zone.
- Extend to an **open-loop unstable, nonlinear, and multivariable** case: a delta wing.

Outline of the proposed approach

- Our proposed approach of closed-loop OED for online parameter identification has been initially proposed in [Flila et al. \[2008\]](#) for the **mono-variable case** (SISOSP).
- Synthesize the **online OED** and **online closed-loop parameter identification**.
- For **linear** and **nonlinear** dynamic model based systems.
- Online optimal input design which **optimizes the sensitivities** of the measurements with respect to the unknown constant model parameters.
- Combine **observer design theory** and an on-line predictive controller (**MPC**).
- **Input and output constraints** may be specified to keep the process in a desired operating zone.
- Extend to an **open-loop unstable, nonlinear, and multivariable** case: a delta wing.

Outline of the proposed approach

- Our proposed approach of closed-loop OED for online parameter identification has been initially proposed in [Flila et al. \[2008\]](#) for the **mono-variable case** (SISOSP).
- Synthesize the **online OED** and **online closed-loop parameter identification**.
- For **linear** and **nonlinear** dynamic model based systems.
- Online optimal input design which **optimizes the sensitivities** of the measurements with respect to the unknown constant model parameters.
- Combine **observer design theory** and an on-line predictive controller (**MPC**).
- **Input and output constraints** may be specified to keep the process in a desired operating zone.
- Extend to an **open-loop unstable, nonlinear, and multivariable** case: a delta wing.


Outline of the proposed approach

- Our proposed approach of closed-loop OED for online parameter identification has been initially proposed in [Flila et al. \[2008\]](#) for the **mono-variable case** (SISOSP).
- Synthesize the **online OED** and **online closed-loop parameter identification**.
- For **linear** and **nonlinear** dynamic model based systems.
- Online optimal input design which **optimizes the sensitivities** of the measurements with respect to the unknown constant model parameters.
- Combine **observer design theory** and an on-line predictive controller (**MPC**).
- **Input and output constraints** may be specified to keep the process in a desired operating zone.
- Extend to an **open-loop unstable, nonlinear, and multivariable** case: a delta wing.

Outline of the proposed approach

- Our proposed approach of closed-loop OED for online parameter identification has been initially proposed in [Flila et al. \[2008\]](#) for the **mono-variable case** (SISOSP).
- Synthesize the **online OED** and **online closed-loop parameter identification**.
- For **linear** and **nonlinear** dynamic model based systems.
- Online optimal input design which **optimizes the sensitivities** of the measurements with respect to the unknown constant model parameters.
- Combine **observer design theory** and an on-line predictive controller (**MPC**).
- **Input and output constraints** may be specified to keep the process in a desired operating zone.
- Extend to an **open-loop unstable, nonlinear, and multivariable** case: a delta wing.

Closed loop control structure



The components

Model (linear or nonlinear)

$$(M) \begin{cases} \dot{x}(t) &= f(x(t), \theta, u(t)) \\ y(t) &= h(x(t), \theta, u(t)) \end{cases} \quad (1)$$

where $x \in \mathbb{R}^n$ is the state vector, $y \in \mathbb{R}^p$ is the output vector, $u \in \mathcal{U} \subset \mathbb{R}^m$ is the input vector, $\theta \in \mathbb{R}^q$ is the unknown constant parameters vector. f and h are nonlinear functions of suitable dimensions.

Assumptions

- 1 In this study, the unknown model parameters are all constant.
- 2 In the system (1), f and h are C^∞ w.r.t. their arguments.

The components

Model (linear or nonlinear)


$$(M) \begin{cases} \dot{x}(t) &= f(x(t), \theta, u(t)) \\ y(t) &= h(x(t), \theta, u(t)) \end{cases} \quad (1)$$

where $x \in \mathbb{R}^n$ is the state vector, $y \in \mathbb{R}^p$ is the output vector, $u \in \mathcal{U} \subset \mathbb{R}^m$ is the input vector, $\theta \in \mathbb{R}^q$ is the unknown constant parameters vector. f and h are nonlinear functions of suitable dimensions.

Assumptions

- 1 In this study, the unknown model parameters are all constant.
- 2 In the system (1), f and h are C^∞ w.r.t. their arguments.

Closed loop control structure



The components

Observer design for augmented system

System augmented with the unknown constant model parameters.

$$(M_a) \begin{cases} \dot{x}(t) &= f(x(t), \theta(t), u(t)) \\ \dot{\theta} &= 0 \\ y(t) &= h(x(t), \theta(t), u(t)) \end{cases} \quad (2)$$

The augmented state vector $x_a = [x \ \theta]^T$ and the vector function $f_a = [f \ 0]^T$

Observer definition

A general form for an observer for system (2) can be given by

$$(O) \begin{cases} \dot{\hat{x}}_a(t) = f_a(\hat{x}_a(t), u(t)) + g_a(t, h(\hat{x}_a(t), u(t)) - y_p(t)) \\ \text{with: } g_a(t, 0) = 0, \end{cases} \quad (3)$$

such that

- i) if $\hat{x}_a(0) = x_a(0)$, then $\hat{x}_a(t) = x_a(t)$, $\forall t \geq 0$;
- ii) if $\forall x_a(0)$, $\forall \hat{x}_a(0)$, then $\lim_{t \rightarrow +\infty} \|\hat{x}_a(t) - x_a(t)\| = 0$,

where g_a is a function of the output estimation error to be designed.

The components

Observer design for augmented system

System augmented with the unknown constant model parameters.

$$(M_a) \begin{cases} \dot{x}(t) &= f(x(t), \theta(t), u(t)) \\ \dot{\theta} &= 0 \\ y(t) &= h(x(t), \theta(t), u(t)) \end{cases} \quad (2)$$

The augmented state vector $x_a = [x \ \theta]^T$ and the vector function $f_a = [f \ 0]^T$

Observer definition

A general form for an observer for system (2) can be given by


$$(O) \begin{cases} \dot{\hat{x}}_a(t) = f_a(\hat{x}_a(t), u(t)) + g_a(t, h(\hat{x}_a(t), u(t)) - y_p(t)) \\ \text{with: } g_a(t, 0) = 0, \end{cases} \quad (3)$$

such that

- i) if $\hat{x}_a(0) = x_a(0)$, then $\hat{x}_a(t) = x_a(t)$, $\forall t \geq 0$;
- ii) if $\forall x_a(0)$, $\forall \hat{x}_a(0)$, then $\lim_{t \rightarrow +\infty} \|\hat{x}_a(t) - x_a(t)\| = 0$,

where g_a is a function of the output estimation error to be designed.

Closed loop control structure



The components

Sensitivity model

Using the definition of the sensitivity function $(\cdot)_\theta = \frac{\partial(\cdot)}{\partial\theta}$ of a variable (\cdot) with respect to the parameters θ , and the dynamical model (M) , we give the sensitivity model as follows

$$(M_\theta) \begin{cases} \dot{x}_\theta(t) &= \frac{\partial f(x(t), \theta, u(t))}{\partial x} x_\theta + \frac{\partial f(x(t), \theta, u(t))}{\partial \theta} \\ y_\theta(t) &= x_\theta(t), \end{cases} \quad (4)$$

where $x_\theta \in R^{n \times q}$ and $y_\theta \in R^{r \times q}$ are the matrices of sensitivities of the states (the outputs) with respect to the parameters.

The relative-sensitivity function

$$\begin{cases} \bar{x}_\theta(i, j) &= \frac{\theta_j}{x_i} x_\theta(i, j); & i = 1, \dots, n; j = 1, \dots, q \\ \bar{y}_\theta(i, j) &= \frac{\theta_j}{y_i} y_\theta(i, j); & i = 1, \dots, r; j = 1, \dots, q. \end{cases} \quad (5)$$

The components

Sensitivity model

Using the definition of the sensitivity function $(\cdot)_\theta = \frac{\partial(\cdot)}{\partial\theta}$ of a variable (\cdot) with respect to the parameters θ , and the dynamical model (M) , we give the sensitivity model as follows

$$(M_\theta) \begin{cases} \dot{x}_\theta(t) &= \frac{\partial f(x(t), \theta, u(t))}{\partial x} x_\theta + \frac{\partial f(x(t), \theta, u(t))}{\partial \theta} \\ y_\theta(t) &= x_\theta(t), \end{cases} \quad (4)$$

where $x_\theta \in R^{n \times q}$ and $y_\theta \in R^{r \times q}$ are the matrices of sensitivities of the states (the outputs) with respect to the parameters.

The relative-sensitivity function

$$\begin{cases} \bar{x}_\theta(i, j) &= \frac{\theta_j}{x_i} x_\theta(i, j); & i = 1, \dots, n; j = 1, \dots, q \\ \bar{y}_\theta(i, j) &= \frac{\theta_j}{y_i} y_\theta(i, j); & i = 1, \dots, r; j = 1, \dots, q. \end{cases} \quad (5)$$


Model Predictive Control (MPC): general framework

- Advantages:
 - many theoretical papers published
 - +4000 applications in the world (Qin and Badgwell [2003])
- Idea:
 - use the model to predict the future process behavior
 - optimize any specified criteria
 - take account for constrains on measures/estimations
 - closed loop control approach

Model Predictive Control (MPC): general framework

- Advantages:
 - many theoretical papers published
 - +4000 applications in the world (Qin and Badgwell [2003])
- Idea:
 - use the model to predict the future process behavior
 - optimize any specified criteria
 - take account for constrains on measures/estimations
 - closed loop control approach

Closed loop control structure



Optimal control law design

- Time discretization: $t = k \times T_s$ (k = current time index)
- At each k , over the prediction horizon N_p : maximize the norm of the sensitivity $\frac{\partial y_p}{\partial \theta}$ to get "rich" data for parameter identification.

Sensitivity matrix

$$\bar{y}_{\theta|k} = \begin{bmatrix} \bar{y}_{\theta}(1, 1)|_{l|k} & \bar{y}_{\theta}(1, 2)|_{l|k} & \dots & \bar{y}_{\theta}(1, q)|_{l|k} \\ \bar{y}_{\theta}(2, 1)|_{l|k} & \ddots & & \vdots \\ \vdots & & \ddots & \vdots \\ \bar{y}_{\theta}(r, 1)|_{l|k} & \dots & \dots & \bar{y}_{\theta}(r, q)|_{l|k} \end{bmatrix}. \quad (6)$$

which gives at the current instant k the prediction at a future time $l \leq k$ ($l \in [k, k + N_p]$) of the normalized outputs sensitivity \bar{y}_{θ} .

Fisher Information Matrix (FIM)

$$M_{l|k} = \|\bar{y}_{\theta|k}\|^2 \quad (7)$$

Optimal control law design

- Time discretization: $t = k \times T_s$ (k = current time index)
- At each k , over the prediction horizon N_p : maximize the norm of the sensitivity $\frac{\partial y_p}{\partial \theta}$ to get "rich" data for parameter identification.

Sensitivity matrix

$$\bar{y}_{\theta|k} = \begin{bmatrix} \bar{y}_{\theta}(1, 1)|_{l|k} & \bar{y}_{\theta}(1, 2)|_{l|k} & \dots & \bar{y}_{\theta}(1, q)|_{l|k} \\ \bar{y}_{\theta}(2, 1)|_{l|k} & \ddots & & \vdots \\ \vdots & & \ddots & \vdots \\ \bar{y}_{\theta}(r, 1)|_{l|k} & \dots & \dots & \bar{y}_{\theta}(r, q)|_{l|k} \end{bmatrix}. \quad (6)$$

which gives at the current instant k the prediction at a future time $l \leq k$ ($l \in [k, k + N_p]$) of the normalized outputs sensitivity \bar{y}_{θ} .

Fisher Information Matrix (FIM)

$$M_{l|k} = \|\bar{y}_{\theta|k}\|^2 \quad (7)$$

Optimal control law design

- Time discretization: $t = k \times T_s$ (k = current time index)
- At each k , over the prediction horizon N_p : maximize the norm of the sensitivity $\frac{\partial y_p}{\partial \theta}$ to get "rich" data for parameter identification.

Sensitivity matrix

$$\bar{y}_{\theta|k} = \begin{bmatrix} \bar{y}_{\theta}(1,1)|_{l|k} & \bar{y}_{\theta}(1,2)|_{l|k} & \dots & \bar{y}_{\theta}(1,q)|_{l|k} \\ \bar{y}_{\theta}(2,1)|_{l|k} & \ddots & & \vdots \\ \vdots & & \ddots & \vdots \\ \bar{y}_{\theta}(r,1)|_{l|k} & \dots & \dots & \bar{y}_{\theta}(r,q)|_{l|k} \end{bmatrix}. \quad (6)$$

which gives at the current instant k the prediction at a future time $l \leq k$ ($l \in [k, k + N_p]$) of the normalized outputs sensitivity \bar{y}_{θ} .

Fisher Information Matrix (FIM)

$$M_{l|k} = \|\bar{y}_{\theta|k}\|^2 \quad (7)$$

Optimal control law design

- Cost function

$$\begin{cases} F(\bar{y}_{\theta|k}, u_{|k}, y_p(k), \hat{x}_a(k)) = \frac{1}{N_p} \sum_{l=k+1}^{k+N_p} M_{l|k} \\ u_{|k} = \{u(k) \dots u(l) \dots u(k+N_p)\}, l \in [k, k+N_p]. \end{cases} \quad (8)$$

- E-optimality

$$\begin{cases} u_{|k}^* = \arg \max_{u_{|k}} \left(J(u_{|k}) = \frac{\lambda_{\min}(F)}{\lambda_{\max}(F)} \right) \\ u_{|k} = \{u(k) \dots u(l) \dots u(k+N_p)\}, l \in [k, k+N_p]. \end{cases} \quad (9)$$

- Handling specified constraints:

- Constraints on the inputs (physical limitations of the actuator):

$$u_{\min} \leq u(k) \leq u_{\max}, \forall k \quad (10)$$

Velocity constraints may also be added.

- Constraints on the estimated states and/or the measured outputs (dealing with safety, operating zone, production, ...):

$$g_{\min} \leq g(\hat{x}(k), y_p(k), u(k)) \leq g_{\max}, \forall k \quad (11)$$

Optimal control law design

- Cost function

$$\begin{cases} F(\bar{y}_{\theta|k}, u_{|k}, y_p(k), \hat{x}_a(k)) = \frac{1}{N_p} \sum_{l=k+1}^{k+N_p} M_{l|k} \\ u_{|k} = \{u(k) \dots u(l) \dots u(k + N_p)\}, l \in [k, k + N_p]. \end{cases} \quad (8)$$

- E-optimality

$$\begin{cases} u_{|k}^* = \arg \max_{u_{|k}} \left(J(u_{|k}) = \frac{\lambda_{\min}(F)}{\lambda_{\max}(F)} \right) \\ u_{|k} = \{u(k) \dots u(l) \dots u(k + N_p)\}, l \in [k, k + N_p]. \end{cases} \quad (9)$$

- Handling specified constraints:

- Constraints on the inputs (physical limitations of the actuator):

$$u_{\min} \leq u(k) \leq u_{\max}, \forall k \quad (10)$$

Velocity constraints may also be added.

- Constraints on the estimated states and/or the measured outputs (dealing with safety, operating zone, production, ...):

$$g_{\min} \leq g(\hat{x}(k), y_p(k), u(k)) \leq g_{\max}, \forall k \quad (11)$$

Optimal control law design

- **Cost function**

$$\begin{cases} F(\bar{y}_{\theta|k}, u_{|k}, y_p(k), \hat{x}_a(k)) = \frac{1}{N_p} \sum_{l=k+1}^{k+N_p} M_{l|k} \\ u_{|k} = \{u(k) \dots u(l) \dots u(k + N_p)\}, l \in [k, k + N_p]. \end{cases} \quad (8)$$

- **E-optimality**

$$\begin{cases} u_{|k}^* = \arg \max_{u_{|k}} \left(J(u_{|k}) = \frac{\lambda_{\min}(F)}{\lambda_{\max}(F)} \right) \\ u_{|k} = \{u(k) \dots u(l) \dots u(k + N_p)\}, l \in [k, k + N_p]. \end{cases} \quad (9)$$

- Handling specified **constraints**:

- Constraints on the inputs (**physical limitations of the actuator**):

$$u_{\min} \leq u(k) \leq u_{\max}, \forall k \quad (10)$$

Velocity constraints may also be added.

- Constraints on the estimated states and/or the measured outputs (dealing with **safety, operating zone, production, ...**):

$$g_{\min} \leq g(\hat{x}(k), y_p(k), u(k)) \leq g_{\max}, \forall k \quad (11)$$

The unstable nonlinear model of delta wing

The unstable nonlinear model of the system is:

$$\begin{cases} \dot{x}_1(t) &= x_2(t) \\ \dot{x}_2(t) &= \alpha_1 \theta_1 x_1(t) + (\alpha_1 \theta_2 - \alpha_2) x_2(t) + \alpha_1 \theta_3 x_1^3(t) \dots \\ &\dots + \alpha_1 \theta_4 x_1^2 x_2(t) + \alpha_1 \theta_5 x_1 x_2^2(t) + \alpha_3 u(t) \\ y(t) &= [x_1(t) \ x_2(t)], \end{cases} \quad (12)$$

where:

- u is the control input to the model
- α is the known constant parameter vector
- θ is the vector of **five unknown constant parameters**
- input constraints: $-0.01 \leq u \leq 0.01$ (unstable zone in open loop)
- output constraints: $-0.5 \leq y_{p1} \leq 0.5$ (defined by trial and error)

Objective: based on (12) online identify the 5 unknowns parameters.
(more development details on appendix)

Review of Jain et al. [2005]

- Method used in Jain et al. [2005]¹:
 - A feedback linearizing control is used to cancel the nonlinear terms in the plant model and to alter the linear terms such that the closed-loop behavior matches with a specified linear reference model.
 - The reference model is taken to be a second-order linear system.
 - An external forcing signal is chosen to be a damped sinusoidal input in the adaptive control law.
 - Both designs of the reference model and the forcing input are not really discussed.
- Simulation results:
 - Two linear parameters (θ_1 and θ_2) converge to their targets at $t > 1000s$.
 - The convergence of the tree nonlinear parameter estimations(θ_3 , θ_4 and θ_5) to their targets is not achieved.

¹Jain, H., Kaul, V., and Ananthkrishnan, N. (2005). Parameter estimation of unstable, limit cycling systems using adaptive feedback linearization: example of delta wing roll dynamics. *Journal of Sound and Vibration*, 939-960.

Review of Jain et al. [2005]

- Method used in Jain et al. [2005]¹:
 - A **feedback linearizing control** is used to cancel the nonlinear terms in the plant model and to alter the linear terms such that the closed-loop behavior matches with a specified linear reference model.
 - The **reference model** is taken to be a second-order linear system.
 - An **external forcing signal** is chosen to be a damped sinusoidal input in the **adaptive control law**.
 - Both designs of the reference model and the forcing input are not really discussed.
- Simulation results:
 - Two linear parameters (θ_1 and θ_2) converge to their targets at $t > 1000s$.
 - The convergence of the tree nonlinear parameter estimations (θ_3 , θ_4 and θ_5) to their targets is **not achieved**.

¹Jain, H., Kaul, V., and Ananthkrishnan, N. (2005). Parameter estimation of unstable, limit cycling systems using adaptive feedback linearization: example of delta wing roll dynamics. *Journal of Sound and Vibration*, 939-960.

Review of Jain et al. [2005]

- Method used in Jain et al. [2005]¹:
 - A **feedback linearizing control** is used to cancel the nonlinear terms in the plant model and to alter the linear terms such that the closed-loop behavior matches with a specified linear reference model.
 - The **reference model** is taken to be a second-order linear system.
 - An **external forcing signal** is chosen to be a damped sinusoidal input in the **adaptive control law**.
 - Both designs of the reference model and the forcing input are not really discussed.
- Simulation results:
 - Two linear parameters (θ_1 and θ_2) converge to their targets at $t > 1000s$.
 - The convergence of the tree nonlinear parameter estimations (θ_3 , θ_4 and θ_5) to their targets is **not achieved**.


¹Jain, H., Kaul, V., and Ananthkrishnan, N. (2005). Parameter estimation of unstable, limit cycling systems using adaptive feedback linearization: example of delta wing roll dynamics. *Journal of Sound and Vibration*, 939-960.

Simulation results

- Input applied: $u(t)$
- Process outputs: $y_{p1}(t)$ and $y_{p2}(t)$
- Parameter estimation: θ_1 , θ_2 , and θ_3
- Parameter estimation: θ_4 and θ_5
- Initial and final estimation errors:

Simulation results

- Input applied: $u(t)$
- Process outputs: $y_{p1}(t)$ and $y_{p2}(t)$
- Parameter estimation: θ_1 , θ_2 , and θ_3
- Parameter estimation: θ_4 and θ_5
- Initial and final estimation errors:





Simulation results

- Input applied: $u(t)$
- Process outputs: $y_{p1}(t)$ and $y_{p2}(t)$
- Parameter estimation: θ_1 , θ_2 , and θ_3
- Parameter estimation: θ_4 and θ_5
- Initial and final estimation errors:

Simulation results

- Input applied: $u(t)$
- Process outputs: $y_{p1}(t)$ and $y_{p2}(t)$
- Parameter estimation: $\theta_1, \theta_2,$ and θ_3
- Parameter estimation: θ_4 and θ_5
- Initial and final estimation errors:




Simulation results

- Input applied: $u(t)$
- Process outputs: $y_{p1}(t)$ and $y_{p2}(t)$
- Parameter estimation: θ_1 , θ_2 , and θ_3
- Parameter estimation: θ_4 and θ_5
- Initial and final estimation errors:

Simulation results

- Input applied: $u(t)$
- Process outputs: $y_{p1}(t)$ and $y_{p2}(t)$
- Parameter estimation: θ_1 , θ_2 , and θ_3
- Parameter estimation: θ_4 and θ_5
- Initial and final estimation errors:




Simulation results

- Input applied: $u(t)$
- Process outputs: $y_{p1}(t)$ and $y_{p2}(t)$
- Parameter estimation: θ_1 , θ_2 , and θ_3
- Parameter estimation: θ_4 and θ_5
- Initial and final estimation errors:

Simulation results

- Input applied: $u(t)$
- Process outputs: $y_{p1}(t)$ and $y_{p2}(t)$
- Parameter estimation: θ_1 , θ_2 , and θ_3
- Parameter estimation: θ_4 and θ_5
- Initial and final estimation errors:



Simulation results

- Input applied: $u(t)$
- Process outputs: $y_{p1}(t)$ and $y_{p2}(t)$
- Parameter estimation: θ_1 , θ_2 , and θ_3
- Parameter estimation: θ_4 and θ_5
- Initial and final estimation errors:

Simulation results

- Input applied: $u(t)$
- Process outputs: $y_{p1}(t)$ and $y_{p2}(t)$
- Parameter estimation: $\theta_1, \theta_2,$ and θ_3
- Parameter estimation: θ_4 and θ_5
- Initial and final estimation errors:

θ	1	2	3	4	5
Initial error (%)	80	-200	200	80	-200
Final error (%)	0.1	0.4	0.8	-0.26	-2.88

Conclusion

- The **proposed approach** is able to
 - + **design online** the **optimal experiment** under **constraints**;
 - + **identify online model parameters** at the same time.
- The combination of an observer and a predictive control in closed loop improves the **speed** of the parameter estimation.
- The sensitivity criteria improve the **accuracy** of parameter estimation and leads to an optimal control at the same time.
- The input and output **constraints** specify the physical limitations imposed by the system and ensure the efficiency of the OED.
- The proposed approach may be **adapted and tuned** for **any user defined dynamic model**.

Contacts, acknowledgements and time for discussion

Software

- ODOE4OPE (Optimal Design Of Experiments for Online Parameter Estimation)
Email: odoe4ope@univ-lyon1.fr; Website: <http://odoe4ope.univ-lyon1.fr>

People

- Acystème company: Expertise in automation, process control, signal processing, optimization, software development, ...
Website: <http://www.acsysteme.com/en>
- LAGEP: Laboratory of Process Control and Chemical Engineering, UMR 5007 CNRS-UCBL1
Website: <http://www-lagep.univ-lyon1.fr>

Acknowledgements (fundings)

- The french company Acystème
- The french ministry of higher education and research, for the financial support of this CIFRE PhD thesis 2011/0876

Annex A: Delta Wing

- Simulation condition

$$\left\{ \begin{array}{l} \alpha = [0.354 \ 0.001 \ 1] \\ \theta_{Target} = [-0.05686 \ 0.03254 \ 0.07334 \ -0.3597 \ 1.46681] \\ \text{initial values of model states: } [x_{m1}(0) \ x_{m2}(0)] = [0 \ 0] \\ \text{initial estimate of state 2: } \hat{x}_2(0) = -0.01; \\ \text{prediction horizon: } N_p = 5 \\ \text{time of the simulation: } T_{fin} = 1200s \\ \text{sampling time: } T_s = 1s. \end{array} \right. \quad (13)$$

Annex A: Delta Wing

- Observer design for system delta wing
 - System augmented

$$\begin{cases} \dot{x}_a(t) &= A_a(y(t))x_a(t) + B_a(u(t)) \\ y(t) &= C_a x_a(t), \end{cases} \quad (14)$$

which is a state affine system up to output nonlinear injection with:

$$x_a(t) = \begin{bmatrix} x_1(t) \\ x_2(t) \\ \theta_1 \\ \theta_2 \\ \theta_3 \\ \theta_4 \\ \theta_5 \end{bmatrix}; B_a(u(t)) = \begin{bmatrix} 0 \\ -\alpha_3 u(t) \\ 0 \\ 0 \\ 0 \\ 0 \\ 0 \end{bmatrix}; C_a^T = \begin{bmatrix} I_{2 \times 2} \\ 0_{5 \times 2} \end{bmatrix};$$

$$A_a(y(t)) = \begin{bmatrix} 0_{2 \times 1} & A(y(t)) \\ 0_{5 \times 1} & 0_{5 \times 6} \end{bmatrix}; A^T(y(t)) = \begin{bmatrix} 1 & -\alpha_2 \\ 0 & \alpha_1 y_1(t) \\ 0 & \alpha_1 y_2(t) \\ 0 & \alpha_1 y_1^3(t) \\ 0 & \alpha_1 y_1^2(t) y_2(t) \\ 0 & \alpha_1 y_1(t) y_2^2(t) \end{bmatrix},$$

where $I_{2 \times 2}$ is the 2×2 identity matrix, $0_{a \times b}$ is the $a \times b$ matrix of zeros.

Annex A: Delta Wing

- Exponential observer for (14)

Theorem

Assuming that $v(t) := C_a \chi_a(t, x_a(0))$ is regularly persistent for

$$\begin{cases} \dot{x}_a(t) &= A_a(v(t))x_a(t) + B_a(u(t)) \\ y(t) &= C_a x_a(t), \end{cases} \quad (15)$$

for any $x_a(0)$, then the system admits an exponential observer of the form

$$\begin{cases} \dot{\hat{x}}_a(t) &= A_a(y(t))\hat{x}_a(t) + B_a(u(t)) \\ &\dots - RS_\mu(t)^{-1}C_a^T(C_a\hat{x}_a(t) - y_p(t)) \\ \dot{S}_\mu(t) &= -\mu S_\mu(t) - A_a(y(t))^T S_\mu(t) - S_\mu(t)A_a(y(t)) \\ &\dots + C_a^T R C_a, \end{cases} \quad (16)$$

where S_μ is a symmetric positive definite 7×7 matrix, the positive constant $\mu > 0$ and $R > 1$ are the observer tuning parameters.

Annex A: Delta Wing

- Sensitivity model of the delta wing

$$\left\{ \begin{array}{l}
 \dot{x}_{1\theta_1} = x_{2\theta_1} \\
 \dot{x}_{1\theta_2} = x_{2\theta_2} \\
 \dot{x}_{1\theta_3} = x_{2\theta_3} \\
 \dot{x}_{1\theta_4} = x_{2\theta_4} \\
 \dot{x}_{1\theta_5} = x_{2\theta_5} \\
 \dot{x}_{2\theta_1} = \alpha_1(x_1 + \theta_1 x_{1\theta_1}) + (\alpha_1 \theta_2 - \alpha_2)x_{2\theta_1} + 3\alpha_1 \theta_3 x_1^2 x_{1\theta_1} \dots \\
 \quad \dots + \alpha_1 \theta_4 (2x_1 x_{1\theta_1} x_2 + x_1^2 x_{2\theta_1}) + \alpha_1 \theta_5 (x_{1\theta_1} x_2^2 + 2x_1 x_2 x_{2\theta_1}) \\
 \dot{x}_{2\theta_2} = \alpha_1 \theta_1 x_{1\theta_2} + (\alpha_1(x_2 + (\theta_2 x_{2\theta_2}) - \alpha_2 x_{2\theta_2})) + 3\alpha_1 \theta_3 x_1^2 x_{1\theta_2} \dots \\
 \quad \dots + \alpha_1 \theta_4 (2x_1 x_{1\theta_2} x_2 + x_1^2 x_{2\theta_2}) + \alpha_1 \theta_5 (x_{1\theta_2} x_2^2 + 2x_1 x_2 x_{2\theta_2}) \\
 \dot{x}_{2\theta_3} = \alpha_1 \theta_1 x_{1\theta_3} + (\alpha_1 \theta_2 - \alpha_2)x_{2\theta_3} + \alpha_1(x_1^3 + 3\theta_3 x_1^2 x_{1\theta_3}) \dots \\
 \quad \dots + \alpha_1 \theta_4 (2x_1 x_{1\theta_3} x_2 + x_1^2 x_{2\theta_3}) + \alpha_1 \theta_5 (x_{1\theta_3} x_2^2 + 2x_1 x_2 x_{2\theta_3}) \\
 \dot{x}_{2\theta_4} = \alpha_1 \theta_1 x_{1\theta_4} + (\alpha_1 \theta_2 - \alpha_2)x_{2\theta_4} + 3\alpha_1 \theta_3 x_1^2 x_{1\theta_4} \dots \\
 \quad \dots + \alpha_1(x_1^2 x_2 + \theta_4(2x_{1\theta_4} x_1 x_2 + x_1^2 x_{2\theta_4})) + \alpha_1 \theta_5 (x_{1\theta_4} x_2^2 + 2x_1 x_2 x_{2\theta_4}) \\
 \dot{x}_{2\theta_5} = \alpha_1 \theta_1 x_{1\theta_5} + (\alpha_1 \theta_2 - \alpha_2)x_{2\theta_5} + 3\alpha_1 \theta_3 x_1^2 x_{1\theta_5} + \dots \\
 \quad \dots \alpha_1 \theta_4 (2x_{1\theta_5} x_1 x_2 + x_1^2 x_{2\theta_5}) + \alpha_1 (x_1 x_2^2 + \theta_5 (x_{1\theta_5} x_2^2 + 2x_1 x_2 x_{2\theta_5})).
 \end{array} \right. \quad (17)$$

Perspective: Economic Model Predictive Control (EMPC)

- EMPC optimizes directly in real time the economic performance of the process, rather than tracking to setpoint.
- Closed-loop stability analysis based on the Lyapunov function.
- Bibliography:

- [1] Rawlings, J.B. and Angeli, D. and Bates, C.N. (2012), *Fundamentals of Economic Model Predictive Control*, 51st IEEE Conference on Decision and Control, 3851-3861, Maui, Hawaii, USA.
- [2] Amrit, R. and Rawlings, J.B. and Angeli, D. (2011), *Economic optimization using model predictive control with a terminal cost*, Annual Reviews in Control, 35, 178-186.
- [3] Christofides, P.D. and Liu, J.F. and Heidarinejad, M. (2013), *Algorithms for improved fixed-time performance of Lyapunov-based economic model predictive control of nonlinear systems*, Journal of Process Control, 23, 404-414.