



HAL
open science

A Nitsche finite element method for dynamic contact

Franz Chouly, Patrick Hild, Yves Renard

► **To cite this version:**

Franz Chouly, Patrick Hild, Yves Renard. A Nitsche finite element method for dynamic contact. 11th World Congress on Computational Mechanics (WCCM XI), Jul 2014, Barcelona, Spain. pp.a1255. hal-01061496

HAL Id: hal-01061496

<https://hal.science/hal-01061496>

Submitted on 6 Sep 2014

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

A NITSCHKE FINITE ELEMENT METHOD FOR DYNAMIC CONTACT

Franz Chouly^{1,*}, Patrick Hild² and Yves Renard³

¹ Laboratoire de Mathématiques de Besançon - UMR CNRS 6623, Université de Franche-Comté, 16 route de Gray, 25030 Besançon Cedex, France.

email: franz.chouly@univ-fcomte.fr url: <http://lmb.univ-fcomte.fr/franz-chouly>

² Institut de Mathématiques de Toulouse - UMR CNRS 5219, Université Paul Sabatier, 118 route de Narbonne, 31062 Toulouse Cedex 9, France.

email: patrick.hild@math.univ-toulouse.fr

url: <http://www.math.univ-toulouse.fr/~phild/>

³ Université de Lyon, CNRS, INSA-Lyon, ICJ UMR5208, LaMCoS UMR5259, F-69621, Villeurbanne, France.

email: yves.renard@insa-lyon.fr url: <http://math.univ-lyon1.fr/~renard/>

Key words: *unilateral contact, elastodynamics, finite elements, Nitsche's method, time-marching schemes, stability*

We present a new approximation of elastodynamic frictionless contact problems based both on the finite element method and on an adaptation of Nitsche's method which was initially designed for Dirichlet's condition [4]. The corresponding space semi-discretized weak form reads:

$$\left\{ \begin{array}{l} \text{Find a displacement } \mathbf{u}^h : [0, T] \rightarrow \mathbf{V}^h \text{ such that for } t \in [0, T] : \\ \langle \rho \ddot{\mathbf{u}}^h(t), \mathbf{v}^h \rangle + A_{\Theta\gamma_h}(\mathbf{u}^h(t), \mathbf{v}^h) + \int_{\Gamma_C} \frac{1}{\gamma_h} [P_{\gamma_h}(\mathbf{u}^h(t))]_+ P_{\Theta\gamma_h}(\mathbf{v}^h) d\Gamma = L(t)(\mathbf{v}^h), \\ \forall \mathbf{v}^h \in \mathbf{V}^h, \\ \mathbf{u}^h(0, \cdot) = \mathbf{u}_0^h, \quad \dot{\mathbf{u}}^h(0, \cdot) = \dot{\mathbf{u}}_0^h. \end{array} \right. \quad (1)$$

In the above formulation \mathbf{V}^h is a finite element space built from standard Lagrange finite elements, piecewise linear or quadratic, $A_{\Theta\gamma_h}(\mathbf{u}^h, \mathbf{v}^h) := \int_{\Omega} \boldsymbol{\sigma}(\mathbf{u}^h) : \boldsymbol{\varepsilon}(\mathbf{v}^h) d\Omega - \int_{\Gamma_C} \Theta\gamma_h \sigma_n(\mathbf{u}^h)\sigma_n(\mathbf{v}^h) d\Gamma$ and $P_{\Theta\gamma_h}(\mathbf{v}^h) := v_n^h - \Theta\gamma_h \sigma_n(\mathbf{v}^h)$. The linear form $L(\cdot)$ stands for prescribed body and boundary forces. The domain of the elastic body is denoted by Ω and the contact boundary by Γ_C ; T is the final time of simulation; ρ is the density of the elastic material; the notation v_n^h stands for the normal component on Γ_C of \mathbf{v}^h , and $\sigma_n(\mathbf{v}^h)$ is the normal stress on Γ_C ; \mathbf{u}_0^h (resp. $\dot{\mathbf{u}}_0^h$) is an approximation of the initial displacement \mathbf{u}_0 (resp. the initial velocity $\dot{\mathbf{u}}_0$). The notation $[\cdot]_+$ stands for the positive part of a scalar quantity, and $\langle \cdot, \cdot \rangle$ stands for the $L^2(\Omega)$ inner product. The parameter γ_h

is a positive piecewise constant function on the contact interface Γ_C ($\gamma_h(x) = \gamma_0 h_T(x)$, where γ_0 is a positive constant and $h_T(x)$ is the size of the mesh element T). Note the additional numerical parameter Θ which can be freely chosen in \mathbb{R} . As in Nitsche's method for (static) unilateral contact, values of interest for Θ are $-1, 0, 1$ [1].

A main interesting characteristic is that this approximation produces well-posed space semi-discretizations, for any value of $\gamma_0 > 0$, contrary to standard finite element discretizations. We study associated energy conservation properties and manage to prove that :

$$\frac{d}{dt} E_{\Theta}^h(t) = (\Theta - 1) \int_{\Gamma_C} \frac{1}{\gamma_h} [P_{\gamma_h}(\mathbf{u}^h(t))]_+ \dot{u}_n^h(t) d\Gamma$$

where $E_{\Theta}^h(t) := E^h(t) - \Theta R^h(t)$ is an augmented energy associated to the semi-discrete solution $\mathbf{u}^h(t)$. The mechanical energy is given by $E^h(t) := \frac{1}{2} [\rho \|\dot{\mathbf{u}}^h(t)\|_{0,\Omega}^2 + \frac{1}{2} a(\mathbf{u}^h(t), \mathbf{u}^h(t))]$ and $R^h(t) := \frac{1}{2} [\|\gamma_h^{\frac{1}{2}} \sigma_n(\mathbf{u}^h(t))\|_{0,\Gamma_C}^2 - \|\gamma_h^{-\frac{1}{2}} [P_{\gamma_h}(\mathbf{u}^h(t))]_+\|_{0,\Gamma_C}^2]$ is an extra term, which represents, roughly speaking, the non-fulfillment of the contact conditions at the semi-discrete level. Note in particular that the symmetric variant ($\Theta = 1$) conserves the discrete augmented energy E_{Θ}^h .

Various time-discretizations for (1) are then considered, with the families of θ -schemes and Newmark schemes. We also introduce a new hybrid scheme which is second-order accurate and numerically stable without any restriction on the time-step in the case $\Theta = 1$. This new scheme is inspired from [2, 3], and introduces much less dissipation than unconditionally stable variants of θ -schemes and Newmark schemes. We study theoretically the well-posedness of each discrete scheme as well as its energy conservation properties. We finally achieve the corresponding numerical experiments.

REFERENCES

- [1] F. CHOULY, P. HILD, AND Y. RENARD, *Symmetric and non-symmetric variants of Nitsche's method for contact problems in elasticity: theory and numerical experiments*. <http://hal.archives-ouvertes.fr/hal-00776619>. To appear in Math. Comp.
- [2] O. GONZALEZ, *Exact energy and momentum conserving algorithms for general models in nonlinear elasticity*, Comput. Methods Appl. Mech. Engrg., 190 (2000), pp. 1763–1783.
- [3] P. HAURET AND P. LE TALLEC, *Energy-controlling time integration methods for nonlinear elastodynamics and low-velocity impact*, Comput. Methods Appl. Mech. Engrg., 195 (2006), pp. 4890–4916.
- [4] J. NITSCHKE, *Über ein Variationsprinzip zur Lösung von Dirichlet-Problemen bei Verwendung von Teilräumen, die keinen Randbedingungen unterworfen sind*, Abhandlungen aus dem Mathematischen Seminar der Universität Hamburg, 36 (1971), pp. 9–15.