

# Multichannel sEMG signal analysis using Hilbert-Huang transform to Identify time-frequency features

Alvaro Altamirano-Altamirano, Arturo Vera, Roberto Muñoz, Lorenzo Leija,

Didier Wolf

# ► To cite this version:

Alvaro Altamirano, Arturo Vera, Roberto Muñoz, Lorenzo Leija, Didier Wolf. Multichannel sEMG signal analysis using Hilbert-Huang transform to Identify time-frequency features. 36th Annual International Conference of the IEEE Engineering in Medicine and Biology Society, EMBC 2014, Aug 2014, Chicago, United States. hal-01067484

# HAL Id: hal-01067484 https://hal.science/hal-01067484

Submitted on 11 Jun2023

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

# Multichannel sEMG signal analysis using Hilbert-Huang Transform to identify time-frequency features

A. Altamirano-Altamirano, A. Vera, R. Muñoz, L. Leija-Member, IEEE, and D.Wolf.

*Abstract*— Surface EMG signals have important characteristics that could be useful to anticipate user's movements for orthotic & prosthetic devices. To perform a real-time analysis over these signals is important to simplify the processing method and reduce time-computing; applying Empirical Mode Decomposition (EMD) method we obtain the Intrinsic Mode Functions (IMFs) for a multichannel signal to filter, discard and identify frequencies. Results are considered to simplify the sEMG signal processing for real-time analysis.

### I. INTRODUCTION

sEMG signals provide information about muscular activity in a non-invasive way becoming an effective source for prosthetic control [1]. Appropriate algorithms and methods for EMG signal analysis are available [2] [3] [4].

This work reports the process to analyze multichannel sEMG signals using Hilbert-Huang Transform (HHT) as a technique to decompose signals into a sets of elemental signals, Intrinsic Mode Functions (IMFs), and get their instantaneous frequencies to identify patterns.

## II. METHODOLOGY

Using an acquisition system with four differential channels [5] with a high common mode rejecting ratio in the circuit (94 dB) and applying adaptive filters (band-pass filters from 20 Hz to 450 Hz), we take out noising signals, from the original signal. We saved the resulting signal into a matrices: 1,000 records from 20 non-amputee users. Matrices were divided in 3 segments: repose, transitory and stabilized contraction.

Empirical Mode Decomposition is a technique to decompose a given signal into a set of elemental signals called IMFs; is the base of the HHT.

Given any signal, x(t), the IMFs were found by an iterative procedure called *sifting algorithm*. Spectral estimation is the second step of the HHT, consists in a computing of the instantaneous frequency for each IMF using the Hilbert Transform (HT) and the analytic signal concept.

### **III. EXPERIMENTAL RESULTS**

For each channel we calculated their IMFs to extract the main components of the signal. AM/FM components from

channels were found and presented the following conditions:

- Resolution: 45dB between Signal and Bias energy.
- Residual energy: 45dB between Signal/Residual.
- Each channel presented 8 IMFs to 10 IMFs.
- Reconstruction of the signal with the obtained IMFs is the same as the original one.
- IMFs could be filtrated or treated with hard thresholds to eliminate undesirable frequencies in lower and higher orders.

## IV. CONCLUSION

New ways could be taken to reveal the information contained in a raw EMG; those from filter, de-noising, decomposition, time changes, frequency behavior, etcetera.

HHT method could remain as a valuable detail of the signal, because it can make prevention of energy leak and the energy is centralized in the spectrum.

HHT method could help to find intrinsic features of the EMG signals for real-time analysis; avoiding all traditional calculations, only identifying the main frequencies involved the hand movements.

The goal is to control a hand prosthetic device in real-time to improve its performance, reducing the time respond and improving resolution.

#### ACKNOWLEDGMENT

We appreciate the funding for the development of the presented work to the projects: ECOS Mexico-France Program P: M10-S02. CONACYT Fondo SALUD No. 201590 y 201256 and Joint Cooperation Fund Mexico-Uruguay (SRE-AUCI) 2012-2013.

#### REFERENCES

- J. Rafiee, M. Rafiee, F. Yavari and M. Schoen, "Feature extraction of forearm EMG signals for prosthetics," *Experts Systems with Applications*, vol. 38, no. 4, pp. 4058-4067, 2010.
- [2] T. W. Beck, T. J. Housh, G. O. Johnson, J. P. Weir, J. P. Cramer and J. W. Coburn, "Comparision of Fourier and Wavelet transform procedures for examining mechanomyographic and electromyophic frequency versus isokinetic torque relationships," *Electromyography and Clinical Neurophysiology*, vol. 2, no. 45, pp. 93-103, 2005.
- [3] C. Castellini and P. van der Smagt, "Surface EMG in advanced hand prosthetics," *Biological Cybernetics*, no. 100, pp. 35-47, 2009.
- [4] C. J. De Luca, A. Adam, R. Wotiz, L. D. Gilmore and S. H. Nawab, "Decomposition of Surface EMG Signals," *Journal of Neurophysiology*, no. 96, pp. 1646-1657, 2006.
- [5] P. M. León, Clasificación de Patrones Mioeléctricos para la Operación de un Dispositivo Antropomórfico, Doctoral Thesis. ed., México, D.F.: Centro de Investigación y de Estudios Avanzados del Instituto Politécnico Nacional, 2012.

Altamirano-Altamirano, Vera, Muñoz and Leija are in the *Centro de Investigación y de Estudios Avanzados del Instituto Politécnico Nacional*, México D.F. 07360 México. (phone: +52 5557473800 Ext. 6212; e-mail: aaltamiranoa@cinvestav.mx).

Didier Wolf, is in the Centre de Recherche en Automatique de Nancy, Unicersité de Lorraine CNRS UMR 7039, Vandoeuvre, Nancy 54506 France.