



## Perceptual effects of radiation control with a multi-lousspeaker device

Nicolas Misdariis, Alexandre Lang, Brian F. G. Katz, Patrick Susini

### ► To cite this version:

Nicolas Misdariis, Alexandre Lang, Brian F. G. Katz, Patrick Susini. Perceptual effects of radiation control with a multi-lousspeaker device. Acoustics08, Jun 2008, Paris, France. 2008. hal-01107055

HAL Id: hal-01107055

<https://hal.science/hal-01107055>

Submitted on 25 Jan 2024

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

# Perceptual Effects of Radiation Control with a Multi-Louspeaker Device

Misdariis N. \*, Lang A. \*\*, Katz B. \*\*\*, Susini P. \*


\* IRCAM - UMR CNRS 9912, Equipe Perception et Design Sonores

\*\* Université de Technologie de Compiègne, E.A. Costech - Groupe de Suppléance Perceptive


\*\*\* LIMSI-CNRS, ORSAY

## FRAMEWORK: Analysis, Synthesis and Control of the Acoustical Radiation of a Sound Source


Spherical Harmonics Decomposition Principle




$$\sum_{i=1}^N a_i(\omega) \cdot P_i(\vec{r}_0, \omega) = T(\vec{r}_0, \omega) \quad , \forall \vec{r}_0 \in S$$



H0



H1x, y, z



Source S:  $\{P_i\}_{i=1,\dots,N}$

Target T: Spherical Harmonics (SH)

Application: Encoding / Decoding

## OBJECTIVES:

Perceptual evaluation of the acoustical radiation control

Identification of the principal components influencing the perception of the directivity

## EXPERIMENT:

- Question:** Does the acoustical radiation control allow to reduce the perceived gap between a real sound and a sound coming from an electro-acoustical device ?

### Corpus:

- 3 technological devices:

[1-D]



fig.1a: 1-D device

[2-D]



fig.1b: 2-D device

[3-D]



fig.1c: 3-D device

- 2 groups of stimuli:

### speaking/singing voice

- signal data**: recorded in anechoic room for different phonemes
- spatial data**: measured in anechoic room for different phonemes
- sequence**: succession of phonemes (/a/-/ch/-/i/, ...)
- stimulus**: each unit of the sequence associated to a directivity pattern


### simulated plate

- signal data**: synthesized by physical modeling (modal approach)
- spatial data**: theoretical model of radiation [Laulagnet, JASA 1998]
- sequence**: superposition of vibration modes
- stimulus**: each mode associated to a directivity pattern [SAS : Warusfel & al., ASA 2004]

↳ 2 control factors for the directivity:

- degree of freedom of the diffusion device: D1, D2, D3 (cf. fig.1)
- level of complexity of the controlled directivity:

R1: uncontrolled – R2: cardioid – R3: dipole – R4: monopole – R5: "real"



- ↳ dummy head recording at Ircam auditorium (ESPRO)
- ↳ binaural rendering in a sound isolation booth

- Task:** Semantic differential judgements on 3 scales :

E1: « width » – E2: « distance » – E3: « realism »

## PERSPECTIVES:

- Further investigations involving:
  - . a definition of a relevant set of semantic attributes
  - . a single type of stimuli with the missing link to the reality (a human speaker/singer or a physically hit plate)
- Investigations on the links between perceptual attributes and objectives criteria (Directivity Index, Reverberation Time, etc. ...)

## RESULTS: (for voice stimuli only)

### Analysis #1: MANOVA 1

- **independant variables**: D2, D3, R2, R4, R5
- **dependant variables**: E1, E2, E3




fig.3a: effect of D on E




fig.3b: effect of R on E

↳ significant effect of D and R on E

[Lambda de Wilks test, F=75,8 (resp. 20,1), p<0,0001]




fig.4a: D/E interaction on E1




fig.4b: D/E interaction on E2




fig.4c: D/E interaction on E3

↳ non significant interaction between D and R

### Analysis #2: MANOVA 2

- **independant var.**: D1, D2, D3, C1, C2, C4, C5, C6, C8, C9 (D1+R1) (D2+R2) (D2+R4) (D2+R5) (D3+R2) (D3+R4) (D3+R5)

- **dependant var.**: E1, E2, E3




fig.5a: effect of C on E1




fig.5b: effect of C on E2




fig.5c: effect of C on E3

↳ significant effect of C on E

[Lambda de Wilks test, F=21,06, p<0,0005]

→ on E1: significant difference between {C1, C2, C4, C5} and {C6, C8, C9}

→ on E2: significant difference between {C1, C2} and {C4, C5, C6, C8, C9}

→ on E3: no significant difference

↳ interaction between C and Stimulus

[Lambda de Wilks test, F=2,21, p<0,05]

## CONCLUSIONS:

- Radiation control has a significant effect on auditory perception
- This effect is significant for « width » and « distance » attributes
- Scale « realism » doesn't seem appropriate for evaluating this effect
- The gap between real source and diffusion device tends to be reduced