



HAL
open science

2D modelling of thin skeletal elastic shallow shells

B. Michalak, Cz. Wozniak

► **To cite this version:**

B. Michalak, Cz. Wozniak. 2D modelling of thin skeletal elastic shallow shells. PAMM, 2009, 9, pp.359-360. hal-01117624

HAL Id: hal-01117624

<https://hal.science/hal-01117624>

Submitted on 17 Feb 2015

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

2D modelling of thin skeletal elastic shallow shells

B. Michalak^{*1}, Cz. Woźniak^{**1}

¹ Technical University of Lodz, Al. Politechniki 6, 93-590 Łódź, Poland

The subject of this contribution is a certain thin skeletal elastic shallow shell. The aim of analysis is to derive and apply a 2D-macroscopic model for shallow shells with the non-uniformly oscillating microstructure. The main feature of the proposed mathematical model is that the microstructure length parameter λ is similar compared to thickness δ of the shell ($\lambda \cong \delta$). The formulation of approximate mathematical model of these shells is based on a tolerance averaging approximation [5]. The general results of the contribution will be illustrated by the analysis of a specific problem.

1 Introduction

The considered skeletal shell is made of two families of thin beams. The regions situated between the beams are filled a homogeneous matrix material (Fig. 1). From a formal point of view, the structure under consideration can be described in the framework of the well-known theories for thin elastic shallow shells. However, due to the inhomogeneous microstructure of the shell, this direct description of the structure leads to shell equations with discontinuous and highly oscillating coefficients. The aim of the contribution is to formulate non-asymptotic averaged model describing composite shallow shell under consideration. The formulation of the macroscopic mathematical model for the analysis of dynamic behaviour of these shells will be based on the tolerance averaging technique. The applications of this technique for the modelling of various dynamic problems of elastic periodic composites are given in a series papers [1], [2], [3], [4].

2 Direct description

The starting point of this contribution is the direct description of the structure in the framework of the well known theory of thin shallow shells. The displacement field of the arbitrary point of the shallow shell we write in form

$$w_3(x, z) = w_3(x) \quad w_\alpha(x, z) = w_\alpha^0(x) - \partial_\alpha w_3(x) z \quad (1)$$

Denoting by $\mathbf{p}(\mathbf{x}, t)$ the external forces, by ρ the mass density and setting $\partial_x = \partial / \partial x^k$, in the framework of the linear approximated theory for thin shallow shells, we obtain the following system of equations




Fig. 1 Fragment of skeletal shell.

(i) strain-displacement relations

$$\varepsilon_{\alpha\beta}(x, z) = \varepsilon_{\alpha\beta}^0(x) + \kappa_{\alpha\beta}(x) z, \quad \varepsilon_{\alpha\beta}^0 = \partial_{(\beta} w_{\alpha)}^0 - b_{\alpha\beta} w_3, \quad \kappa_{\alpha\beta} = -\partial_{\alpha\beta} w_3 \quad (2)$$

(ii) strain energy averaged over the shell thickness

$$E(x) = \frac{1}{2} B^{\alpha\beta\gamma\delta} \partial_{\alpha\beta} w_3 \partial_{\gamma\delta} w_3 + \frac{1}{2} D^{\alpha\beta\gamma\delta} (\partial_{(\beta} w_{\alpha)}^0 - b_{\alpha\beta} w_3) (\partial_{(\delta} w_{\gamma)}^0 - b_{\gamma\delta} w_3) \quad (3)$$

^{*} Corresponding author: e-mail bmichala@p.lodz.pl, Phone: +48 42 6313564, Fax: +48 42 6313564

^{**} e-mail czeslaw.wozniak@p.lodz.pl, Phone: +48 42 6313564, Fax: +48 42 6313564

2 Averaged description

Introduce the orthogonal coordinate system $Ox^1x^2x^3$. Let the midsurface of the undeformed shell under consideration be given by $x^3 = z(x^1, x^2)$, $(x^1, x^2) \in \Omega$, where plane $\Omega = (-L_1/2, L_1/2) \times (-L_2/2, L_2/2)$ is the shell projection on $x_3 = 0$. In the case of a shallow shells we will be to consider the non-uniform cell distribution in Ω . Every $\Delta(x)$, where x belong to Ω , will be referred to the cell in Ω with center at x

$$\square(x) = \left(x_1 - \frac{\lambda_1}{2}, x_1 + \frac{\lambda_1}{2} \right) \times \left(x_2 - \frac{\lambda_2}{2}, x_2 + \frac{\lambda_2}{2} \right), \quad x = (x_1, x_2) \in \Omega: \quad \square \equiv \{ \square(x), x \in \Omega \}. \quad (4)$$

Denoting by $\lambda_\alpha(x_\alpha)$ the diameter of $\Delta(x)$ and define $\lambda = \sup(\lambda_\alpha)$ as a microstructure length parameter, we assume that $\lambda_\alpha(x_\alpha)$ are small compared to the minimum characteristic length dimension of region Ω ($\lambda_\alpha \ll L_\alpha$). At the same time, the thickness h of the shell under consideration is supposed to be constant and of an order of the microstructure length parameter λ ($\lambda \approx h \ll \min\{L_1, L_2\}$).

The modeling technique will be based on the tolerance averaging approximation and on the restriction of the displacement field under consideration given by

$$w_3(x, z, t) = V_3(x, t), \quad w_\alpha(x, z, t) = V_\alpha(x, t) + \varphi^A(x) V_\alpha^A(x, t) + (-\partial_\alpha V_3(x, t) + \varphi^A(x) u_\alpha^A(x, t))z \quad (5)$$

The governing equations derived from stationary action principle of the averaged lagragian $\langle \mathcal{L} \rangle = \langle K \rangle - \langle E \rangle + \langle F \rangle$ have the form

$$\begin{aligned} \partial_{\alpha\beta} \left((\tilde{B}^{\alpha\beta\gamma\delta} - \tilde{B}^{\tau\alpha\beta\gamma} \frac{\tilde{B}^{\mu\alpha\gamma\delta}}{\tilde{B}^{\mu\alpha\tau\beta}}) \partial_{\gamma\delta} V_3 \right) - \tilde{D}^{\alpha\beta} \partial_\beta V_\alpha - \tilde{D}^{\alpha A} V_\alpha^A + \tilde{D}^{33} V_3 + \langle \rho h \rangle \ddot{V}_3 &= \langle f^3 \rangle \\ \partial_\delta (\tilde{D}^{\alpha\beta\gamma\delta} \partial_\beta V_\alpha + \tilde{D}^{\alpha A \gamma\delta} V_\alpha^A - \tilde{D}^{\gamma\delta} V_3) - \langle \rho h \rangle \ddot{V}_\gamma &= - \langle f^\gamma \rangle \\ \tilde{D}^{\alpha A \gamma\delta} \partial_\delta V_\gamma + \tilde{D}^{\alpha A \gamma B} V_\gamma^B - \tilde{D}^{\alpha A} V_3 + \langle \rho h \rangle \varphi^A \varphi^B > \ddot{V}_\alpha^B &= \langle f^\alpha \varphi^A \rangle \end{aligned} \quad (1)$$

The above equations have the smooth and functional coefficients in contrast to equations in direct description with the discontinuous and highly oscillating coefficients.

3 Conclusion

The results obtained in this contribution justify to formulate the following conclusions:

1. The tolerance averaging approximation can be successfully applied to formulate averaging model of thin skeletal shallow shells.
2. The obtained model leads to the governing equations with non-constant but the smooth coefficients in contrast to equations in direct description with the discontinuous and highly oscillating coefficients.
3. Since the proposed model equations have smooth and functional coefficients then in most cases solutions to specific problem for skeletal shells under consideration have to be obtained using numerical methods.

Acknowledgements This contribution is supported by the Ministry of Science and Higher Education under grant No. N N506 398535.

References

- [1] E. Baron, *Arch. Appl. Mech.* 73: 505-516 (2003).
- [2] J. Jędrzyński, *Arch. Appl. Mech.* 69: 345-356 (1999).
- [3] B. Michałak, Vibrations, *Arch. Appl. Mech.* 70: 508-518 (2000).
- [4] B. Tomczyk, *J. Theor. Appl. Mech.* 41: 755-774 (2003).
- [5] Cz. Woźniak, B. Michałak, J. Jędrzyński, (eds), *Thermomechanics of microheterogeneous solids and structures*. Wydawnictwo Politechniki Łódzkiej. Łódź (2008).