

A computation chain in fluid-structure interaction for marine applications

Camille Yvin, Alban Leroyer, Michel Visonneau

▶ To cite this version:

Camille Yvin, Alban Leroyer, Michel Visonneau. A computation chain in fluid-structure interaction for marine applications. 11th World Congress on Computational Mechanics (WCCM XI), 5th European Conference on Computational Mechanics (ECCM V), 6th European Conference on Computational Fluid Dynamics (ECFD VI), May 2014, Barcelone, Spain. hal-01202473

HAL Id: hal-01202473

https://hal.science/hal-01202473

Submitted on 22 Feb 2021

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



A COMPUTATION CHAIN IN FLUID-STRUCTURE INTERACTION FOR MARINE APPLICATIONS

Camille Yvin ¹, Alban Leroyer ² and Michel Visonneau³

DCNS Research, 1 rue de la Noë 44321 Nantes Cedex 3 France
1,2,3 LHEEA, CNRS UMR 6598, École Centrale Nantes,
1 rue de la Noë 44321 Nantes Cedex 3 France

 1 e-mail : camille.yvin@sirehna.com, camille.yvin@eleves.ec-nantes.fr 2 e-mail : alban.leroyer@ec-nantes.fr 3 e-mail : michel.visonneau@ec-nantes.fr

Key words: Fluid Structure Interaction, Co-simulation, Added-mass, Applications.

Fluid Structure Interaction (FSI) problems are commonly encountered in naval architecture. They can be solved with a monolithic or a partitioned approach [1]. The partitioned approach (or block-iterative method) consists in solving the fluid and the structure problems in a segregated way. Even if this can be done through a single solver, it is most commonly used in a co-simulation context and consequently it is especially well fitted to the resolution of complex FSI problems. Indeed, the co-simulation allows to use complex models for both the fluid and the structure without additional simplifications because each solvers can be numerically adapted to its problem.

In this work, two different general solvers are used. ISIS-CFD, which is a CFD solver available as a part of the FINETM/Marine computing suite and dedicated to marine applications [2], is used to solve the fluid problem. To solve the structure problem, the solver MBDyn is used. It is an open-source solver intended for the simultaneous solution of multi-disciplinary problems including non-linear dynamics and aero-servo-elasticity among others [3]. The combination of this two solvers makes possible the study of a broad spectrum of applications in the marine field.

When a partitioned approach is used, convergence can be slow [4] and the coupling algorithm stability is not guaranteed due to the well known added mass effect [5] which is often met in marine applications. In order to reduce the computational time, the coupling iteration occurs during the non-linear iterations of the fluid solver because it is the most costly solver in our applications. To take into account the destabilising added-mass effect, a modification of the artificial added mass method is used. The original method consists in adding artificial added mass terms in the structure equations which do not affect the converged result. However this is not a suitable solution in a co-simulation context due

to the modification of the structure solver [6]. A relaxation technique of the structural kinematics is preferred because it can be directly handled by the coupling algorithm. Of course, the relaxation operator is related to the artificial added mass matrix. Stabilisation of the coupling algorithm is effective if the artificial added mass matrix is chosen high enough, but this work shows that also good convergence properties are obtained if the artificial added mass matrix is close to the physical one [7]. To compute an approximated or exact added mass matrix, an on-line resolution of an original pressure-like equation integrated in the fluid solver is performed [8].

The computation chain consisting of ISIS-CFD and MBDyn has been validated numerically for rigid bodies with six degrees of freedom and strong added mass effect. When it is possible, results were compared to experimental tests. Simulations of a ship in regular head waves are in good agreement with the experimental data. Harmonic analysis of pitch and heave motions are especially close to the experiments up to the second harmonic. Future works will be dedicated to simulate original physical configurations with complex mechanical systems and multi-body cases in the marine field.

REFERENCES

- [1] G. Hou, J. Wang and A. Layton. Numerical methods for fluid-structure interaction A review. *Communications in Computational Physics*, Vol. **12**, 337–377, 2012.
- [2] P. Queutey, M. Visonneau. An interface capturing method for free-surface hydrodynamic flows. *Computers & Fluids*, Vol. **36(9)**, 1481-1510, 2007.
- [3] P. Masarati. Comprehensive Multibody AeroServoElastic Analysis of Integrated Rotorcraft Active Controls. Dipartimento Di Ingegneria Aerospaziale, Politecnico Di Milano, PhD. thesis, 1999.
- [4] J. Degroote, K.-J. Bathe and J. Vierendeels. Performance of a new partitioned procedure versus a monolithic procedure in fluid-structure interaction. *Computers & Structures*, Vol. 87, 793–801, 2009.
- [5] W.A. Wall, C. Förster, M. Neumann and E. Ramm. Advances in fluid-structure interaction. 17th International Conference on the Application of Computer Science and Mathematics in Architecture and Civil Engineering, Weimar, Germany, 2006.
- [6] M. Durand. Interaction fluide-structure souple et légère, applications aux voiliers. École Centrale de Nantes, PhD. thesis, 2012.
- [7] C. Yvin and A. Leroyer and M. Visonneau. Co-simulation in fluid-structure interaction with rigid bodies. 16th Numerical Towing Tank Symposium, Duisburg, Germany, 2013.
- [8] H. Söding. How to integrate free motions of solids in fluids. 4th Numerical Towing Tank Symposium, Hamburg, Germany, 2001.