Ecole Nationale d'Ingénieurs de Tarbes



Laboratoire Génie de Production A multi-layer approach of interactive path planning for assisted manipulation in Virtual Reality

Simon Cailhol, Philippe Fillatreau, Jean-Yves Fourquet and Yingshen Zhao École Nationale d'Ingénieurs de Tarbes-Laboratoire Génie de Production

	Proposition	
	Environment modeling	Semantic map
	Path planning	
Context	_ Interaction means	<u>c</u> <u>c</u>
Industrial motivation		aracteri:
		Topological map

While designing products with the Product Lifecycle management (PLM) approach, the tasks involving manipulations by a human operator can be simulated in Virtual Reality (VR) applications. One of the main issues for most of such tasks is to find path for systems components to move.

**On-line simulation** 

operator.

Manipulation in VR assembly applications.

Environment hard to handle for human

# Path finding tools

# **Off-line simulation**

Path planners from robotic research field. Computation time for highly integrated systems.

# **Assisted VR assembly**

Use an automatically planned trajectory to guide human operator immersed in VR application.



## Contribution

Multi-layer environment model	Planning process	Interaction and control sharing
very complex very complex $B_{1,6} \xrightarrow{P_6} B_{4,6} \xrightarrow{P_8} B_{2,8}$	$B_{16} \xrightarrow{P_6} B_{46} \xrightarrow{P_8} B_{28}$	



- Semantics characterizes places and obstacles.
- **Topology** represents places, borders and their connectivity.
- Geometry describes obstacles and free space.



A two phases path planning process involving both semantic information :

- 1. Coarse planning defines a path in the topology and split it in steps. Semantics controls the topology exploration.
- 2. Fine planning defines the geometrical path crossing each step. Semantics chose the planning technique.



intent

prediction

- Operator's actions are used to define **Semantics** utilization for cost functions and planning techniques
- Operator intent is predicted at **topological** level and used for path re-planning
- Authority is shared between automatic planner and human operator for geometrical manipulation

Results

### Path planning 3D environment



#### Guidance following planned trajectory

#### **Operator control planned trajectory**





