



**HAL**  
open science

## **Eigenerosion: extension and applications to heterogeneous media**

Lionel Bichet, Frédéric Dubois, Yann Monerie, Céline Péliissou, Frédéric Perales

► **To cite this version:**

Lionel Bichet, Frédéric Dubois, Yann Monerie, Céline Péliissou, Frédéric Perales. Eigenerosion: extension and applications to heterogeneous media. CFRAC 2015, Jun 2015, Cachan, France. hal-01262580

**HAL Id: hal-01262580**

**<https://hal.science/hal-01262580>**

Submitted on 26 Jan 2016

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

# *Eigenerosion: extension and applications to heterogeneous media*

**L. Bichet<sup>1,3</sup>, F. Dubois<sup>1,3</sup>, Y. Monerie<sup>1,3</sup>, C. Pélissou<sup>2,3</sup>, F. Perales<sup>2,3</sup>**

<sup>1</sup> Laboratoire de Mécanique et Génie Civil, Université de Montpellier, CNRS,  
CC 048 place Eugène Bataillon, 34095 Montpellier cedex 05, France  
{lionel.bichet, frederic.dubois, yann.monerie}@univ-montp2.fr

<sup>2</sup> Institut de Radioprotection et de Sûreté Nucléaire, CE Cadarache  
Bât. 702, BP3-13115 Saint-Paul-lez-Durance, France  
{celine.pelissou, frederic.perales}@irsn.fr

<sup>3</sup> Laboratoire de Micromécanique et d'Intégrité des Structures, MIST,  
IRSN-CNRS-Université de Montpellier

In 1921, Griffith introduced the concept of energy release rate in brittle fracture: below a certain amount of energy, no crack extension can occur. A variational formulation of this idea has been proposed by Francfort and Marigo [1] in the late 90's whose a regularization (1) has been recently developed by Schmidt *et al.* [4].

$$F_\epsilon(u, \epsilon^*, t) = \underbrace{\int_{\Omega} W(\epsilon(u) - \epsilon^*) dV}_{\text{strain}} - \underbrace{\int_{\Gamma_f} \bar{T} \cdot u dS}_{\text{load}} + G_c \underbrace{\frac{|\mathcal{C}_\epsilon|}{2\epsilon}}_{\text{crack}} \quad (1)$$

where  $\bar{T}$  is the applied traction on the part  $\Gamma_f$  of the boundary of the domain  $\Omega$ ,  $W$  is the elastic strain energy density of the body,  $\epsilon(u)$  is the strain operator of linear elasticity,  $\epsilon^*$  is an eigendeformation field [2],  $G_c$  is the critical energy-release rate and  $\epsilon$  is a small length which defines  $\mathcal{C}_\epsilon$  an  $\epsilon$ -neighbourhood to the crack,  $|\mathcal{D}|$  is the measure of any domain  $\mathcal{D}$ . When  $\epsilon$  tends to zero the standard Griffith's theory is recover.

The minimization of the functional (1) within the finite element framework was firstly realized by Pandolfi and Ortiz [3] in the context of homogeneous elastic media. These authors proposed to model the crack propagation associated to the eigenerosion using a 'killing element' method (deletion of elements verifying the crack propagation criterion). Two physical quantities areinvolved in this process.

- A **variation of energy**.

$$-\Delta E_K = \underbrace{\frac{1}{2} u^T \Delta S_K u}_{\text{element contribution}} + \underbrace{\frac{1}{2} u^T \Delta S_K S^{-1} \Delta S_K u}_{\text{structure contribution}} \quad (2)$$

where  $\Delta S_K$  is the stiffness matrix of the  $K$ -th element,  $S$  is the stiffness matrix of the meshed body where the element  $K$  is removed and  $u$  the displacement field before the erosion or equivalently before the assumed crack propagation. For sake of simplicity, [3] have taken into account only the element contribution in the equation (2).

- A crack length increment. For a crack occupying a domain  $C$ , the size of its extension is evaluated by a neighbourhood process [3]:

$$\delta A(K) = \frac{|(C \cup K)_\epsilon \setminus C_\epsilon|}{2\epsilon}, \quad (3)$$

where  $(C \cup K)_\epsilon$  is the current neighbourhood of the crack,  $C_\epsilon$  is the previous configuration of the crack-neighbourhood and  $K$  is the current killed element. When  $\epsilon$  tends to 0,  $\delta A(K)$  approaches the physical increment of the crack.

In the present work, 1/ we investigate a criterion with a both local-global energy, 2/ we propose an extension of the eigerosion method to fracture dynamics, 3/ we point out and clarify some technical problems related to the crack length increment (new crack-neighbourhood process, crack-boundary interactions, crack-crack interactions) and 4/ we extend the eigerosion method to heterogeneous media. Each development is validated on benchmark.

The extension to heterogeneous media is based on a local predictor-corrector method. The prediction phase consists in determining the elements that are candidates to the erosion process, i.e. that maximize the ratio  $-\Delta E_K / [\delta A(K) G_c(K)]$  over the structure, where  $G_c(K)$  denotes the critical energy release rate of the  $K$ -th element depending on the underlying phase. This extension to heterogeneous media is applied to an engineering problem: the study of the crack tortuosity in concrete media. The effect of two distinct parameters is studied: the aggregates volume fraction and the size polydispersity of the aggregates.

Moreover, the extension of the method to the 3D case is actually studied.

## References

- [1] G.A. Francfort and J.-J. Marigo. Revisiting brittle fracture as an energy minimisation problem. Journal of the Mechanics and Physics of Solids, 1319-1342, 1998.
- [2] T. Mura. Mechanics of Defects in Solids, Martinus Nijhorff, 1987.
- [3] A. Pandolfi and M. Ortiz. An eigerosion approach to brittle fracture. International Journal For Numerical Methods In Engineering, 694-714, 2012.
- [4] B. Schmidt and F. Fraternali and M. Ortiz. Eigenfracture: an eigendeformation approach to variational fracture. Multiscale Modeling and Simulation, 1237-1266, 2009.