
Unsupervised clustering of hyperspectral images of brain tissues by hierarchical non-negative matrix factorization



Bangalore Ravi Kiran, Bogdan Stanciulescu, and Jesus Angulo CAOR, CMM, MINES ParisTech, PSL-Research University

Problem overview and workflow



Hierarchical Non-Negative Matrix Factorization

Cotton

Plastic

Tissue 1

Segmentation and subsequent spectral unmixing

Invivo-Image classification (Cluster prediction using random forest classifier)

Pathology veryifying tumor presence in ring markers locations

Inputs: VNIR-HSI images of In-vivo brain tissue surface during surgery and Ex-vivo extracted tumor are provided.

Goals: Identify the spectrum of the different brain tissues synthetic surgical materials and eventually spectral delineation of tumors.

Issues: Noisy & uncalibrated image, severe illumination variation, variability across patients & tumors. No ground truth labels for tumors. Specular reflections prominent in many images.

Methodology: Unsupervised clustering or segmentation and subsequent training of random forest classifier to predict subspace clusters.


Hierarchical Rank-2 NMF clustering (H2NMF)

- 1. Select cluster with least approximation error : $\arg \min E_k$ in (1)
- 2. Split the cluster by projecting the data points onto the first two eigen vectors, by SVD.

 3. Iterate (1,2) till r-clusters are reached.
- This yields pure-pixels in the HSI cube approximating the first principle component.

$$E_k = \sigma_1^2(X(:, K_i^1)) + \sigma_1^2(X(:, K_i^2)) - \sigma_1^2(X(:, K_i))$$
(1)

Use (H2NMF) to cluster different materials and tissues based on homogeneity of spectral signature.




By viewing the endmembers (spectra) at different levels, we can infer visually that blood is a dominant material in the scene (blue peak around 400nm).

Number of Clusters


Mean removed spectral angle (MSRA) between two spectra is defined as:

$$\phi(\mathbf{x}, \mathbf{y}) = \frac{1}{\pi} \arccos\left(\frac{(x - \bar{x})^T (y - \bar{y})}{\|x - \bar{x}\|^2 \|y - \bar{y}\|^2}\right) \in [0, 1]$$
 (2)



Left: Variation of the maximum MRSA eq. (2) w.r.t number of clusters to evaluate the homogeneity of clusters w.r.t endmember signature. Right: Variation approximation error in (1) with increasing leaves.

Learning on levels of (H2NMF) hierarchy



H2NMF clustering on the training set X_{train} acts as training set for constructing the random forest classifier.

Classification on Test images (Invivo and Exvivo)

