

Coupling Parareal with Non-Overlapping Domain Decomposition Method

Rim Guetat

▶ To cite this version:

Rim Guetat. Coupling Parareal with Non-Overlapping Domain Decomposition Method. 2016. hal-01312528v1

HAL Id: hal-01312528 https://hal.science/hal-01312528v1

Preprint submitted on 6 May 2016 (v1), last revised 6 Dec 2016 (v2)

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés. Rubrique

Coupling Parareal with Non-Overlapping Domain Decomposition Method

Rim Guetat

Faculty of Sciences of Tunis, University of Tunis El Manar 2060 Tunis, Tunisia rymguetat@yahoo.fr

ABSTRACT. In this paper, we present a new parallel algorithm for time dependent problems based on coupling parareal with non-overlapping domain decomposition method in order to increase parallelism in time and in space. For this we focus on the iterative methods of parallization in space to solve the interface problem like Neumann-Neumann method. In the new algorithm, the coarse temporel propagator is defined on the global domain and the Neumann-Neumann method is chosen as a fine propagator with a few iterations. We present the rigorous convergence analysis of the new coupled algorithm on bounded time interval. Numerical experiments illustrate the performance of this new algorithm and confirm our analysis.

RÉSUMÉ. Dans ce papier, nous présentons un nouvel algorithme parallèle pour les problèmes dépendant du temps basé sur le couplage du pararéel avec les méthodes de décomposition de domaine sans recouvrement afin d'augmenter le parallélisme dans le temps et l'espace. Nous nous concentrons sur les méthodes itératives de parallélisation en espace pour résoudre le problème d'interface par la méthode de Neumann-Neumann. Dans ce nouvel algorithme, le propagateur grossier est définie sur le domaine global et la méthode de Neumann-Neumann est choisi pour le propagateur fin avec quelques itérations. Nous présentons l'analyse rigoureuse de convergence du nouvel algorithme couplé sur un intervalle de temps borné. Des expèriences numériques illustrent les performances de ce nouvel algorithme et confirment notre analyse.

KEYWORDS : Parallel Algorithm, Parareal algorithm, Non-overlapping domain decomposition method, Schur complement, Neumann-Neumann method.

MOTS-CLÉS : Algorithme parallèle, Algorithme du pararéel, Méthodes de décomposition de domaine sans recouvrement, Complément de Schur, Méthode de Neumann-Neumann.

1. Introduction

In this paper we will focus on domain decomposition methods (DDM)[13, 11] applied to Finite Element Method (FEM). Though non-overlapping domain decomposition methods are powerful techniques for solving elliptic partial differential equations (PDEs). These methods consist of splitting the global domain into serval non overlapping subdomains and using a parallel solver to solve the local problems. This procedure leads to iterative methods to find interface unknowns connecting domains together, namely the interface displacements in the Schur complement methods.

The performance of the method depends on the choice of efficient preconditioner for the interface operators. In this context three methods arose in 91's such as the Neumann-Neumann method, Finite Element Tearing and Interconnect (FETI) [5] and Balanced Domain Decomposition (BDD)[10]. In the present paper, the method of non-overlapping domain decomposition used is Neumann-Neumann method [7]. This method consists of solving the subdomain problems using Dirichlet interface conditions, followed by a correction step involving Neumann interface conditions.

Non-overlapping domain decomposition method can be extended to time dependent problems. The classical approach consists in discretizing in time with an implicit scheme and applying a domain decomposition method for the steady problems obtained at each time step [4]. The numerical temporal evolution schemes are sequential in nature and can be costly on a parallel computer. To reduce the computational cost over the whole time interval, recent interest arose in order to exploit modern engineering and modern hardware architectures, increased parallelism in numericals algorithms are of great importance. This development have lead to an increased focus on temporal parallelization in research, for this purpose we adopt the parareal algorithm introduced for the first time by Lions and al [8] which need to be solved in real-time. The parareal algorithm can be interpreted as different approaches, such as multigrid-in-time algorithm [6] or predictor-corrector method [3]. To be valuable to solve stiff models in real-time simulations, parareal use different models for the coarse and the fine solvers. The parareal algorithm has been applied to many fields by many authors [2, 9].

For problems with a larger size, or larger complexity, the parareal method suffers from the size of the spatial subproblem to solve, in this case we propose to combine the parareal algorithm with the domain decomposition method in order to reduce the complexity and performs the parallelism both in space and in time subdomains. There are at least three variants of the parareal algorithm which all contain some spatial parallelism: the first variant, which is the subject of this contribution, uses for the fine propagator a domain decomposition method; the second variant uses for the coarse propagator a domain decomposition method, and finally the third variant employs for both the coarse and fine propagators a domain decomposition method.

We develop in this paper a new parallel algorithm for advection-dominated diffusion problem by coupling the parareal algorithm and the non-overlapping domain decomposition like Neumann-Neumann method.

In this new algorithm, the Neumann-Neumann method is chosen as the fine propagator on each sub-interval with only a few iterations, where the interface problem is solved by Krylov type such as GMRES. In particular there is no coarse mesh needed in the case of many subdomains, if the time step is not too big. The remainder of the paper proceeds as follows. The model problem is presented in Section 2. In Section 3, we present the Neumann-Neumann method. Section 4 describes the parareal in time algorithm. We propose our new coupled-algorithm in Section 5. Some experimental results are reported in Section 6. Our conclusion is given finally in Section 7.

2. Model problem

Let Ω be a bounded domain in \mathbb{R}^d , d = 1, 2, 3 with a Lipschitz boundary $\partial \Omega$. Our model problem is the advection-dominated diffusion problem defined by

$$\begin{cases} \frac{\partial u}{\partial t} - \nu \Delta u + \alpha . \nabla u = f(t) \quad in \quad \Omega \times]0, T],\\ u(\mathbf{x}, t = 0) = u_0 \quad in \quad \Omega,\\ u(\mathbf{x}, t) = 0 \quad on \quad \partial\Omega \times [0, T], \end{cases}$$
(1)

where $\alpha = (\alpha_1, \alpha_2)$ is the advection velocity and f is the second term. If $u_0 \in H_0^1(\Omega)$, the unique weak solution u is in $L^2(0, T; H^2(\Omega)) \cap H^1(0, T; L^2(\Omega))$.

Once equation (1) discretized in time by an implicit scheme of first order, with a uniform time step equal to Δt , the model problem reduces at every time step $T_{n+1} = (n+1)\Delta t$ to the solution of

$$\bar{\mathcal{L}}(u^{n+1}) := (\frac{1}{\Delta t} - \nu\Delta + \alpha\nabla)u^{n+1} = f^{n+1} + \frac{u^n}{\Delta t} = \underline{f}^{n+1}.$$
 (2)

After discretization of the problem by finite element we have

$$A\mathbf{u}^{n+1} := (I + \Delta tK)\mathbf{u}^{n+1} = b^{n+1}$$
(3)

where $\mathbf{u}^n(\mathbf{x})$ is the vector of nodal values of the approximation of the solution $u(\mathbf{x}, T_n)$, I is a identity matrix, K is a symmetric positive definite matrix arising from the discretization of the advection-dominated diffusion problem and b^{n+1} the vector of nodal values of the right hand side depending on $\mathbf{u}^n(\mathbf{x})$. At a fixed time level T_{n+1} , we have to solve the problem (2) depending on the time step parameter by applying domain decomposition methods.

3. The Neumann-Neumann preconditioner

We decompose the computational domain Ω into finitely many non-overlapping subdomains $\Omega_i, i = 1 \dots N_s$ and denote the subdomain boundaries by $\partial \Omega_i$. The local interfaces are defined by $\Gamma_{ij} = (\partial \Omega_i \cap \Omega_j) \setminus \partial \Omega$. Furthermore, at a fixed time level T_{n+1} , we define the global interface of this decomposition $\Gamma = \bigcup_{i \neq j} \Gamma_{ij}$. Let $A^{(i)}$ be the local stiff-

ness matrix corresponding to subdomain Ω_i , \mathbf{u}_i^{n+1} be the vector of degrees of freedom corresponding to all elements in Ω_i , and let $R^{(i)}$ denote the restriction matrix with entries 0 or 1 mapping the degrees of freedom \mathbf{u}_i into global degrees of freedom. We introduce the interface degrees of freedom, $\gamma^{n+1} := R^{(i)} \mathbf{u}_i^{n+1}|_{\Gamma}$ and $b^{(i,n+1)}$ the vector of nodal values of the right hand side in Ω_i . The stiffness matrix A is obtained by the standard subassembly process

$$A = \sum_{i=1}^{N_s} R^{(i)T} A^{(i)} R^{(i)}, \tag{4}$$

the system $A\mathbf{u}^{n+1} = b^{n+1}$ can now be rewritten

$$\begin{bmatrix} A_{II}^{(1)} & \dots & 0 & A_{I\Gamma}^{(1)}R^{(1)} \\ \vdots & \ddots & \vdots & \vdots \\ 0 & \dots & A_{II}^{(N_s)} & A_{I\Gamma}^{(N_s)}R^{(N_s)} \\ R^{(1)^T}A_{I\Gamma}^{(1)^T} & \dots & R^{(N_s)^T}A_{I\Gamma}^{(N_s)^T} & \sum_{i=1}^{N_s} R^{(i)^T}A_{\Gamma\Gamma}^{(i)}R^{(i)} \end{bmatrix} \begin{bmatrix} \mathbf{u}_{1,I}^{n+1} \\ \vdots \\ \mathbf{u}_{N_s,I}^{n+1} \\ \gamma^{\mathbf{n}+1} \end{bmatrix} = \begin{bmatrix} b_I^{(1,n+1)} \\ \vdots \\ b_I^{(N_s,n+1)} \\ \sum_{i=1}^{N_s} R^{(i)^T}b_{\Gamma}^{(i,n+1)} \end{bmatrix}$$
(5)

Eliminating the unknowns corresponding to the subdomain interior i.e. $\mathbf{u}_{i,I}^{n+1}$ and in (3) we arrive at

$$\left(\sum_{i=1}^{N_s} R^{(i)T} (A_{\Gamma\Gamma}^{(i)} - A_{I\Gamma}^{(i)T} A_{II}^{(i)-1} A_{I\Gamma}^{(i)}) R^{(i)}\right) \gamma_{\mathbf{n+1}} = \sum_{i=1}^{n_s} R^{(i)T} \left(b_{\Gamma,n+1}^{(i)T} - A_{I\Gamma}^{(i)T} A_{II}^{(i)-1} b_{I}^{(i,n+1)}\right)$$
(6)

We introduce the following notation

$$S_{i} = \left(A_{\Gamma\Gamma}^{(i)} - A_{I\Gamma}^{(i)}{}^{T}A_{II}^{(i)}{}^{-1}A_{I\Gamma}^{(i)}\right), \quad S = \sum_{i=1}^{M} R^{(i)}{}^{T}S_{i}R^{(i)},$$

$$g_{i}^{n+1} = \left(b_{\Gamma}^{(i,n+1)} - A_{I\Gamma}^{(i)}{}^{T}A_{II}^{(i)}{}^{-1}b_{I}^{(i,n+1)}\right), \quad g_{n+1} = \sum_{i=1}^{M} R^{(i)}{}^{T}g_{(i)}^{n+1},$$
(7)

where S_i is the local primal Schur complement. We obtain the following Schur complement problem on interface

$$S\gamma^{\mathbf{n+1}} = g^{n+1}.\tag{8}$$

The parallel preconditioner "Neuman-Neumann" P_{NN} is then defined as follows

$$P_{NN}^{-1} = \sum_{i=1}^{N_s} R^{(i)T} D^{(i)} S_i^{-1} D^{(i)} R^{(i)}, \qquad (9)$$

with D_i is a scaling diagonal subdomain matrix and form a decomposition of unity on the interface.

$$\sum_{i=1}^{N_s} R^{(i)T} D^{(i)} R^{(i)} = I_{\Gamma}.$$
(10)

The Neumann-Neumann algorithms are preconditioned GMRES methods for solving the preconditioned linear system

$$P_{NN}^{-1} S \gamma_{n+1} = P_{NN}^{-1} g.$$

3.1. Convergence analysis

3.1.1. Schur complement algorithm in the continuous case

To define the Schur complement in the continuous case for the model problem (1) at each time step T_{n+1} on the space domain Ω , where $\Omega = [0,1] \times \mathbb{R}$. We assume that the spatial domain is partitioned into two non-overlapping subdomains $\Omega_1 = [0,c] \times \mathbb{R}$ and

 $\Omega_2 = [c, 1] \times \mathbb{R}$ where $c \in]0, 1[$. We denote by $\Gamma = \{(x, y) \in [0, 1] \times \mathbb{R} \mid x = c\}$, $\mathbf{n_i}$ the unit outward normal for Ω on the interface Γ and \mathbf{n} the unit outward normal vector on Γ directed from Ω_1 to Ω_2 . We split the original problem (2) into two locals problems as follows

$$\begin{cases} \bar{\mathcal{L}}u_i^{n+1}(x,y) &= \underline{f}_i^{n+1}(x,y) \text{ in } \Omega_i, \ i = 1, 2, \\ u_1^{n+1}(x,y) &= u_2^{n+1}(x,y) \quad \text{ on } \Gamma, \\ \frac{\partial u_1^{n+1}}{\partial \mathbf{n}}(x,y) &= \frac{\partial u_2^{n+1}}{\partial \mathbf{n}}(x,y) \quad \text{ on } \Gamma, \\ u_i^{n+1}(x,y) &= 0 \quad \text{ on } \partial \Omega_i \cap \partial \Omega, i = 1, 2. \end{cases}$$
(11)

The split problem (11) with transmission conditions $(11)_2, (11)_3$ is equivalent to the original one, in the sense we introduce the Dirichlet data on the interface $\gamma^{n+1} = u^{n+1}|_{\Gamma}$. Introducing the extension operators \mathcal{H}_i and \mathcal{G}_i as follows

$$\begin{cases} \bar{\mathcal{L}}\mathcal{H}_{i}\gamma^{n+1} = 0 & \text{in }\Omega_{i}, \ i = 1, 2, \\ \mathcal{H}_{i}\gamma^{n+1} = \gamma^{n+1} & \text{on }\Gamma, \\ \mathcal{H}_{i}\gamma^{n+1} = 0 & \text{on }\partial\Omega_{i} \cap \partial\Omega, \end{cases}$$
(12)

and

$$\begin{aligned}
\left\{ \begin{split}
\bar{\mathcal{L}}\mathcal{G}_i \underline{f}_i^{n+1} &= \underline{f}_i^{n+1} & \text{ in } \Omega_i, i = 1, 2, \\
\mathcal{G}_i \underline{f}_i^{n+1} &= 0 & \text{ on } \Gamma, \\
\mathcal{G}_i \underline{f}_i^{n+1} &= 0 & \text{ on } \partial\Omega_i \cap \partial\Omega.
\end{aligned}$$
(13)

The solution is constructed by defining

$$u_i^{n+1} = \mathcal{H}_i \gamma^{n+1} + \mathcal{G}_i \underline{f}_i^{n+1}, \ i = 1, 2.$$
(14)

The Steklov-Poincaré equation is given by

$$S\gamma_{n+1} = \chi_{n+1} \tag{15}$$

where χ_{n+1}

$$\chi_{n+1} := \frac{\partial \mathcal{G}_2 \underline{f}^{n+1}}{\partial \mathbf{n}} - \frac{\partial \mathcal{G}_1 \underline{f}_1^{n+1}}{\partial \mathbf{n}}$$
$$= -\sum_{i=1}^2 \frac{\partial \mathcal{G}_i \underline{f}_i^{n+1}}{\partial \mathbf{n}_i},$$

and

$$S\gamma := \frac{\partial \mathcal{H}_1 \gamma}{\partial \mathbf{n}} - \frac{\partial \mathcal{H}_2 \gamma}{\partial \mathbf{n}}$$
$$= \sum_{i=1}^2 \frac{\partial \mathcal{H}_i \gamma}{\partial \mathbf{n}_i}.$$

The local Steklov-Poincaré operators S_i are then defined as follows

$$S_i \gamma := \frac{\partial \mathcal{H}_i \gamma}{\partial \mathbf{n_i}}.$$
(16)

For accelerating the convergence we initialize the interface condition with the previous solution at convergence (computed in time T_n). $\gamma^{n+1,0} = \gamma^{n,P_{max}}$. Now the Schur

complement algorithm consists of the following steps: at every time step T_{n+1} , given an initial guess $\gamma^{0,0} = u_{0|\Gamma}$ along the interface Γ , compute for p = 1, 2...

$$\begin{cases} \bar{\mathcal{L}}(u_i^{n+1,p+1})(x,y) &= \underline{f}_{i,n+1}(x,y) \quad \text{in } \Omega_i, i = 1, 2, \\ u_i^{n+1,p+1}(x,y) &= 0 \quad \text{on } \partial \Omega_i \cap \partial \Omega, \\ u_i^{n+1,p+1}(x,y) &= \gamma^{n+1,p} \quad \text{on } \Gamma, \end{cases}$$
(17)

and then update the value along the interface using

$$\gamma^{n+1,p+1} = \gamma^{n+1,p} - \theta(S\gamma^{n+1,p} - g^{n+1}), \text{ on } \Gamma,$$
(18)

 $\theta \in]0,1]$ being a relaxation parameter. To investigate the convergence of the iterative solutions of split problem (17) we define the error $e_i^{n,p}$ between the exact solution u^n and the iterates $u_i^{n,p}$ at fixed time level T_n . By linearity, the error satisfies a homogeneous advection-dominated diffusion. We study in the sequel the homogenuous problem with data on the interfaces only. Let $\tilde{\gamma}^{n,p} = \gamma^{n,p} - u_{|\Gamma|}^n$ with $\tilde{\gamma}^p(0) = 0$ to satisfy the compatibility condition. The error equations are given by

$$\begin{cases} \bar{\mathcal{L}}(e_1^{n+1,p+1}) = 0 & \text{in } \Omega_1, \\ e_1^{n+1,p+1}(.) = 0 & \text{on } \partial \Omega_i \cap \partial \Omega, \\ e_1^{n+1,p+1}(.) = \tilde{\gamma}^{n+1,p}, & \text{on } \Gamma, \end{cases}$$
(19)

$$\begin{cases} \bar{\mathcal{L}}(e_2^{n+1,p+1}) = 0 & \text{in } \Omega_2, \\ e_2^{n+1,p+1}(.) = 0 & \text{on } \partial \Omega_i \cap \partial \Omega, \\ e_2^{n+1,p+1}(.) = \tilde{\gamma}^{n+1,p} & \text{on } \Gamma, \end{cases}$$

$$\widetilde{\gamma}^{n+1,p+1} = \widetilde{\gamma}^{n+1,p} - \theta(S_1 + S_2) \widetilde{\gamma}^{n+1,p} & \text{on } \Gamma, \\ = (Id - \theta(S_1 + S_2)) \widetilde{\gamma}^{n+1,p}, & \text{on } \Gamma. \end{cases}$$
(20)

We define the Fourier transform of $e_i^{n,p}$ in the y direction by

$$\hat{e}_i^{n,p}(x,w) := \int_{\mathbb{R}} \exp(-iwy) e_i^{n,p}(x,y) dy.$$
(21)

Applying formally the Fourier transform to the equations (19) and (35), we obtain

$$\begin{cases} \widehat{\mathcal{L}}\widehat{e}_{1}^{n+1,p+1}(x,w) &= 0 \text{ for } (x,w) \in]0, c[\times \mathbb{R}, \\ \widehat{e}_{1}^{n+1,p+1}(0,w) &= 0 \text{ on } \mathbb{R}, \\ \widehat{e}_{1}^{n+1,p+1}(c,w) &= \widehat{\gamma}^{n+1,p}(w) \text{ on } \mathbb{R}, \end{cases}$$
(22)

$$\begin{cases} \widehat{\mathcal{L}}\widehat{e}_{2}^{n+1,p+1}(x,w) &= 0 \text{ pour } (x,w) \in]c, 1[\times \mathbb{R}, \\ \widehat{e}_{2}^{n+1,p+1}(1,w) &= 0 \text{ on } \mathbb{R}, \\ \widehat{e}_{2}^{n+1,p+1}(c,w) &= \widehat{\widetilde{\gamma}}^{n+1,p}(w) \text{ on } \mathbb{R}, \end{cases}$$
(23)

where

$$\hat{\vec{\mathcal{L}}} = -\nu\partial^2/\partial^2 x + \alpha_1\partial/\partial x + (i\alpha_2\nu w + \nu w^2).$$
(24)

The characteristic equation of the second order ordinary differential equation in the x-variable will give us

$$-\nu x^{2} + \alpha_{1} x + \left(\frac{1}{\Delta t} + i\alpha_{2} w + \nu w^{2}\right) = 0,$$
(25)

where the solutions have the form

$$\widehat{e}_{1}^{n+1,p+1}(x,w) = C_{1,1}^{+} \exp(\sigma^{+}x) + C_{1,2}^{-} \exp(\sigma^{-}x), \ x \in [0,c],
\widehat{e}_{2}^{n+1,p+1}(x,w) = C_{2,1}^{+} \exp(\sigma^{+}(x-1)) + C_{2,2}^{-} \exp(\sigma^{-}(x-1)), \ x \in [c,1],$$
(26)

with the characteristic roots

$$\sigma^+ = rac{lpha_1 + \sqrt{r}}{2
u}$$
 and $\sigma^- = rac{lpha_1 - \sqrt{r}}{2
u},$

where r = Re + iIm is a complex number with a real part $Re = \alpha_1^2 + 4\nu(\frac{1}{\Delta t} + \nu w^2)$ and a imaginary part $Im = 4\nu\alpha_2 w$. The complex square root is defined by

$$\sqrt{r} = \frac{1}{\sqrt{2}} (Re + \sqrt{Re^2 + \mathrm{Im}^2})^{1/2} + i \frac{\mathrm{Im}}{|\mathrm{Im}|\sqrt{2}} (-Re + \sqrt{Re^2 + \mathrm{Im}^2})^{1/2}$$
(27)

The coefficients $C_{i,1}$ and $C_{i,2}$ are computed from the boundary conditions in the error equations $(26)_1, (26)_2$, we get

$$\begin{cases} \hat{e}_{1}^{n+1,p+1}(0,w) = 0 \qquad \Rightarrow C_{1,1} = -C_{1,2} \\ \hat{e}_{1}^{n+1,p+1}(c,w) = \hat{\gamma}^{n+1,p} \qquad \Rightarrow C_{1,1} = \frac{\hat{\gamma}^{n+1,p}}{\exp(\frac{\alpha_{1}}{2\nu}c)\sinh(\frac{\sqrt{r}}{2\nu}c)} \\ \hat{e}_{2}^{n+1,p+1}(1,w) = 0 \qquad \Rightarrow C_{2,1} = -C_{2,2} \\ \hat{e}_{2}^{n+1,p+1}(c,w) = \hat{\gamma}^{n+1,p} \qquad \Rightarrow C_{2}^{+} = \frac{\hat{\gamma}^{n+1,p}}{\exp(\frac{\alpha_{1}}{2\nu}(c-1))\sinh(\frac{\sqrt{r}}{2\nu}(c-1))} , \end{cases}$$
(28)

and inserting them into the error equations $(26)_1, (26)_2$ we deduce the subdomain solutions

$$\begin{cases} \widehat{e}_{1}^{n+1,p+1}(x,\Delta t,w) = \exp(\frac{\alpha_{1}}{2\nu}(x-c))\frac{\sinh(\frac{\sqrt{r}}{2\nu}x)}{\sinh(\frac{\sqrt{r}}{2\nu}c)}\widehat{\widetilde{\gamma}}^{n+1,p}, & x \in [0,c], \\ \widehat{e}_{2}^{n+1,p+1}(x,\Delta t,w) = \exp(\frac{\alpha_{1}}{2\nu}(x-c))\frac{\sinh(\frac{\sqrt{r}}{2\nu}(x-1))}{\sinh(\frac{\sqrt{r}}{2\nu}(c-1))}\widehat{\widetilde{\gamma}}^{n+1,p}, & x \in [c,1], \end{cases}$$
(29)

We obtain for the transformed local Steklov-Poincaré operators

$$\begin{cases} \widehat{S}_{1}\widehat{\widetilde{\gamma}}^{n+1,p} = \frac{\partial \widehat{e}_{1}^{n+1,p+1}}{\partial x} = \left[\frac{\alpha_{1}}{2\nu} + \frac{\sqrt{r}}{2\nu} \coth(\frac{\sqrt{r}}{2\nu}c)\right] \widehat{\widetilde{\gamma}}^{n+1,p}, \\ \widehat{S}_{2}\widehat{\widetilde{\gamma}}^{n+1,p} = -\frac{\partial \widehat{e}_{2}^{n+1,p+1}}{\partial x} = -\left[\frac{\alpha_{1}}{2\nu} + \frac{\sqrt{r}}{2\nu} \coth(\frac{\sqrt{r}}{2\nu}(c-1))\right] \widehat{\widetilde{\gamma}}^{n+1,p}, \end{cases}$$
(30)

hence the global Steklov-Poincaré operator can be written as

$$\widehat{S} = \widehat{S}_1 + \widehat{S}_2 = \frac{\sqrt{r}}{2\nu} \left[\coth(\frac{\sqrt{r}}{2\nu}c) - \coth(\frac{\sqrt{r}}{2\nu}(c-1)) \right].$$
(31)

Remark For studying the error solutions of the subproblems (17) over bounded subdomains $\Omega_1 = [0, c] \times [a, b]$ and $\Omega_2 = [c, 1] \times [a, b]$, where 0 < a < b. We define for any bounded functions h the norm

$$||h(.,.)||_{\infty} := \sup_{(x,y)\in\Omega} |h(x,y)|.$$

The error-estimates of the error solutions (19) and (35) are presented in the following lemma :

Lemma 1. (Super-Solutions) At each time step T_{n+1} , for all $p \in \mathbb{N}$ and $r = \alpha_1^2 + 4\nu(\frac{1}{\Delta t} + \nu b^2)$, the error solutions of the subproblems (17) with $\alpha_2 = 0$ satisfy

$$0 \le e_i^{n+1,p}(x,y) \le \tilde{e}_i^{n+1,p}, i = 1, 2,$$

where the super-solutions $\tilde{e}_i^{n+1,p}$ are the solutions of the linear problems

$$\begin{cases} \bar{\mathcal{L}}(\tilde{e}_{1}^{n+1,p+1}) = 0 & \text{in } \Omega_{1}, \\ \tilde{e}_{1}^{n+1,p+1} = 0 & \text{on } \partial \Omega_{i} \cap \partial \Omega, \\ \tilde{e}_{1}^{n+1,p+1}(x) = \exp(\frac{\alpha_{1}}{2\nu}(x-c)) \frac{\sinh(\frac{\sqrt{r}}{2\nu}x)}{\sinh(\frac{\sqrt{r}}{2\nu}c)} \|\widetilde{\gamma}^{n+1,p}\|_{\infty}, x \in [0,c] \end{cases}$$
(32)

$$\begin{cases} \bar{\mathcal{L}}(\tilde{e}_{2}^{n+1,p+1}) = 0 & \text{in } \Omega_{2}, \\ \tilde{e}_{2}^{n+1,p+1} = 0 & \text{on } \partial\Omega_{i} \cap \partial\Omega, \\ \tilde{e}_{2}^{n+1,p+1}(x) = \exp(\frac{\alpha_{1}}{2\nu}(x-c)) \frac{\sinh(\frac{\sqrt{r}}{2\nu}(x-1))}{\sinh(\frac{\sqrt{r}}{2\nu}(c-1))} \|\tilde{\gamma}^{n+1,p}\|_{\infty}, x \in [c,1], \end{cases}$$
(33)

The solutions to (32) and (33) state non-negative solutions

.

$$\begin{cases} \tilde{e}_{1}^{n+1,p+1}(x,\Delta t) = \exp(\frac{\alpha_{1}}{2\nu}(x-c))\frac{\sinh(\frac{\sqrt{r}}{2\nu}x)}{\sinh(\frac{\sqrt{r}}{2\nu}c)} \|\tilde{\gamma}^{n+1,p}\|_{\infty}, \ x \in [0,c],\\ \tilde{e}_{2}^{n+1,p+1}(x,\Delta t,w) = \exp(\frac{\alpha_{1}}{2\nu}(x-c))\frac{\sinh(\frac{\sqrt{r}}{2\nu}(x-1))}{\sinh(\frac{\sqrt{r}}{2\nu}(c-1))} \|\tilde{\gamma}^{n+1,p}\|_{\infty}. \ x \in [c,1], \end{cases}$$
(34)

The difference $E_i := \widetilde{e}_i^{p+1} - e_i^{p+1}$, i = 1, 2 satisfy

$$\begin{cases} \bar{\mathcal{L}}(E_i^{n+1,p+1}) &= 0 & \text{in } \Omega_i, \\ E_i^{n+1,p+1}(.) &= 0 & \text{on } \partial \Omega_i \cap \partial \Omega, \\ E_i^{n+1,p+1}(.) &\geq 0 & \text{on } \Gamma, \end{cases}$$
(35)

Now the Positivity Lemma [3] applies therefore $E_i^{n+1,p+1} = \tilde{e}_i^{n+1,p+1} - e_i^{n+1,p+1} \ge 0$ and similarly for $\tilde{E}_i^{n+1,p+1} = \tilde{e}_i^{n+1,p+1} + e_i^{n+1,p+1} \ge 0$ the error solutions (19) and (35) can be bounded by

$$\begin{cases} \mid e_1^{n+1,p+1} \mid \leq \widetilde{e}_1^{n+1,p+1}(x,\Delta t) = \exp(\frac{\alpha_1}{2\nu}(x-c)) \frac{\sinh(\frac{\sqrt{r}}{2\nu}x)}{\sinh(\frac{\sqrt{r}}{2\nu}c)} \|\widetilde{\gamma}^{n+1,p}\|_{\infty}, \ x \in [0,c], \\ \mid e_2^{n+1,p+1} \mid \leq \widetilde{e}_2^{n+1,p+1}(x,\Delta t) = \exp(\frac{\alpha_1}{2\nu}(x-c)) \frac{\sinh(\frac{\sqrt{r}}{2\nu}(x-1))}{\sinh(\frac{\sqrt{r}}{2\nu}(c-1))} \|\widetilde{\gamma}^{n+1,p}\|_{\infty}. \ x \in [c,1], \end{cases}$$

$$(36)$$

Evaluating the derivates of these equations at x = c taking the supremum over Γ the symbol of the global Steklov-Poincaré operator can be bounded by the quantity

$$\frac{\sqrt{r}}{2\nu} \left[\coth(\frac{\sqrt{r}}{2\nu}c) - \coth(\frac{\sqrt{r}}{2\nu}(c-1)) \right]$$

3.1.2. Neumann-Neumann algorithm

The Neumann-Neumann algorithm starts with an initial guess $\psi_{i,n+1}^0$ along the interface $\Gamma \times [0,T]$ and then computes for $\theta \in]0,1]$ simultaneously for i = 1,2 with $p = 1,2,\ldots$

$$\begin{cases} \bar{\mathcal{L}}u_{i}^{n+1,p+1} &= \underline{f}_{i}^{n+1} \text{ in } \Omega_{i}, \ i = 1, 2, \\ u_{i}^{n+1,p+1} &= \gamma^{n+1,p} \quad \text{ on } \Gamma, \\ u_{i}^{n+1,p+1} &= 0 \quad \text{ on } \partial\Omega_{i} \cap \partial\Omega, i = 1, 2, \end{cases}$$
(37)

$$\begin{cases} \bar{\mathcal{L}}\psi_i^{n+1,p+1} = 0 & \text{in }\Omega_i, \ i = 1, 2, \\ \frac{\partial \psi_i^{n+1,p+1}}{\partial \mathbf{n}_i} = \frac{1}{2} \left(\frac{\partial u_1^{n+1,p+1}}{\partial \mathbf{n}_1} + \frac{\partial u_2^{n+1,p+1}}{\partial \mathbf{n}_2} \right) & \text{on } \Gamma, \\ \psi_i^{n+1,p+1} = 0 & \text{on } \partial\Omega_i \cap \partial\Omega, \ i = 1, 2, \end{cases}$$
(38)

$$\gamma^{n+1,p+1} = \gamma^{n+1,p} - \theta(\frac{1}{2}\psi_1^{n+1,p+1} + \frac{1}{2}\psi_2^{n+1,p+1}) \text{ on } \Gamma.$$
(39)

The Neumann-Neumann preconditionner is a weighted sum of inverse of transform local Steklov-Poinaré. Thus the Fourier transform preconditionner for two sub-domains is defined by:

$$\widehat{P_{NN}}^{-1} = \frac{1}{4}(\widehat{S}_1^{-1} + \widehat{S}_2^{-1}),$$

where from (30)

$$\widehat{S}_1^{-1} = \frac{2\nu}{\alpha_1 + \sqrt{r} \coth(\frac{\sqrt{r}}{2\nu}c),}$$

$$\widehat{S}_2^{-1} = \frac{2\nu}{\sqrt{r} \coth(\frac{\sqrt{r}}{2\nu}(c-1)) - \alpha_1.}$$

However, the Fourier transform of the interface equation (39) becomes

$$\widehat{\gamma}^{n+1,p+1} = (Id - \theta \widehat{P_{NN}}^{-1} \widehat{S}) \widehat{\gamma}^{n+1,p} \text{ on } \Gamma,$$
(40)

where the symbol of the preconditioned operator is easily determined as

$$\widehat{P}_{NN}^{-1}\widehat{S} = \frac{1}{4} \frac{r\left(\coth(\frac{\sqrt{r}}{2\nu}c) + \coth(\frac{\sqrt{r}}{2\nu}(c-1))\right)^2}{\left(\sqrt{r}\coth(\frac{\sqrt{r}}{2\nu}c) + \alpha_1\right)\left(\sqrt{r}\coth(\frac{\sqrt{r}}{2\nu}(c-1)) - \alpha_1\right)}.$$
(41)

3.1.3. Convergence analysis

The main goal of the analysis is to estimate the efficiency of the proposed preconditioner. For this prupose we study the convergence factor. In numerical calculation, the frequency parameter w can not be high and we have $|w| \in [w_{min}, w_{max}]$, where $w_{min} = \pi$ and $w_{max} = \pi/h$ are the frequency minimum and maximum parameters. By indication, the updating boundary condition in (40) satisfies the following inequality

$$\max_{|w|\in[w_{min},w_{max}]} \left| \hat{\gamma}^{n+1,p} \right| = \rho^p \max_{|w|\in[w_{min},w_{max}]} \left| \hat{\gamma}^{n+1,0} \right|, \tag{42}$$

where the optimal convergence factor ρ^p is defined by

$$\rho := \max_{|w| \in [w_{min}, w_{max}]} \left| 1 - \theta \frac{r \left(\coth(\frac{\sqrt{r}}{2\nu}c) + \coth(\frac{\sqrt{r}}{2\nu}(c-1)) \right)^2}{\left(\sqrt{r} \coth(\frac{\sqrt{r}}{2\nu}c) + \alpha_1 \right) \left(\sqrt{r} \coth(\frac{\sqrt{r}}{2\nu}(c-1)) - \alpha_1 \right)} \right|$$
(43)

Remark The convergence factor depends on the relaxation parameter θ but in practical computation Krylov subspace method is more robust and gives better results. For this prupose, in the discrete case, we remplace the Richardson iteration by GMRES iteration.

Lemma 2. For a symmetric decomposition c = 0.5. The convergence factor ρ_{GMRES} of Neumann-Neumann preconditioning in a GMRES iteration is bounded from

$$\rho_{GMRES} \le \left(1 - \frac{(\min_{w \in [\pi, \frac{\pi}{h}]} Re(\phi(w)))^2}{\max_{w \in [\pi, \frac{\pi}{h}]} |\phi(w)|^2} \right)^{1/2},$$
(44)

where $\phi(w)$ is the complex valued can be defined as

$$\phi(w) = \frac{r \coth^2(\frac{\sqrt{rc}}{2\nu})}{r \coth^2(\frac{\sqrt{rc}}{2\nu}) - \alpha_1^2}.$$
(45)

Proof. The reduction factor in a GMRES iteration, for a positive real matrix A with symmetric part $M = \frac{1}{2}(A + A^T)$, is bounded from above [12, 1]

$$\rho_{GMRES} = \left(1 - \frac{(\lambda_{min}(M))^2}{\lambda_{max}(A^T A)}\right)^{1/2}.$$
(46)

where $A = \hat{P}_{NN}^{-1} \hat{S}$, λ_{min} and λ_{max} are the minimum and maximum eigenvalues. After a short calculation, we deduce from (??) the quantity for the preconditioned operator ϕ .

4. The parareal in time algorithm

The exact flow of the model problem (1) is denoted $u(t) = \mathcal{E}_t(u_0)$. The strategy of parareal algorithm is to do a time decomposition in the spirit of domain decomposition. We divide the total simulation time into N subintervals $[T_n, T_{n+1}]$, $n = 0, \ldots, N-1$ of size ΔT . Then $u(T_n) = \mathcal{E}_{\Delta T}(u(T_n)) = \mathcal{E}_{n\Delta T}(u_0)$, from the semigroup property of \mathcal{E} . In general \mathcal{E} is not realizable and can only be approximated, we thus introduce a fine and precise propagator \mathcal{F} , it is based on an appropriate classical discretization scheme based on a small enough time step δt , then we have the approximation $u(T_n) \simeq U_n = \mathcal{F}_{n\Delta T}(u_0)$. The original parareal algorithm makes it possible to define iteratively a sequence U_n^k that converges toward U_n as k goes to infinity. The definition of this sequence requires a coarse propagator \mathcal{G} , which represents a cheap and less accurate approximation to $\mathcal{F}_{\Delta T}$ and based on a similar scheme in time with the larger time step

 ΔT , $\delta t \ll \Delta T$. By nature \mathcal{G} has to be run sequentially and \mathcal{F} in parallel. In this way, the algorithm starts with an initial approximation U_n^0 given for example by the sequential computation :

$$U_0^0 = u_0, \qquad U_n^0 = \mathcal{G}_{\Delta T}(U_{n-1}^0),$$

the numerical scheme of the parareal method is given by :

$$U_n^{k+1} = \mathcal{G}_{\Delta T}(U_{n-1}^{k+1}) + \mathcal{F}_{\Delta T}(U_{n-1}^k) - \mathcal{G}_{\Delta T}(U_{n-1}^k),$$
(47)

with the initial condition $U_0^k = u_0$. Note that after k iterations of the parareal method, the solution U_m^k for $m \le k$ is exactly equal to the numerical solution given by using the \mathcal{F} propagator in a serial manner. In an other hand, it is clear that we have $U_n = \mathcal{F}_{n\Delta T}(0, u_0)$ for any n and then we must converge with $k \ll N$ iterations so that the algorithm is interesting.

4.1. Convergence analysis

We review here the stability and the convergence of the standard parareal algorithm in two dimensions. The convergence have been first presented in [3] on the entire domain \mathbb{R} . We define the error derived from the standard algorithm (47) for n = 1, ..., N and $k = 0, ..., k_{conv}$ by $e_n^k := U_n^k - U_n$. After adding and subtracting $\mathcal{G}_{\Delta T}(U_{n-1})$ and $\widetilde{\mathcal{F}}_{\Delta T}(U_{n-1}^{k-1})$ this error e_n^k satisfies for $n \ge 1$ and $k \ge 1$

$$e_{n}^{k} = \mathcal{G}_{\Delta T}(U_{n-1}^{k}) - \mathcal{G}_{\Delta T}(, U_{n-1}^{k-1}) + \mathcal{F}_{\Delta T}(U_{n-1}^{k-1}) - \mathcal{F}_{\Delta T}(, U_{n-1}) = [\mathcal{G}_{\Delta T}(U_{n-1}^{k}) - \mathcal{G}_{\Delta T}(U_{n-1})] + [\mathcal{G}_{\Delta T}(\mathcal{F}_{T_{n-1}}(u_{0})) - \mathcal{F}_{\Delta T}(U_{n-1})]$$
(48)

We now denote by ΔG the difference $\mathcal{F} - G$. Then the relation (48) becomes over Ω ; for every n and k

$$e_{n}^{k} = [\mathcal{G}_{\Delta T}(, U_{n-1}^{k}) - \mathcal{G}_{\Delta T}(U_{n-1})] + [\Delta \mathcal{G}_{\Delta T}(U_{n-1}) - \Delta \mathcal{G}_{\Delta T}(U_{n-1}^{k-1})].$$
(49)

Our purpose now is to have an estimation of the error $e_n^k(x)$ based on the Fourier transformation of the exact and discrete solutions which is given for any h in the bounded domain in \mathbb{R}^{\neq} by

$$\hat{h}(t,\xi_1,\xi_2) = \sum_{\xi_1 = -\infty}^{+\infty} \sum_{\xi_2 = -\infty}^{+\infty} h(t,x,y) \exp(-i(\xi_1 x + \xi_2 y)).$$

We apply the Fourier transform in x and y directions to the model problem (1) with u_0 is periodic, we obtain

$$\begin{cases} \frac{\partial \hat{u}}{\partial t}(t,\xi_1,\xi_2) + (\nu(\xi_1^2 + \xi_2^2) + i(\alpha_1\xi_1 + \alpha_2\xi_2))\hat{u}(t,\xi_1,\xi_2) = 0, (\xi_1,\xi_2) \in \mathbb{Z} \times \in \mathbb{Z} \\ \hat{u}(t,\xi_1,\xi_2) = \hat{u}_0(\xi_1,\xi_2) \end{cases}$$
(50)

We note $\delta(\xi_1, \xi_2) := ((\nu(\xi_1^2 + \xi_2^2) + i(\alpha_1\xi_1 + \alpha_2\xi_2))\Delta T \text{ and } \xi = (\xi_1, \xi_2)$. The exact solution of problem (50) is given at time T_n by

$$\hat{u}(\xi, T_n) = \exp(-n\delta(\xi))\hat{u}_0(\xi) = \widehat{\mathcal{E}}_{T_n}(\delta(\xi), T_0, \hat{u}_0)$$
(51)

In a similar manner to (47), we introduce two approximations $\widehat{\mathcal{F}}$ and $\widehat{\mathcal{G}}$ of $\widehat{\mathcal{E}}_{T_n}$ and we define a sequence $\{\widehat{U}_n\}_{n\geq 1}$ by

$$\hat{U}_n(\xi) = \widehat{\mathcal{F}}_{\Delta T}(\delta(\xi), \hat{U}_{n-1}(\xi)). \quad \forall n, \ \hat{U}_0 = \hat{u}_0,$$

and we construct a sequence $\{\hat{U}_n^k\}_k$ by

$$\hat{U}_0^0(\xi) = \hat{u}_0(\xi), \qquad \hat{U}_n^0(\xi) = \hat{\mathcal{G}}_{\Delta T}(\delta(\xi), U_{n-1}^0(\xi)) \text{ for } n = 1, \dots, N,$$

and then performs for $k = 0, ..., k_{conv}$ the correction iterations :

$$\hat{\lambda}_n^{k+1}(\xi) = \widehat{\mathcal{G}}_{\Delta T}(\delta(\xi), \widehat{U}_{n-1}^{k+1}(\xi) - \widehat{\mathcal{G}}_{\Delta T}(\delta(\xi), \widehat{U}_{n-1}^k(\xi)) \text{ for } n = 1, \dots, N.$$

Here specially, $\widehat{\mathcal{F}}$ is taken exact so that $\widehat{U}_n(\xi) = \exp(-n\delta(\xi))\widehat{U}_0(\xi)$ and for implicit first order Euler scheme $\widehat{\mathcal{G}}_{\Delta T}(\xi,.) = (1 + \delta(\xi))^{-1}$. Let $\widehat{e}_n^k := \widehat{U}_n^k - \widehat{U}_n$ and $\Delta \widehat{\mathcal{G}} = \widehat{\mathcal{F}} - \widehat{\mathcal{G}}$. This error satisfies for all $\xi \in \mathbb{Z}^2$

$$\hat{e}_{n}^{k}(\xi) = \left[\widehat{\mathcal{G}}_{\Delta T}(\delta(\xi), \hat{U}_{n-1}^{k}(\xi)) - \widehat{\mathcal{G}}_{\Delta T}(\delta(\xi), \hat{U}_{n-1}(\xi)) \right] \\
+ \left[\Delta \widehat{\mathcal{G}}_{\Delta T}(\delta(\xi), \hat{U}_{n-1}(\xi)) - \Delta \widehat{\mathcal{G}}_{\Delta T}(\delta(\xi), \hat{U}_{n-1}^{k-1}(\xi)) \right]$$
(52)

We introduce the stability function R

$$R_{k,n}(\delta) = |\widehat{\mathcal{G}}_{\Delta T}(\delta, \widehat{U}_{n-1}^k(\xi))|^{n-k} |\widehat{\mathcal{F}}_{\Delta T}(\delta, \widehat{U}_{n-1}^k(\xi)) - \widehat{\mathcal{G}}_{\Delta T}(\delta, \widehat{U}_{n-1}^k(\xi))|^k \begin{pmatrix} n \\ k-1 \\ (53) \end{pmatrix}$$

The parareal algorithm replaces an algorithm of order m by an algorithm of order km and requires to solve a fine scale problem k times to obtain this accuracy. The stability is then stated in the following theorem (see Theorem 2 in [3]).

Theorem 1. Let us assume that the coarse scheme is an approximation of first order of the exact propagator and that it is dissipative in the sense that there exist two constants C and $\gamma > 0$ such that for all ξ

$$\begin{aligned} |\mathcal{F}_{\Delta T}(\delta(\xi)) - \mathcal{G}_{\Delta T}(\delta(\xi))| &\leq C(|\delta(\xi)|^2 \wedge 1), \\ |\mathcal{G}_{\Delta T}(\delta(\xi))| &\leq (1 + C\Delta T) \exp(-\gamma(|\delta(\xi)| \wedge 1)). \end{aligned}$$
(54)

Then the parallel algorithm is stable in the sense that $R_{k,n}(\delta)$ given by (53) is bounded uniformly in k and $\delta = \delta(\xi)$ for $\xi \in \mathbb{Z}^2$ where $a \wedge b = \min(a, b)$.

The one dimensional results (see Theorem 3 in [3]) have been generalized to two dimensions and we have the following result of convergence at final time T = 1 by using

$$\| u \|_{H^1(\Omega)} = \sum_{\xi_1 = -\infty}^{+\infty} \sum_{\xi_2 = -\infty}^{+\infty} |\hat{u}|^2 (1 + \xi_1^2 + \xi_2^2).$$

Theorem 2. Under the assumptions of theorem 1 and if u_0 is periodic, the error e_n^k given by (52) is bounded by

$$\parallel e_n^k \parallel_{H^1(\Omega)} \le C\Delta T^k \parallel u_0 \parallel_{H^1(\Omega)}.$$
(55)

5. Parareal-Non-Overlapping Domain Decomposition Method

The parareal-domain decomposition algorithm does this by using a parareal approximation for the initial condition and a domain decomposition algorithms for the boundary conditions. We use the Neumann-Neumann algorithm for the approximate resolution of the fine propagator independently over each block $\Omega_i \times [T_{n-1}, T_n]$, $i = 1, \ldots, N_s, n = 0, \ldots, N$. The coupled parareal is based on the dual iterative definition of the snapshots U_n^k at each time T_n and on the interface condition $\gamma_{n-1}^{k,0} := u_{n-1,\Gamma}^{k,0}$. The algorithm is thus expressed as follows

$$U_{n}^{k+1} = \mathcal{G}_{\Delta T}(U_{n-1}^{k+1}) + \widetilde{\mathcal{F}}_{\Delta T}(U_{n-1}^{k}, \gamma_{n-1}^{k,0}) - \mathcal{G}_{\Delta T}(U_{n-1}^{k}),$$
(56)

where $\widetilde{\mathcal{F}}_{\Delta T}(U_{n-1}^k, \gamma_{n-1}^{k,0})$ is the approximate propagator with only some P domain decomposition iterations.

More precisely we construct $\widetilde{\mathcal{F}}_{\Delta T}$ as following. We denote by $u_{i,n-1}^{k,P}(x,t)$ the local solutions on the space-time slices $\Omega_i \times [T_{n-1}, T_n]$ at iteration k. The fine solution approximated by the algorithm is built, for every fixed k and in each subdomain Ω_i , in several steps by a propagation over $\Omega_i \times [T_{n-1}, T_n]$, an update of the boundary conditions and a new propagation over $\Omega_i \times [T_{n-1}, T_n]$ using the new boundary conditions. The definition of the fine solver is then completed by the compute of the new global solution over $\Omega \times [T_{n-1}, T_n]$. More precisely, for $p = 1, \ldots, P$ we solve

$$\begin{cases} \overline{\mathcal{L}}(u_{i,n-1}^{k,p}) &= 0 & \text{in } \Omega_i \times]T_{n-1}, T_n[\\ u_{i,n-1}^{k,p}(x,t) &= \gamma_{n-1}^{k,p-1}(t) \text{ on } \Gamma \times]T_{n-1}, T_n[\\ u_{i,n-1}^{k,p}(0,t) &= 0 & \text{in }]T_{n-1}, T_n[, \\ \\ \overline{\mathcal{L}}(\psi_{i,n-1}^{k,p}) &= 0 & \text{in } \Omega_i \times]T_{n-1}, T_n[\\ \psi_{i,n-1}^{k,p}(x,t) &= \frac{1}{2} \left(\frac{\partial u_{1,n-1}^{k,p}}{\partial \mathbf{n}_1} + \frac{\partial u_{2,n+1}^{k,p}}{\partial \mathbf{n}_2} \right) \text{ on } \Gamma \times]T_{n-1}, T_n[\\ \psi_{i,n-1}^{k,p}(x,t) &= 0 & \text{ in }]T_{n-1}, T_n[. \end{cases}$$

Then we define the global fine solution by

$$\widetilde{\mathcal{F}}_{\Delta T}(U_{n-1}^k, u_{n-1,\Gamma}^{k+1,0}) = \sum_{i=1}^{N_s} \chi^i(x) u_{i,n-1}^{k,p}(x, T_n),$$

where χ^i are a regular partition of unity defined by

$$\forall x \in \Omega, \ \sum_{i=1}^{N_s} \chi^i(x) = 1, \ \chi^i \ge 0, \ i = 1, \dots, N_s.$$

Remark

To accelerate convergence, we initialized the interface conditions by the previous iterate parareal after a few iterations of domain decomposition methods

$$u_{n-1,\Gamma}^{k,0} = u_{n-1,\Gamma}^{k-1,P},$$

where the boundary condition at the interface is compatible with the initial condition provided at time T_{n-1} for each local problem.

For $P \to \infty$ we have $u_{n-1,\Gamma}^{k-1,\infty}$ the exact interface conditions associated with the initial condition U_{n-1}^{k-1} which then verify $\widetilde{\mathcal{F}}_{\Delta T}(U_{n-1}^k, u_{n-1,\Gamma}^{k,\infty}) = \mathcal{F}_{\Delta T}(U_{n-1}^k)$ we obtain the standard parareal algorithm (47).

The parareal-Neumann-Neumann algorithm for the problem (1) can be written like (see Algorithme 1) :

Algorithme 1 : Parareal-Neumann-Neumann algorithm $U_0^0 \Leftarrow u_0;$ ϵ a tolerance of the algorithm ; for $n \leftarrow 1$ to N do $\gamma_{n-1}^{0,0} \Leftarrow u_0;$ Step 1. solve \mathcal{G} to obtain the initial guess U_n^0 $Un^0 \leftarrow \mathcal{G}_{\Delta T}(U_{n-1}^0)$ end repeat Step 2. solve in parallel $\widetilde{\mathcal{F}}$ by Neumann-Neumann method parallel for $n \leftarrow 1$ to N do $\begin{aligned} & \left[\mathbf{parallel \ for \ } i \leftarrow 1 \ \mathbf{to} \ N_s \ \mathbf{do} \\ & u_{i,n}^k \Leftarrow \widetilde{\mathcal{F}}_{\Delta T}(U_{n-1}^0, \gamma_{n-1}^{k,P}) \end{aligned} \right. \end{aligned}$ endfor endfor Step 3. initialize the interface condition by the previous iterate parareal after a few iterations of Neumann-Neumann method for $n \leftarrow 1$ to N do $\gamma_{n-1}^{k+1,0} = \gamma_{n-1}^{k,P}$ end Step 4. compute the new iterate U_n^{k+1} , $n = 1 \dots N$ by a series of correction iterations
$$\begin{split} & U_n^{k+1} = \mathcal{G}_{\Delta T}(U_{n-1}^{k+1}) + \widetilde{\mathcal{F}}_{\Delta T}(U_{n-1}^k,\gamma_{n-1}^{k,0}) - \mathcal{G}_{\Delta T}(U_{n-1}^k); \\ & \text{end} \end{split}$$
 $\begin{aligned} k &\Leftarrow k+1 \\ \textbf{until} \ \|U_n^{k+1} - U_n^k\| < \epsilon; \end{aligned}$

5.1. Convergence analysis

We present now a convergence result of the coupled parareal algorithm.

Theorem 3. Under the hypothesis (54) and assuming that

$$\rho^P \approx \frac{1}{N^{\frac{5}{2}}},\tag{57}$$

The parareal algorithm (56) applied to the one dimensional convection diffusion problem (1) with u_0 in $H^1(\Omega)$ satisfies the estimate

$$\| U_n^k(x) - u_n(x) \|_{H^1(\Omega)} \le C\Delta T^{k+1} + \rho^P \Delta T^{k-1} \| u_0 \|_{H^1(\Omega)} .$$
(58)

Proof. The proof of this theorem is based on the classic recurrence method and will appear in [7]. The estimations of the error $v(x) = U_n^k(x) - u_n(x)$ provided from the convergence rate ΔT^{k+1} of standard parareal algorithm and from the convergence factor ρ of the domain decomposition method. We present however a detailed numerical study of the convergence in the following section.

6. Numerical Results

We present now numerical experiments to study the theoretical convergence factor ρ according to Lemma (2) of the discretized Neumann-Neumann algorithm for the model problem on the unit square in two dimensions with the initial condition $u_0(x) = \sin(\pi x) \sin(\pi y)$, advection velocity $\alpha = (\alpha_1, \alpha_2)$ and f(t) = 1 + t. We choose $\nu = 0.5$, $\alpha_1 = 1$ and $\alpha_2 = 0$ The prototype implementation was done in FreeFem++, The library MPI is used for the parallelization of the code. We discretize in space using finite elements P^1 -Lagrange on a uniform mesh with meshsize h. The time discretization is a characteristics method of first order for the advection and implicit for the diffusion. We decompose the domain into two non-overlapping subdomains $\Omega_1 = [0, 0.5] \times [0, 1]$ and $\Omega_2 = [0.5,] \times [0, 1]$. For determining the values of interface conditions for domain decomposition algorithms the GMRES method is applied. We test the Neumann-Neumann algorithm by choosing the interface condition $\gamma^{0,0} = u_{0,\Gamma}$.

6.1. Convergence of the Neumann-Neumann algorithm

We wish to study the convergence factor. From Figure 1 to Figure 4, we show the convergence factor behavior for different values of mesh size h for Schur complement algorithm and for the best preconditionner Neumann-Neumann for different time-steps Δt . One can clearly see that the behavior of the algorithms depend on time step. We observe in Figure 2 and Figure 4 that the Neumann-Neumann algorithm converges as fast as the Schur complement algorithm for bigger time step. We deduce that the Schur complement algorithm is much less sensitive with respect the mesh size. The use of parallel preconditioner Neumann-Neumann propagator is necessary to accelerate convergence. From Figure 1 and Figure 3 we observe convergence results for no preconditioner Schur complement shows a strong mesh size h-dependence.

6.2. Convergence of the coupled parareal-Neumann-Neumann algorithm

We now focus on the coupled parareal algorithm. We choose for the spatial discretization step $h = \frac{1}{128}$, for the coarse time step $\Delta T = \frac{1}{10}$ and for the fine time step $\delta t = \frac{\Delta T}{50}$. For the Neumann-Neumann algorithm we make the number GMRES constant (2 iterations per subdomain) for fine time step $\Delta t = \delta t$. We initialize the interface condition by



Figure 1. The theoretical convergence factor ρ of Schur complement for different values of mesh size h = 1/8, 1/16, 1/32 and Δt varying through $[10^{-3}, 10^{-2}]$.

Figure 2. The theoretical convergence factor ρ of Neumann-Neumann preconditioner for different values of mesh size h = 1/8, 1/16, 1/32 and Δt varying through $[10^{-3}, 10^{-2}]$.





Figure 3. The theoretical convergence factor ρ of Schur complement for different values of mesh size h = 1/64, 1/128 and Δt varying through $[10^{-3}, 10^{-2}]$.

Figure 4. The theoretical convergence factor ρ of Neumann-Neumann preconditioner for different values of mesh size h1/64, 1/128 and Δt varying through $[10^{-3}, 10^{-2}]$.



 $\gamma_n^{k,0} = \gamma_n^{k-1,2}$. To test the convergence of the solution obtained from the coupled parareal algorithm to the monodomain fine solution \mathcal{F} , we compare the relative errors

$$\frac{\|U_{exact}(T_n) - \mathcal{F}_{n\Delta T}(u_0)\|_{H^1(\Omega)}}{\|U_{exact}(T_n)\|_{H^1(\Omega)}}$$
(59)

with

$$\frac{\|U_{exact}(T_n) - U_n^k\|_{H^1(\Omega)}}{\|U_{exact}(T_n)\|_{H^1(\Omega)}}$$
(60)

where U_{exact} is supposed the exact solution (reference solution) computed in the global domain with a very fine time step $\delta t/10$. Table 1 illustrates the errors between the exact solution and the pure sequential fine solver \mathcal{F} at the instant times $T_n, 1 \leq n \leq 10$.

T_n	$ U_{exact}(T_n) - \mathcal{F}_{n\Delta T}(u_0) _{H^1(\Omega)}$
	$ U_{exact}(T_n) _{H^1(\Omega)}$
0.1	$1.85 \ 10^{-4}$
0.2	$8.80 \ 10^{-5}$
0.3	$1.16 \ 10^{-4}$
0.4	$1.63 \ 10^{-4}$
0.5	$1.91 \ 10^{-4}$
0.6	$2.11 \ 10^{-4}$
0.7	$2.28 \ 10^{-4}$
0.8	$2.43 \ 10^{-4}$
0.9	$2.58 \ 10^{-4}$
1	$2.73 \ 10^{-4}$

Table 1. Error between a fine solution and the exact solution obtained with a very fine time step $\delta t/10$ at the instant times $T_n, 1 \le n \le 10$.

T_n	k=1	k=2	k=3	k=4
0.1	$4.43 \ 10^{-3}$	$1.36 \ 10^{-3}$	$1.92 \ 10^{-4}$	$1.72 \ 10^{-4}$
0.2	$2.37 \ 10^{-3}$	$1.11 \ 10^{-3}$	$1.13 \ 10^{-4}$	$9.14 \ 10^{-5}$
0.3	$1.21 \ 10^{-3}$	$1.17 \ 10^{-3}$	$1.19\ 10^{-3}$	$1.18 \ 10^{-3}$
0.4	$1.42 \ 10^{-3}$	$1.29 \ 10^{-3}$	$1.28 \ 10^{-3}$	$1.26 \ 10^{-3}$
0.5	$1.76 \ 10^{-3}$	$1.39 \ 10^{-3}$	$1.37 \ 10^{-3}$	$1.32 \ 10^{-3}$
0.6	$1.97 \ 10^{-3}$	$1.50 \ 10^{-3}$	$1.47 \ 10^{-3}$	$2.02 \ 10^{-4}$
0.7	$2.11\ 10^{-3}$	$1.60\ 10^{-3}$	$1.57 \ 10^{-3}$	$2.07 \ 10^{-4}$
0.8	$2.22\ 10^{-3}$	$1.69 \ 10^{-3}$	$3.66 \ 10^{-4}$	$2.12\ 10^{-4}$
0.9	$2.31 \ 10^{-3}$	$1.79 \ 10^{-3}$	$3.76 \ 10^{-4}$	$2.18\ 10^{-4}$
1	$2.40\ 10^{-3}$	$1.89 \ 10^{-3}$	$3.86 \ 10^{-4}$	$2.25 \ 10^{-4}$

Table 2. Coupled parareal : Historic of the errors between the exact solution and solution of coupled parareal for different values of iteration of parareal k = 1, 2, 3, 4 for P = 2.

The Tables 2 represent the error between the coupled parareal obtained after two iterations of Neumann-Neumann algorithm and the numerical solution computed in the global domain. Tables 2 shows the convergence of the coupled algorithm after k = 4. The conclusion reached from these experiment is that with algorithm, a few iterations in each time step are sufficient to obtain convergence. The measured convergence factor of GMRES $\rho^P = 1.078 \ 10^{-2}$, we notice that at convergence for modified algorithm it is sufficient that $\rho^P \approx C\Delta T^2$. The results confirm the theoretical hypothesis (57) derived in Theorem (6.3).

6.3. Experiments with more than two subdomains

These experiments are of interest to generalize the convergence results for two subdomains to many subdomains. We consider the same model problem with the same parameters. We decompose the global domain $\Omega = [0,1] \times [0,1]$ into $N_s = 4$ non-overlapping subdomains with cross-points, namely interface nodes that belong to more than two domains, $\Omega_1 = [0,0.5] \times [0,0.5], \Omega_2 = [0.5,1] \times [0,0.5], \Omega_3 = [0,0.5] \times [0.5,1]$ and $\Omega_4 = [0.5,1] \times [0.5,1]$. We fixed two iteration of GMRES of preconditioner Neumann-Neumann. We compare the maximum error in time of (59) with the error (60), the maximum error in time (60).

We note that convergence can be achieved in a finite number of a GMRES in two iterations only after 4 iterations of parareal. The measured convergence factor of GMRES $\rho^2 = 1.257 \ 10^{-2}$ The results confirm the theoretical hypothesis in Theorem . Furthermore the convergence is independent of the number of subdomains.

k = 1	k = 2	k = 3	k = 4	k = 5
$5.39 \ 10^{-2}$	$4.42 \ 10^{-3}$	$3.05 \ 10^{-4}$	$2.74 \ 10^{-4}$	$2.74 \ 10^{-4}$

Table 3. Historic of the error using a norm $L^{\infty}(0,T; H^1(\Omega))$ between parareal-domain decomposition solutions and the reference one, for different values of k

Numerical scalability of the parallel Finally we investigate the numerical scalability of the parallel with respect to the coarse time step ΔT . We split the global domain Ω into $N_s = 8$ from $\Omega_1 = [0, 0.25] \times [0, 0.5]$ to $\Omega_8 = [0.75, 1] \times [0.5, 1]$. We use two iterations of GMRES constant, next we fix the fine time step $\delta t = \frac{1}{6000}$ and vary the coarse time step ΔT . The log_{10} scale error between the global fine solution and the reference one is -3.38. From Table 4, we observe that the convergence can be achieved after k = 4. One can see that when increasing the number of time decompositions subdomains parareal is barely affected.

k	ΔT	$\Delta T/2$	$\Delta T/4$	$\Delta T/8$
1	-1.16	-1.57	-2.05	-2.1
2	-1.82	-2.26	-2.74	-2.85
3	-2.55	-3.03	-3.37	-3.37
4	-3.25	-3.31	-3.37	-3.37
5	-3.37	-3.38	-3.37	-3.37

Table 4. Historic of the error using a norm $L^{\infty}(0,T; H^1(\Omega))$ in log_{10} scale between parareal-domain decomposition solutions and the reference one, for different values of

$\frac{k}{7}$. Conclusion

The purpose of this paper was to develop an efficient algorithm for advection-dominated diffusion problem by combining the parareal algorithm with Neumann-Neumann domain decomposition algorithm, in order to perform the parallelism both in time and space. We have studied more precisely the convergence factor of Neumann-Neumann algorithm, the main properties used in the convergence analysis is a Fourier analysis and a maximum principle for the 2D case and a two subdomain decomposition. Numerical results show that, with only two iterations of GMRES with Neumann-Neumann preconditioner in each parareal iteration, the new algorithm leads to a good monodomain solution.

8. References

- Y. ACHDOU, F. NATAF, "A Robin-Robin preconditioner for an advection-diffusion problem, In Domain decomposition methods, 10 (Boulder, CO, 1997), pages 377–383. Amer. Math. Soc., Providence, RI, 1998.
- [2] L. BAFFICO, S. BERNARD, MADAY, Y., TURINICI, G. & ZÉRAH, G." Parallel-in-time molecular-dynamics simulations, *Phys. Rev. E*, vol. 66, num. 057701, 2002.
- [3] G. BAL, Y. MADAY, "On the convergence and the stability of the parareal algorithm to solve partial differential equations", C. R. Acad. Sci. Paris Sér. I Math., vol. 40 pages 425–432, 2005.
- [3] H. BREZIS ", Analyse fonctionnelle: Théorie et applications Collection: Sciences Sup, Dunod 2005 - 248 pages.
- [4] X.-C. CAI, "Additive Schwarz algorithms for parabolic convection- diffusion equations", *Numerische Mathematik*, vol. 60 num. 1 pages 41-61, 1991.
- [5] C. FARHAT, "A Lagrange multiplier based divide and conquer finite element algorithm", Journal of Computer and Systems Engineering, num. 2 pages 149-156, 1991.
- [6] M. J. GANDER, S. VANDEWALLE, "Analysis of the parareal time-parallel time-integration method", SIAM J. Sci. Comput., vol. 29 pages 556-578, 2007.
- [7] R. GUETAT "Méthode de parallélisation en temps: Application aux méthodes de décomposition de domaine,", *PhD thesis, UPMC& EPT*, 203 pages, 2011.
- [7] P. LE TALLEC, "Domain decomposition methods in computational mechanics", *in: Oden (J. T.), Computational Mechanics Advances*vol. 1 num. 2, 121–220, 1994.
- [8] J.-L. LIONS Y. MADAY, G. TURINICI, "Résolution d'EDP par un schéma en temps pararéel", C. R. Acad. Sci. Paris Sér. I Math., vol. 332 num. 7 pages 661–668, 2001.

- [9] Y. MADAY, G. TURINICI," A parareal in time procedure for the control of partial differential equation, *C.R. Acad. Sci. Paris., Ser.Ivol.* 335 pages 387-392, 2002.
- [10] J.MANDEL "Balancing domain decomposition", Communications in Numerical Methods in Engineering, : vol. 233 num. 9(3), 1993.
- [11] A. QUARTERONI, A. VALLI "Domain decomposition methods for partial differential equations", *Oxford University Press.* 2000.
- [12] Y. SAAD, H. SCHULTZ, "GMRES: a generalized minimal residual algorithm for solving nonsymmetric linear systems, SIAM J. Sci. Stat. Comput. 7 (3) pages 856-869, 1986.
- [13] A. TOSELLI, O. WIDLUNG, "Domain Decomposition Methods Algorithms and Theory", *Springer Series in Computational Mathematics. Springer*, vol. 20, 2005.