



## Towards Consistency-Based Reliability Assessment

Laurence Cholvy, Laurent Perrussel, William Raynaut, Jean-Marc Thévenin

### ► To cite this version:

Laurence Cholvy, Laurent Perrussel, William Raynaut, Jean-Marc Thévenin. Towards Consistency-Based Reliability Assessment. 14th International Joint Conference on Autonomous Agents and Multiagent Systems (AAMAS 2015), May 2015, Istanbul, Turkey. pp. 1643-1644. hal-01327078

**HAL Id: hal-01327078**

**<https://hal.science/hal-01327078>**

Submitted on 6 Jun 2016

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



## Open Archive TOULOUSE Archive Ouverte (OATAO)

OATAO is an open access repository that collects the work of Toulouse researchers and makes it freely available over the web where possible.

This is an author-deposited version published in : <http://oatao.univ-toulouse.fr/>  
Eprints ID : 15444

The contribution was presented at :  
<http://www.aamas2015.com/en/>

**To cite this version** : Cholvy, Laurence and Perrussel, Laurent and Raynaut, William and Thévenin, Jean-Marc *Towards Consistency-Based Reliability Assessment*. (2015)  
In: International Joint Conference on Autonomous Agents and Multiagent Systems (AAMAS 2015), 4 May 2015 - 8 May 2015 (Istanbul, Turkey).

Any correspondence concerning this service should be sent to the repository administrator: [staff-oatao@listes-diff.inp-toulouse.fr](mailto:staff-oatao@listes-diff.inp-toulouse.fr)

# Towards Consistency-Based Reliability Assessment

## (Extended Abstract)

Laurence Cholvy  
ONERA  
Toulouse, France

Laurent Perrussel  
Université Toulouse 1 Capitole  
Toulouse, France

William Raynaut  
ONERA  
Toulouse, France

Jean-Marc Thévenin  
Université Toulouse 1 Capitole  
Toulouse, France

### Keywords

Logics for agents and multi-agent systems, Reasoning in agent-based systems

## 1. MOTIVATION

Merging information provided by several sources is an important issue and merging techniques have been extensively studied. When the reliability of the sources is not known, one can apply merging techniques such as majority or arbitration merging or distance-based merging for solving conflicts between information. At the opposite, if the reliability of the sources is known, either represented in a quantitative or in a qualitative way, then it can be used to manage contradictions: information provided by a source is generally weakened or ignored if it contradicts information provided by a more reliable source [1, 4, 6]. Assessing the reliability of information sources is thus crucial. The present paper addresses this key question. We adopt a qualitative point of view for reliability representation by assuming that the relative reliability of information sources is represented by a total preorder. This works considers that we have no information about the sources and in particular, we do not know if they are correct (i.e they provide true information) or not. We focus on a preliminary stage of observation and assessment of sources. We claim that during that stage the key issue is a consistency analysis of information provided by sources, whether it is the consistency of single reports or consistency w.r.t trusted knowledge or the consistency of different reports together. We adopt an axiomatic approach: first we give some postulates which characterize what this reliability preorder should be, then we define a generic operator for building this preorder in agreement with the postulates.

## 2. PRELIMINARIES

Let  $A$  be a finite set of agents; let  $L$  be a propositional logic defined over the finite set of propositional letters and propositional constants  $\top$  and  $\perp$ . An interpretation  $m$  is a mapping from the set of formulas of  $L$  to the set of truth values  $\{0, 1\}$  so that  $m(\top) = 1$  and  $m(\perp) = 0$ . Interpretation  $m$  is a *model* of formula  $F$  iff  $m(F) = 1$ . The set of  $F$  models is denoted  $M(F)$ . *Tautologies* are formulas which are interpreted by 1 in any interpretation. We write  $\models F$  when  $F$  is a tautology. *Consistent* formulas are interpreted by 1 in at least one interpretation. A formula is *consistent* iff it has one model.

Let  $\leq$  be a total preorder on  $A$  representing the relative reliability of agents:  $a \leq b$  stands for  $b$  is at least as reliable as  $a$ .  $a = b$  stands for  $a \leq b$  and  $b \leq a$ .  $GT(a, \leq) = \{x \in A \setminus \{a\} : a \leq x\}$  is the set of agents which are as least as reliable as  $a$ . Let  $a \in A$ ,  $\leq_1$  be a total preorder on  $A$  and  $\leq_2$  a total preorder on  $A \setminus \{a\}$ ;  $\leq_1$  is *compatible with*  $\leq_2$  iff  $\forall x \forall y \ x \leq_2 y \implies x \leq_1 y$ .

A *communication set* on  $A$ ,  $\Psi$ , is a set of pairs  $\langle a, \varphi \rangle$  where  $a \in A$  and  $\varphi$  is a formula reported by  $a$ . We define  $Ag(\Psi) = \{a \in A, \exists \varphi \ \langle a, \varphi \rangle \in \Psi\}$ ,  $\Psi_a = \{\langle a, \varphi \rangle \mid \langle a, \varphi \rangle \in \Psi\}$  and  $\Psi(C) = \bigcup_{a \in C} \Psi_a$ , if  $C$  is a set of agents. Finally we define  $\text{Report}(\Psi)$  by  $\bigwedge_{\langle a, \varphi \rangle \in \Psi} \varphi$  if  $\Psi \neq \emptyset$  and by  $\top$  otherwise.

Let  $\Psi$  and  $\Psi'$  be two communication sets on  $A$ .  $\Psi$  and  $\Psi'$  are *equivalent* (denoted  $\Psi \equiv \Psi'$ ) iff  $\forall a \in A \ \models \text{Report}(\Psi_a) \leftrightarrow \text{Report}(\Psi'_a)$ .  $\Psi$  and  $\Psi'$  are *weakly equivalent* (denoted  $\Psi \rightharpoonup \Psi'$ ) iff  $\forall a \in A, \exists b \in A, \exists c \in A \ \models \text{Report}(\Psi_a) \leftrightarrow \text{Report}(\Psi'_b)$  and  $\models \text{Report}(\Psi'_a) \leftrightarrow \text{Report}(\Psi_c)$ .

Consistency of communication sets is evaluated with respect to some integrity constraint  $IC$ , which is a consistent formula of  $L$ .  $IC$  has to be viewed as information taken for granted or certain. Let  $\Psi$  be a communication set on  $A$ .  $\Psi$  is *IC-contradictory* iff  $\text{Report}(\Psi) \wedge IC$  is inconsistent; otherwise  $\Psi$  is *IC-consistent*.  $\Psi$  is *minimal IC-contradictory* iff  $\Psi$  is *IC-contradictory* and no strict subset of  $\Psi$  is *IC-contradictory*. The set of *minimal IC-contradictory* subsets of  $\Psi$  is denoted  $\Psi \perp IC$ .

$A^\perp = \bigcup_{F \in \Psi \perp IC} Ag(F)$  is the set of agents which have reported a piece of information which belongs to some *minimal IC-contradictory* communication set. Notice that  $A^\perp \neq \emptyset$  iff  $\Psi$  is *IC-contradictory*.

Finally consider  $C \subseteq A$ .  $C$  is *IC-conflicting* iff  $\text{Report}(\Psi(C)) \wedge IC$  is inconsistent.  $C$  is *minimal IC-conflicting* iff it is *IC-conflicting* and no strict subset of  $C$  is *IC-conflicting*.

### 3. RELIABILITY ASSESSMENT

Given a set of agents  $A$ , an integrity constraint  $IC$  and a communication set  $\Psi$ , the total preorder representing the relative reliability of agents in  $A$  is denoted  $\Gamma^{IC,A}(\Psi)$ . The operator  $\Gamma$ , which defines this relative reliability preorder is characterized by the following postulates:

- P1**  $\Gamma^{IC,A}(\Psi)$  is a total preorder on  $A$ .
- P2** If  $\Psi \equiv \Psi'$  then  $\Gamma^{IC,A}(\Psi) = \Gamma^{IC,A}(\Psi')$ .
- P3** If  $\models IC \leftrightarrow IC'$  then  $\Gamma^{IC,A}(\Psi) = \Gamma^{IC',A}(\Psi)$ .
- P4** If  $\models \text{Report}(\Psi_a)$  then  $\Gamma^{IC,A}(\Psi)$  is compatible with  $\Gamma^{IC,A \setminus \{a\}}(\Psi \setminus \Psi_a)$ .
- P5** If  $A$  is not  $IC$ -conflicting then  $\Gamma^{IC,A}(\Psi)$  is the equality preorder.
- P6** If  $A$  is  $IC$ -conflicting then  $A \setminus A^\perp \subseteq GT(a, \Gamma^{IC,A}(\Psi))$  for any  $a \in A^\perp$ .
- P7** If  $\{a_1, \dots, a_k\}$  ( $k \geq 2$ ) is a minimal  $IC$ -conflicting subset of agents then  $\exists i \forall j \neq i, GT(a_j, \Gamma^{IC,A}(\Psi)) \subset GT(a_i, \Gamma^{IC,A}(\Psi))$ .

Postulate **P1** specifies that the expected result is a total preorder. **P2** and **P3** deal with syntax independence. **P4** states that an agent which reports a tautology or which reports no information has no influence on the relative reliability of other agents. **P5**, **P6** and **P7** focus on consistency of information provided by agents in  $A$ . **P5** considers the case when  $A$  is not  $IC$ -conflicting. In such a case, the sources are considered as equally reliable. **P6** and **P7** consider the cases when  $A$  is  $IC$ -conflicting. According to **P6**, any agent reporting a piece of information belonging to some minimal  $IC$ -contradictory communication set is considered as less reliable than any other agent which have not. According to **P7**, if some agents are minimally  $IC$ -conflicting, then at least one of these agents is strictly less reliable than the others. This is inline with our understanding of reliability: if some agents are at the same level of reliability, then we will believe, with the same strength, information they will provide. But, it is generally admitted ([2, 5]) that it is impossible to believe with the same strength, several pieces of information which are contradictory. Consequently, agents who are  $IC$ -conflicting should not be at the same levels of reliability.

### 4. A GENERIC OPERATOR

We start by introducing a measure to quantify the inconsistency degree of communication sets. This measure is adapted from the Shapley inconsistency measure proposed in [3] for measuring inconsistency of sets of formulas.

**DEFINITION 1.** A weak-independent  $IC$ -inconsistency measure is a function  $I_{IC}$  which associates any communication set  $\Psi$  with a positive real number  $I_{IC}(\Psi)$  so that:

- Consistency:**  $I_{IC}(\Psi) = 0$  iff  $\Psi$  is  $IC$ -consistent.
- Monotony:**  $I_{IC}(\Psi \cup \Psi') \geq I_{IC}(\Psi)$
- Dominance:** for all  $\phi$  and  $\psi$ , if  $IC \wedge \phi \models \psi$  and  $IC \wedge \phi$  is consistent, then  $I_{IC}(\Psi \cup \{< a, \phi >\}) \geq I_{IC}(\Psi \cup \{< b, \psi >\})$  for any  $a, b \in A$ .
- Free formula independence:** If  $< a, \phi >$  is free (it does not belong to any minimal  $IC$ -contradictory subset of  $\Psi \perp IC$ ), then  $I_{IC}(\Psi) = I_{IC}(\Psi \setminus \{< a, \phi >\})$ .
- Syntax weak-independence:**  $\forall IC'$  if  $\models IC \leftrightarrow IC'$  then  $I_{IC}(\Psi) = I_{IC'}(\Psi)$  and  $\forall \Psi'$  if  $\Psi \rightleftharpoons \Psi'$  then  $I_{IC}(\Psi) = I_{IC}(\Psi')$

For instance, the two following measures are syntax weak-independent  $IC$ -inconsistency measures.

- $I_{drastic}^{IC}(\Psi) = 0$  if  $\Psi$  is  $IC$ -consistent; 1 otherwise.
  - $I_{MI}^{IC}(\Psi) = \text{size of } (\bigcup_{a \in Ag(\Psi)} < a, \text{Report}(\Psi_a) > \perp IC)$
- Then we introduce a function for measuring how much an agent contributes to the  $IC$ -inconsistency of a communication set. Ac-

cording to this definition, the contribution of an agent to the fact that  $\Psi$  is  $IC$ -contradictory is the importance of this agent in a coalitional game defined by function  $I_{IC}$ .

**DEFINITION 2.** Consider a set of agents  $A$ , a communication set  $\Psi$  on  $A$ , an integrity constraint  $IC$  and a syntax weak-independent  $IC$ -inconsistency measure  $I_{IC}$ . Function  $\text{Cont}_{\Psi}^{I_{IC}}$  associates any agent  $a$  with a positive real number  $\text{Cont}_{\Psi}^{I_{IC}}(a) = \sum_{\substack{C \subseteq A \\ C \neq \emptyset}} \frac{(|C|-1)! (|A|-|C|)!}{|A|!} (I_{IC}(\Psi(C)) - I_{IC}(\Psi(C \setminus \{a\})))$

Function  $\text{Cont}_{\Psi}^{I_{IC}}$  obviously induces a total preorder among agents. But this preorder does not satisfy **P7**. This is why we propose the following generic operator for ranking agents,  $\Gamma^{I_{IC}}$ , which agrees with postulates.

**DEFINITION 3.**  $\Gamma^{I_{IC}}$  is defined by:

1.  $X \leftarrow A$
2.  $E \leftarrow \Psi \perp IC$
3.  $\leq \leftarrow \{a \leq b \mid a, b \in A\}$
4. **While**  $E \neq \emptyset$  **do**
  - (a) Deterministically choose  $a \in Ag(\cup_{F \in E} F)$  which maximizes  $\text{Cont}_{\Psi}^{I_{IC}}(a)$
  - (b)  $X \leftarrow X \setminus \{a\}$
  - (c)  $E \leftarrow E \setminus \{F \in E \mid a \in Ag(F)\}$
  - (d)  $\leq \leftarrow \leq \setminus \{b \leq a \mid b \in X\}$
5. **Return**  $\leq$

**THEOREM 1.**  $\Gamma^{I_{IC}}$  operator satisfies postulates **P1-P7**.

### 5. CONCLUSION

This work proposes to assess the relative reliability of some information sources by analysing the consistency of information they report, whether it be the consistency of each single report, or the consistency of a report as regard to some trusted knowledge or the consistency of different reports together. We have given some postulates stating what the relative reliability preorder should be. Then we have introduced a generic operator for building such preorder which is parametrized by a function for measuring the inconsistency of the information reported. We prove that this generic operator agrees with the postulates.

Notice that if one has already some partial information about the reliability of the agents (for instance, one knows that  $a$  is more reliable than  $b$  but has no idea about  $c$  reliability) then this process is not applicable as is. In that case, reliability assessment consists of combining the different preorders. For future work, we plan to study these agregation operators.

### REFERENCES

- [1] L. Cholvy, Reasoning about merged information, In Handbook of Defeasible Reasoning and Uncertainty management, Vol 1, Kluwer Publishers 1998.
- [2] R. Demolombe, C.-J. Liao. A logic of Graded Trust and Belief Fusion. Proc. of the 4<sup>th</sup> Workshop on Deception, Fraud and Trust in Agent Societies, pp. 13-25.
- [3] Anthony Hunter, Sébastien Konieczny, On the measure of conflicts: Shapley Inconsistency Values. Artificial Intelligence 174(14): 1007-1026 (2010)
- [4] C.-J. Liao, A modal logic framework for multi-agent belief fusion, In ACM Transactions on Computational Logic, 6(1): 124-174 (2005)
- [5] N. Laverny and J. Lang. From Knowledge-based programs to graded belief-based programs, Part I: on-line reasoning. Synthese 147, pp 277-321, Springer, 2005.
- [6] E. Lorini and L. Perrussel and J.M. Thévenin, A Modal Framework for Relating Belief and Signed Information. in: Proc. of CLIMA'11, LNAI 6814, 58-73, Springer-Verlag (2011).