

Private Multi-party Matrix Multiplication and Trust Computations

Jean-Guillaume Dumas, Pascal Lafourcade, Jean-Baptiste Orfila, Maxime

Puys

▶ To cite this version:

Jean-Guillaume Dumas, Pascal Lafourcade, Jean-Baptiste Orfila, Maxime Puys. Private Multi-party Matrix Multiplication and Trust Computations. SECRYPT 2016: 13th International Conference on Security and Cryptography, Jul 2016, Lisbonne, Portugal. hal-01344750v1

HAL Id: hal-01344750 https://hal.science/hal-01344750v1

Submitted on 12 Jul 2016 (v1), last revised 14 Sep 2016 (v2)

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Private Multi-party Matrix Multiplication and Trust Computations*

Jean-Guillaume Dumas¹, Pascal Lafourcade², Jean-Baptiste Orfila¹ and Maxime Puys³

¹Université Grenoble Alpes, CNRS, LJK, 700 av. centrale, IMAG/CS-40700, 38058 Grenoble cedex 9, France. {Jean-Guillaume.Dumas,Jean-Baptiste.Orfila}@imag.fr

²Université Clermont Auvergne, LIMOS, Campus Universitaire des Cézeaux, BP 86, 63172 Aubière Cedex, France. Pascal.Lafourcade@udamail

³Université Grenoble Alpes, CNRS, Verimag, 700 av. centrale, IMAG - CS 40700, 38058 Grenoble cedex 9, France. Maxime.Puys@imag.fr

July 12, 2016

Abstract

This paper deals with distributed matrix multiplication. Each player owns only one row of both matrices and wishes to learn about one distinct row of the product matrix, without revealing its input to the other players. We first improve on a weighted average protocol, in order to securely compute a dot-product with a quadratic volume of communications and linear number of rounds. We also propose a protocol with five communication rounds, using a Paillier-like underlying homomorphic public key cryptosystem, which is secure in the semi-honest model or secure with high probability in the malicious adversary model. Using ProVerif, a cryptographic protocol verification tool, we are able to check the security of the protocol and provide a countermeasure for each attack found by the tool. We also give a randomization method to avoid collusion attacks. As an application, we show that this protocol enables a distributed and secure evaluation of trust relationships in a network, for a large class of trust evaluation schemes.

1 Introduction

Secure multiparty computations (MPC), introduced by Yao [29] with the millionaires' problem, has been intensively studied during the past thirty years. The idea of MPC is to allow n players to jointly compute a function f using their private inputs without revealing them. In the end, they only know the result of the computation and no more information. Depending on possible corruptions of players, one may prove that a protocol may resist against a collusion of many players, or that it is secure even if attackers try to maliciously modify their inputs. Mostly any function can be securely computed [4] and many tools exist to realize MPC protocols. They comprise for instance the use of a Trusted Third Party [14], the use of Shamir's secret sharing scheme [27], or more recently the use of homomorphic encryption [18]. It is also possible to mix these techniques [10].

Our goal is to apply MPC to the a distributed evaluation of trust, as defined in [21, 15]. There, confidence is a combination of degrees of trust, distrust and uncertainty between players. Aggregation of trusts between players on a network is done by a matrix product defined on two monoids (one for the addition of trust, the other one for multiplication, or transitivity): each player knows one row of the matrix, its partial trust on its neighbors, and the network as a whole has to compute a distributed matrix squaring. Considering that the trust of each player for his colleagues is private, at the end of the computation, nothing but one row of the global trust has to be learned by each player (*i.e.*, nothing about private inputs should be revealed to others). Thus, an MPC protocol to resolve this problem should combine privacy (nothing is learned but the output), safety (computation of the function does not reveal anything about inputs) and efficiency [23]. First, we need to define a MPC protocol which allows us to efficiently compute a distributed matrix product with this division of data between players. The problem is reduced to the computation of a dot product between vectors U and V such that one player knows U and V is

^{*}This work was partially supported by "Digital trust" Chair from the University of Auvergne Foundation, by the HPAC project (ANR 11 BS02 013), the ARAMIS project (PIA P3342-146798) and the LabEx PERSYVAL-Lab (ANR-11-LABX-0025).

divided between all players.

Related Work. Dot product in the MPC model has been widely studied [13, 2, 28]. However, in these papers, assumptions made on data partitions are different: there, each player owns a complete vector, and the dot product is computed between two players where; in our setting, trust evaluation should be done among peers, like certification authorities. For instance, using a trusted third party or permuting the coefficients is unrealistic. Now, computing a dot product with *n* players is actually close to the MPWP protocol of [12], computing a mean in a distributed manner: computing dot products is actually similar to computing a weighted average where the weights are in the known row, and the values to be averaged are privately distributed. In MPWP the total volume of communication for a dot product is $O(n^3)$ with O(n) communication rounds. Other generic MPC protocols exist, also evaluating circuits, they however also require $O(n^3)$ computations and/or communications per dot-product [6, 10].

Contributions. We provide the following results:

- A protocol *P-MPWP*, improving on *MPWP*, which reduces both the computational cost, by allowing the use of Paillier's cryptosystem, and the communication cost, from $O(n^3)$ to $O(n^2)$.
- An O(n) time and communications protocol *Distributed and Secure Dot-Product* (*DSDP_i*) (for *i* participants) which allows us to securely compute a dot product *UV*, against a semi-honest adversary, where one player owns a vector *U* and where each player knows one coefficient of *V*.
- A parallel variant that performs the dot-product computation in parallel among the players, limits the total number of rounds. This is extended to a *Parallel Distributed and Secure Matrix-Multiplication (PDSMM_i*) family of protocols.
- A security analysis of the *DSDP* protocol using a cryptographic protocol verification tool, here ProVerif [7, 8]. This tool allows us to define countermeasures for each found attack: adapted proofs of knowledge in order to preserve privacy and a *random ring order*, where private inputs are protected as in a wiretap code [25] and where the players take random order in the protocol to preserve privacy with high probability, even against a coalition of malicious insiders.
- Finally, we show how to use these protocols for the computation of trust aggregation, where classic addition and multiplication are replaced by more generic operations, defined on monoids.

In Section 2, we thus first recall some multi-party computation notions. We then introduce in Section 3 the trust model based on monoids. In Section 4, we present our quadratic variant of MPWP and a linear-time protocol in Section 5. We then give the associated security proofs and countermeasures in Section 6 and present parallelized version in Section 7. Finally, in Section 8, we show how our protocols can be adapted to perform a private multi-party trust computation in a network.

2 Background and Definitions

We use a public-key homomorphic encryption scheme where both addition and multiplication are considered. There exist many homomorphic cryptosystems, see for instance [24, § 3] and references therein. We need the following properties on the encryption function E (according to the context, we use E_{PubB} , or E_1 or just E to denote the encryption function, similarly for the signature function, D_1 or D_{privB}): computing several modular additions, denoted by $Add(c_1;c_2)$, on ciphered messages and one modular multiplication, denoted by Mul(c;m), between a ciphered message and a cleartext. That is, $\forall m_1, m_2 \in \mathbb{Z}/m\mathbb{Z}$: $Add(E(m_1); E(m_2)) =$ $E(m_1 + m_2 \mod m)$ and $Mul(E(m_1);m_2) = E(m_1m_2 \mod m)$. For instance, Paillier's or Benaloh's cryptosystems [26, 5, 17] can satisfy these requirements, *via* multiplication in the ground ring for addition of enciphered messages ($Add(E(m_1); E(m_2)) = E(m_1)E(m_2) \mod m$), and *via* exponentiation for ciphered multiplication ($Mul(E(m_1); m_2) = E(m_1)^{m_2} \mod m$), we obtain the following homomorphic properties:

$$E(m_1)E(m_2) = E(m_1 + m_2 \mod m)$$
 (1)

$$E(m_1)^{m_2} = E(m_1m_2 \mod m)$$
 (2)

Since we consider the semantic security of the cryptosystem, we assume that adversaries are probabilistic polynomial time machines. In MPC, most represented intruders are the following ones:

- Semi-honest (honest-but-curious) adversaries: a corrupted player follows the protocol specifications, but also tries to gather as many information as possible in order to deduce some private inputs.
- *Malicious adversaries*: a corrupted player that controls the network and stops, forges or listens to messages in order to gain information.

3 MONOIDS OF TRUST

There are several schemes for evaluating the transitive trust in a network. Some use a single value representing the probability that the expected action will happen; the complementary probability being an uncertainty on the trust. Others include the *distrust* degree indicating the probability that the opposite of the expected action will happen [19]. More complete schemes can be introduced to evaluate trust: Jøsang introduces the *Subjective Logic* notion which expresses beliefs about the truth of propositions with degrees of "uncertainty" in [21]. Then the authors of [20] applied the associated calculus of trust to public key infrastructures. There, trust is represented by a triplet, (trust, distrust, uncertainty) for the proportion of experiences proved, or believed, positive; the proportion of experiences *proved negative*; and the proportion of experiences with unknown character. As *uncertainty* = 1 - trust - distrust, it is sufficient to express trust with two values as $\langle trust, distrust \rangle$. In *e.g.* [16] algorithms are proposed to quantify the trust relationship between two entities in a network, using transitivity and reachability. For instance, in [15] the authors use an adapted power of the adjacency matrix to evaluate the trust using all existing (finite) trust paths between entities. We show in the following of this section, that powers of this adjacency matrix can be evaluated privately in a distributed manner, provided than one disposes of an homomorphic cryptosystem satisfying the homomorphic Properties (1) and (2).

3.1 Aggregation of Trust

Consider Alice trusting Bob with a certain trust degree, and Bob trusting Charlie with a certain trust degree. The sequential aggregation of trust formalizes a kind of transitivity to help Alice to make a decision about Charlie, that is based on Bob's opinion. In the following, we first consider that the trust values are given as a pair $\langle a, b \rangle \in \mathbb{D}^2$, for \mathbb{D} a principal ideal ring: for three players P_1 , P_2 and P_3 , where P_1 trusts P_2 with trust value $\langle a, b \rangle \in \mathbb{D}^2$ and P_2 trusts P_3 with trust value $\langle c, d \rangle \in \mathbb{D}^2$ the associated *sequential aggregation of trust* is a function $\bigstar : \mathbb{D}^2 \times \mathbb{D}^2 \to$

 \mathbb{D}^2 , that computes the trust value over the trust path $P_1 \xrightarrow{\langle a,b \rangle} P_2 \xrightarrow{\langle c,d \rangle} P_3$ as $\langle a,b \rangle \bigstar \langle c,d \rangle = \langle ac+bd,ad+bc \rangle$. Similarly, from Alice to Charlie, there might be several ways to perform a sequential aggregation (several paths with existing trust values). Therefore it is also possible to aggregate these parallel paths with the same measure, in the following way: for two disjoint paths $P_1 \xrightarrow{\langle a,b \rangle} P_3$ and $P_1 \xrightarrow{\langle c,d \rangle} P_3$, the associated *parallel aggregation of trust* is a function $\bigstar : \mathbb{D}^2 \times \mathbb{D}^2 \to \mathbb{D}^2$, that computes the resulting trust value as: $\langle a,b \rangle \bigstar \langle c,d \rangle = \langle a+c-ac,bd \rangle$. We prove the following Lemma.

Lemma 1. $\langle a,b \rangle$ is invertible for \mathbf{A} if and only if (b is invertible in \mathbb{D}) and (a = 0 or a - 1 is invertible).

Proof. As $\langle a + 0 - a.0, b.1 \rangle = \langle a, b \rangle$, $\langle 0, 1 \rangle$ is neutral for \mathbf{F} . Then, for *b* invertible, if a = 0, then $\langle 0, b^{-1} \rangle$ is an inverse for $\langle 0, b \rangle$. Otherwise, for a - 1 invertible, $\langle a(a-1)^{-1}, b^{-1} \rangle \mathbf{F} \langle a, b \rangle = \langle a, b \rangle \mathbf{F} \langle a(a-1)^{-1}, b^{-1} \rangle = \langle a + a(a-1)^{-1} - a^2(a-1)^{-1}, bb^{-1} \rangle = \langle 0, 1 \rangle$. Similarly, if $\langle a, b \rangle \mathbf{F} \langle c, d \rangle = \langle 0, 1 \rangle$, then bd = 1 and *b* is invertible. Then also (a-1)c = a. Finally if $a \neq 0$ and a-1 is a zero divisor, there exists $\lambda \neq 0$ such that $\lambda(a-1) = 0$, thus $\lambda(a-1)c = 0 = \lambda a$, but then $\lambda(a-1) - \lambda a = -\lambda = 0$. As this is contradictory, the only possibilities are a = 0 or a-1 invertible.

3.2 Multi-party Private Aggregation

For *E* an encryption function, we define the natural morphism on pairs, so that it can be applied to trust values: $E(\langle a, b \rangle) = \langle E(a), E(b) \rangle$. We can thus extend homomorphic properties to pairs so that the parallel and sequential aggregation can then be computed homomorphically, provided that one entry is in clear.

Lemma 2. With an encryption function E, satisfying the homomorphic Properties (1) and (2), we have:

$$Mul(E(\langle a,b\rangle);\langle c,d\rangle) = E(\langle a,b\rangle \bigstar \langle c,d\rangle)$$
$$= \langle E(a)^{c}E(b)^{d}, E(a)^{d}E(b)^{c}\rangle$$
$$Add(E(\langle a,b\rangle);\langle c,d\rangle) = E(\langle a,b\rangle \bigstar \langle c,d\rangle)$$
$$= \langle E(a)E(c)E(a)^{-c}, E(b)^{d}\rangle$$

Moreover, those two functions can be computed on an enciphered $\langle a, b \rangle$, provided that $\langle c, d \rangle$ is in clear.

Proof. From the homomorphic properties of the encryption functions, we have: $E(a)^{c}E(b)^{d} = E(ac+bd)$, $E(a)^{d}E(b)^{c} = E(ad+bc)$, $E(a)E(c)E(a)^{-c} = E(a+c+a(-c))$ and $E(b)^{d} = E(bd)$. For the computation, both right hand sides depend only on ciphered values E(a), E(b), and on clear values c and d(E(c) can be computed with the public key, from c).

This shows, that in order to compute the aggregation of trust privately, the first step is to be able to compute dot-products privately.

4 FROM MPWP TO P-MPWP

4.1 MPWP description

The *MPWP* protocol [12] is used to securely compute private trust values in an additive reputation system between *n* players. Each player P_i (excepted P_1 , assumed to be the master player) has a private entry v_i , and P_1 private entries are weights u_i associated to others players. The goal is to compute a weighted average trust, *i.e.*, $\sum_{i=2}^{n} u_i * v_i$. The idea of *MPWP* is the following: the first player creates a vector *TV* containing her private entries ciphered with her own public key using Benaloh's cryptosystem, *i.e.*, $TV = [E_1(w_2), \ldots, E_1(w_n)]$. Then, P_1 also sends a $(n-1) \times (n-1)$ matrix *M*, with all coefficients initialized to 1 and a variable A = 1. Once (M, TV, A) received, each player computes: $A = A * E_1(u_i)^{v_i} * E_1(z_i)$, where z_i is a random value generated by P_i . At the end, the first player gets $D_1(A) = \sum_{i=2}^{n} u_i v_i + z_i$. Then, the idea is to cut the z_i values in n-1 positive shares such that $z_i = \sum_{j=2}^{n} z_{i,j}$. Next, each $z_{i,j}$ is ciphered with the public key of P_j , the result is stored into the *i*th column of *M*, and *M* is forwarded to the next player. In a second phase, players securely remove the added random values to *A*, from $M = (m_{i,j}) = (E_j(z_{i,j}))$: each player P_j , except P_1 , computes her $PSS_j = \sum_{i=2}^{n} D_j(m_{i,j}) = \sum_{i=2}^{n} z_{i,j}$ by deciphering all values contained in the *j*th row of *M*; then they send $\gamma_j = E_1(PSS_j)$ to P_1 , their PSS_i ciphered with the public key of P_1 . At the end, P_1 retrieves the result by computing $Trust = D_1(A) - \sum_{j=2}^{n} D_1(\gamma_j) = D_1(A) - \sum_{j=2}^{n} PSS_j = D_1(A) - \sum_{i=2}^{n} Z_{i,j} = D_1(A) - \sum_{i=2}^{n} Z_{i,j} = U_i v_i$.

4.2 P-MPWP: A lighter MPWP

P-MPWP is a variant of *MPWP* with two main differences: first Paillier's cryptosystem is used instead of Benaloh's, and, second, the overall communications cost is reduced from $O(n^3)$ to $O(n^2)$ by sending parts of the matrix only. All steps of *P-MPWP* but those clearly identified in the following are common with *MPWP*, including the players' global settings. Since *P-MPWP* is using a cryptosystem where players can have different modulus, some requirements must be verified in the players' settings. First of all, a bound *B* needs to be fixed for the vectors' private coefficients:

$$\forall i, 0 \le u_i \le B, 0 \le v_i \le B \tag{3}$$

With Benaloh, the common modulus M must be greater than the dot product, thus at most:

$$(n-1)B^2 < M. \tag{4}$$

Differently, with Paillier, each player P_i has a different modulus N_i . Then, by following the *MPWP* protocol steps, at the end of the first round, P_1 obtains $A = \prod_{i=2}^{n} E_1(u_i)^{v_i} * E_1(z_i)$. In order to correctly decipher this coefficient, if the players' values, as well as their random values z_i , satisfy the bound (3), her modulo N_1 must be greater than $(n-1)(B^2 + B)$. For others players, there is only one deciphering step, at the second round. They received (n-1) shares all bounded by B. Hence, their modulus N_i need only be greater than (n-1)B. These modulus requirements are summarized in the following lemma:

Lemma 3. Let n > 3 be the number of players. Under the bound (3), if $\forall i, 0 \le z_i \le B$ and if also the modulus satisfy $(n-1)(B^2+B) < N_1$ and $(n-1)B < N_i$, $\forall i = 2, ..., n$, then at the end of P-MPWP, P_1 obtains $S_n = \sum_{i=2}^n u_i * v_i$.

Now, the reduction of the communications cost in *P-MPWP*, is made by removing the exchange of the full *M* matrix between players. At the $z_{i,j}$ shares computation, each P_i directly sends the j^{th} coefficient to the j^{th} player instead of storing results in *T*. In the end, each player P_i receives (n-1) values ciphered with his public key, and he can compute the *PSS_i* by deciphering and adding each received values, exactly as in *MPWP*. Thus, each player sends only O(n) values, instead of $O(n^2)$. All remaining steps can be executed as in *MPWP*.

Both Paillier's and Benaloh's cryptosystems provides semantic security, thus the security of *P-MPWP* is not altered. Moreover, since a common bound is fixed *a priori* on private inputs, *P-MPWP* security can be reduced to the one in *MPWP* with the common modulo *M* between all players [1]. Finally, since all exploitable (*i.e.*, clear or ciphered with the dedicated key) information exchanged represents a subset of the *MPWP* players' knowledge, if one is able to break *P-MPWP* privacy, then one is also able to break it in *MPWP*.

5 A LINEAR DOT PRODUCT PROTOCOL

5.1 Overview with Three Players

We first present in Figure 1 our $DSDP_3$ protocol (Distributed and Secure Dot-Product), for 3 players. The idea is that Alice is interested in computing a dimension 3 dot-product $S = u^T \cdot v$, between her vector u and a vector v whose coefficients are owned by different players. The other players send their coefficients, encrypted, to Alice. Then she homomorphically multiplies each one of these by her u_i coefficients and masks the obtained u_iv_i by a

random value r_i . Then the other players can decrypt the resulting $u_iv_i + r_i$: with two unknowns u_i and r_i they are not able to recover v_i . Finally the players enter a ring computation of the overall sum before sending it to Alice. Then only, Alice removes her random masks to recover the final dot-product. Since at least two players have added $u_2v_2 + u_3v_3$, there is at least two unknowns for Alice, but a single equation.





We need that after several decryptions and re-encryptions, and removal of the random values r_i , S is exactly $\sum u_i v_i$. The homomorphic Properties (1) and (2) only guaranty that $D(\text{Add}(\text{Mul}(E(v_i);u_i);r_i)) = v_i u_i + r_i \mod N_i$, for the modulo N_i of the cryptosystem used by player P_i . But then these values must be re-encrypted with another player's cryptosystem, potentially with another modulo. Finally Alice also must be able to remove the random values and recover S over \mathbb{Z} . On the one hand, if players can share the same modulo $M = N_i$ for the homomorphic properties then decryptions and re-encryptions are naturally compatible. This is possible for instance in Benaloh's cipher. On the other hand, in a Paillier-like cipher, at the end of the protocol, Alice will actually recover $S_4 = ((u_2v_2 + r_2) \mod N_2 + u_3v_3 + r_3) \mod N_3$. He can remove r_3 , $via S_3 = S_4 - r_3 \mod N_3$, but then $S_3 = ((u_2v_2 + r_2) \mod N_2 + u_3v_3) \mod N_3$. Now, if vectors coefficients are bounded by say B, and if the third modulo is larger than the second, $N_3 > N_2 + B^2$, the obtained value is actually the exact value over the naturals: $S_3 = (u_2v_2 + r_2) \mod N_2 + u_3v_3$. Then Alice can remove the second random value, this time modulo $N_2: S_2 = (u_2v_2 + u_3v_3) \mod N_2$, where now $N_2 > 2B^2$ suffices to recover $S = S_2 \in \mathbb{N}$. We generalize this in the following section.

5.2 General Protocol with *n* Players

We give the generalization $DSDP_n$, of the protocol of Figure 1 for *n* players in Algorithm 4 hereafter. For this protocol to be correct, we use the previously defined bound (3) on the players' private inputs. Then, for *n* players, there are two general cases: First, if all the players share the same modulo $M = N_i$ for all *i* for the homomorphic properties, then Alice can also use *M* to remove the r_i . Then, to compute the correct value *S*, it is sufficient to satisfy the bound (4). Second, for a Paillier-like cipher, differently, the modulo of the homomorphic properties are distinct. We thus prove the following Lemma 5.

Lemma 5. Under the bound (3), and for any r_i , let $M_2 = (u_2v_2 + r_2) \mod N_2$ and $M_i = (M_{i-1} + u_iv_i + r_i) \mod N_i$, for $i = 2 \dots n - 1$. Let also $S_{n+1} = M_n$ and $S_i = (S_{i+1} - r_i) \mod N_i$ for $i = n \dots 2$. If we have:

$$\begin{cases} N_{i-1} + (n-i+1)B^2 < N_i, & \text{for all } i = 3..n \\ (n-1)B^2 < N_2 \end{cases}$$
(5)

then $S_2 = \sum_{i=2}^n u_i v_i \in \mathbb{N}$.

Proof. By induction, we first show that $S_i = M_{i-1} + \sum_{j=i}^n u_j v_j$, for i = n..3: indeed $S_n = (M_n - r_n) \mod N_n = (M_{n-1} + u_n v_n) \mod N_n$. But M_{n-1} is modulo N_{n-1} , so $(M_{n-1} + u_n v_n) < N_{n-1} + B^2$, and then (5) for i = n, ensures that $N_{n-1} + B^2 < N_n$ and $S_n = M_{n-1} + u_n v_n \in \mathbb{N}$. Then, for $3 \le i < n$, $S_i = (S_{i+1} - r_i) \mod N_i = (M_i + \sum_{j=i+1}^n u_j v_j - r_i) \mod N_i = (M_{i-1} + u_i v_i + r_i + \sum_{j=i+1}^n u_j v_j - r_i) \mod N_i = (M_{i-1} + \sum_{j=i}^n u_j v_j) \mod N_i$, by induction. But (3) enforces that $M_{i-1} + \sum_{j=i}^n u_j v_j < N_{i-1} + (n-i+1)B^2$ and (5) also ensures the latter is lower than N_i . Therefore $S_i = M_{i-1} + \sum_{j=i}^n u_j v_j$ and the induction is proven. Finally, $S_2 = (S_3 - r_2) \mod N_2 = (N_i - 1) + (N_$

Algorithm 4 DSDP_n Protocol: Distributed and Secure Dot-Product of size n

Require: $n \ge 3$ players, two vectors U and V such that P_1 knows complete vector U, and each players P_i knows component v_i of V, for i = 1...n;

Require: E_i (resp. D_i), encryption (resp. decryption) function of P_i , for i = 2...n. **Ensure:** P_1 knows the dot-product $S = U^T V$.

1: **for** i = 2...n **do** $\{P_i : c_i = E_i(v_i); P_i \stackrel{c_i}{\to} P_1\}$ 2: **for** i = 2...n **do** 3: $P_1 : r_i \stackrel{\leq}{\to} \mathbb{Z}/N_i\mathbb{Z}$ 4: $P_1 : \alpha_i = c_i^{u_i} * E_i(r_i)$ so that $\alpha_i = E_i(u_iv_i + r_i)$ 5: $P_1 \stackrel{\alpha_2}{\to} P_2$ 6: **for** i = 2...n - 1 **do** $P_1 : \stackrel{\alpha_{i+1}}{\to} P_i$ 7: $P_2 : \Delta_2 = D_2(\alpha_2)$ so that $\Delta_2 = u_2v_2 + r_2$ 8: $P_2 : \beta_3 = \alpha_3 * E_3(\Delta_2)$ so that $\beta_3 = E_3(u_3v_3 + r_3 + \Delta_2); P_2 \stackrel{\beta_3}{\to} P_3$ 9: **for** i = 3...n - 1 **do** 10: $P_i : \Delta_i = D_i(\beta_i)$ so that $\Delta_i = \sum_{k=2}^i u_k v_k + r_k$ 11: $P_i : \beta_{i+1} = \alpha_{i+1} * E_{i+1}(\Delta_i)$ so that $\beta_{i+1} = E_{i+1}(u_{i+1}v_{i+1} + r_{i+1} + \Delta_i); P_i \stackrel{\beta_{i+1}}{\to} P_{i+1}$ 12: $P_n : \Delta_n = D_n(\beta_n); P_n : \gamma = E_1(\Delta_n); P_n \stackrel{\gamma}{\to} P_1$ 13: **return** $P_1 : S = D_1(\gamma) - \sum_{i=1}^{n-1} r_i + u_1v_1$.

 $(M_2 + \sum_{j=3}^n u_j v_j - r_2) \mod N_2 = (\sum_{j=2}^n u_j v_j) \mod N_2$. As $\sum_{j=2}^n u_j v_j < (n-1)B^2$, by (5) for i = 2, we have $S_2 = \sum_{j=2}^n u_j v_j \in \mathbb{N}$.

This shows that the $DSDP_n$ protocol of Algorithm 4 can be implemented with a Paillier-like underlying cryptosystem, provided that the successive players have increasing modulo for their public keys.

Theorem 6. Under the bounds (3), and under Hypothesis (4) with a shared modulus underlying cipher, or under Hypothesis (5) with a Paillier-like underlying cipher, the $DSDP_n$ protocol of Algorithm 4 is correct. It requires O(n) communications and O(n) encryption and decryption operations.

Proof. First, each player sends his ciphered entry to P_1 , then homomorphically added to random values, r_i . Then, P_i $(i \ge 2)$ deciphers the message received by P_{i-1} into Δ_i . By induction, we obtain $\Delta_i = \sum_{k=2}^i u_k v_k + r_k$. This value is then re-enciphered with next player's key and the next player share is homomorphically added. Finally, P_1 just has to remove all the added randomness to obtain $S = \Delta_n - \sum_{i=2}^n r_i + u_1 v_1 = \sum_{i=1}^n u_i v_i$. For the complexity, the protocol needs n-1 encryptions and communications for the c_i ; 2(n-1) homomorphic operations on ciphers and n-1 communications for the α_i ; n-1 decryptions for the Δ_i ; n-1 encryptions, homomorphic operations and communications for the β_i ; and finally one encryption and one communication for γ . Then P_1 needs O(n) operations to recover S.

6 SECURITY OF DSDP

We study the security of $DSDP_n$ using both mathematical proofs and automated verifications. We first demonstrate the security of the protocol for *semi-honest* adversaries. Then we incrementally build its security helped by attacks found by ProVerif, an automatic verification tool for cryptographic protocols.

6.1 Security Proofs

The standard security definition in MPC models [23] covers actually many security issues, such as correctness, inputs independence, privacy, etc. We first prove that under this settings, computation of the dot product is safe.

Lemma 7. For $n \ge 3$, the output obtained after computing a dot product where one player owns complete vector U, and where each coefficient v_i of the second vector V is owned by the player P_i , is safe.

Proof. After executing $DSDP_n$ with $n \ge 3$, P_1 received the dot product of U and V. Therefore, it owns only one equation containing (n-1) unknown values (coefficients from v_2 to v_n). Then, he cannot deduce other players' private inputs.

Then, proving the security relies on a comparison between a real-world protocol execution and an ideal one. The latter involves an hypothetical trusted third party (*TTP*) which, knowing only the players' private inputs, returns the correct result to the correct players. The protocol is considered secure if the players' views in the ideal case cannot be distinguished from the real ones. Views of a player P_i (denoted $View_{P_i}$) are defined as distributions containing: the players' inputs (including random values), the messages received during a protocol execution and the outputs. The construction of the corrupted players' view in the ideal world is made by an algorithm called *Simulator*.

Definition 8. In the presence of a set C of semi-honest adversaries with inputs set X_C , a protocol Π securely computes $f : ([0,1]^*)^m \to ([0,1]^*)^m$ (and f_C denotes the outputs of f for each adversaries in C) if there exists a probabilistic polynomial-time algorithm Sim, such that: $\{Sim(C, \{X_C\}, f_C(X))\}_{X \in ([0,1]^*)^m}$ is computationally indistinguishable from $\{C, \{View_P^{\Pi}\}_{P_i \in C}\}$.

For $DSDP_n$, it is secure only if C is reduced to a singleton, *i.e.* if only one player is corrupted.

Lemma 9. By assuming the semantic security of the cryptosystem E, for $n \ge 3$, $DSPD_n$ is secure against one semi-honest adversary.

Proof. We assume that the underlying cryptosystem E is semantically secure (IND-CPA secure). First, we suppose that only P_1 is corrupted. His view, in a real execution of the protocol, is $View_{P_1} = \{U, R, \gamma, S, A, B, C\}$, where $U = \{u_i\}_{1 \le i \le n}$, $R = \{r_i\}_{1 \le i \le n}$, $A = \{\alpha_i\}_{2 \le i \le n}$, $B = \{\beta_i\}_{3 \le i \le n-1}$ and $C = \{c_i\}_{2 \le i \le n}$. Now, Sim₁ is the simulator for P_1 in the ideal case, where a simulated value x is denoted x': by definition, P_1 's private entries (vectors U and R) are directly accessible to Sim_1 , along with the output S, sent by the TTP. Sim_1 starts by generating n-2 random values, and then ciphers them using the corresponding public keys: this simulates the c'_i values. Then, using the provided r_i and u_i with the associated c'_i and P_i 's public key, Sim_1 computes: $\alpha'_i = c'^{u_i}_i * E_i(r_i), 2 \le i \le n$. Next, the simulation of B' is done by ciphering random values with the appropriate public key. The γ' value is computed using R along with the protocol output S: $\gamma' = E_1(S + \sum_{i=1}^{n-2} r_i + u_1v_1)$. In the end, the simulator view is $View_{Sim_1} = \{U, R, \gamma', S, A', B', C'\}$. If an adversary is able to distinguish any ciphered values (*e.g.* C' from C and thus A' from A), hence he is able to break the semantic security of the underlying cryptographic protocol. This is assumed impossible. Moreover, since the remaining values are computed as in a real execution, P_1 is not able to distinguish $View_{P_1}$ from $View_{Sim_1}$. Second, we suppose that a player P_i , $i \ge 2$ is corrupted and denote by Simi the simulator in this case. Since the role played by each participant is generic, (except for P_n , which only differs by his computation of γ instead of β_{n+1}), the simulators are easily adaptable. During a real protocol execution, the view of P_i is $View_{P_i} = \{v_i, A, B, C, \gamma, \Delta_i\}$. Simulating the values also known to P_1 is similar, up to the used keys. Hence, the simulation of A', B', γ', C' (except c_i) is made by ciphering random values using the adequate public key. c_i is ciphered using v_i and the public key of P_i . For Δ'_i , the simulator Sim_i has to forward the random value previously chosen to be ciphered as α_i . Indistinguishability is based on the semantic security of E (for A, B, C and γ) and on the randomness added by P_1 (and thus unknown by P_i). Then, Δ'_i is computationally indistinguishable from the real Δ_i . Hence, $View_{P_i}$ and $View_{S_i}$ are indistinguishable and $DSDP_n$ is secure against one semi-honest adversary.

6.2 Automated Verification

Alongside mathematical proofs, we use an automatic protocol verification tool to analyze the security of the protocol. Among existing tools, we use ProVerif [7, 8]. It allows users to add their own equational theories to model a large class of protocols. In our case, we model properties of the underlying cryptosystem including addition and multiplication. Sadly, verification of protocol in presence of homomorphic function over abelian groups theory has been proven undecidable [11]. Moreover, as showed in [22], some equational theories such as Exclusive-Or can already outspace the tool's capacities. Thus we have to provide adapted equational theories to be able to obtain results with the tool. We modeled the application of Pailler's or shared modulus encryption properties on α_i messages that Bob receives as follows:

(i). $\forall u, v, r, k, bob(E_k(r), u, E_k(v)) = E_k(uv+r)$

This property allows Bob to obtain $u_2v_2 + r_2$ from α_2 . This also allows an intruder to simulate such calculus and impersonate Bob. We also model:

(ii). β_3 by $\forall u, v, r, x, y, z, k$, charlie $(E_k(uv+r), E_k(xy+z)) = E_k(uv+xy+r+z)$

(iii). β_4 by $\forall u, v, r, x, y, z, a, b, c, k, dave(E_k(uv + xy + r + z), E_k(ab + c)) = E_k(uv + xy + ab + r + z + c)$

In the following, we use ProVerif to prove the security of our protocols under the abstraction of the functionalities given in our equational theory. ProVerif discovers some attacks in presence of active intruder. We then propose some countermeasures. The limits of ProVerif are reached and it does not terminate. The associated source files are available in a web-site: *http://matmuldistrib.forge.imag.fr*

Intruder(Alice)
Bob Charlie

$$\begin{array}{c} \overbrace{c_2 = E_{pubB}(v_2)} \\
\alpha_2 = c_2^{u_1} * E_{pubB}(r_I) \\
x_3 = E_{pubC}(v_I) \\
\alpha_3 = x_3^{u_1'} * E_{pubC}(r_I') \\
\overbrace{\Delta_2 = D_{privB}(\alpha_2)} \\
& \overbrace{\Delta_3 = D_{privC}(\beta_3)} \\
& \lbrace \text{now } \Delta_3 \text{ is } (v_1u_1' + r_1') + (v_2u_1 + r_I) \rbrace \\
\xrightarrow{\gamma = E_{pubA}(\Delta_3)} \\
v_2 = (D_{privA}(\gamma) - v_1u_1' - r_I - r_1')u_1^{-1}
\end{array}$$

Figure 2: Attack on the secrecy of v_2

Analysis in case of a passive adversary. Using these equational theories on the protocol described in Figure 1, we verify it in presence of a passive intruder. Such adversary is able to observe all the traffic of the protocol and tries to deduce secret information of the messages. This corresponds to a ProVerif intruder that only listens to the network and does not send any message. By default, this intruder does not possess the private key of any agent and thus does not belong to the protocol. To model a *semi-honest* adversary as defined in Section 2, we just give secret keys of honest participants to the passive intruder knowledge in ProVerif. Then the tool proves that all secret terms cannot be learn by the intruder for any combinations of leaked key. This confirms the proofs given in Section 6.1 against the *semi-honest* adversaries.

Analysis in case of malicious adversary. The *malicious* adversary described in Section 2 is an active intruder that controls the network and knows a private key of a compromised honest participant. Modeling this adversary in ProVerif, we are able to spot the two following attacks and give some countermeasures:

(i) Only the key of Alice is compromised and the countermeasure uses proofs of knowledge.

(ii) Only the key of Charlie is compromised and the countermeasure uses signatures.

In the rest of the section, we present these two points. In the Section 7.2, we also give a solution called *random ring* for the case where both keys of Alice and Charlie are compromised.

(i) The key of Alice is compromised. An attack on the secrecy of v_2 , the secret generated by Bob, is then presented in Figure 2.

The malicious adversary usurps Alice and replaces all the α_i messages, arriving from the other agents, with one message she generated, except one message, denoted c_2 in Figure 2. He lets the protocol end normally and obtains a term where only v_2 is unknown. He learns v_2 . If the key of Alice (P_1) is compromised, ProVerif also finds an attack on any of the other players secrecy. Suppose, w.l.o.g, that P_2 is the target, P_1 replaces each α_i except α_2 by ciphers $E_i(x_i)$ where x_i are known to him. $x_i = 0$ could do for instance ($x_i = 0v_i + r_i$ also), since after completion of the protocol, P_1 learns $u_2v_2 + r_2 + \sum_{i=3}^n x_i$, where the u_i and r_i are known to him. Therefore, P_1 learns v_2 . Note also that similarly, for instance, $\alpha_2 = 1v_2 + 0$ and $x_3 = v_3$ could also reveal v_2 to P_3 . Counter measure: this attack, and more generally attacks on the form of the α_i can be counteracted by zero-knowledge proofs of knowledge. P_1 has to prove to the other players that α_i is a non trivial affine transform of their secret v_i . For this we use a variant of a proof of knowledge of a discrete logarithm [9] given in Figure 3.

In the Protocol 4, this proof of a non trivial affine transform applies as is to α_2 with $\mu_2 = g^{\mu_2}$, $\rho_2 = g^{r_2}$ so that



Figure 3: Proof of a non trivial affine transform

the check of P_2 is $\delta_2 = g^{\Delta_2} \stackrel{?}{=} \mu_2^{v_2} \rho_2$. Differently, for the subsequent players, the $\delta_{i-1} = g^{\Delta_{i-1}}$ used to test must be forwarded: indeed the subsequent players have to check in line 10 that $\Delta_i = u_i v_i + r_i + \Delta_{i-1}$. Thus with P_1 providing $\mu_i = g^{u_i}$, $\rho_i = g^{r_i}$ and P_{i-1} providing δ_{i-1} , the check of player P_i ends with $\delta_i = g^{\Delta_i} \stackrel{?}{=} \mu_i^{v_i} \rho_i \delta_{i-1}$. As for proofs of knowledge of discrete logarithm, secrecy of our proof of non trivial affine transform is guaranteed as long as the discrete logarithm is difficult. The overhead in the protocol, in terms of communications, is to triple the size of the messages from P_1 to P_i , with α_i growing to $(\alpha_i, \mu_i, \rho_i)$, and to double the size of the messages from P_i to P_{i+1} , with β_i growing to (β_i, δ_i) . In terms of computations, it is also a neglectible linear global overhead.

(*ii*) The key of Charlie is compromised. There ProVerif finds another attack on the secrecy of v_2 . This time the key of Charlie is compromised and the malicious adversary blocks all communications to and from Alice who is honest. The adversary performs the same manipulation on the α_i terms which are directly sent to Bob. Thus, this attack becomes feasible since the adversary knows the terms u_2 , u_3 , r_2 , r_3 and v_3 that he generated and $\Delta_3 = (v_2u_2 + r_2) + (v_3u_3 + r_3)$ using the private key of Charlie. Such an attack relies on the fact that Bob has no way to verify if the message he receives from Alice has really been sent by Alice. This can be avoided using cryptographic signatures.

This attack can be generalized to any number of participants. The attack needs the adversary to know the key of Alice (since she is the only one to know the u_i and r_i values thanks to the signatures). Then, to obtain the secret value of a participant P_i , the key of participants P_{i-1} and P_{i+1} are also needed:

(i). P_{i-1} knows $\Delta_{i-1} = (u_2v_2 + \dots + u_{i-1}v_{i-1} + r_2 + \dots + r_{i-1}).$

(ii). P_{i+1} knows $\Delta_{i+1} = (u_2v_2 + \dots + u_{i-1}v_{i-1} + u_iv_i + u_{i+1}v_{i+1} + r_2 + \dots + r_{i-1} + r_i + r_{i+1}).$

Thus, by simplifying Δ_{i-1} and Δ_{i+1} , the malicious adversary obtains $u_iv_i + u_{i+1}v_{i+1} + r_i + r_{i+1}$ where he can remove u_{i+1} , v_{i+1} , r_i , r_{i+1} and u_i to obtain v_i . For more than three participants, we see in Section 7.2 that these kinds of threats can be diminished if the protocol is replayed several times in random orders.

7 PARALLEL APPROACH

In order to speed up the overall process, we show that we can cut each dot-product into blocks of 2 or 3 coefficients. On the one hand, the overall volume of communications is unchanged, while the number of rounds is reduced from n to a maximum of 5. On the other hand, semantic security is dropped, but we will see at the end of this section that by simply repeating the protocol with a wiretap mask it is possible to make the probability of breaking the protocol negligible.

An application of the $DSDP_n$ protocol is the computation of matrix multiplication. In this case, instead of knowing one vector, each player P_i owns two rows, A_i and B_i , one of each $n \times n$ matrices A and B. At the end,

each P_i learns a row C_i of the matrix C = AB. In order to compute the matrix product, it is therefore natural to parallelize $DSDP_n$: each dot-product is cut into blocks of 2 or 3 coefficients. Indeed, scalar product between three players (resp. four) involves two (resp. three) new coefficients in addition to the ones already known by P_i . For P_1 , the idea is to call $DSDP_3$ on the coefficients u_1, v_1 and u_2, u_3 of P_1 , and v_2, v_3 of P_2 and P_3 . Then P_1 knows $s = u_1v_1 + u_2v_2 + u_3v_3$. P_1 can then continue the protocol with P_4 and P_5 , using (s, 1) as his first coefficient and u_4, u_5 to be combined with v_4, v_5 , etc. P_1 can also launch the computations in parallel. Then P_1 adds his share u_1v_1 only after all the computations. For this it is sufficient to modify line 13 of $DSDP_n$ as: $P_1 : S = D_1(\gamma) - \sum_{i=1}^{n-1} r_i$. This is given as the $ESDP_n$ protocol variant in Algorithm 10.

Algorithm 10 ESDP_n Protocol: External Secure Dot-Product of size n

Require: n + 1 players, P_1 knows a coefficient vector $U \in \mathbb{F}^n$, each P_i knows components v_{i-1} of $V \in \mathbb{F}^n$, for i = 2...n + 1. **Ensure:** P_1 knows $S = U^T V$.

return $DSDP_{n+1}(P_1 \dots P_{n+1}, [0, U], [0, V]).$

7.1 Partition in Pairs or Triples

Depending on the parity of *n*, and since gcd(2,3) = 1, calls to $ESDP_2$ and $ESDP_3$ are sufficient to cover all possible dot-product cases, as shown in protocol $PDSMM_n$ of Algorithm 11. The protocol is cut in two parts. The loop allows us to go all over coefficients by block of size 2. In the case where *n* is even, a block of 3 coefficients is treated with an instance of $ESDP_3$. In terms of efficiency and depending on the parity of *n*, $ESDP_2$ is called $\frac{n-1}{2}$ or $\frac{n}{2} - 2$ times, and $ESDP_3$ is called 0 or 1 times.

```
Algorithm 11 PDSMM<sub>n</sub> Protocol: Parallel Distributed and Secure Matrix Multiplication
Require: n players, each player P_i knows rows A_i and B_i of two n \times n matrices A, B.
Ensure: Each player P_i knows row i of C = AB.
  1: for Each row: i=1 ... n do
         for Each column: j=1 ... n do
  2:
  3:
            s \leftarrow a_{i,i}b_{i,j}
            if n is even then
  4:
               k_1 \leftarrow (i-1) \mod n+1; k_2 \leftarrow (i-2) \mod n+1; k_3 \leftarrow (i-3) \mod n+1;
  5:
               s \leftarrow s + ESDP_3(P_i, [P_{k_3}, P_{k_2}, P_{k_1}], [a_{i,k_3}, a_{i,k_2}, a_{i,k_1}], [b_{k_3,j}, b_{k_2,j}, b_{k_1,j}])
  6:
               t \leftarrow \frac{n-4}{2}
  7:
            else
  8:
            t \leftarrow \frac{n-1}{2}<br/>for h = 1 \dots t do
  9.
10:
               k_1 \leftarrow (i+2h-1) \mod n+1; k_2 \leftarrow (i+2h) \mod n+1;
11:
12:
               s \leftarrow s + ESDP_2(P_i, [P_{k_1}, P_{k_2}], [a_{i,k_1}, a_{i,k_2}], [b_{k_1,j}, b_{k_2,j}])
13:
            c_{i,j} \leftarrow s
```

Theorem 12. The $PDSMM_n$ Protocol in Algorithm 11 is correct. It runs in less than 5 parallel communication rounds.

Proof. Correctness means that at the end, each P_i has learnt row C_i of C = AB. Since the protocol is applied on each rows and columns, let us show that for a row *i* and a column *j*, Algorithm 11 gives the coefficient c_{ij} such that $c_{ij} = \sum_{k=1}^{n} a_{ik} * b_{kj}$. First, the k_i coefficients are just the values $1 \dots (i-1)$ and $(i+1) \dots n$ in order. Then, the result of any $ESDP_2$ step is $a_{i,k_1}b_{k_1,j} + a_{i,k_2}b_{k_2,j}$ and the result of the potential $ESDP_3$ step is $a_{i,k_3}b_{k_3,j} + a_{i,k_2}b_{k_2,j} + a_{i,k_1}b_{k_1,j}$. Therefore accumulating them in addition of $a_{i,i} * b_{i,j}$ produces as expected $c_{ij} = \sum_{k=1}^{n} a_{ik} * b_{kj}$.

Now for the number of rounds, for all *i* and *j*, all the *ESDP* calls are independent. Therefore, if each player can simultaneously send and receive multiple data we have that: in parallel, *ESDP*₂, like *DSDP*₃ in Figure 1, requires 4 rounds with a constant number of operations: one round for the c_i , one round for the α_i , one round for β_3 and one round for γ . As shown in Algorithm 4, *ESDP*₃, like *DSDP*₄, requires only a single additional round for β_4 .

7.2 Random Ring Order Mitigation

We have previously seen that if the first player of a dot-product cooperates with the third one she can always recover the second player private value. If the first player cooperates with two well placed players she can recover the private value of a player in between. In the trust evaluation setting every malicious player plays the role of the first player in its row and therefore as soon as there is a collaboration, there is a risk of leakage. To mitigate this cooperation risk, our idea is to repeat the dot product protocol in random orders, except for the first player. To access a given private value, the malicious adversaries have to be well placed in *every* occurrence of the protocol. Therefore if their placement is chosen uniformly at random the probability that they recover some private value diminishes with the number of occurrences. In practice, they use a pseudo, but unpredictable, random generator to decide their placement: as each of them has to know their placement, they can for instance use a cryptographic hash function seeded with the alphabetical list of the players distinguished names, with the date of the day and with random values published by each of the players. We detail the overall procedure only for one dot-product, within the *PDSMM_n* protocol. Each player except the first one masks his coefficient *v* as in a simple wiretap channel [25], as sketched in Algorithm 13.

Algorithm 13 Wiretap repetition of the dot-product

- 1: The players agree on *d* occurrences.
- 2: Each player computes his placement order in each occurrence of the protocol from the cryptographic hash function.
- 3a: With a shared modulus cryptosystem, the players should share a common modulo *M* satisfying Hypothesis (4). In the first occurrence, each player P_j then masks his private input coefficient v_j with d-1 random values $\lambda_{j,i} \in \mathbb{Z}/M\mathbb{Z}$: $v_j - \sum_{i=2}^d \lambda_{j,i}$.
- 3b: With a Paillier-like cryptosystem, the players choose their moduli according to Hypothesis (5), where B^2 is replaced by dB^2 , in groups of size n = 4 (the requirements of (5) on the moduli are somewhat sequential, but can be satisfied independently if each modulo is chosen in a distinct interval larger than $3dB^2$). Then, in the first occurrence, each player P_j masks his private input coefficient v_j with d 1 random values $0 \le \lambda_{j,i} < B$: $v_j + \sum_{i=2}^{d} (B \lambda_{j,i}) < dB$.
- 4: Then for each subsequent occurrence, each player replaces its coefficient by one of the $\lambda_{i,i}$.
- 5: In the end, the first player has gathered d dot-products and just needs to sum them in order to recover the correct one.

Theorem 14. Algorithm 13 correctly allows the first player to compute the dot-product.

Proof. First, in a shared modulus setting, after the first occurrence, Alice (P_1) gets $S_1 = \sum_{j=2}^n u_j (v_j - \sum_{i=2}^d \lambda_{j,i})$. Then in the following occurrences, Alice gets $S_i = \sum_{j=2}^n u_j \lambda_{j,i}$. Finally she computes $\sum_{i=1}^d S_i = \sum_{j=2}^n u_j v_j$. Second, similarly, in a Paillier-like setting, after the first occurrence, Alice recovers $S_1 = \sum_{j=2}^n u_j (v_j + \sum_{i=2}^d (B - \lambda_{j,i}))$. Then in the following occurrences, Alice gets $S_i = \sum_{j=2}^n u_j \lambda_{j,i}$. Finally she computes $\sum_{i=1}^d S_i - (d-1)B(\sum_{j=2}^n u_j) = \sum_{j=2}^n u_j (v_j + (d-1)B) - (d-1)Bu_j = \sum_{j=2}^n u_j v_j$.

We give now the probability of avoiding attacks in the case when n = 2t + 1, but the probability in the even case should be close.

Theorem 15. Consider n = 2t + 1 players, grouped by 3, of which $k \le n - 2$ are malicious and cooperating, including the first one Alice. Then, it is on average sufficient to run Algorithm 13 with $d \le 2\ln\left(\min\{k-1, n-k, \frac{n-1}{2}\}\right)\left(1 + \frac{k-1}{n-k-1}\right)$ occurrences, to prevent the malicious players from recovering any private input of the non malicious ones.

Proof. The idea is that for a given private input of a non malicious player Bob, to be revealed to Alice, Bob needs to be placed between cooperating malicious adversaries *at each occurrence* of the protocol. If there is only one non malicious player, then nothing can be done to protect him. If there is 2 non malicious, they are safe if they are together one time, this happens with probability $\frac{1}{n-2}$, and thus on average after n-2 occurrences. Otherwise, *PDSMM_n* uses $t = \frac{n-1}{2}$ groups of 3, including Alice. Thus, each time a group is formed with one malicious and one non malicious other players, Alice can learn the private value of the non malicious player. Now, after any occurrence, the number *a* of attacked players is less than the number of malicious players minus 1 (for Alice) and obviously less than the number of non malicious players: $0 \le a < \min\{k-1, n-k\}$. Thus let b = k - 1 - a and c = n - k - a. In the next occurrence, the probability of saving at least one more non malicious is $\frac{a(a-1+c)(n-3)!}{(n-1)!} \frac{n-1}{2} = \frac{a(a-1+c)}{2(n-2)} = \frac{a(n-k-1)}{2(n-2)}$, so that the average number of occurrences to realize this is $\mathbb{E}_{n,k}(a) = \frac{2(n-2)}{a(n-k-1)}$. Thus, $T_{n,k}(a)$, the average number of occurrences to save all the non malicious players,

satisfies $T_{n,k}(a) \leq \mathbb{E}_{n,k}(a) + T_{n,k}(a-1) \leq \sum_{i=a}^{3} E_{n,k}(i) + T_{n,k}(2) = (\sum_{i=a}^{3} \frac{1}{i}) \frac{2(n-2)}{n-k-1} + T_{n,k}(2)$. With 2 attacked and *c* saved, $T_{n,k=n-c-2}(2) = \frac{n-2}{c+1}$ so that $T_{n,k}(a) \leq (H_a - \frac{3}{2}) \frac{2(n-2)}{n-k-1} + \frac{n-2}{n-k-1}$, where bounds on the Harmonic numbers give $H_a \leq \ln a$ (see, *e.g.*, [3]) and since $a \leq k-1$ and $a \leq n-k$, this shows also that $2a \leq n-1$. Therefore, $T_{n,k}(a) \leq 2\ln \left(\min\{k-1,n-k,\frac{n-1}{2}\}\right) \frac{n-2}{n-k-1}$.

For instance, if k, the number of malicious insiders, is less than the number of non malicious ones, the number of repetitions sufficient to prevent any attack is on average bounded by $O(\log k)$. To guaranty a probability of failure less than ε , one needs to consider also the worst case. There, we can have k = n - 2 malicious adversaries and the number of repetitions can grow to $n \ln(1/\varepsilon)$:

Proposition 16. With n = 2t + 1, the number d of random ring repetitions of Algorithm 13 to make the probability of breaking the protocol lower than ε satisfies $d < n \ln(1/\varepsilon)$ in the worst case.

Proof. There are at least 2 non-malicious players, otherwise the dot-product reveals the secrets in any case. Any given non-malicious player is safe from any attacks if in at least one repetition he was paired with another non-malicious player. In the worst case, k = n - 2 players are malicious and the latter event arises with probability $(1 - \frac{1}{n-1})^d$ for *d* repetitions. If $d \ge n (\ln (\varepsilon^{-1}))$, then $d > (n-1)(-\ln \varepsilon) > \frac{\ln \varepsilon}{\ln(1 - \frac{1}{n-1})}$, which shows that $(1 - \frac{1}{n-1})^d < \varepsilon$.

Overall, the wiretap variant of Algorithm 13 can guaranty any security, at the cost of repeating the protocol. As the number of repetitions is fixed at the beginning by all the players, all these repetitions can occur in parallel. Therefore, the overall volume of communication is multiplied by the number of repetitions, while the number of rounds remains constant. This is summarized in Table 1 and Figure 4, for the average (Theorem 15) and worst (Proposition 16) cases of Algorithm 13, and where the protocols of the previous sections are also compared.

Volume Rounds Protocol Paillier MPWP $O(n^3)$ O(n)Х $n^{2+o(1)}$ $P-MPWP(\S 4)$ O(n)1 $\frac{n^{2+o(1)}\ln\left(\frac{1}{\varepsilon}\right)}{n^{1+o(1)}}$ Alg. 13 (Wiretap) 5 Alg. 4 (DSDP_n) O(n) $n^{1+o(1)}$ Alg. 11 (PDSMM $_n$) 5 1 $n^{1+o(1)}$ Alg. 13 (Average) 5

 Table 1: Communication complexities

On the one hand, we see in Figure 4 that quadratic protocols, with homomorphic encryption, are not usable for a realistic large group of players (trust aggregation could be used for instance by certificate authorities, and there are several hundreds of those in current operating systems or web browsers). On the other hand, quasi linear time protocols present good performance, while preserving some reasonable security properties: the average wiretap curve is on average sufficient to prevent any attack and still has a quasi linear asymptotic behavior. The steps in this curve are the rounding of log(n) to the next integer and correspond to one more random ring wiretap round.

8 CONCLUSION: MPC OF TRUST

We now come back to the aggregation of trust. As shown in Section 3, the first step is to reduce the computation to that of dot-products. We show how to fully adapt the protocol of Section 5 to the evaluation of trust values with parallel and sequential aggregations:

Corollary 17. The protocol DSDP of Algorithm 4 can be applied on trust values, provided that the random values r_i are invertible for \mathbf{H} .

Proof. • $u_i, v_i, r_i, c_i, \alpha_i, \beta_i, \Delta_i, \gamma$ are now couples;

- Encryption and decryption $(E(v_i), D(\beta_i), E(\Delta_i), E(\gamma), \text{ etc.})$ now apply on couples, using the morphism $E(\langle a, b \rangle) = \langle E(a), E(b) \rangle$;
- α_i is $E((u_i \bigstar v_i) \bigstar r_i) = \text{Add}(\text{Mul}(E(v_i); u_i); r_i)$, and can still be computed by P_1 , since $c_i = E(v_i)$ and u_i and r_i are known to him;
- Similarly, $\beta_i = E(\alpha_i \bigstar \Delta_i) = \text{Add}(E(\alpha_i); \Delta_i).$
- Finally, as \bigstar is commutative, S is recovered by adding the inverses for \bigstar of the r_i .



Figure 4: Quadratic and linear protocols timings

From [15, Definition 11], the *d*-aggregation of trust is a dot-product but slightly modified to *not* include the value u_1v_1 . Therefore at line 3, in the protocol of Algorithm 11, it suffices to set *s* to the neutral element of \mathbf{x} (that is $s \leftarrow \langle 0, 1 \rangle$, instead of $s \leftarrow a_{i,j}b_{i,j}$).

There remains to encode trust values that are proportions, in [0, 1], into $\mathbb{D} = \mathbb{Z}/N\mathbb{Z}$. With *n* participants, we use a fixed precision 2^{-p} such that $2^{n(2p+1)} < N \le 2^{n(2(p+1)+1)}$ and round the trust coefficients to $\lfloor x2^p \rfloor \mod N$ from $[0, 1] \to \mathbb{D}$. Then the dot-product can be bounded as follows:

Lemma 18. If each coefficient of the u_i and v_i are between 0 and $2^p - 1$, then the coefficients of $S = \mathbf{A}_{i=1}^n (u_i \bigstar v_i)$ are bounded by $2^{n(2p+1)}$ in absolute value.

Proof. For all u, v, the coefficients of $(u \neq v)$ are between 0 and $(2^p - 1)(2^p - 1) + (2^p - 1)(2^p - 1) = 2^{2p+1} - 2^{p+2} + 2 < 2^{2p+1} - 1$ for p a positive integer. Then, by induction, when aggregating k of those with $\not =$, the absolute values of the coefficients remain less than $2^{k(2p+1)} - 1$.

Therefore, with N an 2048 bits modulus and $n \le 4$ in the *ESDP* protocols of Algorithm 11, Lemma 18 allows a precision close to $2^{-255} \approx 10^{-77}$.

In conclusion, we provide an efficient and secure protocol $DSDP_n$ to securely compute dot products (against semi-honest adversary) in the MPC model, with unsual data division between *n* players. It can be used to perform a private matrix multiplication and also be adapted to securely compute trust aggregation between players.

References

- [1] Vulnerabilities of decentralized additive reputation systems regarding the privacy of individual votes. *Wireless Personal Communications*, 66(3):559–575, 2012. doi:10.1007/s11277-012-0734-z.
- [2] Artak Amirbekyan and Vladimir Estivill-Castro. A new efficient privacy-preserving scalar product protocol. In AusDM 2007, volume 70 of CRPIT, pages 209–214, 2007. URL: http://crpit.com/ confpapers/CRPITV70Amirbekyan.pdf.
- [3] Necdet Batir. Sharp bounds for the psi function and harmonic numbers. *Mathematical inequalities and applications*, 14(4), 2011. doi:10.7153/mia-14-77.

- [4] Michael Ben-Or, Shafi Goldwasser, and Avi Wigderson. Completeness theorems for non-cryptographic fault-tolerant distributed computation. STOC'88, pages 1–10. ACM, 1988. URL: http://doi.acm.org/ 10.1145/62212.62213, doi:10.1145/62212.62213.
- [5] Josh Benaloh. Dense probabilistic encryption. In First Annual Workshop on Selected Areas in Cryptography, pages 120–128, Kingston, ON, May 1994. URL: http://sacworkshop.org/proc/SAC_94_006. pdf.
- [6] Rikke Bendlin, Ivan Damgård, Claudio Orlandi, and Sarah Zakarias. Semi-homomorphic encryption and multiparty computation. In KennethG. Paterson, editor, *Advances in Cryptology – EUROCRYPT 2011*, volume 6632 of *Lecture Notes in Computer Science*, pages 169–188. Springer Berlin Heidelberg, 2011. URL: http://dx.doi.org/10.1007/978-3-642-20465-4_11, doi:10.1007/978-3-642-20465-4_ 11.
- [7] B. Blanchet. An efficient cryptographic protocol verifier based on prolog rules. In *Proc. CSFW'01*, pages 82–96. IEEE Comp. Soc. Press, 2001.
- [8] B. Blanchet. Cryptographic Protocol Verifier User Manual, 2004. URL: http://www.di.ens.fr/ ~blanchet/crypto/proverif-manual.ps.gz.
- [9] David Chaum, Jan-Hendrik Evertse, Jeroen van de Graaf, and René Peralta. Demonstrating possession of a discrete logarithm without revealing it. In Andrew M. Odlyzko, editor, Advances in Cryptology - CRYPTO '86, Santa Barbara, California, USA, 1986, Proceedings, volume 263 of Lecture Notes in Computer Science, pages 200–212. Springer, 1986. URL: http://dx.doi.org/10.1007/3-540-47721-7_14, doi:10.1007/3-540-47721-7_14.
- [10] Ivan Damgård, Valerio Pastro, Nigel Smart, and Sarah Zakarias. Multiparty computation from somewhat homomorphic encryption. In Reihaneh Safavi-Naini and Ran Canetti, editors, Advances in Cryptology – CRYPTO 2012, volume 7417 of Lecture Notes in Computer Science, pages 643–662. Springer Berlin Heidelberg, 2012. URL: http://dx.doi.org/10.1007/978-3-642-32009-5_38, doi:10. 1007/978-3-642-32009-5_38.
- [11] Stéphanie Delaune. An undecidability result for agh. *Theor. Comput. Sci.*, 368(1-2):161–167, December 2006. URL: http://dx.doi.org/10.1016/j.tcs.2006.08.018, doi:10.1016/j.tcs.2006.08.018.
- [12] Shlomi Dolev, Niv Gilboa, and Marina Kopeetsky. Computing multi-party trust privately: in O(n) time units sending one (possibly large) message at a time. In *Proceedings of the 2010 ACM Symposium on Applied Computing*, SAC '10, pages 1460–1465, New York, NY, USA, 2010. ACM.
- [13] Wenliang Du and M. J. Atallah. Privacy-preserving cooperative statistical analysis. In Proceedings of the 17th Annual Computer Security Applications Conference, ACSAC '01, pages 102–110, December 2001. doi:10.1109/ACSAC.2001.991526.
- [14] Wenliang Du and Zhijun Zhan. A practical approach to solve secure multi-party computation problems. In Proceedings of the 2002 Workshop on New Security Paradigms, NSPW '02, pages 127–135, New York, NY, USA, 2002. ACM. URL: http://doi.acm.org/10.1145/844102.844125, doi:10.1145/844102. 844125.
- [15] Jean-Guillaume Dumas and Hicham Hossayni. Matrix powers algorithm for trust evaluation in PKI architectures. In Audun Jøsang, Pierangela Samarati, and Marinella Petrocchi, editors, STM'2012, Proceedings of the eigth International Workshop on Security and Trust Management (co-ESORICS 2012), Pisa, Italy, volume 7783 of Lecture Notes in Computer Science, pages 129–144, September 2012. URL: http://hal.archives-ouvertes.fr/hal-00607478, doi:10.1007/978-3-642-38004-4_9.
- [16] Simon N. Foley, Wayne Mac Adams, and Barry O'Sullivan. Aggregating trust using triangular norms in the keynote trust management system. In Jorge Cuéllar, Javier Lopez, Gilles Barthe, and Alexander Pretschner, editors, Security and Trust Management - 6th International Workshop, STM 2010, Athens, Greece, September 23-24, 2010, Revised Selected Papers, volume 6710 of Lecture Notes in Computer Science, pages 100–115. Springer, 2010. URL: http://dx.doi.org/10.1007/978-3-642-22444-7_7, doi:10.1007/978-3-642-22444-7_7.
- [17] Laurent Fousse, Pascal Lafourcade, and Mohamed Alnuaimi. Benaloh's dense probabilistic encryption revisited. In Abderrahmane Nitaj and David Pointcheval, editors, *Progress in Cryptology - AFRICACRYPT* 2011 - 4th International Conference on Cryptology in Africa, Dakar, Senegal, July 5-7, 2011. Proceedings, volume 6737 of Lecture Notes in Computer Science, pages 348–362. Springer, 2011. URL: http://dx. doi.org/10.1007/978-3-642-21969-6_22, doi:10.1007/978-3-642-21969-6_22.
- [18] Bart Goethals, Sven Laur, Helger Lipmaa, and Taneli Mielikäinen. On private scalar product computation for privacy-preserving data mining. In Choon-sik Park and Seongtaek Chee, editors, *Information Security* and Cryptology ICISC 2004, volume 3506 of Lecture Notes in Computer Science, pages 104–120. Springer Berlin Heidelberg, 2005. URL: http://dx.doi.org/10.1007/11496618_9, doi:10.1007/11496618_ 9.

- [19] Ramanathan V. Guha, Ravi Kumar, Prabhakar Raghavan, and Andrew Tomkins. Propagation of trust and distrust. In Stuart I. Feldman, Mike Uretsky, Marc Najork, and Craig E. Wills, editors, *Proceedings of the* 13th international conference on World Wide Web, WWW 2004, New York, NY, USA, May 17-20, 2004, pages 403–412. ACM, 2004. URL: http://doi.acm.org/10.1145/988672.988727, doi:10.1145/ 988672.988727.
- [20] Jingwei Huang and David M. Nicol. A formal-semantics-based calculus of trust. *IEEE Internet Computing*, 14(5):38–46, 2010. URL: http://doi.ieeecomputersociety.org/10.1109/MIC.2010.83, doi:10. 1109/MIC.2010.83.
- [21] Audun Jøsang. Probabilistic logic under uncertainty. In Joachim Gudmundsson and C. Barry Jay, editors, Theory of Computing 2007. Proceedings of the Thirteenth Computing: The Australasian Theory Symposium (CATS2007). January 30 - Febuary 2, 2007, Ballarat, Victoria, Australia, Proceedings, volume 65 of CRPIT, pages 101–110. Australian Computer Society, 2007. URL: http://crpit.com/abstracts/ CRPITV65Josang.html.
- [22] Pascal Lafourcade and Maxime Puys. Performance evaluations of cryptographic protocols. verification tools dealing with algebraic properties. In *FPS 2015*, 2015.
- [23] Yehuda Lindell. Secure computation for privacy preserving data mining. In John Wang, editor, Encyclopedia of Data Warehousing and Mining, Second Edition (4 Volumes), pages 1747–1752. IGI Global, 2009. URL: http://www.igi-global.com/Bookstore/Chapter.aspx?TitleId=11054, doi: 10.4018/978-1-60566-010-3.
- [24] Payman Mohassel. Efficient and secure delegation of linear algebra. IACR Cryptology ePrint Archive, 2011:605, 2011. URL: http://eprint.iacr.org/2011/605.
- [25] Lawrence H. Ozarow and Aaron D. Wyner. Wire-tap channel II. In Thomas Beth, Norbert Cot, and Ingemar Ingemarsson, editors, *EUROCRYPT'84, Paris, France*, volume 209 of *LNCS*, pages 33–50. Springer, 1984. URL: http://dx.doi.org/10.1007/3-540-39757-4_5, doi:10.1007/3-540-39757-4_5.
- [26] Pascal Paillier. Public-key cryptosystems based on composite degree residuosity classes. In Jacques Stern, editor, Advances in Cryptology EUROCRYPT '99, International Conference on the Theory and Application of Cryptographic Techniques, Prague, Czech Republic, May 2-6, 1999, Proceeding, volume 1592 of Lecture Notes in Computer Science, pages 223–238. Springer, 1999. URL: http://dx.doi.org/10. 1007/3-540-48910-X_16, doi:10.1007/3-540-48910-X_16.
- [27] Adi Shamir. How to share a secret. Commun. ACM, 22(11):612–613, November 1979. URL: http: //doi.acm.org/10.1145/359168.359176, doi:10.1145/359168.359176.
- [28] I-Cheng Wang, Chih hao Shen, Tsan sheng Hsu, Churn-Chung Liao, Da-Wei Wang, and J. Zhan. Towards empirical aspects of secure scalar product. In *Information Security and Assurance, 2008. ISA 2008. International Conference on*, pages 573–578, April 2008. doi:10.1109/ISA.2008.78.
- [29] Andrew C. Yao. Protocols for secure computations. 2013 IEEE 54th Annual Symposium on Foundations of Computer Science, 0:160–164, 1982. doi:http://doi.ieeecomputersociety.org/10.1109/SFCS. 1982.88.