

## Advances in remote sensing of cultivated landscapes at LISAH

Denis Feurer, Cécile Gomez, Jean-Stéphane Bailly, Guillaume Coulouma, Philippe Lagacherie, Frédéric Jacob, Laurent Prevot, Damien D. Raclot

#### ► To cite this version:

Denis Feurer, Cécile Gomez, Jean-Stéphane Bailly, Guillaume Coulouma, Philippe Lagacherie, et al.. Advances in remote sensing of cultivated landscapes at LISAH. Journées CRITEX, EQUIPEX - Investissements d'Avenir, Jan 2016, Rennes, France. 2016. hal-01381254

#### HAL Id: hal-01381254 https://hal.science/hal-01381254v1

Submitted on 14 Oct 2016

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Distributed under a Creative Commons Attribution 4.0 International License

# Advances in remote sensing of cultivated landscapes at

**Abstract:** In order to propose new and sustainable methods for cultivated areas managment, the French INRA-IRD-Supagro laboratory for the study of Soil-Agrosystem-Hydrosystem Interactions (LISAH) develops tools for modelling fluxes (water, soils, solutes) based on a fine characterisation and observation of the landscape mosaics and of its dynamic (field limits, networks, structures, vegetation, agricultural practices, topography, etc.). Such observations require to develop innovative acquisition and processing methods. This poster presents somes of these methods concerning different scales and techniques.



**References :** Gomez, C., Lagacherie, P., & Bacha, S. (2012). Using Vis-NIR hyperspectral data to map topsoil properties over bare soils in the Cap-Bon Region, Tunisia. In B. Minasny, B. Malone, & A. B McBratney (Eds.), Digital Soil Assessment and Beyond (pp. 387–392).

properties with Vis-NIR hyperspectral covariates in the Cap Bon region (Tunisia). In B. Minasny, B Malone, & A. B. McBratney (Eds.) Digital Soil Assessments and Beyond (pp. 393–398).

Lagacherie, P., Sneep, A.-R., Gomez, C., Bacha, S., Coulouma, G., Hamrouni, M. H., & Mekki, I. (2013) Combining Vis–NIR hyperspectral imagery and legacy measured soil profiles to map subsurface soil properties in a Mediterranean area (Cap-Bon, Tunisia). Geoderma, 209–210(0), 168–176. doi:http://dx.doi.org/10.1016/j.geoderma.2013.06.005

# III. Gullies detection with THRS imagery

**Objective:** Exhaustive mapping of gullies for hydrological modelling

- **Approach :** > Contour detection from THRS satellite imagery
  - Filter combination and decision rules with ancillary data





References : Bailly, J.; Lagacherie, P.; Millier, C.; Puech, C. & Kosuth, P. (2008), 'Agrarian landscapes linear features detection from LiDAR: application to artificial drainage networks', International Journal of Remote Sensing 29(12), 3489-3508.

Bailly, J.; Levavasseur, F. & Lagacherie, P. (2011), 'A stochastic algorithm to reconstruct artificial drainage networks from incomplete remote sensing delineations', International Journal of Applied Earth Observation and Geoinformation 13, 853--862.

V. 3D modelling by photogrammetry and Structure-from-Motion (SfM)

**Objectives:** 

Attaining a decimeter to centimeter scale description of landscape features at the watershed scale **Approach :** 

**Reference :** Desprats J.F., Raclot D., Rousseau M., Cerdan O., Garcin M., Le Bissonnais Y., Ben Slimane A., Fouche J., Monfort-Climent D. (2013). Mapping linear erosion features using high and very high resolution satellite imagery. Land Degradation & Development, 24: 22-32. doi: 10.1002/ldr.1094.

# VI. Mapping evapotranspiration of vineyards

**Objective:** Mapping of vineyard daily evapotranspiration (ETR) over the Peyne catchment (65 km2)

**Approach :** 12 ETR maps produced from visible-NIR and thermal IR images (ASTER instrument, 90 m resolution) using two water stress indices : WDI (Moran et al., 1994) and S-SEBI (Roerink et al., 2000)

Lightweight platform (UAV); ultra high resolution

IV. Soil Crust Mapping

**Objective:** Monitoring of soil crust dynamics at the

crop scale

MERI

Mapping of soil surface characteristics

**Approach** :



Reference : C. Corbane, D. Raclot, F. Jacob, J. Albergel, P. Andrieux, Remote sensing of soil surface characteristics from a multiscale classification approach CATENA, Volume 75, Issue 3, 15 November 2008, Pages 308-318, ISSN 0341 8162, http://dx.doi.org/10.1016/j.catena.2008.07.009.



- Lightweight image acquisition : light platforms (kite) and consumer grade cameras
- High image redundancy and SfM approaches for processing



### **Results:**

Operationnal method of image acquisition and 3D processing which obtain allows to decimetric to centimetric DEM on areas up to several km<sup>2</sup>



Reference : Feurer, D.; El Maaoui, M. A.; Planchon, O.; Boussema, M. R. & Pierrot-Deseilligny, M. Kite-Borne photogrammetry for decimetric 3D mapping of several square kilometres areas Proceedings of IEEE 2015 International Geoscience and Remote Sensing Symposium (IGARSS'15), 2015

## VII. Mistigri mission design

**Objective:** Design of a high spatial and temporal resolution thermal satellite

#### **Approach :**







ETR Hydrus-1D (mm.day-1)

Reference : Galleguillos, M., Jacob, F., Prévot, L., Lagacherie, P. and French, A., Comparing two simplified models for inferring daily evapotranspiration from ASTER over a Mediterranean vineyard watershed. Remote Sensing of Environment, 2015, 6 (115), 1326-1340

ETR eddy covariance (mm.day-1)





Impact of the revisit time (1, 2, 5 days) on the availability of data (a:Rennes, b: Avignon). Impact of acquisition time (10, 12, and 14 h UTC) for Rennes (c) and Avignon (d)



and retrieved from evapotranspiration airborne hyperspectral scanner



Potential accessibility at ground in the case of (a) 1 satellite at 561 km or (b) 2 at 720 km





Simulation of different spectral configurations with 4 or 3 bands and different positions in the thermal infrared spectrum

**Results:** Having worked on the spectral sampling (bands, bands resolutions) the LISAH team proposed a spectral configuration allowing for a 1K accuracy in temperature estimation

Reference : Lagouarde, J.-P.; Bach, M.; Sobrino, J. A.; Boulet, G.; Briottet, X.; Cherchali, S.; Coudert, B.; Dadou, I.; Dedieu, G.; Gamet, P.; Hagolle, O.; Jacob, F.; Nerry, F.; Olioso, A.; Ottlé, C.; louis Roujean, J. & Fargant, G. The MISTIGRI thermal infrared project: scientific *objectives and mission specifications*. International Journal of Remote Sensing, 2013, 34, 3437-3466

Poster coordinated by Denis Feurer with the contributions of Gomez C., Bailly J.-S., Coulouma G., Lagacherie P., Jacob F., Prevot L. and Raclot D. Contact : denis.feurer@ird.fr, guillaume.coulouma@supagro.inra.fr