

# Coupling Modified Constitutive Relation Error, Model Reduction and Kalman filtering algorithms for Real-Time Parameters Identification

5th International Workshop on New Computational Methods for Inverse Problems

## Context

Dynamic Data Driven Application Systems (DDDAS) paradigm [4] is based on a continuous exchange between physical system and its numerical model in order to :

(i) Use observations data to identify and update model parameters


Inverse problem

(ii) Control system evolution according to criteria

Optimal control problem

Application example :

Damage evolution identification and control in composite structures [8].



## Mathematical representation

Dynamical system :

$$\begin{cases} \mathbf{u}^{(k+1)} = \mathcal{M}(\mathbf{u}^{(k)}) + \mathbf{e}_M \\ \mathbf{s}^{(k)} = \mathcal{H}(\mathbf{u}^{(k)}) + \mathbf{e}_S \end{cases}$$

$\mathbf{u}^{(k)} \in \mathbb{R}^n$  state vector at time  $t^{(k)}$

$\mathbf{s}^{(k)} \in \mathbb{R}^m$  observation vector at time  $t^{(k)}$

$\mathbf{e}_M \in \mathbb{R}^n$  model error assumed to be Gaussian white noise

$\mathbf{e}_S \in \mathbb{R}^m$  observation error assumed to be Gaussian white noise

$\mathcal{M} : \mathbb{R}^n \rightarrow \mathbb{R}^n$  model operator

$\mathcal{H} : \mathbb{R}^n \rightarrow \mathbb{R}^m$  observation operator

## Kalman filter based identification

Inverse problem resolution based on Kalman filtering [6] using non-linear formulation, here the Unscented Kalman Filter [5]. The idea is to define an expanded state vector  $\bar{\mathbf{u}}$  and associated dynamical system :

$$\begin{cases} \bar{\mathbf{u}}^{(k+1)} = \mathcal{M}(\bar{\mathbf{u}}^{(k)}) + \mathbf{e}_M \\ \mathbf{s}^{(k)} = \mathcal{H}(\bar{\mathbf{u}}^{(k)}) + \mathbf{e}_S \end{cases} \quad \text{with } \bar{\mathbf{u}}^{(k)} = \begin{bmatrix} \mathbf{u}^{(k)} \\ \mathbf{p}^{(k)} \end{bmatrix}$$

UKF idea is based on Unscented Transform which allows to reconstruct mean and covariance with sample of  $2 \cdot \dim(\bar{\mathbf{u}}) + 1$  points. But complexity is  $O(\dim(\bar{\mathbf{u}})^3)$

## Modified CRE

Modified Constitutive Relation Error [7] is based on energy fonctionnal (transient thermal case)

$$\mathcal{E}_m^2(u, \mathbf{q}; \mathbf{s}, \mathbf{p}) = \frac{1}{2} \int_T \int_\Omega (\mathbf{q} - \kappa \nabla u) \kappa^{-1} (\mathbf{q} - \kappa \nabla u) + \frac{1}{2(1-r)} \int_T \|\Pi u - \mathbf{s}\|^2$$

The identification problem can be formulated as, find  $\mathbf{p} \in \mathcal{P}$  such that;

$$\mathbf{p} = \underset{\xi \in \mathcal{P}}{\operatorname{argmin}} \min_{(u, \mathbf{q}) \in \mathcal{U} \times \mathcal{S}} \mathcal{E}_m^2(u, \mathbf{q}; \mathbf{s}, \xi)$$

Resolution using alternating minimization + fixed point algorithm

• Minimization according to  $\mathcal{U} \times \mathcal{S} \rightarrow (u_{ad}, \mathbf{q}_{ad})$  (coupled forward/backward problem in time)

• Minimization according to  $\mathcal{P} \rightarrow \mathbf{p}$  (gradient method)

## Modified Kalman Filter

The approach we propose, **Modified Kalman Filter** (MKF), is slightly similar to the approach proposed in [1]

$$\begin{cases} \mathbf{p}^{(k+1)} = \mathbf{p}^{(k)} + \mathbf{e}_P \\ \mathbf{s}^{(k)} = \mathcal{H}_m(\mathbf{p}^{(k)}, \mathbf{s}^{(k-1:k)}) + \mathbf{e}_S \end{cases}$$

with observation operator defined as follow :

$$\mathcal{H}_m(\mathbf{p}^{(k)}, \mathbf{s}^{(k-1:k)}) = \mathcal{H} \circ \text{mCRE}_1(\mathbf{p}^{(k)}, \mathbf{s}^{(k-1:k)})$$

projector

Admissible fields computation

**Advantages :**

1. Implementation, since the method is based on sampling points
2. Robustness, since the system state is computed as an admissible field according to mCRE

**Drawbacks :**

Computation time associated to the coupled forward/backward problem.

## Proper Generalized Decomposition

Proper Generalized Decomposition [3] based on :

- (i) Variable separation
- (ii) Parametric solution
- (iii) offline modes computation
- (iv) online solution evaluation

The incremental approach we consider involves that PGD decomposition must be on the following form :

$$\mathbf{u}^{(k)} \simeq \mathbf{u}_M(\mathbf{x}, t^{(k)}, \mathbf{p}, \mathbf{s}^{(k-1)}, \mathbf{s}^{(k)}, \mathbf{u}_0^{(k)})$$

$\mathbf{u}_0^{(k)}$  initial condition on  $I_t^{(k)} = [t^{(k-1)}, t^{(k)}]$ .

## Numerical results

### Problem setting

- parabolic PDE (transient thermal problem)
- Time-dependant Neumann Boundary Condition identification (example 1)
- Time-independant conductivity identification in multi-layer structure (example 2)

### Simulated observations


- (i) Solve direct problem with fine time discretization
- (ii) Extract values according to sensors placement and acquisition times (coarser than for resolution)
- (iii) Add Gaussian white noise

$$s_i^{(k)} = s_{i,exact}^{(k)} (1 + \mathcal{N}(0, \Sigma)) \quad \forall i = 1, \dots, m; \forall k$$



### Global identification strategy

- Offline** – compute PGD parametric solution
- Online** – identification process using MKF approach


### Example 1





space : 980 TRI3  
time : 100 time steps  
noise :  $\Sigma = 0.2$



### Example 2



space : 148 TRI3  
time : 100 time steps  
noise :  $\Sigma = 0.1$



## Conclusions

The strategy we propose, based on coupling between Unscented Kalman filter, modified Constitutive Relation Error and PGD reduced model offers :

- (i) more robustness to highly corrupted data
- (ii) a significant computation time-saving

## Future works

- (i) Extend Modified Kalman Filter approach coupled with PGD to field parameters identification
  - (a) adaptive mesh approach
  - (b) multiscale method
- (ii) Address full-fields measurements

## References

- [1] A. Alarcon, C. Bodel, M. Bonnet. *A coupled unscented Kalman filter and modified error in constitutive relation technique for structural dynamics identification*, Proc. EURO DYN, 2163-2168, 2011.
- [2] O. Allix, P. Feissel, H. Nguyen. *Identification strategy in the presence of corrupted measurements*, Engineering Computations, 487-504, 2005.
- [3] F. Chinesta, R. Keunings, A. Leygue. *The Proper Generalized Decomposition for advanced Numerical Simulations*, Springer, 2014.
- [4] F. Darema. *Dynamic Data Driven Applications Systems : A new paradigm for applications simulations and measurements*, Computational Science-ICCS 2004: 4th International Conference, Springer, 662-669, 2004.
- [5] S. Julier, J. Uhlmann., *A new extension of the kalman filter to nonlinear systems*, The 11th Int. Symposium on Aerospace/Defense Sensing and Simulation and Controls, 1996.
- [6] R. Kalman. *A new approach to linear filtering and prediction problems*, Journal of Basic Engineering, 35-45, 1960.
- [7] P. Ladevèze, D. Nedjar, M. Reynier. *Updating of finite element models using vibration tests*, AIAA Journal, 1485-1491, 1994.
- [8] E. Prudencio, P. Bauman, D. Faghghi, K. Ravi-Chandar, J. Oden. *A computational framework for dynamic data driven material damage control, based on bayesian inference and model selection*, International Journal for Numerical Methods in Engineering, 2014