



HAL
open science

Therapeutic target discovery using Boolean network attractors: improvements of kali

Arnaud Poret, Carito Guziolowski

► **To cite this version:**

Arnaud Poret, Carito Guziolowski. Therapeutic target discovery using Boolean network attractors: improvements of kali. 2017. hal-01395079v2

HAL Id: hal-01395079

<https://hal.science/hal-01395079v2>

Preprint submitted on 8 Nov 2017 (v2), last revised 8 Jan 2018 (v3)

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Distributed under a Creative Commons Attribution - NonCommercial - NoDerivatives 4.0 International License

Therapeutic target discovery using Boolean network attractors: improvements of kali

Arnaud Poret, Carito Guziolowski

November 8, 2017

Abstract

In a previous article, an algorithm for identifying therapeutic targets in Boolean networks modeling pathological mechanisms was introduced. In the present article, the improvements made on this algorithm, named kali, are described. These improvements are i) the possibility to work on asynchronous Boolean networks, ii) a finer assessment of therapeutic targets and iii) the possibility to use multivalued logic. kali assumes that the attractors of a dynamical system, such as a Boolean network, are associated with the phenotypes of the modeled biological system. Given a logic-based model of pathological mechanisms, kali searches for therapeutic targets able to reduce the reachability of the attractors associated with pathological phenotypes, thus reducing their likeliness. kali is illustrated on an example network and used on a biological case study. This case study is a published logic-based model of bladder tumorigenesis from which kali returns consistent results. However, like any computational tool, kali can predict but can not replace human expertise: it is a supporting tool for coping with the complexity of biological systems in the field of drug discovery.

Copyright 2016-2017 Arnaud Poret

This article is licensed under the Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License. To view a copy of this license, visit <https://creativecommons.org/licenses/by-nc-nd/4.0/>.

arnaud.poret@gmail.com (corresponding author)
carito.guziolowski@ls2n.fr
Laboratoire des Sciences du Numérique de Nantes
Nantes, France

Contents

1	Introduction	3
1.1	Handling asynchronous updating	3
1.2	Managing basin sizes for therapeutic purpose	4
1.3	Extending to multivalued logic	4
2	Methods	5
2.1	Additional definitions	5
2.2	Handling asynchronous updating	5
2.3	Managing basin sizes for therapeutic purpose	6
2.4	Extending to multivalued logic	7
2.5	Example network	7
2.6	Case study: bladder tumorigenesis	8
2.7	Implementation, code availability, license	10
3	Results	12
3.1	Example network	12
3.1.1	Attractor sets	12
3.1.2	Therapeutic bullets	13
3.2	Case study: bladder tumorigenesis	15
3.2.1	Attractor sets	15
3.2.2	Therapeutic bullets	18
3.3	Computation times	19
4	Conclusion	20
5	Author contributions	22
6	Supplementary material listing	22
6.1	Appendices	22
6.2	Supporting files	22
6.3	Source codes	23
7	Appendix 1: recall of previous concepts	24
7.1	Biological networks	24
7.2	Boolean networks	24
7.3	Definitions	24
8	Appendix 2: multivalued case	26
8.1	Attractor sets	26
8.2	Therapeutic bullets	27
9	Appendix 3: core of kali	30
9.1	Defined types	30
9.2	Parameters	30
9.3	Functions	31
10	Appendix 4: case study equations	37

1 Introduction

In a previous article, an algorithm for *in silico* therapeutic target discovery was presented in its first version [1]. In the present article, the improvements made on this algorithm, named kali, are described. The complete background was introduced in the previous article whose some important concepts are recalled in [Appendix 1](#) page 24.

kali still belongs to the logic-based modeling formalism [2–4], mainly Boolean networks [5, 6], and keeps its original goal: searching for therapeutic interventions aimed at healing a supplied pathologically disturbed biological network. Such a network is intended to model the biological mechanisms of a studied disease and is on what kali operates. Therapeutic interventions are combinations of targets, these combinations being named bullets. Targets are network components, such as enzymes or transcription factors, and can be subjected to inhibitions or activations. This is what bullets specify: which targets and which actions to apply on them.

The pivotal assumption on which kali is based postulates that the attractors of a dynamical system, such as a Boolean network, are associated with the phenotypes of the modeled biological system. In other words: attractors model phenotypes [7]. This assumption was successfully applied in several works [8–14] and makes sense since the steady states of a dynamical system, the attractors, should mirror the steady states of the modeled biological system, the phenotypes.

In the mean time, various works using logical modeling with applications in therapeutic innovation were published. For example, Melody Morris and colleagues used fuzzy logic through their constrained fuzzy logic formalism [15]. This formalism aims at giving more quantitative abilities to logical models. They applied this approach on a molecular interaction network dedicated to the hepatocellular carcinoma microenvironment. They successfully predicted the impact of several combinations of kinase inhibitors on key transcription factors.

Another example is the work of Hyunho Chu and colleagues [16]. They built a molecular interaction network involved in colorectal tumorigenesis and studied its dynamics, particularly its attractors and their basins, with stochastic Boolean modeling. They highlighted what they termed the flickering, that is the displacement of the system from one basin to another one due to stochastic noise. They suggest that the flickering is involved in pushing the system from a physiological state to a pathological one during colorectal tumorigenesis.

Concerning kali, three improvements were done: i) adding the possibility to work with asynchronous Boolean networks, ii) implementing a finer assessment of therapeutic targets and iii) adding the possibility to use multivalued logic. The technical features resulting from these improvements are illustrated on a simple example network while their biological significance is assessed on a case study, namely a published logic-based model of bladder tumorigenesis [17].

1.1 Handling asynchronous updating

To compute the behavior of a discrete dynamical system, such as a Boolean network, its variables have to be iteratively updated. These iterative updates, also named time steps, can be made synchronously or not [18]. If all the variables are simultaneously updated at each iteration then the network is synchronous,

otherwise it is asynchronous. Compared to an asynchronous updating, the synchronous one is easier to perform. However, when the dynamics of a biological network is computed synchronously, it is assumed that all its components evolve simultaneously, an assumption which can be inappropriate according to what is modeled.

The asynchronous updating is frequently built so that one randomly selected variable is updated at each iteration. This allows to capture two important features: i) biological entities do not necessarily evolve simultaneously and ii) noise due to randomness can affect when biological interactions take place [19–21]. This is particularly true at the molecular scale, such as with signaling pathways, where macromolecular crowding and Brownian motion can impact the firing of biochemical reactions [22].

Therefore, the choice between a synchronous and an asynchronous updating may depend on the model, the computational resources and the acceptability of synchrony. Knowing that the luxury is to have the choice, kali can now use synchronous and asynchronous updating.

1.2 Managing basin sizes for therapeutic purpose

Until now, kali requires therapeutic bullets to remove all the attractors associated with pathological phenotypes, here named pathological attractors. This criterion for selecting therapeutic bullets is somewhat drastic. A smoother criterion should enable to consider more targeting strategies and then more possibilities for counteracting diseases. However, it could also unravel less effective therapeutic bullets, but being too demanding potentially leads to no results and the loss of nonetheless interesting findings.

The therapeutic potential of bullets could be assessed by estimating their ability at reducing the size of the pathological basins, namely the basins of pathological attractors. This criterion is more permissive since therapeutic bullets no longer have to necessarily remove the pathological attractors. Reducing the size of a pathological basin renders the corresponding pathological attractor less reachable, and then the associated pathological phenotype less likely. This new criterion includes the previous one: removing an attractor means reducing its basin to the empty set. Consequently, therapeutic bullets obtainable with the previous criterion are still obtainable.

1.3 Extending to multivalued logic

One of the main limitations of Boolean models is that their variables can take only two values, which can be too simplistic in some cases. Depending on what is modeled, such as activity level of enzymes or abundance of gene products, considering more than two levels can be better. Without leaving the logic-based modeling formalism, one solution is to extend Boolean logic to multivalued logic [23]. With multivalued logic, a finite number h of values in the interval of real numbers $[0; 1]$ is used, thus allowing variables to model more than two levels. For example, the level 0.5 can be introduced in order to model partial activations of enzymes or moderate concentrations of gene products.

2 Methods

2.1 Additional definitions

In addition to the background introduced in the previous article [1] and briefly recalled in Appendix 1 page 24, here are some supplementary definitions:

- **physiological state space:** the state space S_{physio} of the physiological variant
- **pathological state space:** the state space S_{patho} of the pathological variant
- **testing state space:** the state space S_{test} of the pathological variant under the effect of a bullet
- **physiological basin:** the basin $B_{physio,i}$ of a physiological attractor $a_{physio,i}$
- **pathological basin:** the basin $B_{patho,i}$ of a pathological attractor $a_{patho,i}$
- **n -bullet:** a bullet made of n targets

2.2 Handling asynchronous updating

To incorporate asynchronous updating, the corresponding algorithms of BoolNet were implemented into kali. BoolNet is an R [24] package for generation, reconstruction and analysis of Boolean networks [25]. Asynchronous updating is implemented so that one randomly selected variable is updated at each iteration. This random selection is made according to a uniform distribution and implies that the network is no longer deterministic. To do so, given a Boolean network, BoolNet uses the three following functions:

- **AsynchronousAttractorSearch:** this function computes the attractor set of a supplied Boolean network by using the two following functions
- **ForwardSet:** this function computes the forward reachable set (see below) of a state and considers it as a candidate attractor
- **ValidateAttractor:** this function checks if a forward reachable set is a terminal strongly connected component (terminal SCC, see below), that is an attractor

The forward reachable set $Fwd_{\mathbf{x}} \subset S$ of a state $\mathbf{x} \in S$ is the set made of the states reachable from \mathbf{x} , including \mathbf{x} itself. A terminal SCC is a set $tSCC \subset S$ made of the forward reachable sets of its states: $\forall \mathbf{x} \in tSCC, Fwd_{\mathbf{x}} \subset tSCC$. As a consequence, when a terminal SCC is reached, the system can not escape it: this is an attractor in the sense of asynchronous Boolean networks [26].

Asynchronous Boolean networks with random updating are not deterministic: their attractors are no longer deterministic sequences of states, namely cycles, but terminal SCCs. To find such an attractor, a long random walk is performed in order to reach an attractor with high probability. This candidate attractor is then validated, or not, by checking if it is a terminal SCC.

2.3 Managing basin sizes for therapeutic purpose

To implement the new criterion for selecting therapeutic bullets, kali considers a bullet as therapeutic if it increases the union of the physiological basins $\bigcup B_{physio,i}$ in the testing state space S_{test} without creating *de novo* attractors. Knowing that an attractor is either physiological or pathological, increasing $\bigcup B_{physio,i}$ is equivalent to decreasing $\bigcup B_{patho,i}$.

The goal is to increase the physiological part of the pathological state space, or equivalently to decrease its pathological part. Consequently, a pathologically disturbed biological network receiving such a therapeutic bullet tends to, but not necessarily reaches, an overall physiological behavior.

However, as with the previous criterion, it does not ensure that all the physiological attractors are preserved. *A fortiori*, it does not ensure that their basin remains unchanged. It means that a therapeutic bullet can also alter the reachability of the physiological attractors. Nevertheless, as with the previous criterion, this is a matter of choice between a therapeutic bullet or no bullet at all.

The therapeutic potential of a bullet is expressed by its gain. It is displayed as follows:

$$x\% \rightarrow y\% \text{ with } x = 100 \cdot \frac{|\bigcup B_{physio,i}|}{|S_{patho}|} \text{ and } y = 100 \cdot \frac{|\bigcup B_{physio,i}|}{|S_{test}|}$$

expressed in percents. Therefore, in order to increase the physiological part of the pathological state space, a therapeutic bullet has to make $y \geq x$.

Note that $y = x$ is allowed. In this particular case, it is conceivable that the size of several pathological basins changed while the size of their union did not. In other words, the composition of the pathological part changed while its size did not. It can be therapeutic if, for example, the basin of a weakly pathological attractor increased at the expense of the basin of a heavily pathological attractor.

The increase of the physiological part of the pathological state space can be subjected to a threshold δ : $y \geq x$ becomes $y - x \geq \delta$. As x and y , δ is expressed in percents of the state space. This threshold is introduced to allow the stringency of kali to be tuned. By the way, using this threshold also decreases the probability to obtain misassessed therapeutic bullets due to roundoff errors, or sampling errors when the state space is too big to be exhaustively used.

A therapeutic bullet as defined by the previous criterion, namely which removes all the pathological attractors, makes *de facto* $\bigcup B_{physio,i} = 100\%$ of S_{test} . As already mentioned, the previous criterion is included in this new one: therapeutic bullets obtainable with the former are also obtainable with the latter.

It must be pointed out that the current implementation of the method described in this article, namely kali, estimates basin sizes by counting the number of initial states leading to a given attractor. If kali runs on a subset of the state space then basin sizes are estimations. Moreover, if an asynchronous updating is used then the system is not deterministic, implying that an initial state can lead to more than one attractor. Consequently, in those cases, basin sizes and therapeutic gains are estimations also subjected to random variations.

In other words, concerning the calculation of basin sizes, the current implementation of kali is more an attractor reachability estimation than a true basin

size calculation. Nevertheless, speaking in terms of basins is kept in order to better comply with the underlying method, independently of its implementation which is subjected to improvements.

2.4 Extending to multivalued logic

Extending to multivalued logic requires suitable operators to be introduced. One solution is to use an implementation of the Boolean operators which also works with multivalued logic, just as the Zadeh operators. These operators are a generalization of the Boolean ones proposed for fuzzy logic by its pioneer Lotfi Zadeh [27]. Their formulation is:

$$\begin{aligned}x \wedge y &= \min(x, y) \\x \vee y &= \max(x, y) \\ \neg x &= 1 - x\end{aligned}$$

With a h -valued logic, the size of the n -dimensional state space is h^n , bringing more computational difficulties than with Boolean logic. The same applies to the testable bullets (see below) since there are h^r possible modality arrangements and then $(n! \cdot h^r)/(r! \cdot (n-r)!)$ possible bullets, where r is the number of targets per bullet.

As introduced in the previous article [1] and recalled in [Appendix 1](#) page 24, a bullet is a couple (c_{targ}, c_{moda}) where $c_{targ} = (targ_1, \dots, targ_r)$ is a combination without repetition of r nodes and $c_{moda} = (moda_1, \dots, moda_r)$ is an arrangement with repetition of r perturbations, here termed modalities. $moda_i$ is intended to be applied on $targ_i$.

To illustrate how kali works with multivalued logic without overloading it, a 3-valued logic is used with $\{0, 0.5, 1\}$ as domain of value: $x_i \in \{0, 0.5, 1\}$. 0 and 1 have the same meaning as with Boolean logic. 0.5 is an intermediate truth degree which can be interpreted as an intermediate level of activity/abundance depending on what the variables refer to. By the way, $S = \{0, 0.5, 1\}^n$ and $moda_i \in \{0, 0.5, 1\}$.

2.5 Example network

To conveniently illustrate the technical features resulting from the improvements made on kali, a simple and fictive example network is used. A biological case study is then proposed to address a concrete case, namely a published logic-based model of bladder tumorigenesis [17]. The example network is depicted in [Figure 1](#) page 9.

Among the three improvements made on kali, only the asynchronous updating and the management of basin sizes are illustrated. Multivalued logic is a straightforward extension of the Boolean case and is illustrated in [Appendix 2](#) page 26. Below are the Boolean equations encoding the example network, also available in text format in the supporting file `example_equations.txt`:

$$\begin{aligned}
do &= do \\
factory &= factory \\
energy &= factory \vee (energy \wedge \neg task) \\
locker &= \neg energy \\
releaser &= do \\
sequester &= \neg releaser \\
activator &= do \wedge \neg locker \\
effector &= activator \wedge \neg sequester \\
task &= effector
\end{aligned}$$

The *do* instruction and the *factory* are the two inputs: they are constant and thus equal to themselves. The equation of *energy* tells that *energy* is present if the *factory* is active, even when the *task* is running: the *factory* has a sufficient production capacity. However, if the *factory* is not active then *energy* disappears as soon as the *task* is initiated. Concerning the *activator* and the *effector*, their equations tell that their respective inhibitor takes precedence: whatever is the state of the other nodes, if the inhibitor is active then the target is not.

The physiological variant f_{physio} is the network as is. The pathological variant f_{patho} is the network plus a constitutive inactivation of the *locker*: the execution of the *task* no longer considers if *energy* is available. Consequently, f_{locker} becomes $locker = 0$ in f_{patho} .

2.6 Case study: bladder tumorigenesis

This case study consists in running *kali* on a logic-based model of bladder tumorigenesis published by Elisabeth Remy and colleagues [17]. Elisabeth Remy and colleagues have built an influence network linking three extracellular input signals and one intracellular input event to three cellular output phenotypes. The three extracellular input signals are growth stimulations, represented by the *EGFRstimulus* and *FGFR3stimulus* parameters, and growth inhibitions, mainly modeling TGF- β effects and represented by the *GrowthInhibitors* parameter. The intracellular input event is DNA damage, represented by the *DNA damage* parameter. The three cellular output phenotypes are proliferation, growth arrest and apoptosis. The model integrates downstream effectors of growth factor receptors such as Ras and PI3K, growth inhibitors such as p14ARF and p16INK4a, and regulators of the cell cycle such as cyclinD1, E2F3 and pRb.

Some variables are ternary: they can take three possible values in order to account for different effects depending on the activation level. These three possible values are 0 and 1 as in the Boolean case, plus the additional level 2. To make the present case study purely Boolean, these ternary variables are translated into pairs of Boolean variables : one Boolean variable per activation level, namely level 1 and level 2.

For example and according to the model, in its normal expression level (level 1, $E2F1 = 1$) the transcription factor E2F1 stimulates the expression of genes supporting the cell cycle. However, when over-expressed (level 2, $E2F1 = 2$)




Figure 1: This network, running in a fictive cell, controls the execution of a task according to two inputs: i) the do instruction, which tells the task to be performed, and ii) energy supply. The task consumes energy and must be prevented if no energy is available, even if the do instruction is sent. The task is initiated by an effector, which is maintained inactive by a sequester. The do instruction activates a releaser which suppresses the sequestering activity of the sequester, thus releasing the effector. However, to initiate the task and in addition to be released, the effector has also to be activated by an activator. When released and activated, the effector initiates the task. To ensure that the task is performed only if energy is available, a locker maintains the activator in an inactive state if there is no energy, even if the do instruction is sent. Concerning the factory, it supplies energy.

E2F1 stimulates the expression of genes supporting apoptosis. Consequently, this ternary variable is translated into the pair of Boolean variables $E2F1_{lv1}$ and $E2F1_{lv2}$:

$$\begin{aligned} E2F1 = 1 &\Leftrightarrow E2F1_{lv1} = 1 \\ E2F1 = 2 &\Leftrightarrow E2F1_{lv2} = 1 \end{aligned}$$

The variable modeling the output phenotype *Apoptosis* is one of these ternary variables. The goal of Elisabeth Remy and colleagues was to relate apoptosis to its trigger: p53-dependent apoptosis ($Apoptosis_{lv1}$) and E2F1-dependent apoptosis ($Apoptosis_{lv2}$). However, in the present case study, only the cell fate matters. These two trigger-dependent apoptosis are therefore merged into one equation:

$$Apoptosis = Apoptosis_{lv1} \vee Apoptosis_{lv2}$$

Since the four inputs of the model are parameters, their respective value are directly injected into the concerned equations so that no equations are dedicated to them, thus reducing computational requirements. Again to reduce computational requirements and knowing that the three output phenotypes are readouts not influencing other variables, their corresponding equation are put out of the model and evaluated from the returned attractors once the run terminated:

$$\begin{aligned} Proliferation &= CyclinE1 \vee CyclinA \\ GrowthArrest &= p21CIP \vee RB1 \vee RBL2 \\ Apoptosis &= TP53 \vee E2F1_{lv2} \end{aligned}$$

Altogether, the above described adaptations made on the model of bladder tumorigenesis by Elisabeth Remy and colleagues give a case study of 27 Boolean equations. These equations are listed in **Appendix 4** page 37, also available in text format in the supporting file `bladder_equations.txt`. A network-based representation is shown in **Figure 2** page 11.

The physiological variant \mathbf{f}_{physio} is the model as is. The pathological variant \mathbf{f}_{patho} is the model plus a deletion of the tumor suppressor gene CDKN2A, as observed in bladder cancers [28, 29]. Note that the CDKN2A gene encodes two growth inhibitors: p14ARF and p16INK4a. Consequently, the equations modeling these two variables become $p14ARF = 0$ and $p16INK4a = 0$ in \mathbf{f}_{patho} .

2.7 Implementation, code availability, license

kali is implemented in Go [30], tested with Go version go1.9 linux/amd64 under Arch Linux [31]. kali is licensed under the GNU General Public License [32] and freely available on GitHub at <https://github.com/arnaudporet/kali>. The core of kali in pseudocode can be found in **Appendix 3** page 30.




Figure 2: A network-based representation of the case study used to assess kali on a concrete case. As explained in the text, it is derived from a published logic-based model of bladder tumorigenesis [17]. Nodes represent Boolean variables while edges indicate positive (black) and negative (red) influences. The input signals/events growth stimulations, growth inhibitions and DNA damage are in red while the output phenotypes proliferation, growth arrest and apoptosis are in green.

3 Results

3.1 Example network

3.1.1 Attractor sets

The example network is computed asynchronously over the whole state space, namely 512 possible initial states, using Boolean logic. As explained in the **Methods** section page 5, the asynchronous attractor search uses long random walks to reach candidate attractors with high probability, and then checks if they are indeed true attractors. Owing to the small size of the example network, the length max_k of these random walks is set to 1 000 steps. With larger state spaces, random walks should be longer to reach candidate attractors with high probability.

The resulting attractors can be studied along four variables: the do instruction, the factory, the locker and the task. It is possible for energy to be present without a running factory in the initial conditions. In this case, if the do instruction is sent then energy is consumed by the task but not remade by the factory. With the physiological variant, the locker is expected to stop the task. However, with the pathological variant where the locker is disabled, an abnormal behavior is expected. Below are the computed attractors:

- A_{physio} :

attractor	basin (% of S_{physio})	<i>do</i>	<i>factory</i>	<i>energy</i>	<i>locker</i>	<i>task</i>
$a_{physio1}$	17.8%	0	0	0	1	0
$a_{physio2}$	7.2%	0	0	1	0	0
$a_{physio3}$	25%	0	1	1	0	0
$a_{physio4}$	25%	1	0	0	1	0
$a_{physio5}$	25%	1	1	1	0	1

- A_{patho} :

attractor	basin (% of S_{patho})	<i>do</i>	<i>factory</i>	<i>energy</i>	<i>locker</i>	<i>task</i>
a_{patho1}	18.4%	0	0	0	0	0
$a_{physio2}$	6.6%	0	0	1	0	0
$a_{physio3}$	25%	0	1	1	0	0
a_{patho2}	25%	1	0	0	0	1
$a_{physio5}$	25%	1	1	1	0	1

With the physiological variant, the behavior is as expected: the task runs only if the do instruction is sent and only if the factory can remade the consumed energy. With the pathological variant, two pathological phenotypes represented by a_{patho1} and a_{patho2} appear. a_{patho1} is pathological because the locker is inactive while there is no available energy. However, it is weakly pathological since the do instruction is not sent: there is no task to stop, an operational locker is not mandatory.

In contrast, a_{patho2} is heavily pathological because an operational locker is required to stop the task in absence of energy supply. In the fictive cell bearing this example network, a_{patho2} could drain all the energy content and bring the cell to thermodynamical death. Moreover, a_{patho2} should not be neglected since its basin occupies 25% of the pathological state space.

3.1.2 Therapeutic bullets

Bullets are assessed for their therapeutic potential on the pathological variant f_{patho} according to the new criterion: decreasing the size of the pathological basins $B_{patho,i}$. All the bullets made of one to two targets are tested with a threshold of 5%.

Choosing a threshold can appear somewhat arbitrary. It tells that if the physiological part $\cup B_{physio,i}$ in the pathological state space S_{patho} occupies $x\%$ of it, then to be therapeutic a bullet has to bring this value above $(x + 5)\%$ in the testing state space S_{test} . Therefore, the increases below this threshold are considered not significant by kali. Even the choice of using a threshold can be arbitrary, as discussed in the **Methods** section page 6.

Knowing that $\cup B_{physio,i} = 56.6\%$ of S_{patho} , with a threshold of 5% the 1,2-bullets have to make $\cup B_{physio,i} \geq (56.6 + 5)\% = 61.6\%$ of S_{test} to be considered therapeutic. Below are the returned therapeutic bullets:

- 1-therapeutic bullets:

bullet	gain		$B_{physio1}$	$B_{physio2}$	$B_{physio3}$	$B_{physio4}$	$B_{physio5}$	B_{patho1}	B_{patho2}
$do[0]$	56.6%	→ 64.4%	0%	14.4%	50%	0%	0%	35.5%	0%
$factory[1]$	56.6%	→ 100%	0%	0%	50%	0%	50%	0%	0%

- 2-therapeutic bullets:

bullet		gain		$B_{physio1}$	$B_{physio2}$	$B_{physio3}$	$B_{physio4}$	$B_{physio5}$	B_{patho1}	B_{patho2}
$do[0]$	$factory[1]$	56.6%	→ 100%	0%	0%	100%	0%	0%	0%	0%
$do[1]$	$factory[1]$	56.6%	→ 100%	0%	0%	0%	0%	100%	0%	0%
$do[0]$	$energy[1]$	56.6%	→ 100%	0%	50%	50%	0%	0%	0%	0%
$do[0]$	$locker[0]$	56.6%	→ 64.1%	0%	14.1%	50%	0%	0%	35.9%	0%
$do[0]$	$releaser[0]$	56.6%	→ 62.9%	0%	12.9%	50%	0%	0%	37.1%	0%
$do[0]$	$sequester[1]$	56.6%	→ 62.5%	0%	12.5%	50%	0%	0%	37.5%	0%
$do[0]$	$activator[0]$	56.6%	→ 64.8%	0%	14.8%	50%	0%	0%	35.2%	0%
$do[0]$	$effector[0]$	56.6%	→ 67.8%	0%	17.8%	50%	0%	0%	32.2%	0%
$do[0]$	$task[0]$	56.6%	→ 73.2%	0%	23.2%	50%	0%	0%	26.8%	0%
$factory[1]$	$energy[1]$	56.6%	→ 100%	0%	0%	50%	0%	50%	0%	0%
$factory[1]$	$locker[0]$	56.6%	→ 100%	0%	0%	50%	0%	50%	0%	0%

where $x[y]$ means that the variable x has to be set to the value y . For example, the therapeutic bullet $do[0] factory[1]$ suggests to abolish the do instruction while maintaining the factory active.

All the returned therapeutic bullets not removing all the pathological attractors exhibit the ability to suppress the basin of a_{patho2} while increasing the one of a_{patho1} . Certainly, removing all the pathological attractors should be better, but knowing the a_{patho2} is more pathological than a_{patho1} , such therapeutic bullets can nevertheless be interesting. With the previous criterion, namely removing all the pathological attractors, these therapeutic bullets are not obtainable, thus highlighting fewer therapeutic strategies.

Some of the found therapeutic bullets enable physiological attractors required by the pathological variant to react properly to the do instruction. For example, the therapeutic bullet *factory*[1] enables $a_{physio3}$ and $a_{physio5}$, corresponding respectively to “no do, no task” and “do the task, energy supply”. However, the remaining of the therapeutic bullets, such as *do*[0] *releaser*[0] or *do*[1] *factory*[1], either disable or force the do instruction, thus either suppressing or forcing the task. A network unable at performing the task or, at the opposite, permanently doing it may not be therapeutically interesting, even if energy is supplied.

None of the found therapeutic bullets suggest to reverse the constitutive inactivation of the locker. This highlights that applying the opposite action of the pathological disturbance is not necessarily a therapeutic solution, which can appear counterintuitive. This is because biological entities subjected to pathological disturbances belong to complex networks exhibiting behaviors which can not be predicted by mind [33, 34]. In such context, computational tools and their growing computing capabilities can help owing to their integrative power [35–39].

Also, none of the found therapeutic bullets allow the recovery of all the physiological attractors: there are no golden bullets. In a general manner, the components of biological networks should be able to take several states, such as enzymes which should be active when suitable. Consequently, healing a pathologically disturbed biological network by maintaining some of its components in a particular state should not allow the recovery of a complete and healthy behavior. This is a limitation of the method implemented in kali.

This limitation is common in biomedicine while not necessarily being an issue. For example, statins are well known lipid-lowering drugs widely used in cardiovascular diseases with proven benefits [40, 41]. They inhibit an enzyme, the HMG-CoA reductase, and they do it constantly, just as the targets are modulated in the therapeutic bullets returned by kali. The HMG-CoA reductase is component of a complex metabolic network and maintaining it in an inhibited state should not allow this network to run properly, maybe causing some adverse effects. Nevertheless, such as with all drugs, this is a matter of benefit-risk ratio.

All of this is to point that there are no perfect methods for counteracting diseases and that computational tools, such as kali, can help scientists but can certainly not replace their expertise. Human expertise is mandatory to interpret predictions according to a concrete setting, and ultimately to take decisions.

3.2 Case study: bladder tumorigenesis

3.2.1 Attractor sets

The state space of the case study is quite big with 134 217 728 possible states. kali is therefore run asynchronously using Boolean logic on a subset of 1 000

randomly selected initial states. A bigger state space also requires longer random walks to reach candidate attractors with high probability. The length max_k of random walks is then increased to 10 000 steps. The 4 inputs of the model are tuned to simulate a biological situation where undamaged cells receive both growth stimulating and growth inhibiting signals from their environment:

$$\begin{aligned}EGFRstimulus &= 1 \\FGFR3stimulus &= 1 \\GrowthInhibitors &= 1 \\DNAdamage &= 0\end{aligned}$$

This input configuration aims at predicting the possible responses of the model to opposite growth instructions. In a cancerous setting, it is desirable that the growth inhibiting signal takes precedence over the stimulating one. With the pathological variant, where the two growth inhibitors p14ARF and p16INK4a are absent, this desired precedence might be compromised in favor of tumorigenesis, thus correlating with the observed CDKN2A gene deletion in bladder cancers [28, 29].

The phenotypes associated with the returned attractors are evaluated using their respective equation once the run terminated, as explained in the **Methods** section page 10. Below are the computed attractors together with their phenotypes and basins, expressed in percents of the corresponding state space:

name basin phenotype	A_{physio}			A_{patho}	
	$a_{physio1}$ 10.7% GA	$a_{physio2}$ 74.5% GA	$a_{physio3}$ 14.8% P	$a_{physio1}$ 65.4% GA	a_{patho1} 34.6% P
<i>AKT</i>	0	0	0	0	0
<i>ATM_{lvl1}</i>	0	0	0	0	0
<i>ATM_{lvl2}</i>	0	0	0	0	0
<i>CDC25A</i>	0	0	1	0	1
<i>CHEK1/2_{lvl1}</i>	0	0	0	0	0
<i>CHEK1/2_{lvl2}</i>	0	0	0	0	0
<i>CyclinA</i>	0	0	1	0	1
<i>CyclinD1</i>	0	0	0	0	1
<i>CyclinE1</i>	0	0	1	0	1
<i>E2F1_{lvl1}</i>	0	0	1	0	1
<i>E2F1_{lvl2}</i>	0	0	0	0	0
<i>E2F3_{lvl1}</i>	0	1	1	0	1
<i>E2F3_{lvl2}</i>	0	0	0	0	0
<i>EGFR</i>	0	0	0	0	0
<i>FGFR3</i>	1	1	1	1	1
<i>GRB2</i>	0	0	0	0	0
<i>MDM2</i>	0	0	0	0	0
<i>p14ARF</i>	0	0	1	0	0
<i>p16INK4a</i>	0	1	1	0	0
<i>p21CIP</i>	1	1	0	1	0
<i>PI3K</i>	0	0	0	0	0
<i>PTEN</i>	0	0	0	0	0
<i>RAS</i>	1	1	1	1	1
<i>RB1</i>	1	0	0	1	0
<i>RBL2</i>	1	1	0	1	0
<i>SPRY</i>	1	1	1	1	1
<i>TP53</i>	0	0	0	0	0

where GA means growth arrest and P means proliferation.

The physiological variant is able to exhibit the two possible responses according to the input configuration: proliferation, represented by $a_{physio3}$, and growth arrest, represented by $a_{physio1}$ and $a_{physio2}$. Growth arrest occupies 85.2% of the physiological state space, suggesting that normal cells are more likely to comply with growth inhibiting signals than with stimulating ones.

With the pathological variant modeling cells whose the two growth inhibitors p14ARF and p16INK4a are lost, the two possible responses are still present with again growth arrest being more likely than proliferation. Even if $a_{physio2}$ disappears, growth arrest is still possible with $a_{physio1}$ whose the basin increases from 10.7% in S_{physio} to 65.4% in S_{patho} . The proliferating phenotype is also still possible but through the pathological attractor a_{patho1} which, in a way, replaces the physiological attractor $a_{physio3}$.

However, the global tendency toward growth arrest significantly decreases: proliferation is more than twice likely in the pathological variant than in the physiological one with a shift from 14.8% in S_{physio} to 34.6% in S_{patho} . Therefore, such pathological cells might be less responsive to growth inhibiting signals and more apt at proliferating, which is a major concern in tumorigenesis and consistent with the loss of two growth inhibitors.

3.2.2 Therapeutic bullets

As in the example network, bullets are assessed for their therapeutic potential on the pathological variant f_{patho} according to the new criterion: increasing the physiological part $\bigcup B_{physio,i}$ in the testing state space S_{test} with a threshold of 5%. It means that therapeutic bullets have to push $\bigcup B_{physio,i}$ from 65.4% in S_{patho} to at least $65.4 + 5 = 70.4\%$ in S_{test} .

This case study belonging to a cancerous setting, it is desirable that therapeutic bullets also promote growth arrest in order to slow down tumorigenesis. In terms of basins and attractors, it means that interesting therapeutic bullets should decrease B_{patho1} , avoid $a_{physio3}$, increase $B_{physio1}$ and reintroduce $a_{physio2}$. Such therapeutic bullets could be qualified as anti-proliferative.

All the 1 458 bullets made of one to two targets are tested. Among them, kali find 9 1-therapeutic bullets and 174 2-therapeutic bullets, listed in the supporting files `bladder_B_therap_1.txt` and `bladder_B_therap_2.txt` respectively. In addition to increasing the physiological part, all the returned therapeutic bullets are anti-proliferative. Indeed, all of them do not reintroduce $a_{physio3}$ and decrease B_{patho1} , thus promoting growth arrest through $a_{physio1}$ and/or $a_{physio2}$.

For example, the two following 1-therapeutic bullets increase $B_{physio1}$ while decreasing B_{patho1} , thus exhibiting anti-proliferative effect as expected when targeting the well known growth promoting PI3K/Akt pathway [42]:

bullet	gain		$B_{physio1}$	$B_{physio2}$	$B_{physio3}$	B_{patho1}
<i>AKT</i> [0]	65.4%	→ 89.3%	89.3%	0%	0%	10.7%
<i>PI3K</i> [0]	65.4%	→ 86%	86%	0%	0%	14%

Below is an other interesting 1-therapeutic bullet predicting that inhibiting CDC25A is anti-proliferative:

bullet	gain		$B_{physio1}$	$B_{physio2}$	$B_{physio3}$	B_{patho1}
<i>CDC25A</i> [0]	65.4%	→ 100%	100%	0%	0%	0%

This therapeutic bullet is able to definitively suppress proliferation by making $B_{physio1} = 100\%$ of S_{test} . It makes sense since the tyrosine phosphatase CDC25A can activate several cyclin-dependent kinases (CDKs) which, with their cyclin partners, promote cell cycle and then growth [43]. Moreover, this prediction correlates with biological knowledge about CDC25A inhibitors as potential anticancer agents [44]. For example, it is demonstrated that inhibiting CDC25A suppresses the growth of hepatocellular carcinoma cells [45,46]. Moreover, a recent work was specially dedicated to the synthesis of anticancer agents inhibiting the CDC25A/B phosphatases [47].

This highlights that dry-lab predictions consistent with factual evidences coming from wet-lab experiments are obtainable through kali, provided that the underlying model is consistent too. Note that this does not imply that all the predictions are correct: needless to say that biological interpretation by experts is still mandatory.

The 2-therapeutic bullets also bring some interesting predictions. For example, they indicate that sprouty (SPRY) could be a therapeutic target but only in combination with another one: there are no 1-therapeutic bullets containing it. Sprouty negatively regulates mitogen-activated protein kinase (MAPK) signaling pathways downstream of growth factor receptors and is down-regulated in many cancers [48]. Consequently, stimulating sprouty should be anti-proliferative

and this is what suggest the two following therapeutic bullets, even if the gain is relatively minor:

bullet		gain		$B_{physio1}$	$B_{physio2}$	$B_{physio3}$
				B_{patho1}		
$E2F3_{lvl2}[0]$	$SPRY[1]$	65.4%	→ 70.5%	70.5%	0%	0%
				29.5%		
$MDM2[0]$	$SPRY[1]$	65.4%	→ 71.7%	71.7%	0%	0%
				28.3%		

These two therapeutic bullets indicate that stimulating sprouty should be done along with an inhibition of MDM2 or E2F3. As with CDC25A, this prediction correlates with biological knowledge: MDM2 is a major inhibitor of the well known tumor suppressor gene p53 [49] while E2F3 is a required transcription factor for the cell cycle [50]. However, only the level 2 of E2F3 is concerned, meaning that only its over-expression should be prevented. In other words, this is not an inhibition of E2F3 but rather the prevention of its over-expression, if any.

In the returned therapeutic bullets there are also intriguing results such as the following one:

bullet	gain		$B_{physio1}$	$B_{physio2}$	$B_{physio3}$	B_{patho1}
$FGFR3[1]$	65.4%	→ 74.1%	74.1%	0%	0%	25.9%

This therapeutic bullet moderately increases $B_{physio1}$ at the expense of B_{patho1} , therefore promoting growth arrest. However, FGFR3 is a growth factor receptor and is frequently subjected to activating mutations in low grade bladder cancers [51]. Therefore, stimulating FGFR3 should promote proliferation, not growth arrest. However, Elisabeth Remy and colleagues have implemented a negative crosstalk from FGFR3 to the growth factor receptor EGFR in their model. This negative crosstalk may explain why stimulating FGFR3 is predicted to be anti-proliferative.

$EGFR[0]$ is one of the returned therapeutic bullet and represent a direct inhibition of EGFR, a well studied target in cancer therapies [52, 53]. Consequently and according to the model, $FGFR3[1]$ can be interpreted as an indirect inhibition of EGFR, especially since these two therapeutic bullets have almost identical effects in magnitude:

bullet	gain		$B_{physio1}$	$B_{physio2}$	$B_{physio3}$	B_{patho1}
$EGFR[0]$	65.4%	→ 75.4%	75.4%	0%	0%	24.6%

Finally, it should be noted that the three following bullets are not predicted therapeutic by kali: $p14ARF[1]$, $p16INK4a[1]$ and $p14ARF[1]$ $p16INK4a[1]$. As with the example network, this suggests that applying the opposite action of the pathological disturbance is not necessarily a therapeutic solution. Moreover and again as with the example network, none of the found therapeutic bullets allow the recovery of all the physiological attractors: golden bullets seems to be as idealistic as golden pills.

3.3 Computation times

The results presented in this article were obtained on a laptop with 16GB of RAM and an Intel Core i7-6600U processor. There are two kali parameters strongly influencing computation times. These two parameters control the attractor search and are:

- max_S : the maximal size of the state space sample from which attractors are searched
- max_k : the length of the random walks performed to reach candidate attractors

The asynchronous attractor search consists in performing max_S random walks of max_k steps. Knowing that such a search is performed for computing an attractor set and that one attractor set is computed per tested bullet, the computation time can greatly increase with max_S and/or max_k . Computation times also increase with n_{targ} , max_{targ} and max_{moda} , three kali parameters controlling how much bullets are tested:

- n_{targ} : the number of targets per bullet
- max_{targ} : the maximum number of target combinations to test
- max_{moda} : the maximum number of modality arrangements to test

The used logic can also increase computation times because the size of the state space is h^n , where n is the number of nodes in the network and h the number of possible values for variables. For example, $h = 2$ with Boolean logic and $h = 3$ with 3-valued logic. h can also increase the number of testable bullets, and then computation times, since there are $(n! \cdot h^{n_{targ}})/(n_{targ}! \cdot (n - n_{targ})!)$ possible bullets.

Below are the computation times of the runs performed for this article:

	example network (Boolean)	example network (3-valued)	case study (Boolean)
max_S	512 (all)	1 000	1 000
max_k	1 000	1 000	10 000
1-bullets	18 (all)	27 (all)	54 (all)
2-bullets	144 (all)	324 (all)	1 404 (all)
A_{physio}	130ms	187ms	6s89ms
A_{patho}	109ms	218ms	6s55ms
B_{therap} ($n_{targ} = 1$)	2s510ms	6s775ms	5m57s950ms
B_{therap} ($n_{targ} = 2$)	19s133ms	1m23s526ms	2h43m36s709ms

4 Conclusion

kali can now work on both synchronous and asynchronous Boolean networks. This is probably the most necessary improvement since asynchronous updating is frequently used in the scientific community and might be better realistic than synchrony, as discussed in the **Introduction** section page 3. Consequently, a computational tool aimed at working on models built by the scientific community, such as kali, has to handle this updating scheme.

Also note that there are more than one asynchronous updating scheme. The one implemented in kali is the most popular and is termed the general asynchronous updating: one randomly selected variable is updated at each iteration. However, other asynchronous updating methods exist. For example, with the random order updating, all the variables are updated at each iteration along a randomly selected order. Implementing various asynchronous updating schemes in kali could be a required future improvement.

kali now uses a new criterion for assessing therapeutic bullets. This new criterion brings a wider range of targeting strategies intended to push pathological behaviors toward physiological ones. It is based on a more permissive assumption stating that reducing the reachability of pathological attractors is therapeutic. For an *in silico* tool such as kali, being a little bit more permissive can be important since the findings obtained by computational simulations have to outlive the bottleneck separating predictions and reality. With a too strict assessment of therapeutic bullets, the risk of highlighting too few candidate targets or to miss some interesting ones can be high. Moreover, predicted does not necessarily mean true: an *in silico* prediction of apparently poor interest can reveal itself of great interest, and *vice versa*.

This new criterion also brings a finer assessment of therapeutic bullets since all the possible increases of $\bigcup B_{physio,i}$ in S_{test} are considered. With the previous criterion, there was only one therapeutic potential: $\bigcup B_{physio,i} = 100\%$ of S_{test} , thus reducing the assessment of bullets to therapeutic or not. Things are not necessarily so dichotomous but rather nuanced: the assessment of therapeutic bullets should be nuanced too.

kali can now work with multivalued logic. Allowing variables to take an arbitrary finite number of values should enable to more accurately model biological processes and produce more fine-tuned therapeutic bullets. However, this accuracy and fine-tuning are at the cost of an increased computational requirement. Indeed, the size of the state space depends on the size of the model and the used logic. Consequently, the size of the model and the used logic should be balanced: the smaller the model is, the more variables should be finely valued. For example, for an accurate therapeutic investigation, the model should only contain the essential and specific pieces of the studied pathological mechanisms modeled by a finely valued logic. On the other hand, for a broad therapeutic investigation, a more exhaustive model can be used but modeled by a coarse-grained logic.

Note that the ultimate multivalued logic is the infinitely valued one, which is fuzzy logic [54]. With fuzzy logic, the whole interval of real numbers $[0; 1]$ is used to valuate variables, which might bring the best accuracy for the qualitative modeling formalism [55–57]. However, using such a continuous logic implies to leave the relatively convenient discrete paradigm to enter the continuous one where, for example, the state space is infinite.

kali also demonstrates that it is able at predicting therapeutic bullets consistent with the underlying model, biological knowledge and experimental evidences. For example, in the bladder tumorigenesis case study, kali returned therapeutic bullets inhibiting the PI3K/Akt pathway or the CDC25A tyrosine phosphatase, two documented targets in cancer therapies. Even the surprising *FGFR3*[1] therapeutic bullets, which suggests to stimulate a growth factor receptor for promoting growth arrest, is consistent with the underlying model. Indeed, according to this model, it appears that *FGFR3*[1] is founded in a negative crosstalk from *FGFR3* to *EGFR*, thus indirectly inhibiting the growth factor receptor *EGFR*, which is also a documented target in cancer therapies.

Two additional improvements are envisioned for kali. The first one is to allow therapeutic bullets to create new attractors, namely *de novo* attractors. It is conceivable that a bullet can greatly decrease pathological basins while creating a new attractor not belonging to the physiological variant nor to the pathological one. Such a *de novo* attractor is currently tagged by kali as not physiological and then pathological, thus rejecting the concerned bullet. However, if a *de*

novo attractor is weakly pathological and induced by a bullet greatly decreasing the basin of other and heavier pathological attractors, such a case should be retained.

The second envisioned improvement is to allow partial matching when checking if an attractor is associated with a physiological phenotype by comparing it to the physiological attractors. Currently, an attractor which does not match a physiological attractor is considered pathologic. However, it is conceivable that some variables not exhibiting a physiological behavior in an attractor do not pathologically impact its associated phenotype. To allow such a case to be considered, some variables within attractors should be allowed to not be matched when assessing the associated phenotype. This suggests the concept of decisive variables, namely variables whose the behavior in the attractors is sufficient to biologically interpret the associated phenotypes. Elisabeth Remy and colleagues have already done this distinction in their model of bladder tumorigenesis used in the present article as case study: decisive variables are those belonging to the equations of the three output phenotypes. Therefore, kali could allow non-decisive variables to not be matched.

Ultimately, this could allow the modeler to specify himself/herself what a physiological attractor is without having to consider a physiological and a pathological variant. This could also allow to no longer think in terms of physiological *versus* pathological attractors but just desirable ones. Moreover, implementing the second envisioned improvement could greatly facilitate the implementation of the first one since the goal would become to obtain desired attractors regardless if they are *de novo* or not.

5 Author contributions

AP designed and implemented kali, designed the example network, selected the case study, adapted the case study, realized the simulations, wrote the article. AP and CG analyzed and discussed the results, addressed the reviewer comments. CG revised the article.

6 Supplementary material listing

6.1 Appendices

Appendix 1: recall of previous concepts

Appendix 2: multivalued case

Appendix 3: core of kali

Appendix 4: case study equations

6.2 Supporting files

`example_equations.txt`: equations of the example network in text format

`bladder_equations.txt`: equations of the case study in text format

`bladder_B_therap_1.txt`: 1-therapeutic bullets of the case study

`bladder_B_therap_2.txt`: 2-therapeutic bullets of the case study

6.3 Source codes

<https://github.com/arnaudporet/kali>

7 Appendix 1: recall of previous concepts

7.1 Biological networks

A network is a directed graph $G = (V, E)$ where $V = \{v_1, \dots, v_n\}$ is the set containing the nodes of the network and $E = \{(v_{i,1}, v_{j,1}), \dots, (v_{i,m}, v_{j,m})\}$ is the set containing the edges linking these nodes. In practice, nodes represent entities while edges represent binary relations $R \subset V^2$ involving them: $v_i R v_j$ [58]. It indicates that the node v_i exerts an influence on the node v_j . For example, in gene regulatory networks [59], v_i can be a transcription factor while v_j a gene product. The edges are frequently signed so that they indicate if v_i exerts a positive or a negative influence on v_j , such as an activation or an inhibition.

7.2 Boolean networks

A Boolean network is a network where nodes are Boolean variables x_i and edges (x_i, x_j) are the *is input of* relation: x_i is input of x_j . Each variable x_i has $b_i \in \llbracket 0, n \rrbracket$ inputs influencing its state. Note that $b_i = 0$ is possible. In this case, x_i is an input of the network. Depending on the updating scheme, at each iteration $k \in \llbracket k_0, k_{end} \rrbracket$, one or more x_i are updated using their associated Boolean transition function f_i . This function uses Boolean operators, typically \wedge (*and*), \vee (*or*) and \neg (*not*), to specify how the inputs $x_{i,1}, \dots, x_{i,b_i}$ of x_i have to be related to compute its value, as in the following pseudocode representing a synchronous updating:

```
for  $k \leftarrow k_0, \dots, k_{end}$ 
   $x_1 \leftarrow f_1(x_{1,1}, \dots, x_{1,b_1})$ 
   $\vdots$ 
   $x_n \leftarrow f_n(x_{n,1}, \dots, x_{n,b_n})$ 
```

end for

which can be written in a more concise form:

```
for  $k \leftarrow k_0, \dots, k_{end}$ 
   $\mathbf{x} \leftarrow \mathbf{f}(\mathbf{x})$ 
```

end for

where $\mathbf{f} = (f_1, \dots, f_n)$ is the Boolean transition function of the network and $\mathbf{x} = (x_1, \dots, x_n)$ is its state vector. The value of the state vector belongs to the state space $S = \{0, 1\}^n$, which is the set containing all the possible states of the network.

The set $A = \{a_1, \dots, a_p\}$ containing the attractors of the network is its attractor set. An attractor a_i is a collection of states $(\mathbf{x}_1, \dots, \mathbf{x}_q)$ such that once the system reaches a state $\mathbf{x}_j \in a_i$, it can subsequently visit the states of a_i but no other ones: the system can not escape. The set $B_i \subset S$ containing the states $\mathbf{x} \in S$ from which a_i can be reached is its basin of attraction, or simply basin.

7.3 Definitions

- **physiological phenotype:** a phenotype which does not impair the life quantity/quality of the organism which exhibits it

- **pathological phenotype:** a phenotype which impairs the life quantity/quality of the organism which exhibits it
- **variant (of a biological network):** given a biological network, a variant is one of its versions, namely the network plus eventually some modifications
- **physiological variant:** a variant which produces only physiological phenotypes, this is the biological network as it should be, the one of healthy organisms
- **pathological variant:** a variant which produces at least one pathological phenotype, this is a dysfunctional version of the biological network, a version found in ill organisms
- **physiological attractor set:** the attractor set A_{physio} of the physiological variant
- **pathological attractor set:** the attractor set A_{patho} of the pathological variant
- **physiological Boolean transition function:** the Boolean transition function f_{physio} of the physiological variant
- **pathological Boolean transition function:** the Boolean transition function f_{patho} of the pathological variant
- **physiological attractor:** an attractor a_i such that $a_i \in A_{physio}$, note that it does not exclude the possibility that $a_i \in A_{patho}$ in addition to $a_i \in A_{physio}$
- **pathological attractor:** an attractor a_i such that $a_i \notin A_{physio}$
- **modality:** the perturbation $moda_i \in \{0, 1\}$ applied on a node v_j of the network, either activating ($moda_i = 1$) or inactivating ($moda_i = 0$), at each iteration $moda_i$ overwrites $f_j(\mathbf{x})$ making $x_j = moda_i$
- **target:** a node $targ_i$ of the network on which a modality $moda_i$ is applied
- **bullet:** a couple (c_{targ}, c_{moda}) where $c_{targ} = (targ_1, \dots, targ_r)$ is a combination without repetition of r targets and $c_{moda} = (moda_1, \dots, moda_r)$ is an arrangement with repetition of r modalities, $moda_i$ is intended to be applied on $targ_i$

8 Appendix 2: multivalued case

Below is the multivalued version of the example network:

$$\begin{aligned}
 do &= do \\
 factory &= factory \\
 energy &= \max(\min(energy, 1 - task), factory) \\
 locker &= 1 - energy \\
 releaser &= do \\
 sequester &= 1 - releaser \\
 activator &= \min(do, 1 - locker) \\
 effector &= \min(activator, 1 - sequester) \\
 task &= effector
 \end{aligned}$$

where the Boolean operators are replaced by the Zadeh ones.

To take advantage of multivalued logic, f_{locker} becomes $locker = \min(1 - energy, 0.5)$ in \mathbf{f}_{patho} . This equation tells that the locker is actionable when required, namely when there is no energy, but that it is unable at being fully operational due to some pathological defects: the maximal value of f_{locker} in \mathbf{f}_{patho} is 0.5.

As mentioned in the article, 0.5 can be interpreted as an incomplete activation/inhibition depending on what is modeled. Consequently, in the pathological variant, the activator is at most partly inhibited by the locker when no energy is available, allowing the task to be nonetheless performed. However, in this case, the task is itself moderately performed.

8.1 Attractor sets

The example network is computed asynchronously on a subset of 1 000 randomly selected initial states using 3-valued logic. The length max_k of the random walks is set to 1 000 steps. Below are the computed attractors:

- A_{physio} :

attractor	basin (% of S_{physio})	do	$factory$	$energy$	$locker$	$task$
$a_{physio1}$	6.1%	0	0	0	1	0
$a_{physio2}$	4.5%	0	0	0.5	0.5	0
$a_{physio3}$	2.5%	0	0	1	0	0
$a_{physio4}$	9.7%	0	0.5	0.5	0.5	0
$a_{physio5}$	1.8%	0	0.5	1	0	0
$a_{physio6}$	10.8%	0	1	1	0	0
$a_{physio7}$	6.5%	0.5	0	0	1	0
$a_{physio8}$	4.8%	0.5	0	0.5	0.5	0.5
$a_{physio9}$	10.3%	0.5	0.5	0.5	0.5	0.5
$a_{physio10}$	10.6%	0.5	1	1	0	0.5
$a_{physio11}$	7.3%	1	0	0	1	0
$a_{physio12}$	3.2%	1	0	0.5	0.5	0.5
$a_{physio13}$	10.3%	1	0.5	0.5	0.5	0.5
$a_{physio14}$	11.6%	1	1	1	0	1

- A_{patho} :

attractor	basin (% of S_{patho})	do	$factory$	$energy$	$locker$	$task$
a_{patho1}	6.2%	0	0	0	0.5	0
$a_{physio2}$	4.7%	0	0	0.5	0.5	0
$a_{physio3}$	2.2%	0	0	1	0	0
$a_{physio4}$	9.7%	0	0.5	0.5	0.5	0
$a_{physio5}$	1.8%	0	0.5	1	0	0
$a_{physio6}$	10.8%	0	1	1	0	0
a_{patho2}	5.5%	0.5	0	0	0.5	0.5
$a_{physio8}$	5.8%	0.5	0	0.5	0.5	0.5
$a_{physio9}$	10.3%	0.5	0.5	0.5	0.5	0.5
$a_{physio10}$	10.6%	0.5	1	1	0	0.5
a_{patho3}	7.3%	1	0	0	0.5	0.5
$a_{physio12}$	3.2%	1	0	0.5	0.5	0.5
$a_{physio13}$	10.3%	1	0.5	0.5	0.5	0.5
$a_{physio14}$	11.6%	1	1	1	0	1

$a_{physio1}$, $a_{physio3}$, $a_{physio6}$, $a_{physio11}$ and $a_{physio14}$ are the physiological attractors found in the Boolean case, with a different numbering due to additional attractors coming from multivalued logic. Given that $\{0, 1\} \subset \{0, 0.5, 1\}$ and that the Zadeh operators also work with Boolean logic, the Boolean results are still obtainable. The same does not apply to the pathological attractors because f_{locker} in f_{patho} differs between the Boolean and multivalued cases.

For example, $a_{physio13}$ indicates that the do instruction is sent while energy is partly supplied. Consequently, the locker is partly activated resulting in a partial inhibition of the activator. The task is thus moderately performed despite full do instruction, hence coping with moderate energy supply.

Concerning the pathological attractors, as an example, a_{patho3} indicates that the do instruction is sent in absence of energy supply. Consequently, the locker should be fully activated to prevent the task. However, due to some pathological defects, the locker is at most partly activated. The task is then performed in absence of energy. However, since the locker is partly operational, the task is not performed at its maximum rate, maybe limiting pathological consequences.

Among the pathological attractors, a_{patho1} can be considered weakly pathological. Indeed, in a_{patho1} the locker should be fully activated since there is no energy. However, there is no do instruction and thus no task to stop. On the other hand, a_{patho2} and a_{patho3} are more pathological since the task is performed while no energy is available.

8.2 Therapeutic bullets

All the bullets made of one to two targets are tested with a threshold of 5%. Below are the returned therapeutic bullets:

- 1-therapeutic bullets:

bullet	gain		$B_{physio1}$	$B_{physio2}$	$B_{physio3}$	$B_{physio4}$	$B_{physio5}$	$B_{physio6}$	$B_{physio7}$	$B_{physio8}$	$B_{physio9}$
			$B_{physio10}$	$B_{physio11}$	$B_{physio12}$	$B_{physio13}$	$B_{physio14}$	B_{patho1}	B_{patho2}	B_{patho3}	
<i>factory</i> [0.5]	81%	→ 100%	0%	0%	0%	29.3%	6.1%	0%	0%	0%	32.2%
<i>factory</i> [1]	81%	→ 100%	0%	0%	0%	0%	0%	0%	0%	0%	0%
			32.2%	0%	0%	0%	32.4%	35.4%	0%	0%	0%

- 2-therapeutic bullets:

bullet	gain		$B_{physio1}$	$B_{physio2}$	$B_{physio3}$	$B_{physio4}$	$B_{physio5}$	$B_{physio6}$	$B_{physio7}$	$B_{physio8}$	$B_{physio9}$
			$B_{physio10}$	$B_{physio11}$	$B_{physio12}$	$B_{physio13}$	$B_{physio14}$	B_{patho1}	B_{patho2}	B_{patho3}	
<i>do</i> [0] <i>factory</i> [0.5]	81%	→ 100%	0%	0%	0%	84%	16%	0%	0%	0%	0%
<i>do</i> [0] <i>factory</i> [1]	81%	→ 100%	0%	0%	0%	0%	0%	100%	0%	0%	0%
<i>do</i> [0.5] <i>factory</i> [0.5]	81%	→ 100%	0%	0%	0%	0%	0%	0%	0%	0%	100%
<i>do</i> [0.5] <i>factory</i> [1]	81%	→ 100%	0%	0%	0%	0%	0%	0%	0%	0%	0%
<i>do</i> [1] <i>factory</i> [0.5]	81%	→ 100%	0%	0%	0%	0%	0%	0%	0%	0%	0%
<i>do</i> [1] <i>factory</i> [1]	81%	→ 100%	0%	0%	0%	0%	0%	0%	0%	0%	0%
<i>do</i> [0] <i>energy</i> [1]	81%	→ 100%	0%	0%	34.9%	0%	32.1%	33%	0%	0%	0%
<i>do</i> [0] <i>task</i> [0]	81%	→ 89%	0%	11.6%	12.3%	21.3%	10.8%	33%	0%	0%	0%
<i>do</i> [0.5] <i>task</i> [0.5]	81%	→ 89.4%	0%	0%	0%	0%	0%	0%	0%	24.3%	32.1%
<i>factory</i> [0] <i>energy</i> [0.5]	81%	→ 100%	0%	35.4%	0%	0%	0%	0%	0%	32.2%	0%
<i>factory</i> [0.5] <i>energy</i> [0.5]	81%	→ 100%	0%	0%	32.4%	0%	0%	0%	0%	0%	32.2%
<i>factory</i> [1] <i>energy</i> [1]	81%	→ 100%	0%	0%	0%	0%	0%	35.4%	0%	0%	0%
<i>factory</i> [1] <i>locker</i> [0]	81%	→ 100%	32.2%	0%	0%	0%	32.4%	0%	0%	0%	0%
			0%	0%	0%	0%	32.4%	35.4%	0%	0%	0%

For example, the therapeutic bullet *factory*[1] *locker*[0] is interesting. It suppresses all the pathological attractors while maintaining three physiological attractors allowing the pathological variant to properly respond to the three possible levels of the *do* instruction. Moreover, the basins of these three physiological attractors, namely $a_{physio6}$, $a_{physio10}$ and $a_{physio14}$, equally span the state space, making them equally reachable.

On the other hand, the therapeutic bullet *do*[0.5] *factory*[0.5] seems to be less interesting. While this bullet also suppresses all the pathological attractors, it enables only one physiological attractor. In this physiological attractor, namely $a_{physio9}$, all the variables are at their intermediate level: the network can not fulfill its switching function.

9 Appendix 3: core of kali

Below is the core of kali in pseudocode derived from its Go [30] sources, freely available on GitHub at <https://github.com/arnaudporet/kali> under the GNU General Public License [32]. Note that the source code may have evolved since the publication of the present article.

9.1 Defined types

```
structure Attractor // an attractor
  field Name // its name, either  $a_{physio}$  or  $a_{patho}$ 
  field Basin // the size of its basin, in percents of the state space
  field States // its states, as a matrix of one state per row
end structure
```

```
structure Bullet // a bullet
  field Targ // its target combination, as a vector
  field Moda // its modality arrangement, as a vector
  field Gain // its gain, see below
  field Cover // the size of each basin under its influence, see below
end structure
```

$b.Gain$ is a vector $(gain_1, gain_2)$ where:

- $gain_1$ is the size of $\bigcup B_{physio,i}$ in S_{patho}
- $gain_2$ is the size of $\bigcup B_{physio,i}$ in S_{test}

in % of S_{patho} and % of S_{test} respectively.

$b.Cover$ is a vector containing the size of the physiological and pathological basins in the testing state space, in percents of it.

9.2 Parameters

```
nodes // the node names, as a vector
 $\Omega$  // the domain of the used logic, as a vector
sync // use synchronous updating ( $sync = 1$ ) or not ( $sync = 0$ )
whole // build the whole state space ( $whole = 1$ ) or not ( $whole = 0$ )
 $max_S$  // the maximal size of the state space sample when  $whole = 0$ 
 $max_k$  // the number of steps for the random walks (asynchronous only)
 $n_{targ}$  // the number of targets per bullet
 $max_{targ}$  // the maximum number of target combinations to test
 $max_{moda}$  // the maximum number of modality arrangements to test
 $\delta$  // the threshold for a bullet to be therapeutic, in percents of the state space
```

To be considered therapeutic, a bullet has to make $gain_2 - gain_1 \geq \delta$ while not creating *de novo* attractors.

9.3 Functions

```

function DoTheJob( $f_{physio}, f_{patho}, n_{targ}, max_{targ}, max_{moda}, max_S, max_k, \delta,$ 
   $sync, nodes, \Omega, whole$ )
  // do the job, this is the main function
   $n \leftarrow Size(nodes)$  // the dimension of the state space  $S$ 
  select  $whole$ 
    case 0 // build a sample of  $S$ 
       $S \leftarrow GenArrangs(\Omega, n, max_S)$ 
    case 1 // build all  $S$ 
       $S \leftarrow GenSpace(\Omega, n)$ 
  end select
   $A_{physio} \leftarrow ComputeAttractorSet(f_{physio}, S, \emptyset, max_k, 0, sync, \emptyset)$ 
   $A_{patho} \leftarrow ComputeAttractorSet(f_{patho}, S, \emptyset, max_k, 1, sync, A_{physio})$ 
   $A_{versus} \leftarrow GetVersus(A_{patho})$  // the pathological attractors, see below
   $C_{targ} \leftarrow GenCombis(\{1, \dots, n\}, n_{targ}, max_{targ})$  // the target combinations
   $C_{moda} \leftarrow GenArrangs(\Omega, n_{targ}, max_{moda})$  // the modality arrangements
  if  $A_{versus} \neq \emptyset$  // there are pathological basins to shrink
     $B_{therap} \leftarrow ComputeTherapeuticBullets(f_{patho}, S, C_{targ}, C_{moda}, max_k,$ 
       $\delta, sync, A_{physio}, A_{patho}, A_{versus})$  // therapeutic bullets
  end if
  return  $S, A_{physio}, A_{patho}, A_{versus}, C_{targ}, C_{moda}, B_{therap}$ 
end function

```

$Size(container)$ returns the number of items in $container$.

$GenSpace(\Omega, n)$ returns the n -dimensional state space of the vectors made of n values from Ω , as a matrix of one state vector per row.

$GenArrangs(\Omega, n, max_{arrang})$ returns max_{arrang} arrangements with repetition made of n elements from Ω , as a matrix of one arrangement per row. If max_{arrang} exceeds its maximal possible value then it is automatically decreased to its maximal possible value.

$GenCombis(\Omega, n, max_{combi})$ returns max_{combi} combinations without repetition made of n elements from Ω , as a matrix of one combination per row. If max_{combi} exceeds its maximal possible value then it is automatically decreased to its maximal possible value.

As explained later, the function $ComputeAttractorSet$ can use an already computed attractor set, namely the reference set, to name the attractors.

A_{physio} is computed without bullet ($b \leftarrow \emptyset$), without reference set ($A_{ref} \leftarrow \emptyset$) and with the physiological setting ($setting \leftarrow 0$).

A_{patho} is computed without bullet ($b \leftarrow \emptyset$), with a reference set ($A_{ref} \leftarrow A_{physio}$) and with the pathological setting ($setting \leftarrow 1$).

A_{versus} is not a true attractor set but the set containing the pathological attractors: $A_{versus} \subset A_{patho}$. A_{patho} can contains physiological attractors if the pathological variant exhibits some of them. However, A_{versus} only contains the

pathological attractors.

Therapeutic bullets are computed only if there are pathological basins to shrink, namely only if $A_{versus} \neq \emptyset$.

Note that target combinations are combinations of positions in the state vector: targets are identified by their position in the state vector, not by their name.

```
function  $f_{physio}(x)$ 
  // update the state vector of the physiological variant
   $y[1] \leftarrow f_{physio}[1](x)$  // update  $x_1$  with  $f_{physio,1}$ 
  :
   $y[n] \leftarrow f_{physio}[n](x)$  // update  $x_n$  with  $f_{physio,n}$ 
  return  $y$  // the updated state vector
end function
```

```
function  $f_{patho}(x)$ 
  // update the state vector of the pathological variant
   $y[1] \leftarrow f_{patho}[1](x)$  // update  $x_1$  with  $f_{patho,1}$ 
  :
   $y[n] \leftarrow f_{patho}[n](x)$  // update  $x_n$  with  $f_{patho,n}$ 
  return  $y$  // the updated state vector
end function
```

```
function  $ComputeAttractor(f, x_0, b, max_k, sync)$ 
  // from  $x_0$ , reach an attractor  $a$ 
  select  $sync$ 
    case 1 // search a cycle
       $a.States \leftarrow ReachCycle(f, x_0, b)$ 
    case 0 // search a terminal SCC
      for
         $a.States \leftarrow GoForward(f, Walk(f, x_0, b, max_k), b)$  // a candidate
        if  $IsTerminal(a, f, b)$  // the candidate attractor is a terminal SCC
          break // then it is an asynchronous attractor
        end if
      end for
    end select
  return  $a$ 
end function
```

```
function  $ComputeAttractorSet(f, S, b, max_k, setting, sync, A_{ref})$ 
  // compute an attractor set  $A$ , namely  $A_{physio}$ ,  $A_{patho}$  or  $A_{test}$ 
   $A \leftarrow \{\}$ 
  select  $setting$  // select the default name for attractors
    case 0 // physiological setting
       $name \leftarrow a_{physio}$ 
    case 1 // pathological setting
       $name \leftarrow a_{patho}$ 
```

```

end select
for  $i \leftarrow 1, \dots, \text{Size}(S)$  // browse  $S$ 
   $a \leftarrow \text{ComputeAttractor}(f, S[i], b, \text{max}_k, \text{sync})$ 
  if  $\exists i_A : A[i_A] = a$  //  $a$  is already found
     $A[i_A].\text{Basin} \leftarrow A[i_A].\text{Basin} + 1$  // then increase its basin
  else // new attractor
     $a.\text{Basin} \leftarrow 1$  // then begin its basin
     $A \leftarrow A \cup \{a\}$  // and add it to the attractor set
  end if
end for
for  $i \leftarrow 1, \dots, \text{Size}(A)$  // browse  $A$ 
   $A[i].\text{Basin} \leftarrow 100 \cdot A[i].\text{Basin} / \text{Size}(S)$  // translate basins to % of  $S$ 
end for
return  $\text{SetNames}(A, \text{name}, A_{\text{ref}})$  // return named attractors, see later
end function

```

```

function  $\text{ComputeTherapeuticBullets}(f_{\text{patho}}, S, C_{\text{targ}}, C_{\text{moda}}, \text{max}_k, \delta, \text{sync},$ 
   $A_{\text{physio}}, A_{\text{patho}}, A_{\text{versus}})$ 
  // compute a set  $B_{\text{therap}}$  of therapeutic bullets
   $B_{\text{therap}} \leftarrow \{\}$ 
   $b.\text{Gain}[1] \leftarrow \text{Sum}(\text{GetCover}(A_{\text{physio}}, A_{\text{patho}})) // \cup B_{\text{physio},i}$  in  $S_{\text{patho}}$ 
  for  $i_1 \leftarrow 1, \dots, \text{Size}(C_{\text{targ}})$  // browse the target combinations to test
    for  $i_2 \leftarrow 1, \dots, \text{Size}(C_{\text{moda}})$  // browse the modality arrangements to test
       $b.\text{Targ} \leftarrow C_{\text{targ}}[i_1]$  // the target combination to test
       $b.\text{Moda} \leftarrow C_{\text{moda}}[i_2]$  // the modality arrangement to test
       $A_{\text{test}} \leftarrow \text{ComputeAttractorSet}(f_{\text{patho}}, S, b, \text{max}_k, 1, \text{sync}, A_{\text{physio}})$ 
       $b.\text{Gain}[2] \leftarrow \text{Sum}(\text{GetCover}(A_{\text{physio}}, A_{\text{test}})) // \cup B_{\text{physio},i}$  in  $S_{\text{test}}$ 
      if  $\text{IsTherapeutic}(b, A_{\text{test}}, A_{\text{versus}}, \delta)$  //  $b$  is therapeutic
         $b.\text{Cover} \leftarrow \text{GetCover}(A_{\text{physio}} \cup A_{\text{versus}}, A_{\text{test}})$  // basins in  $S_{\text{test}}$ 
         $B_{\text{therap}} \leftarrow B_{\text{therap}} \cup \{b\}$  // add  $b$  to the set of therapeutic bullets
      end if
    end for
  end for
  return  $B_{\text{therap}}$ 
end function

```

$\text{Sum}(\text{container})$ returns the sum of the items in container .

```

function  $\text{GetCover}(A_1, A_2)$ 
  // get the size of the  $B_{1,i}$  in  $S_2$ , in % of  $S_2$ 
   $\text{cover} \leftarrow ()$ 
  for  $i_1 \leftarrow 1, \dots, \text{Size}(A_1)$  // browse the attractors of  $A_1$ 
    if  $\exists i_2 : A_2[i_2] = A_1[i_1]$  //  $A_1[i_1]$  also in  $A_2$ 
       $\text{cover} \leftarrow \text{Append}(\text{cover}, A_2[i_2].\text{Basin})$  // get the size of  $B_{1,i_1}$  in  $S_2$ 
    else //  $A_1[i_1]$  not in  $A_2$ 
       $\text{cover} \leftarrow \text{Append}(\text{cover}, 0)$  // then  $B_{1,i_1}$  is empty in  $S_2$ 
    end if
  end for
  return  $\text{cover}$ 
end function

```

Append(container, item) returns *container* with *item* added to it.

```

function GetVersus( $A_{patho}$ )
  // get the pathological attractors
   $A_{versus} \leftarrow \{\}$  // the set of the pathological attractors
  for  $i \leftarrow 1, \dots, Size(A_{patho})$  // browse the attractors of  $A_{patho}$ 
    if IsSubString( $A_{patho}[i].Name, patho$ ) // not a physiological attractor
       $A_{versus} \leftarrow A_{versus} \cup \{A_{patho}[i]\}$  // then add it to  $A_{versus}$ 
    end if
  end for
  return  $A_{versus}$ 
end function

```

IsSubString(s_1, s_2) returns *true* if s_2 is a substring of s_1 .

Remember that A_{versus} is not a true attractor set but the set containing the pathological attractors: $A_{versus} \subset A_{patho}$.

```

function GoForward( $f, x_0, b$ )
  // compute the forward reachable set fwd of  $x_0$  (asynchronous only)
   $fwd \leftarrow \{x_0\}$  // fwd contains  $x_0$  itself
   $stack \leftarrow (x_0)$  // the stack of the visited states
  for
     $x \leftarrow stack[Size(stack)]$  // get the last stack element
     $stack \leftarrow stack[1, \dots, Size(stack) - 1]$  // remove the last stack element
     $y \leftarrow f(x)$  // prepare all the updated  $x_i$ 
    for  $i \leftarrow 1, \dots, Size(y)$  // browse the updated  $x_i$ 
       $z \leftarrow x$  // copy  $x$  to preserve its original value
       $z[i] \leftarrow y[i]$  // update only one  $x_i$ 
       $z \leftarrow Shoot(z, b)$  // apply the bullet
      if  $z \notin fwd$  // new state
         $fwd \leftarrow fwd \cup \{z\}$  // then add it to fwd
         $stack \leftarrow Append(stack, z)$  // and add it to the visited states
      end if
    end for
  if  $Size(stack) = 0$  // no new states to visit
    break // so the complete fwd is obtained
  end if
  end for
  return fwd
end function

```

```

function IsTerminal( $a, f, b$ )
  // check if a candidate attractor  $a$  is a terminal SCC (asynchronous only)
  for  $i \leftarrow 1, \dots, Size(a.States)$  // browse the states of  $a$ 
    if GoForward( $f, a.States[i], b$ )  $\neq a.States$  //  $fwd_i \neq a$ 
      return false // then not a terminal SCC
    end if
  end for

```

```

    return true // assumed to be a terminal SCC until proven otherwise
end function

```

```

function IsTherapeutic( $b, A_{test}, A_{versus}, \delta$ )
    // check if a bullet  $b$  is therapeutic
    if  $b.Gain[2] - b.Gain[1] \geq \delta$  // maybe therapeutic
        for  $i \leftarrow 1, \dots, Size(A_{test})$  // browse the attractors of  $A_{test}$ 
            if  $IsSubString(A_{test}[i].Name, patho) \wedge A_{test}[i] \notin A_{versus}$ 
                return false // because of a de novo attractor
            end if
        end for
        return true // assumed to be therapeutic until proven otherwise
    else
        return false // below the therapeutic threshold
    end if
end function

```

```

function ReachCycle( $f, x_0, b$ )
    // compute the cycle reachable from  $x_0$  (synchronous only)
    cycle  $\leftarrow (x_0)$  // begin the trajectory
     $x \leftarrow x_0$ 
    for
         $x \leftarrow Shoot(f(x), b)$  // update and apply the bullet
        if  $\exists i : cycle[i] = x$  // cycle found in the trajectory
            cycle  $\leftarrow cycle[i, \dots, Size(cycle)]$  // then extract the cycle
            break // mission completed
        else // cycle not yet reached
            cycle  $\leftarrow Append(cycle, x)$  // then pursue the trajectory
        end if
    end for
    return cycle
end function

```

```

function SetNames( $A, name, A_{ref}$ )
    // name the attractors of  $A$  according to  $A_{ref}$ , default to  $name$ 
     $y \leftarrow A$  // copy  $A$  to return a copy
     $k \leftarrow 1$  // initiate the default name numbering
    for  $i \leftarrow 1, \dots, Size(A)$  // browse the attractors of  $A$ 
        if  $\exists i_{ref} : A_{ref}[i_{ref}] = A[i]$  //  $A[i]$  found in  $A_{ref}$ 
             $y[i].Name \leftarrow A_{ref}[i_{ref}].Name$  // then get its name in  $A_{ref}$ 
        else //  $A[i]$  not in  $A_{ref}$ 
             $y[i].Name \leftarrow CatStrings(name, ToString(k))$  // default name
             $k \leftarrow k + 1$  // and increment the default name numbering
        end if
    end for
    return  $y$ 
end function

```

$CatStrings(s_1, s_2)$ returns the concatenation of s_1 and s_2 .

ToString(item) returns the string corresponding to *item*.

This function names the attractors of *A* according to a reference set *A_{ref}*. If an attractor of *A* also belongs to *A_{ref}* then its name in *A_{ref}* is used, otherwise the default name, numbered with *k*, is used.

```
function Shoot(x, b)
  // apply a bullet on a state
  y ← x // copy x to return a copy
  for i ← 1, ..., Size(b.Targ) // browse the targets
    y[b.Targ[i]] ← b.Moda[i] // apply the corresponding modality
  end for
  return y
end function
```

Remember that targets are identified by their position in the state vector, not by their name.

```
function Walk(f, x0, b, maxk)
  // perform a random walk of maxk steps from x0 (asynchronous only)
  x ← x0 // start the walk
  for k ← 1, ..., maxk // for maxk steps
    y ← f(x) // prepare all the updated xi
    i ← RandInt(1, Size(x)) // randomly choose one xi
    x[i] ← y[i] // then update the chosen xi
    x ← Shoot(x, b) // and apply the bullet
  end for
  return x
end function
```

RandInt(a, b) returns a randomly selected integer between *a* and *b* according to a uniform distribution.

10 Appendix 4: case study equations

Below are the 27 Boolean equations of the case study derived from the model of bladder tumorigenesis by Elisabeth Remy and colleagues [17]. These equations are also available in text format in the supporting file `bladder_equations.txt`. A network-based representation is shown in Figure 2 page 11.

$$\begin{aligned}
AKT &= PI3K \\
ATM_{lv11} &= DNAdamage \wedge \neg E2F1_{lv11} \wedge \neg E2F1_{lv12} \\
ATM_{lv12} &= (E2F1_{lv11} \vee E2F1_{lv12}) \wedge DNAdamage \\
CDC25A &= \neg CHEK1/2_{lv11} \wedge \neg CHEK1/2_{lv12} \wedge \neg RBL2 \\
&\quad \wedge (E2F1_{lv11} \vee E2F1_{lv12} \vee E2F3_{lv11} \vee E2F3_{lv12}) \\
CHEK1/2_{lv11} &= (ATM_{lv11} \vee ATM_{lv12}) \wedge \neg E2F1_{lv11} \wedge \neg E2F1_{lv12} \\
CHEK1/2_{lv12} &= (E2F1_{lv11} \vee E2F1_{lv12}) \wedge (ATM_{lv11} \vee ATM_{lv12}) \\
CyclinA &= \neg RBL2 \wedge \neg p21CIP \wedge CDC25A \\
&\quad \wedge (E2F1_{lv11} \vee E2F1_{lv12} \vee E2F3_{lv11} \vee E2F3_{lv12}) \\
CyclinD1 &= (RAS \vee AKT) \wedge \neg p16INK4a \wedge \neg p21CIP \\
CyclinE1 &= \neg RBL2 \wedge \neg p21CIP \wedge CDC25A \\
&\quad \wedge (E2F1_{lv11} \vee E2F1_{lv12} \vee E2F3_{lv11} \vee E2F3_{lv12}) \\
E2F1_{lv11} &= \neg RB1 \wedge \neg RBL2 \wedge ((CHEK1/2_{lv12} \wedge ATM_{lv12} \wedge \neg RAS \wedge E2F3_{lv11}) \\
&\quad \vee ((\neg CHEK1/2_{lv12} \vee \neg ATM_{lv12}) \wedge (RAS \vee E2F3_{lv11} \vee E2F3_{lv12}))) \\
E2F1_{lv12} &= \neg RBL2 \wedge \neg RB1 \wedge ATM_{lv12} \wedge CHEK1/2_{lv12} \wedge (RAS \vee E2F3_{lv12}) \\
E2F3_{lv11} &= \neg RB1 \wedge \neg CHEK1/2_{lv12} \wedge RAS \\
E2F3_{lv12} &= \neg RB1 \wedge CHEK1/2_{lv12} \wedge RAS \\
EGFR &= (EGFRstimulus \vee SPRY) \wedge \neg FGFR3 \wedge \neg GRB2 \\
FGFR3 &= \neg EGFR \wedge FGFR3stimulus \wedge \neg GRB2 \\
GRB2 &= (FGFR3 \wedge \neg GRB2 \wedge \neg SPRY) \vee EGFR \\
MDM2 &= (TP53 \vee AKT) \wedge \neg p14ARF \wedge \neg ATM_{lv11} \wedge \neg ATM_{lv12} \wedge \neg RB1 \\
p14ARF &= E2F1_{lv11} \vee E2F1_{lv12} \\
p16INK4a &= GrowthInhibitors \wedge \neg RB1 \\
p21CIP &= \neg CyclinE1 \wedge (GrowthInhibitors \vee TP53) \wedge \neg AKT \\
PI3K &= GRB2 \wedge RAS \wedge \neg PTEN \\
PTEN &= TP53 \\
RAS &= EGFR \vee FGFR3 \vee GRB2 \\
RB1 &= \neg CyclinD1 \wedge \neg CyclinE1 \wedge \neg p16INK4a \wedge \neg CyclinA \\
RBL2 &= \neg CyclinD1 \wedge \neg CyclinE1 \\
SPRY &= RAS \\
TP53 &= \neg MDM2 \wedge (E2F1_{lv12} \vee ((ATM_{lv11} \vee ATM_{lv12}) \\
&\quad \wedge (CHEK1/2_{lv11} \vee CHEK1/2_{lv12})))
\end{aligned}$$

The four inputs are *EGFRstimulus*, *FGFR3stimulus*, *GrowthInhibitors* and *DNAdamage*. The three outputs are evaluated from the returned attractors once the run terminated according to their respective equation:

Proliferation = *CyclinE1* \vee *CyclinA*
GrowthArrest = *p21CIP* \vee *RB1* \vee *RBL2*
Apoptosis = *TP53* \vee *E2F1_{tot2}*

References

- [1] Arnaud Poret and Jean-Pierre Boissel. An *in silico* target identification using boolean network attractors: avoiding pathological phenotypes. *Comptes Rendus Biologies*, 337(12):661–678, 2014.
- [2] Nicolas Le Novère. Quantitative and logic modelling of molecular and gene networks. *Nature Reviews Genetics*, 16(3):146–158, 2015.
- [3] Michelle L Wynn, Nikita Consul, Sofia D Merajver, and Santiago Schnell. Logic-based models in systems biology: a predictive and parameter-free network analysis method. *Integrative Biology*, 4(11):1323–1337, 2012.
- [4] Melody K Morris, Julio Saez-Rodriguez, Peter K Sorger, and Douglas A Lauffenburger. Logic-based models for the analysis of cell signaling networks. *Biochemistry*, 49(15):3216–3224, 2010.
- [5] Reka Albert and Juilee Thakar. Boolean modeling: a logic-based dynamic approach for understanding signaling and regulatory networks and for making useful predictions. *Wiley Interdisciplinary Reviews: Systems Biology and Medicine*, 6(5):353–369, 2014.
- [6] Rui-Sheng Wang, Assieh Saadatpour, and Reka Albert. Boolean modeling in systems biology: an overview of methodology and applications. *Physical Biology*, 9(5):055001, 2012.
- [7] Johannes Jaeger and Nick Monk. Bioattractors: dynamical systems theory and the evolution of regulatory processes. *The Journal of Physiology*, 592(11):2267–2281, 2014.
- [8] Sung-Hwan Cho, Sang-Min Park, Ho-Sung Lee, Hwang-Yeol Lee, and Kwang-Hyun Cho. Attractor landscape analysis of colorectal tumorigenesis and its reversion. *BMC Systems Biology*, 10(1):96, 2016.
- [9] Xiao Gan and Reka Albert. Analysis of a dynamic model of guard cell signaling reveals the stability of signal propagation. *BMC Systems Biology*, 10(1):78, 2016.
- [10] Jose Davila-Velderrain, Juan C Martinez-Garcia, and Elena R Alvarez-Buylla. Modeling the epigenetic attractors landscape: toward a post-genomic mechanistic understanding of development. *Frontiers in Genetics*, 6:160, 2015.
- [11] Isaac Crespo, Thanneer M Perumal, Wiktor Jurkowski, and Antonio Del Sol. Detecting cellular reprogramming determinants by differential stability analysis of gene regulatory networks. *BMC Systems Biology*, 7(1):1, 2013.
- [12] Herman F Fumia and Marcelo L Martins. Boolean network model for cancer pathways: predicting carcinogenesis and targeted therapy outcomes. *PloS One*, 8(7):e69008, 2013.
- [13] Wei-Yi Cheng, Tai-Hsien Ou Yang, and Dimitris Anastassiou. Biomolecular events in cancer revealed by attractor metagenes. *PLoS Computational Biology*, 9(2):e1002920, 2013.

- [14] Pau Creixell, Erwin M Schoof, Janine T Erler, and Rune Linding. Navigating cancer network attractors for tumor-specific therapy. *Nature Biotechnology*, 30(9):842–848, 2012.
- [15] MK Morris, DC Clarke, LC Osimiri, and DA Lauffenburger. Systematic analysis of quantitative logic model ensembles predicts drug combination effects on cell signaling networks. *CPT: Pharmacometrics & Systems Pharmacology*, 2016.
- [16] Hyunho Chu, Daewon Lee, and Kwang-Hyun Cho. Precritical state transition dynamics in the attractor landscape of a molecular interaction network underlying colorectal tumorigenesis. *PLoS One*, 10(10):e0140172, 2015.
- [17] Elisabeth Remy, Sandra Rebouissou, Claudine Chaouiya, Andrei Zinovyev, Francois Radvanyi, and Laurence Calzone. A modeling approach to explain mutually exclusive and co-occurring genetic alterations in bladder tumorigenesis. *Cancer Research*, 75(19):4042–4052, 2015.
- [18] Abhishek Garg, Alessandro Di Cara, Ioannis Xenarios, Luis Mendoza, and Giovanni De Micheli. Synchronous versus asynchronous modeling of gene regulatory networks. *Bioinformatics*, 24(17):1917–1925, 2008.
- [19] Tamas Szekely and Kevin Burrage. Stochastic simulation in systems biology. *Computational and Structural Biotechnology Journal*, 12(20):14–25, 2014.
- [20] Marcello Buiatti and Giuseppe Longo. Randomness and multilevel interactions in biology. *Theory in Biosciences*, 132(3):139–158, 2013.
- [21] Mukhtar Ullah and Olaf Wolkenhauer. Stochastic approaches in systems biology. *Wiley Interdisciplinary Reviews: Systems Biology and Medicine*, 2(4):385–397, 2010.
- [22] German Rivas and Allen P Minton. Macromolecular crowding *in vitro*, *in vivo*, and in between. *Trends in Biochemical Sciences*, 2016.
- [23] Nicholas Rescher. *Many-valued logic*. Springer, 1968.
- [24] The r project for statistical computing. <https://www.r-project.org>.
- [25] Christoph Mussel, Martin Hopfensitz, and Hans A Kestler. Boolnet—an r package for generation, reconstruction and analysis of boolean networks. *Bioinformatics*, 26(10):1378–1380, 2010.
- [26] Assieh Saadatpour, Istvan Albert, and Reka Albert. Attractor analysis of asynchronous boolean models of signal transduction networks. *Journal of Theoretical Biology*, 266(4):641–656, 2010.
- [27] Lotfi A Zadeh. Fuzzy sets. *Information and Control*, 8(3):338–353, 1965.
- [28] Paul Cairns, Kaori Tokino, Yolanda Eby, and David Sidransky. Homozygous deletions of 9p21 in primary human bladder tumors detected by comparative multiplex polymerase chain reaction. *Cancer Research*, 54(6):1422–1424, 1994.

- [29] Joshua J Meeks, Benedito A Carneiro, Sachin G Pai, Daniel T Oberlin, Alfred Rademaker, Kyle Fedorchak, Sohail Balasubramanian, Julia Elvin, Nike Beaubier, and Francis J Giles. Genomic characterization of high-risk non-muscle invasive bladder cancer. *Oncotarget*, 7(46):75176, 2016.
- [30] The go programming language. <https://golang.org>.
- [31] Arch linux, a lightweight and flexible linux distribution. <https://www.archlinux.org>.
- [32] The gnu general public license. <https://www.gnu.org/licenses/gpl.html>.
- [33] Evangelia Koutsogiannouli, Athanasios G Papavassiliou, and Nikolaos A Papanikolaou. Complexity in cancer biology: is systems biology the answer? *Cancer Medicine*, 2(2):164–177, 2013.
- [34] Christof Koch. Modular biological complexity. *Science*, 337(6094):531–532, 2012.
- [35] S Yu Jessica and Neda Bagheri. Multi-class and multi-scale models of complex biological phenomena. *Current Opinion in Biotechnology*, 39:167–173, 2016.
- [36] Joseph Walpole, Jason A Papin, and Shayn M Peirce. Multiscale computational models of complex biological systems. *Annual Review of Biomedical Engineering*, 15:137–154, 2013.
- [37] Jasmin Fisher and Nir Piterman. The executable pathway to biological networks. *Briefings in Functional Genomics*, 9(1):79–92, 2010.
- [38] EO Voit, Z Qi, and GW Miller. Steps of modeling complex biological systems. *Pharmacopsychiatry*, 41(S 01):S78–S84, 2008.
- [39] Hans Peter Fischer. Mathematical modeling of complex biological systems: from parts lists to understanding systems behavior. *Alcohol Research & Health*, 31(1):49, 2008.
- [40] Christos G Mihos, Andres M Pineda, and Orlando Santana. Cardiovascular effects of statins, beyond lipid-lowering properties. *Pharmacological Research*, 88:12–19, 2014.
- [41] C Mary Schooling, Shiu Lun Au Yeung, and Gabriel M Leung. Why do statins reduce cardiovascular disease more than other lipid modulating therapies? *European Journal of Clinical Investigation*, 44(11):1135–1140, 2014.
- [42] Ingrid A Mayer and Carlos L Arteaga. The pi3k/akt pathway as a target for cancer treatment. *Annual Review of Medicine*, 67:11–28, 2016.
- [43] Tao Shen and Shile Huang. The role of cdc25a in the regulation of cell proliferation and apoptosis. *Anti-Cancer Agents in Medicinal Chemistry*, 12(6):631–639, 2012.
- [44] Antonio Lavecchia, Carmen Di Giovanni, and Ettore Novellino. Cdc25a and b dual-specificity phosphatase inhibitors: potential agents for cancer therapy. *Current Medicinal Chemistry*, 16(15):1831–1849, 2009.

- [45] Xundi Xu, Hirofumi Yamamoto, Guoxing Liu, Yasuhiro Ito, Chew Yee Ngan, Motoi Kondo, Hiroaki Nagano, Keizo Dono, Mitsugu Sekimoto, and Morito Monden. Cdc25a inhibition suppresses the growth and invasion of human hepatocellular carcinoma cells. *International Journal of Molecular Medicine*, 21(2):145–152, 2008.
- [46] Siddhartha Kar, Meifang Wang, Wei Yao, Christopher J Michejda, and Brian I Carr. Pm-20, a novel inhibitor of cdc25a, induces extracellular signal-regulated kinase 1/2 phosphorylation and inhibits hepatocellular carcinoma growth *in vitro* and *in vivo*. *Molecular Cancer Therapeutics*, 5(6):1511–1519, 2006.
- [47] Sherif AF Rostom, Mona H Badr, Heba A Abd El Razik, and Hayam MA Ashour. Structure-based development of novel triazoles and related thiazolotriazoles as anticancer agents and cdc25a/b phosphatase inhibitors. synthesis, *in vitro* biological evaluation, molecular docking and *in silico* adme-t studies. *European Journal of Medicinal Chemistry*, 139:263–279, 2017.
- [48] Samar Masoumi-Moghaddam, Afshin Amini, and David Lawson Morris. The developing story of sprouty and cancer. *Cancer and Metastasis Reviews*, 33(2-3):695–720, 2014.
- [49] Shaomeng Wang, Yujun Zhao, Angelo Aguilar, Denzil Bernard, and Chao-Yie Yang. Targeting the mdm2-p53 protein-protein interaction for new cancer therapy: progress and challenges. *Cold Spring Harbor Perspectives in Medicine*, page a026245, 2017.
- [50] Gustavo Leone, James DeGregori, Zhen Yan, Laszlo Jakoi, Seiichi Ishida, R Sanders Williams, and Joseph R Nevins. E2f3 activity is regulated during the cell cycle and is required for the induction of s phase. *Genes & development*, 12(14):2120–2130, 1998.
- [51] Claude Billerey, Dominique Chopin, Marie-Helene Aubriot-Lorton, David Ricol, Sixtina Gil Diez de Medina, Bas Van Rhijn, Marie-Pierre Bralet, Marie-Aude Lefrere-Belda, Jean-Baptiste Lahaye, Claude C Abbou, et al. Frequent fgfr3 mutations in papillary non-invasive bladder (pta) tumors. *The American Journal of Pathology*, 158(6):1955–1959, 2001.
- [52] Parthasarathy Seshacharyulu, Moorthy P Ponnusamy, Dhanya Haridas, Maneesh Jain, Apar K Ganti, and Surinder K Batra. Targeting the egfr signaling pathway in cancer therapy. *Expert Opinion on Therapeutic Targets*, 16(1):15–31, 2012.
- [53] Nathalie S Dhomen, John Mariadason, Niall Tebbutt, and Andrew M Scott. Therapeutic targeting of the epidermal growth factor receptor in human cancer. *Critical Reviews in Oncogenesis*, 17(1), 2012.
- [54] Lotfi Asker Zadeh. Fuzzy logic. *Computer*, 21(4):83–93, 1988.
- [55] Arnaud Poret, Claudio Monteiro Sousa, and Jean-Pierre Boissel. Enhancing boolean networks with fuzzy operators and edge tuning. *arXiv preprint arXiv:1407.1135*, 2014.

- [56] Melody K Morris, Julio Saez-Rodriguez, David C Clarke, Peter K Sorger, and Douglas A Lauffenburger. Training signaling pathway maps to biochemical data with constrained fuzzy logic: quantitative analysis of liver cell responses to inflammatory stimuli. *PLoS Computational Biology*, 7(3):e1001099, 2011.
- [57] Bree B Aldridge, Julio Saez-Rodriguez, Jeremy L Muhlich, Peter K Sorger, and Douglas A Lauffenburger. Fuzzy logic analysis of kinase pathway crosstalk in tnf/egf/insulin-induced signaling. *PLoS Computational Biology*, 5(4):e1000340, 2009.
- [58] Xiaowei Zhu, Mark Gerstein, and Michael Snyder. Getting connected: analysis and principles of biological networks. *Genes & Development*, 21(9):1010–1024, 2007.
- [59] Frank Emmert-Streib, Matthias Dehmer, and Benjamin Haibe-Kains. Gene regulatory networks and their applications: understanding biological and medical problems in terms of networks. *Frontiers in Cell and Developmental Biology*, 2:38, 2014.