

Hyperspectral Pansharpening: A Review

Laetitia Loncan, Luís Almeida, José M Bioucas-Dias, Xavier Briottet, Jocelyn Chanussot, Nicolas Dobigeon, Sophie Fabre, Wenzhi Liao, Giorgio A. Licciardi, Miguel Simões, et al.

► To cite this version:

Laetitia Loncan, Luís Almeida, José M Bioucas-Dias, Xavier Briottet, Jocelyn Chanussot, et al.. Hyperspectral Pansharpening: A Review. IEEE geoscience and remote sensing magazine, 2015, 3 (3), pp.27-46. 10.1109/MGRS.2015.2440094 . hal-01403205

HAL Id: hal-01403205 https://hal.science/hal-01403205

Submitted on 25 Nov 2016

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Hyperspectral pansharpening: a review

Laetitia Loncan, Luis B. Almeida, José M. Bioucas-Dias, Xavier Briottet, Jocelyn Chanussot, Nicolas Dobigeon, Sophie Fabre, Wenzhi Liao, Giorgio A. Licciardi, Miguel Simões, Jean-Yves Tourneret, Miguel A. Veganzones, Gemine Vivone, Qi Wei and Naoto Yokoya

Abstract—Pansharpening aims at fusing a panchromatic image with a multispectral one, to generate an image with the high spatial resolution of the former and the high spectral resolution of the latter. In the last decade, many algorithms have been presented in the literature for pansharpening using multispectral data. With the increasing availability of hyperspectral systems, these methods are now being adapted to hyperspectral images. In this work, we compare new pansharpening techniques designed for hyperspectral data with some of the state of the art methods for multispectral pansharpening, which have been adapted for hyperspectral data. Eleven methods from different classes (component substitution, multiresolution analysis, hybrid, Bayesian and matrix factorization) are analyzed. These methods are applied to three datasets and their effectiveness and robustness are evaluated with widely used performance indicators. In addition, all the pansharpening techniques considered in this paper have been implemented in a MATLAB toolbox that is made available to the community.

Index Terms—Pansharpening, hyperspectral image, image fusion

I. INTRODUCTION

I N the design of optical remote sensing systems, owing to the limited amount of incident energy, there are critical tradeoffs between the spatial resolution, the spectral resolution, and signal-to-noise ratio (SNR). For this reason, optical systems can provide data with a high spatial resolution but with a small number of spectral bands (for example, panchromatic data with decimetric spatial resolution or multispectral data with three to four bands and metric spatial resolution, like PLEIADES [1]) or with a high spectral resolution but with reduced spatial resolution (for example, hyperspectral data,

Luis B. Almeida and J. M. Bioucas-Dias are with Instituto de Telecomunicações, Instituto Superior Técnico, Universidade de Lisboa, (email:{luis.almeida,bioucas@lx.it.pt}).

J. Chanussot, G. Licciardi, and M. Veganzones are with Gipsa-lab, Grenoble, France (email:{Jocelyn.chanussot,Giorgio-Antonino.Licciardi, miguelangel.veganzones}@gipsa-lab.grenoble-inp.fr).

X. Briottet and S. Fabre are with ONERA, Toulouse, France (email: {Xavier.briottet, Sophie.fabre}@onera.fr).

N. Dobigeon, J.-Y. Tourneret, and Q. Wei are with University of Toulouse, IRIT/INP-ENSEEIHT (email:{nicolas.dobigeon, jeanyves.tourneret,qi.wei}@enseeiht.fr).

W. Liao is with Ghent University, Ghent, Belgium (email:wliao@telin.ugent.be).

M. Simões is with Instituto de Telecomunicações, Instituto Superior Técnico, Universidade de Lisboa and Gipsa-lab, Grenoble, France (email:miguel.simoes@lx.it.pt).

G. Vivone is with North Atlantic Treaty Organization (NATO) Science and Technology Organization (STO) Centre for Maritime Research and Experimentation (CMRE) (email:gvivone@unisa.it).

N. Yokoya is with University of Tokyo (email:yokoya@sal.rcast.u-tokyo.ac.jp).

subsequently referred to as HS data, with more than one hundred of bands and decametric spatial resolution like HYPXIM [2]). To enhance the spatial resolution of multispectral data, several methods have been proposed in the literature under the name of pansharpening, which is a form of superresolution. Fundamentally, these methods solve an inverse problem which consists of obtaining an enhanced image with both high spatial and high spectral resolutions from a panchromatic image and a multispectral image. The huge interest of the community on this topic is evidenced by the existence of sessions dedicated to this topic in the most important remote sensing and Earth observation conferences as well as by the launch of public contests, of which the one sponsored by the data fusion committee of the IEEE Geoscience and Remote Sensing society [3] is an example.

A taxonomy of pansharpening methods can be found in the literature [4], [5], [6]. They can be broadly divided into four classes: component substitution (CS), multiresolution analysis (MRA), Bayesian, and variational. The CS approach relies on the substitution of a component (obtained, e.g., by a spectral transformation of the data) of the multispectral (subsequently denoted as MS) image by the panchromatic (subsequently denoted as PAN) image. The CS class contains algorithms such as intensity-hue-saturation (IHS) [7], [8], [9], principal component analysis (PCA) [10], [11], [12] and Gram-Schmidt (GS) spectral sharpening [13]. The MRA approach is based on the injection of spatial details, which are obtained through a multiscale decomposition of the PAN image into the MS data. The spatial details can be extracted according to several modalities of MRA: decimated wavelet transform (DWT) [14], undecimated wavelet transform (UDWT) [15], "à-trous" wavelet transform (ATWT) [16], Laplacian pyramid [17], nonseparable transforms, either based on wavelets (e.g., contourlets [18]) or not (e.g., curvelets [19]). Hybrid methods have been also proposed, which use both component substitution and multiscale decomposition, such as guided filter PCA (GFPCA), described in Section II-C. The Bayesian approach relies on the used of posterior distribution of the full resolution target image given the observed MS and PAN images. This posterior, which is the Bayesian inference engine, has two factors: a) the likelihood function, which is the probability density of the observed MS and PAN images given the target image, and b) the prior probability density of the target image, which promotes target images with desired properties, such as being segmentally smooth. The selection of a suitable prior allows us to cope with the usual ill-posedness of the pansharpening inverse problems. The variational class is interpretable as particular case of the Bayesian one, where the target image is estimated by maximizing the posterior probability density of the full

L. Loncan is with Gipsa-lab, Grenoble, France and ONERA (email:laetitia.loncan@onera.fr).

resolution image. The works [20], [21], [22] are representative of the Bayesian and variational classes. As indicated in Table I, the CS, MRA, and Hybrid classes of methods are detailed in Sections II-A, II-B, and II-C, respectively. Herein, the Bayesian class is not addressed in the MS+PAN context. It is addressed in detail, however, in Section II-D in the context of HS+PAN fusion.

With the increasing availability of HS systems, the pansharpening methods are now extending to the fusion of HS and panchromatic images [23], [24], [25], [26]. Pansharpening of HS images is still an open issue, and very few methods are presented in the literature to address it. The main advantage of HS image with respect to MS one is the more accurate spectral information they provide, which clearly benefits many applications such as unmixing [27], change detection [28], object recognition [29], scene interpretation [30] and classification [31]. Several of the methods designed for HS pansharpening were originally designed for the fusion of MS and HS data[32]–[36], the MS data constituting the high spatial resolution image. In this case, HS pansharpening can be seen as a particular case, where the MS image is composed of a single band, and thus reduces to a PAN image. In this paper, we divide these methods into two classes: Bayesian methods and matrix factorization based methods. In Section II-D, we briefly present the algorithms of [33], [36], and [35] of the former class and in Section II-E the algorithm of [32] of the latter class.

As one may expect, performing pansharpening with HS data is more complex than performing it with MS data. Whereas PAN and MS data are usually acquired almost in the same spectral range, the spectral range of an HS image normally is much wider than the one of the corresponding PAN image. Usually, the PAN spectral range is close to the visible spectral range of $0.4 - 0.8 \mu m$ (for example, the advanced land imager-ALI-instrument acquires PAN data in the range $0.48 - 0.69 \mu m$). The HS range often covers the visible to the shortwave infrared (SWIR) range (for example, Hyperion acquires HS data in the range $0.4-2.5\mu$ m, the range $0.8-2.5\mu$ m being not covered by the PAN data). The difficulty that arises, consists in defining a fusion model that yields good results in the part of the HS spectral range that is not covered by PAN data, in which the high resolution spatial information is missing. This difficulty already existed, to some extent, in MS+PAN pansharpening, but it is much more severe in the HS+PAN case.

To the best of the authors' knowledge, there is currently no study comparing different fusion methods for HS data, particularly on datasets where the spectral domain of the HS image is larger than the one of the PAN image. This work aims at addressing this specific issue. The remainder of the paper is organized as follows. Section II reviews the methods under study, i.e., CS, MRA, hybrid, Bayesian, and matrix decomposition approaches. Section III summarizes the quality assessment measures that will be used to assess the image fusion results. Experimental results are presented in Section IV. Conclusions are drawn in Section V.

TABLE I

SUMMARY OF THE DIFFERENT CLASSES OF METHODS CONSIDERED IN THIS PAPER. WITHIN PARENTHESES, WE INDICATE THE ACRONYM OF EACH METHOD, FOLLOWED BY THE NUMBER OF THE SECTION IN WHICH THAT METHOD IS DESCRIBED.

METHODS ODICINALLY DESIGNED FOR MC DANGE ADDENING			
METHODS ORIGINALLY DESIGNED FOR MIS PANSHARPENING			
Component substitution (CS, II-A) Principal Component Analysis (PCA, II-A1) Gram Schmidt (GS, II-A2)	Multiresolution analysis (MRA, II-B) Smoothing filter-based intensity modulation (SFIM, II-B1) Laplacian pyramid (II-B2)		
Hybrid methods (II-C) Guided Filter PCA (GFPCA)	Bayesian methods Not discussed in this paper		
METHODS ORIGINALLY DESIGNED FOR HS PANSHARPENING			
Bayesian Methods (II-D) Naive Gaussian prior (II-D1) Sparsity promoting prior (II-D2) HySure (II-D3)	Matrix Factorization (II-E) Coupled Non-negative Matrix Fac- torization (CNMF)		

II. HYPERSPECTRAL PANSHARPENING TECHNIQUES

This section presents some of the most relevant methods for HS pansharpening. First, we focus on the adaptation of the popular CS and MRA MS pansharpening methods for HS pansharpening. Later, we consider more recent methods based on Bayesian and matrix factorization approaches. A toolbox containing MATLAB implementations of these algorithms can be found online¹.

Before presenting the different methods, we introduce notation used along the paper. Bold-face capital letters refer to matrices and bold-face lower-case letters refer to vectors. The notation \mathbf{X}^k refers to the *k*th row of \mathbf{X} . The operator $()^T$ denotes the transposition operation. Images are represented by matrices, in which each row corresponds to a spectral band, containing all the pixels of that band arranged in lexicographic order. We use the following specific matrices:

- $\mathbf{X} = [\mathbf{x}_1, \dots, \mathbf{x}_n] \in \mathbb{R}^{m_\lambda \times n}$ represents the full resolution target image with m_λ bands and n pixels; $\widehat{\mathbf{X}}$ represents an estimate of that image.
- $\mathbf{Y}_{\mathrm{H}} \in \mathbb{R}^{m_{\lambda} \times m}$, $\mathbf{Y}_{\mathrm{M}} \in \mathbb{R}^{n_{\lambda} \times n}$, and $\mathbf{P} \in \mathbb{R}^{1 \times n}$ represents, respectively, the observed HS, MS, and PAN images, n_{λ} denoting the number of bands of the MS image and *m* the total number of pixel in the \mathbf{Y}_{H} image.
- Y_H ∈ ℝ^{m_λ×n} represents the HS image Y_H interpolated at the scale of the PAN image.

We denote by $d = \sqrt{m/n}$ the down-sampling factor, assumed to be the same in both spatial dimensions.

A. Component Substitution

CS approaches rely upon the projection of the higher spectral resolution image into another space, in order to separate spatial and spectral information [6]. Subsequently, the transformed data are sharpened by substituting the component that contains the spatial information with the PAN image (or part of it). The greater the correlation between the PAN image

¹http://openremotesensing.net

and the replaced component, the less spectral distortion will be introduced by the fusion approach [6]. As a consequence, a histogram-matching procedure is often performed before replacing the PAN image. Finally, the CS-based fusion process is completed by applying the inverse spectral transformation to obtain the fused image.

The main advantages of the CS-based fusion techniques are the following: i) high fidelity in rendering the spatial details in the final image [37], ii) fast and easy implementation [8], and iii) robustness to misregistration errors and aliasing [38]. On the negative side, the main shortcoming of this class of techniques is the generation of a significant spectral distortion, cause by the spectral mismatch between the PAN and the HS spectral ranges [6].

Following [4], [39], a formulation of the CS fusion scheme is given by

$$\widehat{\mathbf{X}}^{k} = \widetilde{\mathbf{Y}}_{\mathrm{H}}^{k} + g_{k} \left(\mathbf{P} - \mathbf{O}_{L} \right), \qquad (1)$$

for $k = 1, ..., m_{\lambda}$, where $\widehat{\mathbf{X}}^k$ denotes the *k*th band of the estimated full resolution target image, $\mathbf{g} = [g_1, ..., g_{m_{\lambda}}]^T$ is a vector containing the *injection gains*, and \mathbf{O}_L is defined as

$$\mathbf{O}_L = \sum_{i=1}^{m_\lambda} w_i \widetilde{\mathbf{Y}}_{\mathrm{H}}^i,\tag{2}$$

where the weights $\mathbf{w} = [w_1, \dots, w_i, \dots, w_{m_{\lambda}}]^T$ measure the spectral overlap among the spectral bands and the PAN image [6], [40].

The CS family includes many popular pansharpening approaches. In [26], three approaches based on *principal component analysis* (PCA) [9] and *Gram-Schmidt* [13], [37] transformations have been compared for sharpening HS data. A brief description of these techniques follows.

1) Principal Component Analysis: PCA is a spectral transformation widely employed for pansharpening applications [9]. It is achieved through a rotation of the original data (i.e., a linear transformation) that yields the so-called principal components (PCs). The hypothesis underlying its application to pansharpening is that the spatial information (shared by all the channels) is concentrated in the first PC, while the spectral information (specific to each single band) is accounted for the other PCs. The whole fusion process can be described by the general formulation stated by Eqs. (1) and (2), where the vectors w and g of coefficient vectors are derived by the PCA procedure applied to the HS image.

2) Gram-Schmidt: The Gram-Schmidt transformation, often exploited in pansharpening approaches, was initially proposed in a patent by Kodak [13]. The fusion process starts by using, as the component, a synthetic low resolution PAN image I_L at the same spatial resolution as the HS image². A complete orthogonal decomposition is then performed, starting with that component. The pansharpening procedure is completed by substituting that component with the PAN image, and inverting the decomposition. This process is expressed by (1) using the gains [37]

$$g_k = \frac{\operatorname{cov}(\tilde{\mathbf{Y}}_{\mathrm{H}}^k, \mathbf{O}_L)}{\operatorname{var}(\mathbf{O}_L)}$$
(3)

for $k = 1, ..., m_{\lambda}$, where cov (\cdot, \cdot) and var (\cdot) denote the covariance and variance operations. Different algorithms are obtained by changing the definition of the weights in (2). The simplest way to obtain this low-resolution PAN image simply consists of averaging the HS bands (i.e., by setting $w_i = 1/m_{\lambda}$, for $i = 1, ..., m_{\lambda}$). In [37], the authors proposed an enhanced version, called *GS Adaptive (GSA)*, in which I_L is generated by the linear model in (2) with weights estimated by the minimization of the mean square error between the estimated component and a filtered and downsampled version of the PAN image.

B. Multiresolution Analysis

Pansharpening methods based on MRA apply a spatial filter to the PAN image for generating details to be injected into the HS data. The main advantages of the MRA-based fusion techniques are the following: i) temporal coherence [5] (see Sect.27.4.4), ii) spectral consistency, and iii) robustness to aliasing, under proper conditions [38]. On the negative side, the main shortcomings are i) the implementation is more complicated due to the design of spatial filters, ii) the computational burden is usually larger when compared to CS approaches. The fusion step is summarized as [4], [39]

$$\widehat{\mathbf{X}}^{k} = \widetilde{\mathbf{Y}}_{\mathrm{H}}^{k} + \mathbf{G}_{k} \otimes (\mathbf{P} - \mathbf{P}_{L}), \qquad (4)$$

for $k = 1, ..., m_{\lambda}$, where \mathbf{P}_L denotes a low-pass version of \mathbf{P} , and the symbol \otimes denotes element-wise multiplication. Furthermore, an equalization between the PAN image and the HS spectral bands is often required. $\mathbf{P} - \mathbf{P}_L$ is often called the *details* image, because it is a high-pass version of \mathbf{P} , and Eq. (4) can be seen as describing the way to *inject* details into each of the bands of the HS image. According to (4), the approaches belonging to this category can differ in *i*) the type of PAN low pass image \mathbf{P}_L that is used, and *ii*) the definition of the gain coefficients \mathbf{G}_k . Two common options for defining the gains are:

- 1) $\mathbf{G}_k = \mathbb{1}$ for $k = 1, \dots, m_\lambda$, where $\mathbb{1}$ is an appropriately sized matrix with all elements equal to 1. This choice identifies the so-called *additive* injection scheme;
- 2) $\mathbf{G}_k = \mathbf{\tilde{Y}}_H^k \oslash \mathbf{P}_L$ for $k = 1, \dots, m_\lambda$, where the symbol \oslash denotes element-wise division. In this case, the details are weighted by the ratio between the upsampled HS image and the low-pass filtered PAN one, in order to reproduce the local intensity contrast of the PAN image in the fused image [42]. This coefficient selection is often referred to as *high pass modulation* (HPM) method or *multiplicative* injection scheme. Some possible numerical issues could appear due to the division between $\mathbf{\tilde{Y}}_H^k$ and \mathbf{P}_L for low value of \mathbf{P}_L creating fused pixel with very high value. In our toolbox this problem is addressed by clipping these values by using the information given by the dynamic range.

In the case of HS pansharpening, some further considerations should be taken into account. Indeed, the PAN and

 $^{^{2}}$ GS is a more general method than PCA. PCA can be obtained, in GS, by using the first PC as the low resolution panchromatic image [41].

HS images are rarely acquired with the same platform. Thus, the ratio between the spatial resolutions of the PAN and HS images may not always be an integer number, or a power of two. This implies that some of the conventional approaches initially developed for MS images cannot be extended in a simple way to HS images (for example, dyadic wavelet-based algorithms cannot be applied in these conditions).

1) Smoothing Filter-based Intensity Modulation (SFIM): The direct implementation of Eq. (4) consists of applying a single linear time-invariant (LTI) low pass filter (LPF) h_{LP} to the PAN image **P** for obtaining **P**_L. Therefore, we have

$$\widehat{\mathbf{X}}^{k} = \widetilde{\mathbf{Y}}_{\mathrm{H}}^{k} + g_{k} \left(\mathbf{P} - \mathbf{P} * h_{LP} \right)$$
(5)

for $k = 1, ..., m_{\lambda}$, where the symbol * denotes the convolution operator. The SFIM algorithm [43] sets h_{LP} to a simple box (i.e., an averaging) filter and exploits HPM as the details injection scheme.

2) Laplacian Pyramid: The low-pass filtering needed to obtain the signal \mathbf{P}_L at the original HS scale can be performed in more than one step. This is commonly referred to as pyramidal decomposition and dates back to the seminal work of Burt and Adelson [17]. If a Gaussian filter is used to lowpass filter the images in each step, one obtains a so-called Gaussian pyramid. The differences between consecutive levels of a Gaussian pyramid define the so-called Laplacian pyramid. The suitability of the latter to the pansharpening problem has been shown in [44]. Indeed, Gaussian filters can be tuned to closely match the sensor modulation transfer function (MTF). In this case, the unique parameter that characterizes the whole distribution is the Gaussian's standard deviation, which is determined from sensor-based information (usually from the value of the amplitude response at the Nyquist frequency, provided by the manufacturer). Both additive and multiplicative details injection schemes have been used in this framework [42], [45]. They will be referred to as MTF -Generalized Laplacian Pyramid (MTF-GLP) [45] and MTF-GLP with High Pass Modulation (MTF-GLP-HPM) [42], respectively.

C. Hybrid Methods

Hybrid approaches use concepts from different classes of methods, namely from CS and MRA ones, as explained next. *1) Guided Filter PCA (GFPCA):* One of the main challenges for fusing low-resolution HS and high-resolution PAN/RGB data is to find an appropriate balance between spectral and spatial preservation. Recently, the guided filter [46] has been used in many applications (e.g. edge-aware smoothing and detail enhancement), because of its efficiency and strong ability to transfer the structures of the guidance image to the filtering output. Its application to HS data can be found in [47], where the guided filter was applied to transfer the structures of the principal components of the HS image to the initial classification maps.

Here, we briefly describe an image fusion framework which uses a guided filter in the PCA domain (GFPCA) [48]. The approach won the "Best Paper Challenge" award at the 2014 IEEE data fusion contest [48], by fusing a low spatial resolution thermal infrared HS image and a high spatial resolution, visible RGB image associated with the same scene. Fig. 1 shows the framework of GFPCA. Instead of using CS, which may cause spectral distortions, GFPCA uses a high resolution PAN/RGB image to guide the filtering process aimed at obtaining superresolution. In this way, GFPCA does not only preserve the spectral information from the original HS image, but also transfers the spatial structures of the high resolution PAN/RGB image to the enhanced HS image. To speed up the processing, GFPCA first uses PCA to decorrelate the bands of the HS image, and to separate the information content from the noise. The first $p \ll m_{\lambda}$ PCA channels contain most of the energy (and most of the information) of an HS image, and the remaining $m_{\lambda} - p$ PCA channels mainly contain noise (recall that m_{λ} is the number of spectral bands of the HS image). When applied to these noisy (and numerous) $m_{\lambda} - p$ channels, the guided filter amplifies the noise and causes a high computational cost in processing the data, which is undesirable. Therefore, guided filtering is used to enlarge only the first k PCA channels, preserving the structures of the PAN/RGB image, while cubic interpolation is used to upsample the remaining channels.

Let PC_i , with $(i \le p)$, denote the *i*th PC channel obtained from the HS image Y_H , with its resolution increased to that of the guided image Y (Y may be a PAN or an RGB image) through bicubic interpolation. The output of the filtering, PC'_i , can be represented as an affine transformation of Y in a local window ω_i of size $(2d + 1) \times (2d + 1)$ as follows:

$$\mathbf{PC}'_i = a_j \mathbf{Y} + b_j, \quad \forall i \in \omega_j.$$

The above model ensures that the output PC'_i has an edge only if the guided image Y has an edge, since $\nabla(PC'_i) = a\nabla Y$. The following cost function is used to determine the coefficients a_i and b_i :

$$E(a_j, b_j) = \sum_{i \in \omega_j} \left[(a_j \mathbf{Y} + b_j - \mathbf{PC}_i)^2 + \epsilon a_j^2 \right], \qquad (7)$$

where ϵ is a regularization parameter determining the degree of blurring for the guided filter. For more details about the guided filtering scheme, we invite the reader to consult [46]. The cost function E leads the term $a_j \mathbf{Y} + b_j$ to be as close as possible to PC_i, in order to ensure the preservation of the original spectral information. Before applying inverse PCA, GFPCA also removes the noise from the remaining PCA channels PC_{Rest} using a soft-thresholding scheme (similarly to [49]), and increases their spatial resolution to the resolution



Fig. 1. Fusion of HS and PAN/RGB images with the GFPCA framework.

of the PAN/RGB image using cubic interpolation only (without of U can be written as guided filtering).

D. Bayesian Approaches

The fusion of HS and high spatial resolution images, e.g., MS or PAN images, can be conveniently formulated within the Bayesian inference framework. This formulation allows an intuitive interpretation of the fusion process via the posterior distribution of the Bayesian fusion model. Since the fusion problem is usually ill-posed, the Bayesian methodology offers a convenient way to regularize the problem by defining an appropriate prior distribution for the scene of interest. Following this strategy, different Bayesian estimators for fusing co-registered high spatial-resolution MS and high spectralresolution HS images have been designed [33]-[36], [50]-[54]. The observation models associated with the HS and MS images can be written as follows [50], [55], [56]

$$\begin{aligned} \mathbf{Y}_{\mathrm{H}} &= \mathbf{X}\mathbf{B}\mathbf{S} + \mathbf{N}_{\mathrm{H}} \\ \mathbf{Y}_{\mathrm{M}} &= \mathbf{R}\mathbf{X} + \mathbf{N}_{\mathrm{M}} \end{aligned} \tag{8}$$

where $\mathbf{X}, \mathbf{Y}_{H}$, and \mathbf{Y}_{M} were defined in Section II, and

- $\mathbf{B} \in \mathbb{R}^{n \times n}$ is a cyclic convolution operator, corresponding to the spectral response of the HS sensor expressed in the resolution of the MS or PAN image,
- $\mathbf{S} \in \mathbb{R}^{n \times m}$ is a down-sampling matrix with downsampling factor d,
- $\mathbf{R} \in \mathbb{R}^{n_{\lambda} \times m_{\lambda}}$ is the spectral response of the MS or PAN sensor,
- $N_{\rm H}$ and $N_{\rm M}$ are the HS and MS noises, assumed to have zero mean Gaussian distributions with covariance matrices $\Lambda_{\rm H}$ and $\Lambda_{\rm M}$, respectively.

For the sake of generality, the formulation in this section assumes that the observed data is the pair of matrices $(\mathbf{Y}_{H}, \mathbf{Y}_{M})$. Since a PAN image can be represented by \mathbf{Y}_{M} with $n_{\lambda} = 1$, the observation model (8) covers the HS+PAN fusion problem considered in this paper.

Using geometrical considerations well grounded in the HS imaging literature devoted to the linear unmixing problem [27], the high spatial resolution HS image to be estimated is assumed to live in a low dimensional subspace. This hypothesis is very reliable when the observed scene is composed of a finite number of macroscopic materials (called endmembers). Based on the model (8) and on the low dimensional subspace assumptions, the distributions of \mathbf{Y}_{H} and \mathbf{Y}_{M} can be expressed as follows

$$\begin{aligned} \mathbf{Y}_{\mathrm{H}} | \mathbf{U} &\sim \mathcal{MN}_{m_{\lambda},m}(\mathbf{HUBS}, \mathbf{\Lambda}_{\mathrm{H}}, \mathbf{I}_{m}), \\ \mathbf{Y}_{\mathrm{M}} | \mathbf{U} &\sim \mathcal{MN}_{n_{\lambda},n}(\mathbf{RHU}, \mathbf{\Lambda}_{\mathrm{M}}, \mathbf{I}_{n}) \end{aligned}$$
(9)

where \mathcal{MN} represents the matrix normal distribution [57], the target image is $\mathbf{X} = \mathbf{H}\mathbf{U}$, with $\mathbf{H} \in \mathbb{R}^{m_{\lambda} \times \tilde{m}_{\lambda}}$ containing in its columns a basis of the signal subspace of size $\widetilde{m}_{\lambda} \ll m_{\lambda}$ and $\mathbf{U} \in \mathbb{R}^{\widetilde{m}_{\lambda} \times n}$ contains the representation coefficients of \mathbf{X} with respect to H. The subspace transformation matrix H can be obtained via different approaches, e.g., PCA [58] or vertex component analysis [59].

According to Bayes' theorem and using the fact that the noises N_H and N_M are independent, the posterior distribution

$$p(\mathbf{U}|\mathbf{Y}_{\mathrm{H}}, \mathbf{Y}_{\mathrm{M}}) \propto p(\mathbf{Y}_{\mathrm{H}}|\mathbf{U}) p(\mathbf{Y}_{\mathrm{M}}|\mathbf{U}) p(\mathbf{U})$$
 (10)

or equivalently³

$$-\log p\left(\mathbf{U}|\mathbf{Y}_{\mathrm{H}},\mathbf{Y}_{\mathrm{M}}\right) \doteq \underbrace{\frac{1}{2} \left\|\mathbf{\Lambda}_{\mathrm{H}}^{-\frac{1}{2}}(\mathbf{Y}_{\mathrm{H}}-\mathbf{HUBS})\right\|_{F}^{2}}_{\overset{\mathrm{HS \ data \ term}}{\doteq \log p(\mathbf{Y}_{\mathrm{H}}|\mathbf{U})}} + \underbrace{\frac{1}{2} \left\|\mathbf{\Lambda}_{\mathrm{M}}^{-\frac{1}{2}}(\mathbf{Y}_{\mathrm{M}}-\mathbf{RHU})\right\|_{F}^{2}}_{\overset{\mathrm{MS \ data \ term}}{\doteq \log p(\mathbf{Y}_{\mathrm{H}}|\mathbf{U})}} + \underbrace{\lambda\phi(\mathbf{U})}_{\overset{\mathrm{regularizer}}{\doteq \log p(\mathbf{U})}}$$

$$(11)$$

where $\|\mathbf{X}\|_F \stackrel{\text{def}}{=} \sqrt{\text{Tr}(\mathbf{X}\mathbf{X}^T)}$ is the Frobenius norm of X. An important quantity in the negative log-posterior (11) is the penalization term $\phi(\mathbf{U})$ which allows the inverse problem (8) to be regularized. The next sections discuss different ways of defining this penalization term.

1) Naive Gaussian prior: Denote as u_i $(i = 1, \dots, n)$ the columns of the matrix U that are assumed to be mutually independent and are assigned the following Gaussian prior distributions

$$p(\boldsymbol{u}_i | \boldsymbol{\mu}_i, \boldsymbol{\Sigma}_i) = \mathcal{N}(\boldsymbol{\mu}_i, \boldsymbol{\Sigma}_i)$$
(12)

where μ_i is a fixed image defined by the interpolated HS image projected into the subspace of interest, and Σ_i is an unknown hyperparameter matrix. Different interpolations can be investigated to build the mean vector μ_i . In this paper, we have followed the strategy proposed in [50]. To reduce the number of parameters to be estimated, the matrices Σ_i are assumed to be identical, i.e., $\Sigma_1 = \cdots = \Sigma_n = \Sigma$. The hyperparameter Σ is assigned a proper prior and is estimated jointly with the other parameters of interest. To infer the parameter of interest, namely the projected highly resolved HS image U, from the posterior distribution $p(\mathbf{U}|\mathbf{Y}_{\mathrm{H}},\mathbf{Y}_{\mathrm{M}})$, several algorithms have been proposed. In [33], [34], a Markov chain Monte Carlo (MCMC) method is exploited to generate a collection of $N_{\rm MC}$ samples that are asymptotically distributed according to the target posterior. The corresponding Bayesian estimators can then be approximated using these generated samples. For instance, the minimum mean square error (MMSE) estimator of U can be approximated by an empirical average of the generated samples $\widehat{\mathbf{U}}_{\text{MMSE}} \approx \frac{1}{N_{\text{MC}} - N_{\text{bi}}} \sum_{t=N_{\text{bi}}+1}^{N_{\text{MC}}} \mathbf{U}^{(t)}$, where N_{bi} is the number of burn-in iterations required to reach the sampler convergence, and $\mathbf{U}^{(t)}$ is the image generated in the tth iteration. The highly-resolved HS image can finally be computed as $\mathbf{X}_{MMSE} = \mathbf{H}\mathbf{U}_{MMSE}$. An extension of the proposed algorithm has been proposed in [53] to handle the specific scenario of an unknown sensor spectral response. In [60], a deterministic counterpart of this MCMC algorithm has been developed, where the Gibbs sampling strategy of [33] has been replaced with a block coordinate descent method to compute the maximum a posteriori (MAP) estimator. Finally, very recently, a Sylvester equation-based explicit solution of

³We use the symbol \doteq to denote equality apart from an additive constant. The additive constants are irrelevant, since the functions under consideration are to be optimized, and the additive constants don't change the locations of the optima.

the related optimization problem has been derived in [61], leading to a significant decrease of the computational complexity.

2) Sparsity promoted Gaussian prior: Instead of incorporating a simple Gaussian prior or smooth regularization for the HS and MS fusion [34], [50], [51], a sparse representation can be used to regularize the fusion problem. More specifically, image patches of the target image (projected onto the subspace defined by H) are represented as a sparse linear combination of elements from an appropriately chosen over-complete dictionary with columns referred to as atoms. Learning the dictionary from the observed images instead of using predefined bases [62]–[64] generally improves image representation [65], which is preferred in most scenarios. Therefore, an adaptive sparse image-dependent regularization can be explored to solve the fusion problem (8). In [36], the following regularization term was introduced:

$$\phi(\mathbf{U}) \propto -\log p\left(\mathbf{U}\right) \doteq \frac{1}{2} \sum_{k=1}^{\widetilde{m}_{\lambda}} \left\| \mathbf{U}_{k} - \mathcal{P}\left(\bar{\mathbf{D}}_{k}\bar{\mathbf{A}}_{k}\right) \right\|_{F}^{2}, \quad (13)$$

where

- $\mathbf{U}_k \in \mathbb{R}^n$ is the *k*th band (or row) of $\mathbf{U} \in \mathbb{R}^{\widetilde{m}_\lambda \times n}$, with $k = 1, \dots, \widetilde{m}_\lambda$,
- *P*(·): ℝ<sup>n_p×n_{pat} → ℝ^{n×1} is a linear operator that averages the overlapping patches⁴ of each band, n_{pat} being the number of patches associated with the *i*th band,
 </sup>
- $\bar{\mathbf{D}}_i \in \mathbb{R}^{n_{\mathrm{p}} \times n_{\mathrm{at}}}$ is the overcomplete dictionary, whose columns are basis elements of size n_{p} (corresponding to the size of a patch), n_{at} being the number of dictionary atoms, and
- $\bar{\mathbf{A}}_i \in \mathbb{R}^{n_{\text{at}} \times n_{\text{pat}}}$ is the code of the *i*th band.

Inspired by hierarchical models frequently encountered in Bayesian inference [67], a second level of hierarchy can be considered in the Bayesian paradigm by including the code **A** within the estimation, while fixing the support $\overline{\Omega} \triangleq$ $\{\overline{\Omega}_1,\ldots,\overline{\Omega}_{\widetilde{m}_{\lambda}}\}$ of the code **A**. Once $\overline{\mathbf{D}}, \overline{\Omega}$ and **H** have been learned from the HS and MS data, maximizing the posterior distribution of U and A reduces to a standard constrained quadratic optimization problem with respect to (w.r.t.) U and A. The resulting optimization problem is difficult to solve due to its large dimension and due to the fact that the linear operators $H(\cdot)BD$ and $\mathcal{P}(\cdot)$ cannot be easily diagonalized. To cope with this difficulty, an optimization technique that alternates minimization w.r.t. U and A has been introduced in [36] (where details on the learning of **D**, Ω and **H** can be found). In [61], the authors show that the minimization w.r.t. U can be achieved analytically, which greatly accelerates the fusion process.

3) HySure: The works [35], [54] introduce a convex regularization problem which can be seen under a Bayesian framework. The proposed method uses a form of vector total variation (VTV) [68] for the regularizer $\phi(\mathbf{U})$, taking into account both the spatial and the spectral characteristics of the data. In addition, another convex problem is formulated to estimate the relative spatial and spectral responses of the sensors \mathbf{B} and \mathbf{R} from the data themselves. Therefore, the complete methodology can be classified as a blind superresolution method, which, in contrast to the classical blind linear inverse problems, is tackled by solving two convex problems.

The VTV regularizer (see [68]) is given by

$$\phi(\mathbf{U}) = \sum_{j=1}^{n} \sqrt{\sum_{k=1}^{\tilde{m}_{\lambda}} \left\{ \left[(\mathbf{U}\mathbf{D}_{h})_{j}^{k} \right]^{2} + \left[(\mathbf{U}\mathbf{D}_{v})_{j}^{k} \right]^{2} \right\}}, \quad (14)$$

where \mathbf{A}_{j}^{k} denotes the element in the *k*th row and *j*th column of matrix \mathbf{A} , and the products by matrices \mathbf{D}_{h} and \mathbf{D}_{v} compute the horizontal and vertical discrete differences of an image, respectively, with periodic boundary conditions.

The HS pansharpened image is the solution to the following optimization problem

$$\begin{array}{ll} \underset{\mathbf{U}}{\text{minimize}} & \frac{1}{2} \left\| \mathbf{Y}_{\mathrm{H}} - \mathbf{HUBS} \right\|_{F}^{2} + \frac{\lambda_{m}}{2} \left\| \mathbf{Y}_{\mathrm{M}} - \mathbf{RHU} \right\|_{F}^{2} \\ & + \lambda_{\phi} \phi(\mathbf{U}), \end{array}$$
(15)

where λ_m and λ_ϕ control the relative weights of the different terms. The optimization problem (15) is hard to solve, essentially for three reasons: the downsampling operator **BS** is not diagonalizable, the regularizer $\phi(\mathbf{U})$ is nonquadratic and nonsmooth, and the target image has a very large size. These difficulties were tackled by solving the problem via the split augmented lagrangian shrinkage algorithm (SALSA) [69], an instance of ADMM. As an alternative, the main step of the ADMM scheme can be conducted using an explicit solution of the corresponding minimization problem, following the strategy in [61].

The relative spatial and spectral responses \mathbf{B} and \mathbf{R} were estimated by solving the following optimization problem:

$$\underset{\mathbf{B},\mathbf{R}}{\text{minimize}} \quad \left\|\mathbf{R}\mathbf{Y}_{\mathrm{H}} - \mathbf{Y}_{\mathrm{M}}\mathbf{B}\mathbf{S}\right\|^{2} + \lambda_{B}\phi_{B}(\mathbf{B}) + \lambda_{R}\phi_{R}(\mathbf{R})$$
(16)

where $\phi_B(\cdot)$ and $\phi_r(\cdot)$ are quadratic regularizers and $\lambda_b, \lambda_R \ge 0$ are their respective regularization parameters.

E. Matrix factorization

The matrix factorization approach for HS+MS fusion essentially exploits two facts: 1) A basis or dictionary **H** for the signal subspace can be learned from the HS observed image $\mathbf{Y}_{\rm H}$, yielding the factorization $\mathbf{X} = \mathbf{H}\mathbf{U}$; 2) using this decomposition in the second equation of (9) and for negligible noise, i.e., $\mathbf{N}_{\rm M} \simeq \mathbf{0}$, we have $\mathbf{Y}_{\rm H} = \mathbf{R}\mathbf{H}\mathbf{U}$. Assuming that the columns of $\mathbf{R}\mathbf{H}$ are full rank or that the columns of \mathbf{U} admit a sparse representation w.r.t. the columns of $\mathbf{R}\mathbf{H}$, then we can recover the true solution, denoted by $\widehat{\mathbf{U}}$, and use it to compute the target image as $\widehat{\mathbf{X}} = \mathbf{H}\widehat{\mathbf{U}}$. The works [32], [70]–[74] are representative of this line of attack. In what follow, we detail the application of the coupled nonnegative matrix factorization (CNMF) [32] to the HS+PAN fusion problem.

The CNMF was proposed for the fusion of low spatial resolution HS and high spatial resolution MS data to produce fused data with high spatial and spectral resolutions [32]. It is applicable to HS pansharpening as a special case, in which

⁴A decomposition into overlapping patches was adopted, to prevent the occurrence of blocking artifacts [66].

the higher spatial resolution image has a single band [75]. CNMF alternately unmixes both sources of data to obtain the endmember spectra and the high spatial resolution abundance maps.

To describe this method, it is convenient to first briefly introduce linear mixture models for HS images. These models are commonly used for spectral unmixing, owing to their physical effectiveness and mathematical simplicity [27]. The spectrum at each pixel is assumed to be a linear combination of several endmember spectra. Therefore, $\mathbf{X} \in \mathbb{R}^{m_{\lambda} \times n}$ is formulated as

$$\mathbf{X} = \mathbf{H}\mathbf{U} \tag{17}$$

where $\mathbf{H} \in \mathbb{R}^{m_{\lambda} \times p}$ is the signature matrix, containing the spectral representations of the endmembers, and $\mathbf{U} \in \mathbb{R}^{p \times n}$ is the abundance matrix, containing the relative abundances of the different endmembers at the various pixels, with *p* representing the number of endmembers. By substituting (17) into (8), \mathbf{Y}_{H} and \mathbf{Y}_{M} can be approximated as

where $\mathbf{U}_{\mathrm{H}} = \mathbf{UBS}$ and $\mathbf{H}_{\mathrm{M}} = \mathbf{RH}$. CNMF alternately unmixes \mathbf{Y}_{H} and \mathbf{Y}_{M} in the framework of nonnegative matrix factorization (NMF) [76] to estimate H and U under the constraints of the relative sensor characteristics. CNMF starts with NMF unmixing of the low spatial resolution HS data. The matrix **H** can be initialized using, for example, the vertex component analysis (VCA) [59], and H and $U_{\rm H}$ are then alternately optimized by minimizing $\|\mathbf{Y}_{\mathrm{H}} - \mathbf{H}\mathbf{U}_{\mathrm{H}}\|_{F}^{2}$ using Lee and Seung's multiplicative update rules [76]. Next, U is estimated from the higher spatial resolution data. \mathbf{H}_{M} is set to **RH** and **U** is initialized by the spatially up-sampled matrix of $U_{\rm H}$ obtained by using bilinear interpolation. For HS pansharpening $(n_{\lambda}=1)$, only U is optimized by minimizing $\|\mathbf{Y}_{M} - \mathbf{H}_{M}\mathbf{U}\|_{F}^{2}$ with the multiplicative update rule, whereas both \mathbf{H}_{M} and \mathbf{U} are alternately optimized in the case of HS+MS data fusion. Finally, the high spatial resolution HS data can be obtained by the multiplication of H and U. The abundance sum-to-one constraint is implemented using a method given in [77], where the data and signature matrices are augmented by a row of constants. The relative sensor characteristics, such as BS and R, can be estimated from the observed data sources [78].

III. QUALITY ASSESSMENT OF FUSION PRODUCTS

Quality assessment of a pansharpened real-life HS image is not an easy task [79], [9], since a reference image is generally not available. When such an image is not available, two kinds of comparisons can be performed: i) Each band of the fused image can be compared with the PAN image, with an appropriate criterion. The PAN image can also be compared with the PAN image reconstructed from the fused image. ii) The fused image can be spatially degraded to the resolution of the original HS image. The two images can then be compared, to assess to what extent the spectral information has been modified by the fusion method. In order to be able to use a reference image for quality assessment, one normally has to resort to the use of semisynthetic HS and PAN images. In this case, a real-life HS image is used as reference. The HS and PAN images to be processed are obtained by degrading this reference image. A common methodology for obtaining the degraded images is Wald's protocol, described in the next subsection. In order to evaluate the quality of the fused image with respect to the reference image, a number of statistical measures can be computed. The most widely used ones are described ahead, and used in the experiments reported in Section IV-B.

A. Wald's Protocol

A general paradigm for quality assessment of fused images that is usually accepted in the research community was first proposed by Wald et al. [79]. This paradigm is based on two properties that the fused data have to have, as much as possible, namely consistency and synthesis properties. The first property requires the reversibility of the pansharpening process: it states that the original HS image should be obtained by properly degrading the pansharpened image. The second property requires that the pansharpened image be as similar as possible to the image of the same scene that would be obtained, by the same sensor, at the higher resolution. This condition entails that both the features of each single band and the mutual relations among bands have to be preserved. However, the definition of an assessment method that fulfills these constraints is still an open issue [80], [81], and closely relates to the general discussion regarding image quality assessment [82] and image fusion [83], [84].

Wald's protocol for assessing the quality of pansharpening methods [79], depicted in Fig. 2, synthetically generates simulated observed images from a reference HS image, and then evaluates the pansharpening methods' results against that reference image. The protocol consists of the following steps:

- Given a HS image, X, to be used as reference, a simulated observed low spatial resolution HS image, Y_H, is obtained by applying a Gaussian blur to X, and then downsampling the result by selecting one out of every *d* pixels in both the horizontal and vertical directions, where *d* denotes the downsampling factor.
- A simulated PAN image, **P**, is obtained by multiplying the reference HS image, on the left, by a suitably chosen spectral response vector, $\mathbf{P} = \mathbf{r}^T \mathbf{X}$.
- The pansharpening method to be evaluated is applied to the simulated observations Y_H and P, yielding the estimated superresolution HS image, \hat{X} .
- Finally, the estimated superresolution HS image and the reference one are compared, to obtain quantitative quality measures.

B. Quality Measures

Several quality measures have been defined in the literature, in order to determine the similarity between estimated and reference spectral images. These measures can be generally classified into three categories, depending on whether they



Fig. 2. Flow diagram of the experimental methodology, derived from Wald's protocol (simulated observations), for synthetic and semi-real datasets.

attempt to measure the spatial, spectral or global quality of the estimated image. This review is limited to the most widely used quality measures, namely the *cross correlation* (CC), which is a spatial measure, the *spectral angle mapper* (SAM), which is a spectral measure, and the *root mean squared error* (RMSE) and *erreur relative globale adimensionnelle de synthèse* (ERGAS) [85], which are global measures. Below we provide the formal definitions of these measures operating on the estimated image $\hat{\mathbf{X}} \in \mathbb{R}^{m_{\lambda} \times n}$ and on the reference HS image $\mathbf{X} \in \mathbb{R}^{m_{\lambda} \times n}$. In the definitions, $\hat{\mathbf{x}}_j$ and \mathbf{x}_j denote the *j*th columns of $\hat{\mathbf{X}}$ and \mathbf{X} , respectively, the matrices $\mathbf{A}, \mathbf{B} \in \mathbb{R}^{1 \times n}$ denote two generic single-band images, and \mathbf{A}_i denotes the *i*th element of \mathbf{A} .

1) Cross correlation: CC, which characterizes the geometric distortion, is defined as

$$CC(\widehat{\mathbf{X}}, \mathbf{X}) = \frac{1}{m_{\lambda}} \sum_{i=1}^{m_{\lambda}} CCS(\widehat{\mathbf{X}}^{i}, \mathbf{X}^{i}),$$
(19)

where CCS is the cross correlation for a single-band image, defined as

$$CCS(\mathbf{A}, \mathbf{B}) = \frac{\sum_{j=1}^{n} (\mathbf{A}_{j} - \mu_{A}) (\mathbf{B}_{j} - \mu_{B})}{\sqrt{\sum_{j=1}^{n} (\mathbf{A}_{j} - \mu_{A})^{2} \sum_{j=1}^{n} (\mathbf{B}_{j} - \mu_{B})^{2}}},$$

where, $\mu_A = (1/n) \sum_{j=1}^n \mathbf{A}_j$ is the sample mean of **A**. The ideal value of CC is 1.

2) Spectral angle mapper: SAM, which is a spectral measure, is defined as

$$SAM(\widehat{\mathbf{X}}, \mathbf{X}) = \frac{1}{n} \sum_{j=1}^{n} SAM(\widehat{\mathbf{x}}_j, \mathbf{x}_j),$$
(20)

where, given the vectors $\mathbf{a}, \mathbf{b} \in \mathbb{R}^{m_{\lambda}}$,

$$SAM(\mathbf{a}, \mathbf{b}) = \arccos\left(\frac{\langle \mathbf{a}, \mathbf{b} \rangle}{\|\mathbf{a}\| \|\mathbf{b}\|}\right),$$
 (21)

 $\langle \mathbf{a}, \mathbf{b} \rangle = \mathbf{a}^T \mathbf{b}$ is inner product between \mathbf{a} and \mathbf{b} , and $\|\cdot\|$ is the ℓ_2 norm. SAM is a measure of the spectral shape preservation. The optimal value of SAM is 0. The values of SAM reported in our experiments have been obtained by averaging the values obtained for all the image pixels.

3) Root mean squared error: The RMSE measures the ℓ_2 error between the two matrices X and \widehat{X}

$$RMSE(\widehat{\mathbf{X}}, \mathbf{X}) = \frac{\|\widehat{\mathbf{X}} - \mathbf{X}\|_F}{\sqrt{n * m_{\lambda}}}$$
(22)

where $\|\mathbf{X}\|_F = \sqrt{\text{trace}(\mathbf{X}^T \mathbf{X})}$ is the Frobenius norm of **X**. The ideal value of RMSE is 0.

4) Erreur relative globale adimensionnelle de synthèse: ERGAS offers a global indication of the quality of a fused image. It is defined as

$$\operatorname{ERGAS}(\widehat{\mathbf{X}}, \mathbf{X}) = 100 \, d \sqrt{\frac{1}{m_{\lambda}} \sum_{k=1}^{m_{\lambda}} \left(\frac{\operatorname{RMSE}_{k}}{\mu_{k}}\right)^{2}}, \qquad (23)$$

where d is the ratio between the linear resolutions of the PAN and HS images, defined as

$$d = \frac{\text{PAN linear spatial resolution}}{\text{HS linear spatial resolution}},$$

 $RMSE_{k} = \frac{\|\widehat{\mathbf{X}}^{k} - \mathbf{X}^{k}\|_{F}}{\sqrt{n}}, \ \mu_{k} \text{ is the sample mean of the } kth \\ \text{band of } \mathbf{X}. \text{ The ideal value of ERGAS is } 0.$

IV. EXPERIMENTAL RESULTS

A. Datasets

The datasets that were used in the experimental tests were all semi-synthetic, generated according to the Wald's protocol. In all cases, the spectral bands corresponding to the absorption band of water vapor, and the bands that were too noisy, were removed from the reference image before further processing. Three real-life HS images have been used as reference images for the Wald protocol. In the following, we describe the datasets that were generated from these images. Table II summarizes their properties. These datasets are expressed in spectral luminance (nearest to the sensor output, without preprocessing) and are correctly registered.

 TABLE II

 CARACTERISTIC OF THE THREE DATASETS

dimensions	spatial res	Ν	instrument	
PAN 185×395	20m	994	AVIDIC	
HS 37×79	100m	224	AVIKIS	
PAN 500×500	4m	195	HuMon	
HS 100×100	20m	120	пумар	
PAN 400×400	4m	195	НуМар	
HS 80×80	20m	120		
	$\frac{\text{dimensions}}{\text{PAN } 185 \times 395} \\ \text{HS } 37 \times 79 \\ \text{PAN } 500 \times 500 \\ \text{HS } 100 \times 100 \\ \text{PAN } 400 \times 400 \\ \text{HS } 80 \times 80 \\ \end{array}$	$\begin{array}{ c c c } \hline \textbf{dimensions} & \textbf{spatial res} \\ \hline PAN \ 185 \times 395 & 20m \\ HS \ 37 \times 79 & 100m \\ \hline PAN \ 500 \times 500 & 4m \\ HS \ 100 \times 100 & 20m \\ \hline PAN \ 400 \times 400 & 4m \\ HS \ 80 \times 80 & 20m \\ \hline \end{array}$	$\begin{array}{ c c c c } \hline \text{dimensions} & \text{spatial res} & \text{N} \\ \hline \text{PAN } 185 \times 395 & 20m & 224 \\ \hline \text{HS } 37 \times 79 & 100m & \\ \hline \text{PAN } 500 \times 500 & 4m & 125 \\ \hline \text{HS } 100 \times 100 & 20m & \\ \hline \text{PAN } 400 \times 400 & 4m & 125 \\ \hline \text{HS } 80 \times 80 & 20m & \\ \end{array}$	

1) Moffett field dataset: This dataset represents a mixed urban/rural scene. The dimensions of the PAN are 185×395 with a spatial resolution of 20m whereas the size of the HS image is 37×79 with a spatial resolution of 100m (which means a spatial resolution ratio of 5 between the two images). The HS image has been acquired by the airborne hyperspectral instrument airborne visible infrared image spectrometer (AVIRIS). This instrument is characterized by 224 bands covering the spectral range $0.4 - 2.5\mu$ m.

2) Camargue dataset: This dataset represents a rural area with different kind of crops. The dimensions of the PAN image are 500×500 pixels with a spatial resolution of 4m whereas the size of the HS image is 100×100 pixels with a spatial resolution of 20m, (which means a spatial resolution ratio of 5 between the two images). The HS image has been acquired by the airborne hyperspectral instrument HyMap (Hyperspectral Mapper) in 2007. The hyperspectral instrument is characterized by 125 bands covering the spectral range $0.4 - 2.5\mu$ m.

3) Garons dataset: This dataset represents a rural area with a small village. The dimension of the PAN image are 400×400 with a spatial resolution of 4m whereas the size of the HS image is 80×80 with a spatial resolution of 20m, (which means a spatial resolution ratio of 5 between the two images). This dataset has been acquired with the HyMap instrument in 2009.

B. Results and Discussion

Methods presented in Section II have been applied on the three datasets presented in Section IV-A and analyzed following the Wald's Protocol (Section III-B). Tables III, IV, V report their quantitative evaluations with respect to the quality measures detailed in Section III-B.

 TABLE III

 QUALITY MEASURES FOR THE MOFFETT FIELD DATASET

method	CC	SAM	RMSE	ERGAS
SFIM	0.92955	9.5271	365.2577	6.5429
MTF-GLP	0.93919	9.4599	352.1290	6.0491
MTF-GLP-HPM	0.93817	9.3567	354.8167	6.1992
GS	0.90521	14.1636	443.4351	7.5952
GSA	0.93857	11.2758	363.7090	6.2359
PCA	0.89580	14.6132	463.2204	7.9283
GFPCA	0.91614	11.3363	404.2979	7.0619
CNMF	0.95496	9.4177	314.4632	5.4200
Bayesian Naive	0.97785	7.1308	220.0310	3.7807
Bayesian Sparse	0.98168	6.6392	200.3365	3.4281
HySure	0.97059	7.6351	254.2005	4.3582

Figures 3, 4, 5 represent the RMSEs per pixel between the image estimated by some methods and the reference image for the three considered datasets. Note that, for sake of conciseness, some methods have not been considered here but only their improved versions are presented. More specifically, GS has been removed since GSA is an improved version of GS. Indeed, GSA is expected to give better results than GS

 TABLE IV

 QUALITY MEASURES FOR THE CAMARGUE DATASET

method	CC	SAM	RMSE	ERGAS
SFIM	0.91886	4.2895	637.1451	3.4159
MTF-GLP	0.92397	4.3378	622.4711	3.2666
MTF-GLP-HPM	0.92599	4.2821	611.9161	3.2497
GS	0.91262	4.4982	665.0173	3.5490
GSA	0.92826	4.1950	587.1322	3.1940
PCA	0.90350	5.1637	710.3275	3.8680
GFPCA	0.89042	4.8472	745.6006	4.0001
CNMF	0.9300	4.4187	591.3190	3.1762
Bayesian Naive	0.95195	3.6428	489.5634	2.6286
Bayesian Sparse	0.95882	3.3345	448.1721	2.4712
HySure	0.9465	3.8767	511.8525	2.8181

 TABLE V

 QUALITY MEASURES FOR THE GARONS DATASET

method	CC	SAM	RMSE	ERGAS
SFIM	0.77052	6.7356	1036.4695	5.1702
MTF-GLP	0.80124	6.6155	956.3047	4.8245
MTF-GLP-HPM	0.79989	6.6905	962.1076	4.8280
GS	0.80347	6.6627	1037.6446	5.1373
GSA	0.80717	6.7719	928.6229	4.7076
PCA	0.81452	6.6343	1021.8547	5.0166
GFPCA	0.63390	7.4415	1312.0373	6.3416
CNMF	0.82993	6.9522	893.9194	4.4927
Bayesian Naive	0.86857	5.8749	784.1298	3.9147
Bayesian Sparse	0.87834	5.6377	750.3510	3.7629
HySure	0.86080	6.0224	778.1051	4.0454

thanks to its adaptive estimation of the weight for generating the equivalent PAN image from the HS image, which allows the spectral distortion to be reduced. Bayesian naive approach has been also removed since the sparsity-based approach relies on a more complex prior and gives also better results. MTF-GLP and MTF-GLP-HPM yield similar results so only the latter has been considered.

Figures 6 and 7 show extracts of the final result obtained by the considered methods on the Camargue dataset in the visible (R= 704.39nm, G= 557.90nm, B= 454.5nm) and in the SWIR (R= 1216.7nm, G= 1703.2nm, B= 2159.8nm) domains, respectively.

Figures 8, 9 and 10 show pixel spectra recovered by the fusion methods, which correspond to 10th, 50th and 90th percentile of RMSE, respectively. Those spectra have been selected by choosing GSA as the reference for RMSE value. GSA have been chosen since it is a classical approach that has been widely used in literature and also gives good results. To ensure a reasonable number of figures, only visual results and some spectra of the Camargue dataset has been reported in this article. The results for the two other datasets can be found in the supporting document [86] available online⁵. In

⁵http://openremotesensing.net



Fig. 3. RMSE between the methods' result and the reference image, per pixel for the Moffett field dataset



Fig. 4. RMSE between the methods' result and the reference image, per pixel for the Camargue dataset



Fig. 5. RMSE between the methods' result and the reference image, per pixel for the Garons dataset

particular, because of the nature of the Garons dataset (village with lot of small buildings) and the chosen ratio of 5, worse results have been obtained than for the two first datasets since



Fig. 6. Details of original and fused Camargue dataset HS image in the visible domain. (a) reference image, (b) interpolated HS image, (c) SFIM, (d) MTF-GLP-HPM, (e) GSA, (f) PCA, (g) GFPCA, (h) CNMF, (i) Bayesian Sparse, (j) HySure

a lot of mixing is presented in the HS image.

A visual analysis of the result shows that most of the fusion approaches considered in this paper give good results, excepted two methods: PCA and GFPCA. PCA belongs to the class of CS methods which are known to be characterized by their high fidelity in rendering the spatial details but their generation of significant spectral distortion. This is clearly visible in Figure 6 (f), where significant differences of color can be observed with respect to the reference image, in particular when examining the different fields. GFPCA here also performs poorly. Compared with PCA, there is less spectral distortion but the included spatial information seems to be not sufficient, since the fused image is significantly blurred. Spatial information provided by PCA is better since the main information of HS image (where the spatial information is contained) is replaced by the high spatial information contained in the PAN image. When using GFPCA, the guided filter controls the amount of spatial information added to the data, so not all the spatial information may be added to avoid to modify the spectral information too much. For the Moffett field dataset, GFPCA performs a little bit better since, in this dataset, there is a lot of large areas. Thus blur is less present whereas, in the Garons



Fig. 7. Details of original and fused Camargue dataset HS image in the SWIR domain. (a) reference image, (b) interpolated HS image, (c) SFIM, (d) MTF-GLP-HPM, (e) GSA, (f) PCA, (g) GFPCA, (h) CNMF, (i) Bayesian Sparse, (j) HySure



Fig. 8. Luminance of the pixel corresponding to the 10th percentile of the RMSE (Camargue dataset)

dataset, GFPCA performs worse since this image consists of numerous small features, leading to more blurring effects. As a consequence, in this case, GFPCA performs worse than PCA.

To analyze the spectrum in detail, chosen thanks to RMSE



Fig. 9. Luminance of the pixel corresponding to the 50th percentile of the RMSE (Camargue dataset)



Fig. 10. Luminance of the pixel corresponding to the 90th percentile of the RMSE (Camargue dataset)

percentiles, some additional information about the corresponding pixels are needed. Fig. 9 corresponds to a pixel in the reference image which represents a red building. Since in the HS image this building is mixed with its neighborhood, we do not have the same information between the reference image ("pure" spectrum) and the HS image ("mixed" spectrum). Fig. 8 corresponds to a pixel in a vegetation area, no mixing is present and very good results have been obtained for all the methods. For Fig. 10, the pixel belongs to a small building not visible in the HS image and spectral mixing is then also present. More generally, spectra in the HS and reference images differ since some mixing processes occur in the HS image. Thus, the HS pansharpening methods are expected to provide spectra that are more similar to the HS spectra (which contains the available spectral information) than the reference (which has information missing in the HS which should not be found in the result, unless successful unmixing has been conducted). However, it is important to note that for Fig.9, Bayesian methods and HySure successfully recover spectra that are more similar to the reference spectrum than the HS spectrum.

Table VI report the computational times required by each HS pansharpening methods on the Camargue dataset those values have been obtained with a Intel Core i5 3230M 2.6 GHz with 8 GB RAM. Based on this table, these methods can be classified as follows:

- Methods which do not work well for HS pansharpening: PCA, GS, GFPCA
- Methods which work well with a low time of computation (few seconds): GSA, MRA methods, Bayesian Naive
- Methods which work well with an average time of computation (around one minute): CNMF
- Methods which work well (slightly better) with an important time of computation (few minutes, depends greatly on the size of the dataset): Bayesian Sparse and HySure.

 TABLE VI

 COMPUTATIONAL TIMES OF THE DIFFERENT METHODS (IN SECONDS)

method	Moffett	Camargue	Garons
SFIM	1.26	3.47	2.74
MTF-GLP	1.86	4.26	4.00
MTF-GLP-HPM	1.71	4.25	2.98
GS	4.77	8.29	5.56
GSA	5.52	8.73	5.99
PCA	3.46	8.92	6.09
GFPCA	2.58	8.51	4.36
CNMF	10.98	47.54	23.98
Bayesian Naive	1.31	7.35	3.07
Bayesian Sparse	133.61	485.13	259.44
HySure	140.05	296.27	177.60

To summarize, the comparison of the different methods performances for RMSE curves and quality measures confirms than PCA and GFPCA does not provide good results for HS pansharpening (GFPCA is know to perform much better on HS+RGB data). The other methods perform well, with Bayesian approaches having slightly better result but with a higher computational cost. The favorable fusion performance obtained by the Bayesian methods can be explained, in part, by the fact that they rely on a forward modeling of the PAN and HS images and explicitly exploit the spatial and spectral degradations applied to the target image. However, these algorithms may suffer from performance discrepancies when the parameters of these degradations (i.e., spatial blurring kernel, sensor spectral response) are not perfectly known. In particular, when these parameters are fully unknown and need to be fixed, they can be estimated jointly with the fused image, as in [53], or estimated from the MS and HS images in a preprocessing step, following the strategies in [78] or [35]. CS methods are fast to compute and easy to implement. They provide good spatial results but poor spectral results with significant spectral distortions, in particular when considering PCA and GS. GSA provides better results than the two other methods thanks to its adaptive weight estimation reducing the spectral distortion of the equivalent PAN image created from the HS image. MRA methods are fast, MTF-based methods give better results than SFIM and perform as well as the most competitive algorithms with higher computational complexity. SFIM does not perform as well than the other MRA methods since it used a box filter which should give less good result. In our experimentations, results from SFIM are not so different from those obtained with the MTF-based methods. This may come from the fact that semi-synthetic datasets are used so MTF may not be fully used to its potential. Table VII report these pro and cons associated with each HS pansharpening method.

Finally, note that, in our experimentations, no registration error and temporal misalignment have been considered, which suggests that the robustness of the different methods has not been fully analyzed. When such problems may occur, CS and MRA methods may perform better thanks to their great robustness. In particular, CS methods are robust against misregistration error and aliasing, whereas MRA approaches are robust against aliasing and temporal misalignment. It is also worthy to note that the quality of a fusion method should also be related to a specific application (such as classification or target detection). Indeed, a method providing images with good performance metrics may or may not be the best for this specific application.

V. CONCLUSION

In this paper a qualitative and quantitative comparison of 11 different HS pansharpening methods was conducted, considering classical MS pansharpening techniques adapted to the HS context, and methods originally designed for HS pansharpening. More precisely, five classes of methods were presented: CS, MRA, Hybrid, Bayesian and matrix factorization. Those methods were evaluated on three different datasets representative of various scenario: mixed urban/rural area, rural area and urban area.

A careful analysis of their performances suggested a classification of these methods into four groups: i) Methods with poor fusion results (CS-based methods and GFPCA), ii) Methods with good fusion performances and low computational costs (MRA methods, GSA and Bayesian naive) that may be suitable for fusing large scale images, which is often the case for spaceborne hyperspectral imaging missions, iii) Methods with good fusion performances and reasonable computational costs (CNMF), iv) Methods with slightly better fusion results but with higher computational costs (HySure and Bayesian Sparse). Those results were obtained with semi-synthetic datasets with no registration error or temporal misalignment. Thus robustness of the methods against these issues were not taken into account. When such problems may happen, different results could be obtained and classical pansharpening methods (CS and MRA) may give better results thanks to their robustness to these specific issues.

The experiments and the quality measures presented in this paper were performed using MATLAB implementations of the algorithms. A MATLAB toolbox is made available online⁶ to the community to help improving and developing new HS pansharpening methods and to facilitate comparison of the different methods.

⁶http://openremotesensing.net

method	pros	cons
		1) Reduced performance
SFIM	1) Low computational	when compared to MTF
II.B.1	complexity	methods (since it uses a
		box filter)
	1) Performs well	
MTF-GLP	2) Low computational	
II.B.2	complexity	
	1) Performs well	
MTF-GLP-HPM	2) Low computational	
II.B.2	complexity	
	1) Spatial information	
	is well preserved	1) Low performance
GS	2) Low computational	for HS images
II.A.2	complexity	2) Significant spectral
	3) Fasy implementation	distortion
	1) Spatial information	
	is well preserved	
	2) Spectral distortion	
GSA	is reduced (compared	
	to CS)	
11.A.2	2) Low commutational	
	5) Low computational	
	complexity	
	4) Easy implementation	
	1) Spatial information	1) Low performance
PCA	is well preserved	for HS images
II.A.1	2)Low computational	2) Significant spectral
	complexity	distortion
	3) Easy implementation	-
		1) Low performance
	1) Spectral information	for HS images (work
GFPCA	is well preserved	better with RGB images)
II.C.1	2) Low computational	2) Not enough spatial
	complexity	information added (lot
		of blur)
		1) Sensor characteristics
CNMF	1) Good results	required
II.E.1	(spatial and spectral)	2) Medium computational
		cost
	1) Good results	
Bayesian Naive	(spatial and spectral)	1) Sensor characteristics
II.D.1	2) Low computational	required
	complexity	
		1) high computational
Bayesian Sparse	1) Good results	cost
II.D.2	(spatial and spectral)	2) Sensor characteristics
		required
HySure	1) Good results	1) high computational
ILD.3	(spatial and spectral)	cost

TABLE VII PROS AND CONS OF EACH METHODS

VI. ACKNOWLEDGMENT

The Garons and Camargue datasets were acquired in the frame of the PRF Enviro program (internal federative project lead at ONERA). This work was partially 13

supported by the Fundacc ao para a Ciência e Tecnologia, Portuguese Ministry of Science and Higher Education (UID/EEA/50008/2013), project PTDC/EEI-PRO/1470/2012, and grant SFRH/BD/87693/2012. Part of this work has been also supported by the Hypanema ANR Project n°ANR-12-BS03-003 and by ANR-11-LABX-0040-CIMI within the program ANR-11-IDEX-0002-02. This work was supported by the SBO-IWT project Chameleon: Domain-specific Hyperspectral Imaging Systems for Relevant Industrial Applications, and FWO project G037115N "Data fusion for image analysis in remote sensing". This work is supported by China Scholarship Council. This work is supported by DGA (Direction Generale de l'Armement). This work was finally supported by the ERC CHESS (CHallenges in Extraction and Separation of Sources) and by ANR HYEP ANR 14-CE22-0016-01 (Agence National de la Recherche, Hyperspectral Imagery for Environmental Planning).

REFERENCES

- [1] [Online]. Available: http://smsc.cnes.fr/PLEIADES/index.htm
- [2] S. Michel, P. Gamet, and M.-J. Lefevre-Fonollosa, "HYPXIM a hyperspectral satellite defined for science, security and defence users," in *Proc. IEEE GRSS Workshop Hyperspectral Image SIgnal Process.: Evolution in Remote Sens. (WHISPERS)*, Lisbon, Portugal, June 2011, pp. 1–4.
- [3] L. Alparone, L. Wald, J. Chanussot, C. Thomas, P. Gamba, and L. M. Bruce, "Comparison of pansharpening algorithms: Outcome of the 2006 GRS-S data fusion contest," *IEEE Trans. Geosci. and Remote Sens.*, vol. 45, no. 10, pp. 3012–3021, Oct. 2007.
- [4] G. Vivone, L. Alparone, J. Chanussot, M. Dalla Mura, Garzelli, and G. Licciardi, "A critical comparison of pansharpening algorithms," in *Proc. IEEE Int. Conf. Geosci. Remote Sens. (IGARSS)*, July 2014, pp. 191–194.
- [5] B. Aiazzi, L. Alparone, S. Baronti, A. Garzelli, and M. Selva, "25 years of pansharpening: a critical review and new developments," in *Signal and Image Processing for Remote Sensing*, 2nd ed., C. H. Chen, Ed. Boca Raton, FL: CRC Press, 2011, ch. 28, pp. 533–548.
- [6] C. Thomas, T. Ranchin, L. Wald, and J. Chanussot, "Synthesis of multispectral images to high spatial resolution: a critical review of fusion methods based on remote sensing physics," *IEEE Trans. Geosci. and Remote Sens.*, vol. 46, no. 5, pp. 1301–1312, May 2008.
- [7] W. Carper, T. M. Lillesand, and P. W. Kiefer, "The use of intensityhue-saturation transformations for merging SPOT panchromatic and multispectral image data," *Photogramm. Eng. Remote Sens.*, vol. 56, no. 4, pp. 459–467, April 1990.
- [8] T.-M. Tu, S.-C. Su, H.-C. Shyu, and P. S. Huang, "A new look at IHS-like image fusion methods," *Information Fusion*, vol. 2, no. 3, pp. 117–186, Sept. 2001.
- [9] P. S. Chavez Jr., S. C. Sides, and J. A. Anderson, "Comparison of three different methods to merge multiresolution and multispectral data: Landsat TM and SPOT panchromatic," *Photogramm. Eng. Remote Sens.*, vol. 57, no. 3, pp. 295–303, March 1991.
- [10] P. S. Chavez and A. Y. Kwarteng, "Extracting spectral contrast in landsat thematic mapper image data using selective principal component analysis," *Photogramm. Eng. Remote Sens.*, vol. 55, no. 3, pp. 339–348, 1989.
- [11] V. Shettigara, "A generalized component substitution technique for spatial enhancement of multispectral images using a higher resolution data set," *Photogramm. Eng. Remote Sens.*, vol. 58, no. 5, pp. 561–567, 1992.
- [12] V. P. Shah, N. Younan, and R. L. King, "An efficient pan-sharpening method via a combined adaptative-PCA approach and contourlets," *IEEE Trans. Geosci. and Remote Sens.*, vol. 56, no. 5, pp. 1323–1335, May 2008.
- [13] C. Laben and B. Brower, "Process for enhacing the spatial resolution of multispectral imagery using pan-sharpening," U.S. Patent US6 011 875, 2000.
- [14] S. Mallat, "A theory for multiresolution signal decomposition: the wavelet representation," *IEEE Trans. Patt. Anal. Mach. Intell.*, vol. 11, no. 7, pp. 674–693, July 1989.

- [15] G. P. Nason and B. W. Silverman, "The stationary wavelet transform and some statistical applications," in *Wavelets and Statistics*, A. Antoniadis and G.Oppenheim, Eds. New York, NY: Springer-Verlag, 1995, vol. 103, pp. 281–299.
- [16] M. J. Shensa, "The discrete wavelet transform: wedding the a trous and Mallat algorithms," *IEEE Trans. Signal Process.*, vol. 40, no. 10, pp. 2464–2482, Oct. 1992.
- [17] P. J.Burt and E. H. Adelson, "The Laplacian pyramid as a compact image code," *IEEE Trans. Comm.*, vol. 31, no. 4, pp. 532–540, April 1983.
- [18] M. N. Do and M. Vetterli, "The contourlet transform: an efficient directional multiresolution image representation," *IEEE Trans. Image Process.*, vol. 14, no. 12, pp. 2091–2106, Dec. 2005.
- [19] J. F. J.-L. Starck and F. Murtagh, "The undecimated wavelet decomposition and its reconstruction," *IEEE Trans. Image Process.*, vol. 16, no. 2, pp. 297–309, Feb. 2007.
- [20] C. Ballester, V. Caselles, L. Igual, J. Verdera, and B. Rougé, "A variational model for P+XS image fusion," *Int. J. Computer Vision*, vol. 5969, no. 1, pp. 43–58, 2006.
- [21] F. Palsson, J. Sveinsson, M. Ulfarsson, and J. A. Benediktsson, "A new pansharpening algorithm based on total variation," *IEEE Geosci. and Remote Sensing Lett.*, vol. 11, no. 1, pp. 318–322, Jan. 214.
- [22] X. He, L. Condat, J. Bioucas Dias, J. Chanussot, and J. Xia, "A new pansharpening method based on spatial and spectral sparsity priors," *IEEE Trans. Image Process.*, vol. 23, no. 9, pp. 4160–4174, Sept 2014.
- [23] M. Moeller, T. Wittman, and A. L. Bertozzi, "A variational approach to hyperspectral image fusion," in *SPIE Defense, Security, and Sensing*, 2009.
- [24] A. Garzelli, B. Aiazzi, S. Baronti, M. Selva, , and L. Alparone, "Hyperspectral image fusion," in *Proc. Hyperspectral Workshop*, 2010, pp. 17–19.
- [25] L. Alparone, B. Aiazzi, S. Baronti, and A. Garzelli, *Remote Sensing Image Fusion*, ser. Signal and Image Processing of Earth Observations. Boca Raton, FL: CRC Press, 2015.
- [26] G. Vivone, L. Alparone, J. Chanussot, M. Dalla Mura, Garzelli, and G. Licciardi, "Multi-resolution analysis and component substitution techniques for hyperspectral pansharpening," in *Proc. IEEE Int. Conf. Geosci. Remote Sens. (IGARSS)*, July 2014, pp. 2649–2652.
- [27] J. M. Bioucas Dias, A. Plaza, N. Dobigeon, M. Parente, Q. Du, P. Gader, and J. Chanussot, "Hyperspectral unmixing overview: Geometrical, statistical, and sparse regression-based approaches," *IEEE J. Sel. Topics Appl. Earth Observ. Remote Sens.*, vol. 5, no. 2, pp. 354–379, Apr. 2012.
- [28] C. Souza Jr, L. Firestone, L. M. Silva, and D. Roberts, "Mapping forest degradation in the Eastern Amazon from SPOT 4 through spectral mixture models," *Remote Sens. Environment*, vol. 87, no. 4, pp. 494–506, 2003, large Scale Biosphere Atmosphere Experiment in Amazonia.
- [29] A. Mohammadzadeh, A. Tavakoli, and M. J. V. Zoej, "Road extraction based on fuzzy logic and mathematical morphology from pansharpened IKONOS images," *The Photogrammetric Record*, vol. 21, no. 113, pp. 44–60, Feb. 2006.
- [30] F. Laporterie-Déjean, H. de Boissezon, G. Flouzat, and M.-J. Lefèvre-Fonollosa, "Thematical and statistical evaluations of five panchromatic/multispectral fusion methods on simulated PLEIADES-HR image," *Information Fusion*, vol. 6, pp. 193–212, 2005.
- [31] G. A. Licciardi, A. Villa, M. M. Khan, and J. Chanussot, "Image fusion and spectral unmixing of hyperspectral images for spatial improvement of classification maps," in *Proc. IEEE Int. Conf. Geosci. Remote Sens.* (*IGARSS*), 2012, pp. 7290–729.
- [32] N. Yokoya, T. Yairi, and A. Iwasaki, "Coupled nonnegative matrix factorization unmixing for hyperspectral and multispectral data fusion," *IEEE Trans. Geosci. and Remote Sens.*, vol. 50, no. 2, pp. 528–537, Feb. 2012.
- [33] Q. Wei, N. Dobigeon, and J.-Y. Tourneret, "Bayesian fusion of multiband images," *IEEE J. Sel. Topics Signal Process.*, 2015, to appear.
- [34] —, "Bayesian fusion of hyperspectral and multispectral images," in Proc. IEEE Int. Conf. Acoust., Speech, and Signal Processing (ICASSP), Florence, Italy, May 2014, pp. 3176–3180.
- [35] M. Simões, J. Bioucas Dias, L. Almeida, and J. Chanussot, "A convex formulation for hyperspectral image superresolution via subspace-based regularization," *IEEE Trans. Geosci. and Remote Sens.*, 2015, to appear.
- [36] Q. Wei, J. M. Bioucas Dias, N. Dobigeon, and J.-Y. Tourneret, "Hyperspectral and multispectral image fusion based on a sparse representation," *IEEE Trans. Geosci. and Remote Sens.*, vol. 53, no. 7, pp. 3658– 3668, Sept. 2015.
- [37] B. Aiazzi, S. Baronti, and M. Selva, "Improving component substitution Pansharpening through multivariate regression of MS+Pan data," *IEEE*

Trans. Geosci. and Remote Sens., vol. 45, no. 10, pp. 3230–3239, Oct. 2007.

- [38] S. Baronti, B. Aiazzi, M. Selva, A. Garzelli, and L. Alparone, "A theoretical analysis of the effects of aliasing and misregistration on pansharpened imagery," *IEEE J. Sel. Topics Signal Process.*, vol. 5, no. 3, pp. 446–453, June 2011.
- [39] G. Vivone, L. Alparone, J. Chanussot, M. Dalla Mura, Garzelli, and G. Licciardi, "A critical comparison among pansharpening algorithms," *IEEE Trans. Geosci. and Remote Sens.*, vol. 53, no. 5, pp. 2565–2586, may 2015.
- [40] T.-M. Tu, P. S. Huang, C.-L. Hung, and C.-P. Chang, "A fast intensityhue-saturation fusion technique with spectral adjustment for IKONOS imagery," *IEEE Geosci. and Remote Sensing Lett.*, vol. 1, no. 4, pp. 309–312, 2004.
- [41] B. Aiazzi, S. Baronti, F. Lotti, and M. Selva, "A comparison between global and context-adaptive pansharpening of multispectral images," *IEEE Geosci. and Remote Sensing Lett.*, vol. 6, no. 2, pp. 302–306, April 2009.
- [42] G. Vivone, R. Restaino, M. Dalla Mura, G. Licciardi, and J. Chanussot, "Contrast and error-based fusion schemes for multispectral image pansharpening," *IEEE Geosci. and Remote Sensing Lett.*, vol. 11, no. 5, pp. 930–934, May 2014.
- [43] J. G. Liu, "Smoothing filter based intensity modulation: a spectral preserve image fusion technique for improving spatial details," *Int. J. Remote Sens.*, vol. 21, no. 18, pp. 3461–3472, Dec. 2000.
- [44] L. Alparone, B. Aiazzi, S. Baronti, and A. Garzelli, "Sharpening of very high resolution images with spectral distortion minimization," in *Proc. IEEE Int. Conf. Geosci. Remote Sens. (IGARSS)*, July 2003, pp. 458–460.
- [45] B. Aiazzi, L. Alparone, S. Baronti, A. Garzelli, and M. Selva, "MTFtailored multiscale fusion of high-resolution MS and Pan imagery," *Photogramm. Eng. Remote Sens.*, vol. 72, no. 5, pp. 591–596, May 2006.
- [46] K. He, J. Sun, and X. Tang, "Guided image filtering," *IEEE Trans. Patt. Anal. Mach. Intell.*, vol. 35, no. 6, pp. 1397–1409, 2013.
- [47] X. Kang, J. Li, and J. A. Benediktsson, "Spectral-spatial hyperspectral image classification with edge-preserving filtering," *IEEE Trans. Geosci.* and Remote Sens., vol. 52, no. 5, pp. 2666–2677, 2014.
- [48] W. Liao, X. Huang, F. Coillie, S. Gautama, A. Pizurica, W. Philips, H. Liu, T. Zhu, M. Shimoni, G. Moser, and D. Tuia, "Processing of multiresolution thermal hyperspectral and digital color data: Outcome of the 2014 IEEE GRSS data fusion contest," *IEEE J. Sel. Topics Appl. Earth Observ. Remote Sens.*, Submitted.
- [49] W. Liao, B. Goossens, J. Aelterman, H. Luong, A. Pizurica, N. Wouters, W. Saeys, and W. Philips, "Hyperspectral image deblurring with pca and total variation," in *Proc. IEEE GRSS Workshop Hyperspectral Image SIgnal Process.: Evolution in Remote Sens. (WHISPERS)*, Florida, US, June 2013, pp. 1–4.
- [50] R. C. Hardie, M. T. Eismann, and G. L. Wilson, "MAP estimation for hyperspectral image resolution enhancement using an auxiliary sensor," *IEEE Trans. Image Process.*, vol. 13, no. 9, pp. 1174–1184, Sept. 2004.
- [51] Y. Zhang, S. De Backer, and P. Scheunders, "Noise-resistant waveletbased Bayesian fusion of multispectral and hyperspectral images," *IEEE Trans. Geosci. and Remote Sens.*, vol. 47, no. 11, pp. 3834–3843, Nov. 2009.
- [52] M. Joshi and A. Jalobeanu, "MAP estimation for multiresolution fusion in remotely sensed images using an IGMRF prior model," *IEEE Trans. Geosci. and Remote Sens.*, vol. 48, no. 3, pp. 1245–1255, March 2010.
- [53] Q. Wei, N. Dobigeon, and J.-Y. Tourneret, "Bayesian fusion of multispectral and hyperspectral images with unknown sensor spectral response," in *Proc. IEEE Int. Conf. Image Processing (ICIP)*, Paris, France, Oct. 2014, pp. 698–702.
- [54] M. Simões, J. Bioucas Dias, L. B. Almeida, and J. Chanussot, "Hyperspectral image superresolution: An edge-preserving convex formulation," in *Proc. IEEE Int. Conf. Image Processing (ICIP)*, Paris, France, Oct. 2014, pp. 4166–4170.
- [55] R. Molina, A. K. Katsaggelos, and J. Mateos, "Bayesian and regularization methods for hyperparameter estimation in image restoration," *IEEE Trans. Image Process.*, vol. 8, no. 2, pp. 231–246, 1999.
- [56] R. Molina, M. Vega, J. Mateos, and A. K. Katsaggelos, "Variational posterior distribution approximation in Bayesian super resolution reconstruction of multispectral images," *Applied and Computational Harmonic Analysis*, vol. 24, no. 2, pp. 251 – 267, 2008.
- [57] A. K. Gupta and D. K. Nagar, *Matrix Variate Distributions*, ser. Monographs and surveys in pure and applied mathematics. Boca Raton, FL: Chapman & Hall/CRC, 2000, vol. 104.

- [58] M. D. Farrell Jr and R. M. Mersereau, "On the impact of PCA dimension reduction for hyperspectral detection of difficult targets," *IEEE Geosci.* and Remote Sensing Lett., vol. 2, no. 2, pp. 192–195, 2005.
- [59] J. M. Nascimento and J. M. Bioucas Dias, "Vertex component analysis: a fast algorithm to unmix hyperspectral data," *IEEE Trans. Geosci. and Remote Sens.*, vol. 43, no. 4, pp. 898–910, April 2005.
- [60] Q. Wei, N. Dobigeon, and J.-Y. Tourneret, "Bayesian fusion of multispectral and hyperspectral images using a block coordinate descent method," in Proc. IEEE GRSS Workshop Hyperspectral Image SIgnal Process.: Evolution in Remote Sens. (WHISPERS), Tokyo, Japan, June 2015.
- [61] —, "Fast fusion of multi-band images based on solving a Sylvester equation," 2015, submitted. [Online]. Available: http: //arxiv.org/abs/1502.03121/
- [62] S. Mallat, A wavelet tour of signal processing. New York: Academic Press, 1999.
- [63] J.-L. Starck, E. Candes, and D. Donoho, "The curvelet transform for image denoising," *IEEE Trans. Image Process.*, vol. 11, no. 6, pp. 670– 684, 2002.
- [64] N. Ahmed, T. Natarajan, and K. Rao, "Discrete cosine transform," *IEEE Trans. Computers*, vol. C-23, no. 1, pp. 90–93, 1974.
- [65] M. Elad and M. Aharon, "Image denoising via sparse and redundant representations over learned dictionaries," *IEEE Trans. Image Process.*, vol. 15, no. 12, pp. 3736–3745, 2006.
- [66] O. G. Guleryuz, "Nonlinear approximation based image recovery using adaptive sparse reconstructions and iterated denoising – Part I: theory," *IEEE Trans. Image Process.*, vol. 15, no. 3, pp. 539–554, 2006.
- [67] A. Gelman, J. B. Carlin, H. S. Stern, D. B. Dunson, A. Vehtari, and D. B. Rubin, *Bayesian data analysis*, 3rd ed. Boca Raton, FL: CRC press, 2013.
- [68] X. Bresson and T. Chan, "Fast dual minimization of the vectorial total variation norm and applications to color image processing," *Inverse Probl. and Imag.*, vol. 2, no. 4, pp. 455–484, 2008.
- [69] M. Afonso, J. Bioucas Dias, and M. Figueiredo, "An augmented Lagrangian approach to the constrained optimization formulation of imaging inverse problems." *IEEE Trans. Image Process.*, vol. 20, no. 3, pp. 681–95, 2011.
- [70] O. Berné, A. Tielens, P. Pilleri, and C. Joblin, "Non-negative matrix factorization pansharpening of hyperspectral data: An application to mid-infrared astronomy," in *Proc. IEEE GRSS Workshop Hyperspectral Image SIgnal Process.: Evolution in Remote Sens. (WHISPERS)*, 2010, pp. 1–4.
- [71] R. Kawakami, J. Wright, Y. Tai, Y. Matsushita, M. Ben-Ezra, and K. Ikeuchi, "High-resolution hyperspectral imaging via matrix factorization," in *Proc. IEEE Int. Conf. Comp. Vision and Pattern Recognition* (CVPR), 2011, pp. 2329–2336.
- [72] A. Charles, B. Olshausen, and C. Rozell, "Learning sparse codes for hyperspectral imagery," *IEEE J. Sel. Topics Signal Process.*, vol. 5, no. 5, pp. 963–978, 2011.
- [73] B. Huang, H. Song, H. Cui, J. Peng, and Z. Xu, "Spatial and spectral image fusion using sparse matrix factorization," *IEEE Trans. Geosci.* and Remote Sens., vol. 52, no. 3, pp. 1693–1704, 2014.
- [74] M. Veganzones, M. Simes, G. Licciardi, J. M. Bioucas Dias, and J. Chanussot, "Hyperspectral super-resolution of locally low rank images from complementary multisource data," in *Proc. IEEE Int. Conf. Image Processing (ICIP)*, Paris, France, Oct. 2014, pp. 703–707.
- [75] N. Yokoya, T. Yairi, and A. Iwasaki, "Hyperspectral, multispectral, and panchromatic data fusion based on coupled non-negative matrix factorization," in *Proc. IEEE GRSS Workshop Hyperspectral Image SIgnal Process.: Evolution in Remote Sens. (WHISPERS)*, 2011, pp. 1–4.
- [76] D. D. Lee and H. S. Seung, "Learning the parts of objects by nonnegative matrix factorization," *Nature*, vol. 401, pp. 788–791, 1999.
- [77] D. C. Heinz and C. -I Chang, "Fully constrained least-squares linear spectral mixture analysis method for material quantification in hyperspectral imagery," *IEEE Trans. Geosci. and Remote Sens.*, vol. 29, no. 3, pp. 529–545, March 2001.
- [78] N. Yokoya, N. Mayumi, and A. Iwasaki, "Cross-calibration for data fusion of EO-1/Hyperion and Terra/ASTER," *IEEE J. Sel. Topics Appl. Earth Observ. Remote Sens.*, vol. 6, pp. 419–2013, April 2013.
- [79] L. Wald, T. Ranchin, and M. Mangolini, "Fusion of satellite images of different spatial resolutions: Assessing the quality of resulting image," *IEEE Trans. Geosci. and Remote Sens.*, vol. 43, pp. 1391–1402, 2005.
- [80] I. Amro, J. Mateos, M. Vega, R. Molina, and A. K. Katsaggelos, "A survey of classical methods and new trends in pansharpening of multispectral images," *EURASIP J. Adv. Signal Process.*, vol. 2011, no. 1, pp. 1–22, 2011.

- [81] Q. Du, N. H. Younan, R. L. King, and V. P. Shah, "On the performance evaluation of pan-sharpening techniques," *IEEE Geosci. and Remote Sensing Lett.*, vol. 4, pp. 518–22, Oct. 2007.
- [82] Z. Wang and A. C. Bovik, "A universal image quality index," *IEEE Signal Process. Lett.*, vol. 9, no. 3, pp. 81–84, March 2002.
- [83] L. Alparone, B. Aiazzi, S. Baronti, A. Garzelli, F. Nencini, and M. Selva, "Multispectral and panchromatic data fusion assessment without reference," *Photogramm. Eng. Remote Sens.*, vol. 74, no. 2, pp. 193–200, Feb. 2008.
- [84] G. Piella and H.Heijmans, "A new quality metric for image fusion," in *Proc. IEEE Int. Conf. Image Processing (ICIP)*, vol. 2, 2003, pp. 173–176.
- [85] L. Wald, Data Fusion : Definitions and Architectures Fusion of images of different spatial resolutions. Les Presses de l'Ecole des Mines, 2002.
- [86] L. Loncan, L. B. Almeida, J. M. Bioucas-Dias, X. Briottet, J. Chanussot, N. Dobigeon, S. Fabre, W. Liao, G. Licciardi, M. Simoes, J.-Y. Tourneret, M. Veganzones, G. Vivone, Q. Wei, and N. Yokoya, "Hyperspectral pansharpening: a review – Complementary results and supporting materials," Tech. Rep., 2015. [Online]. Available: http://openremotesensing.net