

Impurities enhance caking in lactose powder

Mélanie Carpin, H. Bertelsen, A. Dalberg, Claire Roiland, J. Risbo, Pierre Schuck, Romain Jeantet

▶ To cite this version:

Mélanie Carpin, H. Bertelsen, A. Dalberg, Claire Roiland, J. Risbo, et al.. Impurities enhance caking in lactose powder. Journal of Food Engineering, 2017, 198, pp.91-97. 10.1016/j.jfoodeng.2016.11.013 . hal-01408010

HAL Id: hal-01408010

https://hal.science/hal-01408010

Submitted on 3 Apr 2017

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Accepted Manuscript

Impurities enhance caking in lactose powder

M. Carpin, H. Bertelsen, A. Dalberg, C. Roiland, J. Risbo, P. Schuck, R. Jeantet

PII: S0260-8774(16)30420-4

DOI: 10.1016/j.jfoodeng.2016.11.013

Reference: JFOE 8718

To appear in: Journal of Food Engineering

Received Date: 30 August 2016
Revised Date: 13 October 2016

Accepted Date: 18 November 2016

Please cite this article as: Carpin, M., Bertelsen, H., Dalberg, A., Roiland, C., Risbo, J., Schuck, P., Jeantet, R., Impurities enhance caking in lactose powder, *Journal of Food Engineering* (2016), doi: 10.1016/j.jfoodeng.2016.11.013.

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.



1 Impurities enhance caking in lactose powder pr

- 2 M. Carpin^{1,2,4}, H. Bertelsen², A. Dalberg², C. Roiland³, J. Risbo⁴, P. Schuck¹, R. Jeantet¹
- 3 ¹ UMR 1253, Science and Technology of Milk and Eggs, Inra-Agrocampus Ouest, 35042
- 4 Rennes cedex, France
- 5 ² Arla Foods Ingredients Group P/S, 6920 Videbæk, Denmark
- 6 ³ University of Rennes 1, UMR CNRS 6226, Campus de Beaulieu, Rennes, France
- ⁴ Department of Food Science, University of Copenhagen, 1958 Frederiksberg C, Denmark
- 8 melanie.carpin@inra.fr
- 9 hans.bertelsen@arlafoods.com
- 10 anders.dalberg@arlafoods.com
- 11 claire.roiland@univ-rennes1.fr
- 12 jri@food.ku.dk
- 13 pierre.schuck@inra.fr
- 14 romain.jeantet@agrocampus-ouest.fr
- 15 Abstract:
- 16 Caking of lactose and other dry ingredients is a common problem in the dairy and food
- 17 industries. The lactose production process includes different purification steps, depending on
- 18 the type of lactose produced. The aim of this study was therefore to investigate how the
- remaining impurities (i.e. non-lactose components) affect the caking tendency of the final
- 20 powder. The results from a combination of different methods, including dynamic vapor sorption,
- 21 characterization of the physicochemical composition and assessment of caking with a ring
- shear tester, suggested humidity caking. Larger amounts of impurities in the lactose powder
- 23 resulted in enhanced moisture sorption and greater caking tendency. These findings emphasize
- the importance of controlling the washing and purification steps throughout the production
- 25 process in order to limit caking in the final product.
- 26 Keywords:
- 27 Caking, lactose, impurities, amorphous, moisture sorption, ring shear tester

29

30

31

32

33

34

35

36

37

38

39

40

41

42

43

44

45

46

47

48

49

50

51

52

53

54

55

56

As a consequence of trade globalization and significant advances in drying and powder handling technology, the volume of food ingredients produced in powder form has dramatically increased in the past decade. Indeed, as dry ingredients have better storage stability and are easier to transport, a major part of the recent investments in the dairy sector has been focused on dry products (International Dairy Federation, 2015). In particular, whey, which was traditionally considered as waste, has gained considerable attention, and its different constituents (whey proteins, lactose, lactoferrin, milk salts, etc.) are now separated and sold as high value products in the dry state. The range of applications for whey-derived dry ingredients has thus expanded considerably. Among the whey-derived ingredients, lactose is used in various food and pharmaceutical applications. For example, lactose powder is the main ingredient of infant formulae and provides an important source of carbohydrates to match the composition of human milk. Lactose can be found in different forms, but the most common and stable form is crystallized α-lactose monohydrate. α-lactose monohydrate is produced industrially by evaporation of whey followed by slow cooling in a crystallization tank. Typically, the harvested crystals are then washed and dried in a fluidised bed dryer. Different purification steps can make the process more complex, depending on the type of lactose produced. For example, calcium and phosphate are usually removed prior to evaporation in order to increase the running time of the evaporators and reduce fouling. The lactose production process has been described in greater detail by Hourigan et al. (2013).The handling and storage of lactose and other dry food products can be complicated by a problem that is well known in the food industry, i.e. the unwanted agglomeration of powder particles observed as lumps of various sizes and hardness. This process, known as caking, results in non-conform products and significant economic loss. Although α-lactose monohydrate is generally considered to be a stable product, caking of lactose is a major problem in the dairy industry. The three most relevant caking mechanisms in food powders have recently been reviewed (Carpin et al., 2016). Amorphous caking is the main mechanism in amorphous powders whereby a temperature increase above the glass transition temperature (Tg) of the

material leads to viscous flow to contact points. Due to the plasticization effect of water, storage at relatively high relative humidity (RH) can lower the Tq and initiate amorphous caking. Humidity is also a crucial factor in the second caking mechanism, called humidity caking. Water molecules are adsorbed on the surface of the particles and liquid bridges can be formed by capillary condensation. If the RH increases above the deliquescence relative humidity (DRH) of the material, the solid can dissolve in the surrounding water layer. A subsequent decrease in RH results in solid bridges and thus stronger links between particles. Finally, the third mechanism, mechanical caking, is an aggravating factor rather than a caking mechanism in itself. Mechanical pressure on a powder bed brings the particles closer to each other, thereby increasing the interactions between particles and the number of contact points. Mechanical caking therefore worsens any caking tendency due to humidity or the presence of amorphous material. In view of the above three mechanisms, it is obvious that caking can be influenced by several parameters such as water content, particle size and shape, amorphous content, etc. Several studies have investigated how these factors affect caking of α-lactose monohydrate. Listiohadi et al. (2008, 2005a, 2005b) focused on the role of the different lactose polymorphs, amorphous lactose and the milling procedure. Bronlund and Paterson (2004) examined the effects of particle size and temperature on the moisture sorption characteristics of lactose powder and temperature-induced moisture migration in a bag of lactose (Paterson and Bronlund, 2009). As humidity has a crucial role in both amorphous and humidity caking, any impurity that can enhance lactose hygroscopicity, such as peptides and minerals, can be detrimental. This parameter has not been investigated to date. The aim of this study was therefore to characterize the effects of impurities on lactose caking.

79 2. Materials and methods

57

58

59

60

61

62

63

64

65

66

67

68

69

70

71

72

73

74

75

76

77

78

81

82

83

- 80 2.1. Production of lactose powders on a pilot scale
 - Decalcified and decolored ultrafiltered (UF) whey permeate was obtained from Arla Foods
 Ingredients, Viby J, Denmark. The solids content was raised to 60% in a Centritherm CT2
 evaporator (Flavourtech, Griffith, Australia). The concentrate was cooled in a tank from 79 ℃ to
 11 ℃ in about 18 hours for lactose crystallization purposes. For the washing step, a Lemitec

MD80 laboratory decanter centrifuge (Lemitec GMBH, Berlin, Germany) was used to produce five lactose powders with different washing grades. The slurry was first run through the decanter once without water for a pre-wash (Wash 0). The prewashed slurry was then mixed with water at different water / lactose slurry (w/w) ratios: 1/3 (Wash 0.3), 1/2 (Wash 0.5), 1/1 (Wash 1) and 2/1 (Wash 2). The different washing grades of slurry were run through the decanter once more, and then dried on an Anhydro SFD 47 spin flash dryer (SPX Flow Technology, Søborg, Denmark) with an inlet temperature of 105 °C and an outlet temperature of 82-87 °C. Finally the powders were packaged in two layers of plastic bags and a Kraft paper bag before transportation to the analysis laboratory where they were poured into airtight plastic containers of various sizes to minimize the headspace. The powders were stored at 20 $^{\circ}$ C before analysis. Pharmaceutical grade lactose (Lactochem ® Crystals, batch number 663108) was purchased from DFE pharma (Goch, Germany) for comparison with the experimental lactose powders produced at different washing grades. Pharmaceutical grade lactose is produced industrially from edible grade lactose by re-dissolving the lactose in clean water followed by additional purification steps (Paterson, 2009). It is therefore the most pure lactose available on the market. Pharmaceutical grade lactose was mixed with distilled water to make a 15% (w/w) lactose solution which was left to stand at 40 ℃ for one hour. The solution was then cooled to 20 ℃ and spray dried on a pilot-scale spray dryer (GEA Niro A/S, Mobile Minor Dryer (MMD), Soeborg, Denmark) to obtain amorphous lactose. The inlet and outlet air temperatures were 200 ℃ and 90 °C, respectively, and the feed flow rate was 40 mL.min⁻¹.

2.2. Chemical composition

85

86

87

88

89

90

91

92

93

94

95

96

97

98

99

100

101

102

103

104

105

106

107

108

109

110

111

112

Protein, moisture and ash content were determined according to the methods described by Schuck et al. (2012). Total nitrogen content determined by Kjeldahl with a 6.38 conversion factor will be designated as protein content. Given the filtration steps in the lactose process, it is however unlikely that proteins remain in the final powder. Therefore, impurities formally expressed as protein may more likely be smaller nitrogen containing components such as peptides and amino-acids. Analysis of moisture and ash content was carried out in triplicate and the protein content was determined in duplicate. The lactose content was then calculated by

113 difference. Individual minerals (calcium, phosphorus, sodium, potassium and magnesium) were 114 measured by inductively coupled plasma optical emission spectrometry (ICP-OES) on an 115 Optima 2000 DV (PerkinElmer, Waltham, Massachusetts, USA). Chloride was determined by 116 potentiometry. All minerals were analyzed in duplicate. 117 2.3. Sieving and measurement of particle size 118 The lactose powders of different washing grades were sieved to separate 80, 160, 250, 355 and 119 500 µm fractions. The particle size distribution of the powders was measured by laser light 120 scattering using a Malvern Mastersizer 2000 equipped with a Scirocco 2000 dry dispersion unit 121 (Malvern Instruments, Worchestershire, UK). 122 2.4. Moisture sorption measurements 123 Sorption isotherms of powders were obtained with a Dynamic Vapor Sorption (DVS) Advantage 124 (Surface Measurement Systems Ltd., London, UK) equipped with a Cahn microbalance. The 125 experiments were carried out in duplicate at a constant temperature (25 °C) using a nitrogen flow rate of 200 standard cm³.min⁻¹. Approximately 40 mg of powder was subjected to ramping 126 127 of RH from 0% to 95% in 10%-RH steps with water as solvent. Equilibrium was considered to be 128 reached if the rate of change in mass was less than 0.0002 %.min⁻¹. 129 2.5. Particle morphology — scanning electron microscopy (SEM) 130 The surface morphology of the lactose samples was examined using a scanning electron 131 microscope (SEM, JEOL JCM-6000 - NeoScope II, Tokyo, Japan) operating at 15 kV. Samples 132 were mounted on an aluminium stub and coated with a thin layer of gold (JEOL JFC-1300 auto 133 fine coater) prior to analysis. The photomicrographs were taken at ×1,000 magnification. 134 2.6. Solid-state Nuclear Magnetic Resonance (NMR) 135 13C NMR spectra were obtained using proton decoupling, magic angle spinning (MAS) and

cross polarization (CP). The spectra were recorded on a Bruker Avance I WB 300 MHz

(7T) instrument (Bruker, Billerica, USA) at ambient temperature according to the method

described by Gustafsson et al. (1998), with the following parameters: spinning rate 5 kHz,

136

137

138

contact time 2 ms, acquisition time 147 ms, sweep widths 2190 ppm and delay between pulses of 3 s. For each spectrum, about 150,000 transients were cumulated with 49k data points. The spectra were referenced to trimethylsilane (TMS).

2.7. Quantification of caking

Caking, also known as time consolidation, was measured with a ring shear tester (RST-XS, Schulze-Schüttgutmesstechnik, Wolfenbüttel, Germany). The measurement procedure has been described in detail by Schulze (2008). First the yield locus of each powder was measured for a normal stress at preshear σ_{pre} corresponding to a consolidation stress σ_c of around 9.3 kPa. This value was chosen to simulate powder consolidation at the bottom of a flexible intermediate bulk container (FIBC), also called a Big Bag. Three points of incipient flow were used to draw the yield locus. Once the initial yield locus was established, the powder was preconditioned using the same σ_{pre} as above and stored at 20 $^{\circ}$ C and 60% RH for four d ays. A temperature and humidity data logger was used to check the storage conditions. Loads of 2 kg (corresponding to a consolidation stress of 9.3 kPa) were applied to the samples for the duration of storage. After storage the samples were sheared to obtain the time yield locus. From this, the unconfined yield strength σ_1 and the ratio of σ_c to σ_1 , called *ffc*, were identified. By definition, a sample with an *ffc* lower than 1 was considered to be caked (Jenike, 1964). For each powder except Wash 0.3, the *ffc* was measured in triplicate. As the amount of Wash 0.3 was limited, the analysis could only be performed in duplicate.

Results and discussion

159 3.1. Chemical composition

The results showed, as expected, that the higher the washing grade, the fewer the remaining impurities measured in the final powder (i.e. nitrogen containing components expressed as proteins, free moisture, ash and minerals) (Table 1 and Fig. 1). The remaining ash and protein levels were highly correlated (R^2 =0.972). Moreover, ash and protein levels were found to correlate better with moisture measured by loss on drying at 87°C for 16 hours (R^2 =0.995 and R^2 =0.972, respectively) than with moisture measured after drying at 105°C for 5 hours (R^2 =0.709

and R²=0.840, respectively) (data not shown). The method to measure food moisture by loss on 166 167 drying has been criticized for the lack of discrimination between the different types of water, 168 distinguished by the extent of binding with solids (Isengard, 2001). "Free" and "bound" water can 169 indeed be difficult to differentiate, and the results at 105 ℃ may overestimate the "free" water 170 content of the samples. 171 The amounts of all minerals decreased with a higher degree of washing, with the exception of 172 calcium (Fig. 1). The decalcification and subsequent separation steps applied to the UF 173 permeate reduced the initial calcium and phosphorus content (Hourigan et al., 2013). Thus the 174 starting material for the trial already had low calcium and phosphorus content from the 175 beginning. Fig. 1 shows that it was not possible to reduce the calcium content much further by 176 washing the lactose crystals. This suggests that, as mentioned by Guu and Zall (1992), most of 177 the remaining calcium formed strong complexes with lactose. Interestingly, phosphate did not 178 follow the same trend as calcium. Guu and Zall (1991) reported that calcium phosphate 179 precipitates may act as nuclei facilitating lactose crystallization. It was therefore expected that 180 calcium phosphate could be trapped inside the crystals, thereby preventing it from being washed 181 away. This was however not observed in the present study. 182 Using a basic mass balance with simple assumptions, the expected amount of impurities in the 183 different washing grades after decantation was calculated from the amount measured in Wash 0. 184 The water content in the decanter output was considered the same for all washing grades (i.e. 185 10%) and it was assumed that no lactose was dissolved during the decantation process. The 186 calculated levels of protein and ash were in general lower than the measured amounts (data not 187 shown). The inclusion of droplets of mother liquor inside the crystals, as suggested by 188 Mathlouthi and Rogé (2003) for sucrose, could explain the limited effect of washing. 189 3.2. Moisture sorption 190 Sieving the powders led to standardization of particle size distribution (Fig. 2). Indeed it has 191 been shown that particle size can have a significant effect on moisture sorption (Stoklosa et al.,

192

2012).

193 Moisture sorption was highly dependent on the washing grade (Fig. 3). For the same particle 194 size fraction (160<x<250µm), the sorption of the unwashed powder (Wash 0) was dramatically 195 enhanced from 30% RH and the final sorption was almost ten times higher than the most 196 washed powders (Wash 1 and Wash 2). Crystalline lactose is characterized by a very low 197 hygroscopicity, with a deliquescence relative humidity (DRH) value of 95% (Salameh et al., 198 2006). However, Tereshchenko (2015) reported that, for a water soluble crystalline solid, 199 moisture sorption below the DRH was due to impurities. Enhanced sorption and reduced DRH 200 due to the presence of low levels of impurities have also been reported in a model deliquescent 201 pharmaceutical salt, in agreement with our results (Guerrieri et al., 2007). The sorption behavior 202 of the different lactose powders is thus likely to originate from differences in impurity contents 203 (Table 1). This was further evidenced by a comparison with pharmaceutical grade lactose. The 204 latter was found to contain about 20 times less ash and proteins than the most washed powder 205 produced during the pilot trial (Table 1). The difference in moisture sorption behavior between 206 Wash 2 and the pharmaceutical grade powder was very clear: indeed, Wash 2 powder adsorbed 207 almost 10 times more moisture than pharmaceutical grade lactose above 50% RH (Fig. 4). 208 As moisture sorption occurs primarily on the surface of crystals, a comparison of the surface of 209 the different washing grade lactose powders was undertaken by scanning electron microscopy 210 (Fig. 5). All samples from the pilot trial (Fig. 5A-D) presented a rough surface. Wash 0 powder 211 had many pores (Fig. 5A), which would provide greater possibilities for capillary condensation 212 and could therefore partly explain the enhanced moisture sorption previously reported (Fig. 3). 213 Compared to pharmaceutical grade lactose, which presented a smooth surface (Fig. 5E), Wash 214 0.5, 1 and 2 powders had significant amounts of fines agglomerated on the surface of their large 215 tomahawk crystals (Fig. 5B-D). Mathlouthi and Rogé (2003) showed that the presence of fines in 216 sucrose crystals enhanced moisture sorption and that the greater the number of fine particles, 217 the closer the sorption behavior of the sample to that of the amorphous state. Their findings are 218 consistent with the moisture sorption isotherms obtained in this study, showing less sorption for 219 pharmaceutical grade lactose (Fig. 4). 220 Moreover, a higher concentration of impurities on the surface of the crystals would probably lead 221 to enhanced sorption behavior. On the other hand, impurities trapped inside the crystals are not

expected to have a significant role in moisture sorption. This point requires further attention to identify which impurities (nature, concentration) are present on the surface of the particles.

3.3. Role of amorphous material

222

223

224

225

226

227

228

229

230

231

232

233

234

235

236

237

238

239

240

241

242

243

244

245

246

247

248

One particular kind of impurity is amorphous material, which is well known for its high hygroscopicity compared to the crystalline counterpart. Amorphous lactose can be formed on the surface of lactose particles during rapid drying and milling (Vollenbroek et al., 2010). As the samples were dried in a spin flash dryer in the present study, the possibility of formation of amorphous material due to rapid drying cannot be excluded. The impurities remaining after the washing process (e.g. minerals and protein fractions) were likely to retain some mother liquor which could turn into amorphous lactose upon drying. The presence of increasing, yet very low, amounts of amorphous lactose at lower washing grades could thus be another explanation for the enhanced hygroscopicity of the corresponding powders. However, no recrystallization event was observed in the moisture sorption curves, contrary to previously reported sorption isotherms of predominantly crystalline materials containing some amorphous content (Sheokand et al., 2014). For example, a weight increase and subsequent decrease due to amorphous lactose absorbing moisture and crystallizing has been reported in samples containing between 0.125 and 0.5 w/w % amorphous material (Buckton and Darcy, 1995). However, the presence of amorphous material in our samples cannot be ruled out from the sorption isotherms. Residual amorphous lactose might be present at lower levels than those studied by Buckton and Darcy (1995). Moreover, Buckton and Darcy (1995) used physical mixes of spray-dried lactose and α-lactose monohydrate in their study, which can facilitate the crystallization event compared to a situation where the amorphous material is in close contact with crystalline portions on the same particle. The samples with different washing grades were therefore analyzed by solid-state NMR. A detection limit of 0.5% amorphous lactose has been reported for this technique (Gustafsson et al., 1998), which is among the lowest levels for the detection of amorphous material in

predominantly crystalline materials (Giron et al., 2007). No disorder indicating amorphous

material was detected in our samples (Fig. 6). It can therefore be concluded that if any amorphous material was present in the samples, the amorphous content was probably below 0.5%. However, the analysis of very low levels of amorphous material is always challenging in terms of sample storage and sampling. Indeed, amorphous material can crystallize during storage before analysis, thus preventing its identification.

3.4. Caking tendency

249

250

251

252

253

254

255 For the different particle size distributions investigated, the unwashed powder was characterized 256 by a poorer flowability and hence a higher tendency to caking than the washed powders (Fig. 7). 257 Moreover, a ffc after storage of 0.6 ± 0.1 was obtained for non-sieved Wash 0.3 while non-258 sieved pharmaceutical grade lactose still flowed easily after the four-day storage. It was not 259 straightforward to discriminate Wash 1 and Wash 2 powders from each other. 260 It is clear from these results that higher levels of impurities lead to greater risk of caking. In the 261 present study, the samples were stored at 20 °C and 60% RH for four days in the ring shear 262 cells before measurement of caking tendency. Amorphous lactose stored at room temperature 263 (20-25 ℃) has been reported to crystallize at about 40% RH (Jouppila and Roos, 1994; 264 Thomsen et al., 2005). Amorphous caking was therefore expected to occur if the samples 265 contained amorphous lactose. However, as mentioned in section 3.3., the solid state NMR 266 analysis did not indicate the presence of disordered structures, meaning that the amorphous 267 content of the samples was probably below 0.5%. Thus amorphous caking cannot be considered 268 to be the main mechanism responsible for the caking tendency observed here. In his work on 269 caking of crystalline lactose, Bronlund (1997) also showed that amorphous caking was only 270 marginal for amorphous content below 5%, and that the major contribution to caking from the 271 amorphous material occurred through moisture sorption. 272 The sorption isotherms of Wash 0, 1, 2 powders and pharmaceutical grade lactose showed that 273 the difference in sorption behavior was important at 60% and room temperature (Fig. 3 and Fig. 274 4). During the caking experiments, the samples were given time to equilibrate with ambient air at 275 60% RH. Due to humidity caking, the caking tendency was therefore expected to be enhanced 276 for samples which could adsorb more moisture. This was confirmed by the flowability results

277 after storage (Fig. 7). Only Wash 1 and Wash 2 showed similar flowability values, although 278 Wash 1 was found to adsorb twice as much moisture as Wash 2 at 60% RH according to the 279 DVS measurements. The difference in the impurity levels and thus moisture sorption between 280 these two powders was probably too small for the ring shear tester to detect a difference 281 between the caking tendencies of the two powders. 282 As humidity caking could be evidenced by the caking measurements with the ring shear tester, 283 the repeatability of the measurement was considered acceptable. In order to discriminate 284 between samples with similar sorption behaviors (such as Wash 1 and Wash 2), it might be 285 helpful to increase the repeatability even further. As pointed out by Hartmann and Palzer (2011), 286 one drawback of the ring shear cells is that they are almost closed, which hampers moisture 287 exchange between the powder and the surrounding atmosphere. If the impurities are not 288 homogeneously distributed in the powder, moisture sorption might be heterogeneous at a local 289 level, leading to various degrees of consolidation. It is however interesting to note the low 290 standard deviation associated with the results for Wash 0 and Wash 0.3. It seems therefore that 291 once humidity caking has reached a certain level, it systematically proceeds to strong and 292 repeatable caking. This level may be associated with the DRH which, as explained in section 293 3.2., can be significantly decreased by the presence of impurities. Moreover, a critical step in the 294 experimental procedure is relieving the shear cells from the consolidation pressure and moving 295 them from the humidity controlled chamber to the ring shear tester. This operation requires care 296 as interactions between the powder particles can be damaged. It is thus consistent that the 297 stronger the interactions between particles, the better the caking reproducibility.

4. Conclusions

298

299

300

301

302

303

Time consolidation experiments with a ring shear tester constitute an appropriate method to discriminate between samples with different caking tendencies. Combined with DVS measurements and characterization of the physicochemical composition, including the amorphous content, the caking test results suggested a humidity caking mechanism. The presence of impurities in lactose powder was found to greatly enhance moisture sorption and

to prevent caking in the final product.

307	Acknowledgments ACCEPTED MANUSCRIPT
308	This work was partially funded by Innovation Fund Denmark. The authors wish to thank Jens
309	Kristian Bech for his input in the preparation of the pilot trial and Morten Nielsen for his great
310	help in conducting the trial. We are grateful to Betina Mikkelsen and Anne Dolivet for showing us
311	how to conduct SEM imaging and for all the physicochemical characterization analyses.
312	References
313	Bronlund, J., 1997. The modelling of caking in bulk lactose. Massey University.
314	Bronlund, J., Paterson, T., 2004. Moisture sorption isotherms for crystalline, amorphous and
315	predominantly crystalline lactose powders. Int. Dairy J. 14, 247-254. doi:10.1016/S0958-
316	6946(03)00176-6
317	Buckton, G., Darcy, P., 1995. The use of gravimetric studies to assess the degree of crystallinity
318	of predominantly crystalline powders. Int. J. Pharm. 123, 265-271.
319	Carpin, M., Bertelsen, H., Bech, J.K., Jeantet, R., Risbo, J., Schuck, P., 2016. Caking of lactose:
320	A critical review. Trends Food Sci. Technol. 53, 1–12. doi:10.1016/j.tifs.2016.04.002
321	Giron, D., Monnier, S., Mutz, M., Piechon, P., Buser, T., Stowasser, F., Schulze, K., Bellus, M.,
322	2007. Comparison of quantitative methods for analysis of polyphasic pharmaceuticals. J.
323	Therm. Anal. Calorim. 89, 729–743. doi:10.1007/s10973-006-7962-y
324	Guerrieri, P., Salameh, A.K., Taylor, L.S., 2007. Effect of small levels of impurities on the water
325	vapor sorption behavior of ranitidine HCl. Pharm. Res. 24, 147-56. doi:10.1007/s11095-
326	006-9134-y
327	Gustafsson, C., Lennholm, H., Iversen, T., Nystro, C., 1998. Comparison of solid-state NMR and
328	isothermal microcalorimetry in the assessment of the amorphous component of lactose. Int.
329	J. Pharm. 174, 243-252.
330	Guu, M.Y.K., Zall, R.R., 1991. Lactose Crystallization - Effects of Minerals and Seeding. Process
331	Biochem. 26, 167–172. doi:10.1016/0032-9592(91)80013-F

- 332 Guu, Y.K., Zall, R.R., 1992. Nanofiltration Concentration Effect on the Efficacy of Lactose Crystallization. J. Food Sci. 57, 735–739. doi:10.1111/j.1365-2621.1992.tb08084.x
- Hartmann, M., Palzer, S., 2011. Caking of amorphous powders Material aspects, modelling and applications. Powder Technol. 206, 112–121. doi:10.1016/j.powtec.2010.04.014

- Hourigan, J., Lifran, E., Vu, L., Listiohadi, Y., Sleigh, R., 2013. Lactose: Chemistry, Processing,
- and Utilization, in: Smithers, G.W., Augustin, M.A. (Eds.), Advances in Dairy Ingredients.
- 338 John Wiley & Sons, Inc., pp. 31–69.
- International Dairy Federation, 2015. The world dairy situation 2015, Bulletin of the International
- 340 Dairy Federation 481/2015. doi:10.1111/j.1471-0307.2010.00573.x
- 341 Isengard, H.D., 2001. Water content, one of the most important properties of food. Food Control
- 342 12, 395–400. doi:10.1016/S0956-7135(01)00043-3
- Jenike, A.W., 1964. Storage and flow of solids, Bulletin 123 of the University of Utah. Salt Lake
- 344 City.
- Jouppila, K., Roos, Y.H., 1994. Glass Transitions and Crystallization in Milk Powders. J. Dairy
- 346 Sci. 77, 2907–2915. doi:10.3168/jds.S0022-0302(94)77231-3
- 347 Listiohadi, Y., Hourigan, J., Sleigh, R., Steele, R., 2008. Moisture sorption, compressibility and
- 348 caking of lactose polymorphs. Int. J. Pharm. 359, 123–34.
- 349 doi:10.1016/j.ijpharm.2008.03.044
- 350 Listiohadi, Y., Hourigan, J., Sleigh, R., Steele, R., 2005a. Role of amorphous lactose in the
- 351 caking of α-lactose monohydrate powders. Aust. J. dairy Technol. 60, 19–32.
- 352 Listiohadi, Y., Hourigan, J., Sleigh, R., Steele, R., 2005b. Effect of milling on the caking
- behaviour of lactose. Aust. J. Dairy Technol. 60, 214–224.
- 354 Mathlouthi, M., Rogé, B., 2003. Water vapour sorption isotherms and the caking of food
- 355 powders. Food Chem. 82, 61–71. doi:10.1016/S0308-8146(02)00534-4
- 356 Paterson, A.H.J., 2009. Production and uses of lactose, in: McSweeney, P.L.H., Fox, P.F.
- 357 (Eds.), Advanced Dairy Chemistry. Springer New York, pp. 105-120. doi:10.1007/978-0-
- 358 387-84865-5
- 359 Paterson, A.H.J., Bronlund, J.E., 2009. The practical implications of temperature induced
- 360 moisture migration in bulk lactose. J. Food Eng. 91, 85–90.
- 361 doi:10.1016/j.jfoodeng.2008.08.021
- 362 Salameh, A.K.A., Mauer, L.J.L., Taylor, L.S.L., 2006. Deliquescence Lowering in Food
- 363 Ingredient Mixtures. J. Food Sci. 71, E10–E16. doi:10.1111/j.1365-2621.2006.tb12392.x
- 364 Schuck, P., Dolivet, A., Jeantet, R., 2012. Analytical Methods for Food and Dairy Powders.

365	Wiley-Blackwell, Oxford, UK. doi:10.1002/9781118307397					
303	Wiley-Blackwell, Oxford, Ox. doi:10-1002/9761.1030/3917					
366	Schulze, D., 2008. Powders and Bulk Solids: Behavior, Characterization, Storage and Flow.					
367	Springer Berlin Heidelberg, Berlin, Heidelberg. doi:10.1007/978-3-540-73768-1					
368	Sheokand, S., Modi, S.R., Bansal, A.K., 2014. Dynamic Vapor Sorption as a Tool for					
369	Characterization and Quantification of Amorphous Content in Predominantly Crystalline					
370	Materials. J. Pharm. Sci. 103, 3364–3376. doi:10.1002/jps.24160					
371	Stoklosa, A.M., Lipasek, R. a., Taylor, L.S., Mauer, L.J., 2012. Effects of storage conditions					
372	formulation, and particle size on moisture sorption and flowability of powders: A study of					
373	deliquescent ingredient blends. Food Res. Int. 49, 783-791.					
374	doi:10.1016/j.foodres.2012.09.034					
375	Tereshchenko, A.G., 2015. Deliquescence: Hygroscopicity of Water-Soluble Crystalline Solids					
376	J. Pharm. Sci. doi:10.1002/jps.24589					
377	Thomsen, M.K., Jespersen, L., Sjostrom, K., Risbo, J., Skibsted, L.H., 2005. Water activity					
378	temperature state diagram of amorphous lactose. J. Agric. Food Chem. 53, 9182-9185					
379	doi:10.1021/jf0508394					
380	Vollenbroek, J., Hebbink, G. a., Ziffels, S., Steckel, H., 2010. Determination of low levels of					
381	amorphous content in inhalation grade lactose by moisture sorption isotherms. Int. J					
382	Pharm. 395, 62-70. doi:10.1016/j.ijpharm.2010.04.035					
383						

- Table 1: Composition of lactose powders as a function of degree of washing of the crystals. Results are given as average \pm standard deviation. Number of repeats = 3 for moisture and ash and 2 for proteins.
- Figure 1: Variations in the mineral content (potassium (K), chlorine (Cl), sodium (Na), phosphorus (P), calcium (Ca), and magnesium (Mg)) of lactose powder as a function of degree of washing of the lactose crystals.
- Figure 2: Particle size distributions of lactose powders for three different washing grades (0, 1, 2) but with the same particle size fraction $(160 < x < 250 \mu m)$.
- Figure 3: Moisture sorption isotherms of lactose powders with three different washing grades but the same particle size fraction (160<x<250 μ m): Wash 0 (squares), Wash 1 (circles), Wash 2 (triangles).
- Figure 4: Moisture sorption isotherms of non-sieved pharmaceutical grade lactose (circles) and the most washed lactose from the pilot trial (Wash 2) (squares).
- Figure 5: SEM images showing details of particle surface of different washing grade lactose powders: (A) Wash 0; (B) Wash 0.5; (C) Wash 1; (D) Wash 2; (E) Pharmaceutical grade lactose.
- Figure 6: 13C CP/MAS NMR spectra of (A) Wash 0; (B) Wash 0.3; (C) pharmaceutical grade lactose; (D) amorphous lactose.
- Figure 7: ffc of non-sieved (crosses) and sieved (triangles) lactose powders between 160 μm and 250 μm as a function of the washing grade. The ffc was measured after storage for four days at 60% RH and 20 ℃. Each sample was consolidated under a pressure of 9.3 kPa. The flowability of pharmaceutical grade lactose after storage is included for comparison purposes.

Table 1: Composition of lactose powders as a function of degree of washing of the crystals.

Results are given as average \pm standard deviation. Number of repeats = 3 for moisture and ash and 2 for proteins.

Washing Grade	Protein (g.100g ⁻¹)	Moisture (g.100g ⁻¹)	Ash (g.100g ⁻¹)	Lactose (g.100g ⁻¹)
0	0.640 ± 0.014	1.12 ± 0.01	2.14 ± 0.05	96.09
0.3	0.332 ± 0.005	0.89 ± 0.00	0.79 ± 0.04	97.99
0.5	0.227 ± 0.006	0.77 ± 0.02	0.52 ± 0.02	98.49
1	0.152 ± 0.006	0.36 ± 0.02	0.43 ± 0.04	99.05
2	0.082 ± 0.001	0.31 ± 0.01	0.19 ± 0.00	99.42
Pharmaceutical grade lactose	0.004 ± 0.002	n.d.	0.01 ± 0.00	n.d.




Figure 1: Variations in the mineral content (potassium (K), chlorine (Cl), sodium (Na), phosphorus (P), calcium (Ca), and magnesium (Mg)) of lactose powder as a function of degree of washing of the lactose crystals.

16 Wash 0 14 Wash 1 12 ··· Wash 2 Volume Density (%) 8 6 2 0 10 Size (µm) 0.01 0.1 1 100 1000

Figure 2: Particle size distributions of lactose powders for three different washing grades (0, 1, 2) but with the same particle size fraction $(160 < x < 250 \mu m)$.




Figure 3: Moisture sorption isotherms of lactose powders with three different washing grades but the same particle size fraction (160<x<250 μ m): Wash 0 (squares), Wash 1 (circles), Wash 2 (triangles).




Figure 4: Moisture sorption isotherms of non-sieved pharmaceutical grade lactose (circles) and the most washed lactose from the pilot trial (Wash 2) (squares).

ACCEPTED MANUSCRIPT




Figure 5: SEM images showing details of particle surface of different washing grade lactose powders: (A) Wash 0; (B) Wash 0.5; (C) Wash 1; (D) Wash 2; (E) Pharmaceutical grade lactose.




Figure 6: 13C CP/MAS NMR spectra of (A) Wash 0; (B) Wash 0.3; (C) pharmaceutical grade lactose; (D) amorphous lactose.




Figure 7: ffc of non-sieved (crosses) and sieved (triangles) lactose powders between 160 μm and 250 μm as a function of the washing grade. The ffc was measured after storage for four days at 60% RH and 20 °C. Each sample was consolidated under a pressure of 9.3 kPa. The flowability of pharmaceutical grade lactose after storage is included for comparison purposes.

ACCEPTED MANUSCRIPT

- Caking of lactose results in non-conform products and significant economic loss.
- Impurities in the lactose powder increased moisture sorption and caking tendency.
- The ring shear tester is a valuable tool to assess caking.
- The washing and purification steps should be closely monitored to limit caking.