#### Projection under pairwise distance control

#### Hiba Alawieh, Nicolas Wicker, Christophe Biernacki

Laboratoire Paul Painlevé, Université Lille 1, 59655, Villeneuve d'Ascq, France.

CMStatistics 2016 9-11 December 2016

< ロ > < 同 > < 三 > < 三 >

#### Table of contents



Projection under pairwise distance control method

#### 3 Application




Projection under pairwise distance control


(4月) トイヨト イヨト

Introduction

Projection under pairwise distance control method Application Conclusions & Perspectives

### Multidimensional Data






・ロト ・四ト ・ヨト ・ヨト

臣

Projection under pairwise distance control



・ロト ・日ト ・ヨト ・ヨト

臣

# Short reminder of the PCA method

• Aim: Project the original data set in a reduced space by preserving as much of the variance from the original data set as possible.

# Short reminder of the PCA method

- Aim: Project the original data set in a reduced space by preserving as much of the variance from the original data set as possible.
- Local quality: Squared cosine of angle between the principal space and the vector of the point gives the local measure.
  - usable in linear projection.
  - unusable in non-linear projection.
  - Not interpretable as distances.


- 4 回 ト 4 三 ト

## Presentation of the method

#### Our objective

Propose a new **non-linear** projection method taking into account the **local projection quality** that is **interpretable** as distances.

• The idea is to bound the distance *d<sub>ij</sub>* by a minimal and maximal distances calculated on the projected points and the radii.



Projection under pairwise distance control

#### Basic of the method:

$$D = \begin{bmatrix} d_{11} & d_{12} & \cdots & d_{1n} \\ d_{21} & d_{22} & \cdots & d_{2n} \\ \vdots & \vdots & \vdots & \vdots \\ d_{n1} & d_{n1} & \cdots & d_{nn} \end{bmatrix} \xrightarrow{(r_1, \dots, r_n)} X = \begin{bmatrix} x_{11} & \cdots & x_{1k} \\ x_{21} & \cdots & x_{2k} \\ \vdots & \vdots & \vdots \\ x_{n1} & \cdots & x_{nk} \end{bmatrix}$$

The variables (r<sub>1</sub>,..., r<sub>n</sub>) are called radii given for each point i such that r<sub>i</sub> ∈ ℝ for all i = 1,..., n.

・ロト ・日ト ・ヨト ・ヨト

#### Characteristics of Radii

- Radii are important elements introduced to assess how much the distance ||x<sub>i</sub> − x<sub>j</sub>|| is far from d<sub>ij</sub>.
- $(r_i, r_j)$  are small  $\Rightarrow ||x_i x_j||$  is close to  $d_{ij}$ .
- Radii indicate to which extent the projection of each point is accurate.
- The local quality is then given by the values of the radii.
- Both units of  $d_{ij}$ 's and  $r_i$ 's are identical.

The projection under pairwise distance control problem can be written as the following optimization problem:

$$\mathcal{P}_{r,x}: \left\{ \begin{array}{l} \min_{r_1,\dots,r_n \in \mathbb{R}, x_1,\dots,x_n \in \mathbb{R}^k} \sum_{i=1}^n r_i \\ s.t \quad |d_{ij} - \|x_i - x_j\|| \le r_i + r_j, \text{ for } 1 \le i < j \le n \end{array} \right.$$

Problem  $\mathcal{P}_{r,x}$  is a hard non-linear optimization problem.

イロト イポト イヨト イヨト

# Simplification of problem $\mathcal{P}_{r,x}$ :

- $(x_1, ..., x_n)$  are fixed using PCA or any other projection method.
- Problem  $\mathcal{P}_r$  is a new linear optimization problem obtained after fixing  $(x_1, \ldots, x_n)$ .
- It can easily be solved in  $(r_1, \ldots, r_n)$  using linear programming.

$$\mathcal{P}_r: \left\{ \begin{array}{l} \min_{r_1, \dots, r_n \in \mathbb{R}} \sum_{i=1}^n r_i \\ s.t \quad |d_{ij} - \|x_i - x_j\| \| \le r_i + r_j, \text{ for } 1 \le i < j \le n \end{array} \right.$$

• Solution of  $\mathcal{P}_r$  is not in general the optimum of problem  $\mathcal{P}_{r,x}$ .

イロト イボト イヨト イヨト

Different ways to find a solution of problem  $\mathcal{P}_{r,x}$ :

- Lower bound.
- Optimization.
- Simulation.

イロト イヨト イヨト イヨト

臣

## Lower Bound of problem $\mathcal{P}_{r,x}$

• Let  $x_1, \dots, x_n; r_1, \dots, r_n$  a feasible solution of  $\mathcal{P}_{r,x}$ , and  $M \in \mathbb{R}$  such that:

$$M = \max_{(i,j)} \{ \| x_i - x_j \| \}.$$

イロン 不同 とくほど 不同 とう

æ

# Lower Bound of problem $\mathcal{P}_{r,x}$

• Let  $x_1, \dots, x_n; r_1, \dots, r_n$  a feasible solution of  $\mathcal{P}_{r,x}$ , and  $M \in \mathbb{R}$  such that:

$$M = \max_{(i,j)} \{ \parallel x_i - x_j \parallel \}.$$

• The objective is to find three functions noted *f*, *g*, *h* depending on *M* such that:

 $\sum_{i=1}^{n} r_i^{opt} \ge \min_{M} \max\{f(M); g(M); h(M)\} \text{ for all feasible solutions.}$ 

## Computation of the functions


**Function** f(M): This function is obtained by:

- summing all the squared constraints  $d_{ij}^2 \leq (||x_i x_j|| + r_i + r_j)^2$ .
- bounding  $\sum_{1 \le i < j \le n} ||x_i x_j||^2$  by  $\frac{n(n-1)}{3}M^2$  after maximizing the inertia of the projected points  $x_i$  under constraints:  $||x_i x_j|| \le M$  for all (i, j).

Indeed, we consider:


- (C) be the smallest circle containing the n points
- A, B and C belong to (C) and  $||x_B x_C|| = M$ .

イロト イポト イヨト イヨト



#### Projection under pairwise distance control

◆□▶ ◆御▶ ◆臣▶ ◆臣▶ 三臣…



#### Projection under pairwise distance control

・ロト ・四ト ・ヨト ・ヨト 三日

• We have proved that the maximum of the inertia  $\sum_{i=1}^{n} || y_i - g ||^2$ , under the constraint that  $y_1, \ldots, y_n$  are inside (C), is equal to  $nr^2 = n\frac{M^2}{3}$ .

Thus,

$$\sum_{i=1}^{n} \| x_i - g \|^2 \le n \frac{M^2}{3}.$$

Projection under pairwise distance control


イロト イヨト イヨト イヨト

**Function** g(M): This function is obtained using the maximal distance of  $d_{ij}$ .

$$g(M) = |M - d_{max}|$$


**Function** h(M): This function is obtained by taking four distinct points *i*, *j*, *k* and *l* such that:

- For couple (i, j),  $||x_i x_j|| = M$  and  $x_i$  or  $x_j$  is equal to zero.
- We consider the following linear combinations:



・ 同 ト ・ 三 ト ・ 三 ト

#### Illustration of the three function $\overline{f}$ , g and h.



Projection under pairwise distance control

イロト イヨト イヨト イヨ

#### Simulation algorithm

Stochastic optimization method  $\Rightarrow$  Metropolis-Hastings algorithm .

イロン 不同 とくほど 不同 とう

臣

#### Simulation algorithm

Stochastic optimization method  $\Rightarrow$  Metropolis-Hastings algorithm .

#### Target distribution

- The target distribution is related with the objective function of problem  $\mathcal{P}_{r,x}$ .
- An application *E* is given by:

$$E: \begin{array}{ccc} \mathcal{M}_{n \times p} & \longmapsto & \mathbb{R} \\ X = (x_1, \dots, x_n) & \longmapsto & E(X) = \text{Solution of } \mathcal{P}_r \text{ with } x \text{ fix.} \end{array}$$

• The target distribution is:  $\pi(s) \propto \exp(-E(x)/T)$ .

The proposal distribution  $q(X \rightarrow .)$  has been constructed by giving priority to the selection of points involved in saturated constraints.

・ロト ・日ト ・ヨト ・ヨト

The proposal distribution  $q(X \rightarrow .)$  has been constructed by giving priority to the selection of points involved in saturated constraints.

#### Proposal distribution

• For each point *i*, choose a point  $j^{(i)}$  with probability equal to:

$$P_{j(i)} = \frac{\exp\left(-\lambda(r_i + r_{j(i)} - ||d_{ij(i)} - ||x_i - x_{j(i)}|||)\right)}{\sum_{k=1, k \neq i}^{n} \exp\left(-\lambda(r_i + r_k - ||d_{ik} - ||x_i - x_k|||)\right)}$$

- Choose a constant  $c_{ij^{(i)}}$  using Gaussian distribution  $\mathcal{N}_k(0,\sigma)$ .
- Generate a matrix X\* by moving each vector x<sub>i</sub> of matrix X<sup>t-1</sup> as follows:

• If 
$$d_{ij^{(i)}} - ||x_i - x_{j^{(i)}}|| > 0$$
 then  $x_i^* = x_i + |c_{ij^{(i)}}|L_i$ .  
• else  $x_i^* = x_i - |c_{ij^{(i)}}|L_i$ .  
with  $L_i = \frac{x_i - x_{j^{(i)}}}{||x_i - x_{j^{(i)}}||}$ .

Algorithm 1 Metropolis-Hastings Algorithm:

for t = 1 to N do

Generate  $X^*$  from the proposal distribution  $q(X^{t-1} \rightarrow X^*)$ . Solve linear optimization problem  $\mathcal{P}_r$ .

Calculate 
$$\alpha = \frac{g(s^*)q(X^* \to X^{t-1})}{g(s^{t-1})q(X^{t-1} \to X^*)} = \frac{g(s^*)\prod_{i=1}^n P_j^{i^*}}{g(s^{t-1})\prod_{i=1}^n P_j^{i^{t-1}}}$$

if  $\alpha = 1$  then Take  $X^t = X^*$ . else  $u = \mathcal{U}(0; 1)$ .

if  $u \le \alpha$  then Take  $X^t = X^*$ else  $X^t = X^{t-1}$ . end if end if end for

Projection under pairwise distance control

・ロト ・日ト ・ヨト ・ヨト


臣

# Application

- Different types of real data sets are used.
  - For example: Quantitative data( Iris data set).
- Parameters of Metropolis-Hastings:
  - Parameter  $\lambda = 100$ .
  - The standard deviation  $\sigma = 0.01$ .
  - Temperature T = 100

< ロ > < 同 > < 三 > < 三 >

#### PCA




Projection under pairwise distance control

◆□ ▶ ◆□ ▶ ◆ □ ▶ ◆ □ ▶ →

Ð,

### Projection under pairwise distance



Projection under pairwise distance control

Image: A match the second s

# Conclusions & Perspectives

#### Conclusions

- new non-linear projection method based on a new local measure of projection quality.
- The quality of projection is given here by additional variables called radii.
- Radii enable to give a bound on the original distances.
- The idea can be written as an optimization problem in order to minimize the sum of the radii under some constraints.
- Different algorithms and a lower bound for the objective function are developed.

(4月) トイヨト イヨト

# Conclusions & Perspectives

#### Conclusions

- new non-linear projection method based on a new local measure of projection quality.
- The quality of projection is given here by additional variables called radii.
- Radii enable to give a bound on the original distances.
- The idea can be written as an optimization problem in order to minimize the sum of the radii under some constraints.
- Different algorithms and a lower bound for the objective function are developed.

#### Perspectives

• Improvement of the lower bound in order to assess how close the algorithms are from the minimum.

# Thank you!

◆□▶ ◆□▶ ◆臣▶ ◆臣▶ 臣 のへで