



Design of an Experimental Platform for Hybrid EEG-fMRI Neurofeedback Studies

Marsel Mano, Elise Bannier, Lorraine Perronnet, Anatole Lécuyer, Christian Barillot

► To cite this version:

Marsel Mano, Elise Bannier, Lorraine Perronnet, Anatole Lécuyer, Christian Barillot. Design of an Experimental Platform for Hybrid EEG-fMRI Neurofeedback Studies. 22nd Annual Meeting of the Organization for Human Brain Mapping (OHBM 2016), Jun 2016, Genève, Switzerland. . hal-01426072

HAL Id: hal-01426072

<https://hal.science/hal-01426072>

Submitted on 4 Jan 2017

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Design of an Experimental Platform for Hybrid EEG-fMRI Neurofeedback Studies

Presented During: Poster Session

Monday, June 27, 2016: 12:45 PM - 02:45 PM

Stand-By Time

Monday, June 27, 2016: 12:45 PM - 2:45 PM

Poster Number:

2078

Submission Type:

Abstract Submission

On Display:

Monday, June 27 & Tuesday, June 28

Authors:

Marsel Mano^{1,2}, Elise Bannier^{3,2}, Lorraine Perronnet^{1,2}, Anatole Lécuyer¹, Christian Barillot²

Institutions:

¹Inria, Hybrid Team, Rennes, France, ²Inria, VisAGeS Project-Team, Rennes, France, ³Service de Radiologie, CHU Pontchaillou, Rennes, France

E-Poster

Introduction:

Neurofeedback (NF) can be defined as the self-regulated change of a particular brain activity that is reflected in the change of a neural signal or a combination of neural signals such as EEG, fMRI, MEG, etc. There exist a variety of unimodal (i.e. EEG or fMRI) NF researches [1-2], but very few with multimodal NF applications [3]. This is primarily because of the associated technical burdens [4-6].

The purpose of this abstract is to give a technical description of the hybrid EEG-fMRI system that we have developed for our NF experiments as part of the project Hemisfer¹, including the hardware/software components and their roles.


Methods:

Our system is based on the integration and the synchronization of MR-compatible EEG and fMRI acquisitions.

The EEG signals are acquired with a 64 channel MR-compatible solution from Brain Products (BP)². The system uses a synchronization module to achieve EEG-fMRI phase synchronization, necessary for the MR gradient artifact removal [7] and an ECG channel for ballistocardiogram artifact removal [8]. These artifacts are filtered in real-time using the vendor's software (*RecView*). Next, the EEG data is sent via TCP/IP to the *EEG object* in Matlab. This object can pre-process, filter, extract features, train NF models and estimate EEG-NF in real-time. The results are sent to *Joint NF*. The MR imaging is performed on a 3T Verio Siemens scanner (VB17) with a 12-ch head coil. High resolution structural 3D T1 is acquired, followed by task-related EPI acquisitions (TR/TE=2000/23ms, 2x2x4mm³ voxel size, 32 slices). The fMRI data is sent to the acquisition computer using a client/server buffer solution from FieldTrip³. The fMRI data is received and processed in real-time by the *fMRI object* in Matlab/SPM8. Besides acquisition, this object can pre-process volumes (i.e. realignment, slice-time correction, smoothing), extract ROI(s) and features, train NF models, and estimate fMRI-NF. The NF results are sent to the *Joint NF*.

The *Joint NF* does the fusion (i.e. averaging, normalizing, modeling, etc.) of the EEG and fMRI NFs, and then sends the results to *Visualize*. *Visualize* controls the display that communicates with the subject. It has a collection of visual objects (Matlab/Psychtoolbox) for explaining the NF tasks (i.e. texts) and for animating the NF representation (i.e. 2D/3D objects). Tasks/NF are transmitted using the NordicNeurolab⁴ hardware.

Finally, the *NF Control object* contains the experiment protocol (types of tasks, duration, repetition, etc.). It starts/stops the experiment, controls all the other objects' behavior throughout the experiments, and stores the data.



*Recorder and RecView are commercial software from Brain Products

**The orange box represents software modules build in-house (Matlab and C++)

Figure 1. Diagram of the developed hybrid EEG-fMRI neurofeedback system

Results:

Our platform tests showed very good real-time performance with various pre-processing, filtering, and NF estimation and visualization methods. The entire fMRI process from acquisition to NF takes always less than 200ms, well below the TR of regular EPI sequences (2s). The same process for EEG, with NF update cycles varying 2-5Hz, is done in virtually real time (~50Hz).

Various NF tasks scenarios for regulating the measured brain activity were tested with subjects. In particular, the platform was used for a NF study on 10 subjects with over 50 sessions using three NF protocols based on motor imagery related brain activity: a) fMRI-NF, b) EEG-NF and c) EEG&fMRI-NF; and two online brain activity regulating protocols without NF. The task used in the experiments is shown in Fig.2.




Figure 2. The NF task is to put the white circle into the green box (goal). The system uses the brain activity (EEG & fMRI) to estimate the NF and then translates it into 2D motion of the circle toward the goal.

Conclusions:

The system presented here offers a reliable platform for the hybrid EEG-fMRI NF experiments in our project. Its modular architecture is easily adaptable to different experimental environments, and offers high efficiency for optimal real-time NF applications.

¹<http://www.hemisfer.cominlabs.ueb.eu/>

²<http://www.brainproducts.com/>

³<http://www.fieldtriptoolbox.org/>

⁴<http://www.nordicneurolab.com>

Imaging Methods:

Anatomical MRI
BOLD fMRI
EEG

Modeling and Analysis Methods:

Methods Development ¹
Multivariate modeling ²

Poster Session:

Poster Session - Monday

Keywords:

Electroencephaology (EEG)
FUNCTIONAL MRI
Other - Neurofeedback, real-time EEG, real-time fMRI, system desing

^{1|2}Indicates the priority used for review

Would you accept an oral presentation if your abstract is selected for an oral session?

Yes

I would be willing to discuss my abstract with members of the press should my abstract be marked newsworthy:

Yes

Please indicate below if your study was a "resting state" or "task-activation" study.

Task-activation

Healthy subjects only or patients (note that patient studies may also involve healthy subjects):

Healthy subjects

Internal Review Board (IRB) or Animal Use and Care Committee (AUC) Approval. Please indicate approval below. Please note: Failure to have IRB or AUC approval, if applicable will lead to automatic rejection of abstract.

Not applicable

Please indicate which methods were used in your research:

Functional MRI
EEG/ERP
Structural MRI

For human MRI, what field strength scanner do you use?

3.0T

Which processing packages did you use for your study?

SPM
Other, Please list - Brain Vision, FieldTrip, Psychtoolbox

Provide references in author date format

- [1] Weiskopf, N., Scharnowski, F., Veit, R., Goebel, R., Birbaumer, N., & Mathiak, K. (2004). Self-regulation of local brain activity using real-time fMRI. *Journal of Physiology-Paris*, 98(4), 357-373.
- [2] Zich, C., Debener, S., Kranczioch, C., Bleichner, M. G., Gutberlet, I., & De Vos, M. (2015). Real-time EEG feedback during simultaneous EEG-fMRI identifies the cortical signature of motor imagery. *NeuroImage*, 114, 438-447.
- [3] Zotev, V., Phillips, R., Yuan, H., Misaki, M., & Bodurka, J. (2014). Self-regulation of human brain activity using simultaneous real-time fMRI and EEG neurofeedback. *NeuroImage*, 85, 985-995.
- [4] Sulzer, J., Haller, S., Scharnowski, F., Weiskopf, N., Birbaumer, N., Blefari, M. L., . . . Seifritz, E. S. (2013). Real-time fMRI neurofeedback: progress and challenges. *Neuroimage*, 76, 386-399.
- [5] Birbaumer, N., Ruiz, S., & Sitar, R. (2013). Learned regulation of brain. *Trends in cognitive sciences*, 17(6), 295-302.
- [6] Stoeckel, L. E., Garrison, K. A., Ghosh, S. S., Wighton, P., Hanlon, C. A., Gilman, J. M., . . . Breitera, H. (2014). Optimizing real time fMRI neurofeedback for therapeutic discovery and development. *NeuroImage: Clinical*, 5, 245-255.
- [7] Allen, P. J., Josephs, O., & Turner, R. (2000). A method for removing imaging artifact from continuous EEG recorded during functional MRI. *Neuroimage*, 12(2), 230-239.
- [8] Debener, S., Mullinger, K. J., Niazy, R. K., & Bowtell, R. W. (2008). Properties of the ballistocardiogram artefact as revealed by EEG recordings at 1.5, 3 and 7 T static magnetic field strength. *International Journal of Psychophysiology*, 67(3), 189-199.

