

Acoustical and optical radiation pressures and the development of single beam acoustical tweezers

Jean-Louis Thomas, Régis Marchiano, Diego Baresch

▶ To cite this version:

Jean-Louis Thomas, Régis Marchiano, Diego Baresch. Acoustical and optical radiation pressures and the development of single beam acoustical tweezers. Journal of Quantitative Spectroscopy and Radiative Transfer, 2017, 195, pp.55-65. 10.1016/j.jqsrt.2017.01.012 . hal-01438774

HAL Id: hal-01438774 https://hal.science/hal-01438774

Submitted on 18 Jan 2017

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Acoustical and optical radiation pressures and the development of single beam acoustical tweezers

Jean-Louis Thomas^{a,*}, Régis Marchiano^b, Diego Baresch^{a,b}

 ^aSorbonne Universités, UPMC Univ Paris 06, CNRS UMR 7588, Institut des NanoSciences de Paris, 4 place Jussieu, Paris, France
 ^bSorbonne Universités, UPMC Univ Paris 06, CNRS UMR 7190, Institut Jean le Rond d'Alembert, 4 place Jussieu, Paris, France

Abstract

Studies on radiation pressure in acoustics and optics have enriched one another and have a long common history. Acoustic radiation pressure is used for metrology, levitation, particle trapping and actuation. However, the dexterity and selectivity of single-beam optical tweezers are still to be matched with acoustical devices. Optical tweezers can trap, move and positioned micron size particles, biological samples or even atoms with subnanometer accuracy in three dimensions. One limitation of optical tweezers is the weak force that can be applied without thermal damage due to optical absorption. Acoustical tweezers overcome this limitation since the radiation pressure scales as the field intensity divided by the speed of propagation of the wave. However, the feasibility of single beam acoustical tweezers was demonstrated only recently. In this paper, we propose a historical review of the strong similarities but also the specificities of acoustical and optical radiation pressures, from the expression of the force to the development of single-beam acoustical tweezers.

Keywords:

Radiation pressure in optics, Radiation pressure in acoustics, Acoustical tweezers, Pseudo-momentum

1 1. Introduction

Radiation pressure is a mean force exerted by a wave that, in many situations, pushes an interface or a particle in the direction of propagation of the

Preprint submitted to Journal of Quantitative Spectroscopy & Radiative TransferJanuary 18, 2017

^{*}Corresponding author

wave. This is usually interpreted as a transfer of linear momentum when the 4 wave is scattered. Since the wave at linear order is seen as an oscillation with 5 no mean momentum, radiation pressure is a nonlinear effect. It is common 6 to track back the beginning of the long and complex history of radiation 7 pressure to Kepler in 1619. On observing the specific shape of a comet's tail, 8 he made the assumption that the radiation from the sun exerts a force on 9 the comet's tail which changes its shape. The theoretical formulation of this 10 hypothesis was made more than two centuries later by Maxwell, who intro-11 duced the stress tensor due to electromagnetic waves [1]. Hence, it is possible 12 to compute the magnitude of the so-called *radiation pressure* exerted by the 13 EM waves which is proportional to the ratio between the energy flux and 14 the speed of the light. Therefore, the magnitude of this second order effect 15 is very weak and the experimental demonstration of this force remained a 16 real challenge for a quarter of a century. At the beginning of the twentieth 17 century, two different experiments proposed by Lebedev [2], and Nichols and 18 Hull [3] validated Maxwell's theory. On the acoustics side, the story began, 19 as often, with the pioneering works of Lord Rayleigh [4, 5] who introduced 20 the counterpart of the EM radiation pressure for acoustic waves. Shortly 21 after Rayleigh's first paper and considering the experimental observations 22 made by Dvorak on acoustic fountains [6], Altberg [7] proposed to use the 23 radiation pressure to measure the amplitude of ultrasonic waves. 24

The experimental observation of the radiation pressure for electromag-25 netic and acoustic waves was a real challenge at this early stage. As men-26 tioned above, radiation pressure is due to second order effect. But many 27 phenomena may lead to second order effect and can contribute to an appar-28 ent force and to erroneous interpretation. In optics, Crooks' radiometer was 29 claimed to be sensitive to radiation pressure. In fact, the force acting on 30 Crooks' radiometer was due to temperature gradient and its magnitude was 31 larger than the one expected. Nichols and Hull [3] improved the radiome-32 ter to avoid this effect and succeeded in measuring the radiation pressure 33 with an amplitude in agreement with Maxwell's prediction. The situation 34 is different in acoustics. Indeed, while non adiabatic behavior is common 35 for gas, it is negligible for most liquids. However, wave attenuation occurs 36 also due to viscosity. This is a transfer of a kind of linear momentum from 37 the wave to the medium which generates a flow called acoustic streaming. 38 This effect is small but grows with the propagation distance and time. It 39 has to be distinguished from the radiation force, even though the distinction 40 is not always simple [8]. Even though the energy is conserved, the situation 41

remains subtle since the definition of mean linear momentum is quite difficult 42 as soon as the wave propagates in a material medium. Indeed the momentum 43 can be split in the wave momentum and the medium momentum and this 44 is somewhat arbitrary. This leads to the controversy between Minkowsky 45 and Abraham's momentum in optics. In acoustics, this also lead to many 46 difficulties, and many papers are devoted to the concept of momentum and 47 pseudo-momentum [9], [10]. Another difficulty, mostly in acoustics, comes 48 from the different sources of nonlinearities (nonlinear terms appear both in 49 the equation of momentum conservation and in the state equation). Com-50 bined with the notion of linear momentum for acoustic waves, this is at the 51 core of the differences between Rayleigh and Langevin radiation pressure. 52 Indeed, in acoustics Rayleigh and Langevin proposed two definitions of the 53 radiation pressure due to a plane wave acting on an interface. This leads 54 to different theoretical expressions of the radiation pressure, the Rayleigh's 55 radiation pressure is sensitive to the nonlinear parameter of the medium. 56 while Langevin's is not. Brillouin proposed a different approach which is not 57 restricted to incident plane waves and he introduced a stress tensor which 58 has many similarities with the Maxwell's stress tensor [11]. 59

Radiation pressure offers the ability to apply forces without physical both
 in acoustics and in optics.

In acoustics, levitation traps have been known for a long time [12], [13], 62 [14]. Levitation traps are generally based on standing waves. For particles 63 which are very small in comparison with the wavelength, Gorkov proposed an 64 elegant theory. He derived a theoretical formulation of the radiation pressure 65 valid everywhere in an acoustic field due to standing waves. This formulation 66 is widely used because many acoustics applications meet Gorkov's assump-67 tions. For instance, acoustic radiation pressure is widely used in microfluidics 68 to act on particles carried by the flow, it is called acoustophoresis [15, 16]. 69 Even if 3D manipulations are possible, these kinds of devices do not allow 70 a selective control of a single particle [17, 18] because of the nature of the 71 acoustic field. Indeed, standing waves possess a lot of nodes and maxima 72 where the particles can be trapped in cluster. Despite its success and the 73 increasing number of applications based on this approach, it is probably not 74 the best one to develop selective traps, ie tweezers. 75

⁷⁶Solution was found in optics three decades ago by Ashkin who experi-⁷⁷mentally demonstrated the possibility to trap a single dielectric particle with ⁷⁸a single-beam gradient force with a system called Optical Tweezers (OT in ⁷⁹short). The first step which paves the way to the OT is the observation by

Ashkin of the axial acceleration of particles illuminated by a laser beam and 80 the presence of a transverse force which attracts the particles toward the 81 beam axis [19]. This transverse force is now known as gradient force. The 82 second step was proposed in the same paper [19]. In order to make an axial 83 trap, Ashkin proposed to use a second laser sending a beam, whose prop-84 agation direction is opposed to the first one. Hence, the lateral forces are 85 added while the axial ones subtract and do not engender an axial expelling. 86 Particles are trapped. From this seminal work, the development of OT took 87 sixteen years. In 1986, Ashkin et al. [20] proposed a new setup based on a 88 sharply focused laser beam able to exert a negative pulling force on a particle 89 located downstream from the focus. Hence, he demonstrated that a stable 90 equilibrium position exists and that it is possible to trap a single dielectric 91 particle with a single-beam gradient force. The negative force is due to a 92 subtle effect of the back scattering field on the particle involving the physical 93 properties of the particle and the incoming beam of light. The dexterity and 94 selectivity of optical tweezers is significantly superior to others optical traps 95 schemes and most applications of optical radiation pressure are made with 96 optical tweezers. 97

In acoustics, soon after, Du and Wu suggested theoretically to use ul-98 trasonic beams to trap and manipulate small elastic particles[21]. However, 99 their analysis derived from Gorkov's theory confirmed that every solid elas-100 tic particle was expelled from the intensity maxima by the gradient force. 101 Surprisingly in Wu's forthcoming experiment, the axial trapping failure was 102 explained by the only presence of acoustic streaming [22]. Using a coun-103 terpropagating wave this axial expelling was canceled and trapping was ob-104 tained. This set-up is the acoustic equivalent of "all-optical light trap" [23]. 105 More recently, two dimensional manipulation was achieved with a focused 106 wave when the axial expelling is stopped by a membrane [24]. In optics, 107 this scheme is coined "single beam traps" [23], [19]. In a series of papers 108 [25, 26, 27], we published the theory and the experimental observations of 109 the first acoustical tweezers. The key was the shape of the beam. Indeed, pre-110 vious studies used plane waves, gaussian beams or focused beams which exert 111 a pushing force on any solid particles. After a careful analysis of the scatter-112 ing problem [25], we proposed to use a singular beam, namely an acoustical 113 vortex, which is a beam with a zero amplitude on its center [26, 27]. Finally, 114 the experimental demonstration of the all-acoustical single beam tweezers 115 was achieved by combining all these elements [27]. Figure 1 illustrates the 116 concept of acoustical tweezers acting on a single elastic sphere. At the same 117




Figure 1: Schematic illustration of acoustical tweezers acting on a single elastic sphere. Note that, the size of the sphere is overstated to be visible

time another experimental demonstration was published [28]. The scheme are very similar, based on the same previous results, used the same kind of fields and the same kind of particles, polystyrene spheres. The main difference is that, the trapping is carried in air. Thus the buoyancy force is quite weak and the weight of the particle precludes any direct demonstration of the axial pulling force.

The goal of this paper is to give the key concepts which make optical and 124 acoustical tweezers fascinating devices able to control one particle remotely. 125 Therefore, the radiation pressure due to EM or acoustical waves is presented 126 in section 1. Special attention is paid to the derivation of Maxwell's stress 127 tensor and its analogous Brillouin's stress tensor. These two tensors show 128 that even though the radiation pressure is a nonlinear effect, it can be com-129 puted from the first order wave fields both in optics and acoustics. Therefore, 130 solving the canonical problem of a sphere illuminated by an arbitrary shaped 131 incident beam is mandatory. This is done thanks to the Generalized Lorenz-132

Mie Theory in optics and its counterpart in acoustics, which are discussed 133 in section 3. The GLMT provides a complete framework allowing to express 134 the radiation pressure exerted on a sphere from the physical properties of the 135 sphere and the parameter of the beam. The special case of small particles 136 compared to the wavelength is discussed for acoustic waves in order to make 137 bridges with usual formulations (Gorkov theory). Section 4 is devoted to 138 the comparison of optical and acoustical tweezers. In particular, the choices 139 associated to the properties of elastic particles and the incident beam are 140 discussed in details for the acoustical case. Finally, a presentation of the 141 advantages and the drawbacks of the two kinds of tweezers is proposed. 142

¹⁴³ 2. Radiation pressure and stress tensor

In this section, we review and compare the mathematical expression for radiation pressure in optics and in acoustics. We emphasize the strong similarities of the final expressions even though the derivation is different to accommodate the specificity of each field. At the end, we compare the optical and acoustical radiation pressures exerted by a plane wave and their relations with pseudo-momentum.

¹⁵⁰ 2.1. Radiation pressure tensor for an optical field

The first step consists in writing the equation of conservation of mechanical momentum and taking the average in time. The change in momentum of free charges, \mathbf{P}_{mech} , is related to the forces applied, i.e the Lorentz force:

$$\frac{\partial \mathbf{P}_{mech}}{\partial t} = \int_{V} \left(\rho \mathbf{E} + \mathbf{J} \wedge \mathbf{B}\right) dV.$$
(1)

First we consider a homogeneous medium : $\nabla \epsilon_{ij}^r = 0$ and $\nabla \mu_{ij}^r = 0$, where ϵ^r and μ^r are respectively the relative permitivity and the relative permeability. The latin subscripts (i, j) are used for spatial coordinates. From this equation and using Maxwell equations for a homogeneous medium without any electrostriction or magnetostriction, one can easily derive a continuity equation [29]:

$$\frac{\partial}{\partial t} \left(\mathbf{P}_{mech} + \int_{V} \mathbf{G}_{M} dV \right) + \int_{V} \nabla \cdot \left(-\mathcal{M} \right) dV = 0, \qquad (2)$$

160 with

$$\mathcal{M}_{i,j} = E_i D_j + B_i H_j - 1/2 \left(E_k D_k + B_k H_k \right) \delta_{ij} \tag{3}$$

$$\mathbf{G}_M \qquad = \mathbf{D} \wedge \mathbf{B} = \mathbf{E} \wedge \mathbf{H} / c_n^2 = \mathbf{S}_o / c_n^2 \tag{4}$$

In these equations, c is the speed of light in vacuum, c_n the phase velocity 161 of light in the medium of index n. \mathbf{G}_M is known as the Minkowski pseudo-162 momentum, \mathcal{M} is the Maxwell stress tensor and \mathbf{S}_o is the Poynting vector. 163 If the medium considered contains no free charge carrier, $\mathbf{P}_{mech} = 0$, we ob-164 tain a continuity equation for the Minkowsky pseudo-momentum, \mathbf{G}_{M} [9], 165 and $-\mathcal{M}$ is its flux. Note that the derived continuity equation, Eq. 2, is ob-166 tained with the assumption of a homogeneous medium. The general equation 167 contains two terms proportional to $\nabla \epsilon_{ij}^r 0$ and $\nabla \mu_{ij}^r$ and is not a continuity 168 equation. Hence Eq. 3 is based on the homogeneity of the medium, i.e in-169 variance with respect to a spatial translation of the material medium. This 170 remark emphasizes the difference with the true linear momentum conserva-171 tion. Indeed, the linear momentum is related to the invariance with respect 172 to translation of spatial coordinates [9]. 173

The radiation pressure is a mean force, the next step is to take the time average, noted $\langle \rangle$, of Eq. 3 for a medium with no free charge. Note that for any stationary of periodic field, the mean of the derivative in time is equal to zero. This yieds:

$$\nabla \cdot \langle \mathcal{M} \rangle = 0 \tag{5}$$

When there is an interface, for instance for a dielectric particle $\nabla \epsilon_{ij}^r \neq 0$, the conservation of $\langle \mathcal{M} \rangle$ is no longer true and a force is applied. This force is equal to the integral of the stress tensor on the surface of the particle, Σ :

$$\mathbf{F} = \int_{S} \langle \mathcal{M} \rangle \cdot \mathbf{n} dS \tag{6}$$

where **n** is the unit vector normal to the surface element of the particle and pointing outward.

However using the conservation of the flux of pseudo-momentum, Eq. 5, and the theorem of divergence, the integral can be performed on any closed surface, S_R , outside the particle.

$$\mathbf{F} = \int_{S} \langle \mathcal{M} \rangle \cdot \mathbf{n} dS = \int_{S_{R}} \langle \mathcal{M} \rangle \cdot \mathbf{n}_{R} dS_{R}$$
(7)

One last remark, the definition of $\mathcal{M}_{i,j}$, Eq. 3, shows that all terms are quadratic quantities. This yields that this tensor can be computed at order with the linear fields.

189 2.2. Radiation pressure tensor for an acoustical field

In optics we have obtained a stress tensor, the Maxwell stress tensor, and 190 identified the radiation pressure as the average of the stress applied on the 191 particle surface. The radiation pressure is of second order since all terms 192 appearing in the expression of the Maxwell stress tensor are quadratic with 193 respect to the electric and magnetic fields. In acoustics, the stress tensor is 194 well identified and, the force on the object is by definition the integral of the 195 stress tensor on the surface of the particle. For a fluid the stress tensor σ_{ij} 196 reduces to the pressure $-P\delta_{ij}$. However an acoustic wave is a displacement of 197 the material particles of the medium of propagation. Therefore the surface of 198 the object is moving and the amplitude of this displacement is proportional to 199 the acoustic field. We can conclude that, as in the optical case, this quantity 200 is at least of second order: 201

$$\mathbf{F} = -\int_{S(t)} P \mathbf{n} dS \tag{8}$$

²⁰² and the radiation pressure is the mean component of this force

$$\langle \mathbf{F} \rangle = -\langle \int_{S(t)} P \mathbf{n} dS \rangle \tag{9}$$

To get an expression more tractable and make an analogy with optical radiation pressure, the fixed Euler coordinates are more convenient. The two points of view, Lagrange and Euler coordinates, are equivalent [30]. The tensorial theory of radiation pressure in Euler coordinates was established by Brillouin in a series of paper and an account of this contribution and these references can be found in his text book, [11]. As in optics, the first step is to write the continuity equation for momentum:

$$\frac{\partial \rho \mathbf{v}}{\partial t} + \nabla \cdot \boldsymbol{\mathcal{B}} = 0 \tag{10}$$

$$\mathcal{B}_{ij} = \rho v_i v_j + P \delta_{ij} \tag{11}$$

where ρ is the specific mass and **v** the particle velocity. This equation can be integrated in a volume bounded on one side by the vibrating surface of the particle and on the other side by a fixed surface in the fluid medium, Fig.2.2. Using the divergence theorem, we get:

$$\int_{V(t)} \frac{\partial \rho \mathbf{v}}{\partial t} dV + \int_{S(t)} \mathcal{B} \cdot \mathbf{n}' dS + \int_{S_R} \mathcal{B} \cdot \mathbf{n}_R dS_R = 0$$
(12)

 \mathbf{n}' is outward-pointing with respect to V(t) and hence is the opposite of \mathbf{n} as defined in Eq. 9. The first term would cancel with time averaging if we could commute the integral volume and the derivative in time. This mathematical step is the Reynolds transport theorem:

$$\frac{\partial}{\partial t} \int_{V(t)} \rho \mathbf{v} dV = \int_{V(t)} \frac{\partial \rho \mathbf{v}}{\partial t} dV + \int_{S(t)} \rho \mathbf{v} \left(\mathbf{v} \cdot \mathbf{n}' dS \right)$$
(13)

²¹⁸ Using this theorem, the continuity relation can be rewritten:

$$\frac{\partial}{\partial t} \int_{V(t)} \rho \mathbf{v} dV + \int_{S(t)} P \mathbf{n}' dS + \int_{S_R} \mathcal{B} \cdot \mathbf{n}_R dS_R = 0$$
(14)

We can now take the average in time and as in the optical case use the fact that the mean of a time derivative cancels:

$$\mathbf{F} = -\langle \int_{S(t)} P \mathbf{n} dS \rangle = - \int_{S_R} \langle \mathcal{B} \rangle \cdot \mathbf{n}_R dS_R \tag{15}$$

This expression is already comparable to the optical case, Eq. 7, the minus 221 sign comes from the tensor used in acoustics, the flux of momentum, rather 222 than a stress tensor. The radiation pressure is the integral of the flux of mo-223 mentum on a closed surface that delineates a volume containing the particle. 224 To get this we needed to take into account the first specificity of acoustics : 225 the surface of the object is vibrating due to the presence of the acoustic field. 226 Since the radiation pressure is a second order effect, this vibration, while of 227 weak amplitude, is not negligible. The second specificity is that we don't 228 directly get a quadratic expression of the linear fields. To proceed further, 229 we need to perform a perturbative decomposition of the fields up to second 230 order. Assuming no flow at rest, this yields at second order: 231

$$\mathbf{v} = \mathbf{v}^1 + \mathbf{v}^2 \tag{16}$$

$$P = P^0 + P^1 + P^2 \tag{17}$$

$$\rho = -\rho^0 + \rho^1 + \rho^2 \tag{18}$$

$$c_a = c^0 + c^1 + c^2 \tag{19}$$




Figure 2: Scattering by a sphere.

where c_a is the speed of sound in the medium.

Many papers have been written to derive the equation giving the pressure 233 at second order. This stage must be done very carefully and the boundary 234 conditions must be taken into account [31], [32], [33]. For instance for a plane 235 wave, i.e with an infinite lateral extension, or for a fluid which is laterally 236 constrained by rigid wall, we get an expression that involves the non linearity 237 of the state equation of the medium. This is the case studied by Rayleigh. 238 However for practical cases, the radiation pressure is computed for an object 239 embedded in a fluid or the wave is of limited extension. Contrary to the 240 Rayleigh radiation pressure, here a static strain can relax laterally. This is 241 the case presented in this review and the expression for the pressure at second 242 order does not involve the nonlinear coefficient of the medium of propagation. 243 These differences were first studied by Langevin and his analysis published 244 by Biquard [34, 35]. 245

$$P_E^2 = \frac{1}{2} \left(\frac{1}{\rho^0} \left(\frac{P^1}{c^0} \right)^2 - \rho^0 \left(\vec{v}^1 \right)^2 \right)$$
(20)

246

$$\mathcal{B}_{ij} = \rho^0 v_i^1 v_j^1 + \frac{1}{2} \left(\frac{1}{\rho^0} \left(\frac{P^1}{c^0} \right)^2 - \rho^0 v_k^1 v_k^1 \right) \delta_{ij}$$
(21)

As for Maxwell's tensor, there is an isotropic term analog to a pressure and a
tensorial term. However, the isotropic term is not the energy per unit volume
yet. To ease the comparison with the optical case this last expression can be
rewritten:

$$\mathcal{B}_{ij} = \frac{1}{2\rho^0} \left(\frac{P^1}{c^0}\right)^2 \delta_{ij} + \rho^0 v_i^1 v_j^1 - \frac{1}{2} \left(\frac{1}{\rho^0} \left(\frac{P^1}{c^0}\right)^2 + \rho^0 v_k^1 v_k^1\right) \delta_{ij}$$
(22)

The two tensors \mathcal{B} and \mathcal{M} can now be compared. Both involve two fields **E**, **H** 251 and p, **v** respectively. The tensors split into an isotropic part and a tensorial 252 part. The isotropic part is the energy density. The sum of the potential 253 and kinetic energy in acoustics and the sum of the electric and magnetic 254 energy in electromagnetism. These two energies yield two tensorial terms in 255 optics. Acoustics gives an analog result but for a fluid medium the pressure 256 field is a scalar. Note that the coefficient $1/(\rho c_0^2)$ is the bulk compressibility 257 of the medium. However, one difference remains. For the optical case, we 258 get the conservation of the pseudo-momentum while in acoustics we used 259

the conservation of momentum. We will see below that in the case studied here corresponding to the case derived by Langevin, this is also a pseudomomentum. Here, we would like to emphasize one more time and after many papers on this subject that the momentum on an acoustic wave is null.

264 2.3. The acoustic momentum and pseudo-momentum

An acoustic wave is an oscillation of particles and no net flux is expected. Indeed, the momentum is

$$\rho \mathbf{v} = \rho^0 \mathbf{v}^1 + \rho^1 \mathbf{v}^1 + \rho^0 \mathbf{v}^2 \tag{23}$$

²⁶⁷ If we take the time average, we get:

$$\langle \rho \mathbf{v} \rangle = \langle \rho^1 \mathbf{v}^1 \rangle + \rho^0 \langle \mathbf{v}^2 \rangle \tag{24}$$

So the mean mass flux is null if : $\langle \rho^1 \mathbf{v}^1 \rangle = -\rho^0 \langle \mathbf{v}^2 \rangle$. It can be demonstrated 268 that this is the case for a plane wave, [36]. Counter-intuitively, $\langle \mathbf{v}^2 \rangle$ points 269 toward the source of sound. This quantity is a Eulerian quantity and rep-270 resents a physical quantity in a fixed position in space and not a quantity 271 related to a given material particle. The mean velocity in Lagrangian coor-272 dinates, i.e. the mean velocity of material particles, is null as expected. $\langle \mathbf{v}^2 \rangle$ 273 appears when the change of coordinates is performed and is the opposite of 274 the Stokes drift. Using the state equations at first order, $p^1 = (c^0)^2 \rho^1$, we 275 get: 276

$$\rho^{1} \mathbf{v}^{1} = P^{1} \mathbf{v}^{1} / (c^{0})^{2} = \mathbf{S}_{a} / (c^{0})^{2}$$
(25)

So while the total momentum is null, there is a finite pseudo-momentum that can be written as a quadratic expression of linear fields. The pseudomomentum is equal to the acoustic Poynting vector, \mathbf{S}_a , divided by the square of the phase velocity in the medium. This is the relation obtained above with Minkowsky pseudo-momentum in the optical case, Eq. 4. In the next section we will see that the radiation pressure is related to this pseudo-momentum.

283 2.4. Acoustical pseudo-momentum for a plane wave

Let us consider a plane wave propagating along z and hence $\mathbf{v}^1 = (0, 0, v^1)$. The flux of momentum is :

$$\mathcal{B} = \rho^0 (v^1)^2 \delta_{zz} + \frac{1}{2} \left(\frac{1}{\rho^0} \left(\frac{P^1}{c^0} \right)^2 - \rho_0 (v^1)^2 \right) \delta_{ij}$$
(26)

286

$$\langle \mathcal{B} \rangle \cdot \mathbf{z} = \langle E \rangle = \langle \frac{S_a}{c^0} \rangle = \langle c^0 \rho^1 v^1 \rangle$$
 (27)

For this simple case, the radiation pressure is equal to the energy density, the Poynting vector divided by the phase velocity, or the pseudo-momentum times the phase velocity.

290 2.5. Optical pseudo-momentum for a plane wave

We consider a plane wave propagation along \mathbf{z} and hence $\mathbf{E} = (E, 0, 0)$ and $\mathbf{B} = (0, B, 0)$. The Maxwell stress tensor is:

$$\mathcal{M} = \epsilon E^2 \delta_{xx} + \frac{1}{\mu} B^2 \delta_y - \frac{1}{2} \left(\epsilon E^2 + \frac{B^2}{\mu} \right) \delta_{ij} \tag{28}$$

The component of the flux of pseudo-momentum along the direction of propagation, \mathbf{z} is :

$$-\langle \mathcal{M} \rangle \cdot \mathbf{z} = \langle E \rangle = \langle \frac{S_o}{c_n} \rangle = \langle c_n G_M \rangle \tag{29}$$

The optical case is identical to the acoustical case but the mean of the Minkowski pseudo-momentum replaces the mean of the acoustic pseudomomentum, $\rho_1 v_1$.

3. Radiation force on a sphere exerted by an arbitrary shaped in cident beam

As long as the free-field condition is fulfilled, Langevin's expression of the 300 excess of pressure can be used and the force is computed using Brillouin's 301 stress or pseudo-momentum tensor. The latter only involves quadratic ex-302 pressions of the first order field as recalled in the previous section. Hence, 303 one needs to calculate the total linear field (the sum of incident and reflected 304 waves) and then to compute the force from these quantities. In this paper we 305 pay attention interaction of waves with spheres as it is a very important case. 306 First of all, the Lorenz-Mie theory is presented. This theory holds for inci-307 dent plane waves on a sphere. When the incident beam is not plane, different 308 strategies have been developed. Here we focus on the Generalized Lorenz-Mie 300 theory and in particular its extension to acoustics radiation problems which 310 permits to compute the scattered field for an arbitrary beam. Then, consid-311 erations on the beam shape coefficients is proposed. Finally, the regime for 312 which the size of the particle is very small compared to the wavelength is 313 studied both in acoustics and optics. 314

315 3.1. Scattering by a plane wave by a sphere

The first derivation of the scattering of a plane wave by an elastic sphere in 316 an inviscid fluid was developed by Faran [37]. Interested in the propagation of 317 ultrasound through suspensions and emulsions like aerosols or other diphasic 318 solutions an important contribution was made by Epstein and Carhart [38] 319 that dealt with the scattering of a thermo-viscous fluid droplet suspended 320 in a thermo-viscous fluid. Allegra and Hawley generalized this model to the 321 case of a visco-elastic sphere [39]. This model is commonly referred to as 322 the ECAH model in acoustics. Importantly, an elastic medium supports the 323 existence of a one compressional and two transverse shear waves. Mathemat-324 ically the displacement vector can be decomposed into its irrotational and 325 solenoidal parts using Helmholtz decomposition. The latter is the curl of a 326 potential vector **A**. As in electromagnetism, this decomposition allows some 327 freedom and the vector potential **A** satisfies the gauge condition $\nabla \cdot \mathbf{A} = 0$. 328 An interesting analogy lies in that this acoustic potential **A** and both the 329 electric and magnetic fields **E**, **B** are solutions of the vector Helmholtz equa-330 tion. Consequently, the same mathematical steps can be followed to retrieve 331 the solution. Nevertheless, the early developments in acoustics all consid-332 ered the restricted case of a plane longitudinal wave incident on a spherical 333 scatterer [37, 38, 39, 40]. Owed to this strong symmetry condition the vector 334 potential in spherical coordinates (r, θ, ϕ) can be written $\mathbf{A} = (0, 0, A(r, \theta))$ 335 for a plane wave propagating along the z axis. The problem is thereafter 336 considerably simplified inside the sphere and the scalar potential A is solu-337 tion of the scalar Helmholtz equation. It can be written as an infinite sum of 338 spherical modes. The incident plane wave is expanded on the same spherical 339 modes and applying the correct boundary conditions yields the expression of 340 the unknown scattering coefficients necessary to calculate the total external 341 field. One can thereafter evaluate the force exerted on a compressible sphere 342 [41], [42].343

It is noteworthy that a transversely polarized wave immediately breaks 344 the aforementioned azimuthal symmetry. It is the case for the scattering 345 of electromagnetic waves and the modern solution often referred to as the 346 Mie or Lorenz-Mie theory can actually be tracked back to Clebsch and his 347 solution for the scattering of elastic waves by a rigid sphere [43, 44]. There are 348 various examples of the resolution of this type of boundary-value problem in 349 acoustics e.g. [45], [46]. A computationally useful method based on the "T-350 Matrix" [47] was initially introduced in acoustics by Waterman [48, 49]. This 351 matrix does not depend on the nature of the incident wave. It is completely 352

³⁵³ defined by the scatterer and the propagation medium.

354 3.2. Scattering of an arbitrarily shaped beam by a sphere

With the growing interest in contact-less particle manipulation, recent 355 research has extended these approaches to the case of a particle located on the 356 axis of an incident acoustic beam. Examples include axisymmetric beams [50, 357 51 or the more complex wavefronts of a helicoidal bessel beam [52, 53]. To 358 deal with the scattering problem, the Bessel beam was decomposed as a series 359 of plane waves and the use of the previously cited results are straightforward. 360 Using an angular spectrum decomposition of the incident field, this result was 361 generalized to the case of a beam with arbitrary wavefront and the radiation 362 pressure was computed in three dimensions [54]. 363

In optics, an important approach referred to as the Generalized Lorenz-364 Mie Theory (GLMT) was developed [55, 56, 57], [58]. In the GLMT, the 365 problem under consideration is the scattering of an arbitrary incident wave 366 by an arbitrarily located dielectric particle. This model was successful in 367 obtaining the radiation pressure exerted by a beam of arbitrary wavefront 368 regardless on the relative position of the sphere [59], [60]. This efficient 369 approach was recently adapted to acoustics [25]. The incident wave is de-370 composed in the spherical basis centered on the sphere using beam shape 371 coefficients. Note that even for a compressional incident acoustic wave, con-372 sidering an arbitrary wavefront or an arbitrary location of the particle breaks 373 down the azimuthal symmetry $\mathbf{A} = (0, 0, A(r, \theta))$. Hence, as long as a spher-374 ical basis is considered, a set of Debye scalar potentials (ψ, χ) for which 375 $\mathbf{A} = \nabla \wedge (\mathbf{r}\psi) + \nabla \wedge \nabla \wedge (\mathbf{r}\chi)$ is used to solve the vectorial Helmholtz equa-376 tion on A. These potentials are solutions of the scalar Helmholtz equation 377 so that ψ and χ can also be decomposed in the spherical basis. Hence the 378 incident, scattered and elastic waves in the sphere are readily described by 379 four independent potentials decomposed in spherical modes. The boundary 380 value problem yields the unknown scattering coefficients that are shown to 381 be identical to the usual plane wave case [25]. 382

At this stage, the total acoustic field can be computed and Eq.(15) yields the force exerted on the center of the sphere. It essentially depends on the material of the sphere and the fluid's properties through the scattering coefficients on one side, and on the nature of the incident field and the position of the sphere through the beam shape coefficients on the other. An interested reader can refer to [25] for further details on the derivation. Note that a similar result was obtained independently [61]. However, the generalized scattering problem was not addressed and the results restricted to rigid (no
 internal propagation) spheres.

The general treatment in $\operatorname{Ref}[25]$ can be extended to account for various 392 other physical effects. For example, the ECAH theory sets the necessary lin-393 ear equations and introduces the vectorial treatment for elastic, viscous and 394 thermal waves each of which can follow the same decomposition (Helmholtz 395 and Debye) into a set of scalar potentials. These physical effects have shown 396 to have a major influence on the radiation force on small particles compared 397 to the wavelength [62, 63, 64] and can be deduced from the ECAH theory 398 [65, 66]. Other extensions to the case of elastic shells [67, 68] were proposed 399 in the context of the development of sonar detection. These models can find 400 applications in radiation force calculations [69, 70]. 401

402 3.3. Computation of the beam shape coefficients

In the context of GLMT theories, a major task resides in the accurate 403 description of the incident beam and its position relative to the center of the 404 scatterer. The beam shape coefficients fulfill this task and many techniques 405 exist to obtain them. Their review is outside the scope of the present paper 406 and the interested reader can refer to [57, 71]. A numerically efficient im-407 plementation using rotation and addition theorems for spherical harmonics 408 is available in optics [72] and was adapted to acoustics. Examples include 409 helicoidal Bessel beams [25], focused axisymmetric and vortex beams [26]. 410

411 3.4. Acoustic radiation force in the long-wavelength limit

When the spherical scatterer has a very small radius a compared to the 412 incident wavelength, the radiation force can be considerably simplified. On 413 the one hand, only two vibrational modes of the sphere are excited. The 414 first one is an isotropic monopolar expansion mode. It occurs when the 415 compressibility of the scatterer differs from that of the fluid. The second one 416 has a dipolar radiation pattern and arises from the back and forth oscillation 417 of the sphere when a contrast of density between the two phases exists. In 418 the small sphere limit, a Taylor expansion of the spherical Bessel functions 419 involved in the two first scattering coefficients yields two different acoustic 420 contrast factors [27]: 421

$$\alpha_m = \alpha_m^0 / (1 + i \frac{k^3}{4\pi} \alpha_m^0) \tag{30}$$

$$\alpha_d = \alpha_d^0 / (1 - i \frac{k^3}{12\pi} \alpha_d^0)$$
 (31)

422 where $k = \omega/c^0$ is the wave number in the liquid and

$$\alpha_m^0 = \frac{4}{3}\pi a^3 \left(1 - \frac{K^0}{K^p} \right)$$
(32)

$$\alpha_d^0 = 4\pi a^3 \left(\frac{\rho^p - \rho^0}{2\rho^p + \rho^0} \right).$$
 (33)

⁴²³ $K^0 = \rho(c^0)^2$ is the bulk elasticity of the material in the fluid and $K^p = \rho^p (4/3c_t^2 - c_l^2)$ in the solid. The sphere's density, longitudinal and transverse ⁴²⁵ wave speeds are noted ρ^p , c_l and c_t respectively.

On the other hand, the beam shape coefficients are formally scalar projections of the incident field on the spherical basis. In the same long wavelength limit, the beam shape coefficients can be written as linear combinations of the derivatives of the incident field taken at the center of the sphere [27]. The final expression of the force for a small elastic sphere in an inviscid fluid reads:

$$\mathbf{F} = -\frac{1}{2} \left\{ \Re(\alpha_m) \nabla \left(\frac{1}{2\rho^0} \left(\frac{|P^1|}{c^0} \right)^2 \right) - \Re(\alpha_d) \nabla \left(\frac{1}{2} \rho^0 |\mathbf{v}^1|^2 \right) \right. \\ \left. + \left(\frac{k}{c^0} \Im(\alpha_m) - \frac{k^4}{12\pi c^0} \Re(\alpha_m) \Re(\alpha_d) \right) \Re(P^1 \mathbf{v}^{1*}) \right. \\ \left. + \rho^0 \Im(\alpha_d) \Im((\mathbf{v}^1 \cdot \nabla) \mathbf{v}^{1*}) \right\}.$$
(34)

 $_{432}$ \Re and \Im denote the real and imaginary parts of these complex fields and * $_{433}$ stands for a complex conjugations.

The first two terms in Eq.(34) stand for an acoustic gradient force. The 434 real part of the monopolar scattering factor is associated with the gradient 435 of the potential energy density of the field while the real part of the dipolar 436 scattering factor is linked to the gradient of the kinetic energy density. It is 437 a force proportional to the volume of the sphere a^3 . Gorkov was probably 438 the first to show that the radiation pressure of a standing wave field could be 439 written as a gradient force [73]. His result is here recovered. The remaining 440 term is called the scattering force and is associated to the imaginary parts of 441 the scattering coefficients and a coupling between the monopolar and dipolar 442 modes. Gorkov had also shown that the force exerted by a plane progressive 443 wave was much weaker since there are no gradients in the fields' energy 444 density. Indeed the imaginary part of the monopolar and dipolar contrast 445

factors are multiplied by an additional factor $(ka)^3 \ll 1$. Eq. 34 generalizes Gorkov's result to account for the scattering force of an arbitrary wavefield. A similar result was obtained elsewhere [54].

It is known that a very slight viscosity in the fluid suffices to drastically increase the magnitude of the scattering term of the force [62]. It is worth noting that the two acoustic contrast factors in Eq.(31) can me modified to account for the thermo-vicosity of the fluid or the visco-elasticity of the sphere [64, 66, 65, 70].

454 3.5. Long-wavelength simplified expression in optics and acoustics

The optical radiation force on a small dielectric sphere has a very similar expression [74],[75],[76]:

 There are also two modes but this time both are dipolar and related to the contrast in dielectric permittivity and magnetic permeability. Note that there is a single dipolar mode in acoustics because we assumed an elastic sphere in a fluid medium. The radiation pressure on a spherical inclusion in a solid would involve transverse incident waves.

- The real part of the scattering coefficient, the clausius-mossotti relation is identical to the acoustic dipolar scattering coefficients if specific mass is replaced by either the dielectric permittivity or the magnetic permeability.
- The scattering coefficients have a small imaginary part proportional to the square of the real part. This correction was recently introduced in optics [76].
- The force can be split in a gradient and a scattering force. In optics this
 was inferred independently of the correct expression of the scattering
 coefficients [75] and compared to the full theory provided by the GLMT.
- The gradient force is related to the energy density of the incident fields at the sphere center and the real part of the scattering coefficient.
- The scattering force is weaker and related to the imaginary part of the scattering coefficient. In both cases there is a term proportional to the mean of the Poynting vector.

There are of course differences due to polarizations. In acoustics, the wave is scalar and longitudinally polarized in the liquid and have longitudinal and transverse components in the solid sphere. In optics the wave is transverse in both media.

481 4. Acoustical tweezers

Applying controlled forces without contact is appealing. It has many 482 practical applications, both in optics and in acoustics. Optical tweezers can 483 manipulate sub-micrometric objects with a nanometer resolution and forces 484 in the pico-newton range. They have found a huge amount of applications 485 from fundamental physics to material science and biophysics [77, 78, 79, 80, 486 81]. Acoustic traps can considerably increase the size of the manipulated 487 particles and the force that can be exerted. From the first acoustic levitation 488 traps [13, 14] to the recent regain in interest in the context of acoustofluidics, 489 acoustic traps have addressed a significant panel of new applications [15, 490 82, 83]. In this section we propose to review the recent demonstration of 491 single-beam acoustical tweezers for which, in comparison to other traps, the 492 development has been rather slow. 493

Unlike optical trapping of high-index particles, solid elastic materials are 494 not transparent to ultrasound. The mechanical index mismatch is such that 495 the preeminent mechanism at the fluid/solid boundary is backscattering in-496 stead of refraction. Moreover, considering a large sphere in the geometrical 497 acoustics regime $(a \ll \lambda)$, not only the scattering force pushes the parti-498 cle but, the refracted rays that in optics usually contribute to the restoring 499 gradient component build up to an additional expelling force in acoustics. 500 Restricting ourselves to much smaller spheres and avoiding as a first step the 501 more complex Mie scattering regime $(a \leq \lambda)$, a quick analysis of Gorkovs 502 theory (see Eq.(15)) shows that a particle that is denser and stiffer than the 503 surrounding medium experiences a gradient force that points away from in-504 tensity maxima. Hence, whatever the size of the solid particle, acoustic beam 505 traps generally exhibit an unstable behavior and the history of acoustic par-506 ticle manipulation has almost always involved standing waves schemes. 507

Holding on to the single-beam concept, it was recently recognized that specific fields called acoustic vortices could act as stable lateral [84] and threedimensional traps [26]. The lateral trapping of vortex type beams was confirmed experimentally in a planar configuration creating 2D annular Bessel function shaped traps [85]. Using a three-dimensional theory for acoustic

forces [25] is was possible to compute the axial trapping force of tightly fo-513 cused vortex beams [26]. It was concluded that a focused vortex beam of 514 topological charge m = 1 could generate a negative axial gradient force to 515 stably trap elastic particles in three dimensions. In fact, using sufficiently 516 small spheres ($a < 0.15\lambda$), the scattering force is greatly diminished on the 517 axis of a vortex beam meanwhile the gradient component points this time 518 towards the focus. Note that other types of beams were proposed in [26] to 519 enhance the axial trapping efficiency similar to what is referred to as "bottle 520 beams" in optics [86, 87]. 521

The research field of structured wavefronts is again intimately related 522 between optics and acoustics. Though the seminal paper published by Nye 523 and Berry in 1974 first introduced the phenomenon of phase singularities 524 within ultrasonic wave trains [88], the optics community rapidly pushed the 525 concept forward towards a whole deal of fundamental studies and applica-526 tions [89, 90, 91]. Remarkably, a route to directly create a beam carrying 527 a screw phase dislocation was first theoretically proposed in acoustics [92] 528 at the time it was recognized that TEM_{01}^* laser modes could be generated 529 [91, 93]. Experimentally demonstrated by Hefner and Marston [94]. Studies 530 of their linear and non-linear behavior include the establishment of a law 531 of conservation of their topological charge and pseudo-angular momentum 532 [94, 95, 96], vortex parametric interaction [97], azimuthal shock waves [98] 533 and their super-oscillation properties applied to sub-wavelength imaging [99]. 534 An example of a synthesized vortex beam is given in Fig.3. The ultrasonic 535 field is generated by a 128 element piezoelectric array in a water tank using 536 the inverse filter technique [95]. As for its optical counterpart, the energy is 537 focused to a ring in the focal plane (panel a)). Note that a hydrophone deliv-538 ers a direct measurement of the spiraling phase structure while in optics the 539 vortex beam generally has to interfere with a plane wave. It is noteworthy 540 that a high numerical aperture acoustic lens was designed to focus the beam 541 to a ring of diameter comparable to λ . The region of undefined phase is a 542 line in three dimensions. Consequently, the entire propagation axis defines a 543 silent zone (see Fig.3c)). 544

The control achieved in creating tightly focused vortex beams led us to experimentally demonstrate the existence of a negative gradient force and in essence observe the first single-beam gradient trap for elastic particles with an ultrasonic beam [27]. In the first configuration a vortex was fired horizontally in the water tank while a polystyrene particle was approached near the focal region by an auxiliary tee. Figure 4 shows a photograph of a 400μ m size




Figure 3: Example of a synthesized vortex beam of topological charge m = 1. a) and b), normalized intensity and phase (rad.) in the focal plane respectively. c), normalized intensity along the propagation axis. Adapted from [65].




Figure 4: Photograph of a trapped polystyrene particle in a horizontal acoustical tweezers setup. A zoomed range of the particle's release is displaced with an overlap of images. The particle's trajectory shows the effect of gravity and acoustic streaming.

⁵⁵¹ polystyrene sphere trapped in the focus of the helicoidal field. The particle ⁵⁵² levitates approximately 30mm away from the outer face of the lens as long ⁵⁵³ as the vortex is emitted. When the source is turned off, an overlapped image ⁵⁵⁴ stack of the release of the sphere is shown. It can be seen from the trajectory ⁵⁵⁵ that at this scale that gravity plays a major role and remark the significant ⁵⁵⁶ effect of acoustic streaming pushing the particle away from the focus.

It was decided to demonstrate that the negative gradient force was so 557 large that it dominated the axial stability in a vertical configuration. The 558 experimental setup described in [27] was used to lift and trap buoyant par-559 ticles against their weight and the pushing force exerted by the streaming 560 flow's drag. Figure 5 is a photograph of a $340\mu m$ polystyrene bead trapped 561 and levitated beneath the focus of the vortex beam. The bead was initially 562 lying on an acoustically transparent polyethylene film. By precisely aim-563 ing the beam, the tweezers can accurately select the particle to be trapped. 564 Other particles can be slightly affected but will not collect in the the focal 565 volume. 566




Figure 5: Photograph of a 340μ m diameter polystyrene sphere trapped in vertical acoustical tweezers. The trapped particle was selected among others that were lying on a thin polyethylene film. Adapted from [27]

567 5. Conclusion

The radiation pressures exerted by sound or light have many similar fea-568 This was shown with the expression of the stress tensor and the tures. 569 relation with pseudo-momentum. Not only these second order effects are 570 similar but also when the linear problem of a spherical scatterer interacting 571 with an incident beam is considered. The Generalized Lorenz-Mie theory 572 has therefore recently found an adaptation to acoustic scattering and force 573 calculations. Regarding the force in the long wavelength limit, it was shown 574 that a beam exerted both a gradient and scattering force in acoustics in a 575 similar fashion to the force exerted by an optical beam on a small dielec-576 tric dipole. The possibility to design manipulation traps for small particles 577 is another appealing and common characteristic. Among all kinds of traps, 578 optical tweezers stand out by their simplicity, accurate localized actuation 579 and great dexterity. Quoting Ashkin [20]: "The single-beam gradient force 580 trap is conceptually and practically one of the simplest radiation pressure 581 traps". A feature which most certainly explains their wide application in 582 various scientific fields. The attention of the acoustic community has essen-583 tially been turned towards standing wave traps where Gorkov's theory has 584 found a sound application. They have addressed a large panel of new appli-585 cations in the context of acoustical levitation or acoustofluidics [15, 82, 83]. 586 A recent review offers an extensive survey of various developed devices [100]. 587 The development of single-beam acoustical tweezers had been impaired by 588 two main difficulties: the lack of a complete theoretical model able to predict 589 the force exerted by acoustic beams and the capacity to synthesize acoustic 590 beams with complex wavefronts as focused acoustical vortices. The complex 591 wavefield synthesis method with a large array of piezo-electric transducers 592 was adapted from previous studies on acoustical vortices [95, 96]. 593

The thermal damage, or "opticution", limit optical tweezers to applications requiring very weak forces and to manipulate very small particles from atoms to molecules. Ultrasound are proven to innocuous for living cells and propagate without significant attenuation in many materials. This feature combined with the much larger forces applied at equivalent energy flux should give to single-beam acoustical tweezers an extended range of manipulation capacities for new applications in material science, fluidics and biophysics.

[1] J. C. Maxwell, Art. 314. medium in which small spheres are uniformly disseminated, chapter ix. conduction through heterogeneous media, A treatise on electricity and magnetism 1.

- [2] P. Lebedev, Experimental examination of light pressure, Annalen der
 physik 6 (1901) 433.
- [3] E. F. Nichols, G. F. Hull, The pressure due to radiation, in: Daedalus,
 Vol. 38, 1903, pp. 559–599.
- ⁶⁰⁸ [4] L. Rayleigh, Phil. Mag. 3 (1902) 338.
- ⁶⁰⁹ [5] L. Rayleigh, Phil. Mag. 10 (1905) 364.
- ⁶¹⁰ [6] V. Dvorak, On acoustic repulsion, Am. J. Sci. 16 (1878) 22–29.
- [7] W. Altberg, ber die druckkrfte der schallwellen und die absolute messung der schallintensitt, Annalen der Physik 316 (6) (1903) 405–420.
- 613 [8] C. Eckart, Vortices and streams caused by sound waves 73 (1) (1948) 614 68–76.
- [9] R. Peirls, Momentum and pseudomomentum of light and sound, Proc.
 Intl. School Phys. "Enrico Fermi", Elsevier Science Ltd, 1985, pp. 237– 255.
- ⁶¹⁸ [10] M. McIntyre, On the "wave momentum" myth, J. Fluid. Mech. 106 (1981) 331–347.
- [11] L. Brillouin, Tensors in mechanics and elasticity, Academic Press, New
 York, 1964.
- [12] A. Eller, Force on a bubble in a standing acoustic wave, J. Acoust. Soc.
 Am. 43 (1) (1968) 170–171.
- [13] E. Trinh, Compact acoustic levitation device for studies in fluid dynamics and material science in the laboratory and microgravity, Rev.
 Sci. Instrum. 56 (11) (1985) 2059–2065.
- [14] R. E. Apfel, Acoustic levitation for studying liquids and biological materials, J. Acoust. Soc. Am. 70 (2) (1981) 636–639.
- [15] T. Laurell, F. Petersson, A. Nilsson, Chip integrated strategies for
 acoustic separation and manipulation of cells and particles, Chem. Soc.
 Rev. 36 (3) (2007) 492–506.

- [16] P. B. Muller, M. Rossi, Á. Marín, R. Barnkob, P. Augustsson, T. Laurell, C. J. Kaehler, H. Bruus, Ultrasound-induced acoustophoretic motion of microparticles in three dimensions, Phys. Rev. E 88 (2) (2013) 023006.
- [17] F. Guo, P. Li, J. B. French, Z. Mao, H. Zhao, S. Li, N. Nama, J. R.
 Fick, S. J. Benkovic, T. J. Huang, Controlling cell-cell interactions
 using surface acoustic waves, Proc. Natl. Acad. Sci. USA 112 (1) (2015)
 43–48.
- [18] C. R. Courtney, C. E. Demore, H. Wu, A. Grinenko, P. D. Wilcox,
 S. Cochran, B. W. Drinkwater, Independent trapping and manipulation
 of microparticles using dexterous acoustic tweezers, App. Phys. Lett.
 104 (15) (2014) 154103.
- [19] A. Ashkin, Acceleration and trapping of particles by radiation pressure,
 Phys. Rev. Lett. 24 (4) (1970) 156–159.
- [20] A. Ashkin, J. Dziedzic, J. Bjorkholm, S. Chu, Observation of a singlebeam gradient force optical trap for dielectric particles, Optics letters
 11 (5) (1986) 288–290.
- [21] J. Wu, G. Du, Acoustic radiation force on a small compressible sphere
 in a focused beam, J. Acoust. Soc. Am. 87 (3) (1990) 997–1003.
- ⁶⁵¹ [22] J. Wu, Acoustical tweezers, J. Acoust. Soc. Am. 89 (5) (1991) 2140– ⁶⁵² 2143.
- ⁶⁵³ [23] A. Ashkin, How it all began, Nature Photonics 5 (2011) 316–317.
- ⁶⁵⁴ [24] J. Lee, K. Shung, Radiation forces exerted on arbitrarily located sphere ⁶⁵⁵ by acoustic tweezer, J. Acoust. Soc. Am. 120 (2) (2006) 1084–1094.
- [25] D. Baresch, J.-L. Thomas, R. Marchiano, Three-dimensional acoustic
 radiation force on an arbitrarily located elastic sphere, J. Acoust. Soc.
 Am. 133 (1) (2013) 25–36.
- [26] D. Baresch, J.-L. Thomas, R. Marchiano, Spherical vortex beams of
 high radial degree for enhanced single-beam tweezers, J. Appl. Phys.
 113 (18) (2013) 184901.

- [27] D. Baresch, J.-L. Thomas, R. Marchiano, Observation of a single-beam
 gradient force acoustical trap for elastic particles: acoustical tweezers,
 Phys. review lett. 116 (2) (2016) 024301.
- [28] A. Marzo, S. A. Seah, B. W. Drinkwater, D. R. Sahoo, B. Long, S. Sub ramanian, Holographic acoustic elements for manipulation of levitated
 objects, Nat. Commun. 6 (2015) 8661.
- [29] J. Jackson, Classical Electrodynamics, John Wiley and Sons Inc., New
 York, 1962, Ch. 6.
- [30] K. Beissner, The acoustic radiation force in lossless fluids in eulerian
 and lagrangian coordinates, J. Acoust. Soc. Am. 103 (5) (1998) 2321–
 2332.
- [31] E. J. Post, Radiation pressure and dispersion, J. Acoust. Soc. Am.
 25 (1) (1953) 55–60.
- [32] K. Beissner, Two concepts of acoustic radiation pressure, J. Acoust.
 Soc. Am. 79 (5) (1986) 1610–1612.
- [33] R. Beyer, Radiation pressure-the history of a mislabeled tensor, J. Acous. Soc. Am. 63 (4) (1978) 1025–1030.
- ⁶⁷⁹ [34] P. Biquard, Rev. Acoust. 1 (1932) 93–109.
- ⁶⁸⁰ [35] P. Biquard, Rev. Acoust. 2 (1933) 315–335.
- [36] B. Chu, R. E. Apfel, Acoustic radiation pressure produced by a beam of sound, J. Acous. Soc. Am. 72 (6) (1982) 1673–1687.
- [37] J. Faran, Sound scattering by solid cylinders and spheres, J. Acoust.
 Soc. Am. 23 (1951) 405–418.
- [38] P. Epstein, R. Carhart, The absorption of sound in suspensions and
 emulsions. i. water fog in air., J. Acoust. Soc. Am. 25 (3) (1953) 553–
 565.
- [39] J. Allegra, S. Hawley, Attenuation of sound in suspensions and emul sions: Theory and experiments, J. Acoust. Soc. Am. 51 (5) (1971)
 1545–1564.

- ⁶⁹¹ [40] P. M. Morse, Vibration and sound, Vol. 2, McGraw-Hill New York, ⁶⁹² 1948.
- [41] K. Yosioka, Y. Kawasima, Acoustic radiation pressure on a compress ible sphere, Acustica 5 (3) (1955) 167–173.
- ⁶⁹⁵ [42] T. Hasegawa, K. Yosioka, Acoustic radiation force on a solid elastic ⁶⁹⁶ sphere, J. Acoust. Soc. Am. 46 (5) (1969) 1139–1143.
- ⁶⁹⁷ [43] N. A. Logan, Early history of the mie solution, J. Opt. Soc. Am. 52 (3) ⁶⁹⁸ (1962) 342–343.
- ⁶⁹⁹ [44] N. A. Logan, Survey of some early studies of the scattering of plane ⁷⁰⁰ waves by a sphere, Proc. IEEE 53 (8) (1965) 773–785.
- [45] N. Einspruch, E. Witterholt, R. Truell, Scattering of a plane transverse
 wave by a spherical obstacle in an elastic medium, J. Appl. Phys. 31 (5)
 (1960) 806-818.
- [46] G. C. Gaunard, H. Überall, Theory of resonant scattering from spherical cavities in elastic and viscoelastic media, J. Acoust. Soc. Am. 63 (6) (1978) 1699–1712.
- [47] T. Nieminen, H. Rubinsztein-Dunlop, N. Heckenberg, Calculation of the t-matrix: general considerations and application of the pointmatching method, J. Quant. Spect. and Rad. Transf. 7980 (2003) 1019 - 1029.
- [48] P. Waterman, New formulation of acoustic scattering, J. Acoust. Soc.
 Am. 45 (6) (1969) 1417–1429.
- [49] P. Waterman, Matrix theory of elastic wave scattering, J. Acoust. Soc.
 Am. 60 (3) (1976) 567–580.
- [50] X. Chen, R. Apfel, Radiation force on a spherical object in the field
 of a focused cylindrical transducer, J. Acoust. Soc. Am. 101 (5) (1996)
 2443–2447.
- [51] P. L. Marston, Axial radiation force of a bessel beam on a sphere and direction reversal of the force, J. Acoust. Soc. Am. 120 (6) (2006) 3518.

- [52] P. L. Marston, Scattering of a bessel beam by a sphere: Ii helicoidal
 case and spherical shell example, J. Acoust. Soc. Am. 124 (5) (2008)
 2905–2910.
- [53] P. L. Marston, Radiation force of a helicoidal bessel beam on a sphere,
 J. Acoust. Soc. Am. 120 (2009) 3539–3547.
- [54] O. A. Sapozhnikov, M. R. Bailey, Radiation force of an arbitrary acoustic beam on an elastic sphere in a fluid, J. Acoust. Soc. Am. 133 (2) (2013) 661–676.
- [55] B. Maheu, G. Gouesbet, G. Gréhan, A concise presentation of the generalized lorenz-mie theory for arbitrary location of the scatterer in an arbitrary incident profile, J. Opt. 19 (2) (1987) 59–67.
- [56] G. Gouesbet, B. Maheu, G. Gréhan, Light scattering from a sphere arbitrarily located in a gaussian beam, using a bromwich formulation, JOSA A 5 (9) (1988) 1427–1443.
- [57] G. Gouesbet, J. Lock, G. Gréhan, Generalized lorenzmie theories and
 description of electromagnetic arbitrary shaped beams : Localized approximations and localized beam models, a review, J. Quant. Spect. and
 Rad. Transf. 112 (2010) 1–27.
- [58] J. P. Barton, D. R. Alexander, S. A. Schaub, Internal and near-surface
 electromagnetic fields for a spherical particle irradiated by a focused
 laser beam, J. Appl. Phys. 64 (4) (1988) 1632–1639.
- [59] K. Ren, G. Gréhan, G. Gouesbet, Radiation pressure forces exerted on
 a particle arbitrarily located in a gaussian beam by using the generalized lorenz-mie theory, and associated resonance effects, Optics Comm.
 108 (1994) 343–354.
- [60] J. P. Barton, D. R. Alexander, S. A. Schaub, Theoretical determination
 of net radiation force and torque for a spherical particle illuminated by
 a focused laser beam, J. Appl. Phys. 66 (10) 4594–4602.
- [61] G. T. Silva, An expression for the radiation force exerted by an acoustic
 beam with arbitrary wavefront, J. Acoust. Soc. Am. 130 (6) (2011)
 3541–3544.

- [62] S. Danilov, M. Mironov, Mean force on a small sphere in a sound field
 in a viscous fluid, J. Acoust. Soc. Am. 107 (1) (2000) 143–153.
- [63] A. A. Doinikov, Acoustic radiation pressure on a rigid sphere in a viscous fluid, Proc Royal Soc. London. A. 447 (1994) 447–466.
- ⁷⁵⁵ [64] M. Settnes, H. Bruus, Physical Review E 85 (1) (2012) 016327.
- [65] D. Baresch, Pince acoustique: piégeage et manipulation d'un objet
 par pression de radiation d'une onde progressive, Ph.D. thesis, Paris 6
 (2014).
- [66] J. T. Karlsen, H. Bruus, Forces acting on a small particle in an acoustical field in a thermoviscous fluid, Phys. Rev. E 92 (2015) 043010.
- [67] V. Ayres, G. C. Gaunaurd, Acoustic Resonance Scattering by Vis coelastic Objects, J. Acoust. Soc. Am. 81 (2).
- ⁷⁶³ [68] M. C. Junger, Sound scattering by thin elastic shells, The Journal of ⁷⁶⁴ the Acoustical Society of America 24 (4) (1952) 366–373.
- [69] T. Hasegawa, Y. Hino, A. Annou, H. Noda, M. Kato, N. Inoue, Acoustic radiation pressure acting on spherical and cylindrical shells, The Journal of the Acoustical Society of America 93 (1) (1993) 154–161.
- [70] J. P. Leão Neto, J. H. Lopes, G. T. Silva, Core-shell particles that are
 unresponsive to acoustic radiation force, Phys. Rev. Applied 6 (2016)
 024025.
- [71] T. Nieminen, H. Rubinsztein-Dunlop, N. Heckenberg, Multipole expansion of strongly focussed laser beams, J. Quant. Spect. and Rad.
 Transf. 79 (2003) 1005–1017.
- T. Nieminen, V. Loke, A. Stilgoe, G. Knner, A. Branczyk, N. Heckenberg, Optical tweezers computational toolbox, J. Opt. A : Pure Appl.
 Opt. 9 (2007) 196–203.
- [73] L. Gor'kov, On the forces acting on a small particle in an acoustic field
 in an ideal fluid, Sov. Phys. Dokl 6 (1962) 773–775.
- [74] T. A. Nieminen, G. Knöner, N. Heckenberg, H. Rubinsztein-Dunlop,
 Physics of optical tweezers, Methods Cell Biol. 82 (2007) 207–236.

- [75] Y. Harada, T. Asakura, Radiation forces on a dielectric sphere in the
 rayleigh scattering regime, Optics Comm. 124 (1996) 529–541.
- [76] P. Chaumet, M. Nieto-Vesperinas, Coupled dipole method determination of the electromagnetic force on a particle over a flat dielectric
 substrate, Phys. Rev. B 61 (20) (2000) 14119–14127.
- [77] A. Ashkin, J. Dziedzic, T. Yamane, Optical trapping and manipulation
 of single cells using infrared laser beams, Nature 330 (6150) (1987) 769–
 771.
- [78] D. G. Grier, A revolution in optical manipulation, Nature 424 (6950)
 (2003) 810–816.
- [79] K. Dholakia, T. Cižmár, Shaping the future of manipulation, Nature
 Photonics 5 (6) (2011) 335–342.
- [80] A. Aspect, E. Arimondo, R. Kaiser, N. Vansteenkiste, C. Cohen-Tannoudji, Laser cooling below the one-photon recoil energy by velocity-selective coherent population trapping, Phys. Rev. Lett. 61 (7) (1988) 826.
- [81] M. Padgett, S. Barnett, R. Loudon, The angular momentum of light
 inside a dielectric, J. Mod. Opt 50 (10) (2003) 1555–1562.
- [82] J. Friend, L. Y. Yeo, Microscale acoustofluidics: Microfluidics driven
 via acoustics and ultrasonics, Reviews of Modern Physics 83 (2) (2011)
 647.
- [83] M. Evander, J. Nilsson, Acoustofluidics 20: applications in acoustic
 trapping, Lab on a chip 12 (22) (2012) 4667–4676.
- [84] S. Kang, C. Yeh, Potential-well model in acoustic tweezers, IEEE Ultrasonics 57 (6) (2010) 1451–1459.
- [85] C. R. Courtney, B. W. Drinkwater, C. E. Demore, S. Cochran, A. Grinenko, P. Wilcox, Dexterous manipulation of microparticles using bessel-function acoustic pressure fields, App. Phys. Lett. 102 (12) (2013) 123508.

- [86] J. Arlt, M. J. Padgett, Generation of a beam with a dark focus surrounded by regions of higher intensity: the optical bottle beam, Opt.
 Lett. 25 (4) (2000) 191–193.
- ⁸¹³ [87] C.-H. Chen, P.-T. Tai, W.-F. Hsieh, Bottle beam from a bare laser for ⁸¹⁴ single-beam trapping, Appl. Opt. 43 (32) (2004) 6001–6006.
- ⁸¹⁵ [88] J. Nye, M. Berry, Dislocations in wave trains, Proc. R. Soc. London ⁸¹⁶ 336 (1974) 165–190.
- [89] M. Soskin, M. Vasnetsov, Singular optics, Progress in optics 42 (2001)
 219–276.
- [90] G. Gibson, J. Courtial, M. J. Padgett, M. Vasnetsov, V. Pasko, S. M.
 Barnett, S. Franke-Arnold, Free-space information transfer using light
 beams carrying orbital angular momentum, Optics Express 12 (22)
 (2004) 5448-5456.
- [91] M. R. Dennis, K. O'Holleran, M. J. Padgett, Singular optics: optical
 vortices and polarization singularities, Progress in Optics 53 (2009)
 293–363.
- [92] C. Cain, S. Umemura, Concentric-ring and sector-vortex phased-array
 applicators for ultrasound hyperthermia, IEEE Transactions on Mi crowave Theory and Techniques 34 (5) (1986) 542–551.
- [93] C. Tamm, C. O. Weiss, Bistability and optical switching of spatial patterns in a laser, J. Opt. Soc. Am. B 7 (6) (1990) 1034–1038.
- [94] B. T. Hefner, P. L. Marston, An acoustical helicoidal wave transducer
 with applications for the alignment of ultrasonic and underwater systems, J. Acous. Soc. Am. 106 (6) (1999) 3313–3316.
- [95] J.-L. Thomas, R. Marchiano, Pseudo angular momentum and topological charge conservation for nonlinear acoustical vortices, Phys. Rev.
 Lett. 91 (24) (2003) 1–4.
- [96] R. Marchiano, J.-L. Thomas, Synthesis and analysis of linear and nonlinear acoustical vortices, Phys. Rev. E. 71 (2005) 1–11.
- [97] R. Marchiano, J.-L. Thomas, Doing arithmetic with nonlinear acoustic
 vortices, Phys. Rev. Lett. 101 (2008) 1–4.

- [98] T. Brunet, J.-L. Thomas, R. Marchiano, F. Coulouvrat, Experimental
 observation of azimuthal shock waves on nonlinear acoustical vortices,
 New J. Phys. 11 (2009) 013002.
- [99] T. Brunet, J.-L. Thomas, R. Marchiano, Transverse shift of helical
 beams and subdiffraction imaging, Phys. Rev. Lett. 105 (3) (2010)
 034301.
- ⁸⁴⁷ [100] B. W. Drinkwater, Dynamic-field devices for the ultrasonic manipulation of microparticles, Lab on a Chip 16 (2016) 2360–2375.