



HAL
open science

Emotion facial recognition by the means of automatic video analysis

Antitza Dantcheva, Piotr Bilinski, Jean Claude Broutart, Philippe Robert,
Francois Bremond

► **To cite this version:**

Antitza Dantcheva, Piotr Bilinski, Jean Claude Broutart, Philippe Robert, Francois Bremond. Emotion facial recognition by the means of automatic video analysis. Gerontechnology, 2016. hal-01446930

HAL Id: hal-01446930

<https://hal.science/hal-01446930>

Submitted on 9 Mar 2017

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Emotion facial recognition by the means of automatic video analysis.

A. DANTCHEVA, P. BILINSKI, J. C. BROUTART, P. ROBERT, F. BREMOND.

Gerontechnology 2016;15(suppl); doi:10.4017/gt.2016.15.s.939.00

Purpose The elderly population has been growing dramatically and future predictions and estimations showcase that by 2050 the number of people over 65 years old will increase by 70%, the number of people over 80 years old will increase by 170%, outnumbering younger generations from 0-14 years¹. Other studies indicate that around half of the current population of over 75 year olds suffer from physical and / or mental impairments and as a result are in need of high level of care². The loss of autonomy can be delayed by maintaining an active life style, which also would lead to reduced healthcare financial costs³. With the expected increase of the world elderly population, and on the other hand limited available human resources for care a question arises as "How can we improve health care in an efficient and cost effective manner?".

Method Motivated by the above, we propose an approach for detecting facial expressions in Alzheimer's disease (AD) patients that can be a pertinent unit in an automated assisted living system for elderly subjects. Specifically, we have collected video-data of AD patients in musical therapy at the AD center Fondation G.S.F J. L. Noisiez in Biot, France from multiple therapy-sessions for validating our method. We note that in such sessions even AD patients suffering from apathy exhibit a number of emotions and expressions. We propose a spatio-temporal algorithm for facial expression recognition based on dense trajectories, Fisher Vectors and support vector machine classification⁴. We compared the proposed algorithm to a facial-landmark-based algorithm concerning signal displacement of tracked points within the face⁵.

Results & Discussion Our algorithm differentiates between four different facial expressions: (i) neutral, (ii) smile, (iii) talking, and (iv) singing with an accuracy of 56%, outperforming the facial-landmark-based algorithm. Challenging for both algorithms has been the unconstrained setting involving different poses, changes in illumination and camera movement. One expected benefit for AD patients is that positive expressions and their cause could be determined and replicated in order to increase life standard for such patients, which also brings to the fore a delay in the development of AD.

References

1. <http://www.un.org/esa/population/publications/worldageing19502050/pdf/80chapteriii.pdf>
2. http://www.cdc.gov/features/agingandhealth/state_of_aging_and_health_in_america_2013.pdf
3. Willett W. C., Koplan J. P., Nugent R., Dusenbury C., Puska P., and Gaziano T. A.. Prevention of Chronic Disease by Means of Diet and Lifestyle Changes. In: Jamison D. T., Breman J. G., Measham A. R., et al., editors. Disease Control Priorities in Developing Countries. 2nd edition. Washington (DC): The International Bank for Reconstruction and Development / The World Bank; 2006. Chapter 44.
4. Bilinski P, and Bremond F.. "Video covariance matrix logarithm for human action recognition in videos." In IJCAI 2015-24th International Joint Conference on Artificial Intelligence (IJCAI). 2015.
5. Asthana A., Zafeiriou S., Cheng S., and Pantic M.. "Incremental face alignment in the wild." In Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition, pp. 1859-1866. 2014.

Keywords: expression recognition, automated healthcare for older adults, computer vision

Address: INRIA, Sophia Antipolis, France;

E: antitza.dantcheva@inria.fr




Figure 1. Expression recognition in AD patients based on dense trajectories and Fisher vectors⁴. Dense trajectories visualization.