

Search Pattern Design Optimization for 2D Electronic Scanning Fixed Panel Radar

Yann Briheche, Frédéric Barbaresco, Fouad Bennis, Damien Chablat

▶ To cite this version:

Yann Briheche, Frédéric Barbaresco, Fouad Bennis, Damien Chablat. Search Pattern Design Optimization for 2D Electronic Scanning Fixed Panel Radar. Ph Day Radar THALES/ONERA/SONDRA, Oct 2015, Rungis, France. 2015, Ph Day Radar THALES/ONERA/SONDRA. hal-01472073

HAL Id: hal-01472073 https://hal.science/hal-01472073v1

Submitted on 20 Feb 2017

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Search Pattern Design Optimization for 2D Electronic Scanning Fixed Panel Radar

Yanis Briheche, Frédéric Barbaresco, Fouad Bennis, Damien Chablat



THALES

1. Motivation & Methodology

Radar explores surrounding space by using a *search pattern*, ie a set of dwells



3. Integer Program Formulation

Formulation of dwell cover as a binary vector



For a given dwell *d*, at a given case (*i*, *j*), dwell cover is defined by :

 $\mathbf{C}_{d}(i,j) = \begin{cases} 1, \text{ if } E_{d}(i,j) \ge E_{req}(i,j) \\ 0, \text{ else} \end{cases}$

and represents cases where detection complies with requirements.

It must ensure detection at given range, using as low time budget as possible, and take into account anisotropic properties of the radar (deflection losses)



Currently, search patterns are hand-designed. Our objectives are to provide:
a framework for algorithmic generation of optimized search patterns
adaptive scanning for inhomogeneous environments (clutter, ridges, ...)

Methodology

- Definition of the radar model on a discrete grid.
- Formulation of the discrete model as an Integer Program
- Optimization by Linear Relaxation and Branch&Bound



Formulation of range constraints as a matrix inequality

We search a subset of dwells (among *D* feasible dwells) covering all cases. Having each case covered by at least one dwell is equivalent to the inequation



where $x_d = 1$ if the dwell *d* is chosen, and 0 otherwise. $\mathbf{x} = (x_0, \dots, x_D)$ is a binary encoding of a search pattern : $S = \{d_i, \text{ s.t. } x_i = 1\}$

Formulation of search pattern duration as a linear function We wish to minimize the duration of the search pattern *S*, defined as :

$$\sum_{d\in S} T_d = \sum_i x_i \cdot T_i = \mathbf{x} \cdot \mathbf{T}$$

with $\mathbf{T} = (T_0, \cdots, T_D)$

4. Optimization

2. Radar Model

Discrete Radar space

Approximation of the region of interest by a $M \times N$ grid



Dwell (rectangular model)

Combination of beamshape (where it emits) and waveform (what it emits)



The set of potential dwells is the combination (Cartesian product) : • All possible beamshapes, ie all possible subrectangles in the grid ($\approx \frac{M^2N^2}{4}$) • A set of *W* given waveforms : $\mathcal{W} = \{wf_1, wf_2, \dots, wf_W\}$. Each wf_i associated to a duration T_i , and an energetic efficiency η_i Minimization of search pattern duration under detection constraints

 $\begin{array}{ll} \min \quad \mathbf{x} \cdot \mathbf{T} \\ \text{s.t.} \quad \mathbf{A} \cdot \mathbf{x} \geq \mathbf{1} \\ \mathbf{x} \in \{\mathbf{0}, \mathbf{1}\}^D \end{array}$

Solver (GPLK, MATLAB intlinprog) outline for Integer Programming







- linear optimal solution
- ---- branch&bound (integer solver)
- \Rightarrow integer optimal solution



In practice, the set of feasible dwells is smaller :
smallest beamshape : focalised beam × deflection
largest beamshape : limited by radar post-processing speed

"Energy" requirements : $E_{req} = Range^4 \cdot Loss_{defl}$





Perspectives

1. Study combinatorial structure of the problem. (Strongly NP ? Likely. Possibly reduced to bin packing).
2. Improve radar model : beamforming, waveform generation, etc.

This PhD thesis is funded by French MoD (DGA/MRIS) and THALES AIR SYSTEMS - ref. 1/2014/DGA

yanis.briheche@gmail.com