

Silica Nanoparticles Assisted Electrochemical Biosensor for the Detection and Degradation of Escherichia Coli Bacteria

Marion Mathelié-Guinlet, Ibtissem Gammoudi, Laure Beven, Fabien Moroté, Marie-Hélène Delville, Christine Grauby-Heywang, Touria Cohen-Bouhacina

▶ To cite this version:

Marion Mathelié-Guinlet, Ibtissem Gammoudi, Laure Beven, Fabien Moroté, Marie-Hélène Delville, et al.. Silica Nanoparticles Assisted Electrochemical Biosensor for the Detection and Degradation of Escherichia Coli Bacteria. Procedia Engineering, 2016, 168, pp.1048 - 1051. 10.1016/j.proeng.2016.11.337. hal-01477777

HAL Id: hal-01477777 https://hal.science/hal-01477777

Submitted on 27 Feb 2017 $\,$

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Distributed under a Creative Commons Attribution - NonCommercial - ShareAlike 4.0 International License





Available online at www.sciencedirect.com



Procedia Engineering 168 (2016) 1048 - 1051

Procedia Engineering

www.elsevier.com/locate/procedia

30th Eurosensors Conference, EUROSENSORS 2016

Silica Nanoparticles Assisted Electrochemical Biosensor For The Detection And Degradation Of *Escherichia Coli* Bacteria

Marion Mathelié-Guinlet^{a,b}, Ibtissem Gammoudi^a, Laure Beven^c, Fabien Moroté^a, Marie-Hélène Delville^b, Christine Grauby-Heywang^a, Touria Cohen-Bouhacina^{a,d,*}

LOMA, Université de Bordeaux, UMR CNRS 5798, 351 cours de la Libération, 33400 Talence, France
ICMCB, 87 avenue du Dr Albert Schweitzer, 33600 Pessac, France
INRA, UMR 1332 Biologie du Fruit et Pathologie, 33140 Villenave-d'Ornon, France

d. Cellule de transfert NanoPhyNov, ADERA, LOMA, 351 cours de la Libération, 33400 Talence, France

Abstract

An electrochemical biosensor, based on an amplification method using nanoparticles, is being developed for bacteria detection. Firstly, silica nanoparticles with different sizes were synthesized and studied in interaction with *Escherichia coli* cells for their potential toxicity, by atomic force microscopy and viability tests. A critical diameter in the range of 50-70 nm was found under which nanoparticles triggered drastic membrane damage even leading to cell lysis. Secondly, harmless nanoparticles were used in combination with polyelectrolytes as a transducer. A two steps spin coating protocol enabled (i) to immobilize a polyelectrolytes multilayer and (ii) to adsorb a 100 nm – NPs solution at $1g.L^{-1}$. Lastly, we plan to conjugate these nanoparticles with antibodies specific to *Escherichia coli* for their selective and sensitive detection through an electrochemical sensor.

@ 2016 The Authors. Published by Elsevier Ltd. This is an open access article under the CC BY-NC-ND license (http://creativecommons.org/licenses/by-nc-nd/4.0/).

Peer-review under responsibility of the organizing committee of the 30th Eurosensors Conference

Keywords: bacteria; nanoparticles; toxicity; biosensor; AFM.

1. Introduction

Rapid and selective detection of pathogenic bacteria, eventually followed by their degradation, is of great importance for biomedical, environmental and defense issues. Compared to conventional methods, biosensors integrating nanomaterials, offer rapid, ultrasensitive and cost-effective detection [1]. Though, for the safe

* Corresponding author : Touria Cohen Bouhacina - Tel : +33(0)5 4000 8408 ; e-mail : touria.cohen-bouhacina@u-bordeaux.fr

development of such technique, it is necessary first to understand, at the cellular level, the interactions between bacteria and nanoparticles (NPs).

Among widely used biological systems, *Escherichia coli* (*E. coli*) are the most thoroughly studied Gram-negative bacteria. Along with the cytoplasmic membrane and a peptidoglycan layer, they possess an outer membrane (OM), containing lipopolysaccharides (LPS) molecules and proteins. Diverse nanomaterials (metal oxides, silver...) proved to be bactericidal towards *E. coli* through mainly disruption of the membrane integrity and reactive oxygen species production [2]. Surprisingly, their interactions with silica NPs (SiO₂-NPs), which proved to be good candidates for biomedical applications (biocompatible, low toxicity) [3] are not well documented despite some toxicity studies relying only on the percentage of dead cells [4].

This work presents the development of a miniaturized electrochemical biosensor (a "lab on chip") for the detection of *E. coli* bacteria, based on their recognition and elimination by selective functionalized SiO₂-NPs, which can both detect the specific antigen and induce bacteria stress, even lysis, if necessary. It will first investigate the influence of the size and charge of SiO₂- NPs on *E. coli* to distinguish between the bactericidal and harmless NPs for the future biosensor. Atomic force microscopy (AFM) is a well suited technique for such study as it it allows (i) to observe, both in air and in physiological environment, in real time, biological systems at a nanometer scale, and (ii) to probe their nanomechanical properties. Morphological and rheological AFM studies allow thus to probe the effect of antibacterial agents such as NPs on the cell behavior, the membrane elasticity and integrity [5].

2. Results

2.1. Existence of a size threshold in the action of SiO_2 -NPs on E. coli

In a fundamental study, we first optimized the size of SiO₂-NPs needed for (i) *E. coli* bacteria detection and (ii) antibacterial activity.



Fig. 1. (a) Viability test of *E. coli* bacteria incubated with SiO₂-NPs⁻ of different diameters during 2h; (b) AFM height images of *E. coli* without and with SiO₂-NPs⁻; (c) corresponding zoom-in, in phase images, of the OM structure of *E. coli*.

Antibacterial activity experiments (Fig. 1a) revealed that negatively charge NPs (SiO₂-NPs⁻) smaller than a critical diameter ϕ_c (50 nm – 70 nm) induce a significant increase in the colony forming units (CFU) capacity of *E. coli*, notably due to cells cluster splitting. Larger SiO₂-NPs⁻ do not change CFUs nor bacteria population organization, implying their harmless activity, though a potential balance between toxic and splitting effects could be considered. Viability tests offered an overview of the bacteria population but appeared to be insufficient to determine the potential toxicity of SiO₂-NPs⁻. Consequently, AFM observations allowed for a more detailed study, from hundreds of microns to the nanometer scale. In air, *E. coli* bacteria exhibit a typical rod shape with an average length, width and height of 2.0 µm, 1.2 µm and 300 nm, respectively. Their surface exhibit a domain separation pattern with the presence of nanodomains, referred as "ripples" thereafter, mainly emphasized in phase images (Fig.

1b-c). This separation is attributed to molecules present in the OM of such bacteria, probably LPS [6]. The influence of SiO₂-NPs⁻ size was then investigated on both the morphology and rheology of *E. coli*. Whatever is their size, all SiO₂-NPs⁻ tend to aggregate in a non specific way around cells and on the substrate. SiO₂-NPs⁻ larger than ϕ_c (SiO₂-NPs⁻ 70 and 100 nm in diameter) neither change *E. coli* morphology nor its OM organization, keeping the ripples structure (Fig. 1b-c). Conversely, SiO₂-NPs⁻ smaller than ϕ_c (SiO₂-NPs⁻ 4, 10 and 50 nm in diameter) induce an unusual spherical shape, suggesting the disruption of the peptidoglycan layer integrity. In addition, such small SiO₂-NPs⁻ induce membrane damage: the OM exhibited spherical aggregates (Fig. 1c) as observed in the early ageing of *E. coli* bacteria [6], invaginations and protrusions (results not shown), leading, in turn, to leakage of cellular compounds and cell lysis (Fig. 1b white arrow).

2.2. E. coli morphology degradations induced by SiO_2 -NPs⁺

Unlike large positively charged NPs (SiO₂-NPs⁺ 100 nm in diameter), the small SiO₂-NPs⁺ (SiO₂-NPs⁺ 30 nm) lead to a strong decrease of CFUs, associated with a strong aggregation of cells (Fig. 2a). Again, viability test do not lead to any conclusion on the toxicity of SiO₂-NPs⁺ as compared to SiO₂-NPs⁻. Electrostatic attractions observed in dark field microscopy are also emphasized in AFM, as shown in Fig. 2b for SiO₂-NPs 100 nm: at equivalent diameter, SiO₂-NPs⁺ exclusively accumulate on and around cells, suggesting an increased affinity with *E. coli*. For both SiO₂-NPs⁺ under and above ϕ_c (SiO₂-NPs⁺ 30 and 100 nm in diameter), the OM structure remains organized in ripples domains (Fig. 2c) but drastic membrane damage are observed : extra-membrane aggregates circling cells and membrane invaginations such as pore-like lesions (Fig. 2d arrows) are even more frequent than with small SiO₂-NPs⁻. Consequently, we showed that the size threshold is not the same when changing the charge of SiO₂-NPs and that similar cell damage could be due to different mechanisms discriminating the charge and size effects.



Fig. 2. (a) Viability test of *E. coli* bacteria incubated with SiO₂-NPs⁺ of different diameters during 2h; (b-d) AFM images of different samples of *E. coli* incubated with SiO₂-NPs⁺ 100 nm.

2.3. Conception of the bacteria biosensor

Based on this fundamental work, we integrated harmless SiO₂-NPs ($\phi > \phi_c$) in a biosensor for bacteria detection. First, we optimized the functionalization procedure of the transducer on a mica substrate, used for its very low roughness compatible with AFM. Positive (PAH) and negative (PSS) polyelectrolytes were alternatively deposited to immobilize SiO₂-NPs used for the further detection, both by spin-coating allowing for highly reproducible results (Fig. 3). The influence of spin speed and spinning time were investigated to achieve (i) the lower roughness for the polyelectrolytes multilayer (PEM) and (ii) the best homogeneous coverage for NPs. Increasing time and speed lead to higher roughness and lower hydrophilicity; optimal PEM is obtained for [45 s; 100 rpm; 200 s⁻²]. For NPs coverage, the lower the speed, the higher the aggregation; the best coverage is observed for [60 s; 1000 rpm; 200 s⁻²]. This optimized protocol was successfully applied to functionnalize our working nanoelectrodes. Then, antibody-antigen cross linking allowed cells detection. A protocol has been established but still need to be approved: mixing for 2-4 h, at 200 rpm and room temperature, an amino-functionalized SiO₂-NPs solution and an anti-*E. coli* antibody solution with a 1000:1 ratio should led to a good conjugation rate. Detection of *E. coli* cells will finally be estimated through cyclic voltametry and QCM-D measurements by respectively following oxydo-reduction reactions and frequency shifts (mass deposition and dissipation), as in our previous work [7].



Fig. 3. (a) Influence of spinning time and speed on the roughness of the PEM, part of the biosensor transducer. (b) Influence of the number of polyelectrolyte layers on the thickness of the transducer. (c) AFM height image of the immobilisation of SiO_2-NPs^-100 on a PEM (7 layers) ended by PAH. (d) Scheme of the final transducer enabling the specific detection of *E. coli* cells.

Acknowledgements

Authors thank the Région Aquitaine and CNRS (France) for supporting this work through the equipment of the NanoSpectroImagerie (NSI-LOMA) platform used in this work (CPER COLA2). They are grateful to the Direction Générale de l'Armement (DGA, Ministère de la Défense, France) and the Région Aquitaine (France) for their financial support through the Ph.D. grant of M. Mathelié-Guinlet.

References

[1] N.Sanvicens, C. Pastells, N. Pascual, M. Pilar Marco, Nanoparticle-based biosensors for detection of pathogenic bacteria, Trends in Analytical Chemistry, Vol. 28, No. 11 (2009) 1243-1252.

[2] Yamamoto, O.; Sawai, J.; Sasamoto, T. Change in Antibacterial Characteristics with Doping Amount of ZnO in MgO–ZnO Solid Solution, Int. J. Inorg. Mater, 2 (2000) 451–454

[3] Wang, Y.; Zhao, Q.; Han, N.; Bai, L.; Li, J.; Liu, J.; Che, E.; Hu, L.; Zhang, Q.; Jiang, T.; *et al.* Mesoporous Silica Nanoparticles in Drug Delivery and Biomedical Applications, Nanomedicine Nanotechnol. Biol. Med., *11* (2015) 313–327

[4] Adams, L. K.; Lyon, D. Y.; Alvarez, P. J. J. Comparative Eco-Toxicity of Nanoscale TiO2, SiO2, and ZnO Water Suspensions. Water Res. 40 (2006) 3527–3532

[5] Muller, D. J. AFM: A Nanotool in Membrane Biology, Biochemistry (Mosc.), 47 (2008) 7986–7998

[6] I. Gammoudi, M. Mathelie-guinlet, F. Morote, L. Beven, D. Moynet, C. Grauby-heywang, T. Cohen-bouhacina, Morphological and nanostructural surface changes in Escherichia coli over time, monitored by atomic force microscopy, Colloids Surf. B Biointerfaces. 141 (2016) 355–364

[7] I. Gammoudi, V. Raimbault, H. Tarbague, F. Moroté, C. Grauby-Heywang, A. Othmane, et al., Enhanced bio-inspired microsensor based on microfluidic/bacteria/love wave hybrid structure for continuous control of heavy metals toxicity in liquid medium, Sens. Actuators B Chem. 198 (2014) 278–284