



**HAL**  
open science

# Self-Stabilizing Disconnected Components Detection and Rooted Shortest-Path Tree Maintenance in Polynomial Steps

Stéphane Devismes, David Ilcinkas, Colette Johnen

► **To cite this version:**

Stéphane Devismes, David Ilcinkas, Colette Johnen. Self-Stabilizing Disconnected Components Detection and Rooted Shortest-Path Tree Maintenance in Polynomial Steps . Discrete Mathematics and Theoretical Computer Science, 2015, ISS. hal-01485652v1

**HAL Id: hal-01485652**

**<https://hal.science/hal-01485652v1>**

Submitted on 9 Mar 2017 (v1), last revised 30 Nov 2017 (v4)

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

# Self-Stabilizing Disconnected Components Detection and Rooted Shortest-Path Tree Maintenance in Polynomial Steps\*

Stéphane Devismes<sup>1</sup>David Ilcinkas<sup>2</sup>Colette Johnen<sup>2</sup><sup>1</sup> *Université Grenoble Alpes, Grenoble, France*<sup>2</sup> *Univ. Bordeaux & CNRS, LaBRI, UMR 5800, F-33400 Talence, France**received 1998-10-14, revised 2002-07-19, accepted 2015-09-09.*

---

We deal with the problem of maintaining a shortest-path tree rooted at some process  $r$  in a network that may be disconnected after topological changes. The goal is then to maintain a shortest-path tree rooted at  $r$  in its connected component,  $V_r$ , and make all processes of other components detecting that  $r$  is not part of their connected component. We propose, in the composite atomicity model, a silent self-stabilizing algorithm for this problem working in semi-anonymous networks, where edges have strictly positive weights. This algorithm does not require any *a priori* knowledge about global parameters of the network. We prove its correctness assuming the distributed unfair daemon, the most general daemon. Its stabilization time in rounds is at most  $3n_{\max\text{CC}} + D$ , where  $n_{\max\text{CC}}$  is the maximum number of non-root processes in a connected component and  $D$  is the hop-diameter of  $V_r$ . Furthermore, if we additionally assume that edge weights are positive integers, then it stabilizes in a polynomial number of steps: namely, we exhibit a bound in  $O(\bar{w}_{\max} n_{\max\text{CC}}^3 n)$ , where  $\bar{w}_{\max}$  is the maximum weight of an edge and  $n$  is the number of processes.

**Keywords:** distributed algorithm, self-stabilization, routing algorithm, shortest path, disconnected network, shortest-path tree

---

## 1 Introduction

Given a connected undirected edge-weighted graph  $G$ , a *shortest-path (spanning) tree rooted at node  $r$*  is a spanning tree  $T$  of  $G$ , such that for every node  $u$ , the unique path from  $u$  to  $r$  in  $T$  is a shortest path from  $u$  to  $r$  in  $G$ . This data structure finds applications in the networking area (*n.b.*, in this context, nodes actually represent processes), since many distance-vector routing protocols, like *RIP (Routing Information Protocol)* and *BGP (Border Gateway Protocol)*, are based on the construction of shortest-path trees. Indeed, such algorithms implicitly builds a shortest-path tree rooted at each destination.

---

\*This study has been partially supported by the ANR projects DESCARTES (ANR-16-CE40-0023), ESTATE (ANR-16-CE25-0009), and MACARON (ANR-13-JS02-002). This study has been carried out in the frame of “the Investments for the future” Programme IdEx Bordeaux – CPU (ANR-10-IDEX-03-02). A preliminary version of this paper appeared in the Proceedings of the 20th International Conference on Principles of Distributed Systems (OPODIS 2016) [DIJ16].

From time to time, the network may be split into several connected components due to the network dynamics. In this case, routing to process  $r$  correctly operates only for the processes of its connected component,  $V_r$ . Consequently, in other connected components, information to reach  $r$  should be removed to gain space in routing tables, and to discard messages destined to  $r$  (which are unable to reach  $r$  anyway) and thus save bandwidth. The goal is then to make the network converging to a configuration where every process of  $V_r$  knows a shortest path to  $r$  and every other process detects that  $r$  is not in its own connected component. We call this problem the *Disconnected Components Detection and rooted Shortest-Path tree Maintenance* (DCDSPM) problem. Notice that a solution to this problem allows to prevent the well-known *count-to-infinity* problem [LGW04], where the distances to some unreachable process keep growing in routing tables because no process is able to detect the issue.

When topological changes are infrequent, they can be considered as transient faults [Tel01] and self-stabilization [Dij74] — a versatile technique to withstand *any* finite number of transient faults in a distributed system — becomes an attractive approach. A self-stabilizing algorithm is able to recover without external (*e.g.*, human) intervention a correct behavior in finite time, regardless of the *arbitrary* initial configuration of the system, and therefore, also after the occurrence of transient faults, provided that these faults do not alter the code of the processes.

A particular class of self-stabilizing algorithms is that of silent algorithms. A self-stabilizing algorithm is *silent* [DGS99] if it converges to a global state where the values of communication registers used by the algorithm remain fixed. Silent (self-stabilizing) algorithms are usually proposed to build distributed data structures, and so are well-suited for the problem considered here. As quoted in [DGS99], the silent property usually implies more simplicity in the algorithm design, moreover a silent algorithm may utilize less communication operations and communication bandwidth.

For the sake of simplicity, we consider here a single destination process  $r$ , called the *root*. However, the solution we will propose can be generalized to work with any number of destinations, provided that destinations can be distinguished. In this context, we do not require the network to be fully identified. Rather,  $r$  should be distinguished among other processes, and all non-root processes are supposed to be identical: we consider semi-anonymous networks.

In this paper, we propose a silent self-stabilizing algorithm, called Algorithm RSP, for the DCDSPM problem with a single destination process in semi-anonymous networks. Algorithm RSP does not require any *a priori* knowledge of processes about global parameters of the network, such as its size or its diameter. Algorithm RSP is written in the locally shared memory model with composite atomicity introduced by Dijkstra [Dij74], which is the most commonly used model in self-stabilization. In this model, executions proceed in (atomic) steps, and a self-stabilizing algorithm is silent if and only if all its executions are finite. Moreover, the asynchrony of the system is captured by the notion of *daemon*. The weakest (*i.e.*, the most general) daemon is the *distributed unfair daemon*. Hence, solutions stabilizing under such an assumption is highly desirable, because it works under any other daemon assumption. Moreover, time complexity (the *stabilization time*, mainly) can be bounded in terms of steps only if the algorithm works under an unfair daemon. Otherwise (*e.g.*, under a weakly fair daemon), time complexity can only be evaluated in terms of rounds, which capture the execution time according to the slowest process.

There are many self-stabilizing algorithms proven under the distributed unfair daemon, *e.g.*, [ACD<sup>+</sup>16, CDD<sup>+</sup>15, DLV11a, DLV11b, GHIJ14]. However, analyses of the stabilization time in steps is rather unusual and this may be an important issue. Indeed, recently, several self-stabilizing algorithms, which work under a distributed unfair daemon, have been shown to have an exponential stabilization time in steps in the worst case. In [ACD<sup>+</sup>16], silent leader election algorithms from [DLV11a, DLV11b] are

shown to be exponential in steps in the worst case. In [DJ16], the Breadth-First Search (BFS) algorithm of Huang and Chen [HC92] is also shown to be exponential in steps. Finally, in [Ga16] authors show that the first silent self-stabilizing algorithm for the DCDSM problem (still assuming a single destination) they proposed in [GHIJ14] is also exponential in steps.

### 1.1 Contribution

Algorithm RSP proposed here is proven assuming the distributed unfair daemon. We also study its stabilization time in rounds. We establish a bound of at most  $3n_{\max\text{CC}} + D$  rounds, where  $n_{\max\text{CC}}$  is the maximum number of non-root processes in a connected component and  $D$  is the hop-diameter of  $V_r$  (defined as the maximum over all pairs  $\{u, v\}$  of nodes in  $V_r$  of the minimum number of edges in a shortest path from  $u$  to  $v$ ).

Furthermore, RSP is the first silent self-stabilizing algorithm for the DCDSM problem which, assuming that the edge weights are positive integers, achieves a polynomial stabilization time in steps. Namely, in this case, the stabilization time of RSP is at most  $(\bar{w}_{\max} n_{\max\text{CC}}^3 + (3 - \bar{w}_{\max})n_{\max\text{CC}} + 3)(n - 1)$ , where  $\bar{w}_{\max}$  is the maximum weight of an edge and  $n$  is the number of processes. (*N.b.*, this stabilization time is less than or equal to  $\bar{w}_{\max} n^4$ , for all  $n \geq 3$ .)

Finally, notice that when all weights are equal to one, the DCDSM problem reduces to a BFS tree maintenance and the step complexity becomes at most  $(n_{\max\text{CC}}^3 + 2n_{\max\text{CC}} + 3)(n - 1)$ , which is less than or equal to  $n^4$  for all  $n \geq 2$ .

### 1.2 Related Work

To the best of our knowledge, only one self-stabilizing algorithm for the DCDSM problem has been previously proposed in the literature [GHIJ14]. This algorithm is silent and works under the distributed unfair daemon, but, as previously mentioned, it is exponential in steps. However, it has a slightly better stabilization time in rounds, precisely at most  $2(n_{\max\text{CC}} + 1) + D$  rounds<sup>(i)</sup>.

There are several shortest-path spanning tree algorithms in the literature that do not consider the problem of disconnected components detection. The oldest distributed algorithms are inspired by the Bellman-Ford algorithm [Bel58, FJ56]. Self-stabilizing shortest-path spanning tree algorithms have then been proposed in [CS94, HL02], but these two algorithms are proven assuming a central daemon, which only allows sequential executions. However, in [Hua05b], Tetz Huang proves that these algorithms actually work assuming the distributed unfair daemon. Nevertheless, no upper bounds on the stabilization time (in rounds or steps) are given. More recently, Cobb and Huang [CH09] proposed an algorithm constructing shortest-path trees based on any maximizable routing metrics. This algorithm does not require a priori knowledge about the network but it is proven only for the central weakly-fair daemon. It runs in a linear number of rounds and no analysis is given on the number of steps.

Self-stabilizing shortest-path spanning tree algorithms are also given in [AGH90, CG02, JT03]. These algorithms additionally ensure the loop-free property in the sense that they guarantee that a spanning tree structure is always preserved while edge costs change dynamically. However, none of these papers consider the unfair daemon, and consequently their step complexity cannot be analyzed.

Whenever all edges have weight one, shortest-path trees correspond to BFS trees. In [DDL12], the authors introduce the *disjunction* problem as follows. Each process has a constant input bit, 0 or 1. Then, the problem consists for each process in computing an output value equal to the disjunction of all input

---

<sup>(i)</sup>In fact, [GHIJ14] announced  $2n + D$  rounds, but it is easy to see that this complexity can be reduced to  $2(n_{\max\text{CC}} + 1) + D$ .

bits in the network. Moreover, each process with input bit 1 (if any) should be the root of a tree, and each other process should join the tree of the closest input bit 1 process, if any. If there is no process with input bit 1, the execution should terminate and all processes should output 0. The proposed algorithm is silent and self-stabilizing. Hence, if we set the input of a process to 1 if and only if it is the root, then their algorithm solves the DCDSM problem when all edge-weights are equal to one, since any process which is not in  $V_r$  will compute an output 0, instead of 1 for the processes in  $V_r$ . The authors show that their algorithm stabilizes in  $O(n)$  rounds, but no step complexity analysis is given. Now, as their approach is similar to [DLV11b], it is not difficult to see that their algorithm is also exponential in steps.

Several other self-stabilizing BFS tree algorithms have been proposed, but without considering the problem of disconnected components detection. Chen *et al.* present the first self-stabilizing BFS tree construction in [CYH91] under the central daemon. Huang and Chen present the first self-stabilizing BFS tree construction in [HC92] under the distributed unfair daemon, but recall that this algorithm has been proven to be exponential in steps in [DJ16]. Finally, notice that these two latter algorithms [CYH91, HC92] require that the processes know the exact number of processes in the network.

According to our knowledge, only the following works [CDV09, CRV11] take interest in the computation of the number of steps required by their BFS algorithms. The algorithm in [CDV09] is not silent and has a stabilization time in  $O(\Delta n^3)$  steps, where  $\Delta$  is the maximum degree in the network. The silent algorithm given in [CRV11] has a stabilization time  $O(D^2)$  rounds and  $O(n^6)$  steps. Finally, several other papers propose self-stabilizing algorithms stabilizing in both a polynomial number of rounds and a polynomial number of steps, *e.g.*, [ACD<sup>+</sup>16] (for the leader election problem), [CDPV06, CDV05] (for the DFS token circulation problem), [Cou09, KK05] (for the spanning tree problem).

### 1.3 Roadmap

In the next section, we present the computational model and basic definitions. In Section 3, we describe Algorithm RSP. Its proof of correctness and a complexity analysis in steps are given in Section 4. Finally, an analysis of the stabilization time in rounds is proposed in Section 5.

## 2 Preliminaries

We consider *distributed systems* made of  $n \geq 1$  interconnected processes. Each process can directly communicate with a subset of other processes, called its *neighbors*. Communication is assumed to be bidirectional. Hence, the topology of the system can be represented as a simple undirected graph  $G = (V, E)$ , where  $V$  is the set of processes and  $E$  the set of edges, representing communication links. Every process  $v$  can distinguish its neighbors using a *local labeling* of a given datatype  $Lbl$ . All labels of  $v$ 's neighbors are stored into the set  $\Gamma(v)$ . Moreover, we assume that each process  $v$  can identify its local label in the set  $\Gamma(u)$  of each neighbor  $u$ . Such labeling is called *indirect naming* in the literature [SK87]. By an abuse of notation, we use  $v$  to designate both the process  $v$  itself, and its local labels.

Each edge  $\{u, v\}$  has a strictly positive *weight*, denoted by  $\omega(u, v)$ . This notion naturally extends to paths: the weight of a path in  $G$  is the sum of its edge weights. The weighted distance between the processes  $u$  and  $v$ , denoted by  $d(u, v)$ , is the minimum weight of a path from  $u$  to  $v$ . Of course,  $d(u, v) = \infty$  if and only if  $u$  and  $v$  belong to two distinct connected components of  $G$ .

We use the *composite atomicity model of computation* [Dij74, Dol00] in which the processes communicate using a finite number of locally shared registers, called *variables*. Each process can read its own

variables and those of its neighbors, but can write only to its own variables. The *state* of a process is defined by the values of its local variables. The union of states of all processes determines the *configuration* of the system.

A *distributed algorithm* consists of one local program per process. We consider semi-uniform algorithms, meaning that all processes except one, the *root*  $r$ , execute the same program. In the following, for every process  $u$ , we denote by  $V_u$  the set of nodes (including  $u$ ) in the same connected component of  $G$  as  $u$ . In the following  $V_u$  is simply referred to as the connected component of  $u$ . We denote by  $n_{\max\text{CC}}$  the maximum number of non-root processes in a connected component of  $G$ . By definition,  $n_{\max\text{CC}} \leq n - 1$ .

The *program* of each process consists of a finite set of *rules* of the form *label* : *guard*  $\rightarrow$  *action*. *Labels* are only used to identify rules in the reasoning. A *guard* is a Boolean predicate involving the state of the process and that of its neighbors. The *action* part of a rule updates the state of the process. A rule can be executed only if its guard evaluates to *true*; in this case, the rule is said to be *enabled*. A process is said to be enabled if at least one of its rules is enabled. We denote by  $\text{Enabled}(\gamma)$  the subset of processes that are enabled in configuration  $\gamma$ .

When the configuration is  $\gamma$  and  $\text{Enabled}(\gamma) \neq \emptyset$ , a *daemon* selects a non-empty set  $\mathcal{X} \subseteq \text{Enabled}(\gamma)$ ; then every process of  $\mathcal{X}$  *atomically* executes one of its enabled rules, leading to a new configuration  $\gamma'$ , and so on. The transition from  $\gamma$  to  $\gamma'$  is called a *step*. The possible steps induce a binary relation over  $\mathcal{C}$ , denoted by  $\mapsto$ . An *execution* is a maximal sequence of configurations  $e = \gamma_0\gamma_1 \dots \gamma_i \dots$  such that  $\gamma_{i-1} \mapsto \gamma_i$  for all  $i > 0$ . The term “maximal” means that the execution is either infinite, or ends at a *terminal* configuration in which no rule is enabled at any process.

As previously stated, each step from a configuration to another is driven by a daemon. In this paper we assume the daemon is *distributed* and *unfair*. “Distributed” means that while the configuration is not terminal, the daemon should select at least one enabled process, maybe more. “Unfair” means that there is no fairness constraint, *i.e.*, the daemon might never select an enabled process unless it is the only enabled process.

In the composite atomicity model, an algorithm is *silent* if and only if all its executions are finite. Hence, we can define silent self-stabilization as follows.

**Definition 1 (Silent Self-Stabilization)** *Let  $\mathcal{L}$  be a non-empty subset of configurations, called set of legitimate configurations. A distributed system is silent and self-stabilizing under the daemon  $S$  for  $\mathcal{L}$  if and only if the following two conditions hold:*

- *all executions under  $S$  are finite, and*
- *all terminal configurations belong to  $\mathcal{L}$ .*

We use the notion of *round* [DIM93] to measure the time complexity. The first round of an execution  $e = \gamma_0, \gamma_1, \dots$  is the minimal prefix  $e_1 = \gamma_0, \dots, \gamma_j$ , such that every process that is enabled in  $\gamma_0$  either executes a rule or is neutralized during a computation step of  $e_1$ . A process  $v$  is *neutralized* during a computation step  $\gamma_i \mapsto \gamma_{i+1}$ , if  $v$  is enabled in  $\gamma_i$  but not in configuration  $\gamma_{i+1}$ . Let  $e'$  be the suffix  $\gamma_j, \gamma_{j+1}, \dots$  of  $e$ . The second round of  $e$  is the first round of  $e'$ , and so on.

The *stabilization time* of a silent self-stabilizing algorithm is the maximum time (in steps or rounds) over every execution (starting from any initial configuration) to reach a terminal (legitimate) configuration.



### 3 Algorithm RSP

This section is devoted to the presentation of our algorithm, Algorithm RSP (which stands for *Rooted Shortest-Path*). The code of Algorithm RSP is given in Algorithms 1 and 2.

#### 3.1 Variables

In RSP, each process  $u$  maintains three variables:  $st_u$ ,  $par_u$ , and  $d_u$ . Those three variables are constant for the root process<sup>(ii)</sup>,  $r$ :  $st_r = C$ ,  $par_r = \perp$ <sup>(iii)</sup>, and  $d_r = 0$ . For each non-root process  $u$ , we have:

- $st_u \in \{I, C, EB, EF\}$ , this variable gives the *status* of the process.  $I$ ,  $C$ ,  $EB$ , and  $EF$  respectively stand for *Isolated*, *Correct*, *Error Broadcast*, and *Error Feedback*. The two first states,  $I$  and  $C$ , are involved in the normal behavior of the algorithm, while the two last ones,  $EB$  and  $EF$ , are used during the correction mechanism. Precisely,  $st_u = C$  (resp.  $st_u = I$ ) means that  $u$  believes it is in  $V_r$  (resp. not in  $V_r$ ). The meaning of status  $EB$  and  $EF$  will be further detailed in Subsection 3.3.
- $par_u \in Lbl$ , a *parent pointer*. If  $u \in V_r$ ,  $par_u$  should designate a neighbor of  $u$ , referred to as its *parent*, and in a terminal configuration, the parent pointers exhibit a shortest path from  $u$  to  $r$ .  
Otherwise ( $u \notin V_r$ ), the variable is meaningless.
- $d_u \in \mathbb{R}^*$ , the *distance* value. If  $u \in V_r$ , then in a terminal configuration,  $d_u$  gives the weight of the shortest path from  $u$  to  $r$ .  
Otherwise ( $u \notin V_r$ ), the variable is meaningless.

#### 3.2 Normal Execution

Consider any configuration, where every process  $u \neq r$  satisfies  $st_u = I$ , and refer to such a configuration as a *normal initial configuration*. Each configuration reachable from a *normal initial configuration* is called a *normal configuration*, otherwise it is an *abnormal configuration*. Recall that  $st_r = C$  in all configurations. Then, starting from a normal initial configuration, all processes in a connected component different from  $V_r$  is disabled forever. Focus now on the connected component  $V_r$ . Each neighbor  $u$  of  $r$  is enabled to execute  $\mathbf{R}_R(u)$ . A process eventually chooses  $r$  as parent by executing this rule, which in particular sets its status to  $C$ . Then, executions of rule  $\mathbf{R}_R$  are asynchronously propagated in  $V_r$  until all its processes have status  $C$ : when a process  $u$  with status  $I$  finds one of its neighbor with status  $C$  it executes  $\mathbf{R}_R(u)$ :  $u$  takes status  $C$  and chooses as parent its neighbor  $v$  with status  $C$  such that  $d_v + \omega(u, v)$  is minimum,  $d_u$  being updated accordingly. In parallel, rules  $\mathbf{R}_C$  are executed to reduce the weight of the tree rooted at  $r$ : when a process  $u$  with status  $C$  can reduce  $d_u$  by selecting another neighbor with status  $C$  as parent, it chooses the one allowing to minimize  $d_u$  by executing  $\mathbf{R}_C(u)$ . Hence, eventually, the system reaches a terminal configuration, where the tree rooted at  $r$  is a shortest-path tree spanning all processes of  $V_r$ .

---

<sup>(ii)</sup>We should emphasize that the use of constants at the root is not a limitation, rather it allows to simplify the design and proof of the algorithm. Indeed, these constants can be removed by adding a rule to correct all root's variables, if necessary, within a single step.

<sup>(iii)</sup> $\perp$  is a particular value which is different from any value in  $Lbl$ .

### 3.3 Error Correction

Assume now that the system is in an abnormal configuration. Some non-root processes locally detect that their state is inconsistent with that of their neighbors. We call *abnormal roots* such processes. Informally (see Subsection 3.4 for the formal definition), a process  $u \neq r$  is an *abnormal root* if  $u$  is not isolated (i.e.,  $st_u \neq I$ ) and satisfies one of the following four conditions:

1. its parent pointer does not designate a neighbor,
2. its parent has status  $I$ ,
3. its distance value  $d_u$  is inconsistent with the distance value of its parent, or
4. its status is inconsistent with the status of its parent.

Every non-root process  $u$  that is not an abnormal root satisfies one of the two following cases. Either  $u$  is *isolated*, i.e.,  $st_u = I$ , or  $u$  points to some neighbor (i.e.,  $par_u \in \Gamma(u)$ ) and the state of  $u$  is coherent w.r.t. the state of its parent. In this latter case,  $u \in children(par_u)$ , i.e.,  $u$  is a “real” child of its parent (see Subsection 3.4 for the formal definition). Notice that every so-called *parent path*  $\mathcal{P} = u_1, \dots, u_k$  such that  $\forall i, 0 \leq i < k, u_i \in children(u_{i+1})$  is acyclic, and if  $\mathcal{P}$  is maximal, then  $u_k$  is either  $r$ , or an abnormal root. Hence, we define the normal tree  $T(r)$  (resp. an abnormal tree  $T(v)$ , for any abnormal root  $v$ ) as the set of all processes  $u$  such that there is a parent path from  $u$  to  $r$  (resp.  $v$ ).

Then, the goal is to remove all abnormal trees so that the system recovers a normal configuration. We remove these abnormal trees in a top-down manner starting from their roots. Now, we have to prevent the following situation: an abnormal root  $v$  leaves its tree; this removal creates some trees, each of those rooted at a previous child of  $v$ ; and later  $v$  joins one of those (created) trees. Hence, the idea is to freeze each abnormal tree, before removing it. By freezing we mean assigning each member of the tree to a particular state, here  $EF$ , so that (1) no member  $u$  of the tree is allowed to execute  $\mathbf{R}_R(u)$ , and (2) no process  $v$  can join the tree by executing  $\mathbf{R}_C(v)$ . Once frozen, the tree can be safely deleted from its root to its leaves.

The freezing mechanism (inspired from [BCV03]) is achieved using the status  $EB$  and  $EF$ . If a process is not involved into any freezing operation, then its status is  $I$  or  $C$ . Otherwise, it has status  $EB$  or  $EF$  and no neighbor can select it as its parent. These two latter states are actually used to perform a “Propagation of Information with Feedback” [Cha82, Seg83] in the abnormal trees. This is why status  $EB$  means “Error Broadcast” and  $EF$  means “Error Feedback”. From an abnormal root, the status  $EB$  is broadcast down in the tree. Then, once the  $EB$  wave reaches a leaf, the leaf initiates a convergecast  $EF$ -wave. Once the  $EF$ -wave reaches the abnormal root, the tree is said to be *dead*, meaning that all processes in the tree have status  $EF$  and, consequently, no other process can join it. So, the tree can be safely deleted from its abnormal root toward its leaves. There is two possibilities for the deletion. If the process  $u$  to be deleted has a neighbor with status  $C$ , then it executes rule  $\mathbf{R}_R(u)$  to directly join another “alive” tree. Otherwise,  $u$  becomes isolated by executing rule  $\mathbf{R}_I(u)$ , and  $u$  may join another tree later.

Let  $u$  be a process belonging to an abnormal tree at which it is not the root. Let  $v$  be its parent. From the previous explanation, it follows that during the correction,  $(st_v, st_u) \in \{(C, C), (EB, C), (EB, EB), (EB, EF), (EF, EF)\}$  until  $v$  resets by  $\mathbf{R}_R(v)$  or  $\mathbf{R}_I(v)$ . Now, due to the arbitrary initialization, the status of  $u$  and  $v$  may not be coherent, in this case  $u$  should also be an abnormal root. Precisely, as formally defined below, the status of  $u$  is incoherent w.r.t the status of its parent  $v$  if  $st_u \neq st_v$  and  $st_v \neq EB$ .



Actually, the freezing mechanism ensures that if a process is the root of an abnormal alive tree, it is in that situation since the initial configuration (see Lemma 4, page 10). The polynomial step complexity mainly relies on this strong property.

### 3.4 Definitions

**Definition 2 (Abnormal Root)** For every process  $u \neq r$ ,  $abRoot(u) \equiv st_u \neq I \wedge [par_u \notin \Gamma(u) \vee st_{par_u} = I \vee d_u < d_{par_u} + \omega(u, par_u) \vee (st_u \neq st_{par_u} \wedge st_{par_u} \neq EB)]$ .

Every process  $u \neq r$  that satisfies  $abRoot(u)$  is said to be an abnormal root.

**Definition 3 (Alive Abnormal Root)** A process  $u \neq r$  is said to be an alive abnormal root (resp. a dead abnormal root) if  $u$  is an abnormal root and has a status different from  $EF$  (resp. has status  $EF$ ).

**Definition 4 (Children)** For every process  $v$ ,  $children(v) = \{u \in \Gamma(v) \mid st_v \neq I \wedge st_u \neq I \wedge par_u = v \wedge d_u \geq d_v + \omega(u, v) \wedge (st_u = st_v \vee st_v = EB)\}$ .

**Definition 5 (Branch)** A branch is a maximal sequence of processes  $v_1, \dots, v_k$  for some integer  $k \geq 1$ , such that  $v_1$  is  $r$  or an abnormal root and, for every  $1 \leq i < k$ , we have  $v_{i+1} \in children(v_i)$ . The process  $v_i$  is said to be at depth  $i$  and  $v_i, \dots, v_k$  is called a sub-branch. If  $v_1 \neq r$ , the branch is said to be illegal, otherwise, the branch is said to be legal.

**Observation 1** A branch depth is at most  $n$ . A process  $v$  having status  $I$  does not belong to any branch. If a process  $v$  has status  $C$  (resp.  $EF$ ), then all processes of a sub-branch starting at  $v$  have status  $C$  (resp.  $EF$ ).

---

#### Algorithm 1: Code of RSP for the root process $r$

---

Constants:

$st_r$	=	$C$
$par_r$	=	$\perp$
$d_r$	=	$0$

---

## 4 Correctness and Step Complexity of Algorithm RSP

### 4.1 Partial Correctness

Before proceeding with the proof of correctness and the step complexity analysis, we define some useful concepts.

**Definition 6 (Legitimate State)** A process  $u$  is said to be in a legitimate state if  $u$  satisfies one of the following three conditions:

1.  $u = r$ ,
2.  $u \neq r$ ,  $u \in V_r$ ,  $st_u = C$ ,  $d_u = d(u, r)$ , and  $d_u = d_{par_u} + \omega(u, par_u)$ , or
3.  $u \notin V_r$  and  $st_u = I$ .

**Observation 2** Every process  $u \neq r$  such that  $st_u = C$  and  $d_u \neq d_{par_u} + \omega(u, par_u)$  is enabled.

**Algorithm 2:** Code of RSP for any process  $u \neq r$ 


---

<b>Variables:</b>		
$st_u$	$\in$	$\{I, C, EB, EF\}$
$par_u$	$\in$	$Lbl$
$d_u$	$\in$	$\mathbb{R}^*$
<b>Predicates:</b>		
$P_{reset}(u)$	$\equiv$	$st_u = EF \wedge abRoot(u)$
$P_{correction}(u)$	$\equiv$	$(\exists v \in \Gamma(u) \mid st_v = C \wedge d_v + \omega(u, v) < d_u)$
<b>Macro:</b>		
$computePath(u)$	$:$	$par_u := \operatorname{argmin}_{(v \in \Gamma(u) \wedge st_v = C)}(d_v + \omega(u, v));$ $d_u := d_{par_u} + \omega(u, par_u);$ $st_u := C$
<b>Rules</b>		
$R_C(u)$	$:$	$st_u = C \wedge P_{correction}(u) \rightarrow computePath(u)$
$R_{EB}(u)$	$:$	$st_u = C \wedge \neg P_{correction}(u) \wedge (abRoot(u) \vee st_{par_u} = EB) \rightarrow st_u := EB$
$R_{EF}(u)$	$:$	$st_u = EB \wedge (\forall v \in children(u) \mid st_v = EF) \rightarrow st_u := EF$
$R_I(u)$	$:$	$P_{reset}(u) \wedge (\forall v \in \Gamma(u) \mid st_v \neq C) \rightarrow st_u := I$
$R_R(u)$	$:$	$(P_{reset}(u) \vee st_u = I) \wedge (\exists v \in \Gamma(u) \mid st_v = C) \rightarrow computePath(u)$

---

**Definition 7 (Legitimate Configuration)** A legitimate configuration is any configuration where every process is in a legitimate state. We denote by  $\mathcal{LC}_{RSP}$  the set of all legitimate configurations of Algorithm RSP.

Let  $\gamma$  be a configuration. Let  $T_\gamma = (V_r, E_{T_\gamma})$  be the subgraph, where  $E_{T_\gamma} = \{\{p, q\} \in E \mid p \in V_r \setminus \{r\} \wedge par_p = q\}$ . By Definition 6 (point 2), we deduce the following observation.

**Observation 3** In every legitimate configuration  $\gamma$ ,  $T_\gamma$  is a shortest-path tree spanning all processes of  $V_r$ .

We now prove that the set of terminal configurations is exactly the set of legitimate configurations. We start by proving the following intermediate statement.

**Lemma 1** In any terminal configuration, every process has either status  $I$  or  $C$ .

**Proof:** This is trivially true for the root process,  $r$ . Assume that there exists a non-root process with status  $EB$  in a terminal configuration  $\gamma$ . Consider the non-root process  $u$  with status  $EB$  having the largest distance value  $d_u$  in  $\gamma$ . In  $\gamma$ , no process  $v$  with status  $C$  can be a child of  $u$ , otherwise either  $R_{EB}$  or  $R_C$  is enabled at  $v$  in  $\gamma$ , a contradiction. Moreover, by maximality of  $d_u$ ,  $u$  cannot have a child with status  $EB$  in  $\gamma$ . Therefore, in  $\gamma$  process  $u$  has no child or it has only children with status  $EF$ , and thus rule  $R_{EF}$  is enabled at  $u$ , a contradiction. Thus, every process has status  $C$ ,  $I$ , or  $EF$  in  $\gamma$ .

Assume now that there exists a non-root process with status  $EF$  in a terminal configuration  $\gamma$ . Consider the process  $u$  with status  $EF$  having the smallest distance value  $d_u$  in  $\gamma$ . By construction,  $u$  is an abnormal root in  $\gamma$ . So, either  $R_I$  or  $R_R$  is enabled at  $u$  in  $\gamma$ , a contradiction.  $\square$

The next lemma, Lemma 2, deals with the connected components that do not contain  $r$ , if any. Then, Lemma 3 deals with the connected component  $V_r$ .

**Lemma 2** In any terminal configuration, every process that does not belong to  $V_r$  is in a legitimate state.

**Proof:** Consider, by contradiction, that there exists a process  $u$  that belongs to the connected component  $CC$  other than  $V_r$  which is not in a legitimate state in some terminal configuration  $\gamma$ . By definition,  $u$  is not the root, moreover it has status  $C$  in  $\gamma$ , by Lemma 1. Without loss of generality, assume that  $u$  is the process of  $CC$  with status  $C$  having the smallest distance value  $d_u$  in  $\gamma$ . By construction,  $u$  is an abnormal root in  $\gamma$ . Thus, rule  $R_{EB}$  is enabled at  $u$  in  $\gamma$ , a contradiction.  $\square$

**Lemma 3** *In any terminal configuration, every process of  $V_r$  is in a legitimate state.*

**Proof:** Assume, by contradiction, that there exists a terminal configuration  $\gamma$  where at least one process in the connected component  $V_r$  is not in a legitimate state.

Assume also that there exists some process of  $V_r$  that has status  $I$  in  $\gamma$ . Consider now a process  $u$  of  $V_r$  such that in  $\gamma$ ,  $u$  has status  $I$  and at least one of its neighbors has status  $C$ . Such a process exists because no process has status  $EB$  or  $EF$  in  $\gamma$  (Lemma 1), but at least one process of  $V_r$  has status  $C$ , namely  $r$ . Obviously,  $R_R$  is enabled at  $u$  in  $\gamma$ , a contradiction. So, every process in  $V_r$  must have status  $C$  in  $\gamma$ . Moreover, for all processes in  $V_r$ , we have  $d_u = d_{par_u} + \omega(par_u, u)$  in  $\gamma$ , otherwise  $R_C$  is enabled at some process of  $V_r$  in  $\gamma$ .

Assume now that there exists a process  $u$  such that  $d_u < d(u, r)$  in  $\gamma$ . Consider a process  $u$  of  $V_r$  having the smallest distance value  $d_u$  among the processes in  $V_r$  such that  $d_u < d(u, r)$  in  $\gamma$ . By definition,  $u \neq r$  and we have  $d_u > d_{par_u}$  in  $\gamma$ , so  $d_{par_u} \geq d(par_u, r)$  in  $\gamma$ . Hence, we can conclude that  $d_u \geq d(u, r)$  in  $\gamma$ , a contradiction. So, every process  $u$  in  $V_r$  satisfies  $d_u \geq d(u, r)$  in  $\gamma$ .

Finally, assume that there exists a process  $u$  such that  $d_u > d(u, r)$  in  $\gamma$ . Consider a process  $u$  in  $V_r$  having the smallest distance to  $r$  among the processes in  $V_r$  such that  $d_u > d(u, r)$  in  $\gamma$ . By definition,  $u \neq r$  and there exists some process  $v$  in  $\Gamma(u)$  such that  $d(u, r) = d(v, r) + \omega(u, v)$  in  $\gamma$ . Thus, we have  $d_v = d(v, r)$  in  $\gamma$ . So,  $R_C$  is enabled at  $u$  in  $\gamma$ , a contradiction.  $\square$

After noticing that any legitimate configuration is a terminal one (by construction of the algorithm), we deduce the following corollary from the two previous lemmas.

**Corollary 1** *For every configuration  $\gamma$ ,  $\gamma$  is terminal if and only if  $\gamma$  is legitimate.*

## 4.2 Termination

In this section, we establish that every execution of Algorithm RSP under a distributed unfair daemon is finite. Furthermore, we compute the following bound on the number of steps of every execution:  $[\mathbb{W}_{\max} n_{\max CC}^3 + (3 - \mathbb{W}_{\max}) n_{\max CC} + 3](n - 1)$ , where  $n$  is the number of processes,  $\mathbb{W}_{\max}$  is the maximum weight of an edge, and  $n_{\max CC}$  is the maximum number of non-root processes in a connected component, when all weights are strictly positive integers.

**Lemma 4** *No alive abnormal root is created along any execution.*

**Proof:** Let  $\gamma \mapsto \gamma'$  be a step. Let  $u$  be a non-root process that is not an *alive abnormal root* in  $\gamma$ , and let  $v$  be the process such that  $par_u = v$  in  $\gamma'$ . If the status of  $u$  is  $EF$  or  $I$  in  $\gamma'$ , then  $u$  is not an alive abnormal root in  $\gamma'$ . Consider then the case where  $u$  has status  $EB$  in  $\gamma'$ . The only rule  $u$  can execute in  $\gamma \mapsto \gamma'$  is  $R_{EB}$ . Whether  $u$  executes  $R_{EB}$  or not,  $par_u$  is also  $v$  in  $\gamma$ . Since  $u$  is not an alive abnormal root in  $\gamma$ , and thus not an abnormal root either,  $v$  is not  $r$  and necessarily has status  $EB$  in  $\gamma$  in either case. Moreover,  $u$  belongs to  $children(v)$  in  $\gamma$ . So,  $v$  is not enabled in  $\gamma$  and  $u \in children(v)$  remains true in  $\gamma'$ . Hence, we can conclude that  $u$  is still not an alive abnormal root in  $\gamma'$ .

Let study the other case, *i.e.*,  $u$  has status  $C$  in  $\gamma'$ . During  $\gamma \mapsto \gamma'$ , the only rules that  $u$  may execute are  $R_R$  or  $R_C$ . So, we have  $st_v = C$  in  $\gamma$ , because it is a requirement to execute one of the two previous rules, or  $parent_u = v$  in  $\gamma$ . During  $\gamma \mapsto \gamma'$ , the only rules that  $v$  may execute are  $R_C$  or  $R_{EB}$ . Thus, during  $\gamma \mapsto \gamma'$ ,  $v$  either takes the status  $EB$ , decreases its distance value, or does not change the value of its variables. In either cases,  $u$  belongs to  $children(v)$  in  $\gamma'$ , which prevents  $u$  from being an alive abnormal root in  $\gamma'$ .  $\square$

Let  $AAR(\gamma)$  be the set of alive abnormal roots in any configuration  $\gamma$ . From the previous lemma, we know that, for every step  $\gamma \mapsto \gamma'$ , we have  $AAR(\gamma') \subseteq AAR(\gamma)$ . So, we can use the notion of  $u$ -segment (inspired from [ACD<sup>+</sup>16]) to bound the total number of steps in an execution.

**Definition 8 (u-Segment)** Let  $u$  be any non-root process. Let  $e = \gamma_0, \gamma_1, \dots$  be an execution.

If there is no step  $\gamma_i \mapsto \gamma_{i+1}$  in  $e$ , where there is a non-root process in  $V_u$  which is an alive abnormal root in  $\gamma_i$ , but not in  $\gamma_{i+1}$ , then the first  $u$ -segment of  $e$  is  $e$  itself and there is no other  $u$ -segment.

Otherwise, let  $\gamma_i \mapsto \gamma_{i+1}$  be the first step of  $e$ , where there is a non-root process in  $V_u$  which is an alive abnormal root in  $\gamma_i$ , but not in  $\gamma_{i+1}$ . The first  $u$ -segment of  $e$  is the prefix  $\gamma_0, \dots, \gamma_{i+1}$ . The second  $u$ -segment of  $e$  is the first  $u$ -segment of the suffix  $\gamma_{i+1}, \gamma_{i+2}, \dots$ , and so forth.

By Lemma 4, we have

**Observation 4** For every non-root process  $u$ ; for every execution  $e$ ,  $e$  contains at most  $n_{\max CC} + 1$   $u$ -segments, because there are initially at most  $n_{\max CC}$  alive abnormal roots in  $V_u$ .

**Lemma 5** Let  $u$  be any non-root process. During a  $u$ -segment, if  $u$  executes the rule  $R_{EF}$ , then  $u$  does not execute any other rule in the remaining of the  $u$ -segment.

**Proof:** Let  $seg_u$  be a  $u$ -segment. Let  $s_1$  be a step of  $seg_u$  in which  $u$  executes  $R_{EF}$ . Let  $s_2$  be the next step in which  $u$  executes its next rule. (If  $s_1$  or  $s_2$  do not exist, then the lemma trivially holds for  $seg_u$ .) Just before  $s_1$ , all branches containing  $u$  have an alive abnormal root, namely the non-root process  $v$  at depth 1 in any of these branches. (Note that we may have  $v = u$ .) On the other hand, just before  $s_2$ ,  $u$  is the dead abnormal root of all branches it belongs to. This implies that  $v$  must have executed the rule  $R_{EF}$  in the meantime and thus is not an alive abnormal root anymore when the step  $s_2$  is executed. Therefore,  $s_1$  and  $s_2$  belong to two distinct  $u$ -segments of the execution.  $\square$

**Corollary 2** Let  $u$  be a non-root process. The sequence of rules executed by  $u$  during a  $u$ -segment belongs to the following language:  $(R_I + \varepsilon)(R_R + \varepsilon)R_C^*(R_{EB} + \varepsilon)(R_{EF} + \varepsilon)$ .

We use the notion of *maximal causal chain* to further analyze the number of steps in a  $u$ -segment.

**Definition 9 (Maximal Causal Chain)** Let  $u$  be a non-root process and  $seg_u$  be any  $u$ -segment. A maximal causal chain of  $seg_u$  rooted at  $u_0 \in V_u$  is a maximal sequence of actions  $a_1, a_2, \dots, a_k$  executed in  $seg_u$  such that the action  $a_1$  sets  $par_{u_1}$  to  $u_0 \in V_u$  not later than any other action by  $u_0$  in  $seg_u$ , and for all  $2 \leq i \leq k$ , the action  $a_i$  sets  $par_{u_i}$  to  $u_{i-1}$  after the action  $a_{i-1}$  but not later than  $u_{i-1}$ 's next action.

**Observation 5**

- An action  $a_i$  belongs to a maximal causal chain if and only if  $a_i$  consists in a call to the macro `computePath` by a non-root process.

- Only actions of Rules  $R_R$  and  $R_C$  contain the execution of *computePath*.

Let  $u$  be a non-root process and  $\text{seg}_u$  be any  $u$ -segment. Let  $a_1, a_2, \dots, a_k$  be a maximal causal chain of  $\text{seg}_u$  rooted at  $u_0$ .

- For all  $1 \leq i \leq k$ ,  $a_i$  consists in the execution of *computePath* by  $u_i$  (i.e.,  $u_i$  executes the rule  $R_R$  or  $R_C$ ) where  $u_i \in V_u$ .
- Denote by  $ds_{\text{seg}_u, v}$  the distance value of process  $v$  at the beginning of  $\text{seg}_u$ . For all  $1 \leq i \leq k$ ,  $a_i$  sets  $d_{u_i}$  to  $ds_{\text{seg}_u, u_0} + \sum_{j=1}^{j=i} w(u_j, u_{j-1})$ .

For the next lemmas and theorems, we recall that  $n_{\text{maxCC}} \leq n - 1$  is the maximum number of non-root processes in a connected component of  $G$ .

**Lemma 6** *Let  $u$  be a non-root process. All actions in a maximal causal chain of a  $u$ -segment are caused by different non-root processes of  $V_u$ . Moreover, an execution of *computePath* by some non-root process  $v$  never belongs to any maximal causal chain rooted at  $v$ .*

**Proof:** First note that any rule  $R_C$  executed by a process  $v$  makes the value of  $d_v$  decrease.

Assume now, by the contradiction, that there exists a process  $v$  such that, in some maximal causal chain  $a_1, a_2, \dots, a_k$  of a  $u$ -segment,  $v$  is used as parent in some action  $a_i$  and executes the action  $a_j$ , with  $j > i$ . The value of  $d_v$  is strictly larger just after the action  $a_j$  than just before the action  $a_i$ . This implies that process  $v$  must have executed the rule  $R_R$  in the meantime. So,  $a_i$  and  $a_j$  are executed in two different  $u$ -segments by Corollary 2 and the fact that  $v$  has status  $C$  just before the action  $a_i$ . Consequently, they do not belong to the same maximal causal chain, a contradiction.

Therefore, all actions in a maximal causal chain are caused by different processes, and a process never executes an action in a maximal causal chain it is the root of. As all actions in a maximal causal chain are executed by process in the same connected component, we are done.  $\square$

**Definition 10** ( $S_{\text{seg}_u, v}$ ) *Given a non-root process  $u$  and a  $u$ -segment  $\text{seg}_u$ , we define  $S_{\text{seg}_u, v}$  as the set of all the distance values obtained after executing an action belonging to any maximal causal chain of  $\text{seg}_u$  rooted at process  $v$  ( $v \in V_u$ ).*

Note that, from Observation 5 and Lemma 6, we have the following observation:

**Observation 6** *The size of the set  $S_{\text{seg}_u, v}$  is bounded by a function of the number of nodes in  $V_u$ .*

**Lemma 7** *Given a non-root process  $u$  and a  $u$ -segment  $\text{seg}_u$ , if the size of  $S_{\text{seg}_u, v}$  is bounded by  $X$  for all process  $v \in V_u$ , then the number of *computePath* executions done by  $u$  in  $\text{seg}_u$  is bounded by  $X(n_{\text{maxCC}} - 1)$ .*

**Proof:** Except possibly the first, all *computePath* executions done by a  $u$  in a  $u$ -segment  $\text{seg}_u$  are done through the rule  $R_C$ . For all these, the variable  $d_u$  is always decreasing. Therefore, all the values of  $d_u$  obtained by the *computePath* executions done by  $u$  are different. By definition of  $S_{\text{seg}_u, v}$  and by Lemma 6, all these values belong to the set  $\bigcup_{v \in V_u \setminus \{u\}} S_{\text{seg}_u, v}$ , which has size at most  $X(n_{\text{maxCC}} - 1)$ .  $\square$

By definition, each step contains at least one action, made by a non-root process. Let  $u$  be any non-root process. Assume that, in any  $u$ -segment  $\text{seg}_u$ , the size of  $S_{\text{seg}_u, v}$  is bounded by  $X$  for all process  $v \in V_u$ .

So, the number of step of  $u$  in  $\text{seg}_u$  is bounded by  $X(n_{\max\text{CC}} - 1) + 3$ , by Lemma 7 and Corollary 2. Moreover, recall that each execution contains at most  $n_{\max\text{CC}} + 1$   $u$ -segments (Observation 4). So,  $u$  executes in at most  $Xn_{\max\text{CC}}^2 + 3n_{\max\text{CC}} - X + 3$  steps. Finally, as  $u$  is an arbitrary non-root process and there are  $n - 1$  non-root processes, follows.

**Theorem 1** *If the size of  $S_{\text{seg}_u, v}$  is bounded by  $X$  for all non-root process  $u$ , for all  $u$ -segment  $\text{seg}_u$ , and for all process  $v$  in  $V_u$ , then the total number of steps during any execution, is bounded by  $(Xn_{\max\text{CC}}^2 + 3n_{\max\text{CC}} - X + 3)(n - 1)$ .*

Let  $W_{\max} = \max_{\{u, v\} \in E} \omega(u, v)$ . If all weights are strictly positive integers, then the size of any  $S_{\text{seg}_u, v}$ , where  $u$  is a non-root process and  $v \in V_u$ , is bounded by  $W_{\max}n_{\max\text{CC}}$ , because  $S_{\text{seg}_u, v} \subseteq [ds_{\text{seg}_u, v} + 1, ds_{\text{seg}_u, v} + W_{\max}(n_{\text{cc}} - 1)]$ , where  $n_{\text{cc}} \leq n_{\max\text{CC}} + 1$  is the number of processes in  $V_u$ . Hence, we deduce the following theorem from Theorem 1, Observation 6, and Corollary 1.

**Theorem 2** *Algorithm RSP is silent self-stabilizing under the distributed unfair daemon for the set  $\mathcal{LC}_{\text{RSP}}$  and, when all weights are strictly positive integers, its stabilization time in steps is at most  $[W_{\max}n_{\max\text{CC}}^3 + (3 - W_{\max})n_{\max\text{CC}} + 3](n - 1)$ , i.e.,  $O(W_{\max}n_{\max\text{CC}}^3n)$ .*

If all edges in  $G$  have the same weight  $w$ , then the size of  $S_{\text{seg}_u, v}$ , where  $u$  is a non-root process and  $v \in V_u$ , is bounded by  $n_{\max\text{CC}}$ . Indeed, in such a case, we have  $S_{\text{seg}_u, v} \subseteq \{ds_{\text{seg}_u, v} + i.w \mid 1 \leq i \leq n_{\text{cc}} - 1\}$ , where  $n_{\text{cc}} \leq n_{\max\text{CC}} + 1$  is the number of processes in  $V_u$ . Hence, we obtain the following corollary.

**Corollary 3** *If all edges have the same weight, then the stabilization time in steps of Algorithm RSP is at most  $(n_{\max\text{CC}}^3 + 2n_{\max\text{CC}} + 3)(n - 1)$ , which is less than or equal to  $n^4$  for all  $n \geq 2$ .*

## 5 Round Complexity of Algorithm RSP

We now prove that every execution of Algorithm RSP lasts at most  $3n_{\max\text{CC}} + D$  rounds, where  $n_{\max\text{CC}}$  is the maximum number of non-root processes in a connected component and  $D$  is the hop-diameter of the connected component containing  $r$ ,  $V_r$ .

The first lemma essentially claims that all processes that are in illegal branches progressively switch to status  $EB$  within  $n_{\max\text{CC}}$  rounds, in order of increasing depth.

**Lemma 8** *Let  $i \in \mathbb{N}^*$ . Starting from the beginning of round  $i$ , there does not exist any process both in state  $C$  and at depth less than  $i$  in an illegal branch.*

**Proof:** We prove this lemma by induction on  $i$ . The base case ( $i = 1$ ) is obvious, so we assume that the lemma holds for some integer  $i \geq 1$ . From the beginning of round  $i$ , no process can ever choose a parent which is at depth smaller than  $i$  in an illegal branch because those processes will never have status  $C$ , by induction hypothesis. Moreover, no process with status  $C$  can have its depth decreasing to  $i$  or smaller by an action of one of its ancestors at depth smaller than  $i$ , because these processes have status  $EB$  and have at least one child not having status  $EF$ . Thus, they cannot execute any rule. Therefore, no process can take state  $C$  at depth smaller or equal to  $i$  in an illegal branch.

Consider any process  $u$  with status  $C$  at depth  $i$  in an illegal branch at the beginning of the round  $i$ .  $u \neq r$ . Moreover, by induction hypothesis,  $u$  is an abnormal root, or the parent of  $u$  is not in state  $C$  (i.e., it is in the state  $EB$ ). During round  $i$ ,  $u$  will execute rule  $R_{EB}$  or  $R_C$  and thus either switch to state  $EB$  or join another branch at a depth greater than  $i$ . This concludes the proof of the lemma.  $\square$



**Corollary 4** *After at most  $n_{\max CC}$  rounds, the system is in a configuration from which no process in any illegal branch has status  $C$  forever.*

*Moreover, once such a configuration is reached, each time a process executes a rule other than  $R_{EF}$ , this process is outside any illegal branch forever.*

The next lemma essentially claims that, once no process in an illegal branch has status  $C$  forever, processes in illegal branches progressively switch to status  $EF$  within at most  $n_{\max CC}$  rounds, in order of decreasing depth.

**Lemma 9** *Let  $i \in \mathbb{N}^*$ . Starting from the beginning of round  $n_{\max CC} + i$ , there does not exist any process at depth larger than  $n_{\max CC} - i + 1$  in an illegal branch having the status  $EB$ .*

**Proof:** We prove this lemma by induction on  $i$ . The base case ( $i = 1$ ) is obvious, so we assume that the lemma holds for some integer  $i \geq 1$ . By induction hypothesis, at the beginning of round  $n_{\max CC} + i$ , no process at depth larger than  $n_{\max CC} - i + 1$  has the status  $EB$ . Therefore, processes with status  $EB$  at depth  $n_{\max CC} - i + 1$  in an illegal branch can execute the rule  $R_{EF}$  at the beginning of round  $n_{\max CC} + i$ . These processes will thus all execute within round  $n_{\max CC} + i$  (they cannot be neutralized as no children can connect to them). We conclude the proof by noticing that, from Corollary 4, once round  $n_{\max CC}$  has terminated, any process in an illegal branch that executes either gets status  $EF$ , or will be outside any illegal branch forever.  $\square$

The next lemma essentially claims that, after the propagation of status  $EF$  in illegal branches, the maximum length of illegal branches progressively decreases until all illegal branches vanish.

**Lemma 10** *Let  $i \in \mathbb{N}^*$ . Starting from the beginning of round  $2n_{\max CC} + i$ , there does not exist any process at depth larger than  $n_{\max CC} - i + 1$  in an illegal branch.*

**Proof:** We prove this lemma by induction on  $i$ . The base case ( $i = 1$ ) is obvious, so we assume that the lemma holds for some integer  $i \geq 1$ . By induction hypothesis, at the beginning of round  $2n_{\max CC} + i$ , no process is at depth larger than or equal to  $n_{\max CC} - i + 1$  in an illegal branch. All processes in an illegal branch have the status  $EF$ . So, at the beginning of round  $2n_{\max CC} + i$ , any abnormal root satisfies the predicate  $P_{reset}$ , they are enabled to execute either  $R_I$ , or  $R_R$ . So, all abnormal roots at the beginning of the round  $2n_{\max CC} + i$  are no more in an illegal branch at the end of this round: the maximal depth of the illegal branches has decreased, since by Corollary 4, no process can join an illegal tree during the round  $2n_{\max CC} + i$ .  $\square$

**Corollary 5** *After at most round  $3n_{\max CC}$ , there are no illegal branches forever.*

Note that in any connected component that does not contain the root  $r$ , there is no legal branch. Then, since the only way for a process to be in no branch is to have status  $I$ , we obtain the following corollary.

**Corollary 6** *For any connected component  $H$  other than  $V_r$ , after at most  $3n_{\max CC}$  rounds, every process of  $H$  is in a legitimate state forever.*

In the connected component  $V_r$ , Algorithm RSP may need additional rounds to propagate the correct distances to  $r$ . In the next lemma, we use the notion of hop-distance to  $r$  defined below.

**Definition 11 (Hop-Distance and Hop-Diameter)** A process  $u$  is said to be at hop-distance  $k$  from  $v$  if the minimum number of edges in a shortest path from  $u$  to  $v$  is  $k$ .

The hop-diameter of a graph  $G$  (resp. of a connected component  $H$  of the graph  $G$ ) is the maximum hop-distance between any two nodes of  $G$  (resp. of  $H$ ).

**Lemma 11** Let  $i \in \mathbb{N}$ . In every execution of Algorithm RSP, starting from the beginning of round  $3n_{\max CC} + i$ , every process at hop-distance at most  $i$  from  $r$  is in a legitimate state.

**Proof:** We prove this lemma by induction on  $i$ . First, by definition, the root  $r$  is always in a legitimate state, so the base case ( $i = 0$ ) trivially holds. Then, after at most  $3n_{\max CC}$  rounds, every process either belongs to a legal branch or has status  $I$  (by Corollary 5), thus any non-isolated process  $v \in V_r$  always stores a distance  $d$  such that  $d \geq d(v, r)$ , its actual weighted distance to  $r$ . By induction hypothesis, every process at hop-distance at most  $i$  from  $r$  has converged to a legitimate state within at most  $3n_{\max CC} + i$  rounds. Therefore, at the beginning of round  $3n_{\max CC} + i + 1$ , every process  $v$  at hop-distance  $i + 1$  from  $r$  which is not in a legitimate state is enabled for executing rule  $R_C$ . Thus, at the end of round  $3n_{\max CC} + i + 1$ , every process at hop-distance at most  $i + 1$  from  $r$  is in a legitimate state (such processes cannot be neutralized during this round). Also, these processes will never change their state since there are no processes that can make them closer to  $r$ .  $\square$

Summarizing all the results of this section, we obtain the following theorem.

**Theorem 3** Every execution of Algorithm RSP lasts at most  $3n_{\max CC} + D$  rounds, where  $n_{\max CC}$  is the maximum number of non-root processes in a connected component and  $D$  is the hop-diameter of the connected component containing  $r$ .

## References

- [ACD<sup>+</sup>16] Karine Altisen, Alain Cournier, Stéphane Devismes, Anaïs Durand, and Franck Petit. Self-stabilizing leader election in polynomial steps. *Information and Computation, special issue of SSS 2014*, 2016. To appear.
- [Afe13] Yehuda Afek, editor. *Distributed Computing - 27th International Symposium, DISC 2013, Jerusalem, Israel, October 14-18, 2013. Proceedings*, volume 8205 of *Lecture Notes in Computer Science*. Springer, 2013.
- [AGH90] A Arora, MG Gouda, and T Herman. Composite routing protocols. In *the 2nd IEEE Symposium on Parallel and Distributed Processing (SPDP'90)*, pages 70–78, 1990.
- [AGM<sup>+</sup>08] I. Abraham, C. Gavoille, D. Malkhi, N. Nisan, and M. Thorup. Compact name-independent routing with minimum stretch. *ACM Transactions on Algorithms*, 4(3):37, 2008.
- [BCV03] Lélia Blin, Alain Cournier, and Vincent Villain. An improved snap-stabilizing PIF algorithm. In Shing-Tsaan Huang and Ted Herman, editors, *Self-Stabilizing Systems, 6th International Symposium, SSS 2003*, volume 2704 of *Lecture Notes in Computer Science*, pages 199–214, San Francisco, CA, USA, June 24-25 2003. Springer.
- [BDV07] Doina Bein, Ajoy Kumar Datta, and Vincent Villain. Self-stabilizing local routing in ad hoc networks. *The Computer Journal*, 50(2):197–203, 2007.

- [Bel58] Richard Bellman. On a routing problem. *Quart. Appl. Math.*, 16:87–90, 1958.
- [BPBRT10] L. Blin, M. Potop-Butucaru, S. Rovedakis, and S. Tixeuil. Loop-free super-stabilizing spanning tree construction. In *the 12th International Symposium on Stabilization, Safety, and Security of Distributed Systems (SSS'10)*, Springer LNCS 6366, pages 50–64, 2010.
- [CDD<sup>+</sup>15] Fabienne Carrier, Ajoy Kumar Datta, Stéphane Devismes, Lawrence L. Larmore, and Yvan Rivierre. Self-stabilizing (f, g)-alliances with safe convergence. *J. Parallel Distrib. Comput.*, 81-82:11–23, 2015.
- [CDPV06] Alain Cournier, Stéphane Devismes, Franck Petit, and Vincent Villain. Snap-stabilizing depth-first search on arbitrary networks. *The Computer Journal*, 49(3):268–280, 2006.
- [CDV05] Alain Cournier, Stéphane Devismes, and Vincent Villain. A snap-stabilizing dfs with a lower space requirement. In *Symposium on Self-Stabilizing Systems*, pages 33–47. Springer, 2005.
- [CDV09] Alain Cournier, Stéphane Devismes, and Vincent Villain. Light enabling snap-stabilization of fundamental protocols. *ACM Transactions on Autonomous and Adaptive Systems*, 4(1), 2009.
- [CG02] J. A. Cobb and M. G. Gouda. Stabilization of general loop-free routing. *Journal of Parallel and Distributed Computing*, 62(5):922–944, 2002.
- [CH09] J. A. Cobb and C.-T. Huang. Stabilization of maximal-metric routing without knowledge of network size. In *2009 International Conference on Parallel and Distributed Computing, Applications and Technologies*, pages 306–311. IEEE, 2009.
- [Cha82] Ernest J. H. Chang. Echo Algorithms: Depth Parallel Operations on General Graphs. *IEEE Trans. Software Eng.*, 8(4):391–401, 1982.
- [Cou09] Alain Cournier. A new polynomial silent stabilizing spanning-tree construction algorithm. In *International Colloquium on Structural Information and Communication Complexity*, pages 141–153. Springer, 2009.
- [CRV11] Alain Cournier, Stephane Rovedakis, and Vincent Villain. The first fully polynomial stabilizing algorithm for BFS tree construction. In *the 15th International Conference on Principles of Distributed Systems (OPODIS'11)*, Springer LNCS 7109, pages 159–174, 2011.
- [CS94] Srinivasan Chandrasekar and Pradip K Srimani. A self-stabilizing distributed algorithm for all-pairs shortest path problem. *Parallel Algorithms and Applications*, 4(1-2):125–137, 1994.
- [CYH91] NS Chen, HP Yu, and ST Huang. A self-stabilizing algorithm for constructing spanning trees. *Information Processing Letters*, 39:147–151, 1991.
- [DDL12] Ajoy Kumar Datta, Stéphane Devismes, and Lawrence L. Larmore. Brief announcement: Self-stabilizing silent disjunction in an anonymous network. In *the 14th International Symposium on Stabilization, Safety, and Security of Distributed Systems (SSS'12)*, Springer LNCS 7596, pages 46–48, 2012.

- [DDL13] Ajoy Kumar Datta, Stéphane Devismes, and Lawrence L. Larmore. Self-stabilizing silent disjunction in an anonymous network. In *14th International Conference on Distributed Computing and Networking (ICDCN 2013)*, Springer LNCS 7730, pages 148–160, 2013.
- [DGS99] Shlomi Dolev, Mohamed G. Gouda, and Marco Schneider. Memory requirements for silent stabilization. *Acta Informatica*, 36(6):447–462, 1999.
- [Dij74] Edsger W. Dijkstra. Self-stabilizing Systems in Spite of Distributed Control. *Commun. ACM*, 17(11):643–644, 1974.
- [DIJ16] Stéphane Devismes, David Ilcinkas, and Colette Johnen. Self-stabilizing rooted shortest-path tree in polynomial steps. In *the 20th International Conference on Principles of Distributed Systems (OPODIS'16)*, page to appear, 2016.
- [DIM93] S Dolev, A Israeli, and S Moran. Self-stabilization of dynamic systems assuming only Read/Write atomicity. *Distributed Computing*, 7(1):3–16, 1993.
- [DJ16] Stéphane Devismes and Colette Johnen. Silent self-stabilizing {BFS} tree algorithms revisited. *Journal of Parallel and Distributed Computing*, 97:11 – 23, 2016.
- [DLP10] Ajoy Kumar Datta, Lawrence L. Larmore, and Hema Piniganti. Self-stabilizing leader election in dynamic networks. In *the 12th International Symposium on Stabilization, Safety, and Security of Distributed Systems (SSS'10)*, Springer LNCS 6366, pages 35–49, 2010.
- [DLV11a] Ajoy K. Datta, Lawrence L. Larmore, and Priyanka Vemula. An  $o(n)$ -time self-stabilizing leader election algorithm. *jpdc*, 71(11):1532–1544, 2011.
- [DLV11b] Ajoy Kumar Datta, Lawrence L. Larmore, and Priyanka Vemula. Self-stabilizing leader election in optimal space under an arbitrary scheduler. *Theoretical Computer Science*, 412(40):5541–5561, 2011.
- [Dol00] Shlomi Dolev. *Self-stabilization*. MIT Press, March 2000.
- [FJ56] Lester R. Ford Jr. Network flow theory. *RAND Corporation*, (Paper P-923), August 14 1956.
- [Ga16] Christian Glacet and Nicolas Hanusse and. Disconnected components detection and rooted shortest-path tree maintenance in networks - extended version. Technical report, LaBRI, CNRS UMR 5800, 2016.
- [GGHI13] Cyril Gavoille, Christian Glacet, Nicolas Hanusse, and David Ilcinkas. On the communication complexity of distributed name-independent routing schemes. In *the 27th International Symposium on Distributed Computing (DISC'13)*, Springer LNCS 8205, pages 418–432, 2013.
- [GHIJ14] Christian Glacet, Nicolas Hanusse, David Ilcinkas, and Colette Johnen. Disconnected components detection and rooted shortest-path tree maintenance in networks. In *the 16th International Symposium on Stabilization, Safety, and Security of Distributed Systems (SSS'14)*, Springer LNCS 8736, pages 120–134, 2014.

- [Gä03] Felix C. Gärtner. A survey of self-stabilizing spanning-tree construction algorithms. Technical report, Swiss Federal Institute of Technology (EPFL), 2003.
- [HC92] Shing-Tsaan Huang and Nian-Shing Chen. A self-stabilizing algorithm for constructing breadth-first trees. *Information Processing Letters*, 41(2):109–117, 1992.
- [Hed88] Charles L Hedrick. Routing information protocol, 1988.
- [HL02] Tetz C Huang and Ji-Cherng Lin. A self-stabilizing algorithm for the shortest path problem in a distributed system. *Computers & Mathematics with Applications*, 43(1):103–109, 2002.
- [Hua05a] Tetz C. Huang. A self-stabilizing algorithm for the shortest path problem assuming read/write atomicity. *Journal of Computer System Sciences*, 71(1):70–85, 2005.
- [Hua05b] Tetz C Huang. A self-stabilizing algorithm for the shortest path problem assuming the distributed demon. *Computers & Mathematics with Applications*, 50(5–6):671 – 681, 2005.
- [JT03] C. Johnen and S. Tixeuil. Route preserving stabilization. In *the 6th International Symposium on Self-stabilizing System (SSS'03)*, Springer LNCS 2704, pages 184–198, 2003.
- [KK05] Adrian Kosowski and Lukasz Kuszner. A self-stabilizing algorithm for finding a spanning tree in a polynomial number of moves. In *6th International Conference Parallel Processing and Applied Mathematics, (PPAM'05)*, Springer LNCS 3911, pages 75–82, 2005.
- [LGW04] Alberto Leon-Garcia and Indra Widjaja. *Communication Networks*. McGraw-Hill, Inc., New York, NY, USA, 2 edition, 2004.
- [RLH06] Y Rekhter, T Li, and S Hares. Rfc 4271: Border gateway protocol 4, 2006.
- [Seg83] Adrian Segall. Distributed Network Protocols. *IEEE Transactions on Information Theory*, 29(1):23–34, 1983.
- [SK87] M Sloman and J Kramer. *Distributed systems and computer networks*. Prentice Hall, 1987.
- [Tel01] G Tel. *Introduction to distributed algorithms*. Cambridge University Press, Cambridge, UK, Second edition 2001.