

## Design of an automated fixed bed reactor used for a catalytic wet oxidation process

Alexis El Khoury, Bouchra Bejjany, Marie Debacq, Alain Delacroix

## ▶ To cite this version:

Alexis El Khoury, Bouchra Bejjany, Marie Debacq, Alain Delacroix. Design of an automated fixed bed reactor used for a catalytic wet oxidation process. ICINCO 2007 - 4th International Conference on Informatics in Control, Automation and Robotics, May 2007, Angers, France. , Proceedings of the 3rd International Workshop on Artificial Neural Networks and Intelligent Information Processing. hal-01487150

HAL Id: hal-01487150

https://hal.science/hal-01487150

Submitted on 14 Apr 2017

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.







## DESIGN OF AN AUTOMATED FIXED BED REACTOR USED FOR A CATALYTIC WET OXIDATION PROCESS


Alexis EL KHOURY, Bouchra BEJJANY, Marie DEBACQ, Alain DELACROIX

Laboratoire de Chimie Industrielle - Génie des Procédés, Cnam, case 302, 2 rue Conté, 75003 PARIS (France) ea21@cnam.fr

The identification of highly refractory and non-biodegradable organic pollutants in wastewater, especially coming from the chemical and petrochemical industry, has challenged conventional wastewater treatments such as incineration or biological abatement. Wet Air Oxidation (WAO) is one of the emerging processes suited for the treatment of special aqueous wastes. It is an efficient process by which organic pollutants can be transformed by oxidation under high oxygen or air pressures (20-250 bar) and high temperatures (200-325°C), into carbon dioxide and water. The complexity and delicacy needed for the design of such processes depends on essential automation techniques and equipments necessary to adequately control and monitor the proper system operation. Intelligent sensor modules are used for system control and data acquisition. Real-time monitoring is achieved through the deployment of a SCADA software leading to the development of a user-friendly graphical interface (GUI).







## Graphical User Interface

- > SCADA Distributed Measurement
- > User-friendly Graphical Interface
- > Real-time System Monitoring
- > DDE and Database Connectivity
- > Distributed Alarms and Data Logging
- > Historical Data Trending
- > Easy Networking

The automation techniques and control equipment helped in the design of an automated catalytic fixed bed reactor that fulfills the required temperature and pressure conditions (up to 300°C and 25 bar) usually used for WAO processes. The developed monitoring interface allows the operator to easily manage and control the process parameters.

