



HAL
open science

Using damage reports to assess different versions of a hydrological early warning system

Dimitri Defrance, P Javelle, D Organde, S Ecrepont, Vazken Andréassian,
Patrick Arnaud

► **To cite this version:**

Dimitri Defrance, P Javelle, D Organde, S Ecrepont, Vazken Andréassian, et al.. Using damage reports to assess different versions of a hydrological early warning system . Hydrology and Earth System Sciences Discussions, 2014, 11, pp.4365-4401. 10.5194/hessd-11-4365-2014 . hal-01494238

HAL Id: hal-01494238

<https://hal.science/hal-01494238>

Submitted on 23 Mar 2017

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Using damage reports to assess a hydrological early warning system

D. Defrance et al.

This discussion paper is/has been under review for the journal Hydrology and Earth System Sciences (HESS). Please refer to the corresponding final paper in HESS if available.

Using damage reports to assess different versions of a hydrological early warning system

D. Defrance¹, P. Javelle¹, D. Organde², S. Ecrepont¹, V. Andréassian³, and P. Arnaud¹

¹IRSTEA, UR OHAX, Aix-en-Provence, France

²HYDRIS Hydrologie, Saint Mathieu de Trévières, France

³IRSTEA, UR HBAN, Antony, France

Received: 25 March 2014 – Accepted: 3 April 2014 – Published: 22 April 2014

Correspondence to: P. Javelle (pierre.javelle@irstea.fr)

Published by Copernicus Publications on behalf of the European Geosciences Union.

[Title Page](#)

[Abstract](#)

[Introduction](#)

[Conclusions](#)

[References](#)

[Tables](#)

[Figures](#)

[⏪](#)

[⏩](#)

[◀](#)

[▶](#)

[Back](#)

[Close](#)

[Full Screen / Esc](#)

[Printer-friendly Version](#)

[Interactive Discussion](#)

Abstract

In Europe, flash floods affect mainly the Mediterranean and mountainous regions, even if other regions also occasionally suffer from them. The catchments involved are usually small and ungauged, with short time of concentration. Forecasting this type of event remains difficult using hydrological models, and assessing the models is even more problematic. Typically, assessment is limited to gauged catchments that have relatively different geomorphological characteristics. The aim of this article is to present a method for assessing the models on real ungauged catchments through the use of damage reports and a multi-threshold approach, with assessment criteria that are based on a contingency table of the Critical Success Index type. The main conclusion, as demonstrated by Irstea's "Adaptation d'Information géographique pour l'Alerte en crue" for "Geographic information adaptation for flood warning" (AIGA) flood forecasting system and by the new version of AIGA for high-altitude catchments, is that while assessing hydrological models on gauged catchments is necessary, it is never sufficient and must be supplemented by assessments on ungauged catchments. This underlines the utility of building flood damage databases that are as exhaustive as possible. Such databases can be a valuable addition to more standard, often limited sources of data, especially for mountainous regions.

1 Introduction

1.1 Assessing the efficiency of early warning systems on ungauged catchments

The Aude River in Southern France in 1999 (Gaume et al., 2004), the Tagliamento River in the Italian Alps in 2003 (Borga et al., 2007), and the Nartuby River in Southern France in 2010 (Javelle et al., 2014) are three examples where flash floods caused major damage, although they occurred on small catchments located mostly outside

HESSD

11, 4365–4401, 2014

Using damage reports to assess a hydrological early warning system

D. Defrance et al.

[Title Page](#)

[Abstract](#)

[Introduction](#)

[Conclusions](#)

[References](#)

[Tables](#)

[Figures](#)

[⏪](#)

[⏩](#)

[◀](#)

[▶](#)

[Back](#)

[Close](#)

[Full Screen / Esc](#)

[Printer-friendly Version](#)

[Interactive Discussion](#)



of the national monitoring networks. These floods were characterised by high specific discharge (Borga et al., 2011) and short response time. Unfortunately, it is impossible to monitor all of these streams, due to the high cost of building gauging stations and ensuring their upkeep (estimated at USD 10 000 year⁻¹ (Gourley et al., 2013). And as Silberstein (2006) ironically pointed out, it is equally inconceivable to trust blindly in simulation models.

However, assessing an alert issued for an ungauged catchment poses specific problems, as you have to make up for the lack of continuous discharge data by relying on proxy data, which is obtained from field campaigns, newspaper clippings, etc. The information provided can be in the form of estimates from hydrological flow calculations or just damage data. Below, three examples of proxy data from damage reports adapted for ungauged catchments are presented: post-event reports, historical data, and damage data with quasi-real-time monitoring.

1.1.1 Post-event reports

Post-event reports consist of very comprehensive damage inventories that are made for major events, based on field surveys and hydrological calculations on small catchments that are not monitored by the national networks. These inventories serve for estimations of peak flows for comparison with the model's simulated flows. Borga et al. (2011) give many recommendations on these reports. The main drawback of this assessment technique is that it tests models only on major floods, with no possibility of assessing the model for smaller floods or of estimating false alerts emanating from the model, since only exceptional flood data are available.

1.1.2 Historical data

This technique consists of comparing simulated results from the hydrologic models with the damage identified in databases like the US National Weather Service (USNWS) Storm Events Database or the RTM Service (for Restauration de Terrains de Montagne,

HESSD

11, 4365–4401, 2014

Using damage reports to assess a hydrological early warning system

D. Defrance et al.

Title Page

Abstract

Introduction

Conclusions

References

Tables

Figures

⏪

⏩

◀

▶

Back

Close

Full Screen / Esc

Printer-friendly Version

Interactive Discussion



Using damage reports to assess a hydrological early warning system

D. Defrance et al.

Title Page

Abstract

Introduction

Conclusions

References

Tables

Figures

⏪

⏩

◀

▶

Back

Close

Full Screen / Esc

Printer-friendly Version

Interactive Discussion

or rehabilitation of land in mountain environments) in France. These two databases are fed from recent reports and newspaper clippings to provide information on past and recent floods (location, date, etc.) and on the damage observed. While there is an advantage to working with long time series, the information is not exhaustive enough to estimate false alerts from the hydrological models with any accuracy. No information is provided for cases where no flood occurred, and the reports usually focus on urban areas, where the risks are more concentrated (Gourley et al., 2010). But compared to the preceding technique, this one allows assessing the models based on a larger number and wider range of floods. Taking false alerts into account is still problematic, however, due to the lack of comprehensive data.

1.1.3 Damage data with quasi-real-time monitoring

This technique collects information on natural disaster damage from the historical database and adds information where reports are lacking. For example, a severe storm without damage will be added to the database. In the US, the Severe Hazards Analysis and Verification Experiment (SHAVE) project works along those lines, contacting businesses and individuals after each event to find out its geolocation and evolution over time, to try to rate the hazard as accurately as possible on a scale of ten categories from “No impact” to “Rescue/Fatality/Injury” (Gourley et al., 2010; Ortega et al., 2009).

The work of Calianno et al. (2013) highlights the advantage of gathering information on non-flood events, using a comparison of the NWS and SHAVE databases. The absence of a “no flood” category (in NWS) affects model assessment negatively by keeping false alerts from being taken into account. It is preferable, therefore, to add no-flood reports to the historical data to improve the assessment of hydrological models, for both missed and false alerts.

1.1.4 Summary

Each type of database has positive and negative aspects, then. Despite the advantages of quasi-real-time monitoring, however, this type of database is rarely used. The historical database from the RTM services in France is used for the present article. It was crucial to be able to work over a ten-year period to ensure there would be enough damage reports to assess the flash flood warning system presented in this article.

Damage data is important for assessing the hydrological models, but cannot be used directly. For the models to issue an alert by simulating flows on catchments, the flows must be quantified and ranked according to a catchment-specific alert threshold. This threshold must be in keeping with the observed damage. This is not easy to achieve and requires the use of the various techniques presented below.

1.2 Determining an alert threshold based on damage reports

When there is no available a priori information about floods, a theoretical alert threshold must be set. One recommendation is to set the threshold at a two-year return period that corresponds to the beginning of stream overflow (Carpenter et al., 1999), although this threshold does not appear to be well-adapted to small catchments (Reed et al., 2002). In reality, each site is flooded more or less often according to its degree of exposure. Ideally, the thresholds should be determined on a large scale, with integration of the exposure risk for human infrastructures (Naulin et al., 2013). Including damage reports can contribute significantly to the determination of flood alert thresholds.

Damage databases are a source of information about the flood risk exposure at the local level and at a large number of sites. However, the link between damage and flood is not clear-cut, for two reasons: (1) the damage is only reported when there are human stakes involved, and (2) floods of the same amplitude can cause different types of damage. (For example, streambank collapse can be caused by cumulative damage from a series of floods, but even if the last flood is the one which causes the

Using damage reports to assess a hydrological early warning system

D. Defrance et al.

[Title Page](#)

[Abstract](#)

[Introduction](#)

[Conclusions](#)

[References](#)

[Tables](#)

[Figures](#)

[⏪](#)

[⏩](#)

[◀](#)

[▶](#)

[Back](#)

[Close](#)

[Full Screen / Esc](#)

[Printer-friendly Version](#)

[Interactive Discussion](#)



collapse, that flood is not necessarily the most severe one.) In spite of these limits, it is actually preferable to link damage reports with the model's alert threshold as much as possible, rather than to use the theoretical two-year threshold recommended by Carpenter et al. (1999).

In the literature, the research results from Versini et al. (2010) and Naulin et al. (2013) on road outages in France's Gard region (ANR Prediflood project) are interesting, in that ground surveys are used to calibrate thresholds for susceptibility, corresponding to flood probability for several return periods. These two studies show that taking the vulnerability of the location into consideration is crucial in defining accurate alert thresholds.

1.3 Scope of the paper

The scope of the paper is to develop a technique to assess hydrological models for actual ungauged catchments, using a damage database. This type of technique is rarely seen in the literature, where assessment is usually limited to flow data from gauged catchments that are much larger than those subject to flash floods.

After defining the assessment method, the article compares the AIGA method ("Adaptation d'Information géographique pour l'Alerte en crue" for "Geographic information adaptation for flood warning") (Javelle et al., 2010) developed for flash floods around the Mediterranean Basin with a new version developed specially for flash floods in mountainous regions.

Section 2 presents the catchment sample groups, the first consisting of gauged catchments and the second, of catchments where only damage reports are available, and then describes both the AIGA method and its new version. Section 3 describe the methodology developed to assess and compare the models on pseudo-ungauged catchments (flows) and real ungauged catchments (damage). The results obtained with both datasets are shown in Sect. 4 and discussed in Sect. 5. The conclusion outlines some avenues for improvement.

HESSD

11, 4365–4401, 2014

Using damage reports to assess a hydrological early warning system

D. Defrance et al.

Title Page

Abstract

Introduction

Conclusions

References

Tables

Figures

⏪

⏩

◀

▶

Back

Close

Full Screen / Esc

Printer-friendly Version

Interactive Discussion

catchment. Therefore, there can be more than one event on the same date, but the model manages each separately. The same process for the second catchment sample group (presented in the next section) was used, obtaining 26 000 other events.

2.2 The RTM damage reports dataset: a unique opportunity to explore real ungauged catchments

A second catchment sample group was assembled from catchments for which only damage reports are available. The Restauration des Terrains en Montagne (RTM) Service collects the reports in order to inventory past and current natural disasters. This database can be found at the website <http://rtm-onf.ifn.fr>. For clarity, these catchments will hereinafter be referred to as “RTM catchments”.

Each event was recorded, located (a site can be a streambank, ravine, section of a river, etc.), identified with an individual number and assigned a specific natural risk. The information about the event was collected from various complementary sources: the export report from an RTM agent, press clippings and personal accounts.

Because the sites recorded in the database were not always comparable to catchments, a catchment should be associated to each site before being able to use the data for hydrological purposes. In the end, only 123 catchments were chosen (Ecrepont, 2012). Over a period of ten years, 179 damage reports were reported on all of these catchments, or 1.45 per catchment. These RTM catchments have different characteristics than the ones in the HYDRO sample group (Table 1). Their catchment area is smaller, with a comparable interval [5887 km²] but a median of 22 km² (compared to 110 km²), and a 27 % median for the snow fraction, more than three times higher than the one obtained on HYDRO catchments. Slopes on RTM catchments are also steeper: 0.02 minimum, 0.26 maximum, and a 0.09 median, or twice as high as for HYDRO catchments (0.17 maximum and 0.04 median). So RTM catchment characteristics are similar to those of the catchments subject to flash floods, and described in the Hydrate project (Marchi et al., 2010; Borga et al., 2011). The

Using damage reports to assess a hydrological early warning system

D. Defrance et al.

[Title Page](#)

[Abstract](#)

[Introduction](#)

[Conclusions](#)

[References](#)

[Tables](#)

[Figures](#)

[⏪](#)

[⏩](#)

[◀](#)

[▶](#)

[Back](#)

[Close](#)

[Full Screen / Esc](#)

[Printer-friendly Version](#)

[Interactive Discussion](#)

reservoir that functions similarly to the one in GR4J. However, unlike with a daily time step, this reservoir does not empty out during an event: evapotranspiration and drainage are equal to 0 mm h^{-1} . The second reservoir (routing) transforms the portion of non-infiltrated precipitation into flow just as for the flow portion obtained by the GR4J routing reservoir. For more information, refer to the full description in Javelle et al. (2010).

2.3.2 The original AIGA method

The original AIGA method is based on the two conceptual hydrological models. Coupling the two models is simple, with only the hourly model's production reservoir being initialised by the fill rate for the GR4J's production reservoir. This fill rate, which takes daily precipitation (P) and evapotranspiration (E_0) into account, is corrected before being inserted into the GRD model, using a regional formula to remove bias for all HYDRO and RTM catchments (Eq. 1, Javelle et al., 2010). The fill value for the GRD routing reservoir is identical for all events and all catchments: 30 % of initial fill, leading to zero flow. Neither model takes snow into account.

$$(S/A)_{\text{GRD}(\text{init})} = a(S/A)_{\text{GR4J}(j-1)} + b(S/A)_{\text{stat}} + c \quad (\text{Javelle et al., 2010}) \quad (1)$$

with $a = 0.52$, $b = 0.38$, and $c = -0.17$: statistical parameter with a pixel value of 0–1

The parameters for both models are identical for all catchments in both sample groups. The values for production reservoir size in both the GRD and the GR4J are about 200 mm, and the routing reservoir size value in the GRD is 50 mm for the entire study area.

2.3.3 The new version of AIGA

Like the original method, the new version of AIGA relies on two global conceptual models: the continuous daily GR4J model, and the hourly event-based GRD model for flood simulation which operates exactly like the original method. Figure 2 shows the

Using damage reports to assess a hydrological early warning system

D. Defrance et al.

Title Page

Abstract

Introduction

Conclusions

References

Tables

Figures

⏪

⏩

◀

▶

Back

Close

Full Screen / Esc

Printer-friendly Version

Interactive Discussion



coupling of the two models, with initialisation of the GRD production reservoir (next paragraph) and initialisation of the routing reservoir fill process as a function of the daily flow on the day before the event simulated by GR4J.

For the initialisation of the GRD production reservoir, a bias removal rule with a parameter “ a ” (Eq. 2) at the catchment scale (global model) is used to link the GR4J fill rate to the initial GRD rate:

$$(S/A)_{\text{GRD}(\text{init})} = a(S/A)_{\text{GR4J}(j-1)} \quad (2)$$

with $(S/A)_{\text{GRD}(\text{init})}$: for the initial filling of the GRD hourly module’s production reservoir, $(S/A)_{\text{GR4J}(j-1)}$: for the filling of the GR4J daily module’s production reservoir on the day before the event, and a : a parameter to be calibrated in order to link the fill rates for the GRD and GR4J modules.

So there are four parameters for GR4J (“ A_{cont} ”, “ B_{cont} ”, “ C ”, “ D ”) and two for the event-based GRD (“ a ” and “ B_{hor} ”), or a total of six parameters to be regionalised and which, unlike the original method, are not identical for all catchments. Based on the research of Wasson et al. (2001), the study area is broken down into four relatively homogeneous hydro-ecoregions (HER) to facilitate the regionalisation of both models. For the 1997–2006 period, the six parameters are calibrated on the 118 HYDRO catchments and then transferred to those HYDRO catchments that are considered to be ungauged, and to the 123 RTM catchments. The transfer method consists of taking the median values for the parameters of the three closest neighbour catchments in the same sub-region, obtained using the Euclidean distance between centroids. This technique makes it possible to obtain the best results for Irstea’s GR models (Oudin et al., 2008).

In the new version of AIGA for studies on mountainous catchments, precipitation is fine-tuned to factor in snowfall. The snowfall portion (%S) of hourly and daily precipitation provides information about the quantity of snow to be subtracted from each rainfall depth estimated by the precipitation (P) radar, in order to keep only the liquid portion of total precipitation data (P). At a daily time step, snowmelt is added to this liquid portion (P) using a regionalised snowfall/snowmelt degree-day module

Using damage reports to assess a hydrological early warning system

D. Defrance et al.

[Title Page](#)

[Abstract](#)

[Introduction](#)

[Conclusions](#)

[References](#)

[Tables](#)

[Figures](#)

[⏪](#)

[⏩](#)

[◀](#)

[▶](#)

[Back](#)

[Close](#)

[Full Screen / Esc](#)

[Printer-friendly Version](#)

[Interactive Discussion](#)



Using damage reports to assess a hydrological early warning system

D. Defrance et al.

Title Page

Abstract

Introduction

Conclusions

References

Tables

Figures

⏪

⏩

◀

▶

Back

Close

Full Screen / Esc

Printer-friendly Version

Interactive Discussion

simulated alerts (one correct in green and one false in yellow). In Fig. 3b, the second threshold ($N = 2$) implies that the model has to simulate 4 alerts for the 2 reports. Consequently, the threshold is lowered to try to increase the number of correct alerts, but as a result, the number of false alerts also increases. So in this case, there is still one correct alert and one missed, and also 3 false alerts, or two more than with the first threshold. At the third threshold ($N = 3$ in Fig. 3c), no alerts are missed (2 correct alerts), but the number of false alerts rises to 4. At the $N = 4$ threshold (Fig. 3d), only the number of false alerts rises to 6.

To summarise, the threshold is gradually lowered, which increases the number of correct alerts and reduces the number of missed alerts; however, at the same time, the number of false alerts increases. So for each threshold tested (the N value), it is possible to associate a number of correct, missed and false alerts for all catchments as a whole, by adding up each category.

2. Plotting the POD/SR curve

For each threshold tested, the correct alerts for all catchments are added up to obtain a total number of correct alerts for the entire catchment sample group. The same procedure is performed for missed and false alerts, and the POD and SR contingency criteria are calculated for each threshold tested (N times). Using all the POD and SR values, the POD/SR graph (Fig. 4) is plotted and the model can be assessed for several thresholds at a time. Let's remember that to obtain an SR value equal to 1 (no false alerts), all reports would have had to correspond to the highest flows for all catchments. Inversely, to obtain a POD equal to 1, all alerts would have to be correct and the threshold would therefore be very low in some cases.

To compare two models, the POD/SR curves for each are plotted on the same graph to enable a comparative analysis of the results and to identify the better model, even when the performance is similar for both. The test is independent of the chosen alert threshold, because the POD and SR are simultaneously considered at a number N of

different thresholds. In the absolute, the best results would be represented by curves close to a value of (1.1), in the upper right corner. The ideal case would be a POD always equal to 1 for all thresholds, with an SR varying between 0 and 1. To distinguish between two close results, the area underneath the curve can be calculated, knowing that its maximum value would be close to 1.

4 Results

4.1 Results on pseudo-ungauged catchments

First, to demonstrate that adapting the new AIGA method to mountainous regions was necessary and beneficial, the performance of the hourly event-based models (for both the original and the new AIGA method) was analysed for all 118 HYDRO catchments using a Nash–Sutcliffe criterion limited to a range from -100 to 100 (Mathevet et al., 2006). Working with the flood events to obtain a criterion per model and per catchment, the events were pieced together to get a continuous time series (Nash pseudo-continuous, NPC). The ten years of data were used for validation, since all of the models were regionalised. The catchments were considered as ungauged, and the observed flows served to assess and compare the two GRD models (original and new version).

As shown in Fig. 5a, the overall results increased by an average 35 points in terms of Nash–Sutcliffe. The median for the results (thick black line) rose from 0 to nearly 30 points. Performance improved (Fig. 5b) on 80% of the catchments (red dots). There was no change in performance between the two versions on only 10% of the catchments (blue dots), and the remaining 10% showed worse performance (green dots). The catchments in these last two cases were scattered all over the study area, which attests to the problems that can crop up with regionalisation.

On the relatively large catchments from the HYDRO database, the new version performs better, thanks to better initialisation (production and routing reservoirs from

Using damage reports to assess a hydrological early warning system

D. Defrance et al.

Title Page

Abstract

Introduction

Conclusions

References

Tables

Figures

⏪

⏩

◀

▶

Back

Close

Full Screen / Esc

Printer-friendly Version

Interactive Discussion

limited effect, since the curves are similar for the Southern Pre-Alps. The new version's performance is worse in the Mediterranean HER, unlike the results for the HYDRO catchment study.

The improvements introduced by the new version are noticeable on the RTM catchments, but only on the high-altitude catchments (Inner Alps). However, performance for both versions (original and new) in this region is the weakest, highlighting various limits that are inherent to the assessment, to the input data, and also to the calibration and regionalisation method for the hydrological models.

5 Discussion

The above results showed improvements in the new version of the AIGA method compared to the original version. The performance remains fairly modest, however, with very low success rates (SR). In the following two paragraphs, the apparent reasons for these weak results are discussed:

- limits linked to the assessment method and to the damage data,
- limits linked to the models and to the rainfall data.

5.1 Limits linked to the use of the RTM database

The POD/SR assessment method is based on the damage reports in the RTM database. The method characterises the relative match between the alerts issued and the damage actually observed, and therefore relies on the following assumptions:

- the existence of a link between flow and the damage suffered: two similar flows cause the same damage, and so both are recorded in the database. This strong assumption implies that there are no effects of “memory” or accumulation and that all events that result in damage are independent. Also, the damage is really

HESSD

11, 4365–4401, 2014

Using damage reports to assess a hydrological early warning system

D. Defrance et al.

Title Page

Abstract

Introduction

Conclusions

References

Tables

Figures

⏪

⏩

◀

▶

Back

Close

Full Screen / Esc

Printer-friendly Version

Interactive Discussion

caused by flood flows and not by debris flow, which causes greater damage by different processes;

- stationarity: over the ten-year period, we infer that there has been no change on the catchment, e.g. in terms of land use that would alter the type of damage caused during the floods. The flow that triggers the damage does not vary over time;
- the exhaustiveness of the database: over the ten-year period, we infer that the reports are obtained for all catchments and for all flood events in a like manner. For example, each field agent has the same understanding of what constitutes damage.

To verify these three assumptions, four catchments that were in both of the sample groups (HYDRO and RTM) were studied, giving access to both observed flow data and damage reports. These four catchments were the only ones common to both sample groups. Comparing observed flows and RTM reports enabled us to validate or invalidate the working assumptions. In the following examples, the fact of presenting the relative match between the damage and *the observed, unmodelled flows* enables us to temporarily exclude any model-related problems. If one of the assumptions is not validated on one of the four catchments, it could also be the case on the other RTM catchments. However, it would not be possible to determine so categorically.

In Fig. 7, the case of the Durance River (Fig. 7a) is ideal: the highest observed flow coincides with the only RTM report, so the highest threshold gives the best result and each time the threshold is lowered, performance declines. For the Mourachonne River (Fig. 7b), there are two reports, and one of the descriptions (green dot) does match the highest observed flow. However, two other observed flows of similar intensity (orange dots), gave rise to no reports, even though a lower observed flow coincides with the 22/11 report (red dot).

Using damage reports to assess a hydrological early warning system

D. Defrance et al.

Title Page

Abstract

Introduction

Conclusions

References

Tables

Figures

⏪

⏩

◀

▶

Back

Close

Full Screen / Esc

Printer-friendly Version

Interactive Discussion



These two examples helped demonstrate that the assumptions on the assessment method were not always borne out. Nevertheless, it is not possible to determine which of the three assumptions is false.

Despite the problem raised, the method has its merits, which lie in its potential for comparing warning models even when flowmeter measurements are absent, which is often the case on catchments subject to flash floods. Performance should be assessed in a relative way from one model to another, and not in the absolute.

5.2 Limits linked to the models and to rainfall data

For limits that are linked to the models and rainfall data used, only the performance of the new AIGA version was analysed to characterise the shortcomings.

In Fig. 9, the results are represented as a function of (1) the two physical characteristics, surface and slope; and (2) the season during which the events occur. For the two physical descriptors, the sample group is divided in two, one comprising the 62 RTM catchments with the lowest values and the other comprising the other 61 catchments with the highest values. In this way, it is possible to determine on which type of catchment the model works the best. For surface (Fig. 9a), the largest catchments (more than 21.8 km²) are shown in orange and the smaller ones in black. For slope (Fig. 9b), the catchments with gentler slopes (< 0.09) are shown in black, and those with the steepest slopes, in orange. For season (Fig. 9c), the results of the new AIGA version are shown in black for summer and in orange for autumn.

The results show that the smallest catchments register the lowest performance, with lower SR and POD values for all ten thresholds, with a roughly 0.1 point difference with respect to the large catchments. These small catchments are often characterised by steep slopes, because they are located mostly in the mountains (Inner Alps). In consequence, the very steep catchments are also the ones with the lowest SR values, at a maximum 0.2. The POD and SR values for catchments with gentler slopes are more acceptable, at a maximum 0.4 for each one of them. The performance is better

Using damage reports to assess a hydrological early warning system

D. Defrance et al.

Title Page

Abstract

Introduction

Conclusions

References

Tables

Figures

⏪

⏩

◀

▶

Back

Close

Full Screen / Esc

Printer-friendly Version

Interactive Discussion

in autumn than in summer, when the SR values are particularly low (< 0.15). So the model is less adapted to small, steep catchments subject to summer flood events.

To explain these differences among catchments, three hypotheses can be proposed:

Hypothesis 1

5 The lower performances are observed on catchments for which there is the least rainfall data. In Fig. 9c, summer is when there appears to be a problem with accurate rainfall data. During this season, small catchments located (mostly) in the mountains of the Inner Alps are often hit with very local storms. In the database, these account for 57 RTM reports out of 179, or 32 %. Estimating the cumulated rainfall for these storms is
10 very difficult. It is often underestimated, either because the storms occur in areas not covered by the raingauge network, which is sparser in mountainous areas (Gottardi, 2009), or because they are so intense that they cause radar signal black-out (par exemple: Berne and Krajewski, 2013; Diss et al., 2009). To illustrate this, the 27 July 2003 rainfall event is represented in Fig. 8.

15 The event is characterised by 50 mm of maximum cumulated rainfall over a two-day period. If the analysis is focused on the three catchments reported on by the RTM (red dots), the cumulated rainfall ranges between 15 and 25 mm, which is low for causing a flash flood. The RTM services did nevertheless find damage. By using a very low threshold, corresponding to 27 times the number of reports for each catchment ($N =$
20 27), i.e. lower than the thresholds used for the POD/SR curves (Eq. 3), no alert is issued in the location where damage is reported, constituting a missed alert (in red), and a false alert (modelled and not matching an RTM report) appears. This problem of modelled alerts is probably linked to an underestimate of cumulated rainfall.

25 The quality of rainfall depth data in mountainous regions, therefore, plays a crucial role in hydrological model performance, and can partially explain the poor results obtained on high-altitude catchments where little rainfall data is available (radar measurement problems or absence of raingauges to recalibrate radar-based rainfall).

Using damage reports to assess a hydrological early warning system

D. Defrance et al.

[Title Page](#)

[Abstract](#)

[Introduction](#)

[Conclusions](#)

[References](#)

[Tables](#)

[Figures](#)

[⏪](#)

[⏩](#)

[◀](#)

[▶](#)

[Back](#)

[Close](#)

[Full Screen / Esc](#)

[Printer-friendly Version](#)

[Interactive Discussion](#)



Hypothesis 2

This hypothesis concerns certain catchment characteristics. In Fig. 9a and b, analysing performance as a function of slope reveals differences between large, flatter catchments and small, steeper ones. These results can be explained by other kinds of phenomena besides flash floods, because small mountain catchments are equally subject to floods and debris flows, where sediment can account for more than 50% of the volume of the water runoff (Bertrand et al., 2013). In that case, it no longer constitutes a flash flood and the catchment processes are no longer the same. Because they are not taken into account in the models, such phenomena have a negative impact on the models, and to add a complementary module to factor in debris flows would be necessary, especially at an hourly time step.

Hypothesis 3

The size difference between the HYDRO catchments used to develop the new AIGA method and the RTM catchments, where the model was assessed, appears to influence the way the model works (Fig. 9a). The new AIGA method was regionalised based on gauged catchments. A “neighbourhood” technique was used within each HER region to transfer parameters from donor catchments to a target catchment. There was no transformation for catchment size, although the physical characteristics of the HYDRO catchments were averaged with respect to the small RTM catchments, which have more specific and more variable physical characteristics. Therefore, the hydrological processes are different (flood dynamics). In this situation, parameter transfer between catchments becomes problematic and the neighbourhood technique can have an adverse effect on the results.

HESSD

11, 4365–4401, 2014

Using damage reports to assess a hydrological early warning system

D. Defrance et al.

[Title Page](#)

[Abstract](#)

[Introduction](#)

[Conclusions](#)

[References](#)

[Tables](#)

[Figures](#)

[⏪](#)

[⏩](#)

[◀](#)

[▶](#)

[Back](#)

[Close](#)

[Full Screen / Esc](#)

[Printer-friendly Version](#)

[Interactive Discussion](#)

6 Conclusion and future works

The method presented in this article enables the use of historical damage databases to compare hydrological models on ungauged catchments. The standard assessment method sticks to the use of catchments that are gauged but considered as ungauged, which poses a problem of scale. In some cases, the assessment concerns actual ungauged catchments, but it restricts itself to extreme events, in effect omitting an assessment of false alerts. To put damage reports to best use for comparing models, a POD/SR curve was developed to factor in the rate of correct and false alerts, and to eliminate the need to select an alert threshold.

As for the results, the improvements to the original AIGA method, e.g. taking snowfall into account, are visible on both gauged catchments and actual ungauged catchments (RTM). However there are still problems linked to insufficient knowledge on rainfall and to lowering the scale. For this reason, dual assessment of the hydrological models is important: while an assessment on gauged catchments is necessary, it is never sufficient for qualifying an early flash flood warning system on ungauged catchments.

To improve the hydrological models, studies are ongoing to try to calibrate the models on the ungauged catchments regionally or locally, using damage reports or limited streamflow data (Perrin et al., 2007; Rojas-Serna et al., 2006). Choosing to use the POD/SR curves directly as a criterion can also give better results. In this way, we can eliminate the need for calibration on large catchments and avoid problems related to scale lowering.

The lack of exhaustive databases remains a problem that can be solved only by improving field reports and setting strict standards for them. Also, to provide assessments that are more accurate than just a threshold that is exceeded, temporal data should be integrated into the databases to assess forecasting, as suggested by Calianno et al. (2013) and Ruin et al. (2008). For data gathering, Gourley et al. recommend more systematic reporting of both damage and the absence of damage (the SHAVE database) (2010) and assembling datasets as in

HESSD

11, 4365–4401, 2014

Using damage reports to assess a hydrological early warning system

D. Defrance et al.

Title Page

Abstract

Introduction

Conclusions

References

Tables

Figures

⏪

⏩

◀

▶

Back

Close

Full Screen / Esc

Printer-friendly Version

Interactive Discussion

the FLASH project (<http://www.nssl.noaa.gov/projects/flash/database.php>) in the US, which groups the SHAVE database, NWS storm reports and USGS streamflow data (2013). Once this new generation of databases is created, it will be possible to use larger sample groups to improve early warning methods for small ungauged catchments.

Acknowledgements. The authors and their institute want to thank the European Union, the Provence–Alpes–Côte d’Azur Region and the French Ministry of Ecology for co-financing the Rhythme (Risques Hydrométéorologiques en Territoires de Montagnes et Méditerranéens/Hydrometeorological Risks in the Mediterranean and Mountainous Regions) project. The authors also want to thank the many people involved in the project.

References

- Andréassian, V., Perrin, C., Berthet, L., Le Moine, N., Lerat, J., Loumagne, C., Oudin, L., Mathevet, T., Ramos, M.-H., and Valéry, A.: HESS Opinions “Crash tests for a standardized evaluation of hydrological models”, *Hydrol. Earth Syst. Sci.*, 13, 1757–1764, doi:10.5194/hess-13-1757-2009, 2009.
- Berne, A. and Krajewski, W. F.: Radar for hydrology: unfulfilled promise or unrecognized potential?, *Adv. Water Resour.*, 51, 357–366, 2013.
- Bertrand, M., Liébault, F., and Piégay, H.: Debris-flow susceptibility of upland catchments, *Nat. Hazards*, 67, 1–15, doi:10.1007/s11069-013-0575-4, 2013.
- Borga, M., Boscolo, P., Zanon, F., and Sangati, M.: Hydrometeorological analysis of the 29 August 2003 flash flood in the Eastern Italian Alps, *J. Hydrometeorol.*, 8, 1049–1067, doi:10.1175/jhm593.1, 2007.
- Borga, M., Anagnostou, E. N., Blöschl, G., and Creutin, J. D.: Flash flood forecasting, warning and risk management: the HYDRATE project, *Environ. Sci. Policy*, 14, 834–844, 2011.
- Calianno, M., Ruin, I., and Gourley, J. J.: Supplementing flash flood reports with impact classifications, *J. Hydrol.*, 477, 1–16, 2013.
- Carpenter, T. M., Sperflage, J. A., Georgakakos, K. P., Sweeney, T., and Fread, D. L.: National threshold runoff estimation utilizing GIS in support of operational flash flood warning systems, *J. Hydrol.*, 224, 21–44, 1999.

Using damage reports to assess a hydrological early warning system

D. Defrance et al.

Title Page

Abstract

Introduction

Conclusions

References

Tables

Figures

⏪

⏩

◀

▶

Back

Close

Full Screen / Esc

Printer-friendly Version

Interactive Discussion



Using damage reports to assess a hydrological early warning system

D. Defrance et al.

[Title Page](#)

[Abstract](#)

[Introduction](#)

[Conclusions](#)

[References](#)

[Tables](#)

[Figures](#)

[⏪](#)

[⏩](#)

[◀](#)

[▶](#)

[Back](#)

[Close](#)

[Full Screen / Esc](#)

[Printer-friendly Version](#)

[Interactive Discussion](#)

Basin Experiments for Hydrological Model Parameterization: Results of the Model Parameter Experiment MOPEX, IAHS Publ. 307, AISH, Wallingford, 211–219, 2006.

Naulin, J. P., Payrastre, O., and Gaume, E.: Spatially distributed flood forecasting in flash flood prone areas: application to road network supervision in Southern France, *J. Hydrol.*, 486, 88–99, 2013.

Ortega, K. L., Smith, T. M., Manross, K. L., Kolodziej, A. G., Scharfenberg, K. A., Witt, A., and Gourley, J. J.: The severe hazards analysis and verification experiment, *B. Am. Meteorol. Soc.*, 90, 1519–1530, doi:10.1175/2009bams2815.1, 2009.

Oudin, L., Hervieu, F., Michel, C., Perrin, C., Andréassian, V., Anctil, F., and Loumagne, C.: Which potential evapotranspiration input for a lumped rainfall–runoff model?: Part 2 – Towards a simple and efficient potential evapotranspiration model for rainfall–runoff modelling, *J. Hydrol.*, 303, 290–306, doi:10.1016/j.jhydrol.2004.08.026, 2005.

Oudin, L., Andreassian, V., Perrin, C., Michel, C., and Le Moine, N.: Spatial proximity, physical similarity, regression and ungaged catchments: a comparison of regionalization approaches based on 913 French catchments, *Water Resour. Res.*, 44, W03413, doi:10.1029/2007WR006240, 2008.

Perrin, C., Michel, C., and Andréassian, V.: Improvement of a parsimonious model for streamflow simulation, *J. Hydrol.*, 279, 275–289, doi:10.1016/S0022-1694(03)00225-7, 2003.

Perrin, C., Oudin, L., Andreassian, V., Rojas-Serna, C., Michel, C., and Mathevet, T.: Impact of limited streamflow data on the efficiency and the parameters of rainfall–runoff models, *Hydrolog. Sci. J.*, 52, 131–151, 2007.

Reed, S., Johnson, D., and Sweeney, T.: Application and national geographic information system database to support two-year flood and threshold runoff estimates, *J. Hydrol. Eng.*, 7, 209–219, 2002.

Rojas-Serna, C., Michel, C., Perrin, C., and Andréassian, V.: Ungaged Catchments: How Make the Most of a Few Streamflow Measurements?, *Large Sample Basin Experiments for Hydrological Model Parameterization: Results of the Model Parameter Experiment MOPEX*, IAHS Publ. 307, AISH, Wallingford, 230–236, 2006.

Ruin, I., Creutin, J.-D., Anquetin, S., and Lutoff, C.: Human exposure to flash floods – relation between flood parameters and human vulnerability during a storm of September 2002 in Southern France, *J. Hydrol.*, 361, 199–213, doi:10.1016/j.jhydrol.2008.07.044, 2008.

HESSD

11, 4365–4401, 2014

Using damage reports to assess a hydrological early warning system

D. Defrance et al.

[Title Page](#)

[Abstract](#)

[Introduction](#)

[Conclusions](#)

[References](#)

[Tables](#)

[Figures](#)

[⏪](#)

[⏩](#)

[◀](#)

[▶](#)

[Back](#)

[Close](#)

[Full Screen / Esc](#)

[Printer-friendly Version](#)

[Interactive Discussion](#)



- Schaefer, J. T.: The critical success index as an indicator of warning skill, *Weather Forecast.*, 5, 570–575, 1990.
- Silberstein, R. P.: Hydrological models are so good, do we still need data?, *Environ. Modell. Softw.*, 21, 1340–1352, doi:10.1016/j.envsoft.2005.04.019, 2006.
- 5 Swets, J. A.: The relative operating characteristic in psychology, *Science*, 182, 990–1000, 1973.
- Tabary, P., Dupuy, P., L'Henaff, G., Gueguen, C., Moulin, L., Laurantin, O., and Merlier, C.: A 10 year (1997–2006) reanalysis of quantitative precipitation estimation over France: methodology and first results, in: *International Symposium on “Weather Radar and Hydrology”*, Exeter, 18–21 April 2011, 672, 2012.
- 10 Versini, P.-A., Gaume, E., and Andrieu, H.: Application of a distributed hydrological model to the design of a road inundation warning system for flash flood prone areas, *Nat. Hazards Earth Syst. Sci.*, 10, 805–817, doi:10.5194/nhess-10-805-2010, 2010.
- Vidal, J. P., Martin, E., Franchistéguy, L., Baillon, M., and Soubeyroux, J. M.: A 50-year high-resolution atmospheric reanalysis over France with the Safran system, *Int. J. Climatol.*, 30, 1627–1644, 2010.
- 15 Wasson, J. G., Chandesris, A., Pella, H., and Souchon, Y.: Définition des hydroécocorégions françaises, *Méthodologie de détermination des conditions de référence au sens de la Directive Cadre pour la gestion des eaux. rapport de phase 1*, Lyon, IRSTEA, 68 p., 2001.

HESSD

11, 4365–4401, 2014

Using damage reports to assess a hydrological early warning system

D. Defrance et al.

Table 1. Characteristics of two catchment sample groups.

Sample group	Surface (km ²)	Snow (% annual precipitation)	Slope
HYDRO	[8.897], median: 110	[0.59], median: 8	[0.003, 0.17], median: 0.04
RTM	[5.887], median: 22	[0.77], median: 27	[0.02, 0.26], median: 0.09

[Title Page](#)[Abstract](#)[Introduction](#)[Conclusions](#)[References](#)[Tables](#)[Figures](#)[⏪](#)[⏩](#)[◀](#)[▶](#)[Back](#)[Close](#)[Full Screen / Esc](#)[Printer-friendly Version](#)[Interactive Discussion](#)

Using damage reports to assess a hydrological early warning system

D. Defrance et al.

Table 2. Contingency statistics and POD/SR/CSI criteria.

	Alert observed	No alert observed	Contingency statistics
Alert calculated	CA	FA	$POD = \frac{\sum CA}{\sum CA + \sum MA}$
No alert calculated	MA		$SR = \frac{\sum CA}{\sum CA + \sum FA}$

$\sum CA$: the number of correct alerts for all catchments (both modelled and observed);

$\sum MA$: the number of missed alerts for all catchments (both observed and unmodelled);

$\sum FA$: the number of false alerts for all catchments (both modelled and unobserved).

[Title Page](#)
[Abstract](#)
[Introduction](#)
[Conclusions](#)
[References](#)
[Tables](#)
[Figures](#)
[Back](#)
[Close](#)
[Full Screen / Esc](#)
[Printer-friendly Version](#)
[Interactive Discussion](#)

HESSD

11, 4365–4401, 2014

Using damage reports to assess a hydrological early warning system

D. Defrance et al.




Fig. 1. Locations of the 118 HYDRO catchments (black) and the 123 RTM catchments (red).

Title Page

Abstract

Introduction

Conclusions

References

Tables

Figures

⏪

⏩

◀

▶

Back

Close

Full Screen / Esc

Printer-friendly Version

Interactive Discussion




Fig. 2. The coupling between the daily model (GR4J) and the hourly model (GRD), with the 2 initialisation rules (production and routing, in red) and the parameters to be calibrated (4 GR4J parameters in dark red, and 2 GRD parameters in green).

Title Page	
Abstract	Introduction
Conclusions	References
Tables	Figures
⏪	⏩
⏴	⏵
Back	Close
Full Screen / Esc	
Printer-friendly Version	
Interactive Discussion	

Using damage reports to assess a hydrological early warning system

D. Defrance et al.




Fig. 3. The change in number of alerts (correct missed, and false) as a function of the given threshold. The values for N vary from 1 to 4.

[Title Page](#)
[Abstract](#) [Introduction](#)
[Conclusions](#) [References](#)
[Tables](#) [Figures](#)
⏪ ⏩
⏴ ⏵
[Back](#) [Close](#)
[Full Screen / Esc](#)
[Printer-friendly Version](#)
[Interactive Discussion](#)



Using damage reports to assess a hydrological early warning system

D. Defrance et al.




Fig. 4. Performance of a model estimated by the POD as a function of SR. The dots correspond to the contingency criteria for N thresholds.

[Title Page](#)[Abstract](#)[Introduction](#)[Conclusions](#)[References](#)[Tables](#)[Figures](#)[⏪](#)[⏩](#)[◀](#)[▶](#)[Back](#)[Close](#)[Full Screen / Esc](#)[Printer-friendly Version](#)[Interactive Discussion](#)

Using damage reports to assess a hydrological early warning system

D. Defrance et al.




Fig. 5. Comparison of the original and new versions of the AIGA method in terms of Nash pseudo-continuous (NPC). **(A)** Box-and-whisker plot with the original version on the left and the new version on the right. The 1st and 3rd quartiles are inside the box and the 1st and 9th decile at whisker ends. **(B)** The range between the two versions: red dots show an improvement with the new version, green dots, a deterioration with the new version, and blue dots, no difference (under 5 points of NPC).

[Title Page](#)

[Abstract](#) | [Introduction](#)

[Conclusions](#) | [References](#)

[Tables](#) | [Figures](#)

[⏪](#) | [⏩](#)

[◀](#) | [▶](#)


[Back](#) | [Close](#)

[Full Screen / Esc](#)


[Printer-friendly Version](#)

[Interactive Discussion](#)






A)



B)



C)

Fig. 6. Comparison of the performance of both AIGA methods using the POD/SR graph, with the original version in black and the new version in orange, for each hydro-ecoregion: **(A)** Inner Alps; **(B)** Mediterranean; **(C)** Southern Pre-Alps.

Title Page

Abstract Introduction

Conclusions References

Tables Figures

⏪ ⏩

◀ ▶

Back Close

Full Screen / Esc

Printer-friendly Version

Interactive Discussion



Using damage reports to assess a hydrological early warning system

D. Defrance et al.




Fig. 8. Cumulated rainfall during the 27 July 2003 event in the French Alpes-de-Haute-Provence, Hautes-Alpes and Alpes-Maritimes departments. A comparison of the alerts from the new AIGA method in relation to the three RTM damage reports, with a very low triggering threshold ($N = 27$).

[Title Page](#)[Abstract](#)[Introduction](#)[Conclusions](#)[References](#)[Tables](#)[Figures](#)[⏪](#)[⏩](#)[◀](#)[▶](#)[Back](#)[Close](#)[Full Screen / Esc](#)[Printer-friendly Version](#)[Interactive Discussion](#)

Using damage reports to assess a hydrological early warning system

D. Defrance et al.




Fig. 9. Demonstration of the new AIGA method's problems linked to catchment characteristics and seasonal rainfall data. **(A)** Surface: performance comparison between large (orange) and small (black) catchments. **(B)** Relief ratio (slope): performance comparison between steep (orange) and “flat” (black) catchments. **(C)** Seasons: performance comparison between autumn (orange) and summer (black).

[Title Page](#)
[Abstract](#)
[Introduction](#)
[Conclusions](#)
[References](#)
[Tables](#)
[Figures](#)
[⏪](#)
[⏩](#)
[◀](#)
[▶](#)
[Back](#)
[Close](#)
[Full Screen / Esc](#)
[Printer-friendly Version](#)
[Interactive Discussion](#)