

WIM data for investigation of truck weights and dimensions

Livia Tovar, Frédéric Domprobst, Franziska Schmidt, Bernard Jacob


▶ To cite this version:

Livia Tovar, Frédéric Domprobst, Franziska Schmidt, Bernard Jacob. WIM data for investigation of truck weights and dimensions. 7th International Conference on Weigh-In-Motion (ICWIM7), Nov 2016, FOZ DO IGUACU, Brazil., 2016. hal-01512675v1

HAL Id: hal-01512675 https://hal.science/hal-01512675v1

Submitted on 24 Apr 2017 (v1), last revised 26 Jun 2017 (v2)

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



ICVIIVI7
Foz do Iguaçu
Nov. 7-10, 2016

WIM data for investigation of truck weights and dimensions



Tovar, Livia, Michelin, Brazil Domprobst*, Frédéric, Michelin, France Schmidt, Franziska, Ifsttar, France Jacob, Bernard, Ifsttar, France

* frederic.domprobst@fr.michelin.com



Context and objectives

Tire manufacturer's stakes

Design the right tire for end users

- Size → volume / load capacity
- Rolling resistance → fuel consumption

Design the right tire for safety

- Load capacity → safety
- Drivability → safety, truck stability

WIM data analysis to understand the trucks' loading habits to anticipate its evolution then the impact on road and tire needs

Perspectives of new and more optimized approach of tire design: product segments based on real use to optimize fleet operations and truck safety performance

WIM data

- WIM stations in France: 29 stations on the road network: 30 millions trucks weighted / year
- WIM data for this study: Sample of 1 year on 3 stations, a database of 3 millions trucks has been used in this study with:

Axle load and spacing
Front/rear overhang
Speed


License plate in case of infringement

Quality of WIM data:

- Accuracy on GVW: ±10%
- Accuracy on axle load: $\pm 15\%$
- Class COST323 : B(10)
- Accuracy on speed: ±1%;
- Accuracy on total length of vehicles: $\pm 10\%$
- Accuracy on distances between axles : $\pm 1\%$
- Plate recognition: +80%.




WIM station




Output of WIM station

Truck classification



Classification of the various truck types by axle spacing, load and overhang criteria based on regulation and OEM specifications.

Truck classes




Truck - semitrailer


Example for tractor 4x2 and semi trailer:


- d01 < 1.75m
- 3m < d12 < 4.4m
- d23 > 4m
- d34 < 1.8m & d45 < 1.8m


Axle load distribution

- Axle load distribution rather well comply with legal limits and tire capacity
- Nevertheless, a very limited amount of vehicle use the full tire load capacity










Load distribution for the 5 axles of the truck-semitrailer (from front axle in the graph of the left, to the last axle of the trailer in the graph on the right)

Load patterns



Payload probability density function for the truck-semitrailer

- Payload PDF for 14t empty convoy: a significant amount of vehicle use the max payload even if the majority of vehicles are "underloaded"
- When the payload increase, the center of gravity (CoG) is moved to the back while the load scattering is reduced
- Above 25 t payload, the CoG is at the middle of the semitrailer

References


Schmidt, F., Jacob, B., Domprobst, F., Study of Truck Dimensions and Loadings using WIM data, TRA2016, 18-21 April 2016, Warsaw, Poland.

Acknowledgements

The general directorate for transportation, infrastructure and sea (DGTIM) of the French Ministry of Transport is acknowledged for the permission to use the WIM data collected on the National WIM network.

Methodology

Aim



Methodology

- Truck classification,
- For each truck class: axle load distribution (load only, which means subtracting the axle loads of the empty truck) and load patterns (determine which axle load combinations are representative of the truck population under study).
- We show here the results for the truck class "truck + semi-trailer", more results are given in (Schmidt et al., 2016).

