



HAL
open science

Steam-jet agglomeration of skim-milk powder : influence of the process parameters.

Mathieu Person, Bernard Cuq, Agnès Duri-Bechemilh, Cécile Le Floch-Fouéré, Pierre Schuck, Romain Jeantet

► To cite this version:

Mathieu Person, Bernard Cuq, Agnès Duri-Bechemilh, Cécile Le Floch-Fouéré, Pierre Schuck, et al.. Steam-jet agglomeration of skim-milk powder : influence of the process parameters.. 8. International Granulation Workshop, Jun 2017, Sheffield, United Kingdom. , 2017. hal-01547545

HAL Id: hal-01547545

<https://hal.science/hal-01547545>

Submitted on 26 Jun 2017

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.


L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.




Distributed under a Creative Commons Attribution - ShareAlike 4.0 International License

- Steam-jet agglomeration is used in the dairy industry in order to obtain **instant powders** with improved rehydration.
- Quality control of industrial products remains **experimental** and **empirical** :
 - Steam-jet agglomeration = **black box** process (closed, fast, random collisions).
 - Instant properties = **multi-factorial** causes (structure, composition, physicochemical state).
- Few scientific studies on dairy powders agglomeration and mainly performed with other technologies → **lack of knowledge**.
 - **How can we study and identify the key process parameters that should be controlled ?**

A steam-jet agglomeration pilot plant was developed :



- Two process parameters were studied : the **steam/powder ratio ($R_{S/P}$)** and the **drying time (t_D)**. One factorial design was realized in triplicate :



- Characterization** of the agglomerates : Circularity, Feret diameter, mechanical strength, water content and wetting time.
- Statistical analysis** : linear model after standardization of the data.

Structure of the pilot plant agglomerates :



- Raw material (left) : Skim-milk powder
- Pilot plant agglomerate (middle) : **porous** structure, **irregular** shape
- Industrial agglomerate (right) : dense structure, spherical shape, regular surface

Influence of the process parameters :

	Circularity	Feret diameter (mm)	Mechanical strength (N)	Water content (g.100 g ⁻¹)	Wetting time (s)
↗ Steam/Powder ratio	↘	↗↗ 1	↗	↗	↗↗↗
↗ Drying time	-	-	↘↘	↘↘↘ 2	↗↗
Interaction	-	-	-	-	↗↗ 3

- Steam/Powder ratio** : more liquid bridges comes with more steam available, leading to **larger** agglomerates.
- Drying time** : increasing the drying time leads to the formation of **dry** and **brittle** agglomerates.
- Interaction** : instant properties mechanisms are complex → difficult to identify a **key process parameter** to control.

A steam-jet granulation pilot plant was developed during this study :

- During the agglomeration step, the steam/powder ratio controls the **extent of granulation** in the studied range of values.
- The drying step is crucial for the **storage evolution** to prevent microbial growth, caking or breakage.
- Further studies are needed to understand the **instant properties mechanisms**.

This pilot plant will allow to study :

- The **agglomeration mechanisms** → hydrotextral diagram (solid volume fraction vs water content).
- The **interactions** between the raw material properties, the process parameters and the product properties.
- The **correlations** between the agglomerates properties to understand the mechanisms of the instant properties (multivariate data analysis).

