



**HAL**  
open science

# For Cybersecurity, Computer Science Must Rely on the Opposite of Gödel's Results

Carl Hewitt

► **To cite this version:**

Carl Hewitt. For Cybersecurity, Computer Science Must Rely on the Opposite of Gödel's Results. Symposium on Logic and Collaboration for Intelligent Applications, Mar 2017, Stanford, United States. hal-01566393v14

**HAL Id: hal-01566393**

**<https://hal.science/hal-01566393v14>**

Submitted on 17 Oct 2018

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Copyright

# Strong Types for Direct Logic

Carl Hewitt

<http://plus.google.com/+CarlHewitt-StandardIoT>

*This article is dedicated to Alonzo Church, Richard Dedekind, Stanisław Jaśkowski, Bertrand Russell, Ludwig Wittgenstein, and Ernst Zermelo.*

## Abstract

*Mathematics* in this article means the precise formulation of standard mathematical theories that axiomatize the following up to a unique isomorphism: booleans, natural numbers, reals, ordinals, sets, lambda calculus procedures, and Actors.

In a strongly typed mathematical theory, every proposition, term, and expression has a type where there is **no** universal type *Any*. Types are constructed bottom up from types that are categorically axiomatized.<sup>1</sup>

Strong types are extremely important in Direct Logic because they block *all* known paradoxes including Berry [Russell 1906], Burali-Forti [Burali-Forti 1897], Church [Church 1934], Curry [Curry 1941], Girard [Girard 1972], and Liar [Eubulides of Miletus], Löb[Löb 1955], and Russell[Russell 1902].<sup>2</sup> Blocking known paradoxes makes Direct Logic safer for use in Intelligent Applications by preventing security holes. Consistent strong mathematical theories can be freely used without introducing additional inconsistent information into inconsistency robust empirical theories that will be the core of future Intelligent Applications.

Direct Logic<sup>3</sup> is called “direct” because it directly deals with propositions instead of attempting to deal with them indirectly using Gödel numbers as is done in Provability Logic<sup>4</sup>. Because propositions in Direct Logic are uncountable, it is impossible to give a Gödel number to every proposition.<sup>5</sup>

Inconsistency Robustness is performance of information systems (including scientific communities) with pervasively inconsistent information.<sup>6</sup> Inconsistency Robustness of the community of professional mathematicians is their performance repeatedly repairing contradictions over the centuries. In the Inconsistency Robustness paradigm, deriving contradictions has been a progressive

development and not “game stoppers.” Contradictions can be helpful instead of being something to be “swept under the rug” by denying their existence, which has been repeatedly attempted by authoritarian theoreticians (beginning with some Pythagoreans). Such denial has delayed mathematical development. This article reports how considerations of Inconsistency Robustness have recently influenced the foundations of mathematics for Computer Science continuing a tradition developing the sociological basis for foundations.

Having a powerful system like Direct Logic is important in computer science because computers must be able to formalize all logical inferences (including inferences about their own inference processes) without requiring recourse to human intervention. Any inconsistency in Classical Direct Logic would be a potential security hole because it could be used to cause computer systems to adopt invalid conclusions.

After [Church 1934], logicians faced the following dilemma:

- 1<sup>st</sup> order theories cannot be powerful lest they fall into inconsistency because of Church’s Paradox.
- 2<sup>nd</sup> order theories contravene the philosophical doctrine that theorems must be computationally enumerable.

The above issues can be addressed by requiring Mathematics to be strongly typed using so that:

- Mathematics self proves that it is “open” in the sense that theorems are not computationally enumerable.<sup>7</sup>
- Mathematics self proves that it is *formally* consistent.<sup>8</sup>
- Strong mathematical theories for Natural Numbers, Ordinals, Set Theory, the Lambda Calculus, Actors, etc. are inferentially decidable, meaning that every true proposition is provable and every proposition is either provable or disprovable.<sup>9</sup>

## Mathematical Foundations for Computer Science

All mathematical entities are instances of types.

Computer Science brought different concerns and a new perspective to mathematical foundations including the following requirements (building on [Maddy 2018]):

- **Practicality** is providing powerful machinery so that arguments (proofs) can be short and understandable and
- **Generality** is formalizing inference so that all of mathematics can take place side-by-side. Direct Logic provides a generality by formalizing theories of the natural numbers, reals, ordinals, set theory, groups, lambda calculus, and Actors side-by-side.
- **Shared Standard** of what counts as legitimate mathematics so people can join forces and develop common techniques and technology. According to [Burgess 2015]:

To guarantee that rigor is not compromised in the process of transferring material from one branch of mathematics to another, it is essential that the starting points of the branches being connected ... be compatible. ... The only obvious way ensure compatibility of the starting points ... is ultimate to derive all branches from a common unified starting point.

Direct Logic provides such a common unified starting point including natural numbers, reals, ordinals, set theory, group theory, geometry, algebra, lambda calculus, and Actors that are axiomatized up to a unique isomorphism.

- **Abstraction** so that fundamental mathematical structures can be characterized up to a unique isomorphism including natural numbers, reals, ordinals, set theory, groups, lambda calculus, and Actors.<sup>10</sup>
- **Guidance** is for practioners in their day-to-day work by providing relevant structures and methods free of extraneous factors. Direct Logic provides guidance by providing strong parameterized types and intuitive categorical inductive axiomatizations of natural numbers, ordinals, sets, lambda calculus, and Actors.
- **Meta-Mathematics** is the formalization of logic and rules of inference. Direct Logic facilitates meta-mathematics because it is its own meta-theory.
- **Automation** is facilitated in Direct Logic by making type checking very easy and intuitive along as well as incorporating Jaśkowski natural deduction for building an inferential system that can be used in everyday work.

- **Risk Assessment** is the danger of contradictions emerging in classical mathematical theories. In this regard, Direct Logic formalizes long-established and well-tested mathematical practice while blocking all known paradoxes including Berry [Russell 1906], Burali-Forti [Burali-Forti 1897], Church [Church 1934], Curry [Curry 1941], Girard [Girard 1972], and Liar [Eubulides of Miletus], Löb[Löb 1955], and Russell[Russell 1902].

Intuitive categorical *inductive* axiomatizations of natural numbers, propositions, types, ordinals, sets, lambda calculus, and Actors promote confidence in operational consistency.

Consistent mathematical theories can be freely used in (inconsistent) empirical theories without introducing additional inconsistency.<sup>11</sup>

### Foundations with strong parameterized types

“Everyone is free to elaborate [their] own foundations. All that is required of [a] Foundation of Mathematics is that its discussion embody absolute rigor, transparency, philosophical coherence, and addresses fundamental methodological issues.”<sup>12</sup>

“The aims of logic should be the creation of “a unified conceptual apparatus which would supply a common basis for the whole of human knowledge.”  
[Tarski 1940]

**Note: parameterized types<sup>13</sup> in Direct Logic are more intuitive for classical mathematical theories than intuitionistic types [Martin-Löf 1998].<sup>14</sup>**

Booleans are Propositions although Propositions are not reducible to Booleans:

- **True:** *Boolean*
- **False:** *Boolean*
- *Boolean*  $\sqsubseteq$  *Proposition* //each Boolean is a Proposition
- *Boolean*  $\neq$  *Proposition* //some Propositions are **not** Booleans
- $(3=3) \neq \mathbf{True}$  //the proposition  $3=3$  is **not** equal to **True**
- $(3=3) \neq (4=4)$   
//the proposition  $3=3$  is **not** equal to the proposition  $4=4$
- $(3=4) \neq \mathbf{False}$  //the proposition  $3=4$  is **not** equal to **False**

In Direct Logic, unrestricted recursion is allowed in programs. For example, There are uncountably many Actors. For example, the procedure call  $\text{Real}_{\bullet}[\ ]$  can output any real number using binary representation between 0 and 1 where<sup>15</sup>

$\text{Real}:[\ ] \rightarrow \mathcal{R}_{[0,1]}$  // Real is a procedure of  
 // no arguments that returns a  $\mathcal{R}_{[0,1]}$

$\text{Real}_{\bullet}[\ ] \equiv [(0 \text{ either } 1), \forall \text{Postpone } \text{Real}_{\bullet}[\ ]]$

where

- o (0 **either** 1) is the nondeterministic choice of 0 or 1,
- o  $[first, \forall rest]$  is the list that begins with *first* and whose remainder is *rest*, and
- o **Postpone** *expression* delays execution of *expression* until the value is needed.

Also, there are uncountably many propositions (because there is a different proposition for every real number). For example, the function p defined as follows:

$$p[x] \equiv \lambda[y:\mathcal{R}] (y=x)$$

defines a different predicate p[x] for each real number x, which holds for only one real number, namely x.<sup>16</sup>

Sentences parse trees are important as a means for constructing propositions. If s is a well formed sentence parse tree **with no free variables**, then [s] is a proposition.

### Sentence Parse Trees

e.g.  $(\forall[n:\mathbb{N}] (\exists[m:\mathbb{N}] (m>n)))$

i.e., sentence parse tree for proposition that  
 for every  $\mathbb{N}$  there is a larger  $\mathbb{N}$

Every proposition is the abstraction of some sentence parse tree.

Classical Direct Logic is a foundation of mathematics for Computer Science, which has a foundational theory (for convenience called “Mathematics”) that can be used in any other theory. A bare turnstile is used for Mathematics so that  $\vdash\Psi$  means that  $\Psi$  is a mathematical proposition that is a theorem of Mathematics and  $\Phi\vdash\Psi$  means that  $\Psi$  can be inferred from  $\Phi$ .

Direct Logic develops foundations for Mathematics by deriving sets from types *and* categorical axioms for the natural numbers and ordinals.

## Higher Order Logic

*“If the mathematical community at some stage in the development of mathematics has succeeded in becoming (informally) clear about a particular mathematical structure, this clarity can be made mathematically exact ... Why must there be such a characterization? Answer: if the clarity is genuine, there must be a way to articulate it precisely. If there is no such way, the seeming clarity must be illusory ... for every particular structure developed in the practice of mathematics, there is [a] categorical characterization of it.”<sup>17</sup>*

Classical Direct Logic is much stronger than 1<sup>st</sup> order axiomatizations of set theory in that it provides categoricity for natural numbers  $\mathbb{N}$ , reals  $\mathbb{R}$ , ordinals  $\mathcal{O}$ . set theory, the lambda calculus and Actors. Categoricity is very important in Computer Science so that there are no nonstandard elements in models of computational systems, e.g., infinite integers and infinitesimal reals. For example, nonstandard models cause problems in model checking if a model has specified properties.

### Natural Number Induction

The mathematical theory<sup>18</sup>  $\mathit{Nat}$  that axiomatises the Natural Numbers has the following axioms:

- $\mathit{N}::$  //  $\mathit{N}$  is a type
- $0:\mathit{N}$  // 0 is of type  $\mathit{N}$
- $+_1:\mathit{N}^{\mathit{N}}$  //  $+_1$  is of type  $\mathit{N}^{\mathit{N}}$
- $\nexists[i:\mathit{N}] +_1[i]=0$
- $\forall[i,j:\mathit{N}] +_1[i]=+_1[j] \Leftrightarrow i=j$

In addition  $\mathit{Nat}$  has the following induction axiom, which has uncountable instances:<sup>19</sup>

$$\forall[P:\mathit{Nat}^{\mathit{N}}] (P[0] \wedge \forall[i:\mathit{N}] P[i] \Rightarrow P[+_1[i]]) \Rightarrow \forall[i:\mathit{N}] P[i]$$

The above induction axiom makes use of the type  $\mathit{Proposition} \langle \mathit{Nat} \rangle$  which has the following axioms:<sup>20</sup>

- $\mathit{Nat}::$  //  $\mathit{Nat}$  is the type of propositions of theory  $\mathit{Nat}$
- $\forall[t_1, t_2:\mathit{Type} \langle \mathit{Nat} \rangle \triangleright; x:t_1] (x:t_2):\mathit{Nat}$
- $\forall[t:\mathit{Type} \langle \mathit{Nat} \rangle; x_1, x_2:t] (x_1=x_2):\mathit{Nat}$

In addition to the above, propositions of **Nat** have the following induction axiom:

$$\begin{aligned}
& \forall [Q: \mathbf{Nat}^{\mathbf{Nat}}] \\
& ((\forall [t: \mathbf{Type} \langle \mathbf{Nat} \rangle; x_1, x_2: t] Q[x_1=x_2]) \wedge \\
& (\forall [\Psi: \mathbf{Nat}] Q[\Psi] \Rightarrow Q[\neg \Psi]) \wedge \\
& (\forall [\Psi_1, \Psi_2: \mathbf{Nat}] Q[\Psi_1] \wedge Q[\Psi_2] \Rightarrow Q[\Psi_1 \wedge \Psi_2]) \wedge \\
& (\forall [t: \mathbf{Type} \langle \mathbf{Nat} \rangle; P: \mathbf{Nat}^t] \forall t Q[P] \Rightarrow Q[\forall t P]) \\
& \Rightarrow \forall [\Psi: \mathbf{Nat}] Q[\Psi]
\end{aligned}$$

The above axioms characterize *Proposition*  $\langle \mathbf{Nat} \rangle$  up to a unique isomorphism.<sup>21</sup>

The following theorem states that each proposition is the abstraction of a sentence parse tree.<sup>22</sup>

**Theorem.**<sup>23</sup>  $\forall [\Psi: \mathbf{Nat}] \exists [s: \mathbf{Sentence} \langle \mathbf{Nat} \rangle] \Psi = [s]$

### Proof Checkers in **Nat**

$$\begin{aligned}
& \forall [\Psi_1, \Psi_2: \mathbf{Nat}] \\
& (\Psi_1 \vdash_{\mathbf{Nat}} \Psi_2) \Leftrightarrow \exists [p: \mathbf{ProofChecker} \langle \mathbf{Nat} \rangle] \Psi_1 \vdash_{\frac{p}{\mathbf{Nat}}} \Psi_2
\end{aligned}$$

where

$$\mathbf{ProofChecker} \langle \mathbf{Nat} \rangle \sqsubseteq \mathbf{Total} \langle [\mathbf{Nat}, \mathbf{Nat}] \rightarrow_1 \mathbf{Boolean} \rangle$$

Proof checking in **Nat** is **computationally decidable**.

$$\begin{aligned}
& \forall [\Psi_1, \Psi_2: \mathbf{Nat}, p: \mathbf{ProofChecker} \langle \mathbf{Nat} \rangle] \\
& (\Psi_1 \vdash_{\frac{p}{\mathbf{Nat}}} \Psi_2) \Leftrightarrow p \cdot [\Psi_1, \Psi_2] = \mathbf{True}
\end{aligned}$$

### **Nat** has uncountable proof checkers

There are uncountable proof checkers of the form `ForAllElimChecker[c]` where  $t: \mathbf{Type} \langle \mathbf{Nat} \rangle$  and  $c: t$  such that

$$\begin{aligned}
& \mathbf{ForAllElimChecker}[c] \cdot [\Psi_1, \Psi_2] \equiv \\
& \Psi_1 \text{ if } (\forall [x: t] P[x]) \text{ then } \Psi_2 = P[c] \text{ else } \mathbf{False} \\
& // \text{ If } \Psi_1 \text{ is } \forall [x: t] P[x], \text{ then } \Psi_2 = P[c], \text{ otherwise } \mathbf{False}
\end{aligned}$$

Consequently,

$$(\forall [x: t] P[x]) \vdash_{\frac{\mathbf{ForAllElimChecker}[c]}{\mathbf{Nat}}} P[c]$$



### Computational Undecidability of Provability in $Nat$

The halting problem is to computationally decide whether a given procedure  $p$  halts on a given input  $x$ , which is formally expressed as  $\text{Halt}[p,x]$ . [Church 1935; Turing 1936] proved that the halting problem is computationally undecidable. Whether a proposition is a theorem of  $Nat$  is computationally undecidable because the predicate  $\text{Halt}$  can be formalized in  $Nat$  such that:

$$\forall[i:N, p:([N] \rightarrow N)] \text{Halt}[p, i] \Leftrightarrow \vdash_{Nat} \text{Halt}[p, i]$$

### Theorem (Indiscernibility for $Nat$ ):

$$\forall[i,j:N] i=j \Leftrightarrow \forall[P:Nat^N] P[i] \Leftrightarrow P[j]$$

**Proof.** Define  $\text{Same}:(Nat^N)^N$

$$\text{Same}[i] \equiv \lambda[j:N] i=j$$

$$\forall[i,j:N] (\text{Same}[i] \Leftrightarrow \text{Same}[j]) \Leftrightarrow i=j$$

### Theorem (Proof Soundness of $Nat$ ): $(\vdash_{Nat} \Psi) \Leftrightarrow \Psi$

Proof soundness means that a theorem in  $Nat$  can be used in proofs.

A consequence of Proof Soundness is that unrestricted cut-elimination does not hold for  $Nat$ .<sup>24</sup>

### Axiomatization of $\vDash_N$

Axioms of  $\vDash_N$  are as follows:

- $\vDash_N \text{True}$
- $\neg \vDash_N \text{False}$
- $(\vDash_N \Phi \wedge \Psi) \Leftrightarrow (\vDash_N \Phi) \wedge (\vDash_N \Psi)$
- $(\vDash_N \neg \Phi) \Leftrightarrow \neg \vDash_N \Phi$
- $\forall[P:Nat^N] (\vDash \forall[i:N] P[i]) \Leftrightarrow (\forall[i:N] \vDash_N P[i])$

### Theorem (Model Soundness of $Nat$ ): $(\vdash_{Nat} \Psi) \Leftrightarrow (\vDash_N \Psi)$

Proof: Suppose  $\vdash_{Nat} \Psi$ . The theorem immediately follows because the axioms for the theory  $Nat$  hold in the type  $N$ .

**Theorem (Categoricity of *Nat*):**<sup>25</sup>

If  $\mathcal{X}$  be a type satisfying the axioms for the natural numbers *Nat*, then there is a unique isomorphism  $I$  with  $\mathcal{N}$  defined as follows:

- $I: \mathcal{X}^{\mathcal{N}}$
- $I[0_{\mathcal{N}}] \equiv 0_{\mathcal{X}}$
- $I[+_1[j]] \equiv +_{\mathcal{X}}^1[I[j]]$

because

- $I$  is defined on  $\mathcal{N}$
- $I$  is 1-1
- $I$  is onto  $\mathcal{X}$
- $I$  is a homomorphism
  - $I[0_{\mathcal{N}}] \equiv 0_{\mathcal{X}}$
  - $\forall [i: \mathcal{N}] I[+_1[j]] \equiv +_{\mathcal{X}}^1[I[j]]$
- $I^{-1}$  is a homomorphism
  - $I^{-1}[0_{\mathcal{X}}] \equiv 0_{\mathcal{N}}$
  - $\forall [z: \mathcal{X}] I^{-1}[+_1^{\mathcal{X}}[z]] \equiv [+_1[I^{-1}[z]]]$
- If  $g$  is an isomorphism with  $\mathcal{X}$ , then  $g=I$



Richard Dedekind

Note that the statement of categoricity is **not** a 1<sup>st</sup> order proposition because it quantifies over **every** type  $\mathcal{X}$  and over every isomorphism between  $\mathcal{X}$ , and  $\mathcal{N}$ .

**Corollary** There are no infinite numbers in models of the theory *Nat*, i.e.,

$$\forall [\mathcal{X}::] \text{Nat}_{\langle \mathcal{X} \rangle} \Rightarrow \nexists [j: \mathcal{X}] \forall [i: \mathcal{X}] j < i$$

### By Contradiction in *Nat*

“[By Contradiction is] one of a mathematician’s first weapons .... It is a far finer gambit than any chess gambit: a chess player may offer the sacrifice of a pawn or even a piece, but a mathematician offers the game.”

G. H. Hardy <sup>26</sup>

By Contradiction is one of the most fundamental principles of Classical Mathematics (going back to before Euclid), which can be formalized

- axiomatically to say that if  $\Psi$  implies  $\Phi$  and  $\neg\Phi$  then  $\neg\Psi$ :

$$(\Psi \Rightarrow \Phi \wedge \neg\Phi) \Rightarrow \neg\Psi$$

- proof theoretically to say that proving the theorem  $\neg\Psi \Rightarrow \Phi \wedge \neg\Phi$  means that  $\Psi$  is a theorem:

$$(\neg\Psi \Rightarrow \Phi \wedge \neg\Phi) \Rightarrow \vdash_{\text{Nat}} \Psi$$

- in [Jaśkowski 1934] natural deduction to say that ( $\Psi$  infers  $\Phi$  and  $\neg\Phi$ ) holds in a subproof <sup>27</sup> of a proof infers that  $\neg\Psi$  holds in the proof:

$$(\Psi \vdash_{\text{Nat}} \Phi \wedge \neg\Phi) \vdash_{\text{Nat}} \neg\Psi$$

**By Contradiction is much more powerful than has been supposed by many philosophers of mathematics. As shown in this article, it is sufficient to prove the formal consistency and the inferential completeness of categorical theories of the natural numbers, reals, ordinals, set theory, the lambda calculus, and Actors.**

**Theorem:**<sup>28</sup> **Inferential completeness of *Nat***

$$\forall[\Psi:\text{Nat}] (\vDash_N \Psi) \Rightarrow \vdash_{\text{Nat}} \Psi$$

Proof.

Suppose in  $\Psi:\text{Nat}$  and  $\vDash_N \Psi$ . Further suppose to obtain a contradiction that  $\neg\Psi$ . Hence  $\Psi$  and  $\neg\Psi$ , which is a contradiction.

Therefore  $\vdash_{\text{Nat}} \Psi$  using By Contradiction in *Nat*.<sup>29</sup>

**Corollary.** Equivalence of satisfiability and provability in  $Nat$ , i.e.,

$$\forall[\Psi:Nat] (\models_N \Psi) \Leftrightarrow (\vdash_{Nat} \Psi)$$

**Theorem.** Inferential Decidability of  $Nat$ <sup>30</sup>, i.e.,

$$\forall[\Psi:Nat] (\vdash_{Nat} \Psi) \vee (\vdash_{Nat} \neg\Psi)$$

**Proof.** Follows immediately from  $(\models_N \Psi) \Leftrightarrow (\vdash_{Nat} \Psi)$

**Theorem.** Theorems of the theory  $Nat$  are **not** computationally enumerable

**Proof.** Suppose to obtain a contradiction that theorems of  $Nat$  are computationally enumerable. Then whether a proposition is a theorem of  $Nat$  is computationally decidable by enumerating theorems until either the proposition or its negation is encountered.

**Theorem (Instance Adequacy of  $Nat$ ):**<sup>31</sup>

$$\forall[P:Nat] (\forall[i:N] \vdash_{Nat} P[i]) \Leftrightarrow \vdash_{Nat} \forall[i:N] P[i]$$

**Proof:** Suppose  $\forall[i:N] \vdash_{Nat} P[i]$  which means by completeness

$\forall[i:N] \models_N P[i]$ . Therefore  $\models_N \forall[i:N] P[i]$  which means by completeness

$$\vdash_{Nat} \forall[i:N] P[i]$$

**Theorem ( $Nat$  is not compact)**<sup>32</sup>

**Definition** Total: $Nat^{[N]} \rightarrow N$  where Total[f]  $\equiv \forall[i:N] \exists[j:N] f.[i]=j$

**Theorem** The theory  $Nat$  proves that it is formally consistent:<sup>33</sup>

$$\vdash_{Nat} \text{Consistent}[Nat]$$

**Proof:** Suppose to derive an inconsistency that  $\neg\text{Consistent}[Nat]$ . By the definition of formal inconsistency for  $Nat$ , there is some proposition

$\Psi_0:Nat$  such that  $\vdash_{Nat} (\Psi_0 \wedge \neg\Psi_0)$  which can be used to infer in  $Nat$  that

$\Psi_0 \wedge \neg\Psi_0$ . The above contradiction completes the proof.

## Uneven Progress

“All truth passes through three stages. First, it is ridiculed. Second, it is violently opposed. Third, it is accepted as being self-evident.”

Arthur Schopenhauer [1818]

“Faced with the choice between changing one’s mind and proving that there is no need to do so, almost everyone gets busy on the proof.”

John Kenneth Galbraith [1971 pg. 50]

“Max Planck, surveying his own career in his Scientific Autobiography [Planck 1949], sadly remarked that ‘a new scientific truth does not triumph by convincing its opponents and making them see the light, but rather because its opponents eventually die, and a new generation grows up that is familiar with it.’ ” [Kuhn 1962]

The inherently social nature of the processes by which principles and propositions in logic are produced, disseminated, and established is illustrated by the following issues with examples:

- **The formal presentation of a demonstration (proof) has not led automatically to consensus.** Formal presentation in print and at several different professional meetings of the extraordinarily simple proof in this paper have not lead automatically to consensus about the theorem that “Mathematics proves that it is formally consistent”. New results can sound crazy to those steeped in conventional thinking. Paradigm shifts often happen because conventional thought is making assumptions taken as dogma. As computer science continues to advance, such assumptions can get in the way and have to be discarded.
- **There has been an absence of universally recognized central logical principles.** Disputes over the validity of the Principle of Excluded Middle led to the development of Intuitionistic Logic.
- **There are many ways of doing logic.** One view of logic is that it is about *truth*; another view is that it is about *argumentation* (i.e. proofs).<sup>34</sup>
- **Argumentation and propositions have be variously (re-)connected and both have been re-used.** Church's paradox [Church 1934] is that assuming theorems of mathematics are computationally enumerable leads to contradiction. In this article, Church’s Paradox is transformed into the fundamental principle that “Mathematics is Open” (i.e. it is a theorem of

mathematics that the proofs of mathematics are not computationally enumerable). See discussion in this article.

- **New technological developments have cast doubts on traditional logical principles.** The pervasive inconsistency of modern large-scale information systems has cast doubt on some logical principles, *e.g.*, Excluded Middle.<sup>35</sup> That there are proofs that cannot be expressed through text alone, overturns a long-held philosophical dogma about mathematical theories, *i.e.*, that all theorems of a theory can be computationally generated by starting with axioms and mechanically applying rules of inference.
- **It has been easier to prove meta theorems for 1<sup>st</sup> order logic.** Since theoreticians found it difficult to prove anything significant about practical mathematical theories, they cut them down to unrealistic 1<sup>st</sup> order theories where results could be proved (*e.g.* compactness) that did not hold for practical mathematical theories. In the famous words of Upton Sinclair:  
    *“It is difficult to get a man to understand something,  
    when his salary depends on his not understanding it.”*  
Some theoreticians have ridiculed dissenting views and attempted to limit their distribution by political means.
- **Political actions have been taken against views differing from the establishment theoreticians.** According to [Kline 1990, p. 32], Hippasus was literally thrown overboard by his fellow Pythagoreans “...for having produced an element in the universe which denied the...doctrine that all phenomena in the universe can be reduced to whole numbers and their ratios.” Fearing that he was dying and the influence that Brouwer might have after his death, Hilbert fired<sup>36</sup> Brouwer as an associate editor of *Mathematische Annalen* because of “incompatibility of our views on fundamental matters”<sup>37</sup> *e.g.*, Hilbert ridiculed Brouwer for challenging the validity of the Principle of Excluded Middle. [Gödel 1931] results were for Principia Mathematica as the foundation for the mathematics of its time including the categorical axiomatization of the natural numbers. In face of Wittgenstein's devastating criticism, Gödel insinuated<sup>38</sup> that he was crazy and retreated to *1stOrderDedekindPeano* in an attempt to salvage his results.

## Summary of *Nat*

The theory *Nat* can be summarized as follows:

- **Indiscernibility for *Nat*:**

$$\forall [i, j: N] i = j \Leftrightarrow \forall [P: \mathit{Nat}^N] P[i] \Leftrightarrow P[j]$$

- **Instance Adequacy of *Nat*:**

$$\forall [P: \mathit{Nat}^N] (\forall [i: N] \vdash_{\mathit{Nat}} P[i]) \Leftrightarrow \vdash_{\mathit{Nat}} \forall [i: N] P[i]$$

- ***Nat* is categorical for *N***

$$\vdash_{\mathit{Nat}} \forall [X::] \mathit{Nat} \triangleleft X \triangleright \Leftrightarrow \text{UniquelyIsomorphic}[X, N]$$

- ***Nat* proves its own formal consistency**

$$\vdash_{\mathit{Nat}} (\neg \exists [\Psi: \mathit{Nat}] \vdash_{\mathit{Nat}} \Psi \wedge \neg \Psi)$$

- **A proposition is true  $\Leftrightarrow$  it is provable in *Nat***

$$\forall [\Psi: \mathit{Nat}] (\models_N \Psi) \Leftrightarrow (\vdash_{\mathit{Nat}} \Psi)$$

- ***Nat* is inferentially decidable**

$$\forall [\Psi: \mathit{Nat}] (\vdash_{\mathit{Nat}} \Psi) \vee (\vdash_{\mathit{Nat}} \neg \Psi)$$

- **$\vdash_{\mathit{Nat}} \Psi$  is computationally undecidable**

## Actor Model


Concurrent message passing was crucially omitted from the  $\lambda$  calculus [Church 1932], Turing Machines (TM) [Turing 1936], Simula-67 [Dahl and Nygaard 1967], and Logic Programs [Hewitt 1969] thereby crippling them as a foundation for the Internet of Things (IoT). Actors [Hewitt, et. al 1973] remedied the omission to provide for scalable computation. **An Actor message passing machine can be millions of times faster than any corresponding pure Logic Program or parallel nondeterministic  $\lambda$  expression.** Since the time of this early work, message passing has grown to be one of the most important paradigms in computing [Hewitt and Woods 2018; Hoare 2016; Milner 1993].

Of course, earlier work made huge pioneering contributions:  $\lambda$  expressions play an important role in programming languages. TM inspired development of the stored program sequential computer. Simula-67 became the basis for object-oriented programming in Java and C++. Logic Programs are fundamental to Scalable Intelligent Systems. [Hewitt and Woods 2018]

## Message Passing in Practice

Concurrency control for readers and writers in a data base is a classic problem that illustrates the power of message passing. The fundamental constraint is that multiple writers are not allowed to operate concurrently in the data base and a writer is not allowed to operate concurrently with a reader. In the figure below for an Actor machine

- Yellow is used for the Actor's region of mutual exclusion
- Within the region of mutual exclusion, a hole in grey allows other messages to be processed which are of two kinds:
  1. Queue (shown as rectangle) hole in which the current activity can be suspended until resumed
  2. Call-out (shown as oval) hole for a request made outside the region of mutual exclusion





Many different policies could be implemented in the above scheduler including the following:

- Reader priority: When a writer comes out of the database, resume all in **ReadersQ**.
- Writer priority: When a writer comes out of the database and both **WritersQ** and **ReadersQ** are nonempty, resume just one in **ReadersQ**, and then when it comes of the database resume one in **WritersQ**.


### **Computation that cannot be done by $\lambda$ Calculus, TM, or pure Logic Programs**

Actor message passing machines can perform computations that a no  $\lambda$  expression, nondeterministic Turing Machine, Simula-67 program, or pure Logic Program can implement. Below is an example of a very simple computation that cannot be performed by a nondeterministic TM:

There is an *always-halting* Actor message passing machine that can compute an integer of unbounded size. This is accomplished using variables **count** initially **0** and **continue** initially **True**. The computation is begun by concurrently sending over the Internet two messages to the Actor machine: a **stop** request that will return an integer  $n$  formalized as **Output[n]** and a **go** message that will return **Void**.

The Actor machine operates as follows:

- When a **go** message is received: If **continue** is **True**, increment **count** by 1, send this Actor machine a **go** message in a hole of the region of mutual exclusion, and afterward return **Void**. If **continue** is **False**, return **Void**.
- When a **stop** message is received, return **count** and set **continue** to **False** for the next message received.




Resend **go** message until **stop** message received

**Theorem.** There is no  $\lambda$  expression, nondeterministic Turing Machine, Simula-67 program, or pure Logic Program that implements the above computation.

**Proof** [Plotkin 1976]:

“Now the set of initial segments of execution sequences of a given nondeterministic program P, starting from a given state, will form a tree.

The branching points will correspond to the choice points in the program. Since there are always only finitely many alternatives at each choice point, the branching factor of the tree is always finite. That is, the tree is finitary. Now König's lemma says that if every branch of a finitary tree is finite, then so is the tree itself. In the present case this means that if every execution sequence of P terminates, then there are only finitely many execution sequences. So if an output set of P is infinite, it must contain a nonterminating computation.”



**Nondeterministic Choice**

### Limitations of 1<sup>st</sup> Order Logic for Concurrent Computation

**Theorem.** It is well known that there is no 1<sup>st</sup> order theory for the above Actor machine.

**Proof.** Every 1<sup>st</sup> order theory is compact meaning that every inconsistent set of propositions has a finite inconsistent subset. Consequently, to show that there is no 1<sup>st</sup> order theory, it is sufficient to show that there is an inconsistent set of propositions such that every finite subset is consistent. The set of propositions **NoOutput** defined to be  $\{\neg\text{Output}[i] \mid i:\mathbb{N}\}$  is inconsistent meaning  $\vdash\neg\text{NoOutput}$  (because  $\vdash\exists[i:\mathbb{N}] \text{Output}[i]$ , i.e., the Actor machine always outputs an integer) but every *finite* subset S of **NoOutput** is consistent meaning  $\not\vdash\neg S$  (because by finiteness of S, there is an upper bound  $b:\mathbb{N}$  such that S is a subset of  $\{\neg\text{Output}[i] \mid i < b\}$  but  $\not\vdash\neg\{\neg\text{Output}[i] \mid i < b\}$  and therefore S is consistent because  $\not\vdash\neg S$ , i.e., the Actor machine output might be larger than b).

Message passing has fundamentally transformed the foundations and practice of computation since the initial conceptions of Turing and Church. Although 1<sup>st</sup>

order sentences can be useful (e.g. in SAT solvers), message passing illustrates why 1<sup>st</sup> order logic cannot be the foundation for theories in Computer Science.

### Categorical Axiomatization of Actors

Let  $x[e]$  be the behavior of Actor  $x$  at local event  $e$ ,  $Com$ <sup>39</sup> be the type for a communication, and  $Behavior$ <sup>40</sup> be the type for a procedure that maps a communication received to an outcome that has a finite set of created Actors, a finite set of sent communications, and a behavior for the next communication received. The mathematical theory **Act** categorically axiomatises Actors using the following axioms where  $\rightsquigarrow$ <sup>41</sup> is transitive and irreflexive:

- Primitive Actors
  - $\forall [i:N] \ i:Actor$  // natural numbers are Actors
  - $\forall [x_1, x_2:Actor] \ [x_1, x_2]:Actor$  // a 2-tuple of Actors is an Actor
- An Actor's event ordering
  - $\forall [x:Actor, c:Com] \ Initial_x \rightsquigarrow Received_x[c] \rightsquigarrow After_x[c]$ <sup>42</sup>
  - $\forall [x:Actor, c_1, c_2:Com] \ c_1 \neq c_2 \Rightarrow Received_x[c_1] \rightsquigarrow Received_x[c_2]$   
 $\vee Received_x[c_2] \rightsquigarrow Received_x[c_1]$ <sup>43</sup>
  - $\forall [x:Actor, c_1:Com] \ \nexists [c_2:Com]$   
 $Received_x[c_1] \rightsquigarrow Received_x[c_2] \rightsquigarrow After_x[c_1]$ <sup>44</sup>
- An Actor's behavior change
  - $\forall [x:Actor, c_1:Com] \ (\nexists [c_2:Com] \ Received_x[c_2] \rightsquigarrow Received_x[c_1])$   
 $\Rightarrow x[Received_x[c_1]] = x[Initial_x]$ <sup>45</sup>
  - $\forall [x:Actor, c:Com] \ x[After_x[c]] = (x[Before_x[c]])[c]$ <sup>46</sup>
  - $\forall [x:Actor, c:Com]$   
 $Let \ processing = Info[Before_x[c]] \sqcup Info[Received_x[c]] \sqcup Info[Created_x[c]]$ <sup>47</sup>  
 $in \ Info[After_x[c]] \sqsubseteq processing$ <sup>48</sup>  $\wedge \ Info[Sent_x[c]] \sqsubseteq processing$ <sup>49</sup>
- Discreteness of Actors event ordering<sup>50</sup>
  - $\forall [e_1, e_2:Event] \ Finite[\{e:Event \mid e_1 \rightsquigarrow e \rightsquigarrow e_2\}]$ <sup>51</sup>
- Actor Induction
  - $\forall [x:Actor, P:Act \ Behavior]$   
 $(P[x[Initial_x]] \wedge \forall [c:Com] \ P[x[Received_x[c]]) \Rightarrow P[x[After_x[c]])$   
 $\Leftrightarrow \forall [c:Com] \ P[x[Received_x[c]]] \wedge P[x[After_x[c]]]$ <sup>52</sup>

**Note that the above axioms do not require that every communication sent must be received.** However, ActorScript provides that every request will either throw a *TooLong* exception or respond with the response sent to its customer.

**Theorem. Computational Adequacy of Actors.**

If for each  $i:\mathbb{N}$ ,  $F_i$  is a nondeterministic  $\lambda$  expression such that

$$\forall [i:\mathbb{N}] F_i \sqsubseteq F_{i+1} \Leftrightarrow (\text{limit}_{i:\mathbb{N}} F_i) : \text{Actor}$$

**Theorem. Categoricity of Act**

If  $\mathcal{X}$  be a type satisfying the axioms for **Act**, then there is a unique isomorphism between  $\mathcal{X}$  and **Actor**.

**Theorem: Inferential completeness of the theory Act**

$$\forall [\Psi:\text{Act}] (\models_{\text{Actor}} \Psi) \Rightarrow (\vdash_{\text{Act}} \Psi)$$

**Corollary.** Equivalence of satisfiability and provability in **Act**, i.e.,

$$\forall [\Psi:\text{Act}] (\models_{\text{Actor}} \Psi) \Leftrightarrow (\vdash_{\text{Act}} \Psi)$$

**Theorem.** Inferential Decidability of **Act**, i.e.,

$$\forall [\Psi:\text{Act}] (\vdash_{\text{Act}} \Psi) \vee (\vdash_{\text{Act}} \neg \Psi)$$

Proof. Follows immediately from  $(\models_{\text{Actor}} \Psi) \Leftrightarrow (\vdash_{\text{Act}} \Psi)$

**Mathematics self proves its own formal consistency (contra [Gödel 1931])**

The following are fundamental to Mathematics<sup>53</sup>:

- By Contradiction, *i.e.*  $\vdash (\neg \Phi \Rightarrow (\Theta \wedge \neg \Theta)) \Rightarrow \Phi$ , which says that a proposition can be proved showing that its negation implies a contradiction.
- A theorem can be used in a proof<sup>54</sup>, *i.e.*  $\vdash ((\vdash \Phi) \Rightarrow \Phi)$

**Theorem:** Mathematics self proves its own formal consistency<sup>55</sup>, i.e.,  $\vdash$ Consistent

**Proof.** Suppose to obtain a contradiction, that mathematics is formally inconsistent, i.e.,  $\neg$ Consistent. By definition of formal consistency, there is some proposition  $\Psi_0$  such that  $\vdash (\Psi_0 \wedge \neg\Psi_0)$  which by the Theorem Use means  $\Psi_0 \wedge \neg\Psi_0$ , which is a contradiction. Thus,  $\vdash$ Consistent using By Contradiction.

1) $\neg$ Consistent	// hypothesis to derive a contradiction <b>just in this subargument</b>
2) $\vdash(\Psi_0 \wedge \neg\Psi_0)$	// definition of inconsistency using 1)
3) $\Psi_0 \wedge \neg\Psi_0$	// axiom of Soundness using 2)
$\vdash$ Consistent	// axiom of Proof by Contradiction using 1) and 3)

### Natural Deduction Proof of Formal Consistency of Mathematics

Please note the following points:

- The above argument mathematically proves that Mathematics is formally consistent and that **it is not a premise of the theorem that Mathematics is formally consistent.**
- Mathematics was designed for consistent theories and consequently Mathematics can be used to prove its own formal consistency regardless of other axioms.<sup>56</sup>
- [Gödel 1931] used formal consistency as the basis of his results. The above theorem does not prove that Mathematics is operationally consistent, i.e., that no contradiction can be derived using the stated axioms and rules.

The above derivation means that “Mathematics is formally consistent” is a theorem in Classical Direct Logic.

**The above self-proof of formal consistency shows that the current common understanding that [Gödel 1931] proved “Mathematics cannot prove its own formal consistency, if it is formally consistent” is inaccurate.<sup>57</sup>**

## Mathematics Self Proves that it is Open.

Mathematics proves that it is open in the sense that it can prove that its theorems cannot be computationally enumerated by a provably total procedure:

**Theorem**  $\vdash$  Mathematics is Open, *i.e.*,

$\vdash \neg$ TheoremsEnumerableByProvableTotalProcedure

Proof.<sup>58</sup>

Suppose to obtain a contradiction that

TheoremsEnumerableByProvableTotalProcedure

Then by the definition of

TheoremsEnumerableByProvableTotalProcedure

Consequently,

$\vdash$ TheoremsEnumerator:  $[N] \rightarrow_1$  *Proposition*

such that

- $\forall [p: \textit{Proposition}] (\vdash p) \Rightarrow \exists [i: N] \text{TheoremsEnumerator} \cdot [i] = p$

A subset of the theorems enumerated by TheoremsEnumerator are those stating that certain real numbers are provably computable. Consequently, there is a provably deterministic total procedure

ProvablyComputableR\_Enumerator:  $([N] \rightarrow_1 \textit{ProvablyComputableR}_{(0,1)})$

which enumerates provably computable real numbers:

- Total[ProvablyComputableR\_Enumerator]
- $\forall [i: N] (\text{ProvablyComputableR_Enumerator} \cdot [i]): \textit{ProvablyComputableR}_{(0,1)}$
- $\forall [r: \textit{ProvablyComputableR}_{(0,1)}]$

$\exists [i: N] \text{ProvablyComputableR_Enumerator} \cdot [i] = r$

ProvablyTotalEnumerator can be used to implement the provably deterministic total procedure

$\vdash$ Diagonal:  $([N] \rightarrow_1 \textit{Boolean})$  as follows:

Diagonal  $\cdot [i] \equiv 1 - (\text{ProvablyComputableR_Enumerator} \cdot [i]) \cdot [i]$

Consequently:

- Diagonal:  $\textit{ProvablyComputableR}_{(0,1)}$  because it is the deterministic composition of provably total deterministic procedures.
- $\neg$ Diagonal:  $\textit{ProvablyComputableR}_{(0,1)}$  because Diagonal differs from every provably computable real number enumerated by ProvablyComputableR\_Enumerator.

The above contradiction completes the proof.

**Some but not all of the theorems of Mathematics can be computationally enumerated.**

[Franzén 2004] argued that Mathematics is inexhaustible because of inferential undecidability of mathematical theories. The above theorem that Mathematics is open provides another independent argument for the inexhaustibility of Mathematics.

**Conclusion**

Strong Types are extremely important in Direct Logic because they block all know paradoxes.

Information Invariance is a fundamental technical goal of logic consisting of the following:

1. *Soundness of inference*: information is not increased by inference
2. *Completeness of inference*: all information that necessarily holds can be inferred.

Computer Science needs a rigorous foundation for all of mathematics that enables computers to carry out all reasoning without human intervention.<sup>59</sup> [Russell 1925] attempted basing foundations entirely on types, but foundered on the issue of being expressive enough to carry to some common mathematical reasoning. [Church 1932, 1933] attempted basing foundations entirely on untyped higher-order functions, but foundered because it was shown to be inconsistent [Kleene and Rosser 1935]. Presently, Isabelle [Paulson 1989] and Coq [Coquand and Huet 1986] are founded on types and do not allow theories to reason about themselves. Classical Direct Logic is a foundation for all of mathematical reasoning based on strong types (to provide grounding for concepts) that allows general inference about reasoning.

[Gödel 1931] claimed inferential undecidability<sup>60</sup> results for mathematics using the proposition *ImUnprovable* In opposition to Wittgenstein's correct argument his proposition leads to contradictions in mathematics, Gödel claimed that the results of [Gödel 1931] were for *1stOrderDedekindPeano*. However, 1<sup>st</sup> order theories are not a suitable foundation for Computer Science for reasons explained elsewhere in this article.



Following [Russell 1925, and Church 1932-1933], Direct Logic was developed and then investigated propositions with results below.

Formalization of Wittgenstein's proof that Gödel's proposition *I'mUnprovable* leads to contradiction in mathematics. So the consistency of mathematics had to be rescued against Gödel's proposition constructed using what [Carnap 1934] later called the “Diagonal Lemma” which is equivalent to the **Y** untyped fixed point operator on propositions. Use of the **Y** untyped fixed point operator on propositions in results of [Curry 1941] and [Löb 1955] also lead to inconsistency in mathematics. Consequently, mathematics had to be rescued against these uses of the **Y** untyped fixed point operator for propositions.

Self-proof of the formal consistency of mathematics. Consequently, mathematics had to be rescued against the claim [Gödel 1931] that mathematics cannot prove its own formal consistency. Also, it became an open problem whether mathematics proves its own formal consistency, which was resolved by the author discovering an amazing simple proof.<sup>61</sup> A solution is to require strongly typed mathematics to bar use of the **Y** untyped fixed point operator for propositions.<sup>62</sup> However, some theoreticians have very reluctant to accept the solution.

According to [Dawson 2006]:<sup>63</sup>

- *Gödel's results altered the mathematical landscape, but they did **not** “produce a debacle”.*
- *There is **less** controversy today over mathematical foundations than there was **before** Gödel's work.*

However, [Gödel 1931] has produced a controversy of a very different kind from the one discussed by Dawson:

- The common understanding that mathematics cannot prove its own formal consistency<sup>64</sup> has been disproved.
- Consequently, [Gödel 1931] has now led to increased controversy over mathematical foundations.

Intelligent Applications need to use higher order logic because moderately strong theories of 1<sup>st</sup> order logic are inconsistent. Categorical higher order theories of Natural Numbers, Reals, and Actors are inferentially complete and inferentially decidable.

Although theorems of mathematical theories in higher order logic are not computationally enumerable, proof checking is computationally decidable. Direct Logic with strong types categorically axiomatize up to a mathematical theory **T**

for the model  $M$  for each of the following models: Natural Numbers, Real Numbers, Computable Procedures, and Actors as follows:

- **Indiscernibility for theory  $T$ :**

$$\forall [x_1, x_2: M] i=j \Leftrightarrow \forall [P: T^M] P[x_1] \Leftrightarrow P[x_2]$$

- **Instance Adequacy of  $T$ :**

$$\forall [P: T^M] (\forall [x: M] \vdash_T P[x]) \Leftrightarrow \vdash_T \forall [x: M] P[x]$$

- **$T$  is categorical for  $M$ :**

$$\vdash_T \forall [X: Type \langle T \rangle] T \langle X \rangle \Leftrightarrow \text{UniquelyIsomorphic}[X, M]$$

- **$T$  proves its own formal consistency**

$$\vdash_T (\neg \exists [\Psi: T] \vdash_T \Psi \wedge \neg \Psi)$$

- **A proposition is true if and only if it is provable in  $T$**

$$\forall [\Psi: T] (\models_M \Psi) \Leftrightarrow (\vdash_T \Psi)$$

- **$T$  is inferentially decidable**

$$\forall [\Psi: T] (\vdash_T \Psi) \vee (\vdash_T \neg \Psi)$$

- **$\vdash_T \Psi$  is computationally undecidable for  $\Psi: T$**

- **$\vdash_T^p \Psi$  is computationally decidable for  $p: \text{ProofChecker} \langle T \rangle$  and  $\Psi: T$**

The development of Direct Logic has strengthened the position of working mathematicians as follows:<sup>65</sup>

- Allowing freedom from the philosophical dogma of the 1<sup>st</sup> Order Thesis
- Providing usable strong types for all of Mathematics that provides theories that have categorical models
- Allowing theories to freely reason about theories
- Providing Inconsistency Robust Direct Logic for safely reasoning about theories of practice that are (of necessity) pervasively inconsistent.

## Acknowledgements

Tom Costello, Eric Martin, Per Stenstrom, and Johan van Benthem made very helpful comments and suggestions. Interactions with John Woods were very helpful in developing a resolution to Church's Paradox. Conversations with Gordon Plotkin were helpful and his suggestions led to the introduction of the

fixed point operator in the categorical theory of the lambda calculus. Michael Beeson suggested a clarification in the argument of Church's Paradox. Hendrik Boom provided an excellent critique, which resulted in a fundamental reorganization. Wilfried Sieg provided information about provability in 1<sup>st</sup> order logic. John Woods, John Perry, and two anonymous referees provided excellent comments and suggestions that materially improved this article. Michael Beeson pointed out that I needed to use the terminology "proof checker."

### **Bibliography**

- Anthony Anderson and Michael Zelëny (editors). *Logic, Meaning and Computation: Essays in Memory of Alonzo Church* Springer. 2002.
- Andrea Asperti, Herman Geuvers, Raja Natarajan. *Social processes, program verification and all that* "Mathematical Structures in Computer Science" Cambridge University Press. 2009.
- Jeremy Avigad and John Harrison. *Formally Verified Mathematics*. CACM. April 2014.
- Steve Awodey and Erich Reck. *Completeness and Categoricity. Parts I and II: Nineteenth-century Axiomatics to Twentieth-century Metalogic*. History and Philosophy of Logic. Vol. 23. 2002.
- Steve Awodey, Álvaro Pelayo, and Michael A. Warren. *Voevodsky's Univalence Axiom in Homotopy Type Theory* Notices of AMS. October 2013.
- Jon Barwise. *Model-Theoretic Logics: Background and Aims* in "Model Theoretic Logics" Springer-Verlag. 1985.
- Francesco Berto. *The Gödel Paradox and Wittgenstein's Reasons* Philosophia Mathematica. February, 2009.
- Andrey Bovykin. *Brief introduction to unprovability*. Logic Colloquium 2006. Lecture Notes in Logic 2009.
- Cesare Burali-Forti. *Una questione sui numeri transfiniti* Rendiconti del Circolo Matematico di Palermo. 1897.
- John Burgess. *Rigor and Structure* Oxford University Press. 2015.
- Andrea Cantini and Riccardo Bruni. *Paradoxes and Contemporary Logic* Stanford Encyclopedia of Philosophy. February 22, 2017.
- Georg Cantor. *Ueber eine elementare Frage der Mannigfaltigkeitslehre* Jahresbericht der Deutschen Mathematiker-Vereinigung. 1891
- Carlo Cellucci "Gödel's Incompleteness Theorem and the Philosophy of Open Systems" *Kurt Gödel: Actes du Colloque, Neuchâtel 13-14 juin 1991*, Travaux de logique N. 7, Centre de Recherches Sémiologiques, University de Neuchâtel. <http://w3.uniroma1.it/cellucci/documents/Goedel.pdf>
- Gregory Chaitin Interview in *Dangerous Knowledge* BBC4 documentary. 2007.
- Alan Chalmers. "What is this thing called science?" Open University Press. 1999.

- Haskell Curry. "Some Aspects of the Problem of Mathematical Rigor" *Bulletin of the American Mathematical Society* Vol. 4. 1941.
- Alonzo Church. *The Richard Paradox*. Proceedings of American Mathematical Society. Vol. 41. No. 6. 1934.
- Alonzo Church. *An unsolvable problem of elementary number theory* Bulletin of the American Mathematical Society 19, May, 1935. American Journal of Mathematics, 58. 1936,
- Alonzo Church: *A Formulation of the Simple Theory of Types*, Journal of Symbolic Logic. vol. 5. 1940.
- Alonzo Church. *Introduction to Mathematical Logic* Princeton University Press. 1956.
- Will Clinger. *Foundations of Actor Semantics* MIT Mathematics Doctoral Dissertation. June 1981.
- Thierry Coquand and Gérard Huet: *The calculus of constructions*. Technical Report 530, INRIA, Centre de Rocquencourt, 1986.
- John Corcoran. *Gaps between logical theory and mathematical practice* in The methodological unity of science. 1973.
- John Corcoran. *Categoricity*. History and Philosophy of Logic. Vol. 1. 1980
- John Corcoran. *Second-order Logic*. Logic, Meaning and Computation. Kluwer. 2001.
- John Dawson. *Shaken Foundations or Groundbreaking Realignment? A Centennial Assessment of Kurt Gödel's Impact on Logic, Mathematics, and Computer Science* FLOC'06.
- Richard Dedekind (1888) "What are and what should the numbers be?" (Translation in *From Kant to Hilbert: A Source Book in the Foundations of Mathematics*. Oxford University Press. 1996) Braunschweig.
- Freeman Dyson. *Heretical Thoughts about Science and Society* Boston University. November 1, 2005.
- Heinz-Dieter Ebbinghaus. *Ernst Zermelo: An Approach to His Life and Work* Springer. 2007.
- Patrik Eklund, M. Angeles Galan, Robert Helgesson, and Jari Kortelainen. *Fuzzy Terms* Fuzzy Sets and Systems. 256. 2014.
- Erwin Engeler. *Algebras and Combinators* Algebra Universalis. 1981.
- Solomon Feferman. "Axioms for determinateness and truth" *Review of Symbolic Logic*. 2008.
- Mike Genesereth and Eric Kao. *The Herbrand Manifesto Thinking Inside the Box*. Rule ML. August 2-5, 2015.
- Jean-Yves Girard. *Interprétation fonctionnelle et Élimination des coupure de l'arithmétique d'ordre supérieur* 1972

- Kurt Gödel (1931) “On formally undecidable propositions of *Principia Mathematica*” in *A Source Book in Mathematical Logic, 1879-1931*. Translated by Jean van Heijenoort. Harvard Univ. Press. 1967.
- G.H. Hardy. *A Mathematician’s Apology* Cambridge University Press, 1992.
- Richard Heck. *Logicism, Ontology, and the Epistemology of Second-Order Logic* in *Being Necessary: Themes of Ontology and Modality from the Work of Bob Hale*. Oxford University Press. 2018.
- Carl Hewitt. *Planner: A Language for Proving Theorems in Robots* IJCAI. 1969.
- Carl Hewitt. “Procedural Embedding of Knowledge In Planner” *IJCAI* 1971.
- Carl Hewitt and John Woods assisted by Jane Spurr, editors. *Inconsistency Robustness*. College Publications. 2015.
- Carl Hewitt. 2015a. *Actor Model of Computation for Scalable Robust Information Systems* in “Inconsistency Robustness” College Publications. 2015.
- Carl Hewitt. 2015b. *ActorScript™ extension of C#®, Java®, Objective C®, C++, JavaScript®, and SystemVerilog using iAdaptive™ concurrency* in *Inconsistency Robustness*. College Publications. 2015.
- Carl Hewitt. 2015c. *Inconsistency Robustness in Logic Programs* in “Inconsistency Robustness” College Publications. 2015.
- Carl Hewitt. 2015d. *Formalizing common sense reasoning for scalable inconsistency-robust information coordination using Direct Logic™ Reasoning and the Actor Model* in “Inconsistency Robustness” College Publications. 2015.
- Carl Hewitt. 2015e. *Inconsistency Robustness in Logic Programs* in “Inconsistency Robustness” College Publications. 2015.
- Carl Hewitt. 2015f. *Actors for CyberThings*. Erlang Keynote. YouTube. March 23, 2015.
- Carl Hewitt. 2016b. *Future Cyberdefenses Will Defeat Cyberattacks* CACM. August 2016.
- Carl Hewitt 2016c. *Islets™ Protect Sensitive IoT Information: Verifiably ending use of sensitive IoT information for mass surveillance fosters (international) commerce* SSRN WP 2836282. 2016.
- David Hilbert. *Die Grundlegung der elementaren Zahlenlehre* Mathematische Annalen. Vol. 104. 1931.
- David Hilbert and Paul Bernays. *Grundlagen der Mathematik* Springer Verlag. 1939.
- J. Roger Hindley and Jonathan Seldin.  *$\lambda$ -calculus and Combinators: An Introduction* Cambridge University Press. 2008.
- Wilfrid Hodges. *Mathematical Logic* Oxford University Press. 2007.

- Stanisław Jaśkowski. "On the Rules of Suppositions in Formal Logic" *Studia Logica* 1, 1934. (reprinted in: *Polish logic 1920-1939*, Oxford University Press, 1967.
- Eric Kao. "Proof by self-refutation and excluded middle lead to explosion" in "Inconsistency Robustness" College Publications. 2015..
- Morris Kline. *Mathematical thought from ancient to modern times* Oxford University Press. 1972.
- Thomas Kuhn. *The Structure of Scientific Revolutions* University of Chicago Press. 1962.
- Imre Lakatos. *Proofs and Refutations* Cambridge University Press. 1976
- John Law. *After Method: mess in social science research* Routledge. 2004.
- Per Martin-Löf. *An intuitionistic theory of types in Twenty-Five Years of Constructive Type Theory*. Oxford University Press. 1998.
- Martin Löb. "Solution of a problem of Leon Henkin." *Journal of Symbolic Logic*. Vol. 20. 1955.
- Penelope Maddy. *What do we want a foundation to do? Comparing set-theoretic, category-theoretic, and univalent approaches* Reflections on Foundations: Univalent Foundations, Set Theory and General Thoughts. 2018.
- David Malone. *Dangerous Knowledge* BBC4 documentary. 2007. [http://www.dailymotion.com/playlist/x1cbyd\\_xSilverPhinx\\_bbc-dangerous-knowledge/1](http://www.dailymotion.com/playlist/x1cbyd_xSilverPhinx_bbc-dangerous-knowledge/1)
- Colin McLarty. *What Does it Take to Prove Fermat's Last Theorem? Grothendieck and the Logic of Number Theory* Journal of Symbolic Logic. September 2010.
- John-Jules Meyer. *Review of Inconsistency Robustness* Amazon. January, 2016.
- Ray Monk. *Bourgeois, Boshevist or anarchist? The Reception of Wittgenstein's Philosophy of Mathematics* in Wittgenstein and his interpreters. Blackwell. 2007.
- Nick Nielsen *Alternative Foundations/philosophical* February 28, 2014. <http://www.cs.nyu.edu/pipermail/fom/2014-February/017861.html>Bashar
- Francis Pelletier *A Brief History of Natural Deduction* "History and Philosophy of Logic" Vol. 20, Issue. 1, 1999.
- William Quine. *Philosophy of Logic* Prentice Hall. 1970.
- Bertrand Russell. *Letter to Gottlob Frege* 1902.
- Bertrand Russell. *Principles of Mathematics* Norton. 1903.
- Bertrand Russell. *Les paradoxes de la logique* Revue de métaphysique et de morale. 1906.
- Bertrand Russell. "Mathematical Logic as Based on the Theory of Types" *American Journal of Mathematics*. 30 (3). 1908.
- Bertrand Russell and Alfred Whitehead, *Principia Mathematica* (3 volumes). Cambridge University Press. 1910-1913.

- Arthur Schopenhauer. *Die Welt als Wille und Vorstellung* 1818. English translation in *The World as Will and Representation* Volume I, Falcon's Wing Press. 1958.
- Natarajan Shankar. *Meta-mathematics, Machines, and Gödel's Proof*. Cambridge University Press. 1994.
- Dana Scott. *Setoids/Modest Sets/PERs: Adding and Using Types with a Type-free  $\lambda$ -Calculus* Domains XII. August 2015.
- Peter Scotch and Ray Jennings. *On Detonating* in Paraconsistent Logic. Springer Verlag. 1989.
- Stewart Shapiro. *Foundations without Foundationalism: A Case for Second-Order Logic* Oxford University Press. 1991.
- Stephen Simpson *Nonprovability of certain combinatorial properties of finite trees* in *Studies in Logic and the Foundations of Mathematics*. North-Holland. 1985.
- Alfred Tarski *Introduction to Logic* Oxford University Press. 1940 (and many subsequent editions).
- Michael Thau. The  $\omega$ -Rule *Studia Logica*. Vol. 51, No. 2. 1992.
- R. Gregory Taylor. *Zermelo's Cantorian Theory of Systems of Infinitely Long Propositions* *Bulletin of Symbolic Logic* December, 2002.
- Rineke Verbrugge *Provability Logic* The Stanford Encyclopedia of Philosophy. 2010.
- Rene Vestergaard. *Structural Induction and the  $\lambda$ -Calculus* RIMS. Kyoto University. 2005
- Ludwig Wittgenstein. 1956. *Bemerkungen über die Grundlagen der Mathematik/Remarks on the Foundations of Mathematics, Revised Edition* Basil Blackwell. 1978
- Hao Wang *A Logical Journey, From Gödel to Philosophy* MIT Press. 1974.
- Eugene Wigner. *The unreasonable effectiveness of mathematics in the natural sciences* *Communications on Pure and Applied Mathematics*. Vol. 13. 1960.
- Andrew Wiles. *Modular elliptic curves and Fermat's Last Theorem* *Annals of Mathematics*. 141. 1995.
- John Woods. *How robust can inconsistency get?* *IfCoLoG Journal of Logics and Their Applications*. 2014.
- John Woods. *Inconsistency: Its present impacts and future prospects* *Inconsistency Robustness* 2015.
- Noson Yanofsky. *The Outer Limits of Reason* MIT Press 2013.
- Ernst Zermelo *Über Grenzzahlen und Mengenbereiche: Neue Untersuchungen über die Grundlagen der Mengenlehre* *Fundamenta mathematicae*. 1930; English translation by Michael Hallett, "On boundary numbers and domains of sets: new investigations in the foundations of set theory" *From Kant to*

- Hilbert: a Source Book in the Foundations of Mathematics*, Oxford University Press, 1996.
- Ernst Zermelo. *Über mathematische System und die Logik des Unendlichen* Forschungen and Fortschritte. Vol. 8. 1932.
- Ernst Zermelo. *Collected Works/Gesammelte Werke: Volume I/Band I - Set Theory, Miscellanea/Mengenlehre, Varia (Schriften der Mathematisch-naturwissenschaftlichen Klasse) (English and German Edition)* Springer. 2010.
- Yoni Zohar. *Reasoning Inside The Box: Gentzen Calculi for Herbrand Logics* Stanford Logic Group. June 7, 2017.



## Appendix 1. Historical Background

“The powerful (try to) insist that their statements are literal depictions of a single reality. ‘It really is that way’, they tell us. ‘There is no alternative.’ But those on the receiving end of such homilies learn to read them allegorically, these are techniques used by subordinates to read through the words of the powerful to the concealed realities that have produced them.” [Law 2004]

### *Gödel was certain*

“‘Certainty’ is far from being a sign of success; it is only a symptom of lack of imagination and conceptual poverty. It produces smug satisfaction and prevents the growth of knowledge.” [Lakatos 1976]

Paul Cohen [2006] wrote as follows of his interaction with Gödel:<sup>66</sup>

“His [Gödel's] main interest seemed to lie in discussing the ‘truth’ or ‘falsity’ of these [mathematical] questions, not merely in their undecidability. He struck me as having an almost unshakable belief in this “realist” position, which I found difficult to share. His ideas were grounded in a deep philosophical belief as to what the human mind could achieve. I greatly admired this faith in the power and beauty of Western Culture, as he put it, and would have liked to understand more deeply what were the sources of his strongly held beliefs. Through our discussions, I came closer to his point of view, although I never shared completely his ‘realist’ point of view, that all questions of Set Theory were in the final analysis, either true or false.”



Kurt Gödel

According to John von Neumann, Gödel was “the greatest logician since Aristotle.”<sup>67</sup> However, [von Neumann 1961] expressed a very different mathematical philosophy than Gödel:

“It is **not** necessarily true that the mathematical method is something absolute, which was revealed from on high, or which somehow, after we got hold of it, was evidently right and has stayed evidently right ever since.”



John von Neumann

[Gödel 1931] based incompleteness results on the thesis that mathematics necessarily has the proposition *I'mUnprovable*.

### Wittgenstein's Paradox

Wittgenstein correctly noted that Gödel's *I'mUnprovable* (such that *I'mUnprovable*  $\Leftrightarrow \neg \vdash_{\text{Russell}} \text{I'mUnprovable}$ ) infers inconsistency in mathematics:<sup>68</sup>

“Let us suppose [Gödel's writings are correct and therefore] I prove<sup>69</sup> the improbability (in Russell's system) of [Gödel's *I'mUnprovable*] P; [i.e.,  $\vdash_{\text{Russell}} \neg P$  where  $P \Leftrightarrow \neg P$ ] then by this proof I have proved P [i.e.,  $\vdash_{\text{Russell}} P$ ]. Now if this proof were one in Russell's system [i.e.,  $\vdash_{\text{Russell}} \vdash_{\text{Russell}} P$ ] — I should in this case have proved at once that it belonged [i.e.,  $\vdash_{\text{Russell}} P$ ] and did not belong [i.e.,  $\vdash_{\text{Russell}} \neg P$  because  $\neg P \Leftrightarrow \vdash_{\text{Russell}} P$ ] to Russell's system.

But there is a contradiction here! [i.e.,  $\vdash_{\text{Russell}} P$  and  $\vdash_{\text{Russell}} \neg P$ ]  
**[This] is what comes of making up such sentences.**” [emphasis added]

Wittgenstein's proof is **valid** in *Nat*, which formalizes standard mathematical practice.

According to [Monk 2007]:

“Wittgenstein hoped that his work on mathematics would have a cultural impact, that it would threaten the attitudes that prevail in logic, mathematics and the philosophies of them. On this measure it has been a spectacular failure.”

Unfortunately, recognition of the worth of Wittgenstein's work on mathematics came long after his death. For decades, many theoreticians mistakenly believed that they had been completely victorious over Wittgenstein.



Ludwig Wittgenstein

Chaitin [2007] presented the following analysis:

Gödel's proof of inferential undecidability [incompleteness] *was too superficial. It didn't get at the real heart of what was going on. It was more tantalizing than anything else. It was not a good reason for something so devastating and fundamental. It was too clever by half. It was too superficial.* [It was based on the clever construction] *I'm unprovable. So what? This doesn't give any insight how serious the problem is.*

Gödel's alleged Mathematical proposition *I'mUnprovable* comes from a nonexistent fixed point (sometimes called the Diagonal Lemma) that doesn't exist because of types. His results were for Principia Mathematica, which was intended as the foundation of all of Mathematics. Unfortunately, Principia Mathematica had some defects in its types that have been corrected in Direct Logic.

Church/Turing correctly proved inferential incompleteness (sometimes called the "First Incompleteness Theorem") without using a nonexistent "self-referential" proposition as follows:

First they proved the computation undecidability of  $\text{Halt}[p,x]$  where  $\text{Halt}[p,x]$  means that the procedure  $p$  halts on input  $x$ . By formalizing computation, it follows that  $\text{Halt}[p,x] \Leftrightarrow \neg \text{Halt}[p,x]$ . Consequently it is computational undecidable whether a proposition is a theorem.

The Church/Turing theorem and its proof are very robust. Afterward Gödel claimed more generality and that his results applied to all consistent mathematical systems that incorporate the Dedekind/Peano axioms for the natural numbers. However, when he learned of Wittgenstein's devastating proof of inconsistency,<sup>70</sup> Gödel retreated to claiming that his results were only for *1stOrderDedekindPeano*:

"Wittgenstein did not understand it [Gödel's 1931 article on Principia Mathematica] (or pretended not to understand it). He interpreted it as a kind of logical paradox, while in fact it is just the opposite, namely a mathematical theorem within an absolutely uncontroversial part of mathematics (finitary number theory or combinatorics)."<sup>71</sup>

However, Gödel engaged in historical revisionism because Wittgenstein's argument that Gödel's *I'mUnprovable* leads to inconsistency was for the higher order theory in Russell's system, which Gödel used in his famous 1931 article that Wittgenstein criticized. After Wittgenstein's criticism, Gödel retreated<sup>i</sup> to the position that his 1931 results were only for *1stOrderDedekindPeano*,

---

<sup>i</sup> without mentioning that he was retreating

which Gödel called “finitary number theory or combinatorics.” The upshot is that Gödel never acknowledged that his “self-referential” proposition<sup>i</sup> implies inconsistency in mathematics.

Retaining Gödel’s results for *I’mUnprovable* requires a very narrow and constricted approach of reducing propositions to strings for sentences and then to Gödel numbers axiomatized in *1stOrderDedekindPeano* to avoid Wittgenstein’s devastating criticism. This narrow constricted view is intolerable for computer science, which needs to reason about propositions in a more natural and flexible way using Strong Types.

Let  $\text{GödelNumber}.\text{[s]}$  be the Gödel number of  $s:\text{String}\langle 1\text{stOrderDedekindPeano}\rangle$ . The Diagonal Lemma is:

If  $F:\text{[N]}\rightarrow\text{String}\langle 1\text{stOrderDedekindPeano}\rangle$ , then there is a  $S:\text{String}\langle 1\text{stOrderDedekindPeano}\rangle$  [called a “fixed point”] such that the following is provable in *1stOrderDedekindPeano*:

$$\text{[S]} \Leftrightarrow \text{[F}.\text{[GödelNumber}.\text{[S]]}]$$

Define  $\text{Eubulides}.\text{[n]}$  to be the string formed by prefixing the character “¬” to the string with Gödel number n. By the above Diagonal Lemma, there is a fixed point *I’mFalse*:  $\text{String}\langle 1\text{stOrderDedekindPeano}\rangle$  such that the following is provable in *1stOrderDedekindPeano*:<sup>72</sup>

$$\begin{aligned} \text{[I’mFalse]} &\Leftrightarrow \text{[Eubulides}.\text{[GödelNumber}.\text{[I’mFalse]]}] \\ &\Leftrightarrow \neg \text{[I’mFalse]} \end{aligned}$$

However, Church<sup>73</sup>, Turing, and many other logicians up to the present day continued to endorse Gödel’s argument based on the proposition *I’mUnprovable*.<sup>74</sup>

Although Gödel’s incompleteness results for *I’mUnprovable* have fundamental problems, the work was extremely significant in further the development of the history of metamathematics. For example, the paradoxes of Curry and Löb were developed following along Gödel’s work.

A key difference is that Direct Logic works directly with propositions as opposed to the work of Gödel, Curry, and Löb, which was based on 1<sup>st</sup> order theories with propositions from sentence strings coded as integers.

---

<sup>i</sup> constructed using fixed points exploiting an untyped notation for mathematics

### Attempt to Axiomatize $\mathcal{N}$ with Computationally Enumerable Theorems

$\text{Nat}_i$  described below illustrates failure in attempting to axiomatize the Natural Numbers using a theory whose theorems are computationally enumerable. The primitive of  $\text{Nat}_i$  are as follows:<sup>75</sup>

- $0: \mathcal{N}$
- $+_1: \mathcal{N}^{\mathcal{N}}$  // add 1
- $\neg: \text{Nat}_1^{\text{Nat}_1}$  // negation
- $\wedge: \text{Nat}_1^{\text{Nat}_1^2}$  // conjunction
- $\exists: \text{Nat}_1^{[\text{Type} \langle \text{Nat}_1 \rangle, \text{Nat}_1^{\text{Type} \langle \text{Nat}_1 \rangle}]}$  // existential quantifier<sup>76</sup>
- $\vdash: \text{Nat}_1^{\text{Nat}_1}$  // provability in  $\text{Nat}_i$

$\text{Nat}_i$  has the following axiom schemas where  $\lfloor s \rfloor$  is abstraction of string  $s$  as a proposition:

- Induction Schema
 
$$\forall [P: \text{String} \langle \text{Nat}_i^{\mathcal{N}} \rangle]$$

$$\vdash (\lfloor P \rfloor [0] \wedge \forall [i: \mathcal{N}] \lfloor P \rfloor [i] \Rightarrow \lfloor P \rfloor [i+1]) \Rightarrow \forall [i: \mathcal{N}] \lfloor P \rfloor [i]$$
- Instance Adequacy Schema [Hilbert 1931, Thau 1992]
 
$$\forall [P: \text{String} \langle \text{Nat}_i^{\mathcal{N}} \rangle] \vdash (\forall [i: \mathcal{N}] \vdash \lfloor P \rfloor [i]) \Rightarrow \forall [i: \mathcal{N}] \lfloor P \rfloor [i]$$

**Theorem:** Axioms and theorems of  $\text{Nat}_i$  are computationally enumerable

**Theorem:**  $\forall [\Psi: \text{Nat}_i] (\vdash \Psi) \Leftrightarrow (\vdash_{\text{Nat}_1} \Psi)$

The following defines the  $\text{Nat}_i$  provable computable real numbers between 0 and 1:

#### Definition

$$\text{Nat}_i \mathcal{R}_{(0,1)} \equiv \mathcal{R}_{(0,1)} \exists \lambda [x] \vdash x: \text{Total} \langle [N] \rightarrow_1 \text{Boolean} \rangle$$

### $Nat_1$ goes too far

Theorems of  $Nat_1$  are computationally enumerable by  $Nat_1$ TheoremsEnumerator where

$$\vdash_{Nat_1} Nat_1\text{TheoremsEnumerator}: Total \langle [N] \rightarrow_1 Theorem \langle Nat_1 \rangle \rangle$$

such that

$$\vdash_{Nat_1} \forall [\Phi: Theorem \langle Nat_1 \rangle] \exists [i: N] Nat_1\text{TheoremsEnumerator} \cdot [i] = \Phi$$

Consequently, there is a  $Nat_1$  provably total procedure  $Nat_1$ ProvablyComputableR<sub>[0,1]</sub> Enumerator such that

$$\forall [r: Nat_1\mathcal{R}_{[0,1]}] \Rightarrow \exists [i: N] Nat_1\text{ProvablyComputableR}_{[0,1]}\text{Enumerator} \cdot [i] = r$$

also

$$\forall [i: N] \Vdash Nat_1\text{ProvablyComputableR}_{[0,1]}\text{Enumerator} \cdot [i]: Nat_1\mathcal{R}_{[0,1]}$$

Therefore by  $Nat_1$  Instance Adequacy,

$$\vdash_{Nat_1} \forall [i: N] Nat_1\text{ProvablyComputableR}_{[0,1]}\text{Enumerator} \cdot [i]: Nat_1\mathcal{R}_{[0,1]}$$

However, this means that

$$\vdash_{Nat_1} Nat_1\text{ProvablyComputableR}_{[0,1]}\text{Enumerator}: Total \langle [N] \rightarrow_1 Nat_1\mathcal{R}_{[0,1]} \rangle$$

$$Nat_1\text{Total} \langle F \rangle \equiv F \exists \lambda [p] \Vdash p: Total \langle F \rangle$$

$$Nat_1\text{Enumerable} \equiv$$

$$Nat_1\text{Total} \langle [N] \rightarrow_1 Nat_1\mathcal{R}_{[0,1]} \rangle \exists \lambda [f] \forall [r: Nat_1\mathcal{R}_{[0,1]}] \Rightarrow \exists [i: N] f \cdot [i] = r$$

**Theorem: The 1<sup>st</sup> order theory  $\text{Nat}_1$  is inconsistent<sup>77</sup>**

1.  $\text{Nat}_1\mathcal{R}_{[0,1]}: \text{Nat}_1\text{Enumerable}$
2.  $\neg \text{Nat}_1\mathcal{R}_{[0,1]}: \text{Nat}_1\text{Enumerable}$

**Proof:**

Suppose to obtain a contradiction that

$\text{Nat}_1\mathcal{R}_{[0,1]}: \text{Nat}_1\text{Enumerable}$


Define the following procedure:

$$\text{Diagonal}_{\bullet}[i] \equiv 1 - (\text{Nat}_1\text{ProvablyComputableR}_{[0,1]}\text{Enumerator}_{\bullet}[i])_{\bullet}[i]$$

Consequently:

- $\vdash_{\text{Nat}_1} \text{Diagonal}: \text{Nat}_1\mathcal{R}_{[0,1]}$  because Diagonal is the deterministic composition of  $\text{Nat}_1$  provably total deterministic procedures.
- $\vdash_{\text{Nat}_1} \neg \text{Diagonal}: \text{Nat}_1\mathcal{R}_{[0,1]}$  because Diagonal differs from every  $\text{Nat}_1\mathcal{R}_{[0,1]}$  enumerated by  $\text{Nat}_1\text{ProvablyComputableR}_{[0,1]}\text{Enumerator}_{\bullet}$ .

The above contradiction completes the proof.



$$\text{Diagonal}_{\bullet}[i:N]: \text{Boolean} \equiv 1 - (\text{Nat}_1\text{ProvablyComputableR}_{[0,1]}\text{Enumerator}_{\bullet}[i])_{\bullet}[i]$$

[Church 1934] pointed out that there is no obvious way to remove the inconsistency, which means that that if  $Nat_i$  is taken to be valid mathematical theory of truths of the natural numbers then,

*“Indeed, if there is no formalization of logic as a whole, then there is no exact description of what logic is, for it in the very nature of an exact description that it implies a formalization. And if there no exact description of logic, then there is no sound basis for supposing that there is such a thing as logic.”*

After [Church 1934], logicians faced the following dilemma:

- 1<sup>st</sup> order theories cannot be powerful enough to be a foundation for Intelligent Applications lest they fall into inconsistency because of Church’s Paradox.
- 2<sup>nd</sup> order theories contravene the philosophical doctrine that theorems must be computationally enumerable.



Alonzo Church



## There Is No 1<sup>st</sup> Order Theory That Axiomatizes Actors


By contrast with the nondeterministic lambda calculus and pure Logic Programs, there is an always-halting Actor Unbounded that when sent a **start[]** message can compute an integer of unbounded size. This is accomplished by creating a counter with the following variables:

- **count** initially 0
- **continue** initially **True**

and concurrently sending it both a **stop[]** message and a **go[]** message such that:

- When a **go[]** message is received:
  1. if **continue** is **True**, increment **count** by 1 and return the result of sending this counter a **go[]** message.
  2. if **continue** is **False**, return **Void**
- When a **stop[]** message is received, return **count** and set **continue** to **False** for the next message received.

By the Actor Model of Computation, the above Actor will eventually receive the **stop[]** message and return an unbounded number.



The following hold:


- $\forall [t:N] \not\models_{Actor} \text{ResponseBefore}[t]$  // unbounded response time
- $\forall [t_1, t_2:N] t_1 < t_2 \wedge \text{ResponseBefore}[t_1] \Rightarrow \text{ResponseBefore}[t_2]$
- $\models_{Actor} \exists [t:N] \text{ResponseBefore}[t]$

**Theorem:** There is no 1<sup>st</sup> order theory that axiomatises *Actor*.

**Proof:** Every 1<sup>st</sup> order theory is compact meaning that every inconsistent set of sentences has a finite inconsistent subset.

Define  $\Sigma \equiv \{ \neg \text{ResponseBefore}[t] \mid i:N \}$ .  $\Sigma$  is inconsistent because

$\models_{Actor} \exists [t:N] \text{ResponseBefore}[t]$ . However, every finite subset of  $\Sigma$  is consistent, which contradicts compactness.



**Discussion**

Church’s Paradox and other paradoxes raise a number of issues that can be addressed by requiring mathematics to be strongly typed and using higher order logic as follows:

1. Requiring Mathematics to be strongly typed using so that
  - Mathematics self proves that it is “open” in the sense that theorems are not computationally enumerable.<sup>78</sup>
  - Mathematics self proves that it is *formally* consistent.<sup>79</sup>
  - Strong mathematical theories for Natural Numbers, Ordinals, Set Theory, the Lambda Calculus, Actors, etc. are inferentially decidable, meaning that every true proposition is provable and every proposition is either provable or disprovable. Furthermore, theorems of these theories are not enumerable by a provably total procedure.
2. It was initially thought that mathematics could be based just on character strings. Then diagonalization was discovered and things haven’t been the same since. The string for the general 1<sup>st</sup> order non-categorical induction

*schema* is as follows for each P:  $String \langle Proposition \langle 1 \rangle^N \rangle$ :

$$([P] [0] \wedge \forall [i:N] [P] [i] \Rightarrow [P] [i+1]) \Rightarrow \forall [i:N] [P] [i]$$

which has countably many 1<sup>st</sup> order propositions as instances that are abstracted from the countably many character strings of type  $String \langle Proposition \langle 1 \rangle \rangle$  and which differs fundamentally from the character string for the *more general* 2<sup>nd</sup> order categorical induction *axiom*, which is as follows:<sup>80</sup>

$$\forall [P: Proposition \langle 1 \rangle^N] (P[0] \wedge \forall [i:N] P[i] \Rightarrow P[i+1]) \Rightarrow \forall [i:N] P[i]$$

Although the theory *Nat* has only *finitely* many axioms, the above string abstracted as a proposition has *uncountably* many 1<sup>st</sup> order propositions as instances.<sup>81</sup> In this way, *Nat* differs fundamentally from a 1<sup>st</sup> order theory because, being uncountable, *not all* instances of the *Nat* induction axiom can be obtained by abstraction from character strings. Proofs abstracted from character strings for the axioms of the natural numbers can be computationally enumerated and are valid proofs in *Nat*, but this does not enumerate *all* of the proofs of *Nat* ! What is to be made of the *uncountable* number of theorems of *Nat* whose proofs cannot be written down in text?



Ernst Zermelo

Zermelo suggested that the [Godel 1931] incompleteness results relied on an overly restrictive conception of quantification and proof. He took it as crucial that true proposition of set theory must be “provable” and that the validity of a proof can reasonably be decided. To this end, he developed an infinitary logic but did not carry it very far. In 1935 he was dismissed for failing to salute Hitler and his proposal was not pursued by anyone else until, perhaps, the revival of infinitary languages in the 1950s. [Shapiro 1991]

#### **Additional limitations of 1<sup>st</sup> order theories**

“[F]rom the 1950s onward, classical mathematics had just one deductive system, namely, first-order Zermelo-Fraenkel Set Theory with [the Axiom of] Choice ...”

[Hodges 2007]

“By this it appears how necessary it is for nay man that aspires to true knowledge to examine the definitions of former authors; and either to correct them, where they are negligently set down, or to make them himself. For the errors of definitions multiply themselves, according as the reckoning proceeds, and lead men into absurdities, which at last they see, but cannot avoid, without reckoning anew from the beginning; in which lies the foundation of their errors...”

[Hobbes *Leviathan*, Chapter 4]<sup>82</sup>

A 1<sup>st</sup> order theory is very weak. For example, a 1<sup>st</sup> order theory is incapable of characterizing even the natural numbers, *i.e.*, there are infinite integers in models of every 1<sup>st</sup> order axiomatization of the natural numbers. Furthermore, there are infinitesimal real numbers in models of every 1<sup>st</sup> order axiomatization of the real numbers.<sup>83</sup> Of course, infinite integers and infinitesimal reals are monsters that must be banned from the mathematical foundations of Computer Science.

However, some theoreticians have found 1<sup>st</sup> order theory to be useful for their careers because it is weak enough that they can prove theorems about 1<sup>st</sup> order axiomatizations whereas they cannot prove such theorems about stronger practical higher order systems, *e.g.*, Classical Direct Logic.<sup>84</sup>

Zermelo considered the 1<sup>st</sup> Order Thesis to be a mathematical “hoax” because it necessarily allowed unintended models of axioms.<sup>85</sup>

[Barwise 1985] critiqued the 1<sup>st</sup> Order Thesis that mathematical foundations should be restricted to 1<sup>st</sup> order theories as follows:

*The reasons for the widespread, often uncritical acceptance of the first-order thesis are numerous. The first-order thesis ... confuses the subject matter of logic with one of its tools. First-order language is just an artificial language structured to help investigate logic, much as a telescope is a tool constructed to help study heavenly bodies. From the perspective of the mathematics in the street, the first-order thesis is like the claim that astronomy is the study of the telescope.*<sup>86</sup>



Jon Barwise

Computer Science is making increasing use of Model Analysis<sup>87</sup> in the sense of analyzing relationships among the following:

- concurrent programs and their Actor Model denotations
- domain axiom systems and computations on these domains

In Computer Science, it is important that the natural numbers be axiomatized in a way that does not allow non-numbers (e.g. infinite ones) in models of the axioms.

**Theorem:** If  $\mathcal{N}$  is a model of a 1<sup>st</sup> order axiomatization  $\mathbf{T}$ , then  $\mathbf{T}$  has a model  $\mathcal{M}$  with an infinite integer.

Proof: The model  $\mathcal{M}$  is constructed as an extension of  $\mathcal{N}$  by adding a new element  $\infty$  with the following atomic relationships:

$$\{\neg \infty < \infty\} \cup \{m < \infty \mid m: \mathcal{N}\}$$

It can be shown that  $\mathcal{M}$  is a model of  $\mathbf{T}$  with an infinite integer  $\infty$ .

The infinite integer  $\infty$  is a monster that must be banned from the mathematical foundations of Computer Science.

**Theorem:** If  $\mathcal{R}$  is a model of a 1<sup>st</sup> order axiomatization  $\mathbf{T}$ , then  $\mathbf{T}$  has a model  $\mathcal{M}$  with an infinitesimal.

Proof: The model  $\mathcal{M}$  is constructed as an extension of  $\mathcal{R}$  by adding a new element  $\infty$  with the following atomic relationships:

$$\{\neg \infty < \infty\} \cup \{m < \infty \mid m: \mathcal{R}\}$$

Defining  $\varepsilon$  to be  $\frac{1}{\infty}$ , it follows that  $\forall [r: \mathcal{R}] 0 < \varepsilon < \frac{1}{r}$ . It can be shown that  $\mathcal{M}$  is a model of  $\mathbf{T}$  with an infinitesimal  $\varepsilon$ , which is a monster that must be banned from the mathematical foundations of Computer Science.

On the other hand, since it is not limited to 1<sup>st</sup> order propositions, Classical Direct Logic characterizes structures such as natural numbers and real numbers up to isomorphism.<sup>88</sup>

There are many theorems of **Nat** that cannot be proved from 1<sup>st</sup> order axioms [Goodstein 1944, Simpson 1985, Wiles 1995, Bovykin 2009, McLarty 2010].

### **Unbounded Nondeterminism**

Of greater practical import, 1<sup>st</sup> order theory is *not* a suitable foundation for the Internet of Things in which specifications require a device respond to a request.<sup>89</sup>

The specification that a computer responds can be formalized as follows:

$\exists[i:\mathcal{N}] \text{ResponseBefore}[i]$ . However, the specification cannot be proved in a 1<sup>st</sup> order theory.

Proof: In order to obtain a contradiction, suppose that it is possible to prove in a 1<sup>st</sup> order theory  $\exists[i:\mathcal{N}] \text{ResponseBefore}[i]$ . Therefore the infinite set of propositions  $\{\neg \text{ResponseBefore}[i] \mid i:\mathcal{N}\}$  is inconsistent. By the compactness theorem of 1<sup>st</sup> order theory, it follows that there is finite subset of the set of propositions that is inconsistent. But this is a contradiction, because all the finite subsets are consistent since the amount of time before a server responds is unbounded, that is,

$\nexists[i:\mathcal{N}] \vdash \text{ResponseBefore}[i]$ .

However, the above specification axiom does *not* compute any actual output! Instead the above axiom simply asserts the *existence* of unbounded outputs for **Unbounded**. $\blacksquare$

**Theorem.** The nondeterministic function defined by Unbounded (earlier in this article) cannot be implemented by a nondeterministic Logic Program<sup>90</sup> or a nondeterministic Turing Machine:

*Proof.*<sup>91</sup>

*The task of a nondeterministic Logic Program P is to start with an initial set of axioms and prove  $\text{Output}=\text{n}$  for some numeral n. Now the set of proofs of P starting from initial axioms will form a tree. The branching points will correspond to the nondeterministic choice points in the program and the choices as to which rules of inference to apply. Since there are always only finitely many alternatives at each choice point, the branching factor of the tree is always finite. Now König's lemma says that if every branch of a finitary tree is finite, then so is the tree itself. In the present case this means that if every proof of P proves  $\text{Output}=\text{n}$  for some numeral n, then there are only finitely many proofs. So if P nondeterministically proves  $\text{Output}=\text{n}$  for every numeral n, it must contain a nonterminating computation in which it does not prove  $\text{Output}=\text{n}$  for some numeral n.*

The following arguments support unbounded nondeterminism in the Actor model [Hewitt 1985]:

- There is no bound that can be placed on how long it takes a computational circuit called an *arbiter* to settle. Arbiters are used in computers to deal with the circumstance that computer clocks operate asynchronously with input from outside, e.g., keyboard input, disk access, network input, etc. So it could take an unbounded time for a message sent to a computer to be received and in the meantime the computer could traverse an unbounded number of states.
- Electronic mail enables unbounded nondeterminism since mail can be stored on servers indefinitely before being delivered.
- Communication links to servers on the Internet can be out of service indefinitely

1<sup>st</sup> order theory is **not** a suitable mathematical foundation for Intelligent Applications for the Internet of Things.

As a foundation of mathematics for Computer Science, Classical Direct Logic provides categorical axiomatizations<sup>92</sup> of numbers (integer and real), sets, lists, trees, graphs, etc. which can be used in arbitrary mathematical theories including

theories for categories, large cardinals, etc. These various theories might have “monsters” of various kinds. However, these monsters should not be imported into models of computation used in Computer Science.

Computer Science needs *stronger* systems than provided by 1<sup>st</sup> order theory in order to weed out unwanted models. In this regard, Computer Science doesn't have a problem computing with “infinite” objects (*i.e.* Actors) such as  $\pi$  and uncountable sets such as the set of real numbers  $\text{Set}\langle\mathcal{R}\rangle$ . However, the mathematical foundation of Computer Science is very different from the general philosophy of mathematics in which the infinite integers and infinitesimal reals allowed by models of 1<sup>st</sup> order theories may be of some interest. Of course, it is always possible to have special theories that are *not* part of the foundations with infinite integers, infinitesimal reals, unicorns, *etc.*<sup>93</sup>

Of course some problems are theoretically not computable. However, even in these cases, it is often possible to compute approximations and cases of practical interest.<sup>94</sup>

The mathematical foundation of Computer Science is very different from the general philosophy of mathematics in which infinite integers and infinitesimal reals may be of some interest. Of course, it is always possible to have special theories with infinite integers, infinitesimal reals, unicorns, *etc.*



## Appendix 2. Appendix 1. More Categorical Mathematical Theories

### Theory of Nondeterministic Lambda Calculus ( $Lam\langle t \rangle$ ) for the Nondeterministic Lambda Procedures $\Lambda\langle t \rangle$

**Definition:**  $Functional\langle t_1, t_2 \rangle \equiv [[t_1] \rightarrow t_2] \rightarrow ([t_1] \rightarrow t_2)$

#### Theory $Lam\langle t \rangle$

In addition to Lambda Induction (below), the theory  $Lam\langle t \rangle$  for a type  $t$  and  $t_1, t_2: Type\langle Lam\langle t \rangle \rangle$  has the following axioms:<sup>95</sup>

- **Base**

$$\forall [x:t] x:\Lambda\langle t \rangle$$

- **Composition**

$$\forall [x:t_1, f:([t_1] \rightarrow t_2)] f \bullet [x]:t_2$$

$$\forall [x_1:t_1, x_2:t_2] [x_1, x_2]:[t_1, t_2]$$

$$\forall [x_1, x_2:\Lambda\langle t \rangle] [x_1, x_2]:\Lambda\langle t \rangle$$

- **Equality**

$$\forall [f_1, f_2:([t_1] \rightarrow t_2)] f_1 = f_2 \Leftrightarrow \forall [x:t_1] f_1 \bullet [x] = f_2 \bullet [x]$$

$$\forall [f:([t_1] \rightarrow t_2)] f = \lambda [x:t_1] f \bullet [x]^{96}$$

- **Primitives**

$$\forall [x:\Lambda\langle t \rangle] \text{Identity}\langle t \rangle \bullet [x] = x$$

$$\forall [x_1, x_2:\Lambda\langle t \rangle] \text{1st}\langle t_1, t_2 \rangle \bullet [[x_1, x_2]] = x_1$$

$$\forall [x_1, x_2:\Lambda\langle t \rangle] \text{2nd}\langle t_1, t_2 \rangle \bullet [[x_1, x_2]] = x_2$$

$$[F:Functional\langle t_1, t_2 \rangle] \text{Fix}\langle t_1, t_2 \rangle \bullet [F] = F \bullet [\text{Fix}\langle t_1, t_2 \rangle \bullet [F]]^{97}$$

$$\forall [x_1, x_2:\Lambda\langle t \rangle] \text{Either}\langle t \rangle \bullet [x_1, x_2] = x_1 \vee \text{Either}\langle t \rangle \bullet [x_1, x_2] = x_2$$

Lambda Induction for  $Lam\langle t \rangle$  is as follows:<sup>98</sup>

$$\forall [P:Lam\langle t \rangle \Lambda\langle t \rangle]$$

$$(\mathbb{P}[\text{Identity}\langle t \rangle] \wedge \mathbb{P}[\text{1st}\langle t_1, t_2 \rangle] \wedge \mathbb{P}[\text{2nd}\langle t_1, t_2 \rangle]$$

$$\wedge \mathbb{P}[\text{Fix}\langle t_1, t_2 \rangle] \wedge \mathbb{P}[\text{Either}\langle t \rangle] \wedge \forall [x:t] \mathbb{P}[x]$$

$$\wedge \forall [x_1:t_1, x_2:t_2] \mathbb{P}[x_1] \wedge \mathbb{P}[x_2] \Leftrightarrow \mathbb{P}[[x_1, x_2]]$$

$$\wedge \forall [F:Functional\langle t_1, t_2 \rangle] \mathbb{P}[F] \Leftrightarrow \mathbb{P}[\text{Fix}\langle t_1, t_2 \rangle \bullet [F]]$$

$$\wedge \forall [x:t_1, f:([t_1] \rightarrow t_2)] \mathbb{P}[x] \wedge \mathbb{P}[f] \Leftrightarrow \mathbb{P}[f \bullet [x]])$$

$$\Leftrightarrow \forall [x:\Lambda\langle t \rangle] \mathbb{P}[x]$$

**Theorem. Computational Inadequacy of Nondeterministic Lambda Calculus.**

The nondeterministic lambda calculus is inadequate to implement all computable procedures.

Proof.  $F_i[j:\mathbf{N}] \equiv j > i$  **if True then** InfiniteLoop **False then**  $i$  **either**  $F_{i+1}$

For each  $i:\mathbf{N}$ ,  $F_i$  is a nondeterministic  $\lambda$  expression but  $(\text{limit}_{i:\mathbf{N}} F_i)$  **cannot** be implemented as a nondeterministic  $\lambda$  expression. However  $(\text{limit}_{i:\mathbf{N}} F_i)$ : *Actor*

**Convergence:**  $\forall [f:([t_1] \rightarrow t_2), x:t_1] f \cdot [x] \downarrow \Leftrightarrow \exists [y:t_2] f \cdot [x] = y$

**Approximation:**  $\forall [f_1, f_2:([t_1] \rightarrow t_2)] f_1 \leq f_2 \Leftrightarrow \forall [x:t_1] f_1 \cdot [x] \downarrow \Rightarrow f_1 \cdot [x] = f_2 \cdot [x]$

**Bottom:**  $\forall [f:t] \neg (\perp \triangleleft t \triangleright \cdot [f]) \downarrow$

Note:  $\forall [f:([t] \rightarrow t)] \perp \triangleleft t \triangleright \leq f$

**Monotone:**

$F$ : *Monotone*  $\triangleleft t_1, t_2 \triangleright \Leftrightarrow F$ : *Functional*  $\triangleleft t_1, t_2 \triangleright \wedge \forall [g:([t_1] \rightarrow t_2)] g \leq F \cdot [g]$

**Limit Theorem:**  $\forall [F:\text{Monotone} \triangleleft t \triangleright] F = \text{limit}_{i:\mathbf{N}_+} F^i \cdot [\perp \triangleleft t \triangleright]$ <sup>99</sup>

**Theorem:** Some nondeterministic procedures have unbounded nondeterminism<sup>100</sup>

$\exists [f:([t] \rightarrow t)] \neg f:\Lambda \triangleleft t \triangleright$

**Theorem.**<sup>101</sup>  $Lam\langle t \rangle$  is categorical with only one model up to a unique isomorphism.

Proof: Suppose that  $\mathcal{X}$  satisfies the axioms for  $Lam\langle t \rangle$ .

By lambda induction, the isomorphism  $I: \mathcal{X}^{\Lambda\langle t \rangle}$  is defined as follows:<sup>102</sup>

- $I[\mathbf{Identity}\langle t \rangle] \equiv \mathbf{Identity}_{\mathcal{X}\langle t \rangle}$
- $I[\mathbf{1st}\langle t_1, t_2 \rangle] \equiv \mathbf{1st}_{\mathcal{X}\langle t_1, t_2 \rangle}$
- $I[\mathbf{2nd}\langle t_1, t_2 \rangle] \equiv \mathbf{2nd}_{\mathcal{X}\langle t_1, t_2 \rangle}$
- $I[\mathbf{Fix}\langle t_1, t_2 \rangle] \equiv \mathbf{Fix}_{\mathcal{X}\langle t_1, t_2 \rangle}$
- $I[\mathbf{Either}\langle t \rangle] \equiv \mathbf{Either}_{\mathcal{X}\langle t \rangle}$
- $I[[x_1, x_2]] \equiv [I[x_1], I[x_2]]_{\mathcal{X}}$
- $\forall [x: t_1, f: (t_1 \rightarrow t_2)] I[f \cdot x] \equiv I[f] \cdot_{\mathcal{X}} I[x]$

$I$  is the unique isomorphism:

- $I$  is one to one
- The range of  $I$  is  $\mathcal{X}$
- $I$  is a homomorphism
- $I^{-1}: \Lambda\langle t \rangle^{\mathcal{X}}$  is a homomorphism
- $I$  is the unique isomorphism: If  $g: \mathcal{X}^{\Lambda\langle t \rangle}$  is an isomorphism, then  $g=I$

**Theorem (Model Soundness of  $Lam\langle t \rangle$ ):**  $(\vdash_{Lam\langle t \rangle} \Psi) \Leftrightarrow \vDash_{\Lambda\langle t \rangle} \Psi$

Proof: Suppose  $\vdash_{Lam\langle t \rangle} \Psi$ . The theorem immediately follows because the axioms for the theory  $Lam\langle t \rangle$  hold in the type  $\Lambda\langle t \rangle$ .

**Theorem (Indiscernibility for  $Lam\langle t \rangle$ ):**<sup>103</sup>

$$\forall [f, g: \Lambda\langle t \rangle] f=g \Leftrightarrow \forall [P: Lam\langle t \rangle^{\Lambda\langle t \rangle}] P[f] \Leftrightarrow P[g]$$

**Theorem: Inferential completeness of  $Lam\langle t \rangle$**

$$\forall [\Psi: Lam\langle t \rangle] (\vDash_{\Lambda\langle t \rangle} \Psi) \Rightarrow \vdash_{Lam\langle t \rangle} \Psi$$

**Corollary.** Equivalence of satisfiability and provability in  $Lam\langle t \rangle$ , i.e.,

$$\forall [\Psi: Lam\langle t \rangle] (\vDash_{\Lambda\langle t \rangle} \Psi) \Leftrightarrow \vdash_{Lam\langle t \rangle} \Psi$$

**Theorem.** Inferential Decidability of  $\text{Lam}\langle t \rangle$ , i.e.,

$$\forall [P: \text{Lam}\langle t \rangle^{\Delta\langle \Phi \rangle}] \\ (\vdash_{\text{Lam}\langle t \rangle} \forall [f: \Lambda\langle t \rangle] P[f]) \vee (\vdash_{\text{Lam}\langle t \rangle} \exists [f: \Lambda\langle t \rangle] \neg P[f])$$

### Weakest Preconditions

$$\text{WeakestPrecondition}[\Phi, f] \equiv \lambda [i: \mathbb{N}] \Phi[f, [i]]$$

**Theorem** Weakest Preconditions are monotonic in both arguments, i.e.,<sup>104</sup>

- $\forall [\Phi_1, \Phi_2: \text{Lam}\langle t \rangle^{\mathbb{N}}; f: ([\mathbb{N}] \rightarrow \mathbb{N})]$   
 $(\Phi_1 \Leftrightarrow \Phi_2) \Rightarrow (\text{WeakestPrecondition}[\Phi_1, f] \Leftrightarrow \text{WeakestPrecondition}[\Phi_2, f])$
- $\forall [\Phi: \text{Lam}\langle t \rangle^{\mathbb{N}}; f_1, f_2: ([\mathbb{N}] \rightarrow \mathbb{N})]$   
 $f_1 \sqsupseteq f_2 \Rightarrow (\text{WeakestPrecondition}[\Phi, f_1] \Leftrightarrow \text{WeakestPrecondition}[\Phi, f_2])$

### Theory of Reals (*Reals*)

*Reals* is strictly more powerful than the 1<sup>st</sup> order theory of *RealClosedFields*.<sup>105</sup>

### Theorem (Categoricity of *Reals*):<sup>106</sup>

If  $X$  is a type satisfying the axioms<sup>107</sup> for the real numbers *Reals*, then there is a unique isomorphism of  $X$  with  $\mathcal{R}$ .

### Theory of Ordinals ( $\mathcal{Ord}$ )

A theory of the ordinals can be axiomatized<sup>108</sup> using a 2<sup>nd</sup> order ordinal induction axiom as follows: For each order:  $N_+$  and  $P: \mathcal{Ord}^\circ$ ,

$$(\forall[\alpha: \mathcal{O}] \forall[\beta < \alpha: \mathcal{O}] P[\beta] \Rightarrow P[\alpha]) \Rightarrow \forall[\alpha: \mathcal{O}] P[\alpha]$$

In order to fill out the ordinals, the following limit axioms are included in  $\mathcal{Ord}$ :

- $\forall[\alpha: \mathcal{O}, f: \mathcal{O}^\circ] \cup_\alpha f: \mathcal{O}$
- $\forall[\alpha, \beta: \mathcal{O}; f: \mathcal{O}^\circ] \beta < \cup_\alpha f \Leftrightarrow \exists[\delta < \alpha] \beta \leq f[\delta]$
- $\forall[\alpha, \beta: \mathcal{O}; f: \mathcal{O}^\circ] (\forall[\delta < \alpha] f[\delta] \leq \beta) \Rightarrow (\cup_\alpha f) \leq \beta$

In order to guarantee that there are enough ordinals, the following axioms are also included in  $\mathcal{Ord}$ :

- $\forall[\alpha: \mathcal{O}] \omega_\alpha: \mathcal{O}$
- Definition by ordinal induction:
  1.  $\omega_0 = N$
  2.  $\omega_{\alpha+1} = \text{Boolean}^{\{\beta: \mathcal{O} \mid \beta < \omega_\alpha\}}$
  3.  $\omega_\alpha = \cup_\alpha (\lambda[\beta: \mathcal{O}] \omega_\beta)$

**Theorem** Ordinals have the following properties:

- Ordinals are well-ordered:
  - Least[ $\{\}$ ] =  $0_\circ$
  - $\forall[S: \text{Boolean}^\circ] S \neq \{\} \Rightarrow \text{Least}[S] \in S$
  - $\forall[S: \text{Boolean}^\circ] S \neq \{\} \Rightarrow \forall[\alpha \in S] \text{Least}[S] \leq \alpha$
- Reals can be well-ordered because  $\omega_1 = \mathcal{R}$

### Proof Checkers in $Ord$

$$\forall[\Psi_1, \Psi_2: Ord]$$

$$(\Psi_1 \vdash_{Ord} \Psi_2) \Leftrightarrow \exists[p: ProofChecker \langle Ord \rangle] \Psi_1 \vdash_{\frac{p}{Ord}} \Psi_2$$

Proof checking in  $Ord$  is **computationally decidable**.

$$\forall[\Psi_1, \Psi_2: Ord, p: ProofChecker \langle Ord \rangle]$$

$$(\Psi_1 \vdash_{\frac{p}{Ord}} \Psi_2) \Leftrightarrow p.[\Psi_1, \Psi_2] = \mathbf{True}$$

Example of a proof checker with a nondenumerable domain:

The  $+_1$  of  $Ord$  checker below has a nondenumerable domain (including  $Ord$  and  $\mathcal{O}$ ) even though  $+_1OrdChecker$  is an effectively computable procedure.

$$+_1OrdChecker: \langle [Ord, Ord] \rightarrow_1 Boolean$$

$$+_1OrdChecker.[\Psi_1, \Psi_2] \equiv \Psi_1 \text{ if } (\alpha: \mathcal{O}) \text{ then } s_2 = (\alpha + 1: \mathcal{O}), \text{ else False}$$

$$// \text{ If } s_1 \text{ is } \alpha: \mathcal{O}, \text{ then } s_2 = (\alpha + 1: \mathcal{O}), \text{ otherwise False}$$

$$+_1OrdChecker: ProofChecker \langle Ord \rangle$$

$$\forall[\alpha: \mathcal{O}] (\alpha: \mathcal{O}) \vdash_{\frac{+_1OrdChecker}{Ord}} (\alpha + 1: \mathcal{O})$$

### Theorem (Categoricity of $Ord$ ):

If  $\mathbf{X}$  be a type satisfying the axioms the theory of the ordinals  $Ord$ , then there is a unique isomorphism with  $\mathcal{O}$ .<sup>109</sup>

### Theorem (Model Soundness of $Ord$ ): $(\vdash_{Ord} \Psi) \Rightarrow \models_{\mathcal{O}} \Psi$

Proof: Suppose  $\vdash_{Ord} \Psi$ . The theorem immediately follows because the axioms for the theory  $Ord$  hold in the type  $\mathcal{O}$ .

### Theorem (Indiscernibility for $Ord$ ):<sup>110</sup>

$$\forall[\alpha, \beta: \mathcal{O}] \alpha = \beta \Leftrightarrow \forall[P: Ord^{\mathcal{O}}] P[\alpha] \Leftrightarrow P[\beta]$$

### Theorem: Inferential completeness of $Ord$

$$\forall[\Psi: Ord] (\models_{\mathcal{O}} \Psi) \Rightarrow \vdash_{Ord} \Psi$$

**Corollary.** Equivalence of satisfiability and provability in  $Ord$ , i.e.,

$$\forall[\Psi:Ord] (\models_{\circ} \Psi) \Leftrightarrow \vdash_{Ord} \Psi$$

**Theorem.** Inferential Decidability of  $Ord$ , i.e.,

$$\forall[\Psi:Ord^{\circ}] (\vdash_{Ord} \Psi) \vee \vdash_{Ord} \neg\Psi$$

Proof.  $\forall[\Psi:Ord] (\vdash_{Ord} \Psi) \Leftrightarrow \models_{\circ} \Psi$

Theorem follows from Equivalence of satisfiability and provability in **Ord**.

**Type Choice**

$$\forall[f:(Boolean^{t_1})^{t_2}] \exists[\text{choice}:t_1^{t_2}] \forall[x:t_1] f[x] \neq \{\} \Rightarrow \text{choice}[x] \in f[x]$$

**Theory  $SetTheory\langle t \rangle$  defined using strong parameterized types**

The type  $Set\langle t \rangle$  can be characterized as follows:

$$Set\langle t \rangle \equiv Boolean^t$$

Of course set membership is defined as follows:

$$\forall[x:t, S:Set\langle t \rangle] x \in S \Leftrightarrow S[x] = \text{True}$$

A set theory  $SetTheory\langle t \rangle$  for sets with base type  $t$  can be axiomatized using a 2<sup>nd</sup> order set induction axiom as follows:

For each  $P:SetTheory\langle t \rangle^{Sets\langle t \rangle}$ :

$$(\forall[S:Set\langle t \rangle, \alpha:\mathcal{O}]$$

$$(S \doteq \alpha \Rightarrow \forall[X:Set\langle t \rangle, \beta < \alpha:\mathcal{O}] P[X] \wedge X \doteq \beta \Rightarrow P[X]) \Rightarrow \forall[S:Set\langle t \rangle] P[S])$$

Inductive definition:

1.  $Sets_0\langle t \rangle \equiv Boolean^t$
2.  $Sets_{\alpha+1}\langle t \rangle \equiv Set\langle Sets_{\alpha}\langle t \rangle \rangle$
3.  $\alpha:Limit\langle \mathcal{O} \rangle \Rightarrow (S:Set_{\alpha}\langle t \rangle \Leftrightarrow \forall[X \in S] \exists[\beta < \alpha:\mathcal{O}, Y:Set_{\beta}\langle t \rangle] X \in Y)$

$$S:Set\langle t \rangle \Leftrightarrow \exists[\alpha:\mathcal{O}] S:Set_{\alpha}\langle t \rangle$$

The properties below mean that  $\text{Sets}\langle t \rangle$  is a "universe" of mathematical discourse.<sup>111</sup>

- Foundation: There are no downward infinite membership chains.<sup>112</sup>
- Transitivity of  $\in$ <sup>113</sup>:  $\forall [S:\text{Sets}\langle t \rangle] \forall [X \in S] X:\text{Sets}\langle t \rangle$
- Powerset:<sup>114</sup>  $\forall [S:\text{Sets}\langle t \rangle] \text{Boolean}^S:\text{Sets}\langle t \rangle$
- Union:<sup>115</sup>

$$\forall [S:\text{Sets}\langle t \rangle] \text{US}:\text{Sets}\langle t \rangle$$

$$\forall [S:\text{Sets}\langle t \rangle] \forall [X:\text{Sets}\langle t \rangle] X \in \text{US} \Leftrightarrow \exists [Y \in S] X \in Y$$
- Replacement:<sup>116</sup> The function image of any set is also a set, *i.e.*:
$$\forall [f:\text{Sets}\langle t \rangle^{\text{Sets}\langle t \rangle}, S:\text{Sets}\langle t \rangle]$$

$$\forall [y:\text{Sets}\langle t \rangle] y \in \text{Image}\langle t \rangle[f, S] \Leftrightarrow \exists [x \in S] f[x]=y$$

**Theorem.**  $\text{Sets}\langle t \rangle$  satisfies axioms for Grothendieck universes.<sup>117</sup>

**Proof.** By the definition of a Grothendieck universe., it is sufficient to prove the following:

1.  $\forall [S_1, S_2:\text{Sets}\langle t \rangle] \{S_1, S_2\}:\text{Sets}\langle t \rangle$
2.  $\forall [S:\text{Sets}\langle t \rangle] \text{Boolean}^S:\text{Sets}\langle t \rangle$
3.  $\forall [f:\text{Sets}\langle t \rangle^{\text{Sets}\langle t \rangle}, S:\text{Sets}\langle t \rangle] \bigcup_{x \in S} f[x]:\text{Sets}\langle t \rangle$



**Theorem.** Theory  $\text{SetTheory}\langle t \rangle$  is isomorphic to  $\text{Sets}\langle t \rangle$  with a unique isomorphism.

Proof:<sup>118</sup> Suppose that  $\mathcal{X}$  satisfies the axioms for  $\text{SetTheory}\langle t \rangle$ .

By ordinal induction, the isomorphism  $I: \mathcal{X}^{\text{Sets}\langle t \rangle}$  as follows:

1.  $S: \text{Sets}_0\langle t \rangle$   
 $I[S] \equiv S$
2.  $S: \text{Sets}_{\alpha+1}\langle t \rangle$   
 $Z \in_{\mathcal{X}} I[S] \Leftrightarrow \exists [Y: \text{Sets}_{\alpha}\langle t \rangle] I[Y] \in_{\mathcal{X}} Z$
3.  $S: \text{Sets}_{\alpha}\langle t \rangle$  and  $\alpha: \text{Limit}\langle \mathcal{O} \rangle$   
 $Z \in_{\mathcal{X}} I[S] \Leftrightarrow \exists [\beta < \alpha: \mathcal{O}, Y: \text{Sets}_{\beta}\langle t \rangle] I[Y] \in_{\mathcal{X}} Z$
4.  $I$  is a unique isomorphism:
  - $I$  is one to one
  - The range of  $I$  is  $\mathcal{X}$
  - $I$  is a homomorphism:
    - $I[\{ \}_{{\text{Sets}}\langle t \rangle}] = \{ \}_{\mathcal{X}}$
    - $\forall [S1, S2: \text{Sets}\langle t \rangle] I[S1 \cup S2] = I[S1] \cup_{\mathcal{X}} I[S2]$
    - $\forall [S1, S2: \text{Sets}\langle t \rangle] I[S1 \cap S2] = I[S1] \cap_{\mathcal{X}} I[S2]$
    - $\forall [S1, S2: \text{Sets}\langle t \rangle] I[S1 - S2] = I[S1] -_{\mathcal{X}} I[S2]$
    - $\forall [S: \text{Sets}\langle t \rangle] I[US] = \cup_{\mathcal{X}} \{ I[x] \mid x \in S \}$
  - $I^{-1}: \text{Sets}\langle t \rangle^{\mathcal{X}}$  is a homomorphism
  - $I$  is the unique isomorphism: If  $g: \mathcal{X}^{\text{Sets}\langle t \rangle}$  is an isomorphism, then  $g = I$

**Theorem (Model Soundness of  $\text{SetTheory}\langle t \rangle$ ):**

$$(\vdash_{\text{SetTheory}\langle t \rangle} \Psi) \Leftrightarrow \models_{\text{Sets}\langle t \rangle} \Psi$$

Proof: Suppose  $\vdash_{\text{SetTheory}\langle t \rangle} \Psi$ . The theorem immediately follows because the axioms for the theory  $\text{SetTheory}\langle t \rangle$  hold in the type  $\text{Sets}\langle t \rangle$ .

**Theorem: Indiscernibility for  $SetTheory\langle t \rangle$** <sup>119</sup>

$$\forall [s_1, s_2: Sets\langle t \rangle] s_1 = s_2 \Leftrightarrow \forall [P: SetTheory\langle t \rangle] P[s_1] \Leftrightarrow P[s_2]$$

**Theorem: Inferential completeness of  $SetTheory\langle t \rangle$**

$$\forall [\Psi: SetTheory\langle t \rangle] (\models_{Sets\langle t \rangle} \Psi) \Rightarrow \vdash_{SetTheory\langle t \rangle} \Psi$$

**Corollary.** Equivalence of satisfiability and provability in  $Sets_t$  i.e.,

$$\forall [\Psi: SetTheory\langle t \rangle] (\models_{Sets\langle t \rangle} \Psi) \Leftrightarrow \vdash_{SetTheory\langle t \rangle} \Psi$$

**Theorem.** Inferential Decidability of  $SetTheory\langle t \rangle$ , i.e.,

$$\forall [\Psi: SetTheory\langle t \rangle] (\vdash_{SetTheory\langle t \rangle} \Psi) \vee (\vdash_{SetTheory\langle t \rangle} \neg \Psi)$$

### Appendix 3: Blocking Known Paradoxes

Strong types block all known paradoxes including the following:

- Liar [Eubulides of Miletus] is an example of using untyped propositions to derive an inconsistency:<sup>120</sup>

$$F\langle n \rangle \equiv \lambda[p:\text{Proposition}\langle n \rangle] \neg p$$

// above definition has no fixed point because  $\neg p$  has

// order one greater than the order of  $p$

The following argument derives a contradiction assuming the existence of a fixed point for  $F$ :

- 1) *I'mFalse*  $\Leftrightarrow \neg I'mFalse$  // *nonexistent* fixed point of  $F$
- 2)  $\neg I'mFalse$  // By Contradiction from 1)
- 3) *I'mFalse* // from 1) and 2)

- Burali-Forti [Burali-Forti 1897] The set of all ordinals  $\Omega$  is *Boolean*<sup>o</sup> so that:  $\forall[\alpha:\mathcal{O}] \alpha \in \Omega \Leftrightarrow \alpha:\mathcal{O}$ . Note that it is **not** the case that  $\Omega$  is of type  $\mathcal{O}$ , thereby blocking the paradox.

- Russell [Russell 1902].

o Russell's paradox for sets is resolved as follows:

$(\text{Sets}\langle N \rangle \ni \lambda[s:\text{Sets}\langle N \rangle] s \notin s) = \text{Sets}\langle N \rangle$  because no set is an element of itself.

o Russell's paradox for predicates is resolved as follows:

$$\text{Russell}\langle n \rangle [p:\text{Proposition}\langle n+1 \rangle \text{Proposition}\langle n \rangle] \equiv \neg p[p]$$

The above definition has no fixed point because  $\neg p[p]$  has order one greater than the order of  $p$ .

- Curry [Curry 1941] Suppose  $\Psi:\text{Proposition}\langle \text{anOrder} \rangle$  and

$$\text{Curry}\langle n \rangle:\text{Proposition}\langle \text{Max}[n+1, \text{anOrder}+1] \rangle \text{Proposition}\langle n \rangle \text{ where}$$

$$\text{Curry}\langle n \rangle \equiv \lambda[p:\text{Proposition}\langle n \rangle] p \Rightarrow \Psi$$

Curry's Paradox is blocked because the procedure Curry does **not** have a fixed point because order of  $p \Rightarrow \Psi$  is greater than the order of  $p$ .

- Löb [Löb 1955] Suppose  $\Psi:\text{Proposition}\langle \text{anOrder} \rangle$ .

$$\text{Löb}\langle n \rangle:\text{Proposition}\langle \text{Max}[n+1, \text{anOrder}+1] \rangle \text{Proposition}\langle n \rangle \text{ where}$$

$$\text{Löb}\langle n \rangle \equiv \lambda[p:\text{Proposition}\langle n \rangle] (\vdash p) \Rightarrow \Psi$$

Löb's Paradox is blocked because the procedure Löb does **not** have a fixed point because order of  $(\vdash p) \Rightarrow \Psi$  is greater than the order of  $p$ .

- Girard [Girard, J. 1972] There is no type *Type* thereby blocking the paradox. However, the type of a type is a type, e.g.  $Type\langle N \rangle$  is the type of  $N$ .
- Berry [Russell 1906] can be formalized using the proposition  $Characterize[s, k]$  meaning that the string  $s$  characterizes the integer  $k$  as follows:

$Characterize \equiv$

$$\lambda[s: String\langle Proposition\langle anOrder \rangle^N \rangle, k: N] \forall [x: N] \lfloor s \rfloor [x] \Leftrightarrow x=k$$

The Berry Paradox is to construct a string  $BString$  for the string for the proposition that holds for integer  $n$  if and only if every string with length less than 100 does not characterize  $n$  using the following definition:<sup>121</sup>

$StringSmallerThan100DoesNotCharacterize: Proposition\langle anOrder+1 \rangle^N$

$StringSmallerThan100DoesNotCharacterize \equiv$

$$\lambda[n: N] \forall [s: String\langle Proposition\langle anOrder \rangle \rangle] \text{Length}[s] < 100 \Leftrightarrow \neg Characterize[s, n]$$

$BString: String\langle Proposition\langle anOrder+1 \rangle^N \rangle$

$BString \equiv \text{“StringForStringSmallerThan100DoesNotCharacterize”}$

Note that

- $\text{Length}[BString] < 100$ .
- $\{s: String\langle Proposition\langle anOrder \rangle \rangle \mid \text{Length}[s] < 100\}$  is finite.
- Therefore, the following set is finite:

$$BSet: Set\langle N \rangle \equiv \{i: N_+ \mid \exists [s: String\langle Proposition\langle anOrder \rangle^N \rangle] \text{Length}[s] < 100 \wedge Characterize[s, i]\}$$

$BSet \neq \{ \}$  because  $\{i: N \mid i \geq 1\}$  is infinite.

$BNumber: N \equiv \text{Least}[BSet]$

$\lfloor BString \rfloor [BNumber]$

$$= \forall [s: String\langle Proposition\langle anOrder \rangle^N \rangle] \text{Length}[s] < 100 \Leftrightarrow \neg Characterize[s, BNumber]^{122}$$

However  $BString: String\langle Proposition\langle anOrder+1 \rangle^N \rangle$  cannot be

**substituted** for  $s: String\langle Proposition\langle anOrder \rangle^N \rangle$



## Appendix 4: Notation of Direct Logic

*Types* i.e., a type is a *discrimination* of the following:<sup>123</sup>

- *Boolean*::<sup>124</sup>, *N*::<sup>125</sup>, *O*::<sup>126</sup> and *Actor*::<sup>127</sup>
- *Term* $\langle t \rangle$ ::<sup>128</sup>, *Expression* $\langle t \rangle$ ::<sup>129</sup>,  $\Lambda \langle t \rangle$ <sup>130</sup>,  
*String* $\langle t \rangle$ ::<sup>131</sup>, and *Type* $\langle t \rangle$ ::<sup>132</sup>, where  $t$ ::<sup>133</sup>
- *Proposition* $\langle \text{anOrder} \rangle$ ::<sup>134</sup> and *Sentence* $\langle \text{anOrder} \rangle$ ::<sup>135</sup> where  
anOrder: $N_+$
- $(t_1 \oplus t_2)$ ::<sup>136</sup>,  $[t_1, t_2]$ ::<sup>137</sup>,  $([t_1] \rightarrow t_2)$ ::<sup>138</sup>,  $([t_1] \rightarrow_1 t_2)$ ::<sup>139</sup> and  $t_2^{t_1}$ ::<sup>140</sup> where  
 $t_1, t_2$ ::
- $(t \exists \mathbf{P})$ :: where  $t$ :: and  $\mathbf{P}$ :*Proposition*<sup>t</sup> <sup>141</sup>

*Propositions*, i.e., a *Proposition* is a *discrimination* of the following:

- $(\neg\Psi_1, \Psi_1\wedge\Psi_2, \Psi_1\vee\Psi_2, \Psi_1\Rightarrow\Psi_2, (\Psi_1\Leftrightarrow\Psi_2)):\mathbf{t}$  where  $\Psi_1, \Psi_2:\mathbf{t}$  and  $\mathbf{t}::$
- $(\mathbf{x}_1=\mathbf{x}_2):\mathit{Proposition} \langle 1 \rangle$  where  $\mathbf{x}_1, \mathbf{x}_2:\mathbf{t}$  and  $\mathbf{t}::$
- $(\mathbf{t}_1\sqsubseteq\mathbf{t}_2):\mathit{Proposition} \langle 1 \rangle$ <sup>142</sup> where  $\mathbf{t}_1, \mathbf{t}_2::$
- $(\mathbf{x}:\mathbf{t}):\mathit{Proposition} \langle 1 \rangle$  where  $\mathbf{t}::$
- $\mathbf{P}[\mathbf{x}]:\mathit{Proposition} \langle \mathit{anOrder}+1 \rangle$  where  $\mathbf{x}:\mathbf{t}, \mathbf{P}:\mathit{Proposition} \langle \mathit{anOrder} \rangle^{\mathbf{t}}$   
and  $\mathit{anOrder}:N_+$
- $\mathbf{P}.\mathbf{[x]}:\mathit{Proposition} \langle \mathit{anOrder}+1 \rangle$  where  $\mathbf{P}:[\mathbf{t}]\rightarrow\mathit{Proposition} \langle \mathit{anOrder} \rangle$ ,  
 $\mathbf{x}:\mathbf{t}, \mathbf{t}::$  and  $\mathit{anOrder}:N_+$
- $(\Psi_1\vdash_T\Psi_2):\mathbf{t}$  where  $T:\mathit{Theory}$ <sup>143</sup>,  $\Psi_1, \Psi_2:\mathit{Proposition} \langle \mathit{anOrder} \rangle$  and  
 $\mathbf{t}\sqsubseteq\mathit{Proposition} \langle \mathit{anOrder} \rangle$  and  $\mathit{anOrder}:N_+$
- $(\Psi_1\vdash_T^{\mathbf{p}}\Psi_2):\mathbf{t}$  where  $\mathbf{p}:\mathit{ProofChecker} \langle T \rangle$ ,  $T:\mathit{Theory}$ ,  
 $\Psi_1, \Psi_2:\mathit{Proposition} \langle \mathit{anOrder} \rangle$ , and  $\mathbf{t}\sqsubseteq\mathit{Proposition} \langle \mathit{anOrder} \rangle$  and  
 $\mathit{anOrder}:N_+$
- $(\forall\mathbf{t}\mathbf{P})$ <sup>144</sup>,  $(\exists\mathbf{t}\mathbf{P})$ <sup>145</sup>:  $\mathit{Proposition} \langle \mathit{anOrder}+1 \rangle$  where  
 $\mathbf{P}:\mathit{Proposition} \langle \mathit{anOrder} \rangle^{\mathbf{t}}$ ,  $\mathbf{t}\sqsubseteq\mathit{Proposition}$  and  $\mathit{anOrder}:N_+$
- $(\lambda\mathbf{t}\mathbf{P})$ <sup>146</sup>:  $\mathit{Proposition} \langle \mathit{anOrder}+1 \rangle$  where  
 $\mathbf{P}:\mathit{Proposition} \langle \mathit{anOrder} \rangle^{\mathbf{t}}$ ,  $\mathbf{t}\sqsubseteq\mathit{Proposition}$  and  $\mathit{anOrder}:N_+$
- $(\models\Phi):\mathbf{t}$  where  $\Phi:\mathbf{t}$ ,  $\mathbf{t}\sqsubseteq\mathit{Proposition} \langle \mathit{anOrder} \rangle$  and  $\mathit{anOrder}:N_+$
- $\lfloor\mathbf{s}\rfloor_T:\mathit{Proposition} \langle \mathit{anOrder} \rangle$  where  $\mathbf{s}:\mathit{Sentence} \langle \mathit{anOrder} \rangle$  with no  
free variables  $T:\mathit{Theory}$ , and  $\mathit{anOrder}:N_+$

Grammar (syntax) trees (*i.e.* terms, expressions and sentences) are defined below.

**Terms**, *i.e.*, a  $Term \langle t \rangle$  is a *discrimination* of the following:

- $(Boolean): Constant \langle Type \langle Boolean \rangle \rangle$ ,
- $(N): Constant \langle Type \langle N \rangle \rangle$ ,  $(O): Constant \langle Type \langle O \rangle \rangle$  and
- $(Actor): Constant \langle Type \langle Actor \rangle \rangle$
- $x: Term \langle t \rangle$  where  $x: Constant \langle t \rangle$  and  $t ::$
- $(x_1 \circ x_2): Term \langle x_1 \circ x_2 \rangle$ ,  $([x_1, x_2]): Term \langle [x_1, x_2] \rangle$ ,
- $([x_1] \rightarrow x_2): Term \langle [x_1] \rightarrow x_2 \rangle$ ,  $([x_1] \rightarrow_1 x_2): Term \langle [x_1] \rightarrow_1 x_2 \rangle$  and
- $(x_2^{x_1}): Term \langle t_2^{t_1} \rangle$  where  $x_1: Term \langle t_1 \rangle$ ,  $x_2: Term \langle t_2 \rangle$ ,  $t_1, t_2 ::$
- $(x \exists P) ::$  where  $x: Term \langle Type \langle t \rangle \rangle$ ,  $P: Term \langle Proposition^t \rangle$  and  $t ::$
- $(\lambda t_1 x): Term \langle t_2^{t_1} \rangle$  where  $x: Term \langle t_2^{t_1} \rangle$ , and  $t_1, t_2 ::$
- $(Fixer \langle t_1, t_2 \rangle [F])^{147}$  where  $F: Term \langle Mapping \langle t_1, t_2 \rangle \rangle$  and  $t_1, t_2 ::$
- $(f[x]): Term \langle t_2 \rangle$  where  $f: Term \langle t_2^{t_1} \rangle$ ,  $x: Term \langle t_1 \rangle$ ,  $t_1, t_2 ::$
- $[x]: t$  where  $x: Term \langle t \rangle$  with **no** free variables and  $t ::$



**Expressions**, i.e., an *Expression*  $\langle t \rangle$  is a *discrimination* of the following:

- $x: \text{Expression} \langle t \rangle$  where  $x: \text{Constant} \langle t \rangle$  and  $t::$
- $x: \text{Expression} \langle t \rangle$  where  $x: \text{Identifier} \langle t \rangle$  and  $t::$
- $(e_1 \oplus e_2): \text{Expression} \langle t_1 \oplus t_2 \rangle$ ,  $([e_1, e_2]): \text{Expression} \langle [t_1, t_2] \rangle$ ,  
 $([e_1] \rightarrow e_2): \text{Expression} \langle [t_1] \rightarrow t_2 \rangle$ , where  $e_1: \text{Expression} \langle t_1 \rangle$ ,  
 $e_2: \text{Expression} \langle t_2 \rangle$ , and  $t_1, t_2::$
- $(e_1 \text{ if True then } e_2, \text{ False then } e_3): \text{Expression} \langle t \rangle^{148}$  where  
 $e_1: \text{Expression} \langle \text{Boolean} \rangle$ ,  $e_2, e_3: \text{Expression} \langle t \rangle$  and  $t::$
- $(\text{Fix} \langle t_1, t_2 \rangle. [F])^{149}$  where  $F: \text{Expression} \langle \text{Functional} \langle t_1, t_2 \rangle \rangle$  and  
 $t_1, t_2::$
- $(e_1 \text{ either } e_2): \text{Expression} \langle t \rangle$  where  $e_1, e_2: \text{Expression} \langle t \rangle$  and  $t::$
- $(t_1 \mapsto E): \text{Expression} \langle [t_1] \rightarrow t_2 \rangle^{150}$  where  
 $E: [ \text{Expression} \langle t_1 \rangle ] \rightarrow \text{Expression} \langle t_2 \rangle$ , and  $t_1, t_2::$
- $(e.[x]): \text{Expression} \langle t_2 \rangle$  where  $e: \text{Expression} \langle [t_1] \rightarrow t_2 \rangle$ ,  
 $x: \text{Expression} \langle t_1 \rangle$ , and  $t_1, t_2::$
- $\text{Le}]: t$  where  $e: \text{Expression} \langle t \rangle$  with **no** free identifiers and  $t::$

**Every nondeterministic computable procedure can be obtained by abstraction from an expression:**

$$\forall [f: ([t_1] \rightarrow t_2)] \text{Nondeterministic}[f] \Rightarrow \exists [e: \text{Expression} \langle [t_1] \rightarrow t_2 \rangle] f = [e]$$

**However as explained in this article, there are computations that cannot be implemented in the nondeterministic lambda calculus and therefore require Actors for their implementation.**

**Sentences**, i.e., a *Sentence* is a *discrimination* of the following:

- $(\neg s_1), (s_1 \wedge s_2), (s_1 \vee s_2), (s_1 \Rightarrow s_2), (s_1 \Leftrightarrow s_2): t$  where  $s_1, s_2: t$  and  $t::$
- $(e_1 = e_2): \text{Sentence} \langle 1 \rangle$  where  $e_1, e_2: \text{Expression} \langle t \rangle$  and  $t::$
- $(e_1 \sqsubseteq e_2): \text{Sentence} \langle 1 \rangle$  where  $e_1, e_2: \text{Expression} \langle t_1 \rangle$ ,  $t_1: t_2$  and  $t_2::$
- $(e_1: e_2): \text{Sentence} \langle 1 \rangle$  where  $e_1: \text{Expression} \langle t_1 \rangle$ ,  $e_2: \text{Expression} \langle t_2 \rangle$  and  $t_1, t_2::$
- $(e::): \text{Sentence} \langle 1 \rangle$  where  $e: \text{Expression} \langle t \rangle$  and  $t::$
- $(\forall t P), (\exists t P): \text{Expression} \langle \text{Sentence} \langle \text{anOrder} + 1 \rangle \rangle$  where,  
 $P: \text{Expression} \langle \text{Sentence} \langle \text{anOrder} \rangle \text{Expression} \langle t \rangle \rangle$ ,  
 $t \sqsubseteq \text{Expression} \langle \text{Sentence} \rangle$ , and  $t::$
- $(\lambda t P): \text{Expression} \langle \text{Sentence} \langle \text{anOrder} + 1 \rangle \rangle$  where  
 $P: \text{Expression} \langle \text{Sentence} \langle \text{anOrder} \rangle \text{Expression} \langle t \rangle \rangle$ ,  
 $t \sqsubseteq \text{Expression} \langle \text{Sentence} \rangle$ , and  $t::$
- $(t \mapsto P): \text{Expression} \langle \text{Sentence} \langle \text{anOrder} + 1 \rangle \rangle^{151}$  where,  
 $P: \text{Expression} \langle \text{Sentence} \langle \text{anOrder} \rangle \text{Expression} \langle t \rangle \rangle$ ,  
 $t \sqsubseteq \text{Expression} \langle \text{Sentence} \rangle$ , and  $t::$
- $(P[x]): \text{Sentence} \langle \text{anOrder} + 1 \rangle^{152}$  where  $x: \text{Expression} \langle t \rangle$ ,  
 $P: \text{Expression} \langle \text{Sentence} \langle \text{anOrder} \rangle \text{Expression} \langle t \rangle \rangle$ ,  $t::$  and  $\text{anOrder}: N_+$
- $(P.[x]): \text{Sentence} \langle \text{anOrder} + 1 \rangle^{153}$  where  $x: \text{Expression} \langle t \rangle$ ,  
 $P: [\text{Expression} \langle t \rangle] \rightarrow \text{Expression} \langle \text{Sentence} \langle \text{anOrder} \rangle \rangle$ ,  $t::$  and  
 $\text{anOrder}: N_+$
- $(s_1 \vdash_T s_2): t$  where  $T: \text{Expression} \langle \text{Theory} \rangle$ ,  $s_1, s_2: t \sqsubseteq \text{Sentence}$  and  
 $\text{anOrder}: N_+$
- $(s_1 \vdash_T^p s_2): t$  where  $p: \text{Expression} \langle \text{ProofChecker} \langle T \rangle \rangle$ ,  
 $T: \text{Expression} \langle \text{Theory} \rangle$ ,  $s_1, s_2: \text{Expression} \langle \text{Sentence} \langle \text{anOrder} \rangle \rangle$   
and  $t \sqsubseteq \text{Proposition} \langle \text{anOrder} \rangle$  and  $\text{anOrder}: N_+$
- $(\models s): t$  where  $s: t$  and  $t::$
- $\lfloor s \rfloor_T: \text{Proposition} \langle \text{anOrder} \rangle$  where  $s: \text{Sentence} \langle \text{anOrder} \rangle$ ,  $\text{anOrder}: N_+$ ,  
 $T: \text{Expression} \langle \text{Theory} \rangle$ , and there are **no** free variables in  $s$ .<sup>154</sup>

### Appendix 5: Inconsistency Robustness

Intelligent Applications must reason about pervasively inconsistent empirical information, which requires restriction on Unlimited Disjunction Introduction, **Contrapositive, Excluded Middle, and By Contradiction** as explained in this section.<sup>155</sup>

- **Excluded Middle** Non-contradiction infers excluded middle.

$$\neg(\Psi \wedge \neg\Psi) \vdash \Psi \vee \neg\Psi$$

- **By Contradiction** Contrapositives infer By Contradiction

$$(\Psi \vdash \neg\Phi), (\neg\Psi \vdash \neg\Phi) \vdash ((\Phi \vdash \Psi \wedge \neg\Psi) \vdash \neg\Phi)$$

- **Contrapositive** Non-contradiction with hypothesis infers Contrapositive

$$((\Psi \vdash \Phi) \vdash \neg(\Psi \wedge \neg\Phi)) \vdash (\neg\Phi \vdash \neg\Psi)$$

## Appendix 6: Rules of Direct Logic

The following are core rules for Direct Logic:

- $\wedge$  (**Conjunction**)
  - $\wedge$  **Introduction**  
 $\Psi, \Phi \vdash (\Psi \wedge \Phi)$
  - $\wedge$  **Elimination**  
 $\Psi \wedge \Phi \vdash \Psi$
  - **Proves Both**  
 $(\Theta \vdash (\Psi \wedge \Phi)) \dashv\vdash ((\Theta \vdash \Psi) \wedge (\Theta \vdash \Phi))$
- $\neg$  (**Negation**)
  - **Negation Distribution**  
 $\neg(\Psi \vee \Phi) \vdash \neg\Psi \wedge \neg\Phi$   
 $\neg(\Psi \wedge \Phi) \vdash \neg\Psi \vee \neg\Phi$
  - **Double Negation**  
 $\neg\neg\Psi \dashv\vdash \Psi$
- $\vee$  (**Disjunction**)
  - **Disjunctive Elimination**  
 $\neg\Psi, \Psi \vee \Phi \vdash \Phi$
  - **Disjunctive Cases**  
 $\Psi \vee \Phi, (\Psi \vdash \Theta), (\Phi \vdash \Omega) \vdash \Theta \vee \Omega$
  - **Conjunction infers Disjunction**  
 $\Psi \wedge \Phi \vdash \Psi \vee \Phi$
- $\vdash$  (**Inference**)
  - **Idempotency**  
 $\Psi \vdash \Psi$
  - **Theorems can be used in proofs**  
 $(\vdash\Psi) \vdash \Psi$
  - **Chaining**  
 $\Psi, (\Psi \vdash \Phi) \vdash \Phi$
  - **Monotonicity**  
 $(\Phi \vdash \Psi) \vdash (\Phi, \Theta \vdash \Psi)$
  - **Subproof**  
 $(\Psi, \Phi \vdash \Theta) \dashv\vdash (\Psi \vdash (\Phi \vdash \Theta))$
  - **Theorems Prove Theorems**  
 $((\vdash\Psi) \vdash \Phi) \vdash (\vdash\Phi)$
  - **Adequacy**  
 $(\Psi \vdash \Phi) \dashv\vdash (\vdash(\Psi \vdash \Phi))$

**Theorem (Step Introduction).**  $(\Psi \vdash \Phi), (\Psi, \Phi \vdash \Theta) \vdash (\Psi \vdash \Theta)$

**Proof:** Follows immediately from  $(\Psi \vdash \Phi), (\Psi, \Phi \vdash \Theta), \Psi \vdash \Theta$

**Theorem (Transitivity).**  $(\Psi \vdash \Theta), (\Theta \vdash \Phi) \vdash (\Psi \vdash \Phi)$

**Proof:** Follows immediately from  $(\Psi \vdash \Theta), (\Theta \vdash \Phi), \Psi \vdash \Phi$  which follows from  $(\Psi \vdash \Theta), (\Theta \vdash \Phi), \Psi, \Theta \vdash \Phi$

### Classical Direct Logic

Classical Direct Logic adds the rule of By Contradiction to the above as follows:

$(\Psi \vdash \Phi \wedge \neg \Phi) \vdash \neg \Psi$

**Implication defined:**  $\Psi \Rightarrow \Phi \equiv (\Psi \vdash \Phi)$

**Theorem (Soundness).**  $(\vdash \Psi) \Rightarrow (\models \Psi)$

**Proof:** Axioms above are true and truth is preserved.<sup>156</sup>

**Theorem (Inferential Completeness).**  $(\vdash \Psi) \Leftrightarrow (\models \Psi)$

**Proof:** It is sufficient to prove  $(\models \Psi) \Rightarrow (\vdash \Psi)$ .  $(\models \Psi) \vdash (\neg \Psi \vdash (\models \Psi) \wedge \neg \Psi)$ .

Hence  $(\models \Psi) \vdash (\neg \Psi \vdash \Psi \wedge \neg \Psi)$  because  $(\models \Psi) \Rightarrow \Psi$ . The theorem follows from By Contradiction.

**Theorem (Formal Consistency).**  $\not\vdash \Psi \wedge \neg \Psi$

**Proof:** Follows immediately from By Contradiction because

$(\vdash \Psi \wedge \neg \Psi) \vdash \Psi \wedge \neg \Psi$

**Theorem (Contrapositive).**  $(\Psi \vdash \Phi) \vdash (\neg \Phi \vdash \neg \Psi)$

**Proof:** Using By Contradiction, follows immediately from

$(\Psi \vdash \Phi) \vdash (\neg \Phi \vdash (\Psi \vdash \Phi \wedge \neg \Phi))$ , which follows from  $(\Psi \vdash \Phi), \neg \Phi \vdash (\Psi \vdash \Phi)$  and

$(\Psi \vdash \Phi), \neg \Phi \vdash (\Psi \vdash \neg \Phi)$ , the latter of which follows from  $(\Psi \vdash \Phi), \neg \Phi, \Psi \vdash \neg \Phi$

## Index

- $\neg$ , 7, 59, 62, 63, 64, 65
- $\oplus$ , 61, 63, 64, 73
- $\therefore$ , 62, 65
- $\therefore$ , 65
- $=$ , 62, 65
- $\forall$ , 7, 62, 65
- $\exists$ , 62, 65
- $\in$ , 55
- $\exists$ , 61, 63
- $\blacksquare$ , 62, 64, 65
- $\doteq$ , 54
- $\sqsubseteq$ , 62, 65
- $\vdash$ , 62, 65
- $\models$ , 8, 53, 56, 57, 62, 65
- U, 55
- $\rightarrow$ , 61, 63, 64, 73
- $\rightarrow$ , 64, 65
- $\Rightarrow$ , 62, 65
- $\rightarrow_1$ , 61, 63
- $\Leftrightarrow$ , 62, 65
- Actor*, 61, 63
- Actors, 64
  - Computational Adequacy, 20
- argumentation, 12
- Barwise, J., 44
- Beeson, M., 26
- Berry Paradox, 59
- Boolean, 4, 61, 63
- Boom, H., 26
- Burali-Forti, C., 58
- By Contradiction, 10, 20, 21, 66, 68
- categorical, 6, 46
- categoricity
  - natural numbers, 9
  - ordinals, 53
  - reals, 51
- choice
  - type, 54
- Church, A., 1, 8, 23, 24, 35, 39
- Church's Paradox, 25
- Classical Direct Logic, 2
- Cohen, P., 32
- compactness, 11
- Computational Adequacy
  - Actors, 20
- computational inadequacy
  - nondeterministic lambda calculus, 49
- consistency
  - formal, 11
- Consistency of Mathematics, 20
- Constant*, 63, 64
- Contrapositive, 66
- Coq, 23
- Coquand, T., 23
- Curry, H., 1, 58
- cut-elimination
  - for *Nat*, 8
- Dawson, J., 24
- decidability
  - inferential, 23
- Dedekind, R., 1
- Direct Logic
  - sentence, 65
- Direct Logic
  - expression, 64
  - proposition, 62
  - term, 63
- either*, 64
- Eubulides of Miletus, 58
- expression
  - Direct Logic, 64
- Expression*, 64
- Expression*, 61
- False, 4
- First-Order Thesis, 44

Fixer, 63  
 formal consistency, 14  
 Foundation  
   sets, 55  
*Functional*, 64  
 Galbraith, J. K., 12  
 Girard, J., 59  
 Gödel  
   validity of incompleteness  
     arguments, 33  
 Gödel, K., 32  
 Grothendieck universe, 55  
 Grothendieck universes, 55  
 Halt, 8, 34  
 halting problem, 8  
 higher order logic, 6  
 Hobbes, T., 43  
 Hodges, W., 43  
 Huet, G., 23  
*Identifier*, 64  
 if, 64  
*I'mUnprovable*, 23, 24, 33  
 Inconsistency Robustness, 1, 66  
   Contrapositive, 66  
   Excluded Middle, 66  
   Unlimited Disjunction  
     Introduction, 66  
 indiscernibility, 8, 14, 25, 50, 53, 57  
 inexhaustibility  
   Mathematics, 23  
 inferability  
   computationally undecidable, 8  
 inferentially decidable, 14  
 Isabelle, 23  
 Kao, E., 66  
 Kleene, S., 23  
 Kuhn, T., 12  
 Lakatos, I., 32  
*Lam* $\triangleleft t \triangleright$ , 48  
 lambda calculus  
   computational inadequacy, 49  
 Lambda Induction, 48  
 Law, J., 32  
 Liar Paradox, 58  
 Löb, M., 1, 58  
 Logic Program  
   nondeterministic, 46  
   pure, 40  
 Maddy, P., 3  
*Mapping*, 63  
 Mathematical rules  
   By Contradiction, 66  
   Contrapositive, 66  
   Disjunction Introduction, 66  
   Excluded Middle, 66  
 Mathematics  
   inexhaustibility, 23  
 Monk, R., 33  
*N*, 6, 44, 61, 63  
*Nat*, 6, 7, 8, 11, 42, 45  
   proposition, 7  
*Nat*<sub>1</sub>, 36  
 Natural Deduction, 21  
 nondeterministic computable  
   procedure, 64  
 nondeterministic lambda calculus,  
   40  
 Nondeterministic Lambda Calculus,  
   48  
 nondeterministic Logic Program, 46  
 nondeterministic Turing Machine,  
   46  
*O*, 61, 63  
*Ord*, 53  
 paradox, 1  
 Paulson, L., 23  
 Planck, M., 12  
 Plotkin, G., 25

- Powerset
  - sets, 55
- Principia Mathematica, 34
- Principle of Excluded Middle, 12
- Proof by Contradiction
  - By Contradiction, 10
- Proof Checker, 7
- proof checking
  - computational decidability, 53
  - computationally decidable, 24
- ProofChecker*, 7, 53, 62, 65
- Proofs, 53
- proposition
  - Direct Logic, 62
- Proposition, 4, 61, 62
- Pythagoreans, 2
- RealClosedFields*, 51
- reals
  - categoricity, 51
- Reals*, 51
- Replacement
  - sets, 55
- Rosser, J. B., 23
- Russell, B., 1, 23, 24
- Russell's paradox
  - for predicates, 58
  - for sets, 58
- self-referential propositions, 35
- sentence
  - Direct Logic, 65
- Sentence*, 61, 65
- sets
  - Axiom of Foundation, 55
  - Axiom of Replacement, 55
  - axiom of Union, 55
  - powerset, 55
  - Transitivity of  $\in$ , 55
- Sets*  $\langle \triangleleft \triangleright \rangle$ , 55
- String*, 61
- Tarski, A., 4
- term
  - Direct Logic, 63
- Term*, 61, 63
- Theory*, 62, 65
- Transitivity of  $\in$ 
  - sets, 55
- True, 4
- truth, 12
- Turing Machine
  - nondeterministic, 46
- Turing, A., 8, 35
- Type*, 61, 73
- types
  - choice, 54
- Unbounded Nondeterminism, 45
- Union
  - sets, 55
- universe
  - sets, 55
- Unlimited Disjunction Introduction, 66
- von Neumann, J., 32
- Wittgenstein
  - validity of Gödel incompleteness arguments, 33
- Wittgenstein, L., 1
- Woods, J., 25
- Zermelo, E., 1, 43
- $\lambda$ , 62, 63, 65
- $\Lambda$ , 61





## End Notes

---

<sup>1</sup> As in programming language integrated development environments, color has no semantics significance.

Double colons are used to express something is a type. For example  $t::$  expresses that  $t$  is a type.

Types can be composed using the following:

- All functions from  $t_1$  into  $t_2$  is  $t_2^{t_1}::$  where  $t_1, t_2::$   
A function is total and may be uncomputable.
- Tuple of types is  $[t_1, t_2]::$  where  $t_1, t_2::$   
For example,  $[N, N]$  is the type of pairs of  $N$
- Discriminated union of types is  $(t_1 \oplus t_2)::$  where  $t_1, t_2::$
- Predicate restriction of a type is  $(t \exists P)::$  where  $t::$  and  $P: \text{Proposition}^t$   
For example replacement for types (range of a function  $f: t_2^{t_1}$ )  
is  $t_2 \exists \lambda[y: t_2] \exists [x: t_1] y=f[x]$
- Computable procedures from  $t_1$  into  $t_2$  is  $([t_1] \rightarrow t_2)::$  where  $t_1, t_2::$   
A computable procedure can be partial and can be indeterminate in its outcome.
- Type of a type is  $\text{Type} \langle t \rangle::$  where  $t::$  and  $\text{Type}$  is a parametrized type with parameter  $t$ . Parametrized types have become popular in programming languages where in Java they are called “generics.”  
There is **no** unparameterized type  $\text{Type}$  in order to block Girard’s paradox.

<sup>2</sup> Blocking *all* the known paradoxes is necessary to defeat hackers.

<sup>3</sup> Inference rules for Direct Logic are presented in an appendix.

<sup>4</sup> [Verbrugge 2010]

<sup>5</sup> Axioms and rules of Direct Logic are presented in appendices of this article.

<sup>6</sup> Performance of computer information systems is measured in consumption of processing cycles and storage space as well as latency for response. Pervasive inconsistency for information systems means that there are numerous inconsistencies that cannot be readily found and that many of the ones that are found cannot be easily removed.

- 
- <sup>7</sup> In this sense, Mathematics is “incomplete”, but nor in the sense of Gödel’s results. See below on the inferential completeness of standard theories of mathematics, such as natural numbers, real numbers, ordinal numbers, set theory, lambda calculus, and Actors.
- <sup>8</sup> Which is not the same as proving the much *stronger* proposition that no contradiction can be derived from the exact axioms and inference rules of Direct Logic.
- <sup>9</sup> Furthermore, theorems of these theories are not enumerable by a provably total procedure.
- <sup>10</sup> Of course, abstraction means that 1<sup>st</sup> order logic is **not** a suitable foundation.
- <sup>11</sup> cf. [Wigner 1960]
- <sup>12</sup> [Nielsen 2014]
- <sup>13</sup> parametrized types have become very popular in programming languages, e.g., Java where they are called “generics.”
- <sup>14</sup> Classical results can be embedded in intuitionistic logic as follows:
- $\neg\neg\neg\Psi \Leftrightarrow \neg\Psi$
  - $\exists$  can be transformed to  $\neg\forall\neg$
  - $\Psi_1\vee\Psi_2$  can be transformed to  $\neg(\neg\Psi_1\wedge\neg\Psi_2)$
- <sup>15</sup> Some of the outputs are conventionally identified as being the same real number, e.g., .0111111... and .1000000000
- <sup>16</sup> For example (p[3])[y] holds if and only if y=3.
- <sup>17</sup> [Isaacson 2007]
- <sup>18</sup> A theory is defined by a set of propositions in Direct Logic that are taken to be axioms of the theory.
- <sup>19</sup> There are **no** sets in the induction axiom. Quine famously criticized 2<sup>nd</sup> order theory as nothing more than “*set theory in sheep’s clothing*” [Quine 1970, pg. 66].

<sup>20</sup>  $Type\langle Nat \rangle ::$  and

$$\begin{aligned}
& \forall [P: Nat^{Type\langle Nat \rangle}] \\
& \quad ((\forall [t_1, t_2: Type\langle Nat \rangle] P[t_1] \wedge P[t_2] \Rightarrow P[t_2^{t_1}]) \\
& \quad \quad // \text{all functions from } t_1 \text{ into } t_2 \\
& \quad (\forall [t_1, t_2: Type\langle Nat \rangle] P[t_1] \wedge P[t_2] \Rightarrow P[t_1 \oplus t_2]) \\
& \quad \quad // \text{discriminated union of } t_1 \text{ and } t_2 \\
& \quad (\forall [t: Type\langle Nat \rangle Q: Nat^{Type\langle Nat \rangle}] P[t] \Rightarrow P[t \dot{\exists} Q]) \\
& \quad \quad // \text{restriction of } t \text{ by } Q \\
& \quad (\forall [t: Type\langle Nat \rangle] P[t] \Rightarrow P[Type\langle t \rangle]) \quad // \text{type of } t \\
& \quad (\forall [t_1, t_2: Type\langle Nat \rangle] P[t_1] \wedge P[t_2] \Rightarrow P[[t_1] \rightarrow t_2])) \\
& \quad \quad // \text{computable procedures from } t_1 \text{ into } t_2 \\
& \Rightarrow (\forall [t: Type\langle Nat \rangle] P[t])
\end{aligned}$$

Above characterizes  $Type\langle Nat \rangle$  up to a unique isomorphism.

<sup>21</sup> **Proof.** Suppose that  $\mathcal{X}$  is propositions of a theory which satisfies the axioms

for propositions of  $Nat$ . Inductively define  $I: \mathcal{X}^{Nat}$  as follows:

- $I[x_1 = x_2] \equiv (x_1 = x_2)$
- $I[\neg \Psi] \equiv \neg I[\Psi]$
- $I[\Psi_1 \wedge \Psi_2] \equiv I[\Psi_1] \wedge I[\Psi_2]$
- $I[\forall [x: t] P[x]] \equiv \forall [x: t] I[P[x]]$  where  $t: Type\langle Nat \rangle$  and  $P: Nat^t$

$I$  is a unique isomorphism between  $Nat$  and  $\mathcal{X}$

<sup>22</sup> There are uncountable sentence parse trees because the constants which they contain are uncountable.

<sup>23</sup> **Proof.** Induction on propositions of  $Nat$

- Inductively suppose that

$$\forall[\Psi: Nat] \exists[s: Sentence \langle Nat \rangle] \lfloor s \rfloor = \Psi$$

Consequently,  $\forall[\Psi: Nat] \exists[s: Sentence \langle Nat \rangle] \lfloor (\neg s) \rfloor = \neg \Psi$

Therefore,  $\forall[\Psi: Nat] \exists[s: Sentence \langle Nat \rangle] \lfloor s \rfloor = \neg \Psi$

- Inductively suppose that

$$\forall[\Psi_1, \Psi_2: Nat] \exists[s_1, s_2: Sentence \langle Nat \rangle] \lfloor s_1 \rfloor = \Psi_1 \wedge \lfloor s_2 \rfloor = \Psi_2$$

Consequently,  $\forall[\Psi_1, \Psi_2: Nat]$

$$\exists[s_1, s_2: Sentence \langle Nat \rangle] \lfloor (s_1 \wedge s_2) \rfloor = \Psi_1 \wedge \Psi_2$$

Therefore,  $\forall[\Psi_1, \Psi_2: Nat] \exists[s: Sentence \langle Nat \rangle] \lfloor s \rfloor = \Psi_1 \wedge \Psi_2$

- Inductively suppose that

$$\forall[t: Type \langle Nat \rangle, x: t, P: Nat^t] \exists[s: Sentence \langle Nat \rangle] \lfloor s \rfloor = P[x]$$

which can be rephrased as follows:

$$\forall[t: Type \langle Nat \rangle, x: t, P: Nat^t]$$

$$\exists[f: \langle Sentence \langle Nat \rangle \rangle^{[Type \langle Nat \rangle, t, Nat^t]}] \lfloor f[t, P, x] \rfloor = P[x]$$

which means that

$$\forall[t: Type \langle Nat \rangle, x: t, P: Nat^t] \exists[g: \langle Sentence \langle Nat \rangle \rangle^{[Type \langle Nat \rangle, Nat^t]^t}]$$

$$\lfloor g[t, P][x] \rfloor = P[x]$$

which means that

$$\forall[t: Type \langle Nat \rangle, x: t, P: Nat^t] \exists[g: Sentence \langle Nat \rangle^{t[Type \langle Nat \rangle, Nat^t]^t}]$$

$$\lfloor \lambda t g[t, P] \rfloor [x] = P[x]$$

which means that

$$\forall[t: Type \langle Nat \rangle, x: t, P: Nat^t]$$

$$\exists[h: Sentence \langle Nat \rangle^{t[Type \langle Nat \rangle, Nat^t]^t}] \lfloor (\lambda t h[t, P]) \rfloor [x] = P[x]$$

which means that

$$\forall[t: Type \langle Nat \rangle, P: Nat^t] \exists[k: Nat^{t[Type \langle Nat \rangle, Nat^t]^t}] \lfloor k[t, P] \rfloor = P$$

Therefore because  $\lfloor (\forall t k[t, P]) \rfloor = \forall t \lfloor k[t, P] \rfloor$

$$\forall[t: Type \langle Nat \rangle, P: Nat^t]$$

$$\exists[k: Nat^{t[Type \langle Nat \rangle, Nat^t]^t}] \lfloor (\forall t k[t, P]) \rfloor = \forall t P$$

Consequently,

$$\forall[t: Type \langle Nat \rangle, P: Nat^t] \exists[s: Sentence \langle Nat \rangle] \lfloor s \rfloor = \forall t P$$

---

<sup>24</sup> For example,  $\Psi$  cannot be cut from the following proof:

$(\vdash_{\text{Nat}} \Psi), (\Psi \vdash_{\text{Nat}} \text{False}) \vdash_{\text{Nat}} (\vdash_{\text{Nat}} \text{False})$

<sup>25</sup> [Dedekind 1888] According to [Isaacson 2007]:

“Second-order quantification is significant for philosophy of mathematics since it is the means by which mathematical structures may be characterized. But it is also significant for mathematics itself. It is the means by which the significant distinction can be made between the independence of Euclid's Fifth postulate from the other postulates of geometry and the independence of Cantor's Continuum hypothesis [conjecture] from the axioms of set theory. The independence of the Fifth postulate rejects the fact, which can be expressed and established using second-order logic, that there are different geometries, in one of which the Fifth postulate holds (is true), in others of which it is false.”

<sup>26</sup> [Hardy 1992] page 19.

<sup>27</sup> highlighted below

<sup>28</sup> cf. [Zermelo 1932] pp. 6-7.

<sup>29</sup> Examples:

○  $\forall [P: \text{Nat}^{\mathbb{N}}] (\models_{\mathbb{N}} \forall [i: \mathbb{N}] P[i]) \Rightarrow \vdash_{\text{Nat}} \forall [i: \mathbb{N}] P[i]$

Suppose in  $\text{Nat}, P: \text{Nat}^{\mathbb{N}}$  and  $\models_{\mathbb{N}} \forall [i: \mathbb{N}] P[i]$ . Further suppose to obtain a contradiction that  $\neg \forall [i: \mathbb{N}] P[i]$ .

Therefore  $\exists [i: \mathbb{N}] \neg P[i]$  and by Existential Elimination  $\neg P[i_0]$  where  $i_0: \mathbb{N}$ , which contradicts  $\models_{\mathbb{N}} P[i_0]$ , from the hypothesis of the theorem.

Therefore  $\vdash_{\text{Nat}} \forall [i: \mathbb{N}] P[i]$  using By Contradiction in  $\text{Nat}$ .

○  $\forall [P: \text{Nat}^{\mathbb{N}}] (\models_{\mathbb{N}} \exists [i: \mathbb{N}] P[i]) \Rightarrow \vdash_{\text{Nat}} \exists [i: \mathbb{N}] P[i]$

Suppose in  $\text{Nat}, P: \text{Nat}^{\mathbb{N}}$  and  $\models_{\mathbb{N}} \exists [i: \mathbb{N}] P[i]$ . Further suppose to obtain a contradiction that  $\neg \exists [i: \mathbb{N}] P[i]$  and therefore

$\forall [i: \mathbb{N}] \neg P[i]$ . However,  $\models_{\mathbb{N}} P[i_0]$  where  $i_0: \mathbb{N}$ , which contradicts  $\neg P[i_0]$ .

Therefore  $\vdash_{\text{Nat}} \exists [i: \mathbb{N}] P[i]$  using By Contradiction in  $\text{Nat}$ .

---

<sup>30</sup> It is well known that *Nat* inferentially decides the Continuum Hypothesis. ContinuumForNat is defined as follows:

$$\text{ContinuumForNat} \Leftrightarrow \nexists [S: \text{Boolean}^{\mathbb{N}}] \mathbb{N} < S < \text{Boolean}^{\mathbb{N}}$$

where  $X < Y$  is defined to mean that there is no 1-to-1  $X^Y$

ContinuumForNat has been proved for well-behaved types, such as Borel as follows:

$$\text{ContinuumForBorel} \Leftrightarrow \nexists [S: \text{Borel}] \mathbb{N} < S < \text{Boolean}^{\mathbb{N}}$$

where a *Borel* is formed from the countable union, countable intersection, and relative complement of open elements of  $\text{Boolean}^{\mathbb{N}}$

However, ContinuumForNat remains a famous open problem.

<sup>31</sup> often misleading called  $\omega$ -consistency [Gödel 1931]

<sup>32</sup> Compactness of *Nat* is defined to be that every *Nat* inconsistent set of propositions has a finite inconsistent subset.

**Proof of Noncompactness of *Nat*:** Define predicates Bounded and Beyond as follows:

$$\text{Bounded}[S \subseteq \mathbb{N}] \equiv \exists [k: \mathbb{N}] \forall [j \in S] j < k$$

$$\text{Beyond}[i: \mathbb{N}, S \subseteq \mathbb{N}] \equiv \exists [j > i] j \in S$$

To show that *Nat* is not compact consider the following sets of *Nat* propositions:

$$\text{Bounded\&BeyondEach}[S \subseteq \mathbb{N}] \equiv \{\text{Bounded}[S]\} \cup \{\text{Beyond}[i, S] \mid i: \mathbb{N}\}.$$

Then  $\vdash_{\text{Nat}} \forall [S \subseteq \mathbb{N}] \neg \text{Consistent}_{\text{Nat}}[\text{Bounded\&BeyondEach}[S]]$  because by boundedness of  $S$ , there is some  $k_0: \mathbb{N}$  such that  $\forall [j \in S] j < k_0$  which contradicts  $\text{Beyond}[k_0, S]$  meaning  $\exists [j > k_0] j \in S$ .

To finish showing that *Nat* is not compact, let  $S_0 \subseteq \mathbb{N}$  and therefore

$$\neg \text{Consistent}_{\text{Nat}}[\text{Bounded\&BeyondEach}[S_0]]$$

Suppose to obtain a contradiction that the following holds: there is some  $\Omega_0 \subseteq \text{Bounded\&BeyondEach}[S_0]$  such that

$$\neg \text{Consistent}_{\text{Nat}}[\Omega_0] \wedge \text{Finite}_{\text{Nat}}[\Omega_0]$$

Because  $\text{Finite}_{\text{Nat}}[\Omega_0]$ , there is an  $i_0: \mathbb{N}$  such that

$$\Omega_0 \subseteq \{\text{Bounded}[S_0]\} \cup \{\text{Beyond}[i, S_0] \mid i < i_0\}$$

Therefore  $\text{Consistent}_{\text{Nat}}[\Omega_0]$ , which is a contradiction.

---

<sup>33</sup> Note that the results in [Gödel 1931] **do not apply** because propositions in Mathematics are strongly typed and consequently the fixed point used construct Gödel’s proposition *I’mUnprovable* **does not exist** in Mathematics. See the critique of Gödel’s results in this article.

<sup>34</sup> According to [Concoran 2001]:

“after first-order logic had been isolated and had been assimilated by the logic community, people emerged who could not accept the idea that first-order logic was not comprehensive. These logicians can be viewed not as conservatives who want to reinstate an outmoded tradition but rather as radicals who want to overthrow an established tradition [of Dedekind, etc.]”

<sup>35</sup> for discussion see [Hewitt 2015d]

<sup>36</sup> in an unlawful way (Einstein, a member of the editorial board, refused to support Hilbert's action)

<sup>37</sup> Hilbert letter to Brouwer, October 1928

<sup>38</sup> Gödel said “Has Wittgenstein lost his mind?”

<sup>39</sup> A *Com* is a *Return*, *Throw*, or a *Request* that has a *Message* and a *Customer* to which a *Throw* or *Request* for the request can be sent.

<sup>40</sup> of type [*Com*]→

```
Outcome[created= FiniteSet<Actor>, // new Actors
        sent= FiniteSet<Com>, // new Communications
        next= Behavior] // behavior for next Com received
```

<sup>41</sup>  $\rightsquigarrow$  is read as “precedes”

<sup>42</sup> A *Com* is received before it has finished being processed

<sup>43</sup> The reception order of an Actor is total.

<sup>44</sup> A *Com* is not received until the previous one has been processed.

<sup>45</sup> Behavior of an Actor on first *Com* received is the same as its initial behavior.

<sup>46</sup> Behavior of an Actor after a *Com* is received is the behavior that results from processing the *Com*.

<sup>47</sup> Information in an Actor while processing a *Com* is contained in the following:

- information in the Actor before the *Com* is received
- information received in the *Com*
- information for Actors created in processing the *Com*.

<sup>48</sup> Information in an Actor after a *Com* has been processed is contained in information while processing the *Com*.



---

<sup>49</sup> Information sent by an Actor while processing a received *Com* is contained in information while processing the *Com*.

<sup>50</sup>  $\forall[x:\text{Actor}, c:\text{Com}] \text{Received}_x[c]:\text{Event} \wedge \text{After}_x[c]:\text{Event}$

Consequently,

$\forall[x:\text{Actor}, c_1, c_2:\text{Com}]$

$\text{Finite}[\{c:\text{Com} \mid \text{Received}_x[c_1] \rightsquigarrow \text{Received}_x[c] \rightsquigarrow \text{Received}_x[c_2]\}]$

<sup>51</sup> There are only finitely many events in  $\rightsquigarrow$  ordering between two events.

<sup>52</sup> An actor behavior always has property P if it initially has the property and whenever it has the property before a *Com* is received then it has the property afterward.

<sup>53</sup> Again, *Mathematics* here means the common foundation of all classical mathematical theories from Euclid to the mathematics used to prove Fermat's Last [McLarty 2010].

<sup>54</sup> Note that the results in [Löb 1955] **do not apply** because propositions in Mathematics are strongly typed and consequently the fixed point used to establish his result does not exist. See discussion of Löb's Paradox in this article.

<sup>55</sup> Note that the results in [Gödel 1931] **do not apply** because propositions in Mathematics are strongly typed and consequently the fixed point used to construct Gödel's proposition *I'mUnprovable* **does not exist** in Mathematics. See the critique of Gödel's results in this article.

<sup>56</sup> As shown above, there is a simple proof in Classical Direct Logic that Mathematics ( $\vdash$ ) is formally consistent. If the stated axioms and rules of inference of Classical Direct Logic have a bug, then there might also be a proof that Mathematics is operationally inconsistent. Of course, if a such a bug is found, then it must be repaired. The Classical Direct Logic proof that Mathematics ( $\vdash$ ) is formally consistent is very robust. One explanation is that formal consistency is built in to the very architecture of Mathematics because it was designed to be consistent. Consequently, it is not absurd that there is a simple proof of the formal consistency of Mathematics ( $\vdash$ ) that does not use all of the machinery of Classical Direct Logic.

The usefulness of Classical Direct Logic depends crucially on the much **stronger** proposition that Mathematics is operationally consistent, i.e., that there is no proof of contradiction from the stated axioms and inference rules of Direct Logic. Good evidence for the operational consistency of Classical Direct Logic comes from the way that it avoids the known paradoxes. Humans have spent millennia devising paradoxes.

In reaction to paradoxes, philosophers developed the dogma of the necessity of strict separation of “object theories” (theories about basic mathematical entities such as numbers) and “meta theories” (theories about theories). This linguistic separation can be very awkward in Computer Science. Consequently, Direct Logic does not have the separation in order that some propositions can be more “directly” expressed. For example, Direct Logic can use  $\vdash \vdash \Psi$  to express that it is provable that  $\Psi$  is provable in Mathematics. It turns out in Classical Direct Logic that  $\vdash \vdash \Psi$  holds if and only if  $\vdash \Psi$  holds. By using such expressions, Direct Logic contravenes the philosophical dogma that the proposition  $\vdash \vdash \Psi$  must be expressed using Gödel numbers.

<sup>57</sup> [Gödel 1931] based incompleteness results on the thesis that Mathematics necessarily has the proposition *I'mUnprovable* using what was later called the “Diagonal Lemma” [Carnap 1934], which is equivalent to the **Y** untyped fixed point operator on propositions. **Using strong parameterized types, it is impossible to construct *I'mUnprovable* because the **Y** untyped fixed point operator does not exist for strongly typed propositions.** In this way, formal consistency of Mathematics is preserved without giving up power because there do not seem to be any practical uses for *I'mUnprovable* in Computer Science.

A definition of NotProvable could be attempted as follows:

$$\text{NotProvable} \equiv \lambda[p] \not\vdash p$$

With strong types, the attempted definition becomes:

$$\text{NotProvable}\langle n:N_s \rangle [ \text{Proposition}\langle n \rangle ] \rightarrow_1 \text{Proposition}\langle n+1 \rangle$$

$$\text{NotProvable}\langle n:N_s \rangle \equiv \lambda[p:\text{Proposition}\langle n \rangle] \not\vdash p$$

Consequently, there is no fixed point *I'mUnprovable* for the procedure  $\text{NotProvable}\langle n:N_s \rangle$  such that the following holds:

$$\text{NotProvable}\langle n:N_s \rangle [ \text{I'mUnprovable} ] \Leftrightarrow \text{I'mUnprovable}$$

Thus Gödel's *I'mUnprovable* does not exist in Strongly Typed Mathematics.

In arguing against Wittgenstein's criticism, Gödel maintained that his results on *I'mUnprovable* followed from properties of *N* using Gödel numbers for strings that are well-formed. The procedure NotProvable could be attempted for strings as follows: *NotProvable*  $\equiv \lambda[s] \text{ “} \not\vdash s \text{”}$

With strong types, the attempted definition becomes:

$$\text{NotProvable}\langle n:N_s \rangle [ \text{String}\langle \text{Proposition}\langle n \rangle \rangle ] \rightarrow_1 \text{String}\langle \text{Proposition}\langle n+1 \rangle \rangle$$

$$\text{NotProvable}\langle n:N_s \rangle \equiv \lambda[s:\text{String}\langle \text{Proposition}\langle n \rangle \rangle] \text{ “} \not\vdash s \text{”}$$

---

Consequently, there is no fixed point *I'mUnprovableString* for the procedure  $\text{NotProvable}\langle n:N, \triangleright \rangle$  such that the following holds (where  $\lfloor s \rfloor$  is the proposition for well-formed string  $s$ ):

$$\lfloor \text{NotProvable}\langle n:N, \triangleright \rfloor \lfloor I'mUnprovableString \rfloor \rfloor \Leftrightarrow \lfloor I'mUnprovableString \rfloor$$

Thus Gödel's *I'mUnprovableString* does not exist in Strongly Typed Mathematics.

Furthermore, Strong Types thwart the known paradoxes while at the same time facilitating proof of new theorems, such as categoricity of the set theory.

<sup>58</sup> This argument appeared in [Church 1934] expressing concern that the argument meant that there is “no sound basis for supposing that there is such a thing as logic.”

<sup>59</sup> Consequently, there can cannot be any escape hatch into an unformalized “meta-theory.”

<sup>60</sup> sometimes called logical “incompleteness”

<sup>61</sup> The claim also relied on Gödel's proposition *I'mUnprovable*.

<sup>62</sup> Fixed points exist for types other than propositions.

<sup>63</sup> emphasis in original

<sup>64</sup> [Gödel 1931] was accepted doctrine by mainstream logicians for over eight decades.

<sup>65</sup> Of course, Direct Logic must preserve as much previous learning as possible.

<sup>66</sup> According to Solomon Feferman, Gödel was “the most important logician of the 20<sup>th</sup> century” and according to John Von Neumann he was “the greatest logician since Aristotle.” [Feferman 1986, pg. 1 and 8]

<sup>67</sup> [Feferman 1986, pg. 1 and 8]

<sup>68</sup> Wittgenstein in 1937 published in Wittgenstein 1956, p. 50e and p. 51e]

<sup>69</sup> Wittgenstein was granting the supposition that [Gödel 1931] had proved inferential undecidability (sometimes called “incompleteness”) of Russell’s system, that is.,  $\vdash_{\text{Russell}} \nvdash_{\text{Russell}} P$ . However, inferential undecidability is easy to prove using the proposition  $P$  where  $P \Leftrightarrow \nvdash P$ :

*Proof.* Suppose to obtain a contradiction that  $\vdash_{\text{Russell}} P$ . Both of the following can be inferred:

1)  $\vdash_{\text{Russell}} \nvdash_{\text{Russell}} P$  from the hypothesis because  $P \Leftrightarrow \nvdash P$

2)  $\vdash_{\text{Russell}} \vdash_{\text{Russell}} P$  from the hypothesis by Adequacy.

But 1) and 2) are a contradiction. Consequently,  $\vdash_{\text{Russell}} \nvdash_{\text{Russell}} P$  follows from By Contradiction.

<sup>70</sup> [Wittgenstein in 1937 published in Wittgenstein 1956, p. 50e and p. 51e]

<sup>71</sup> [Wang 1972] The theory *1stOrderDedekindPeano* to which Gödel refers is not strictly speaking a subtheory of *Nat* even though

$$\forall[\Psi:1stOrderDedekindPeano] (\vdash_{1stOrderDedekindPeano}\Psi) \Rightarrow \vdash_{Nat}\Psi$$

because *1stOrderDedekindPeano* is compact and inferentially undecidable.

<sup>72</sup> The Liar Paradox [Eubulides of Miletus] is an example of using untyped propositions to derive an inconsistency. See appendix on paradoxes.

<sup>73</sup> According to [Church 1956 page 329]: “completeness [as to inferential provability] is unattainable, as is shown in the incompleteness theorems of Gödel.”

<sup>74</sup> [Church 1935] correctly proved computational undecidability without using Gödel's *I'mUnprovable*. The Church theorem and its proof are very robust.

<sup>75</sup> The following axioms hold for the primitives

- $\nexists[i:N] +_1[i]=0$
- $\forall[i,j:N] +_1[i]=+_1[j] \Leftrightarrow i=j$
- $\forall[\Psi:Nat_1] (\vdash \neg\neg\Psi) \Leftrightarrow \vdash\Psi$
- $\forall[\Psi,\Phi:Nat_1] (\vdash\Psi\wedge\Phi) \Leftrightarrow (\vdash\Psi)\wedge(\vdash\Phi)$
- $\forall[\Psi,\Phi:Nat_1] (\vdash\Psi\Rightarrow\Phi) \Leftrightarrow \vdash\neg(\Psi\wedge\neg\Phi)$
- $\forall[\Psi:Nat_1] (\vdash\Psi\wedge\Psi) \Leftrightarrow \vdash\Psi$
- $\forall[\Psi,\Phi:Nat_1] (\vdash\Psi\wedge\Phi) \Leftrightarrow \vdash\Phi\wedge\Psi$
- $\forall[\Psi,\Phi,\Theta:Nat_1] (\vdash(\Psi\wedge\Phi)\wedge\Theta) \Leftrightarrow \vdash\Psi\wedge(\Phi\wedge\Theta)$
- $\forall[\Psi,\Phi:Nat_1] (\vdash\Psi)\wedge(\vdash\Psi\Rightarrow\Phi) \Leftrightarrow \vdash\Phi$
- $\forall[\Psi,\Phi:Nat_1] (\vdash\Psi\Rightarrow\Phi\wedge\neg\Phi) \Leftrightarrow \vdash\neg\Psi$

<sup>76</sup>  $(\exists t P) \Leftrightarrow \exists[x:t] P[x]$

<sup>77</sup> This inconsistency is mentioned in [Hilbert and Bernays 1939] page 123-125.

<sup>78</sup> In other words, the paradox that concerned [Church 1934] (because it could mean the demise of formal mathematical logic) has been transformed into fundamental theorem of foundations!

<sup>79</sup> Which is **not** the same as proving the much *stronger* proposition that Mathematics is operationally consistent, i.e., that there is no proof of contradiction from the stated axioms and inference rules of Direct Logic.

<sup>80</sup> **Theorem:**  $\vdash_{Nat} \forall[P:String \triangleleft Proposition \triangleleft 1 \triangleright N \triangleright]$

$$(\vdash P \vee [0] \wedge \forall[i:N] \vdash P[i] \Rightarrow \vdash P \vee [i+1]) \Rightarrow \forall[i:N] \vdash P[i]$$

<sup>81</sup> with the consequence that the argument in Church's Paradox is blocked in the theory *Nat* because theorems are not enumerable by a provably total procedure

---

<sup>82</sup> In 1666, England's House of Commons introduced a bill against atheism and blasphemy, singling out Hobbes' Leviathan. Oxford university condemned and burnt Leviathan four years after the death of Hobbes in 1679.

<sup>83</sup> Likewise, 1<sup>st</sup> order set theory (*e.g.* ZFC) is very weak. See discussion in this article.

<sup>84</sup> The ContinuumHypothesis is defined as follows:

$$\text{ContinuumHypothesis} \Leftrightarrow \nexists [S: \text{Boolean}^{\mathbb{N}}] \mathbb{N} < S < \text{Boolean}^{\mathbb{N}}$$

where  $X < Y$  is defined to mean that there is no 1-to-1  $X^Y$

ContinuumHypothesis has been proved for well-behaved types, such as Borel as follows:

$$\text{ContinuumForBorel} \Leftrightarrow \nexists [S: \text{Borel}] \mathbb{N} < S < \text{Boolean}^{\mathbb{N}}$$

where a *Borel* is formed from the countable union, countable intersection, and relative complement of open elements of  $\text{Boolean}^{\mathbb{N}}$

Note that it is important not to confuse ContinuumHypothesis with ContinuumFor1stOrderZFC. *1stOrderZFC* has countably many 1<sup>st</sup> order propositions as axioms. [Cohen 1963] proved the following theorem which is much weaker than ContinuumHypothesis because sets in the models of *1stOrderZFC* do **not** include all of *Proposition*  $\langle 1 \rangle^{\mathbb{N}}$  and the theory *1stOrderZFC* is much weaker than the theory *SetTheory*  $\langle \mathbb{N} \rangle$ :

- $\vdash_{1stOrderZFC} \text{ContinuumFor1stOrderZFC}$
- $\vdash_{1stOrderZFC} \neg \text{ContinuumFor1stOrderZFC}$

Cohen's result above is very far from being able to decide the following:

$$\vdash_{\text{Nat}} \text{ContinuumHypothesis}$$

<sup>85</sup> [Zermelo 1930, van Dalen 1998, Ebbinghaus 2007]

<sup>86</sup> 1<sup>st</sup> order theories fall prey to paradoxes like the Löwenheim–Skolem theorems (*e.g.* any 1<sup>st</sup> order theory of the real numbers has a countable model). Theorists have used the weakness of 1<sup>st</sup> order theory to prove results that do not hold in stronger formalisms such as Direct Logic [Cohen 1963, Barwise 1985].

<sup>87</sup> a restricted form of Model Checking in which the properties checked are limited to those that can be expressed in Linear-time Temporal Logic has been studied [Clarke, Emerson, Sifakis, *etc.* ACM 2007 Turing Award].

<sup>88</sup> proving that software developers and computer systems are using the same structures

<sup>89</sup> An implementation of such a system is given below in this article.

<sup>90</sup> the lambda calculus is a special case of Logic Programs

---

<sup>91</sup> cf. Plotkin [1976]

<sup>92</sup> only one model up to a unique isomorphism

<sup>93</sup> Rejection of the 1<sup>st</sup> Order Thesis resolves the seeming paradox between the formal proof in this article that Mathematics formally proves its own formal consistency and the proof that ‘Every “strong enough” formal system that admits a proof of its own consistency is actually inconsistent.’ [Paulson 2014]. Although Mathematics is “strong enough,” the absence of “self-referential” propositions (constructed using the **Y** untyped fixed point operator on propositions) blocks the proof of formal inconsistency to which Paulson referred.

<sup>94</sup> e.g. see Terminator [Knies 2006], which practically solves the halting problem for device drivers

<sup>95</sup> In order to show that the listed primitives are an adequate basis for  $Lam\langle t \rangle$ , it is sufficient to show that the **Substitute** combinator (called **S** in the literature) can be implemented. The following definition suffices:

$$\mathbf{Substitute}\langle t_1, t_2, t_3 \rangle : ([t_1, [[t_1] \rightarrow t_2, [t_2] \rightarrow t_3]] \rightarrow t_3)$$

$$\mathbf{Substitute}\langle t_1, t_2, t_3 \rangle . [x, \text{pair}] \equiv ((\mathbf{2nd} . [\text{pair}]) . [x]) . [\mathbf{1st} . [\text{pair}]] . [x]$$

<sup>96</sup> Because of Lambda Equality, the domain of [Scott 2015] is *not* a valid model of  $Lam\langle t \rangle$ .

<sup>97</sup> **Fix** implements recursion.

For example:

$$F : ([N] \rightarrow N) \rightarrow ([N] \rightarrow N)$$

$$F . [g] \equiv [i : N] \mapsto i = 1 \text{ if True then } 1, \text{ False then } i * g . [i - 1]$$

Therefore by the **Fix** axiom,  $\mathbf{Fix}\langle N, N \rangle . [F] = F . [\mathbf{Fix}\langle N, N \rangle . [F]]$  and

$\mathbf{Fix}\langle N, N \rangle . [F] = F . [\text{Factorial}] = \text{Factorial}$  where

$$\text{Factorial} \equiv [i : N] \mapsto i = 1 \text{ if True then } 1, \text{ False then } i * \text{Factorial} . [i - 1]$$

<sup>98</sup>  $t, t_1, t_2 : Type\langle \Lambda\langle t \rangle \rangle$

cf. [Vestergaard 2005]

<sup>99</sup> where  $F^1 . [x] \equiv F . [x]$

$$F^{n+1} . [x] \equiv F^n . [F . [x]]$$

<sup>100</sup> e.g., ones using concurrent Actors. See discussion in this article.

<sup>101</sup> cf. [Engeler 1981; Hindley, and Seldin 2008]

<sup>102</sup>  $t, t_1, t_2 : Type\langle \Lambda\langle t \rangle \rangle$

<sup>103</sup> Prove by induction on  $f, g : \Lambda\langle t \rangle$

---

<sup>104</sup>  $\Phi_1 \Rightarrow \Phi_2$  means  $\forall [i: \mathcal{N}] \Phi_1[i] \Rightarrow \Phi_2[i]$

Weakest precondition because:

$$\forall [\Psi: \text{Lam} \langle t \rangle^{\mathcal{N}}]$$

$$(\Psi \Rightarrow \lambda [i: \mathcal{N}] \Phi[f_{\bullet}[i]]) \Leftrightarrow (\Psi \Rightarrow \text{WeakestPrecondition}[\Phi, f])$$

<sup>105</sup> Robinson [1961]

<sup>106</sup> [Dedekind 1888]

<sup>107</sup> The following can be used to characterize the real numbers ( $\mathcal{R}$ ) up to a unique isomorphism:

$$\forall [S: \text{Set} \langle \mathcal{R} \rangle] S \neq \{\} \wedge \text{Bounded}[S] \Leftrightarrow \text{HasLeastUpperBound}[S]$$

where

$$\text{Bounded}[S: \text{Set} \langle \mathcal{R} \rangle] \Leftrightarrow \exists [b: \mathcal{R}] \text{UpperBound}[b, S]$$

$$\text{UpperBound}[b: \mathcal{R}, S: \text{Set} \langle \mathcal{R} \rangle] \Leftrightarrow b \in S \wedge \forall [x \in S] x \leq b$$

$$\text{HasLeastUpperBound}[S: \text{Set} \langle \mathcal{R} \rangle] \Leftrightarrow \exists [b: \mathcal{R}] \text{LeastUpperBound}[b, S]$$

$$\text{LeastUpperBound}[b: \mathcal{R}, S: \text{Set} \langle \mathcal{R} \rangle]$$

$$\Leftrightarrow \text{UpperBound}[b, S] \wedge \forall [x \in S] \text{UpperBound}[x, S] \Leftrightarrow x \leq b$$

<sup>108</sup> The theory of the ordinals *Ord* can be axiomatised as follows:

- $0_{\mathcal{O}}: \mathcal{O}$
- Successor ordinals
  - $\forall[\alpha: \mathcal{O}] +_1[\alpha]: \mathcal{O} \wedge +_1[\alpha] > \alpha$
  - $\forall[\alpha: \mathcal{O}] \nexists[\beta: \mathcal{O}] \alpha < \beta < +_1[\alpha]$
- Replacement for ordinals:
  - $\forall[\alpha: \mathcal{O}, f: \mathcal{O}^{\mathcal{O}}] \cup_{\alpha} f: \mathcal{O}$
  - $\forall[\alpha, \beta: \mathcal{O}, f: \mathcal{O}^{\mathcal{O}}] \beta \in \cup_{\alpha} f \Leftrightarrow \exists[\delta < \alpha] \beta \leq f[\delta]$
  - $\forall[\alpha, \beta: \mathcal{O}, f: \mathcal{O}^{\mathcal{O}}] (\forall[\delta < \alpha] f[\delta] \leq \beta) \Rightarrow \cup_{\alpha} f \leq \beta$
- Cardinal ordinals
 

$\omega_0 = \mathbb{N}$

$\forall[\alpha: \mathcal{O}] \alpha > 0_{\mathcal{O}} \Rightarrow \omega_{\alpha} \doteq \text{Boolean}^{\{\beta: \mathcal{O} \mid \beta < \omega_{\alpha}\}}$

$\forall[\alpha, \beta: \mathcal{O}] \beta \doteq \omega_{\alpha} \Rightarrow \omega_{\alpha} = \beta \vee \omega_{\alpha} \in \beta$

where  $t_1 \doteq t_2 \Leftrightarrow \exists[f: t_2^{t_1}] 1 \text{to} 1 \text{onto} \langle t_1, t_2 \rangle [f]$

$1 \text{to} 1 \langle t_1, t_2 \rangle [f: t_2^{t_1}] \Leftrightarrow \forall[x_1, x_2: t_1] f[x_1] = f[x_2] \Rightarrow x_1 = x_2$

$1 \text{to} 1 \text{onto} \langle t_1, t_2 \rangle [f: t_2^{t_1}]$

$\Leftrightarrow 1 \text{to} 1 \langle t_1, t_2 \rangle [f: t_2^{t_1}] \wedge \forall[y: t_2] \exists[x: t_1] f[x] = y$
- Transitivity of <
 

$\forall[\alpha, \beta < \alpha, \delta < \beta: \mathcal{O}] \alpha < \delta$
- $\forall[\alpha, \beta: \mathcal{O}] \alpha < \beta \vee \alpha = \beta \vee \beta < \alpha$
- $\forall[\alpha, \beta: \mathcal{O}] \alpha < \beta \Rightarrow \neg \beta < \alpha$

• The following ordinal induction axiom holds:

$$\forall[P: \text{Ord}^{\mathcal{O}}] (\forall[\alpha: \mathcal{O}] \forall[\beta < \alpha: \mathcal{O}] P[\beta] \Rightarrow P[\alpha]) \Rightarrow \forall[\alpha: \mathcal{O}] P[\alpha]$$

<sup>109</sup> For each type  $X$  that satisfies the theory *Ord* there is a unique isomorphism with  $\mathcal{O}$  that is  $I: X^{\mathcal{O}}$  inductively defined as follows:

$$I[0_{\mathcal{O}}] \equiv 0_X$$

$$\forall[\alpha: \mathcal{O}] I[+_1[\alpha]] \equiv +_1^X[I[\alpha]]$$

$$\forall[\alpha: \text{Limit} \langle \mathcal{O} \rangle] I[\alpha] \equiv y$$

$$\text{where } y: X \wedge \forall[\beta < \alpha] y \leq_X I[\beta] \wedge \forall[z: X] (\forall[\beta < \alpha] z \leq_X I[\beta]) \Rightarrow y \leq_X z$$



Using proofs by ordinal induction on  $\mathcal{O}$  and  $\mathcal{X}$ , the following follow:

1. I is defined for every  $\mathcal{O}$
2. I is one-to-one:  $\forall[\alpha, \beta: \mathcal{O}] I[\alpha] = I[\beta] \Rightarrow \alpha = \beta$
3. The range of I is all of  $\mathcal{X}$ :  $\forall[y: \mathcal{X}] \exists[\alpha: \mathcal{O}] I[\alpha] = y$
4. I is a homomorphism:
  - $I[0_{\mathcal{O}}] = 0_{\mathcal{X}}$
  - $\forall[\alpha: \mathcal{O}] I[+_1[\alpha]] = +_1^{\mathcal{X}}[I[\alpha]]$
  - $\forall[\alpha: \text{Limit} \langle \mathcal{O} \rangle, f: \mathcal{O}^{\mathcal{O}}] I[\bigcup_{\alpha} f] = \bigcup_{f[\alpha]} I \circ f \circ I^{-1}$
5.  $I^{-1}: \mathcal{O}^{\mathcal{X}}$  is a homomorphism
6. I is the unique isomorphism: If  $g: \mathcal{X}^{\mathcal{O}}$  is an isomorphism then  $g=I$

<sup>110</sup> Prove by ordinal induction on  $\alpha, \beta: \mathcal{O}$

<sup>111</sup> [Bourbaki 1972; Fantechi, et. al. 2005]

<sup>112</sup> This implies, for example, that no set is an element of itself.

<sup>113</sup> Proof: Suppose  $S: \text{Sets} \langle t \rangle$  and therefore  $\exists[\alpha: \mathcal{O}] S: \text{Sets}_{\alpha} \langle t \rangle$

Proof by ordinal induction on

$$P[\beta: \mathcal{O}] \equiv \forall[X \in S] X: \text{Sets}_{\beta} \langle t \rangle$$

$$\text{Assume: } (\forall[\beta < \alpha: \mathcal{O}] \forall[X \in S] X: \text{Set}_{\beta} \langle t \rangle) \Leftrightarrow \forall[X \in S] X: \text{Sets}_{\alpha} \langle t \rangle$$

Show:  $\forall[X \in S] X: \text{Sets}_{\alpha} \langle t \rangle$

Assume:  $X \in S$

Show  $X: \text{Sets}_{\alpha} \langle t \rangle$

Proof by cases on  $\alpha$

1.  $X: \text{Sets}_{0} \langle t \rangle$

$$X: \text{Boolean}^t$$

2.  $\forall[\alpha: \mathcal{O}] \text{Sets}_{\alpha} \langle t \rangle = \text{Set} \langle \text{Sets}_{\alpha-1} \langle t \rangle \rangle$

$X: \text{Sets}_{\alpha-1} \langle t \rangle$  QED by induction hypothesis

3.  $\forall[\alpha: \text{Limit} \langle \mathcal{O} \rangle] \exists[\beta < \alpha, Y: \text{Sets}_{\beta} \langle t \rangle] X \in Y$

QED by induction hypothesis

<sup>114</sup> Proof: Suppose  $S: \text{Sets} \langle t \rangle$  and therefore  $\exists[\alpha: \mathcal{O}] S: \text{Sets}_{\alpha} \langle t \rangle$

$S: \text{Sets}_{\alpha} \langle t \rangle$

Show:  $\text{Boolean}^S: \text{Sets} \langle t \rangle$

$\text{Boolean}^S: \text{Sets}_{\alpha+1} \langle t \rangle$  QED

---

<sup>115</sup> Proof by ordinal induction on

$P[\alpha: \mathcal{O}] \equiv \forall[S: \text{Sets}_\alpha \langle t \rangle] US: \text{Sets} \langle t \rangle$

Assume:  $\forall[\beta < \alpha: \mathcal{O}] \forall[S: \text{Sets}_\beta \langle t \rangle] US: \text{Sets} \langle t \rangle$

Show:  $\forall[S: \text{Sets}_\alpha \langle t \rangle] US: \text{Sets} \langle t \rangle$

Assume:  $S: \text{Sets}_\alpha \langle t \rangle$

Show:  $US: \text{Sets} \langle t \rangle$

$\forall[X: \text{Sets} \langle t \rangle] X \in US \Leftrightarrow \exists[Y \in S] X \in Y$

$\forall[X: \text{Sets} \langle t \rangle] X \in US \Leftrightarrow \exists[\beta < \alpha: \mathcal{O}, Y: \text{Sets}_\beta \langle t \rangle] X \in Y$

$\forall[X: \text{Sets} \langle t \rangle] X \in US \Rightarrow X: \text{Sets} \langle t \rangle$

QED by definition of  $\text{Sets} \langle t \rangle$

<sup>116</sup> Suppose  $f: \text{Sets} \langle t \rangle \xrightarrow{\text{Sets} \langle t \rangle}$  and  $S: \text{Sets} \langle t \rangle$

Show  $\text{Image} \langle t \rangle [f, S]: \text{Sets} \langle t \rangle$

Proof by ordinal induction on

$P[\alpha: \mathcal{O}] \Leftrightarrow S: \text{Sets}_\alpha \langle t \rangle \Rightarrow \text{Image} \langle t \rangle [f, S]: \text{Sets} \langle t \rangle$

Suppose  $\forall[\beta < \alpha: \mathcal{O}] S: \text{Sets}_\beta \langle t \rangle \Rightarrow \text{Image} \langle t \rangle [f, S]: \text{Sets} \langle t \rangle$

Show  $S: \text{Sets}_\alpha \langle t \rangle \Rightarrow \text{Image} \langle t \rangle [f, S]: \text{Sets} \langle t \rangle$

Suppose  $S: \text{Sets}_\alpha \langle t \rangle$

Show  $\text{Image} \langle t \rangle [f, S]: \text{Sets} \langle t \rangle$

$\forall[y: \text{Sets} \langle t \rangle] y: \text{Image} \langle t \rangle [f, S] \Leftrightarrow \exists[x \in S] f[x]=y$

Show  $\forall[y: \text{Sets} \langle t \rangle] y \in \text{Image} \langle t \rangle [f, S] \Rightarrow y: \text{Sets} \langle t \rangle$

Suppose  $y: \text{Sets} \langle t \rangle \wedge y \in \text{Image} \langle t \rangle [f, S]$

Show  $y: \text{Sets} \langle t \rangle$

$\exists[x \in S] f[x]=y$  because  $y \in \text{Image} \langle t \rangle [f, S]$

$\exists[\beta < \alpha: \mathcal{O}] x: \text{Sets}_\beta \langle t \rangle$  because  $x \in S$  and  $S: \text{Sets}_\alpha \langle t \rangle$

$\text{Image} \langle t \rangle [f, x]: \text{Sets} \langle t \rangle$  by induction hypothesis

Show  $f[x]: \text{Sets} \langle t \rangle$

Suppose  $z \in f[x]$

Show  $z: \text{Sets} \langle t \rangle$

$z \in \text{Sets} \langle t \rangle$  because  $z \in f[x]$  and  $\text{Image} \langle t \rangle [f, x]: \text{Sets} \langle t \rangle$

$f[x]: \text{Sets} \langle t \rangle$

$y: \text{Sets} \langle t \rangle$  because  $f[x]=y$

<sup>117</sup> Consequently,  $\text{Sets} \langle t \rangle$  is *much stronger* than 1<sup>st</sup> order ZFC.

- 
- <sup>118</sup> Note that this proof is fundamentally different from the categoricity proof in [Martin 2015].
- <sup>119</sup> Prove by ordinal rank on  $s_1, s_2: \text{Set}_y \langle t \rangle$
- <sup>120</sup> According to [Russell 1908]:  
if Epimenides asserts “all first-order propositions affirmed by me are false,” he asserts a second-order proposition.
- <sup>121</sup> Note that the Berry paradox is blocked using strong types because BString is a string for a term of a proposition of anOrder+1 thereby preventing it from being substituted for a string for a term of a proposition of anOrder.  
substituting BNumber for n
- <sup>122</sup> There is no universal type. Instead, *Type* is parameterized, e.g.,  
*Boolean: Type*  $\langle \text{Boolean} \rangle$  and *N: Type*  $\langle N \rangle$
- <sup>123</sup> **True**  $\neq$  **False**, **True: Boolean**, and **False: Boolean**  
 $\forall [x: \text{Boolean}] x = \text{True} \vee x = \text{False}$
- <sup>125</sup> *N* is the type of the natural numbers
- <sup>126</sup> *O* is the type of ordinals
- <sup>127</sup> *Actor* is the type of Actors
- <sup>128</sup> term of type *t*. The following axiom holds:  
 $\forall [t::, x: \text{Term} \langle t \rangle] [x]::t$
- <sup>129</sup> expression of type *t*. The following axiom holds:  
 $\forall [t::, e: \text{Expression} \langle t \rangle] [e]::t$
- <sup>130</sup>  $\Lambda \langle t \rangle$  is the type of lambda procedures over *t*
- <sup>131</sup> string of type *t*. The following axiom holds:  
 $\forall [t::, s: \text{String} \langle t \rangle] [s]::t$
- <sup>132</sup> type of type *t*
- <sup>133</sup>  $\forall [t::] t: \text{Type} \langle t \rangle$
- <sup>134</sup> *Proposition*  $\langle \text{anOrder} \rangle$  is the parametrized type consisting of type *Proposition* parametrized by anOrder.
- <sup>135</sup> *Sentence*  $\langle \text{anOrder} \rangle$  is the parametrized type consisting of type *Sentence* parametrized by anOrder.
- <sup>136</sup> Discrimination of  $t_1$  and  $t_2$   
For  $i=1,2$
- If  $x: t_i$ , then  $((t_1 \oplus t_2)[x]): (t_1 \oplus t_2)$  and  $x = ((t_1 \oplus t_2)[x]) \downarrow t_i$
  - $\forall [z: t] z: t_1 \oplus t_2 \Leftrightarrow \exists [x: t_i] z = (t_1 \oplus t_2)[x]$
- <sup>137</sup> type of 2-element list with first element of type  $t_1$  and with second element of type  $t_2$

- 
- 138 Type of computable *nondeterministic* procedures from  $t_1$  into  $t_2$ .  
 If  $f:([t_1] \rightarrow t_2)$  and  $x:t_1$ , then  $f.[x]:t_2$
- 139 Type of computable *deterministic* procedures from  $t_1$  into  $t_2$ .  
 If  $f:([t_1] \rightarrow_1 t_2)$  and  $x:t_1$ , then  $f.[x]:t_2$ .
- 140 Type of functions from  $t_1$  into  $t_2$ . If  $f:t_2^{t_1}$  and  $x:t_1$ , then  $f[x]:t_2$ .
- 141  $\forall[x:t] x:t \nexists P \Leftrightarrow P[x]$   
 For example,  
 $\forall[t::, X: \text{Set} \langle \text{Set} \langle t \rangle \rangle] \cup X \equiv t \nexists \lambda[y:t] \exists[Z: \text{Set} \langle t \rangle] Z \in X \wedge y \in Z$
- 142  $t_1$  is a subtype of  $t_2$ , i.e.,  $\forall[x:t_1] x:t_2$
- 143 *Theory*  $\equiv$  *Boolean Proposition*, i.e., sets of propositions
- 144 meaning  $\forall[x:t] P[x]$
- 145 meaning  $\exists[x:t] P[x]$
- 146 meaning  $\lambda[x:t] P[x]$
- 147 *Mapping*  $\langle t_1, t_2 \rangle \equiv t_2^{t_1 t_2^{t_1}}$   
 $\text{Fixer} \langle t_1, t_2 \rangle : \text{Mapping} \langle t_1, t_2 \rangle \text{Mapping} \langle t_1, t_2 \rangle$   
 $\text{Fixer} \langle t_1, t_2 \rangle [F] = F[\text{Fixer} \langle t_1, t_2 \rangle [F]]$
- 148 **(if  $e_1$  then  $e_2$  else  $e_3$ )**
- 149 *Functional*  $\langle t_1, t_2 \rangle \equiv [([t_1] \rightarrow t_2)] \rightarrow ([t_1] \rightarrow t_2)$   
 $\text{Fix} \langle t_1, t_2 \rangle : ([\text{Functional} \langle t_1, t_2 \rangle] \rightarrow \text{Functional} \langle t_1, t_2 \rangle)$   
 $\text{Fix} \langle t_1, t_2 \rangle . [F] = F . [\text{Fix} \langle t_1, t_2 \rangle . [F]]$
- 150 i.e. **( $[x:t] \mapsto E.[x]$ )**
- 151 i.e. **( $[x:t] \mapsto P[x]$ )**
- 152 The type of **( $p[x]$ )** means that the untyped **Y** fixed point construction cannot be used to construct sentences for “self-referential” propositions in Direct Logic.
- 153 The type of **( $p[x]$ )** means that the untyped **Y** fixed point construction cannot be used to construct sentences for “self-referential” propositions in Direct Logic.
- 154 Constructing propositions from sentences achieves much of what Russel sought to achieve in the ramified theory of types. [Russell and Whitehead 1910-1913]

---

<sup>155</sup> A contradiction in an empirical theory (which may have inconsistencies) causes detonation of the theory using unrestricted versions of the rules below.

- **Unlimited Disjunction Introduction** detonates every inconsistent empirical theory  
 Suppose Unlimited Disjunction Introduction always holds, i.e.,  

$$\forall[\Psi, \Phi: \textit{Proposition}] \Psi \vdash \Psi \vee \Phi.$$
 Therefore  $\forall[\Psi, \Phi: \textit{Proposition}] \Psi, \neg\Psi \vdash \Phi$  (which detonates the theory) using  $\neg\Psi, \Psi \vee \Phi \vdash \Phi$ .
- **Unlimited Contrapositive** detonates every inconsistent empirical theory  
 Suppose Unlimited Contrapositive always holds, i.e.,  

$$\forall[\Psi, \Phi: \textit{Proposition}] (\Psi \vdash \Phi) \vdash (\neg\Phi \vdash \neg\Psi).$$
 Therefore  $\Psi \vdash \neg(\neg\Psi \wedge \neg\Phi)$  because  $\neg\Psi \wedge \neg\Phi \vdash \neg\Psi$  by monotonicity. Consequently,  $\forall[\Psi, \Phi: \textit{Proposition}] \Psi \vdash \Psi \vee \Phi$  (which detonates the theory using Unlimited Disjunction Introduction) by contrapositive because  $\neg(\neg\Psi \wedge \neg\Phi) \vdash \Psi \vee \Phi$ .
- **Unlimited Excluded Middle** detonates every inconsistent empirical theory [Kao 2015]  
 Suppose Unlimited Excluded Middle always holds, i.e.,  

$$\forall[\Psi, \Phi: \textit{Proposition}] \vdash \Psi \vee \neg\Psi.$$
 Therefore  $\vdash (\Theta \vee \Phi) \vee \neg(\Theta \vee \Phi)$ . by instantiating Excluded Middle with  $\Theta \vee \Phi$ . Consequently,  $\vdash \Theta \vee \neg\Theta \vee \Phi$ . Therefore  $\forall[\Psi, \Phi: \textit{Proposition}] \Psi \vdash \Psi \vee \Phi$  (which detonates the theory using Unlimited Disjunction Introduction) using  $\neg\Psi, \Psi \vee \Phi \vdash \Phi$ .
- **Unlimited By Contradiction** detonates every inconsistent empirical theory  
 Suppose Unlimited By Contradiction always holds, i.e.,  

$$\forall[\Psi, \Phi: \textit{Proposition}] (\Phi \vdash \Psi \wedge \neg\Psi) \vdash \neg\Phi$$
 Therefore  $\forall[\Psi, \Phi: \textit{Proposition}] \Psi, \neg\Psi \vdash \Phi$ , which detonates the theory.

---

<sup>156</sup> The following are axioms for  $\models$ :

- $\models \mathbf{True}$
- $\neg \models \mathbf{False}$
- $(\models \Phi \wedge \Psi) \Leftrightarrow (\models \Phi) \wedge (\models \Psi)$
- $(\models \Phi \vee \Psi) \Leftrightarrow (\models \Phi) \vee (\models \Psi)$
- $(\models \neg \Phi) \Leftrightarrow \neg \models \Phi$
- $(\models (\Phi \vdash \Psi)) \Leftrightarrow ((\models \Phi) \Rightarrow (\models \Psi))$