



# Pre-Coded NRZ and Electrical Duo-Binary Transmission in C and O-band at Data Bit Rates up to 25 Gbit/s

Justine Konopacki, Bertrand Le Guyader, Naveena Genay, Luiz Anet Neto,  
Philippe Chanclou, Didier Erasme

## ► To cite this version:

Justine Konopacki, Bertrand Le Guyader, Naveena Genay, Luiz Anet Neto, Philippe Chanclou, et al.. Pre-Coded NRZ and Electrical Duo-Binary Transmission in C and O-band at Data Bit Rates up to 25 Gbit/s. ICTON, Jul 2017, Girona, Spain. , ICTON, 2017. hal-01569728

HAL Id: hal-01569728

<https://hal.science/hal-01569728>

Submitted on 27 Jul 2017

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

# Pre-coded NRZ and Electrical Duo-Binary Transmission in C and O-band at Data Bit Rates Up To 25 Gbit/s

Justine Konopacki<sup>1-2</sup>, Bertrand Le Guyader<sup>1</sup>, Naveena Genay<sup>1</sup>, Luiz Anet Neto<sup>1</sup>, Philippe Chanclou<sup>1</sup>, Didier Erasme<sup>2</sup>

(1) Orange Labs, 2 avenue Pierre-Marzin, 22307 Lannion, France

(2) LTCI, Télécom ParisTech, Université Paris-Saclay, 75013 Paris, France

**Abstract** We present real-time transmission performance up to 25 Gbit/s for optical access networks.

- Based on pre-coded NRZ and electrical duo-binary modulations
- Using limited electrical bandwidth DML in C and O-band at transceiver
- And an electrical duo-binary receiver with an 8 GHz APD photodiode and a duo-binary to binary converter

## Data bit rates evolution in the optical access network



- Presently PON solutions are based on NRZ modulation formats. [1-4]
- Standardization groups are working on 25 Gbit/s PON.
- Solutions proposed:
  - NRZ coupled with electrical equalization [5, 6]
  - Efficient modulation formats such as PAM-4 [7, 8] & duo-binary [9, 10]

## EDB modulation format

- What is EDB ?

NRZ	EDB
0	0
1	+1 or -1


- Where ?  
At Tx → coder  
At Rx → 8 GHz APD




EDB electrical spectrum is compressed by a factor 2 compared to a NRZ signal at the same data bit rate [9].  
Opportunity to re-use optical components already developed for 10 Gbit/s transmission.

## EDB and pre-coded NRZ (p-NRZ) transmission experimental setup

- Tx: 14/16 GHz C/O band DML
- Rx: 8 GHz APD/TIA → EDB detection
- Duo-binary to NRZ decoder: APD out and out + limiting amplifiers + XOR gate



## O band performance




## Conclusion

### O-band transmission

At 25 Gbit/s, up to 40 km propagation with 26.5 dB OB using pre-coded NRZ emission.

At 20 Gbit/s, up to 40 km propagation with 28 dB OB using EDB & pre-coded NRZ emission.

## C band performance



### C-band transmission

Performance is worse due to chromatic dispersion.  
At 20 Gbit/s, up to 10 km propagation with 28 dB OB with pre-coded NRZ emission. Use pre-equalization and mitigation techniques to increase performance.

## References:

- [1] ITU-T.G.984, "Gigabit-capable passive optical networks (GPON): General characteristics" (2008)
- [2] ITU-T.G.987, "10-Gigabit-capable passive optical networks (XG-PON): General requirements", (2010)
- [3] ITU-T.G.989, "40-Gigabit-capable passive optical networks (NG-PON2): General requirements", (2013)
- [4] "IEEE P802.3ca 100G-EPON PHY Task Force," IEEE Std 802.3-2015 (2016)
- [5] Jin Wang and Joseph M. Kahn, "Performance of Electrical Equalizers in Optically Amplified OOK and DPSK Systems", IEEE Photonics Technology Letters, VOL. 16, NO. 5 (2004)
- [6] Dr. Pulidindi Venugopal, Y.S.V.S.R. Karthik and Jariwala Rudra A, "10Gbps Optical Line Using Electronic Equalizer and its Cost Effectiveness", International Journal of Engineering and technology (IJET), VOL. 5, NO. 4 (2013)
- [7] X. Li, S. Zhou, H. Ji, M. Luo, Q. Yang, L. Yi, R. Hu, C. Li, S. Fu, A. Alphones, W.D. Zhong c. Yu, "Transmission of 4x28-Gb/s PAM-4 over 160-km Single Mode Fiber using 10G-Class DML and Photodiode", OFC, W1A.5, (2016)
- [8] C. Sun, S. H. Bae, H. Kim, "Transmission of 28-Gb/s Duobinary and PAM-4 signal Using DML for Optical Access Network", IEEE Photonics Technology Letters, (2016)
- [9] A. Lender, "The Duobinary Technique for High-Speed Data Transmission", (1963)