



**HAL**  
open science

# $L^\infty$ -Stability of IMEX-BDF2 Finite Volume Scheme for Convection-Diffusion Equation

Caterina Calgaro, Meriem Ezzoug

► **To cite this version:**

Caterina Calgaro, Meriem Ezzoug.  $L^\infty$ -Stability of IMEX-BDF2 Finite Volume Scheme for Convection-Diffusion Equation. FVCA 2017: Finite Volumes for Complex Applications VIII - Methods and Theoretical Aspects, Jun 2017, Lille, France. pp.245-253, 10.1007/978-3-319-57397-7\_17. hal-01574893

**HAL Id: hal-01574893**

**<https://hal.science/hal-01574893>**

Submitted on 16 Aug 2017

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

# $L^\infty$ -stability of IMEX-BDF2 finite volume scheme for convection-diffusion equation

Caterina Calgaro and Meriem Ezzoug

**Abstract** In this paper, we propose a finite volume scheme for solving a two-dimensional convection-diffusion equation on general meshes. This work is based on a implicit-explicit (IMEX) second order method and it is issued from the seminal paper [2]. In the framework of MUSCL methods, we will prove that the local maximum property is guaranteed under an explicit Courant-Friedrichs-Levy condition and the classical hypothesis for the triangulation of the domain.

**Key words:** Convection-diffusion equation, finite volume scheme, IMEX-BDF2 scheme,  $L^\infty$ -stability

**MSC (2010):** 65M99, 76M12, 76E17

## 1 Introduction

Convection-diffusion processes appear in many areas of science, e.g. fluid dynamics or heat and mass transfer. In the study of the evolution of a mixture, the system of PDEs derives from the compressible Navier-Stokes equations. The mixture of two viscous fluids is described by the density  $\rho \geq 0$ , the *mass velocity* field  $\mathbf{v}$  (which is not solenoidal) and the pressure  $p$ . Following Kazhikhov and Smagulov [11], we set

$$\mathbf{u} = \mathbf{v} + \lambda \nabla \ln(\rho), \quad (1)$$

---

Caterina Calgaro  
Univ. Lille, CNRS, UMR 8524 - Laboratoire Paul Painlevé,  
F-59000 Lille, France  
e-mail: caterina.calgaro@univ-lille1.fr

Meriem Ezzoug  
UR: Multifractals et Ondelettes. FSM. Université de Monastir. 5019 Monastir, Tunisie  
ISSIG. Université de Gabès. 6032 Gabès, Tunisie  
e-mail: meriemezzoug@yahoo.fr

for some mass diffusion coefficient  $\lambda > 0$ . This Fick's law describes the diffusive fluxes of one fluid into the other. Clearly, the *volume velocity* field  $\mathbf{u}$  satisfies  $\operatorname{div} \mathbf{u} = 0$  and we obtain the non-standard constraint  $\operatorname{div} \mathbf{v} = -\operatorname{div}(\lambda \nabla \ln(\rho))$ , which is relied on the definition of the pressure  $p$ . Using (1), the mass conservation equation becomes

$$\frac{\partial \rho}{\partial t} + \operatorname{div}(\rho \mathbf{u}) = \lambda \Delta \rho. \quad (2)$$

The momentum equation can also be rewritten in order to obtain the Kazhikhov-Smagulov model [11]. This model was firstly studied in [14, 1] (see also references therein). The mathematical analysis in a three-dimensional domain of Kazhikhov-Smagulov type models was carried out in recent works [5, 8], where the authors study the Kazhikhov-Smagulov models with a specific Korteweg stress tensor. The numerical study of a Kazhikhov-Smagulov model for the two-dimensional case can be found in [4], where the authors propose an hybrid finite volume-finite element method combined with the backward Euler method in time. In order to generalize the analysis given in [4] to second-order methods in time and space, the first goal is to recover the  $L^\infty$ -stability of the finite volume method used for the convection-diffusion equation. This is the purpose of this paper.

## 2 Description of the numerical scheme

This section is devoted to the design of a numerical scheme to approximate (2), using the vertex-based MUSCL finite volume methods introduced in [13] and used in [2] for a second-order accuracy in space, and an implicit-explicit (IMEX) linear multistep methods [10] for a second-order in time.

**Mesh definitions and notations.** Let  $\Omega$  be an open bounded polygonal subset on  $\mathbb{R}^2$ , with sufficiently regular boundary  $\partial\Omega$ , and  $[0, T]$  the time interval, for  $T > 0$ . The discretization of (2) will be carried out on an unstructured triangular mesh. We denote by  $\mathcal{T}_h$  a partition of  $\Omega$  composed of conforming and isotropic triangles  $T_k$ ,  $k \in [1, K]$ , with  $K \in \mathbb{N}^*$ . The  $\mathcal{T}_h$  is called the *primal mesh*. We suppose the following hypotheses:

- (H1) Let  $\{\mathcal{T}_h\}_{h>0}$  be a *regular* family of triangulations of  $\Omega$ .
- (H2) The triangulation  $\mathcal{T}_h$  is of *weakly acute type* (no triangle with an angle greater than  $\pi/2$ ).

For each element  $T \in \mathcal{T}_h$ , we denote  $B_T$  the barycenter of the triangle,  $|T|$  the area of  $T$ , and  $M_i, M_{j_1}, M_{j_2}$  the three vertices of  $T$ . We also denote respectively  $M_{i_{j_1}}$  and  $M_{i_{j_2}}$  the middles of  $[M_i M_{j_1}]$  and  $[M_i M_{j_2}]$ .

Let us construct the *dual mesh*  $\mathcal{C}_h = \{\mathcal{C}_i, i \in [1, I]\}$ , which defines a second partition of  $\Omega$ , ( $I \in \mathbb{N}^*$  is the number of vertices of  $\mathcal{T}_h$ ). The dual finite volume  $\mathcal{C}_i$  associated with each vertex  $M_i$ ,  $i \in [1, I]$ , is a closed polygon obtained in the following way: we join the barycenter  $B_T$  of every triangle  $T \in \mathcal{T}_h$  which share the vertex  $M_i$  with

the middle point of every side of  $T$  containing  $M_i$  (see Fig. 1). If  $M_i \in \partial\Omega$ , then we complete the boundary of  $\mathcal{C}_i$  by the segments joining  $M_i$  with the middle point of boundary sides that contain  $M_i$ .  $\mathcal{C}_i$  is often called the vertex-based control volume around the node  $M_i$ . Accordingly, we have  $\cup_{T \in \mathcal{T}_h} T = \bar{\Omega} = \cup_{i \in [1, I]} \mathcal{C}_i$ .


Moreover, if we denote  $|\mathcal{C}_i|$  the area of  $\mathcal{C}_i \in \mathcal{C}_h$ , then  $|\mathcal{C}_i| = \sum_{T, M_i \in T} \frac{|T|}{3}$ .

For  $i \in [1, I]$ , let  $\mathcal{V}(i) = \{j \in [1, I], \mathcal{C}_j \text{ is a neighbor of } \mathcal{C}_i\}$ . For  $l = 1, 2$ , we denote  $\Gamma_{ij_l}^{(T)}$  the segment  $[M_{ij_l} B_T]$ ,  $A_{ij_l}^{(T)}$  its middle point,  $\mathbf{n}_{ij_l}^{(T)}$  the unit outward normal to  $\mathcal{C}_i$  along  $\Gamma_{ij_l}^{(T)}$  and  $|\Gamma_{ij_l}^{(T)}|$  the length of  $\Gamma_{ij_l}^{(T)}$ . For  $T \in \mathcal{T}_h$  and  $M_i \in T$ , we have:

$$\sum_{l=1}^2 |\Gamma_{ij_l}^{(T)}| \mathbf{n}_{ij_l}^{(T)} = -|T| \nabla \psi_i, \quad (3)$$

where  $\psi_i$  is the  $\mathbb{P}_1$  basis function associated to the vertex  $M_i$  of  $T$ . For every  $\mathcal{C}_i \in \mathcal{C}_h$ , the boundary of  $\mathcal{C}_i$  is

$$\partial \mathcal{C}_i = \bigcup_{T, M_i \in T} \left( \Gamma_{ij_1}^{(T)} \cup \Gamma_{ij_2}^{(T)} \right). \quad (4)$$



**Fig. 1** Dual mesh-Vertex based control volume  $\mathcal{C}_i$  around the node  $M_i$ .

**IMEX-BDF2 finite volume scheme.** Here, we describe the finite volume scheme for solving (2). In order to obtain the density reconstruction on the interfaces  $\Gamma_{ij_l}^{(T)}$ , we use the MUSCL technique with a multislope gradient reconstruction. Concerning the time discretization, we adapt the implicit-explicit (IMEX) linear 2-step methods using *extrapolated BDF2* scheme for the convective term combined with *implicit BDF2* scheme for the diffusive term. The velocity field  $\mathbf{u}(t, \mathbf{x}) \in \mathbb{R}^2$  is a given function verifying the divergence free condition. For the space discretization, the usual vertex-based finite volume scheme on control volume  $\mathcal{C}_i$ , for all  $i \in [1, I]$ , reads

$$\frac{d}{dt} \int_{\mathcal{C}_i} \rho(t, \mathbf{x}) d\mathbf{x} + \int_{\partial\mathcal{C}_i} \rho(t, \mathbf{x}) \mathbf{u}(t, \mathbf{x}) \cdot \mathbf{n} d\sigma = \lambda \int_{\partial\mathcal{C}_i} \nabla \rho(t, \mathbf{x}) \cdot \mathbf{n} d\sigma. \quad (5)$$

We denote by  $\Delta t$  the time step and  $t^n = n\Delta t$ ,  $n \geq 0$ , but variable time steps can also be used. Then, the approximate solution  $\rho_i^n$ ,  $i \in [1, I]$ , at time  $t^n$ , verifies

$$\rho_i^n \approx \frac{1}{|\mathcal{C}_i|} \int_{\mathcal{C}_i} \rho(t^n, \mathbf{x}) d\mathbf{x}.$$

In particular, the numerical approximation of the density is a piecewise constant function in space on the control volume  $\mathcal{C}_i$ . For the time discretization, we consider the implicit BDF2 scheme and an extrapolated BDF2 scheme following [10]. With this choice, we obtain a second-order accuracy in time. Then, the equation (5) is rewritten as follows, for each  $i \in [1, I]$  and  $n \geq 1$ ,

$$\begin{aligned} \rho_i^{n+1} - \frac{2\lambda}{3} \frac{\Delta t}{|\mathcal{C}_i|} \int_{\partial\mathcal{C}_i} \nabla \rho(t^{n+1}, \mathbf{x}) \cdot \mathbf{n} d\sigma &= \frac{4}{3} \rho_i^n - \frac{4}{3} \frac{\Delta t}{|\mathcal{C}_i|} \int_{\partial\mathcal{C}_i} \rho(t^n, \mathbf{x}) \mathbf{u}(t^n, \mathbf{x}) \cdot \mathbf{n} d\sigma \\ &\quad - \frac{1}{3} \rho_i^{n-1} + \frac{2}{3} \frac{\Delta t}{|\mathcal{C}_i|} \int_{\partial\mathcal{C}_i} \rho(t^{n-1}, \mathbf{x}) \mathbf{u}(t^{n-1}, \mathbf{x}) \cdot \mathbf{n} d\sigma. \end{aligned} \quad (6)$$

In order to approximate  $\nabla \rho(t^{n+1}, \mathbf{x})$  in (6), we consider a  $\mathbb{P}_1$ -finite element approach for the density such that

$$\rho|_T^{n+1} \approx \sum_{M_j \in T} \psi_j \rho_j^{n+1}, \quad \text{for all } T \in \mathcal{T}_h,$$

with  $\{\psi_j\}_{j \in [1, I]}$  the canonical basis of the usual  $\mathbb{P}_1$  finite element space. Using (3) and (4), we find  $\rho_i^{n+1}$ ,  $i \in [1, I]$ ,  $n \geq 1$ , verifying the following second-order *IMEX-BDF2 finite volume scheme*:

$$\begin{aligned} \rho_i^{n+1} + \frac{2\lambda}{3} \frac{\Delta t}{|\mathcal{C}_i|} \sum_{T, M_i \in T} |T| \sum_{M_j \in T} \nabla \psi_i \cdot \nabla \psi_j \rho_j^{n+1} \\ = \frac{4}{3} \rho_i^n - \frac{4}{3} \frac{\Delta t}{|\mathcal{C}_i|} \sum_{T, M_i \in T} \sum_{l=1}^2 |\Gamma_{ij_l}^{(T)}| G_{ij_l}^n(\rho_{ij_l}^n, \rho_{ji}^n) \\ - \frac{1}{3} \rho_i^{n-1} + \frac{2}{3} \frac{\Delta t}{|\mathcal{C}_i|} \sum_{T, M_i \in T} \sum_{l=1}^2 |\Gamma_{ij_l}^{(T)}| G_{ij_l}^{n-1}(\rho_{ij_l}^{n-1}, \rho_{ji}^{n-1}). \end{aligned} \quad (7)$$

Here we denote by  $G_{ij_l}(\rho_1, \rho_2)$  a numerical flux that satisfies the consistency, conservativity and monotonicity properties. In particular, for any constant function  $\rho_1$ , we have

$$\sum_{k \in \mathcal{V}(i)} |\Gamma_{ik}^{(T)}| G_{ik}(\rho_1, \rho_1) = 0. \quad (8)$$

In [2],  $G_{ij_l}$  is the upstream flux, but many other numerical fluxes can be considered, as for instance Lax-Friedrichs or Engquist-Osher fluxes. We underline that for multi-

physics coupled models, a particular attention must be paid in the approximation of the continuous velocity associated to any point of  $\partial\mathcal{C}_i$  (see [3]).

In (7),  $\rho_{ij_l}$  and  $\rho_{ji}$  denote the density reconstructions on the segments  $\Gamma_{ij_l}^{(T)}$ , for  $l = 1, 2$ . In order to reach a second-order accuracy in space, we use the MUSCL technique [13] with a multislope gradient reconstruction. Introducing  $\widehat{M} = [M_{j_1} M_{j_2}] \cap (M_i A_{ij_l}^{(T)})$  and  $\widehat{N} \in [M_{k_1} M_{k_2}] \cap (M_i A_{ij_l}^{(T)})$ , we define

$$\rho_{ij_l}^{\text{up}} = \frac{\rho_i - \rho_{\widehat{N}}}{\|M_i \widehat{N}\|} \quad \text{and} \quad \rho_{ij_l}^{\text{down}} = \frac{\rho_{\widehat{M}} - \rho_i}{\|M_i \widehat{M}\|}.$$

Then,  $\rho_{ij_l}$  is the density evaluated at node  $A_{ij_l}^{(T)}$ , defined as:

$$\rho_{ij_l} = \rho_i + \widehat{p}_{ij_l} \|M_i A_{ij_l}^{(T)}\|, \quad \text{with} \quad \widehat{p}_{ij_l} = p_{ij_l}^{\text{up}} \text{Lim} \left( \frac{p_{ij_l}^{\text{down}}}{p_{ij_l}^{\text{up}}} \right),$$

where Lim is a so-called "τ-limiter" (for details see [2]). In particular, they have the following result:

**Lemma 1.** *There exists some coefficients  $\omega_{ij_l k} \geq 0$ ,  $k \in \mathcal{V}(i)$ , such that*

$$\rho_{ij_l} - \rho_i = \sum_{k \in \mathcal{V}(i)} \omega_{ij_l k} (\rho_i - \rho_k)$$

holds, and furthermore, they verify  $\sum_{k \in \mathcal{V}(i)} \omega_{ij_l k} \leq \frac{7\tau}{12} C_{\mathcal{T}_h}$ , where the constant  $C_{\mathcal{T}_h}$  characterizes the mesh regularity (but it is more general than the classical Ciarlet ratio) and  $\tau > 0$  is used in the definition of the τ-limiter.

### 3 $L^\infty$ -stability of the numerical scheme

The IMEX-BDF2 finite volume scheme (7) is rewritten as linear system:

$$\mathbf{A} \boldsymbol{\rho}^{n+1} = \mathbf{F}^n, \tag{9}$$

where the matrix  $\mathbf{A}$  and the right hand side  $\mathbf{F}^n$  are defined as follows:

$$\begin{aligned} A_{i,i} &= 1 + 2\lambda \Delta t \sum_{T, M_i \in T} \|\nabla \psi_i\|^2, \quad A_{i,j} = 2\lambda \Delta t \sum_{T, M_i \neq M_j \in T} \nabla \psi_i \cdot \nabla \psi_j, \quad \forall i, j \in [1, I], \\ F_i^n &= \frac{4}{3} \rho_i^n - \frac{4}{3} \frac{\Delta t}{|\mathcal{C}_i|} \sum_{T, M_i \in T} \sum_{l=1}^2 |\Gamma_{ij_l}^{(T)}| G_{ij_l}^n(\rho_{ij_l}^n, \rho_{ji}^n) \\ &\quad - \frac{1}{3} \rho_i^{n-1} + \frac{2}{3} \frac{\Delta t}{|\mathcal{C}_i|} \sum_{T, M_i \in T} \sum_{l=1}^2 |\Gamma_{ij_l}^{(T)}| G_{ij_l}^{n-1}(\rho_{ij_l}^{n-1}, \rho_{ji}^{n-1}), \quad \forall i \in [1, I]. \end{aligned}$$

Under the hypotheses (H1) and (H2) on the mesh  $\mathcal{T}_h$ , the matrix  $\mathbf{A}$  is an M-matrix.

*Remark 1.* The hypothesis (H2), necessary to establish error estimates, is classical for the vertex-centered finite volume scheme [12] or the combined finite volume-finite element scheme [9]. Obviously, the M-matrix property still holds for Delaunay triangulations (see [6], Sect. 3.4).

Now, we prove the following result:

**Proposition 1.** *If for any  $n \geq 1$ , we have  $\rho^{n-1} \geq 0$  and  $\rho^n \geq 0$ , then the right hand side of linear system (9) satisfy  $\mathbf{F}^n \geq 0$  under the CFL condition:*

$$\Delta t \leq \min_{1 \leq i \leq I} \frac{|\mathcal{C}_i|}{\frac{2}{3} \left( \frac{7\tau}{12} C_{\mathcal{F}_h} + 2 \right) \|\mathbf{u}\|_{i,\infty} \sum_{T, M_i \in T} \left( |\Gamma_{ij_1}^{(T)}| + |\Gamma_{ij_2}^{(T)}| \right)}, \quad (10)$$

with  $\|\mathbf{u}\|_{i,\infty} = \max_{T, M_i \in T} \|\mathbf{u}_T\|_{l^2(\mathbb{R}^2)}$  where  $\mathbf{u}_T$  is the cell average velocity.

*Proof.* Let  $i \in [1, I]$  and  $n \geq 1$ . Thanks to (8), the  $i$ -th row of (9) is given by:

$$\begin{aligned} \left( \mathbf{A} \rho^{n+1} \right)_i &= \frac{4}{3} \rho_i^n - \frac{4}{3} \frac{\Delta t}{|\mathcal{C}_i|} \sum_{T, M_i \in T} \sum_{l=1}^2 |\Gamma_{ij_l}^{(T)}| \left( G_{ij_l}^n(\rho_{ij_l}^n, \rho_{j_l i}^n) - G_{ij_l}^n(\rho_i^n, \rho_i^n) \right) \\ &- \frac{1}{3} \rho_i^{n-1} + \frac{2}{3} \frac{\Delta t}{|\mathcal{C}_i|} \sum_{T, M_i \in T} \sum_{l=1}^2 |\Gamma_{ij_l}^{(T)}| \left( G_{ij_l}^{n-1}(\rho_{ij_l}^{n-1}, \rho_{j_l i}^{n-1}) - G_{ij_l}^{n-1}(\rho_i^{n-1}, \rho_i^{n-1}) \right). \end{aligned} \quad (11)$$

Let us introduce some definitions and notations dropping the time indices, such that

$$\Delta \rho_{ij_l} = \rho_{ij_l} - \rho_i, \quad \tilde{\Delta} \rho_{ij_l} = \rho_{j_l i} - \rho_i, \quad \text{for } l = 1, 2.$$

Thanks to Lemma 1, there exists for  $l = 1, 2$ , some coefficients  $\omega_{ijk} \geq 0$ ,  $k \in \mathcal{V}(i)$ , such that

$$\Delta \rho_{ij_l} = \sum_{k \in \mathcal{V}(i)} \omega_{ijk} (\rho_i - \rho_k), \quad \text{with } \sum_{k \in \mathcal{V}(i)} \omega_{ijk} \leq \frac{7\tau}{12} C_{\mathcal{F}_h}.$$

Also, there exists for  $l = 1, 2$ , some coefficients  $\tilde{\omega}_{ijk} \geq 0$ ,  $k \in \mathcal{V}(i)$ , such that

$$\tilde{\Delta} \rho_{ij_l} = \sum_{k \in \mathcal{V}(i)} \tilde{\omega}_{ijk} (\rho_k - \rho_i), \quad \text{with } \sum_{k \in \mathcal{V}(i)} \tilde{\omega}_{ijk} \leq 2.$$

Next, for  $0 < \delta_{ij_l} < 1$ ,  $l = 1, 2$ , we consider the following quantities:

$$\begin{aligned} E_{ij_l} &= \frac{|\Gamma_{ij_l}^{(T)}|}{|\mathcal{C}_i|} \frac{\partial G_{ij_l}}{\partial \rho_1} (\rho_i + \delta_{ij_l} \Delta \rho_{ij_l}, \rho_i + \delta_{ij_l} \tilde{\Delta} \rho_{ij_l}), \quad l = 1, 2, \\ F_{ij_l} &= -\frac{|\Gamma_{ij_l}^{(T)}|}{|\mathcal{C}_i|} \frac{\partial G_{ij_l}}{\partial \rho_2} (\rho_i + \delta_{ij_l} \Delta \rho_{ij_l}, \rho_i + \delta_{ij_l} \tilde{\Delta} \rho_{ij_l}), \quad l = 1, 2. \end{aligned}$$

Of course, by monotonicity of the numerical flux, we have  $E_{ij_l} \geq 0$  and  $F_{ij_l} \geq 0$ . Hence, using the mean value theorem, the numerical scheme (11) is rewritten as

follows:

$$\begin{aligned} (\mathbf{A}\rho^{n+1})_i &= \frac{4}{3}\rho_i^n - \frac{4}{3}\Delta t \sum_{T, M_i \in T} \sum_{k \in \mathcal{V}(i)} \sum_{l=1}^2 \left( \omega_{ijlk} \mathbf{E}_{ijl}^n (\rho_i^n - \rho_k^n) - \tilde{\omega}_{ijlk} \mathbf{F}_{ijl}^n (\rho_k^n - \rho_i^n) \right) \\ &- \frac{1}{3}\rho_i^{n-1} + \frac{2}{3}\Delta t \sum_{T, M_i \in T} \sum_{k \in \mathcal{V}(i)} \sum_{l=1}^2 \left( \omega_{ijlk} \mathbf{E}_{ijl}^{n-1} (\rho_i^{n-1} - \rho_k^{n-1}) - \tilde{\omega}_{ijlk} \mathbf{F}_{ijl}^{n-1} (\rho_k^{n-1} - \rho_i^{n-1}) \right). \end{aligned} \quad (12)$$

Finally, we obtain the following equations for each  $i \in [1, I]$  and for all  $n \geq 1$ :

$$(\mathbf{A}\rho^{n+1})_i = a_{ii} \rho_i^n + b_{ii} \rho_i^{n-1} + \sum_{k \in \mathcal{V}(i)} (a_{ik} \rho_k^n + b_{ik} \rho_k^{n-1}), \quad (13)$$

where  $a_{ii}$ ,  $b_{ii}$ ,  $a_{ik}$  and  $b_{ik}$  are easily determined from (12). Clearly, we have

$$a_{ii} + b_{ii} + \sum_{k \in \mathcal{V}(i)} (a_{ik} + b_{ik}) = 1. \quad (14)$$

Moreover, by choosing the time step  $\Delta t$  such that for all  $i \in [1, I]$ ,

$$\Delta t \leq \left( \sum_{T, M_i \in T} \sum_{k \in \mathcal{V}(i)} \sum_{l=1}^2 \left( \frac{4}{3} (\omega_{ijlk} \mathbf{E}_{ijl}^n + \tilde{\omega}_{ijlk} \mathbf{F}_{ijl}^n) - \frac{2}{3} (\omega_{ijlk} \mathbf{E}_{ijl}^{n-1} + \tilde{\omega}_{ijlk} \mathbf{F}_{ijl}^{n-1}) \right) \right)^{-1}, \quad (15)$$

we have

$$0 \leq a_{ii} + b_{ii} \leq 1 \quad \text{and} \quad 0 \leq a_{ik} + b_{ik} \leq 1. \quad (16)$$


Hence, (13), (14) and (16) allow us to conclude that for each  $i \in [1, I]$ ,  $(\mathbf{A}\rho^{n+1})_i$  is written as convex combination of  $\rho_i^n$ ,  $\rho_i^{n-1}$ ,  $\rho_k^n$  and  $\rho_k^{n-1}$ ,  $k \in \mathcal{V}(i)$ .  $\square$

Finally, as a consequence of Proposition 1, and recalling that an M-matrix is invertible with positive inverse, we obtain:

**Theorem 1.** *Let the velocity field  $\mathbf{u}$  divergence free and the initial density  $\rho_0$  such that  $\rho_0(x) \geq 0$ . Then, under the CFL condition (10) and the hypotheses (H1) and (H2) on the mesh, the linear system (9) is invertible, and*

$$\rho^{n+1} \geq 0, \quad \forall n \geq 1. \quad (17)$$

**Numerical results.** Here we consider structured meshes on  $\Omega = ]-1, 1[^2$ , a stationary rotating velocity field  $\mathbf{u} = (x_2, -x_1)$  and a small diffusion coefficient  $\lambda = 10^{-6}$ . Setting  $r = \sqrt{(x_1 + 0.5)^2 + x_2^2}$ , the discontinuous initial condition is  $\rho_0 = 1000$  if  $r \leq 0.25$  and  $\rho_0 = 1$  if  $r > 0.25$ . The computations are performed for different values of  $h \geq 0.004$ , until  $T = 0.3$ . In Fig. 2 we show the evolution of the density contours (left) and the solution profiles for some horizontal sections (right). We can remark that the maximum principle is well verified using the IMEX-BDF2 scheme, unlike other classical order two schemes, such as Crank-Nicolson Adams-Bashforth or Crank-Nicolson Runge-Kutta. Some other numerical results can be found in [7].



**Fig. 2** The evolution of the density contours (left) and the solution profiles (right) for  $\lambda = 10^{-6}$ .

## References

1. Bresch, D., Essoufi, E.H., Sy, M.: Effect of density dependent viscosities on multiphase incompressible fluid models. *J. Math. Fluid Mech.* **9**(3), 377–397 (2007)
2. Calgato, C., Chane-Kane, E., Creusé, E., Goudon, T.:  $L^\infty$ -stability of vertex-based MUSCL finite volume schemes on unstructured grids: Simulation of incompressible flows with high density ratios. *J. Comput. Phys.* **229**(17), 6027–6046 (2010)
3. Calgato, C., Creusé, E., Goudon, T.: An hybrid finite volume-finite element method for variable density incompressible flows. *J. Comput. Phys.* **227**(9), 4671–4696 (2008)
4. Calgato, C., Ezzoug, M., Zahrouni, E.: Stability and convergence of an hybrid finite volume-finite element method for a multiphase incompressible fluid model. submitted
5. Calgato, C., Ezzoug, M., Zahrouni, E.: On the global existence of weak solution for a multiphase incompressible fluid model with Korteweg stress. *Mathematical Methods in the Applied Sciences* **40**(1), 92–105 (2017)
6. Eymard, R., Gallouët, T., Herbin, R.: Finite volume methods. In: *Handbook of numerical analysis, Vol. VII, Handb. Numer. Anal., VII*, pp. 713–1020. North-Holland, Amsterdam (2000)
7. Ezzoug, M.: Analyse mathématique et simulation numérique d’écoulements de fluides miscibles. PhD thesis, Université de Monastir, Tunisie (2016)
8. Ezzoug, M., Zahrouni, E.: Existence and asymptotic behavior of global regular solutions to a 3-D kazhikhov-smagulov model with korteweg stress. *Electronic Journal of Differential Equations* **2016**(117), 1–10 (2016)
9. Feistauer, M., Felcman, J., Lukáčová-Medvid’ová, M.: On the convergence of a combined finite volume-finite element method for nonlinear convection-diffusion problems. *Numerical Methods Partial Differential Equations* **13**, 163–190 (1997)
10. Hundsdorfer, W., Ruuth, S.: IMEX extensions of linear multistep methods with general monotonicity and boundedness properties. *J. Comput. Phys.* **225**, 2016–2042 (2007)
11. Kazhikhov, A.V., Smagulov, S.: The correctness of boundary value problems in a diffusion model in an inhomogeneous fluid. *Sov. Phys. Dokl.* **22**, 249–250 (1977)
12. Ohlberger, M.: A posteriori error estimates for vertex centered finite volume approximations of convection-diffusion-reaction equations. *M2AN Math. Model. Numer. Anal.* **35**(2), 355–387 (2001)
13. Van Leer, B.: Towards the ultimate conservative difference scheme V. A second-order sequel to Godunov’s method. *Journal of Computational Physics* **32**, 101–136 (1979)
14. Beirão da Veiga, H.: Diffusion on viscous fluids. Existence and asymptotic properties of solutions. *Ann. Scuola Norm. Sup. Pisa Cl. Sci. (4)* **10**(2), 341–355 (1983)