# Microreactors to measure solubilities in the $CO_2$ -H<sub>2</sub>O-NaCl system.

Marie-Camille CAUMON, Jean DUBESSY, Pascal ROBERT, Boubaker BENAISSA GeoRessources laboratory, Vandœuvre-lès-Nancy, France

# **OBJECTIVES & METHODS**


#### Context


Prevision of the effects of  $CO_2$  injection in saline aquifers:

- Lack of solubility data in saline media at high *PT*.
- Measurements without sampling = no perturbations.

### **Objectives**

 Acquisition of solubility data in saline media by *in situ* Raman techniques at 25-250 °C, 0-500 bar, 0-4 M NaCl.







• Raman data processing selection.

#### Methods

- A fused silica microreactor connected to a pressurization device and placed on a heating-cooling stage is filled with saline water and CO<sub>2</sub>.
- Solubility is measured by Raman spectroscopy and compared to the calculated one (EOS Duan and Sun 2003).





The HPOC setup: a pressure controlling system connected to a fused silica capillary (FSC) placed on a heating-cooling stage (CAP500, Linkam) and coupled with a Raman microspectrometer (Labram HR, Horiba Jobin Yvon).



## RESULTS man data processing Effe







H2Ok


25 °C

units)


(Arb.

100 bar

 $A_{CO2}$ 



Stretching vibration of H<sub>2</sub>O vs. [NaCl]



Different peak ratios to CO<sub>2</sub> solubility vs. salinity

#### Effect of salinity & Raman peak ratios

- Various peak area and peak intensity ratios are calculated *vs.* CO<sub>2</sub> solubility and salinity.
- All the ratios are **linearly correlated** to CO<sub>2</sub> solubility
- Sensibility to salinity varies between the different peak ratios: the less sensitive is  $A_{CO2-1380}/A_{H2Os}$ ; the most sensitive is  $A_{CO2}/A_{H2Ob}$ .

QF (=  $(I_{CO2}/I_{H2Os})/s_{CO2}$ ) as a function of temperature in pure water

## Effect of temperature

- The peak intensity ratio I<sub>CO2</sub>/I<sub>H2Os</sub> is the only ratio linearly correlated to solubility vs. temperature in pure water.
- The correlation depends on temperature.
  The present results are coherent with the previous data of Guo et al. (2014).

## CONCLUSION

The HPOC setup is used to determine CO<sub>2</sub> solubility in saline water at 25 °C in the range 0-4 M NaCl, and in pure water as a function of temperature in the range 25 °C-250 °C. It makes possible fast and reproducible measurements, in a large range of pressure, temperature and salinity. The linearity of the response as a function of salinity, whatever which ratio is calculated (intensity or area, to the bending or stretching vibration band of water), confirms the validity of the equation of state of Duan and Sun (2003) in this range of experiment (25 °C, 0-4 M NaCl).



This work was supported by the ANR grant CGSµLab ANR-12-SEED-0001.