

Use of fallout radionuclides (7Be, 210Pb) to estimate resuspension of Escherichia coli from streambed sediments during floods in a tropical montane catchment

Olivier Ribolzi, O. Evrard, Sylvain Huon, Emma Rochelle-Newall, Thierry Henri-Des-Tureaux, Norbert Silvera, Chanthamousone Thammahacksac, Oloth Sengtaheuanghoung

To cite this version:

Olivier Ribolzi, O. Evrard, Sylvain Huon, Emma Rochelle-Newall, Thierry Henri-Des-Tureaux, et al.. Use of fallout radionuclides (7Be, 210Pb) to estimate resuspension of Escherichia coli from streambed sediments during floods in a tropical montane catchment. Environmental Science and Pollution Research, 2016, 23 (4), pp.3427 - 3435. 10.1007/s11356-015-5595-z. hal-01587403

HAL Id: hal-01587403 <https://hal.science/hal-01587403>

Submitted on 14 May 2020

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

 Abstract Consumption of water polluted by faecal contaminants is responsible for 2 million deaths annually, most of which occur in developing countries without adequate sanitation. In tropical aquatic systems, streambeds can be reservoirs of persistent pathogenic bacteria and high rainfall can lead to contaminated soils entering streams and to the resuspension of sediment-bound microbes in the 5 streambed. Here we present a novel method using fallout radionuclides (${}^{7}Be$ and ${}^{210}Pb_{xx}$) to estimate the proportions of *Escherichia coli*, an indicator of faecal contamination, associated with recently eroded soil particles and with the resuspension of streambed sediments (Fig. 1). We show that using these radionuclides and hydrograph separations we are able to characterize the proportion of particles originating from highly contaminated soils and that from the resuspension of particle-attached bacteria within the streambed. We also found that although overland flow represented just over one-tenth of the total flood volume, it was responsible for more than two-thirds of the downstream transfer of *E. coli*. We propose that data obtained using this method can be used to understand the dynamics of FIB (Faecal Indicator Bacteria) in streams thereby providing information for adapted management plans 14 that reduce the health risks to local populations.

 Keywords: FIB, South East Asia, Hydrological modelling, erosion, land use, overland flow, beryllium-7, lead-210.

Introduction

 It has been estimated that almost 2 million people die annually as a consequence of waterborne diarrheal diseases caused by the use of untreated water. The majority of the victims are children between 0 to 5yr old living in developing countries (WHO 2012). The rural areas of South East Asia (SEA) are particularly affected because many of the poorest households living in the montane agro- ecosystems use contaminated river water for basic domestic needs such as washing, bathing and cooking (Ribolzi et al. 2011a, Rochelle-Newall et al. 2015, Saqalli et al. 2015). Moreover, in areas where proper sanitation infrastructures are lacking, open area human defecation and the use of shallow latrines is frequent (Guiteras et al. 2015, Sturma and Becerra 2012). Furthermore, in the absence of animal husbandry practices that protect streams through the installation of fences, the soil surface in rural areas of SEA is often contaminated with microbial faecal pollutants of human and animal origins (WorldBank 2009). Indeed, in tropical and temperate systems, land use is known to play an important

 role in determining the degree of faecal contamination in a watershed (Ekklesia et al. 2015, Goto and Yan 2011).

 The presence of faecal contamination in soil, sediment and water samples is generally determined using indicator bacteria. These faecal indicator bacteria (FIB) are used because they are much easier to culture and are considered to have a lower health risk than the pathogens for which they are an indicator (Ishii and Sadowsky 2008). Of the FIB generally used, *Escherichia coli* is often cited as being a good indicator of faecal contamination although some authors have questioned the relevance of its use in tropical systems (Byappanahalli and Fujioka 1998, Byappanahalli et al. 2012). Nevertheless, most of the methods used to determine the presence of *E. coli* are easy to employ, relatively cheap, and do not require complex analytical equipment and are therefore adapted for use in sites without access to high grade laboratory facilities.

 Bacteria in aquatic systems can be either free-living or attached to particles and the relative percentages of each fraction vary as a function of turbidity and particle quality (Lemee et al. 2002, Suter et al. 2011). Probably as a consequence of their intestinal origin where they are attached to digested food particles, FIB are mostly particle-bound although the actual percentage associated with particles does vary with TSS concentrations (Byappanahalli et al. 2012, Nguyen et al. in press, Oliver et al. 2007). During storm events characterised by high solid loads (stormflow loading), FIB numbers are often higher than during the inter-storm, low flow periods characterised by lower particle loads (Causse et al. 2015, Chan et al. 2015, Hrdinka et al. 2012, Stumpf et al. 2010). During periods of low flow, the fraction of particle-bound FIB can be deposited and stored in the river channel and stream sediments to form an in-channel reservoir of FIB that can be mobilized during floods (e.g. Pachepsky et al. 2011, Pandey et al. 2012).

 There is a paucity of knowledge on the distribution and survival of FIB in tropical freshwater environments (Rochelle-Newall et al. 2015). In these ecosystems higher and more stable temperatures, greater reserves of nutrients and organic carbon and more stable humidity conditions may lead to higher bacterial survival rates, particularly in sediments where FIB are protected from light and predators (Garzio-Hadzick et al. 2010, Pachepsky and Shelton 2011). Given the risks for human health associated with the consumption of contaminated water, quantifying the proportion of FIB resuspended with sediments during floods is crucial in tropical catchments where informal water sources often

 supply the majority of domestic requirements. Providing solid estimates of this resuspension is essential for the validation of model simulations on FIB transport and survival (Cho et al. 2012, Kim et al. 2010, Pandey et al. 2012).

 Particle-bound FIB that are transported in streams during floods come from two main sources: (1) recently eroded particles from the surface layer of soils on hillslopes and the riparian zone that are supplied to the river by overland flow and (2) resuspension of streambed sediments. However, estimating the relative proportions of these two sources to sediment transport during floods is a difficult challenge. To discriminate recently eroded particles and resuspended material, previous studies have tried to directly quantify resuspension by generating artificial floods in the stream channel during dry weather conditions (Muirhead et al. 2004, Yakirevich et al. 2013). However, these experiments are generally conducted on an isolated reach of the stream and the maximum intensity of these artificial floods remains limited. Moreover, they do not reproduce the dilution effect of pre-event groundwater, which is often a major contributor to natural streamflow (Kirchner 2003). Therefore they are unlikely to recreate the real conditions observed during a natural flood event.

 The objective of this short communication is to estimate the fraction of particle attached *E. coli* resuspended from streambed sediments during a natural flood event in a tropical montane system in SEA. An original method based on previous applications using fallout radionuclide measurements 18 (i.e. ${}^{7}Be$, ${}^{210}Pb_{xs}$) is proposed (Evrard et al. 2010, Matisoff et al. 2005). These radionuclides, characterised by different half-lives (53 days and 22 years, respectively), are supplied to the soils by rainfall. Upon soil contact they are quickly and almost irreversibly bound to fine soil particles (Taylor et al. 2013). These two radionuclides were recently used to quantify the proportions of recently eroded 22 sediment (sediment labelled by short-lived ⁷Be) and particles remobilised from the riverbed/channel 23 (depleted in 7 Be) in the study area (Gourdin et al. 2014b). In addition to the quantification of the contribution of both sources (soil erosion and sediment resuspension), this method can be used to estimate the age of resuspended sediments to which particle-bound bacteria are attached.

Material and methods

Study site

 The study site is a catchment of 60 ha located in North Lao PDR (Fig. 2). It is a sub-basin of the Houay Xon system, which is a tributary of the Mekong River. The geological substrate consists of argillites, siltstones and fine-grained sandstones from Permian to Upper Carboniferous (Department of Geology and Mines, 1990/1991). The soils developed on these bedrocks are mainly Entisol, Ultisol and Alfisol (Soil Survey Staff 1999).

 The terrain is steep with a mean slope gradient of 54%, ranging from 0% to more than 171%. The climate is a wet-dry monsoon tropical climate with an average annual rainfall of \sim 1300 mm.year⁻¹. The rainfall pattern is highly seasonal with 77% of the rainfall occurring during the rainy season from mid-May to mid-October, whereas the November to March period is cooler and mostly dry.

 The mean monthly temperature measured at the local meteorological station ranges between 12 to 35 **°**C, with the highest temperatures observed in April just before the onset of the wet season. Mean monthly relative humidity varies between 17 and 100%. The watershed is characterised by the occurrence of about 30 storms during the wet season of which around 20 generate a flood in the stream. During these storms, rainfall reaches intensities that are commonly observed in tropical systems (up to $17 \quad 100 \text{ mm}$ ¹ over a time step of 6 mins).

 Land use in the catchment is dominated by cropland (with a short fallow cycle) and teak plantations on the hillslopes (Huon et al. 2013). In the stream zone, small domestic gardens and fish ponds are found. These areas are generally uninhabited during the dry season. However, during the wet season, these zones are more frequently used by farmers and their livestock. During this time the inhabitants construct small semi-permanent camps where open air defecation is practiced. Livestock is of relatively low density and includes pigs, chickens, goats and dogs. Wild animals also live in the fallow areas and can contribute to faecal contamination. There are three swamp zones along the stream length.

 This catchment can be considered as representative of the montane agro-ecosystems of SEA. Monitored since 1998, this site is part of MSEC (Multi-scale Environmental Changes, [http://msec.obs-](http://msec.obs-mip.fr/) [mip.fr/\)](http://msec.obs-mip.fr/) South East Asian agro-hydrological observatory. It belongs to the French network of critical

Hydrological measurements and water sampling

zone observatories (RBV, Réseau de Bassins Versants, [http://rnbv.ipgp.fr/\)](http://rnbv.ipgp.fr/).

 Rainwater depth and intensity was measured (with a 6 minute time step) using an automatic rain gauge (Cimel). Steam discharge was measured at the catchment outlet using an automated recording station that consisted of a water level recorder (OTT, Thalimedes/SE200) and a V-notch weir. The control- rating curve was previously determined using cross-sectional metering and slug tests. Stream water was collected in plastic bottles by an automatic sampler (Automatic Pumping Type Sediment Sampler, ICRISAT) installed at the catchment outlet (Fig. 2). During this study, 12 1-liter samples were collected over the flood. Electrical conductivity normalized to 25°C (EC) of each sample was determined with an YSI® 556 probe. The concentration of total suspended solid (TSS) was determined 12 for each sample after evaporation in an oven at 105°C for 48 h. Cumulated TSS exports were calculated by integrating the flux of TSS over the flood.

Escherichia coli **determinations**

 The standardized microplate method (ISO 9308-3) was used for *E. coli* load determinations. This method is based on serial dilutions and an evaluation of the most probable number (MPN) using a culture medium specific for *E. coli*. Each sample was incubated at four dilution rates (i.e. 1:2, 1:20, 1:200 and 1:2000) in a 96-well microplate (MUG/EC, BIOKAR DIAGNOSTICS) and incubated for 36 to 48h at 44°C. Ringers' Lactate solution was used for the dilutions and one plate was used per sample. The number of positive wells for each microplate was noted and the MPN was determined using the Poisson distribution. Each sample was incubated within a few hours after the flood. The *E. coli* load at the sediment surface was also determined at four sites along the stream (Fig. 2). At each site, 10 g of sediment were collected from the upper 2 cm of the sediment surface and were resuspended in 1l of Ringers' Lactate solution. The resulting solution was agitated and the *E. coli* load was determined using the microplate method. This microplate method has previously been used with success in the studied ecosystem (Causse et al. 2015).

Radionuclide analyses

 Radionuclide activities were measured in a total of five suspended sediment samples. Samples were packed into 15–60-ml (depending on the quantity available) polyethylene containers and sealed 4 airtight. The ${}^{7}Be$ and ${}^{210}Pb$ activities were determined by gamma spectrometry using the very low- background coaxial N- and P-type GeHP detectors at the Laboratoire des Sciences du Climat et de l'Environnement (LSCE; Gif-sur-Yvette, France; (Gourdin et al. 2014b). All results were expressed in 7 Bq kg⁻¹. Activities were also decay-corrected for the sampling date. Uncertainties on radionuclide 8 activities were ca. 10% for $^{210}Pb_{xs}$ and 20% for ⁷Be. All samples were analysed within less than 53 days (⁷Be half-life) following the rainfall event.

EC-based hydrograph separation

 A tracer-based approach similar to the one described by Ribolzi et al. (1997) and Collins and Neal (1998) was used to separate storm hydrographs into event water, which mainly includes infiltration excess overland flow (Patin et al. 2012, Ribolzi et al. 2011b), and pre-event water, i.e. ground water pre-stored in the catchment (Vigiak et al. 2008). This approach uses a simple mixing model with two reservoirs and the electrical conductivity (EC) of water as a tracer. It is described by the following equations:

$$
17 \qquad Q_{sw} = Q_{of} + Q_{gw} \tag{1}
$$

$$
18 \qquad Q_{sw} \text{ EC}_{sw} = Q_{of} \text{ EC}_{of} + Q_{gw} \text{ EC}_{gw} \tag{2}
$$

19 Where Q_{sw} represents the instantaneous stream water discharge at the catchment outlet, Q_{of} , 20 the instantaneous discharge of overland flow and Q_{gw} , the instantaneous discharge of groundwater 21 (expressed in 1 s⁻¹). EC_{sw} is the instantaneous EC measured in the stream. EC_{of} and EC_{gw} are the 22 average values respectively for overland flow and groundwater during the storm event. EC_{of} was measured on samples of overland flow that were collected from the soil surface on hillslopes draining to the stream during the rainfall event (Patin et al. 2012). Since groundwater feeds the stream during 25 inter-stormflow periods (Ribolzi et al. 1997), EC_{gw} was approximated from stream measurements carried out prior to storm event.

Solidograph separation and estimate of *E. coli* **resuspension**

2 Due to their different half-lives (53 days and 22 years respectively), ⁷Be and ²¹⁰Pb_{xs} are particularly relevant for quantifying the respective contributions of (1) particles detached from the soil surface 4 along hillslopes and the riparian zone (i.e. recently tagged with 7 Be) and (2) resuspension of stream bed 5 sediments (i.e. isolated from recent fallout and depleted in ⁷Be). The percentage of "new" suspended 6 particles (P_{new} , recently labelled particles detached from the soil surface) in the total stream load at a given sampling time was estimated following the method of Matisoff et al. (2005):

$$
R_{\text{new}} = 100 \left[(A/B) / (A_0/B_0) \right] \tag{3}
$$

9 where A and B are the ⁷Be and ²¹⁰Pb_{xs} activities (Bq kg⁻¹) of the suspended particles collected from the 10 stream and A_0 and B_0 are the ⁷Be and ²¹⁰Pb_{xs} activities in rainfall (Bq l⁻¹). The value 5.4 was used to 11 estimate the ratio A_0/B_0 . It was obtained by averaging signature of 4 rain showers that occurred immediately prior to the flood (i.e. 6-April, 23-May, 31-May and 1-Jun 2012). This value is consistent with other work from the same study area (Gourdin et al. 2014a, Gourdin et al. 2014b).

14 The proportion of "old" suspended particles $(P_{old}$, resuspended streambed sediments isolated from recent fallout) was estimated by the following equations:

$$
16 \t P_{\text{old}} = 100 - P_{\text{new}} \t (4)
$$

$$
17 \t Fold = Fsw Pold / 100
$$
 (5)

Where F_{sw} and F_{old} are, respectively, the total and old suspended solid particle flows (kg s⁻¹) at time t. The flow of *E. coli* from streambed sediment resuspension ($F_{E, coil}$ old; expressed in MPN s⁻¹), mainly composed of old sediment, was then estimated from:

$$
P_{\text{E},\text{coli_old}} = F_{\text{old}} S B_{\text{E},\text{coli}} \tag{6}
$$

Where SB_{Ecoli} is the total load of *E. coli* in streambed sediment (MPN kg⁻¹). The flow of *E.* 23 *coli* due to recently labelled particles detached from the soil surface ($F_{E, coil}$ _{new}; expressed in MPN s⁻¹) was then estimated from:

 $F_{\text{E,coli sw}}$ is the flow of *E. coli* in the stream at time t (MPN s⁻¹) and SW_{E.coli} is the concentration of *E. coli* in the stream water sample $(MPN 1⁻¹)$ at time t.

Results

Description of the rainfall-runoff event

6 The studied flood was triggered by a storm that occurred on May $15th$, 2012. It was the first significant erosive event of the rainy season. During the storm, maximum rainfall intensity occurred between 8 10:30 am and 10:36 am and reached 75 mm h^{-1} (Fig. 3). The cumulated rainfall over the 48 min rain event was 33.5 mm. This corresponds to approximately a one-year return period (34.7 mm daily rainfall) according to Bricquet et al. (2003) for the 1950-2000 period. The lag time between the peak of rainfall and peak discharge was 12 minutes. This storm generated a stormflow of approximately 273 12 min during which discharge peaked at 90 L $s⁻¹$ at 10:48. This corresponds to a maximum specific 13 discharge of 1.5 L s⁻¹ ha⁻¹. The runoff coefficient for this event (depth of streamflow/depth of rain) was 3%.

Variations in the stream flow composition

16 The initial EC was 533 μ S cm⁻¹, characteristic of groundwater (Fig. 3). This then rapidly decreased to 358 μ S cm⁻¹ during the peak of storm flow, indicating the increasing contribution of overland flow that has a lower EC (40 μ S cm⁻¹). EC then progressively increased as the flood receded. TSS concentration 19 reached a peak of $24g L^{-1}$ and TSS loss during the 425min event was 4.3 Mg.

20 The activity of ²¹⁰Pb_{xs} remained relatively stable throughout the flood event at 80 Bq kg⁻¹). In 21 contrast, ⁷Be activity was high at the start of the rain event (398 Bq kg⁻¹) it then further increased 22 slightly to 438 Bq kg⁻¹ at beginning of the flood recession. Activity then dropped drastically to 62 Bq kg^{-1} during the flood recession to thereafter increase to more enriched values towards the end of the 24 flood event. *E. coli* concentrations in the floodwaters were 2100 MPN 100 ml⁻¹ during the early stage 25 of the rising flood. This then increased a maximum value of 49000 MPN 100 ml⁻¹ at the start of the

Separation of suspended particles and *E. coli* **fluxes**

 The separation of TSS flux into recently eroded particles ("new") and resuspended sediments flux ("old") from the streambed is shown in Fig. 4. At the beginning of the flood the major proportion of 2 particles are "new" with an apparent age of 8 days indicating that they were recently marked by 7 Be at the bare soil surface. This peak corresponds to the peak in overland flow. As the flood progressed, the proportion of "old" particles reached a maximum apparent age of 158 days at 140 minutes after the start of the flood and then declined.

The flux of *E. coli* associated with particles recently labelled with ⁷Be was always higher than that associated with the older particles and this during the entire flood. The maximum flux of *E. coli* 13 associated with recently labelled particles $(17.9 \times 10^6 \text{ MPN} \times \text{s}^{-1})$ occurred at peak solid flux (77 mins after the flood peak). Flux then declined steadily until the end of the flood. In contrast to the peak flux of recent particles, the peak in *E. coli* associated with older particles occurred after a lag of approximately 1 hour. We conducted an uncertainty analysis (Monte Carlo type) following the method of Ribolzi et al (2000) to estimate the confidence levels on the proportions of *E. coli* attached to "old" particles at the point of maximum contribution in the hydrograph. We found that the associated errors lead to a coefficient of variation of 12% and 14% of the total fluxes of *E. coli* attached to "old" and "new" particles, respectively. Over the course of the flood a total of 125×10^9 MPN *E. coli* were exported, of which about 89 % were associated with recently eroded particles and 11 % with particles resuspended from the riverbed.

Discussion

Here, we present a novel method using fallout radionuclides (7 Be and $^{210}Pb_{xs}$) to estimate the

proportions of *E. coli* associated with recently eroded soil particles and with the resuspension of

streambed sediments. This method allows the separation of the total flux of particles into two

components: "new "and "old" following the model of Matisoff et al. (2005). A key assumption for the

 use of 7 Be as a tracer is that radionuclides sorption to particles is rapid and irreversible over the timescales of interest (Taylor et al. 2012). Gourdin et al. (2014a) recently validated this assumption by implementing laboratory experiments and field observations during a storm event in the Houay Pano catchment. These authors also used this method to quantify the sources and dynamics of suspended sediment and particulate organic matter (Gourdin et al. 2014b, 2015). Here, we use an extension of this work to estimate the transfer times and sources of *E. coli* in an upland stream (Fig. 4).

Overland flow and groundwater

 As observed by Gourdin et al (2014a) we found higher contributions of recently eroded sediment at the beginning of the rising flood stage and then a progressive dilution of recently eroded sediment by particles remobilised from the riverbed (Fig. 4). Overland flow represented just over one- tenth of the total flood volume but was responsible for more than two-thirds of the downstream transfer of *E. coli* (i.e. fraction attached to recently labeled particles). This result confirms the observations of Causse et al. (2015) in the same study area who concluded that the proportion of soil surface washoff was critical in determining the numbers of *E. coli* in the stream during storms. It is also in agreement with Kim et al. (2010) who simulated *E. coli* loads in the Little Cove Creek watershed (Pennsylvania) with a version of SWAT (Soil and Water Assessment Tool) that took into account streambed bacteria release. They found that surface runoff carried large numbers of *E. coli* to the stream and that sediment resuspension contributed to the baseline concentration of *E. coli* in stream water.

 Another point that should also be emphasized is the importance of the groundwater contribution to flood runoff. During the studied flood event, groundwater largely dominated streamflow with an estimated contribution of up to 89%. This hydrological behavior is often observed 22 in rural catchments with dense vegetation cover (e.g. Kirchner 2003). Genereux and Hooper (1998) estimated in a review paper on tracer-based hydrograph separations that the pre-event groundwater 24 contribution to storms is on average $80 \pm 20\%$. Although this is well known to hydrologists and is often quantified using geochemical and isotopic tracer techniques, this phenomenon is rarely discussed in the literature with a view to better understanding the dynamics of FIB and environmental bacteria. In this context, groundwater that is little contaminated as compared to overland flow will tend to dilute streamwater during stormflow. At the same time, the contribution of groundwater adds to that of overland flow to increase discharge and the resuspension of sediments in the streambed.

Methodological considerations

 The method presented here is adapted for tropical systems with contrasted dry and wet seasons. Moreover, it is particularly appropriate for events occurring at the start of the rainy season 4 when the stock of $7Be$ supplied by rainfall to soils during the previous wet season has completely decayed. It is also important to note that the first floods are generally the most contaminated as the soils have accumulated contaminants throughout the dry season (Causse et al. 2015).

 One of the central assumptions of this work is that *E. coli* are attached to soil particles and that this does not change during the erosion, resuspension and transport processes along hillslopes and downstream toward the creek. We hypothesized that enteric bacteria are more frequently associated with particles both within the host and in the external environment (soils and water) and that this remains relatively constant over short timescales. High proportions of environmental bacteria and enteric bacteria such as *E.coli* are associated with particles in soils (Oliver et al. 2007) and in aquatic systems (Lemee et al. 2002, Unanue et al. 1992). Our results, obtained during a flash flood with low *E. coli* numbers (1 – 230 MPN 100 ml⁻¹ *E. coli*; Causse et al. 2015) and low TSS (< 20 mg L⁻¹) in the stream prior to the storm support this assumption. Although it is likely valid in this case study, this hypothesis should nevertheless be verified when applying this method to other study sites. Our method allows the determination of the age of different particles to which *E. coli* are bound. Therefore, although it does not provide an exact age for *E. coli* or of the particle, one can postulate that

the bacteria associated with the particles in the stream are older than those associated with the particles

20 recently marked with ${}^{7}Be$ (i.e. those at the soil surface on the slopes). We conducted an analysis of

error propagation and by far the largest proportion of the total error is by far associated with the

calculation of the "old" *E. coli* fraction (up to 75%). Most of this error probably arises from the

uncertainty associated with the SB*E.coli* determination. Therefore, given the importance of the values of

 streambed *E. coli* in the calculation, it is critical to obtain a robust estimate of this concentration as the calculations of "old" and "new" *E. coli* fractions are strongly dependent on this value.

Land use

 In these tropical agro-ecosystems there is an intensification of activities linked to the preparation of the land for annual crops at the start of the rainy season. This intensification also brings with it a sharp increase in the potential for soil surface contamination due to the use of informal latrines and open-air defecation by humans and livestock. This contamination is then mobilized by the erosive nature of rain drop impacts (Ribolzi et al. 2011b) and is transported to the stream by overland flow (Patin et al. 2012). Bare soils in teak plantations that lack an understory and in young fallow zones where soils have low infiltration rates (Patin et al. 2012) have particularly high overland flows. Moreover teak plantations often encroach on the riparian zones. Therefore any overland flow from the upslope teak plantation may also wash off any FIB available downslope in the riparian zone located between the plantation and stream proper. In the riparian zone, contaminated particles available at the soil surface can also be detached and disseminated downstream within local seepage zones by groundwater exfiltration in association with overland flow (Vigiak et al. 2008). Domestic gardens, temporary housing and fishponds where contamination levels can be high are often located in the riparian zones and the small paths that interconnect these areas can increase runoff (Ziegler et al. 2000) and enhance *E. coli* transport to the stream. Moreover, riparian zones in tropical systems are often characterised by swamp areas that are both a source and a trap of solid particles and FIB. They therefore play an important role in controlling the dynamic of "old" and "new" *E. coli* in these systems. Quantifying the contribution of these reservoirs to the total flux of *E. coli* during flood events allows a better understanding of the redistribution processes and of the dynamic of particle- bound FIB within catchments. This is critical if we wish to fully understand the dynamic of *E. coli* in watersheds. **Conclusion and perspectives**

 Here we present a way of estimating both the relative proportion of *E. coli* resuspended from streambed sediments and those transferred from the soil surface to the stream by overland flow during a flood event (Fig. 1). At present, because of its analytical cost and level of expertise required for its 26 implementation, the ${}^{7}Be/{}^{210}Pb_{xs}$ method is still limited to a small number of laboratories worldwide. Even though the systematic use of this method in a wide range of watersheds is limited, this method remains useful for distinguishing the source of *E. coli* (resuspension of streambed sediments *vs* soil

 surface washoff). Furthermore, values obtained from this method can then be applied in appropriate models to understand the dynamics of FIB in streams, and then provide information for adapted

management plans that aim to reduce the health risks to the local populations.

Acknowledgements

 The authors would like to thank the Lao Department of Agriculture Land Management (DALAM) and the MSEC project (Multi-Scale Environment Changes) for their support. They are also grateful to Keo Oudone Latsachack, Bounsamai Soulileuth, Marie Arnoux and Elian Gourdin for their help during field and laboratory work. This work was financed by the French Centre National de la Recherche Scientifique EC2CO/BIOHEFECT program (Belcrue and Belkong projects) as well as by the French National Research Agency (TecItEasy project; ANR-13-AGRO-0007).

 Figure 1 - Graphical abstract showing: **(1)** the main water flow processes (i.e. overland flow, groundwater return flow, blue arrows) and sediment flow components (i.e. resuspension and soil erosion, black arrows) during floods in the Houay Pano catchment; **(2)** the general principle of the 5 method using fallout radionuclide markers (i.e. ⁷Be and ²¹⁰Pb_{xs}) to estimate *Escherichia coli* load from the two main sources (i.e. streambed resuspension *vs* soil surface washoff); and 3) the main results obtained during the 15 May 2012 storm event (i.e. relative percentage contribution of each process to the total streamflow, values in parentheses).

 Figure 2 - Geographical location of the Houay Pano catchment, hydro-meteorological equipment, water and streamed sediment sampling points, and land use in 2012.

 Figure 3 – Measurements during the 15 may 2012 stormflow event: rainfall intensity (6-mins time step); stream discharge; electrical conductivity (EC) of the stream water; total suspended solids (TSS) 13 concentration; fallout radionuclides (7 Be and $^{210}Pb_{xs}$) activity; and *Escherichia coli* (*E. coli*) load of the stream.

Figure 4 – Total suspended solid (TSS) flow of "new" (i.e. recently eroded soil surface aggregates)

and "old" (i.e. resuspended sediment) particles estimated using the Matisoff et al. (2005) model;

overland flow (OLF) and groundwater (GW) discharge estimated using a tracer-based model (e.g.

Ribolzi et al., 1997) estimate of *Escherichia coli* (*E. coli*) flow attached to recently labelled and eroded

soil surface particles (new) and to resuspended particles from the streambed (old).

 Bricquet J-P, Boonsaner A, Phommassack T, Toan TD (2003): Statistical analysis of long series rainfall data: A regional study in Southeast Asia. In: IWMI (Hrsg.), IWMI Seminar on Scientific Cooperation. IWMI South East Asia, Kasetsart University, Bangkok, Thailand, pp. 83-89 Byappanahalli MN, Fujioka RS (1998) Evidence that tropical soil environment can support the growth of *Escherichia coli*. Water Sci Technol 38: 171-174 Byappanahalli MN, Nevers MB, Korajkic A, Staley ZR, Harwood VJ (2012) Enterococci in the environment. Microbiol Mol Biol Rev 76: 685-706 Causse J, Billen G, Garnier J, Henri-des-Tureaux T, Olasa X, Thammahacksa C, Latsachak KO, Soulileuth B, Sengtaheuanghoung O, Rochelle-Newall E, Ribolzi O (2015) Field and modelling studies of *Escherichia coli* loads in tropical streams of montane agro-ecosystems Journal of Hydro-environment Research 10.1016/j.jher.2015.03.003 Chan YM, Thoe W, Lee JHW (2015) Field and laboratory studies of *Escherichia coli* decay rate in subtropical coastal water. Journal of Hydro-environment Research 9: 1-14 Cho KH, Pachepsky YA, Kim JH, Kim JW, Park MH (2012) The modified SWAT model for predicting fecal coliforms in the Wachusett Reservoir Watershed, USA. Water Res 46: 4750-4760 Collins RU, Neal C (1998) The hydrochemical impacts of terraced agriculture, Nepal. Sci Total Environ 212: 233-243 Ekklesia E, Shanahan P, Chua LHC, Eikaas HS (2015) Temporal variation of faecal indicator bacteria in tropical urban storm drains. Water Res 68: 171-181

References

