



The MFD trip-based approach applied to multi-reservoir systems.

Guilhem Mariotte, Ludovic Leclercq

► To cite this version:

Guilhem Mariotte, Ludovic Leclercq. The MFD trip-based approach applied to multi-reservoir systems.. hEART2017 - 6th symposium of the European Association for Research in Transportation, Sep 2017, HAIFA, France. 3 p. hal-01589590

HAL Id: hal-01589590

<https://hal.science/hal-01589590>

Submitted on 18 Sep 2017

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

The MFD trip-based approach applied to multi-reservoir systems

Guilhem Mariotte & Ludovic Leclercq

Univ. Lyon, IFSTTAR, ENTPE, LICIT, F-69518, Lyon, France

guilhem.mariotte@ifsttar.fr, ludovic.leclercq@ifsttar.fr

*Extended abstract submitted for presentation at the hEART 2017 6th Symposium
Sept. 12–14, 2017, Haifa, Israel*

Word count: 869 words (excluding the references)

March 30, 2017

Extended abstract

Over the past decade, the Macroscopic Fundamental Diagram (MFD) has appeared to be a powerful tool to describe traffic states at the network level with few implementation and computational efforts. Many studies (e.g. [Knoop & Hoogendoorn, 2014](#), [Yildirimoglu & Geroliminis, 2014](#), [Yildirimoglu et al., 2015](#), [Haddad, 2015](#)) have notably used MFD-based traffic simulators for several applications, like traffic state estimation, perimeter control or assessing routing strategies at a large scale. Their modeling approaches take advantage of the multi-reservoir representation of a city, where the dynamics of each urban subregion is described by the single reservoir model of [Daganzo \(2007\)](#). This framework, also referred as the accumulation-based model, assumes that the reservoir outflow is for the simplest model proportional to the total circulating flow inside the zone or that partial outflows are proportional to fractions of the circulating flow for more advanced models. However, while being acceptable in slow-varying conditions, this hypothesis may be too restrictive when the demand evolves too fast as shown by [Mariotte et al. \(2017\)](#). An idea, initially proposed in [Arnott \(2013\)](#), has been exploited in [Daganzo & Lehe \(2015\)](#) and then [Lamotte & Geroliminis \(2016\)](#) to design a “trip-based” formulation of the MFD model. This approach considers that all users travel at the same speed at a given time, and exit the zone once they have completed their individually assigned trip length. As shown in a thorough comparison with the accumulation-based model by [Mariotte et al. \(2017\)](#), the trip-based approach gives more accurate results during transient phases, and proves to be more flexible to integrate various trip lengths inside the same reservoir. However, despite an attempt provided by these authors, using this framework to model congestion propagation inside the reservoir is still a challenge.

In this study, we propose to extend the trip-based formulation to multi-reservoir systems. Our resolution scheme uses the event-based method proposed in [Mariotte et al. \(2017\)](#). The main challenge is to properly account for congestion spillbacks in upstream reservoirs when trip lengths are different. Simulation results are investigated for two different multi-reservoir systems. The first one has four reservoirs with one regional Origin-Destination (OD) pair and three routes. Its configuration is inspired by the Braess network in choice modeling studies, see figure 1(a). The second one has more than ten reservoirs and is based on a real network: an artificial partitioning of the 6th district in Lyon (France), see figures 1(b) and 1(c). This second case aims to study a more realistic and complex multi-reservoir system with different OD pairs. In that case, network partitioning is made depending on the demand description, and not based on homogeneity constraint like in [Saeedmanesh & Geroliminis \(2016\)](#). The results are then compared with the accumulation-based modeling of these multi-reservoir systems. The corresponding simulator we use is adapted from the study of [Yildiri-](#)

[moglu & Geroliminis \(2014\)](#). In both accumulation- and trip-based approaches, particular attention is paid on how to model congestion propagation inside and between reservoirs. The influence of internal inflow generation within the reservoirs is also explored. The congestion inside a zone is usually modeled with a restriction on the global entrance flow from outside the zone. As there may have a lot of interactions between the reservoirs, this inflow reduction must be performed during the simulation in case of congestion, which is not necessarily trivial due to the event-based structure of the numerical scheme. While this is already well integrated in the accumulation-based framework with fix time step, to our best knowledge, inflow regulation at reservoir perimeter has never been implemented in the trip-based model. In this study, several ways to simulate congestion propagation within this framework are explored: the method of [Newell \(2002\)](#), the upstream inflow restriction function used in the Cell Transmission Model (CTM), and the relationship between inflow and outflow exhibited in the numerical approximation proposed by [Mariotte *et al.* \(2017\)](#). Moreover, when congestion propagates through adjacent regions, different flow merging functions can be used to determine the inflow allocation between all upstream reservoirs. The influence of such merging functions is investigated in both the accumulation- and the trip-based models.

Our first results show a good concordance between the two modeling approaches in steady state for simple network loading cases with the same travel distance for all users. In case of different trip lengths however, the accumulation-based model fails to reproduce reliable evolution of congestion in the reservoirs, the whole system being sometimes very unstable. On the other hand, because the trip-based model keeps the variety of user trip lengths, corrections methods can be implemented to better represent congestion propagation and ensure the system stability. Moreover, for more complicated loading tests involving several OD pairs (especially in the network of Lyon 6), very different steady states may be reached depending on the merge function used in both simulators. As for transient phases, important discrepancies are noticed between the accumulation-based and the trip-based models. This corroborates the observations in [Mariotte *et al.* \(2017\)](#) about the difference in travel time evolution between the two approaches. All these concerns are of great importance for further studies which would include traffic assignment in multi-reservoir systems. All results are not presented here as this study is still an ongoing work.

Keywords: Large network modeling, Macroscopic Fundamental Diagram, multi-reservoir systems




FIG. 1 – Two multi-reservoir systems. (a) Braess network. Lyon 6 network, (b) schematic and (c) link-level representation

Acknowledgement

This project has received funding from the European Research Council (ERC) under the European Union's Horizon 2020 research and innovation programme (grant agreement No 646592 – MAGnUM project).

References

- Arnott, R.** (2013). A bathtub model of downtown traffic congestion. *Journal of Urban Economics*, 76:110–121.
- Daganzo, C. F.** (2007). Urban gridlock: Macroscopic modeling and mitigation approaches. *Transportation Research Part B: Methodological*, 41(1):49–62.
- Daganzo, C. F. & Lehe, L. J.** (2015). Distance-dependent congestion pricing for downtown zones. *Transportation Research Part B: Methodological*, 75:89–99.
- Haddad, J.** (2015). Robust constrained control of uncertain macroscopic fundamental diagram networks. *Transportation Research Part C: Emerging Technologies*, 59:323–339.
- Knoop, V. L. & Hoogendoorn, S. P.** (2014). Network transmission model: a dynamic traffic model at network level. In *Transportation Research Board 93rd Annual Meeting*, 14-1104. Washington DC.
- Lamotte, R. & Geroliminis, N.** (2016). The morning commute in urban areas: Insights from theory and simulation. In *Transportation Research Board 95th Annual Meeting*, 16-2003. Washington DC.
- Mariotte, G., Leclercq, L. & Laval, J. A.** (2017). Dual expression of macroscopic urban models: Analytical and numerical investigations with piecewise linear functions. In *Transportation Research Board 96th Annual Meeting*, 17-04928. Washington DC.
- Newell, G. F.** (2002). A simplified car-following theory: a lower order model. *Transportation Research Part B: Methodological*, 36(3):195–205.
- Saeedmanesh, M. & Geroliminis, N.** (2016). Clustering of heterogeneous networks with directional flows based on snake similarities. *Transportation Research Part B: Methodological*, 91:250–269.
- Yildirimoglu, M. & Geroliminis, N.** (2014). Approximating dynamic equilibrium conditions with macroscopic fundamental diagrams. *Transportation Research Part B: Methodological*, 70:186–200.
- Yildirimoglu, M., Ramezani, M. & Geroliminis, N.** (2015). Equilibrium analysis and route guidance in large-scale networks with {MFD} dynamics. *Transportation Research Part C: Emerging Technologies*, 59:404–420.