

Parameters Identification for Thermal Building Models by a Goal-oriented Inverse Method

Zohra Djatouti, Julien Waeytens, Patrice Chatellier, Ludovic Chamoin

▶ To cite this version:

Zohra Djatouti, Julien Waeytens, Patrice Chatellier, Ludovic Chamoin. Parameters Identification for Thermal Building Models by a Goal-oriented Inverse Method. ADMOS 2017, Jun 2017, Verbania, Italy. 1p. hal-01592738

HAL Id: hal-01592738

https://hal.science/hal-01592738

Submitted on 25 Sep 2017

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Parameters Identification for Thermal Building Models by a Goal-oriented Inverse Method

Djatouti Z.^{†*}, Waeytens J.[†], Chatellier P.[†] and Chamoin L.[‡]

 † Université Paris-Est, COSYS, LISIS, IFSTTAR, F-77447 Marne-la-Vallée, France

[‡] ENS Paris-Saclay, 61 avenue du président Wilson 94230 Cachan, France

ABSTRACT

To carry out a representative energy performance diagnosis of an existing building, one must have a good knowledge of the thermal properties of its systems and envelope. Unfortunately, these pieces of information are generally not available. The present paper introduces an inverse strategy for thermal models parameters identification, namely the goal-oriented inverse method [1]. This original technique aims at identifying only the set of parameters that affects the prediction of a quantity of interest.

To asses the performance of the goal-oriented method in thermal model parameters identification, the technique has been implemented on a simplified mono-zone building thermal model. As a first step, the steady state problem was treated and the parameters to be identified were the global thermal conductivity of the envelope and its outside convective heat exchange coefficient. Then, the dynamic state was considered and the global heat capacity of the envelope was sought in addition to the previous parameters.

In both states, the robustness of the inverse method has been tested on different levels of instrumentation noise and on different configurations of available sensors data. The parameters identification results were compared to those obtained with more common inverse methods, i.e Tikhonov regularization technique [3] and the constitutive relation error approach [2].

The first results show a higher accuracy of the goal-oriented inverse method in the prediction of the quantity of interest and in the identification of the model parameters involved in its computation. This performance is achieved with a reduced amount of instrumentation data and in a reduced computation time. We also observe that the goal-oriented strategy is less sensitive to the instrumentation noise than the classical inverse methods.

REFERENCES

- [1] CHAMOIN, L., LADEVEZE, P., AND WAEYTENS, J. Goal-oriented updating of mechanical models using the adjoint framework. *Computational Mechanics*, 54,1415-1430 54 (2014), 1415–1430.
- [2] LADEVEZE, P., AND CHOUAKI, A. Application of a posteriori error estimation for structural model updating. *Inverse problems* 15 (1999), 49–58.
- [3] TIKHONOV, A., AND ARSENIN, Y. Solutions to ill-posed problems. Wintson-Widley, New York, 1977.