

# The impact of palm oil feedstock within the LCA of a bio-sourced cosmetic cream

Sylvain Martinez, C. Bessou, Léa Hure, J. Guilbot, Arnaud Helias

### ▶ To cite this version:

Sylvain Martinez, C. Bessou, Léa Hure, J. Guilbot, Arnaud Helias. The impact of palm oil feedstock within the LCA of a bio-sourced cosmetic cream. Journal of Cleaner Production, 2017, 145, pp.348-360. 10.1016/j.jclepro.2017.01.042. hal-01605842

## HAL Id: hal-01605842 https://hal.science/hal-01605842v1

Submitted on 26 May 2020

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

## **Accepted Manuscript**

The impact of palm oil feedstock within the LCA of a bio-sourced cosmetic cream

S. Martinez, C. Bessou, L. Hure, J. Guilbot, A. Hélias

PII: S0959-6526(17)30049-5

DOI: 10.1016/j.jclepro.2017.01.042

Reference: JCLP 8789

To appear in: Journal of Cleaner Production


Received Date: 1 June 2016

Revised Date: 23 December 2016

Accepted Date: 9 January 2017

Please cite this article as: Martinez S, Bessou C, Hure L, Guilbot J, Hélias A, The impact of palm oil feedstock within the LCA of a bio-sourced cosmetic cream, *Journal of Cleaner Production* (2017), doi: 10.1016/j.jclepro.2017.01.042.

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.



- 1 7254 words for full text + figures and tables, 336 words for title + authors and affiliations + abstract,
- 2 1662 words for references
- 3 The impact of palm oil feedstock within the LCA of a bio-sourced cosmetic
- 4 cream

5

6 S. Martinez<sup>a,b</sup> C. Bessou<sup>c,b</sup>, L. Hure<sup>a,b</sup> J. Guilbot<sup>d</sup>, A. Hélias<sup>a,b</sup>

7

- 8 aLBE, Montpellier SupAgro, INRA, 102 avenue des Etangs, 11100, Narbonne, France
- 9 <sup>b</sup>Elsa, Research group for Environmental Lifecycle Sustainability Assessment, Montpellier SupAgro, 2
- 10 place Pierre Viala, 34060, Montpellier, France
- 11 <sup>c</sup>CIRAD, UPR Systèmes de pérennes, 34398 Montpellier, France
- 12 dSEPPIC, 81100, Castres, France
- 13 Keywords: Life cycle assessment, Cosmetic, Palm oil, Peat soil, Deforestation, Land Use
- 14 Abstract
- 15 We performed a cradle-to-grave life cycle assessment (LCA) of a bio-based cosmetic cream
- 16 containing Refined Palm Kernel Oil (RPKO). The objective was to investigate the importance of the
- 17 RPKO production within the environmental impact of the cosmetic cream. We assumed a baseline
- scenario with best oil palm agricultural practices in Malaysia, and then tested different parameters,
- i.e. deforestation, peat soil drainage and improved effluent treatment, in order to check their
- 20 influences.
- 21 In the baseline scenario, transport of the cosmetic cream was the main contributing process (largest
- 22 contribution for 11 out of 15 impact indicators). Contribution of the packaging of the cosmetic cream
- 23 was also significant (largest for 2 out of 15). RPKO had a low impact contribution in the baseline
- 24 scenario, albeit a much more critical one in the alternative scenarios. Deforestation and peat soil
- 25 drainage (i.e. transformation and occupation) influenced two environmental indicators: Climate
- 26 Change and Land Use. On Climate change indicator, deforestation caused an increase of about 9% of

27 the cosmetic cream impacts and peat soil occupation an increase of 16%. On Land Use indicator, deforestation caused an increase of 3%, peat soil transformation and occupation caused increases of 28 29 938% and 41%, respectively. Methane capture from palm oil mill effluent treatment and conversion to electricity represented a low decrease of environmental impact of cosmetic cream (from - 0.1% to 30 31 - 2.8%). This paper showed that the palm oil agricultural phase could have a non-negligible impact over the life-cycle of a cosmetic cream in case of deforestation and peat cultivation, despite its small 32 contribution in both mass and economic terms. 33 34 Introduction 1 Assessing environmental impacts has become mainstream when designing new or improved 35 36 production systems. It is particularly crucial when promoting new bio-based products that are meant 37 to displace their fossil equivalents in order to reduce the overall environmental impact. Arguments put forward are the renewable aspect and the independence from oil or mineral, implicitly promising 38 39 low environmental impacts. However, several studies have shown that net environmental benefits from bio-sourced products are not automatic and depend on the studied commodity chain and the 40 way it is assessed (Fargione et al., 2008; Farrel et al., 2006; Gibbs et al., 2008; Gnansounou et al., 41 42 2009). Life Cycle Assessment (LCA) has been widely applied to assess the impact of bio-sourced product 43 (ADEME and BIO Intelligence Service, 2010; JRC et al., 2008; Secchi et al., 2016). LCA holistic 44 approach allows for comparing commodity chains while avoiding hidden problem shifting between 45 46 stages or environmental impacts. It can integrate the whole life cycle of the product (from cradle to 47 grave), i.e. starting with extraction of raw materials until the end of life of the used product, and 48 assesses a wide range of potential environmental impacts. 49 The aim of this study is to assess the environmental impacts of a bio-sourced moisturizing cream applying LCA. This cream contains an alkyl polyglucoside (APG) surfactant based on palm oil. Palm oil 50 51 is nowadays the most used vegetable oil worldwide, accounting in 2015 for 28.3% of the global oils and fats production (European Palm Oil Alliance, 2015). About 19% of total palm oil production is 52 53 used as oleo-chemicals, especially palm kernel oil (Rival and Levang, 2014). Various LCA on palm oil 54 and palm oil-based products have shown that the feedstock production at the farm stage is a major contributor to most of potential environmental impacts (Boonrod et al., 2016; Chavalparit et al., 55 56 2006; Choo et al., 2011; Chuchuoy et al., 2009; Nilsson et al., 2010; Schmidt, 2007; Yusoff and 57 Hansen, 2007). This large contribution of the farm stage, due to combined high input levels in the 58 field and low input levels at the mill and refinery stages, remains a key issue when including further

- 59 processing stages to convert palm oil into biodiesel (Achten et al., 2010; Angarita et al., 2009;
- Arvidsson et al., 2011; Choo et al., 2011; Harsono et al., 2012; Papong et al., 2010; Pleanjai et al.,
- 61 2009). Focusing on global warming impact, main contributors are GHG emissions during the farm
- stage and methane emissions from palm oil mill effluent treatment (POME). Whereas the impact
- from POME can be drastically reduced if the biogas is captured (Choo et al., 2011; Chuchuoy et al.,
- 64 2009) and further used at the mill stage (Chavalparit et al., 2006), the impact from the farm stage
- becomes overwhelming when forests or peat soil areas are converted to palm plantations (Reijnders
- and Huijbregts, 2008; Schmidt, 2007; Wicke et al., 2008; Zulkifli et al., 2009)
- 67 In this paper, we investigated the relative contributions of the various production phases of the
- 68 moisturizing cream over its life cycle from cradle to grave, i.e. from the palm oil production up to the
- 69 cream use. The first objective was to appraise the impact of the palm oil derivative within the whole
- supply chain of the moisturizing cream. Then, we focused on exploring how various palm oil
- 71 production alternatives may critically influence the final LCA results of the bio-based used cream. We
- 72 first described the implementation of the LCA following ISO norms and International Life Cycle Data
- 73 (ILCD) guidelines. We then analysed and discussed the influence of the palm oil production scenarios
- in light of the overall environmental impacts of the studied moisturizing cream.
- 75 2 Material and methods
- 76 2.1 LCA goal and scope
- 77 We implemented LCA according to ISO norms 14040 series and following recommendations from the
- 78 ILCD (EC-JRC, 2011). We used primary data, where available, and we used Simapro v.8 software with
- 79 Ecoinvent v.3 database for background inventories. For palm oil feedstock, we used mixed primary
- 80 and secondary data from the literature to model the plantation management and the industrial
- 81 plant. Field emission models are detailed in sub-section 2.2.1.3. For the other biomass feedstock, we
- 82 relied on Ecoinvent processes. Finally, for the industrial processing of the cosmetic cream, we used
- 83 primary data from a site-specific industry (Guilbot et al., 2013) and secondary data for the
- 84 background processes, e.g. electricity production and related emissions. ILCD guidelines define a set
- of 16 recommended impacts categories, which were applied in this study, except for Water Depletion
- due to some inconsistencies between the water impact assessment method and Ecoinvent v.3
- 87 database.
- The studied functional unit was the preparation and use of one 30 g jar of cosmetic cream (Guilbot et
- al., 2013). The production system consisted of 8 main stages (Fig. 1). We first considered an average
- palm plantation located in Malaysia (stages 1-2), including all transports from the manufacture sites

91

92

93

94

95

96 97

98 99

100

101

102

103

104

105

106

107

108

109

110

#### ACCEPTED MANUSCRIPT

to the field for field inputs and from the plantation gate to the mill for the fruits. Malaysia is the second world producer of palm oil and the most described system in life cycle inventory studies. The palm oil transformation into cetearyl alcohol (Transesterification & Hydrogenation) was assumed to take place in Germany (stage 3), including transport of palm kernel oil from Malaysia to Germany. The wheat production providing the D-glucose was assumed to be located in Northern France (stages 4-5), as well as the final processing step including the production of alkyl polyglucoside (APG) and the final cosmetic cream in accordance with primary data collected by the industry (stages 6-7). We added transport of D-glucose from the Northern (wheat production site) to the Southern part of France, where the final cream production occurred. We finally considered that the cosmetic cream was sold and use in Europe (stage 8), hence accounting for average European market conditions and adding transportation of cosmetic cream from manufacturer to retailer, from retailer to consumer, and of packaging residues from consumer to end of life treatment plant. All capital goods were included, except for the supermarket infrastructure.

To allocate co-product burdens, we reasoned with economic values in accordance with Ecoinvent v3 database guidelines, i.e. using 5 economic allocations:

- Kernel (18.7%) and Crude Palm Oil (81.3%) (Jungbluth et al., 2007)
- Crude Palm Kernel Oil (92.5%) and Palm Kernel Cake (7.5%) (Jungbluth et al., 2007) Palm oil
  prices may be quite volatile, however the ratios between palm oil and palm kernel oil or
  kernel meal are quite constant; hence price ratios from 2007 are still relevant for the study.
- Refined Palm Kernel Oil (99.22%) and Free Fatty Acid (0.78%) (Blonk Agri-footprint, 2014)
- Cetearyl Alcohol (27.9%), Methyl Ester (62.38%) and Glycerol (9.68%) (unpublished industrial data)
- The part of the cosmetic cream in transport during purchasing (the cosmetic cream price represents 4.66% of an average shopping basket)<sup>1</sup>
- 2.2 Production sub-systems and life cycle inventories
- 116 2.2.1 Palm oil production scenarios

In the current work, the baseline scenario was defined according to main standard industrial
 practices and alternative scenarios were investigated to assess critical production parameters. These
 scenarios are further detailed in the following sub-sections.

<sup>&</sup>lt;sup>1</sup> http://www.famillesrurales.org/franche\_comte/Upload/LienCMS/dp\_obsvprix\_janv2015\_2\_ljv\_CMS314.pdf, viewed 29/09/2016

120

2.2.1.1 Baseline scenario

121	We modeled the palm oil production system as a standard industrial production system in Malaysia
122	based on published data. We included all processes and flows from nursery production up to the
123	refined kernel palm oil (RKPO) including background processes. For the baseline scenario, we
124	considered a settled plantation (i.e. without Land Use change) on a mineral soil and conventional
125	industrial transformation processes up to palm oils, notably considering a conventional anaerobic
126	treatment of palm oil mill effluents (POME) in open ponds.
127	Our inventory data for the nursery stage were based on two studies. Data for water consumption,
128	electricity, diesel, plastic (production of polybags in Polyethylene, production of PVC irrigation pipes),
129	fertilizers, pesticides and road transport (seeds, fertilizers and pesticides transport between
130	Malaysian port and nursery) were taken from (Choo et al., 2011; Muhammad et al., 2010). Data for
131	sea transport of field inputs from manufacture site to Malaysian port were taken from Schmidt
132	(2007) (see Table S1, S2 and S3 in supplementary materials).
133	After the nursery, palm seedlings are transplanted in the oil palm plantation and cultivated for 25
134	years. The palms are planted at a density of 142 palms/ha (considering a 5% loss at replanting). Palm
135	Fresh Fruit Bunches (FFB) are harvested the whole year long starting after the third plantation year.
136	The composition of harvested FFB is: 20% oil, 25% nuts (5% kernels, 13% fibre and 7% shell) and 23%
137	of empty fruit bunches (EFB) that are brought back to the field as organic fertilizers. We considered a
138	standard management, including mineral and organic fertilizers, herbicides and field mechanization
139	(Table 1), and an average yearly yield over the whole cycle of 19.16 tFFB/ha.year as detailed in the
140	relevant background publications (Choo et al., 2011; Schmidt, 2007).
141	The collected FFB are directly sent to the palm oil mill and rapidly sterilized (within 24 hours) in order
142	to limit the formation of Free Fatty Acid (FFA) (Guilbot et al., 2013). Pulp from mesocarp and kernel
143	are then separated. Pulp is pressed with a screw press in order to obtain Crude Palm Oil (CPO).
144	Pressed mesocarp fibers and crushed kernel shells are burnt in the boiler to provide heat and power
145	leading to very limited amount of external energy input to the mill (Choo et al., 2011; Schmidt, 2007)
146	Pressing of kernel allows for the extraction of Crude Kernel Palm Oil (CPKO). Inventory data were
147	taken from various Malaysian studies (Choo et al., 2010; Vijaya et al., 2010). In the baseline scenario,
148	POME, which are composed of sterilization condensates and clarification waters (Parveen et al.,
149	2010), were conventionally treated in open anaerobic ponds that emit biogenic methane to the air
150	(Wicke et al., 2008).

151 After the mill stage, CPKO is chemically refined, implying degumming with acid then cleansing with 152 bleaching earth (Yew et al., 2010). Undesirable components such as FFA are stripped under vacuum 153 in the de-acidification and deodorization steps to finally produce refined palm kernel oil (RPKO) (Guilbot et al., 2013). Energy for CPKO refining process is met by electricity from the grid (Malaysian 154 155 grid) and fossil-fuel fed boilers. Liquid wastes from the refinery include wastewater and free fatty 156 acid distillate (Table 1). 157 2.2.1.2 Alternative scenarios Alternative scenarios were investigated from the farm stage up to the RPKO output, exploring (with 158 159 or without) 3 critical parameters: deforestation, peat soil oxidation, and methane capture and 160 electricity recovery from POME. Details on the calculation steps for the modified inventories are 161 provided in the following sub-sections. Within LCA, the impact of deforestation can be included at both inventory and impact assessment 162 163 levels (the appraisal of the Land Use impact category is described in section 2.3.). In the inventory, 164 deforestation is translated into carbon losses from above and below-ground biomass emitted as CO<sub>2</sub>. 165 We applied IPCC guidelines Tier1 (2006) to calculate these emissions, considering as previous Land 166 Use a primary forest in Asia (insular) with 350 x (1+0.37) t biomass/ha using a 37% ratio of below to 167 above-ground biomass. A palm plantation contains 136 x (1+0.28) t biomass/ha using a 28% ratio of below to above-ground biomass (IPCC, 2006). Emissions from land use change were implemented in 168 169 both scenarios with deforestation on mineral and peat soils. 170 On top of deforestation, converting peat soil to cropland area requires a dense drainage that notably 171 leads to the oxidation of soil organic carbon and finally CO<sub>2</sub> emissions. In the inventory, we accounted for annual CO<sub>2</sub> emissions due to the peat oxidation, which we further related to an 172 173 occupation impact (see section 2.3). We relied on the constant emission factor of 40 tCO<sub>2</sub>/ha.year (EPA, 2014). We did not account for a potential peak of emissions during the first 5-6 years right after 174 175 the peat drainage started due to a lack of available emission factor and data. We also accounted for N<sub>2</sub>O emissions from peat soil based on the IPCC emission factor (2013). According to IPCC (2013), we 176 177 did not account for any CH<sub>4</sub> emissions specific to changes in peat soil aeration status. No matter 178 whether the palm plantation on peat was established after forest or after replanting, the annual 179 emissions from peat oxidation were considered constant. We did not consider any fluctuations 180 depending on the initial thickness of the peat layer or the drainage depth. These assumptions were 181 further discussed (section 4).

#### ACCEPTED MANUSCRIPT

Finally, POME can be treated in different ways. The conventional treatment implies to store POME in open ponds, in which fermentation allows for the degradation of organic compounds in order to reach legal critical levels of Chemical and Biological Oxygen Demands before releasing or spreading of treated effluents. The anaerobic transformation of organic compounds leads to methane emissions, which contribute to global warming. Growing awareness on GHG issues has prompted the industries to seek for new solutions. The development of EFB composting allows for the recycling of raw POME. Moreover, a growing numbers of mills are combined with bioreactors that capture and flare methane from POME treatment with or without energy recovery (EPA, 2012). In our baseline scenario, we considered the conventional treatment and included pond methane emissions (Schmidt, 2007), as well as field emissions after treated POME field application based on IPCC emission factors for organic fertilizers (De Klein et al., 2006). In the alternative scenario, we considered the most interesting treatment alternative up to electricity recovery and substitution of grid electricity.

2.2.1.3 Field emission models

We took into account the emissions related to the use of fertilizers and pesticides. We followed IPCC guidelines (De Klein et al., 2006) in order to calculate the fractions of mineral and organic N-fertilizers emitted to the water (NO<sub>3</sub><sup>-</sup>) and the air (NH<sub>3</sub>, direct and indirect N<sub>2</sub>O). NO<sub>x</sub>, emissions were determined according to EMEP/EEA guidelines (EMEP and EEA, 2013). At the nursery stage, it was considered that no leaching could occur through the polybags. We also calculated P-fertilizer losses to the environment based on SALCA-P model (Prasuhn, 2006). For pesticides, we considered that the full rates of pesticides applied ended up in the soil. Fertilizers also contain heavy metals that we considered as stored in the soil (Brockmann et al., 2014).

- 2.2.2 Palm-based surfactant production
- 205 2.2.2.1 Production of the palm-based cetearyl alcohol
- The processing of RPKO into a palm-based surfactant takes place in Europe. RPKO is transported from Malaysia to France (Marseille) by transoceanic freight ship, then to Germany by train (Guilbot et al., 2013). We considered a transesterification of RPKO with methanol in the presence of sodium hydroxide given the low cost, good yield and easiness to process (Zah and Hischer, 2007). The recovered methanol is recycled in the process. The C-8/14 methyl ester is slit from the C-16/18 methyl ester by distillation separation. The last step is a continuous catalysed hydrogenation of the C-16/18 methyl ester under high temperature (250–300 °C) and high hydrogen pressure (25–35 MPa)

213	in a fixed bed trickle flow process. The targeted C-16/18 alcohol is finally distilled to reach a purity of
214	more than 95% (Giraldo et al., 2010) (see Table S4 in supplementary material).
215	2.2.2.2 Production of the complementary wheat-based crystallized D-glucose
216	Crystallized D-glucose is needed to produce the palm-based surfactant (128 g per kilogram of APG).
217	The used crystallized D-glucose is derived from wheat starch (Guilbot et al., 2013). For our study, we
218	used an Ecoinvent wheat inventory ("wheat grain {FR}, wheat production, alloc def") to represent a
219	proxy for the culture of wheat in France. After harvesting, the wheat grains are washed and ground
220	into flour and mixed up with water. The starch and gluten are then separated, and the resulting
221	starch milk is totally hydrolyzed The final processing steps involve demineralization, discoloration,
222	concentration by evaporation and crystallization to obtain anhydrous D-glucose (Gerngross, 1999).
223	An amount of 5.6 g of cultivated wheat provides 3.7 g of D-glucose, with a transformation energy
224	cost of $1.6 \times 10^{-2}$ MJ of energy (heat). The output crystallized D-glucose undergoes a Fischer
225	Glucosylation, with sodium hydroxide as neutralization agent. Un-reacted glucose is removed by
226	decantation and centrifugation (Guilbot et al., 2013).
227	2.2.2.3 Final production of the palm-based surfactant
228	The last step is the shaping of alkyl polyglucoside (APG) by pearlizing, which was assumed in this
229	study to take place in France (Castres city). We assumed a standard batch of 10.9 t of APG (Guilbot et
230	al., 2013), using 10.5 t of cetearyl alcohol and 1.4 t of crystallized D-glucose (Fig. 1). The supplying of
231	these raw materials is done by lorry ( $\sim$ 1200 km for the cetearyl alcohol coming from Germany to
232	Castres and $\sim$ 900 km for the glucose coming from the North of France to Castres). APG is stored in
233	plastic bags, themselves stored in packaging board of 25 kg. We considered the following packaging:
234	$5.44 \times 10^{-2}$ g packaging board and $6.68 \times 10^{-3}$ g of plastic film for $1.50$ g of APG. This packaging was
235	recovered in the cosmetic cream plant. We considered a recycling rate of 89% for packaging board
236	and 20% for plastic film, the remaining being incinerated (Badey and Lahitte, 2013).
237	As the APG is solid at room temperature (melting point $\sim\!65$ °C), the entire process is carried out by
238	heating with steam produced by a gas boiler (104 kg of steam per t of APG) (Guilbot et al., 2013).
239	Water input in the whole pearlizing process amounts 1.4 m³ per t of APG including the used cooling
240	water use that is recycled in a closed circuit system. The final input is dinitrogen, 2.2 m <sup>3</sup> per t of APG,
241	which is used during the entire process in order to prevent coloration with oxygen from the air. Apart
242	from APG, final co-products are: i) glucose muds from the decantation and centrifugation steps
243	( $\sim$ 76 kg per t of APG), which are incinerated in a specific treatment plant (at $^{\sim}$ 160 km from the
244	production site); and ii) liquid aqueous effluents (~14 l per t of APG containing 3000 mg per l of

245 246	materials).
247	2.2.3 Moisturizing cream production and use
248	2.2.3.1 Production of the cosmetic cream
249	The studied cosmetic cream contains 75% of water, 20% of an Argan oil phase (not available and
250	hence replaced by "global market for vegetable oil, refined "from ecoinvent"), and 5% of APG
251	(Guilbot et al., 2013). The emulsification process consists in mixing the three components for about
252	2 h at 70°C under vigorous agitation, which requires 85 kg steam and 6 kWh electricity per tonne of
253	cream. Waste are mud (70 kg per t of cream) and liquid wastewater (10 l per t of cream with
254	3,000 mg COD per I). The final cream is bottled in a 30 g jar made of 7 g of HDPE and a tight fitting lid
255	made of 1.79 g of HDPE. Each jar is packaged in a small cardboard box (5 $\times$ 5 $\times$ 5 cm) wrapped in a
256	very thin HDPE film (100 $\mu$ m). Our functional unit is the study of 1 jar (Table 2).
257	2.2.3.2 Use and end of life stage
258	The final use of the cream is its application on the skin of a consumer. The penetration (dose
259	absorbed through the skin) depends on skin permeability and properties of the cream as saturation
260	solubility. Some authors (Kroes et al., 2007; Williams et al., 2016) defined maximum flux ( $J_{max}$ ) to deal
261	with aspect and classified the dose absorbed during 24haccording it. A cosmetic cream with
262	surfactants, which was the case the present work, enhances skin penetration and promotes dermal
263	absorption of cosmetic ingredients (Williams et al., 2016). Jolliet (Jolliet et al., 2015) considered that
264	after 12h, 96% of the cream was absorbed. Consequently, in the present work, we assumed that the
265	cream was absorbed for the most part and the quantity of the cream streamed to the wastewater
266	treatment was negligible. This is in accordance with the Sustainability consortium (2013) guidelines
267	where wastewater treatment after the use of a cosmetic product is excluded of the system.
268	In our study, we did not consider any direct leakage after skin application (Guilbot et al., 2013).
269	However, we considered other potential impacts before and after the cream use, notably the
270	transport steps between production plant and storage (1,000 km by lorry), storage and retailer store
271	(100 km by lorry), from the store up to the consumer house. We also considered the recovery of
272	the jar.

273	We considered four types of transport in order to buy the cosmetic cream according to the European
274	average: personal car (57%), walk (24%), public transport (11%), and bicycle (8%) (De La Fuente
275	Layos, 2005).
276	The "public transport" category could be separated into 2 sub categories with the following
277	percentages (European Commission, 2014):
278	- Subway: 18% (i.e. 2% from the 11% public transport)
279	- Bus: 82% (i.e. 9% from the 11% public transport)
280	The assumed average roundtrip distance between the customer house and the store was 10 km (De
281	La Fuente Layos, 2005). We carried out an economic allocation in order to calculate the ratio of the
282	cosmetic cream over the total shopped basket during the purchasing transport.
283	Wastes were collected to be treated. The cosmetic cream jar with associated packaging consists of
284	8.79 g of HDPE, 3.75 g of cardboard and 1.41 g of plastic film. If recycling rate for HDPE is very high
285	like for bottles at consumer level, small dirty HDPE containers are commonly not separately collected
286	and can be assimilated to undifferentiated small packaging with a recycled rate of 3% (BIO
287	Intelligence Service, 2013). In the European context, $65\%^2$ of cardboard and 10% of plastic film are
288	recycled (BIO Intelligence Service, 2013). The non-recycled parts (97%, 35% and 90% respectively),
289	are incinerated and landfilled according European waste management practices $^{3}$ , (49% and 51 %
290	respectively). These assumptions are further discussed (section 4).
291	2.3 Impact characterisation and selected indicators
292	We applied ILCD (2011 V1.06) (European Commission, 2012) recommendations regarding the
293	selection of impact characterisation methods. We hence assessed 12 potential midpoint impacts (see
294	Table S6 in supplementary material).
295	Concerning the Land Use impact, following ILCD, we applied the "Land Use" indicator (Brandão and
296	Milà i Canals, 2013; Koellner et al., 2013; Milà i Canals et al., 2007). This indicator measures the
297	change in the amount of organic matter in soil (30 cm deep) as a proxy to quantify how the use of a
298	land area may impact the soil properties and functions. This indicator is expressed in kg C deficit. It
299	integrates the impact due to land transformation and land occupation relatively to a reference state

http://ec.europa.eu/eurostat/web/waste/key-waste-streams/packaging viewed 29/09/2016
http://ec.europa.eu/eurostat/tgm/refreshTableAction.do?tab=table&plugin=1&pcode=tsdpc240&language=en\_viewed 29/09/2016

(without considering any irreversible process). The occupation indicator theoretically includes two compounds. The first one refers to the impact of delaying the restoration of the potential SOC due to land occupation, the second refers to a further actual degradation or improvement in the SOC due to the land occupation. The latter, further referred to as "occupational change", is not yet implemented in ILCD (EC-JRC, 2011). We further refer to "occupational delay" for the currently implemented occupation impact in Land Use indicator. Characterisation factors are calculated based on SOC database from IPCC (2006).

For transformation, the gain or loss of SOC is calculated according to the following formula (Brandão and Milà i Canals, 2013; Milà i Canals et al., 2007):

309 Eq.1

300

301

302

303304

305

306

307

308

$$\Delta SOC\left(\frac{kg_{C}}{m^{2}}\right) = \frac{\frac{1}{2}(t_{relax} - t_{ini}) * (SOC_{ini} - SOC_{end})}{(t_{end} - t_{ini})}$$

310 Where:

- 311  $SOC_{ini}$  = Soil Organic Carbon at the initial state
- 312  $SOC_{end}$  = Soil Organic Carbon at the final state
- 313  $t_{ini}$  = Initial time
- 314  $t_{end}$  = Final time
- 315  $t_{relax}$  = Relaxation time (at  $t_{relax}$  SOC has reverted to the level in the reference state)
- In the baseline scenario, there is no transformation ( $SOC_{ini} = SOC_{end}$  =palm plantation). In the
- 317 alternative scenarios, we first calculated the Land Use transformation impact linked to deforestation
- 318 (i.e.  $SOC_{ini}$  = primary forest on mineral soil;  $SOC_{end}$  = palm plantation on mineral soil). We then also
- calculated the Land Use impact linked to peat soil cultivation with Land Use change (i.e.  $SOC_{ini}$  =
- primary forest on peat soil;  $SOC_{fin}$  = palm plantation on peat soil).
- 321 For peat soil in Asia, there was no characterisation factor in the Land Use indicator of ILCD
- 322 methodology. We hence needed to create this soil category in order to take into account the original
- 323 high carbon stocks in peat soils and potential subsequent effects from the draining and oxidation of
- peat soil. According to Page et al. (2011), the soil carbon content of a peat soil in Southeast Asia is
- 325 55.3 kg C/m² (considering the stock over the first 30 cm depth with a homogeneous distribution over

- the first 150 cm). We considered this stock to be the potential initial carbon stock ( $SOC_{ini}$ ) and used
- the soil carbon content of 8.6 kg C/m<sup>2</sup> as a final stock ( $SOC_{end}$ ). The latter is the one given for
- 328 tropical wetland under natural vegetation. We chose this stock as the final one considering that it
- was too low to refer to a natural undisturbed peat soil under forest.
- 330 In our study, we considered a regeneration or relaxation time,  $t_{relax}$ , for a used peat soil to recover
- its initial soil carbon stock, of 1,000 years. This time period corresponded to the highest relaxation
- time available (i.e. the one considered for sealed land)(Milà I Canals et al., 2007), considering that all
- potential changes are reversible. According to Milà I Canals (2007), we assumed an initial
- instantaneous transformation over one year, i.e.  $t_{end}$   $t_{ini}$  = 1.
- The calculated characterisation factor for peat soil transformation was finally:  $\Delta$  SOC =
- 336 23,350 kg C/m<sup>2</sup>
- For occupation, the impact on soil is calculated according to the following formula:

$$\Delta SOC\left(\frac{kg_{C}}{m^{2}}\right) = \frac{\left(SOC_{pot} - SOC_{ini}\right) * (t_{relax} - t_{ini})}{(t_{end} - t_{ini})}$$

- 338 Where:
- 339  $SOC_{ini}$  = Soil Organic Carbon at the initial state
- 340  $SOC_{not}$  = Soil Organic Carbon potential (at the native state)
- 341  $t_{ini}$  = Initial time
- 342  $t_{end}$  = Final time
- 343  $t_{relax}$  = Relaxation time (at  $t_{relax}$  SOC has reverted to the level in the reference state)
- In this formula, according to Milà I Canals (2007), we considered that  $t_{relax} = t_{end}$
- 345 The occupational delay impact is a constant annual carbon deficit due to the lack in carbon stock
- 346 compared to potential natural state. Result is valid for each year without specification on the soil
- type. For occupation of peat soil in Asia, we took  $SOC_{pot}$  = 55.3 kgC/m², and  $SOC_{ini}$  = 8.6 kgC/m², i.e.
- $\Delta$  SOC = 46.7 kg C/m<sup>2</sup>.year. For occupation of mineral soil, we use the ILCD default characterisation
- factor for "permanent crop Land Use occupation", without specification on the soil type, i.e.  $\Delta$  SOC =
- 350 4 kg C/m<sup>2</sup>.year.

In addition to this occupational delay impact factor, we also added an actual annual degradation, i.e. occupational change, in soil carbon content due to the draining and oxidation of peat soil. The oxidation of peat soil causes high  $CO_2$  emissions, which we have included in the life cycle inventory in terms of greenhouse gas emissions contributing to the Climate Change impact (see section 2.2.1.2). In order to be consistent and to take into account this soil organic carbon loss for the Land Use, we converted this  $CO_2$  inventory flow into an annual carbon stock change for Land Use impact category (was converted into 1.1 kg  $C/m^2$ .year) (section 2.2.1.2).

358

359

360

361

362363

364

365

366

367

368

369

370

371

372

373

374

375

376

377

378

379

380

381

382

351

352

353

354

355

356357

3 Results

3.1. Baseline scenario: continuous palm plantation on mineral soil

We performed a contribution analysis of the various production stages including the refined palm kernel oil (RKPO), the rest of the cosmetic cream compound production and processing, the production of the packaging, the transport to retailer and consumer, and the consumer waste management (Fig.2). We notably wanted to assess the relative contributions of agricultural stage (with a focus on palm oil production) and other industrial and logistical stages.

The contribution of each stage group to the total impacts varied with the impact category. Most impacting stages were transport to retailer and consumer, packaging and cosmetic cream. Transport to retailer and consumer was the main contributing process (largest for 11 out of 15 impacts indictors, min = 12% for Ionising Radiation Human Health, max = 82% for Mineral, Fossil and Renewable Resources Depletion). The high impact in terms of Mineral, Fossil and Renewable Resource Depletion was due to fossil fuel use in engines. Packaging production was also a significant contributing process (largest for 2 out of 15 impacts indicators, min = 4% for Mineral, Fossil and Renewable Resource Depletion, max = 82% for Ionising Radiation Human Health). The high impacts were notably related to the energy input, especially the electricity use from the French mix that relies greatly on nuclear electricity leading to a high contribution on Ionising Radiation Human Health. The total contribution of the production of the cosmetic cream itself, i.e. the production of refined palm kernel oil and other compounds and further transformations and assemblages up to the cream without its packaging, represented a high impact (min = 6% for Ionising Radiation Human Health, max = 58% for Land Use) of the impacts. Main contributing stages in the cosmetic cream production were the industrial transformation processes and the production of other vegetable oil, followed by RPKO and the wheat derivative. Cosmetic cream production, RPKO apart, had a nonnegligible impact (min = 6% for Ionising Radiation Human Health, max = 54% for Land Use). The high

383	impact for Land Use was related to the use other vegetable oil besides RPKO. The RPKO production in
384	the baseline scenario, which represented a non-negligible agricultural input on a feedstock mass
385	basis (1.9 g RPKO for 0.3 g wheat and 6 g of other oils, i.e. $20\%$ of the 30 g cream ), only had limited
386	impacts (min = 0.3% for Ionising Radiation Human Health, max = 12% for Marine Eutrophication). The
387	consumer waste management had a non-negligible impact in terms of avoided impact due to
388	material recycling notably regarding Ionizing Radiation Ecosystems, where it led to a 32% reduction
389	of the global impact.
200	W. C. ale and a state of the control
390	We further investigated the process contributions within the RPKO production stage (Fig. 3). In the
391	baseline scenario, the impacts of RPKO production were driven by the fresh fruit bunch (FFB)
392	production in the field and the palm oil processing. The palm oil mill effluent (POME) treatment
393	essentially contributed to the Climate Change impact (53%) due to the release of methane during
394	anaerobic treatment in open ponds. FFB production had the largest impact overall (min = 34% for
395	Climate Change, max = 96% for Marine Eutrophication). This high impact was notably due to the use
396	of synthetic mineral fertilizers greatly contributing to Climate Change, Photochemical Ozone
397	Formation, Acidification and Eutrophication impact categories. Crude palm oil (CPO) extraction, i.e.
398	fruit production apart, also had a high impact (min = $1\%$ for Land Use, max = $60\%$ for Climate
399	Change). CPO has a high impact for Particulate Matter mostly came from power central (boiler) and
400	to a lesser extent from the plant construction. Further contributions from other energy and chemical
401	uses (refinery step), as well as input and fruit transport to the mill, had low impacts.
402	3.2. Influences of deforestation, peat soil oxidation, and POME treatment
403	We investigated deeper the influence on the overall cosmetic cream impacts of the palm plantation
404	establishment and the palm oil mill effluent treatment. The parameters tested in the alternative
405	scenarios (see section 2.2.1.2) were the following:
406	- The previous Land Use: primary forest, i.e. deforestation, or palm cultivation, i.e. continuous
407	agricultural land use
408	- Soil type: mineral or peat soils
409	- The treatment of POME: conventional treatment or methane capture and electricity recovery.
410	Deforestation and peat soil transformation and occupation were translated i) in the life cycle
411	inventory as GHG emissions, and ii) in soil organic carbon changes embedded in the Land Use impact.
412	Hence, these two parameters only influenced two impact categories, i.e. Climate Change and Land

413	Use (Fig. 4). On Climate Change indicator, deforestation caused an increase of about 9% in the
414	cosmetic cream final impact (i.e. +282% in the RPKO impact), peat soil occupational change (i.e.
415	annual degradation of carbon stock and related CO <sub>2</sub> emissions) caused an even greater increase of
416	16% over the whole cosmetic cream life cycle (i.e. +46% for the RPKO). On Land Use indicator,
417	deforestation caused an increase of 3%, peat soil occupational delay (i.e. both the annual
418	degradation and the annual cost for delaying the relaxation to natural stock) and transformation
419	caused impact increases of 41% and 938%, respectively. The influence of peat soil transformation
420	and occupational delay was tremendous and in particular even much higher than that of
421	deforestation. These high increases corresponded to a variation of +917% for peat soil occupational
422	delay and +20,904% for peat soil transformation when focusing on the RPKO impacts.
423	Methane capture and conversion to electricity represented a low decrease in environmental impact
424	(min = $-0.1\%$ for Ionizing Radiation Human Health, max = $-3\%$ for Marine Eutrophication). The gain
425	provided by the improved treatment of POME was very low but consistent across all impact
426	categories. Focusing on RPKO production stage, POME improved treatment allowed a low decrease.
427	So, at the agricultural scale, POME improved treatment in order to produce electricity remained
428	interesting. At the cream final product scale, the gain provided remained negligible. However,
429	compared to deforestation and peat soil transformation and occupation, improved POME treatment
430	had a general, albeit small, positive influence on all impact categories.
424	A. Disavesias
431	4 Discussion
432	In the baseline scenario, which corresponded to a standard industrial palm production system in
433	Malaysia with no land use change, we could observe an impact of the palm kernel oil production and
434	refinery on the overall life cycle impact of the cosmetic cream. In this context, the contribution of
435	refined palm kernel oil was not critical with regard to the other process stages along the whole life-
436	cycle of the cosmetic cream. Moreover, palm kernel oil extraction and refinery processes were less
437	energy intensive (particularly in terms of fossil energy use) than most of the other up- and
438	downstream processes.
439	In comparison with the baseline economic allocation approach, using mass allocation ratios (except
440	at purchase stage due to lack of data for mass of shopping basket), environmental impacts would
441	have been lower (min=-0.4% for Ionizing Radiation; max=-15% for Marine Eutrophication). Mass
442	allocation ratios lowered RPKO impacts given the higher price per mass unit compared to refined
443	palm oil. The contribution of RPKO production to the final cream impact was very low. Besides

446

447

448

449

450

451 452

453

454

455

456

457

458

459

460

461

462

463464

465

466

467

468

469

470

471

472473

474

475

#### ACCEPTED MANUSCRIPT

reduction in RPKO impacts with mass allocation ratio, the contributions of other cream life cycle stages were not influenced by the change in allocation ratios.

Within the whole life-cycle of the cosmetic cream, the more impacting stages were packaging and transport. The primary data from the industrial partner allowed for a refined site-specific modelling of the industrial phase. However, some assumptions were still needed as well as the use of some secondary data from Ecoinvent v.3 database for some upstream background processes. We also modelled average current practices in term of transportation means and distances. More specific transport strategies might be explored to reduce the overall impacts but would need to be assessed on a case-by-case basis. Transport apart, the main remaining problem is the packaging which influenced significantly the final cream impacts, we looked at alternative scenarios for the end of life of the packaging (see Fig S1 in supplementary materials). When the HDPE packaging was entirely recycled, the total cream impacts were reduced (min=0% for Ozone Depletion; max=-25% for Ionizing Radiation), with a packaging impact (production + end of life management) contribution slightly decreased. Further complementary investigations might also be needed to check whether the assumption of the cream absorption with negligible washing out (Guilbot et al., 2013) may have an influence on the final results.

In the alternative scenarios, the RPKO contribution became much more critical for two impact categories, i.e. Climate Change and Land Use. The annual CO<sub>2</sub> emissions and the cumulated soil organic carbon depletion due to the draining and oxidation of the peat soil were the most influential parameters over all. Impact of peat soil drainage and oxidation would be even higher considering the former IPCC coefficient for wetland N<sub>2</sub>O emissions (2006), i.e. +10% in the RPKO Climate Change impact, or lower with another reference for CO<sub>2</sub> emissions (Hooijer et al., 2010), i.e. -18% in the RPKO Climate Change impact. This emphasises the need for further research work and consensus finding on guidelines and coefficients to assess the environmental impact of peat soil conversion. We adapted some coefficients and stocks found in the literature and proposed to include some part of the occupation impact, which is usually considered as negligible. However, more needs to be done. Concerning peat soil conversion, several factors in particular would need to be further addressed, e.g. the flush emissions right after opening and drainage start, the irreversible impact due to acute subsidence, the methane emissions from the drains or the indirect impacts at the watershed level, etc. From an environmental point of view, though, these estimate on Climate Change and Land Use impacts, albeit incomplete and perfectible, already highlight the prohibitive impact of peat soil conversion to agricultural uses where dense drainage is mandatory.

Our study aimed at providing a comprehensive LCA of a bio-sourced product, while focusing on the relative importance of the agricultural stage and production conditions over the whole supply chain. Further investigations would be necessary in order to better model potential discrepancies in agroecological performances between oil palm productions on mineral or peat soils, e.g. potential variations in crop cycle length, yields, disease pressure, and pesticide or fertilizer managements.

#### 5 Conclusion

This study dealt with environmental impacts of a cosmetic cream, which contained palm kernel oilbased as surfactant, from feedstock production to end of life management. It gave a precise picture of main impact contributors over the whole life-cycle of a bio-based cosmetic cream. It turned out that the transport from the retailer to the customer had the highest impact (highest for 11 out of 15 impacts indictors, min = 12% for Ionising Radiation Human Health, max = 82% for Mineral, Fossil and Renewable Resource Depletion). It was mainly caused by the use of petrol. The packaging had also a high impact (2 out of 15, min = 4% for Mineral, Fossil and Renewable Resource Depletion, max = 82% for Ionising Radiation Human Health). Agricultural phase in order to obtain RPKO had a small impact contribution (min = 0.3% for Ionising Radiation Human Health, max = 12% for Marine Eutrophication). The rests of the impacts were due to chemical step (min = 6% for Ionising Radiation Human Health, max = 54% for Land Use) and end of life management (min = -32%, max = 11%).

Many parameters could influence the palm oil production (i.e. RPKO impact contribution) and we investigated three of them: the previous land use, soil type and POME management. Mainly two impacts indicators were concerned in the alternative scenarios: Climate Change and Land Use with an increase of 25% and 1,528%, respectively, compared to the baseline scenario. On Climate Change, 9% were caused by deforestation and 16% by peat soil transformation and use. On Land Use, 938% were caused by peat soil transformation, 41% by peat soil use and occupational delay, and 3% by deforestation. Within the complete cream life-cycle, peat soil transformation and cultivation had the highest impact, while POME management was negligible.

An eco-design of the cosmetic cream could reduce its environmental impact considering some improvements at several stages. One of the key aspects was the packaging, where lower mass could reduce production and transportation impacts. Ecodesign would also require the integration of good farming practices, mainly concerning the previous land use and the type of soil, avoiding peat soil use. Through the example of a palm oil based cosmetic cream, this study showed the interest of a whole approach to bring face-to-face agricultural productions, transformations and use of products.

#### References

508	Achten, W.M.J., Vandenbempt, P., Almeida, J., Mathijs, E., Muys, B., 2010. Life Cycle Assessment of a
509	Palm Oil System with Simultaneous Production of Biodiesel and Cooking Oil in Cameroon.
510	Environ. Sci. Technol. 44, 4809–4815. doi:10.1021/es100067p
511	ADEME, BIO Intelligence Service, 2010. Analyse de Cycle de Vie appliquées aux biocarburants de
512	première génération consommés en France.
513	Angarita, E.E.Y., Silva Lora, E.E., da Costa, R.E., Torres, E.A., 2009. The energy balance in the Palm Oil-
514	Derived Methyl Ester (PME) life cycle for the cases in Brazil and Colombia. Renew. Energy 34,
515	2905–2913. doi:10.1016/j.renene.2009.05.007
516	Arvidsson, R., Persson, S., Fröling, M., Svanström, M., 2011. Life cycle assessment of hydrotreated
517	vegetable oil from rape, oil palm and Jatropha. J. Clean. Prod. 19, 129–137.
518	doi:10.1016/j.jclepro.2010.02.008
519	Badey, L., Lahitte, N., 2013. Guide de méthodologie simplifiée pour la réalisation des ACV dans le
520	cadre de la mise à disposition de l'information environnementale des huiles végétales.
521	BIO Intelligence Service, 2013. Study on an increased mechanical recycling target for plastics, Final
522	report prepared for Plastics Recyclers Europe, BIO Intelligence Service for Plastics Recyclers
523	Europe.
524	Blonk Agri-footprint, 2014. Agri-footprint Methodology and Basic Principles.
525	Boonrod, B., Prapainainar, C., Narataruksa, P., Kantama, A., Saibautrong, W., Sudsakorn, K.,
526	Mungcharoen, T., Prapainainar, P., 2016. Evaluating the environmental impacts of bio-
527	hydrogenated diesel production from palm oil and fatty acid methyl ester through life cycle
528	assessment. J. Clean. Prod. 1–12. doi:10.1016/j.jclepro.2016.07.128
529	Brandão, M., Milà i Canals, L., 2013. Global characterisation factors to assess land use impacts on
530	biotic production. Int. J. Life Cycle Assess. 18, 1243–1252. doi:10.1007/s11367-012-0381-3
531	Brockmann, D., Hanhoun, M., Négri, O., Hélias, A., 2014. Environmental assessment of nutrient
532	recycling from biological pig slurry treatmentimpact of fertilizer substitution and field
533	emissions. Bioresour. Technol. 163, 270–9. doi:10.1016/j.biortech.2014.04.032
534	Chavalparit, O., Rulkens, W.H., Mol, A.P.J., Khaodhair, S., 2006. OPTIONS FOR ENVIRONMENTAL
535	SUSTAINABILITY OF THE CRUDE PALM OIL INDUSTRY IN THAILAND THROUGH ENHANCEMENT
536	OF INDUSTRIAL ECOSYSTEMS. Environ. Dev. Sustain. 8, 271–287. doi:10.1007/s10668-005-9018-

537	Z						
538	Choo, Y.M., Muhamad, H., Hashim, Z., Subramaniam, V., Puah, C.W., Tan, Y., 2011. Determination of						
539	GHG contributions by subsystems in the oil palm supply chain using the LCA approach. Int. J.						
540	Life Cycle Assess. 16, 669–681. doi:10.1007/s11367-011-0303-9						
541	Choo, Y.M., Puah, C.W., Yew, A.T., Vijaya, S., Zulkifli, H., Halimah, M., 2010. Part 3a: Life cycle						
542	assessment of the production of crude palm kernel oil. J. oil palm Res. 22, 904–912.						
543	Chuchuoy, K., Paengjuntuek, W., Usubharatana, P., Phungrassami, H., 2009. Preliminary study of						
544	Thailand carbon reduction label: a case study of crude palm oil production. Eur. J. Sci. Res. 34,						
545	252–259.						
546	De Klein, C., Novoa, R.S., Ogle, S., Smith, K.A., Rochette, P., Wirth, T.C., 2006. Chapter 11 N2O						
547	emissions from managed soils, and CO2 emissions from lime and urea application 1–54.						
548	De La Fuente Layos, L.A., 2005. Mobilité des passagers à courte distance en Europe.						
549	Drösler, M., Verchot, L., Freibauer, A., Pan, G., 2013. Chapter 2 drained inland organic soils 1–79.						
550	EC-JRC, 2011. International Reference Life Cycle Data System (ILCD) Handbook: Recommendations						
551	for Life Cycle Impact Assessment in the European context EUR 24571 EN - 2011, First Edit. ed.						
552	Publications Office of the European Union, Luxembourg. doi:10.278/33030						
553	EMEP, EEA, 2013. Air pollutant emission inventory guidebook. doi:10.2800/92722						
554	EPA, 2012. Final Directive on Palm Oil. RFS2. Federal Register / Vol. 77, No. 18.						
555	European Commission, 2012. Characterisation factors of the ILCD Recommended Life Cycle Impact						
556	Assessment methods. doi:10.2788/60825						
557	European Commission, E., 2014. EU Transport in Figures. Statistical Pocketbook 2014.						
558	doi:10.2832/63317						
559	European Palm Oil Alliance, 2015. Palm Oil Consumption [WWW Document]. URL						
560	http://www.palmoilandfood.eu/en/palm-oil-consumption						
561	Fargione, J., Hill, J., Tilman, D., Polasky, S., Hawthorne, P., 2008. Land Clearing and the Biofuel Carbon						
562	Debt. Science (80 ). 319, 1235–1239.						

563	Farrel, A.E., Plevin, R.J., Turner, B.T., Jones, A.D., O'Hare, M., Kammen, D.M., 2006. Ethanol Can
564	Contribute to Energy and Environmental Goals. Science (80 ). 311, 506–509.
565	Gerngross, T.U., 1999. Can Biotechnology move us toward a sustainable society? Nat. Biotechnol. 17,
566	541–544.
567	Gibbs, H.K., Johnston, M., Foley, J. a, Holloway, T., Monfreda, C., Ramankutty, N., Zaks, D., 2008.
568	Carbon payback times for crop-based biofuel expansion in the tropics: the effects of changing
569	yield and technology. Environ. Res. Lett. 3, 34001. doi:10.1088/1748-9326/3/3/034001
570	Giraldo, L., Camargo, G., Tirano, J., Moreno-Piraján, J.C., 2010. Synthesis of Fatty Alcohols from Oil
571	Palm Using a Catalyst of Ni-Cu Supported onto Zeolite. E-Journal Chem. 7, 1138–1147.
572	doi:10.1155/2010/439801
573	Gnansounou, E., Dauriat, A., Villegas, J., Panichelli, L., 2009. Life cycle assessment of biofuels: Energy
574	and greenhouse gas balances. Bioresour. Technol. 100, 4919–4930.
575	doi:10.1016/j.biortech.2009.05.067
576	Guilbot, J., Kerverdo, S., Milius, A., Escola, R., Pomrehn, F., 2013. Life cycle assessment of surfactants
577	the case of an alkyl polyglucoside used as a self emulsifier in cosmetics. Green Chem. 15, 3337.
578	doi:10.1039/c3gc41338a
579	Harsono, S.S., Prochnow, A., Grundmann, P., Hansen, A., Hallmann, C., 2012. Energy balances and
580	greenhouse gas emissions of palm oil biodiesel in Indonesia. GCB Bioenergy 4, 213–228.
581	doi:10.1111/j.1757-1707.2011.01118.x
582	The sustainability consortium, 2013. Life Cycle Impact Study of Leave-on Skin Care Products.
583	https://www.sustainabilityconsortium.org/hpc/
584	Hooijer, A., Page, S., Canadell, J.G., Silvius, M., Kwadijk, J., Wösten, H., Jauhiainen, J., 2010. Current
585	and future CO <sub>2</sub> emissions from drained peatlands in Southeast Asia. Biogeosciences 7, 1505–
586	1514. doi:10.5194/bg-7-1505-2010
587	Hutchings, N., Webb, J., Amon, B., 2013. EMEP/EEA air pollutant emission inventory guidebook -
588	2013 - Crop production and agricultural soil.
589	Intergovernmental Panel on Climate Change, 2006. Volume 4 Agriculture, Forestry and Other Land
590	Use.

591	Jolliet, O., Ernstoff, A.S., Csiszar, S.A., Fantke, P., 2015. Defining Product Intake Fraction to Quantify
592	and Compare Exposure to Consumer Products. Environ. Sci. Technol. 49, 8924–8931.
593	doi:10.1021/acs.est.5b01083
594	JRC, EUCAR, CONCAWE, 2008. Well-to-Wheels study. Version 3, year 2008.
595	Jungbluth, N., Chudacoff, M., Dauriat, A., Dinkel, F., Doka, G., Emmenegger, M.F., Gnansounou, E.,
596	Kljun, N., Schleiss, K., Spielmann, M., Stettler, C., Sutter, J., 2007. Life Cycle Inventories of
597	Bioenergy. ecoinvent report No. 17, Ecoinvent. Dübendorf.
598	Koellner, T., de Baan, L., Beck, T., Brandão, M., Civit, B., Goedkoop, M., Margni, M., i Canals, L.M.,
599	Müller-Wenk, R., Weidema, B., Wittstock, B., 2013. Principles for life cycle inventories of land
600	use on a global scale. Int. J. Life Cycle Assess. 18, 1203–1215. doi:10.1007/s11367-012-0392-0
601	Kroes, R., Renwick, A.G., Feron, V., Galli, C.L., Gibney, M., Greim, H., Guy, R.H., Lhuguenot, J.C., van
602	de Sandt, J.J.M., 2007. Application of the threshold of toxicological concern (TTC) to the safety
603	evaluation of cosmetic ingredients. Food Chem. Toxicol. 45, 2533–2562.
604	doi:10.1016/j.fct.2007.06.021
605	Lodén, M., 2012. Effect of moisturizers on epidermal barrier function. Clin. Dermatol. 30, 286–296.
606	doi:10.1016/j.clindermatol.2011.08.015
607	Milà i Canals, L., Bauer, C., Depestele, J., Dubreuil, A., Freiermuth Knuchel, R., Gaillard, G., Michelsen
608	O., Müller-Wenk, R., Rydgren, B., 2007. Key Elements in a Framework for Land Use Impact
609	Assessment Within LCA (11 pp). Int. J. Life Cycle Assess. 12, 5–15. doi:10.1065/lca2006.05.250
610	Milà I Canals, L., Muñoz, I., McLaren, S., Miguel, B., 2007. LCA Methodology and Modelling
611	Considerations for Vegetable production and Consumption. CES Working Papers 02/07. United
612	Kingdom, Cent. Environ. Strateg. Univ. Surrey 46.
613	Muhammad, H., Hashim, Z., Subramaniam, V., Tan, Y. a, Wei, P.C., Let, C.C., May, C.Y., 2010. Life
614	Cycle Assessment of Oil Palm Seedling Production (Part 1). J. Oil Palm Res. 22, 878–886.
615	Nemecek, T., Schnetzer, J., 2012. Methods of assessment of direct field emissions for LCIs of
616	agricultural production systems 0.
617	Nilsson, K., Flysjö, A., Davis, J., Sim, S., Unger, N., Bell, S., 2010. Comparative life cycle assessment of
618	margarine and butter consumed in the UK, Germany and France. Int. J. Life Cycle Assess. 15,
619	916–926. doi:10.1007/s11367-010-0220-3

620	Page, S.E., Rieley, J.O., Banks, C.J., 2011. Global and regional importance of the tropical peatland
621	carbon pool. Glob. Chang. Biol. 17, 798–818. doi:10.1111/j.1365-2486.2010.02279.x
622	Papong, S., Chom-In, T., Noksa-nga, S., Malakul, P., 2010. Life cycle energy efficiency and potentials
623	of biodiesel production from palm oil in Thailand. Energy Policy 38, 226–233.
624	doi:10.1016/j.enpol.2009.09
625	Parveen, F.R., Rajeev, P.S., Hakimi, I., Norizan, E., 2010. Review of current palm oil mill effluent
626	(POME) treatment methods: Vermicomposting as a sustainable practice. World Appl. Sci 11,
627	70–81.
628	Pleanjai, S., Gheewala, S.H., Garivait, S., 2009. Greenhouse gas emissions from the production and
629	use of palm methyl ester in Thailand. Int. J. Glob. Warm. 1, 418. doi:10.1504/IJGW.2009.029213
630	Prasuhn, V., 2006. Erfassung der PO 4 -Austräge für die Ökobilanzierung. SALCA-Phosphor, in:
631	Agroscope FAL Reckenholz. Zürich.
632	Reijnders, L., Huijbregts, M.A.J., 2008. Palm oil and the emission of carbon-based greenhouse gases.
633	J. Clean. Prod. 16, 477–482. doi:10.1016/j.jclepro.2006.07.054
634	Rival, A., Levang, P., 2014. Palms of controversies Oil palm and development challenges.
635	Schmidt, J.H., 2007. Life cycle assessment of rapeseed oil and palm oil.
636	Secchi, M., Castellani, V., Collina, E., Mirabella, N., Sala, S., 2016. Assessing eco-innovations in green
637	chemistry: Life Cycle Assessment (LCA) of a cosmetic product with a bio-based ingredient. J.
638	Clean. Prod. 129, 269–281. doi:10.1016/j.jclepro.2016.04.073
639	Vijaya, S., Choo, Y.M., Halimah, M., Zulkifli, H., Tan, Y.A., Puach, C.W., 2010. LIFE CYCLE ASSESSMENT
640	OF THE PRODUCTION OF CRUDE PALM OIL ( Part 3 ) 22, 895–903.
641	Wicke, B., Dornburg, V., Junginger, M., Faaij, A., 2008. Different palm oil production systems for
642	energy purposes and their greenhouse gas implications. Biomass and Bioenergy 32, 1322–1337.
643	doi:10.1016/j.biombioe.2008.04.001
644	Williams, F.M., Rothe, H., Barrett, G., Chiodini, A., Whyte, J., Cronin, M.T.D., Monteiro-Riviere, N.A.,
645	Plautz, J., Roper, C., Westerhout, J., Yang, C., Guy, R.H., 2016. Assessing the safety of cosmetic
646	chemicals: Consideration of a flux decision tree to predict dermally delivered systemic dose for
647	comparison with oral TTC (Threshold of Toxicological Concern). Regul. Toxicol. Pharmacol. 76,

## 648 174-186. doi:10.1016/j.yrtph.2016.01.005 649 Yew, A.T., Halimah, M., Zulkifli, H., Vijaya, S., Puah, C.W., Chong, C.L., Maah, N., Choo, Y.M., 2010. Life Cycle Assessment of refined palm oil production and fractionation (part 4) 22, 913–926. 650 651 Yusoff, S., Hansen, S.B., 2007. Feasibility Study of Performing an Life Cycle Assessment on Crude Palm 652 Oil Production in Malaysia. Int. J. Life Cycle Assess. 12, 50-58. Zah, R., Hischer, R., 2007. Life cycle inventories of detergents, Report n°12, Ecoinvent. ed. 653 Zulkifli, H., Halimah, M., Mohd Basri, W., Choo, Y.M., 2009. Life cycle assessment for FFB production. 654 655 PIPOC 2009 Palm Oil - Balanc. Ecol. with Econ. 6. 656 657 658 659

Table 1: Life Cycle Inventory for the production of 23.57kg of RPKO (from 1000kg of FFB)

Table 1: Life Cycle Invento	Unit	FFB	Kernels	СРКО	RPKO
Output products	3			3	
FFB	kg	1,000 <sup>b</sup>			
Kernels	kg	1,000	53.2 <sup>b</sup>		
СРКО	kg		33.2	23.88 <sup>b</sup>	
RPKO	kg			23.00	23.57 <sup>b</sup>
СРО	kg		199.8 <sup>b</sup>		23.37
EFB	kg		225 <sup>b</sup>		
POME	NS .		672.5 <sup>b</sup>		
Palm kernel cake	kg		072.5	27.72 <sup>b</sup>	7
Free Fatty Acid	kg			27.72	0.24 <sup>b</sup>
Input	NS .				0.24
Soil transformation	m²	20.9 <sup>h</sup>			
Soil occupation	m²year	521.9 <sup>h</sup>			7
Energy use	iii yeai	321.9		( )	
Diesel : agriculture	L	2.37 <sup>a</sup>	0.57 <sup>b</sup>		
machinery	<b>-</b>	2.57	0.57		
Electricity from the	MJ		0.8 <sup>b</sup>	10.03 <sup>b</sup>	2.99 <sup>b</sup>
·	IVIJ		0.8	10.05	2.99
grid	MJ		31 <sup>b</sup>		
Electricity produced	MJ		31		7.73 <sup>b</sup>
Heat (steam)	IVIJ				7.73
Material use			4 200b	9.55 <sup>b</sup>	16.5 <sup>b</sup>
Water	L	0.223	1,300 <sup>b</sup>	9.55	16.5
Oil palm seedling	Transplant	0.33°	7		
Amonium sulfate	kg	8.05 a	/		
Urea	kg	0.41 <sup>a</sup>			
Ammonium nitrate	kg	0.76 a			
Ammonium chloride	kg	0.72 a			
Nitrogen fertiliser, as	kg	3.49°			
N		7			
Potassium chloride, as	kg	11.60°			
K <sub>2</sub> O		2			
Potassium fertiliser, as	kg	4.50 <sup>a</sup>			
K <sub>2</sub> O		2			
Phosphate rock, as	kg	6.55 <sup>a</sup>			
P2O5					
Phosphate fertiliser, as	kg	0.64 <sup>a</sup>			
P2O5					
Glyphosate	kg	0.34 a			
[Sufonyl]urea	kg	0.15 <sup>a</sup>			
compounds					
Bipyridylium	kg	0.10°			
compounds					
Pyretroid compounds	kg	2.15x10 <sup>-2 a</sup>			
Organophosphorus	kg	6.40x10 <sup>-2 a</sup>			
compounds					
Dimethylamine	kg	3.10x10 <sup>-2 a</sup>			
Pesticide unspecified	kg	2.13 <sup>a</sup>			
Phosphoric acid	kg				5.89x10 <sup>-3b</sup>

NaOH	kg				6.83x10 <sup>-2b</sup>
Bleaching earth	kg				1.06x10 <sup>-1b</sup>
Transport	<u> </u>				
FFB to mill, lorry	tkm	50			
Fertilizer from plant to	tkm	171.95 <sup>b</sup>			
port, ship					
Pesticides from plant	tkm	14.14 b			
to port, ship					
Fertilizer from port to	tkm	5.10 a			
plantation, lorry					
Pesticides from port to	tkm	0.15 <sup>a</sup>			
plantation, lorry					
Raw material and	tkm		0.1 <sup>b</sup>		
ancillaries, lorry					
Kernel, lorry	tkm			4.2 <sup>b</sup>	/
Palm kernel cake, lorry	tkm			1.1 <sup>b</sup>	
Phosphoric acid	tkm				5.89x10 <sup>-3b</sup>
NaOH	tkm		4		6.84x10 <sup>-2b</sup>
Bleaching earth	tkm				1.06x10 <sup>-1b</sup>
Diesel	tkm	<u> </u>			3.77x10 <sup>-2b</sup>
Fodder fat	tkm				4.71x10 <sup>-2b</sup>
Emissions to air	CKIII				4.717.10
CO <sub>2</sub>	kg	0			
CO <sub>2</sub> land	kg	0			
transformation	∖ Ng				
NH <sub>3</sub>	kg	4.50x10 <sup>-1 c</sup>	4.24x10 <sup>-2b</sup>		
N <sub>2</sub> O	kg	7.57x10 <sup>-2 b,c</sup>	6.81x10 <sup>-3b</sup>		
N <sub>2</sub> O	∖ Ng	7.57×10	0.81710		
NOx	kg	9.35x10 <sup>-2 e</sup>	2.72x10 <sup>-1b</sup>		
CH <sub>4</sub>	Kg		8.74 <sup>b</sup>		
H <sub>2</sub> S	kg	7	5.79x10 <sup>-2b</sup>		
SO <sub>2</sub>	kg		2.4x10 <sup>-3b</sup>		
CO	kg	/	6.71x10 <sup>-1b</sup>		
Particulates, < 2.5 um	kg		1.51x10 <sup>-1b</sup>		
Acetaldehyde	kg		1.2x10 <sup>-4b</sup>		
Arsenic	kg		1.9x10 <sup>-6b</sup>		
Benzene	kg		1.73x10 <sup>-3b</sup>		
Benzene, ethyl-	kg		5.72x10 <sup>-5b</sup>		
Benzene, hexachloro-	kg		1.37x10 <sup>-11b</sup>		
Benzo(a)pyrene	kg		9.52x10 <sup>-7b</sup>		
Cadmium	kg		1.33x10 <sup>-6b</sup>		
Chlorine	kg		3.42x10 <sup>-4b</sup>		
Chromium	kg		7.54x10 <sup>-6b</sup>		
Chromium VI	kg		7.62x10 <sup>-8b</sup>		
Copper	kg		4.20x10 <sup>-5b</sup>		
Dioxin, 2,3,7,8	kg		5.90x10 <sup>-11b</sup>		
Tetrachlorodibenzo-p-	<b>√</b> 8		J.50X10		
Formaldehyde	kα		2.48x10 <sup>-4b</sup>		
Hydrocarbons,	kg		1.73x10 <sup>-3b</sup>		
•	kg		1./3X10		
aliphatic, alkanes, C10,	<u> </u>				

branched					
	lea		6x10 <sup>-3b</sup>		
Hydrocarbons,	kg		OXIO		
aliphatic, unsaturated	lea		4.76x10 <sup>-5b</sup>		
Lead	kg		2.28x10 <sup>-4b</sup>		
m-Xylene	kg				
Manganese	kg		3.24x10 <sup>-4b</sup>		
Mercury	kg		5.72x10 <sup>-7b</sup>		
Nickel	kg		1.14x10 <sup>-5b</sup>		
NMVOC, non-methane	kg		1.71x10 <sup>-3b</sup>		
volatile organic					Y
compounds			5h		
PAH, polycyclic	kg		2.12x10 <sup>-5b</sup>		
aromatic hydrocarbons	_		- 8h		Y
Phenol, pentachloro-	kg		1.54x10 <sup>-8b</sup>		
Phosphorus	kg		5.72x10 <sup>-4b</sup>		
Toluene	kg		5.72x10 <sup>-4b</sup>		
Zinc	kg		5.72x10 <sup>-4b</sup>		
Emissions to water					
NO <sup>3-</sup>	kg	4.78 <sup>c</sup>		7.16x10 <sup>-5b</sup>	
PO <sub>4</sub> <sup>3-</sup>	kg	3.94x10 <sup>-2 f</sup>			
Р	kg				1.88x10 <sup>-3b</sup>
Emissions to soil					
Lead	mg	51.9 a,g			
Cadmium	mg	140 a,g			
Chromium	mg	1,480 a,g	\ <b>Y</b>		
Nickel	mg	265 <sup>a,g</sup>			
Copper	mg	292 a,g			
Zinc	mg	2,460 a,g			
Mercury	mg	0.682 a,g			
Arsenic	mg	73.8 a,g			
Thallium	mg	3.93 <sup>a,g</sup>			
Glyphosate	kg	0.338 a,g			
Metsulfuron-methyl	kg	0.148 a,g			
Paraquat	kg	0.104 a,g			
Cypermethrin	kg	2.15x10 <sup>-2 a,g</sup>			
Glufosinate	kg	3.20x10 <sup>-2 a,g</sup>			
ammonium					
Methamidophos	kg	3.20x10 <sup>-2 a,g</sup>			
Carbofuran	kg	3.50x10 <sup>-2 a,g</sup>			
Dimethylamine	kg	3.10x10 <sup>-2 a,g</sup>			
Waste to treatment	<u> </u>				
Waste water	kg				16.5 <sup>b</sup>
Bleaching earth to	kg				1.51x10 <sup>-1b</sup>
landfill					
<sup>a</sup> (Choo et al. 2011)	I	I	I	l	l .

<sup>&</sup>lt;sup>a</sup> (Choo et al., 2011)

<sup>&</sup>lt;sup>b</sup> (Schmidt, 2007)

c (De Klein et al., 2006) d (Drösler et al., 2013)

<sup>&</sup>lt;sup>e</sup> (Hutchings et al., 2013)

f (Nemecek and Schnetzer, 2012)

Table n°2: LCI of the production of 30 g of cosmetic cream (primary data from the industrial partner)

	Unit	Quantity
Inputs		
APG	g	1.5
Vegetable oil	g	6.0
Nitrogen	g	12.2
Tap water	g	24.7
Energy		
Electricity	kWh	2.1x10 <sup>-2</sup>
Steam	g	2.5x10 <sup>-3</sup>
Transport lorry	kgkm	6.3
Output		
Wastewater	ml	3.0x10 <sup>-1</sup>
Mud to incineration	g	2.1

g (Brockmann et al., 2014)

h (faostat.fao.org/)

## ACCEPTED MANUSCRIPT Crop production & Harvest Fresh Fruit Bunches 13.5 g Mill & Refinery (2) Wheat plantation (4) Wheat Refined Palm Kernel Oil $2.9x10^{-1}g$ $6.6\,\mathrm{g}$ Transesterification & Hydrolysis & Crystallization Hydrogenation (3) Cetearyl alcohol D-glucose 1.9x10<sup>-1</sup> g 1.4 g Glucosylation, Neutralization, Decantation & Pearlizing (6) Alkyl Poly Glucoside 1.5 g Emulsification & Packaging Cosmetic cream 30 g Purchasing, Use & End of Life Jar of cosmetic cream

Fig 1: Overview of the global system for 1 jar of cosmetic cream.




Fig 2: LCA results of the continuous palm plantation on mineral soil (baseline scenario)




Fig 3: LCA results of RPKO in baseline scenario




Fig 4: Influence of deforestation, peat soil transformation, peat soil occupation, POME treatment

#### Highlights

- Transport and packaging contribute the most to all impacts over the cream life cycle
- Refined Palm Kernel Oil represents on average 20% of this total impact
- Deforestation increases Climate Change by 12% and Land Use impact by 6%
- Peat soil occupation increases Climate Change by 22% and Land Use impact by 84%
- Improving palm oil mill effluent treatment reduces impacts by 1.49% on average