

Multi-scale k-means clustering of multispectral images

Mathias Corcel, Cecile Barron, Fabienne Guillon, Marie Francoise Devaux

▶ To cite this version:

Mathias Corcel, Cecile Barron, Fabienne Guillon, Marie Francoise Devaux. Multi-scale k-means clustering of multispectral images. Chimiométrie XVII, Jan 2016, Namur, Belgium. , 2016. hal-01608725

HAL Id: hal-01608725 https://hal.science/hal-01608725

Submitted on 3 Jun2020

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Distributed under a Creative Commons Attribution 4.0 International License









Corcel Mathias¹, Barron Cécile², Guillon Fabienne¹, Devaux Marie-Françoise¹ 1) UR 1268 BIA, INRA Nantes, France 2) UMR 1208 IATE, INRA Montpellier, France



Chimiométrie XVII – Namur - 19/01/2016

Large biological variability

- Many images are acquired for plant caracterization
 - To form a mosaic image representing the cross-section
 - To observe multiple sections of the same sample
 - To observe multiple samples



- Large data
 - Mosaic image with large number of pixels (~20M pixels / mosaic image without background)
 - + number of image per sample
 - + number of samples



Histological analysis through multispectral imaging

- Histological analysis of plant tissues ullet
 - Maize (Zea mays) stems
 - Many phenolic components present in cell walls
 - Hydroxycinnamic acids : ferulic, p-coumaric ...
 - Lignins with various types of monomers
- These components are autofluorescent
- Explore the variability of the different tissues using their autofluorescence
 - Multispectral fluorescence imaging using 4 different excitation conditions of UV or visible light











- Use methods to classify a large number of pixels using all spatial variability with unsupervized classification
- In order to explore the variability
- Using data with large population but small number of variables
 - No a priori knowledge on autofluorescence for most tissues
 - Not possible to select pixels or regions of interest



Pyramids in image processing

- Multi-scale representation on an image
- The image is reduced in each level
- Simple pyramid : Mean pyramids with halved resolution each level
 - Each new pixel is the mean of 4 pixels









Principle of classification using pyramids

- 1) Start at the level with the smallest resolution
- 2) Classify pixels into *k* clusters
 - Using k-means with Euclidian distance on Principal components
- 3) Select *n* pixels in each cluster
 - Random selection
- 4) Expand the selected pixels in the next level
- 5) Repeat from step 2 until the last level of the pyramid



Selection of the pixels in each level



K-means initialisation : Number and position

- Histogram (+ Smoothing) of the Score plot Principal Components 1 and 2
- H-maxima transform
- Gives initial positions for clusters on components 1 and 2
- Positions on other components set to 0







PC1 (60%)



Method used on an image

- Start at level 6
 - Resolution 1/32
- 15 clusters found
- 2000 pixels per cluster selected
 - Constant







Comparison of classification with and without pyramids

Using pyramids (with the same parameters as before)



Without pyramids



• The clusters obtained are largely similar



Comparison of classification with and without pyramids

With Pyramids

Sclerenchyma





Without Pyramids





Comparison of classification with and without pyramids

- Some clusters regroup multiple tissues (Identified by their biological role and/or morphology)
 - Their autofluorescence is too similar
 - Their react the same way to some enzymes
- And both approaches with/without pyramids have the same clusters With Pyramids











 Simple adaptation of image analysis and chemometry : image pyramids and k-means, allow to segment large images with satisfactory results

 The number of pixels is reduced by a factor of ~1000, allowing to analyze a batch with many mosaic images

• The segmentation is done using all the initial variability and without loss during the process





- Test the limits of pyramids
 - Further decrease the resolution
- Improve the selection of pixels
 - Validate the repeatability of the method due to the random selection of pixels in each cluster
 - New method of selection based on the variance inside each mean pixel
- Find a solution to <u>objectively</u> compare unsupervized classifications
- Analyse complete collections of images





Thanks for your attention !

