



HAL
open science

The Alignment Paradigm for Modeling the Self

Alexandre Pitti

► **To cite this version:**

Alexandre Pitti. The Alignment Paradigm for Modeling the Self. Workshop the Development of the Self, Sep 2017, Lisbonne, Portugal. hal-01609647

HAL Id: hal-01609647

<https://hal.science/hal-01609647>

Submitted on 3 Oct 2017

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

the Alignment Paradigm for Modeling the Self

Alexandre Pitti

Abstract—We propose to develop the notion of Alignment as one general design principle to understand how to model the Self. Alignment encompasses the notions of temporal contingency detection between sensors and motors to calibrate the self, the spatial alignment between sensors of different reference frames to represent the physical limits of the body for ego-centered representation and memory alignment as well behind old and new memories important for the autobiographical self. Behind this concept of alignment we identified three complementary neural mechanisms that may serve to achieve this autonomous construction, namely spike timing-dependent plasticity, gain-modulation and predictive coding. We review several robotic researches performed to answer this question in this perspective.

Index Terms—Alignment, Contingency, STDP, Multimodal Integration, Gain-Field, Body Image, Predictive Coding, Working Memory

I. INTRODUCTION

I propose to review in this manuscript different robotic researches I have done in the last decade to understand the development of agency and of self-other differentiation in robots as infants might do and to find which design principles should be replicated in robots in my viewpoint. Although it is now well admitted that the notion of Embodiment is linked to intelligent and autonomous systems [1], [2], [3], the design principles behind the very idea of what it means for an autonomous system to have a body –, agency, self-recognition, self-other representation, awareness, sensorimotor expectation, action observation – are still in a current research investigation state by roboticists.

In so far, no robot can even roughly recognizing itself on a mirror, really grasp an objet, understanding where its own hand is or learning to predict internal or external events and be surprised if they did not occur as expected. If sensorimotor learning in robots is still poorly achieved by cognitive architectures, any changes in the sensorimotor configuration or in the environment achieves to ruin it as any contextual changes modify just slightly sensorimotor contingencies (like perceptual illusions, tool-use, changes of reference frame) and perturb the mapping across the senses.

Thus, it appears that the imprinting of the body in a neural representation in silico should follow some design principles and mechanisms to be robust to changes. In this attempt, we would like to emphasize the concept of *Alignment* as a paradigm to understand (and create) a notion of Self in a robot. For instance, the Alignment Paradigm (*AP*) incorporates the idea of body calibration by that has been enounced by Rochat [4], [5] and Meltzoff [6], [7], temporal synchronization

and timing contingency by Watson [8], [9], as well as of spatial contiguity and dissonance studied by Heed [10], [11], [12].

We propose that Alignment can be one unity measure that can be quantified, and can be ever causal (unidirectional) or mutual (bi-directional) and multidimensional. Furthermore, *AP* is not necessarily centered to physical interactions, it conveys also aspects seen in social interactions: as we interact with others, we can align ourself to the partner as well as to its motion and to its intention. The social alignment can be in the opposite way with the partner adjusting its actions to our owns. And finally, *AP* can be bidirectional between oneself and its partner, together aware of the joint motions. In this case, the mutual alignment cannot be easily separated as it becomes one joint motion or one joint intention. I suppose this last stage is at the root of communication with the development of joint attention, empathy, ethics and theory of mind, which may be the ground for even broader cognitive skills like abstract representation, language.

Another dimension of this Alignment hypothesis is 'Memory' Alignment, which I define as the recursive and cumulative capacity to compare current actions to old ones experienced in the past and stored in the working memory and to decide either to explore new tracks or to follow old paths that were advantageous in the past. We possess some intrinsic mechanisms of predictive coding, reinforcement learning, novelty detection important for the developping of such auto-biographical mind. Hesslow and Adolph called this autothelic force the capacity of Learning-to-Learn [13], [14]. As we acquired more information about our environment, we can form some intuition about the success or failures of our own actions, our working memory can select which actions to choose whether to align to old memories or to search for new ones. Some examples are the A-not-B problem or the mirror test as exemplified in [15], [16], [17], [18], they are constitutive of the beginning of a conscious notion of Self in the human brain. The dynamical comparison between old memories and new actions, known as predictive coding, permits to construct habits and to form memory sequences.

All-in-all, I suggest three bio-inspired mechanisms potentially interesting to develop this idea of Alignment for the construction of the Self, namely (1) the Hebbian learning mechanism of Spike Timing-Dependent Plasticity (STDP) which permits to neurons at the neuron level to learn causally dependent temporal rules, (2) topographic networks based on the mechanism of Gain Modulation for multimodal integration, body representation and sensorimotor transformations at the population level, which can serve for learning a body ego-centered spatial representation as well as for changing it into an allocentric perspective, (3) a hierarchical memory system based on predictive coding for a rule-based episodic memory at the brain level.

A. Pitti is in the Laboratory ETIS, UMR CNRS 8051, the University of Cergy-Pontoise, ENSEA, France.
E-mail: alexandre.pitti@u-cergy.fr

All these three alignment mechanisms underlying Temporal Contingencies, Body Space and Top-Down Prediction are compatible with each other and have been investigated elsewhere by many researchers already. It is not clear however how they can be combined in the brain to give rise to a seeming unity to oneself.

II. TEMPORAL ALIGNMENT

One key mechanism for integrating different modalities into a cohesive neural representation appears to lie in the temporal encoding done by the synapses. Recent advances in neurosciences two decades ago have permitted to find the regulation mechanism based on timing known as Spike Timing-Dependent Plasticity (STDP, cf. [19], [20]) responsible for the functional integration in cortical neurons. Similar to the Hebbian rule of associative learning, STDP reinforces the synaptic links of the most congruous neurons as well as their temporal delays. STDP consists on the bidirectional adaptation mechanism which dynamically regulates the long-term potentiation (LTP) and long-term depression (LTD) in synaptic plasticity readjusting the synaptic weights to the precise timing interval between the initiating and the targeting neurons [19], [20].

Information processing in distributed neural networks is performed at a precise temporal resolution of several milliseconds. Over time, the most congruous neural pairs aggregate themselves into coherent neural patterns whereas the less congruous ones delete their links. Thus, STDP extends the hebbian rule to the temporal domain and can be defined as follows: if $neuron_{pre}$ fires at time t_{pre} , then $neuron_{post}$ is expected to fire at time t_{post} .

Keyser proposed that STDP could shape the specific connectivity and structural organization of the multi-sensory neurons in parieto-motor circuits to represent actions with millisecond order precision [21]. It is proposed that the contingent and redundant multimodal information learned in the sensorimotor circuits sustain then a neural representation of the body in action [22], [23].

At reverse, various perceptual experiences in the environment with temporal discrepancies can modulate differently the levels of integration in the sensorimotor circuits with the disrupting of sensorimotor integration. For instance, perceptual illusions like the McGurk effect or the rubber-hand illusion may be based on this timely-based mechanism. Rochat in [24] and also Shimada and colleagues in [25] performed some visual-delay based contingency detection tests for measuring self-perception in infants and showed that temporal synchrony was effective early at birth. Interestingly, their capabilities for self-perception cover the temporal horizon over 200 and 300 milliseconds above which the feeling of agency was not perceived. These discoveries give some indications on the level of temporal binding in sensorimotor coordination.

In several robotic researches, my colleagues and I have employed the STDP learning rule with spiking neural networks for temporal binding to study visuo-tactile anticipation during prehension and action observation in [26], during visuomotor coordination of a robot head and self-recognition on a mirror

in [27] and recently with Sotaro Shimada to replicate the rubber-hand illusion with an artificial skin in [28]. In these experiments, we associate the level of synchrony within the network to the level of agency, which means the prediction across the neurons related to temporal events detection. Depending on the robotic experience, the incoming information was from vision (camera), touch (artificial skin) or proprioception (motor activity) combined at the same time scale with synaptic delays within the interval range between 0 ms and 30 ms . We showed that multimodal integration was quite robust to temporal delays over 200 ms , which were ten times higher than the capabilities of each neural pairs and that temporal binding was done at the population level. Therefore, we propose that the notion of Self or not-Self is distributed over the network and each neuron contributes to its intermingled representation in between depending on the current state. This is against the hypothesis of the grand-mother cells that encode only specific representations. At reversed, in all our experiments, the study of the networks structural organization presented interesting topologies of population coding following the functional organizations of complex networks such as the small-world networks [29], [30]. These types of networks, similar to archipelagos with few interaction between the sub-clusters, have interesting information processing properties for sparse coding; that is, a distributed representation of information.

One hypothesis is that, depending on timing, temporal alignment permits to switch the functional organization from the *Self*-network into *Other*-network.

III. BODY ALIGNMENT

Perceiving objects in space is one of first tasks babies have to deal with during infancy. It is a rather difficult problem since infants have to represent one object with multiple sensory modalities (vision, sound, tactile) encoded in different reference frames (e.g., eye-centered, head-centered or hand-centered). This curse of dimensionality requires to construct some mapping between the reference frames relying on multiple coordinates transformation between the senses. One brain mechanism I found important is the one of Gain-Field (GF) modulation, which addresses this problem of spatial transformation and multi-sensory representation [31]. The gain-field modulation mechanism describes the phenomenon where the motor and the sensor signals (resp. A and B) mutually influence the amplitude activity of their afferent parietal neurons (resp. C) such that the corresponding mathematical function is similar to a multiplication: $C = A \times B$. This result is surprising because most neurocomputational models rely on classical summation or integral function. Yet, there are some advantages to use multiplication to integrate easily information, like estimating probabilities from two density probabilities or computing matrix-like 3D transformations.

For instance, multiplicative GF neurons have been found to monitor nearby objects in the peripersonal space [32], [33]. These neurons combine diverse incoming information from multiple modalities to process multiple body-centered coordinate systems invariant to motion. Similarly, multimodal GF neurons have been found in the motor cortex to be

activated with respect to where the hand is moving in the visual space [34], [35] or the wrist orientation [36]. In both regions, we observe a neural field activity sensitive to both the preferred motor activity and the preferred visual orientation [37]. Thus, these neurons may participate to the construction of a body image and of the peripersonal space.

Since GF neurons construct body-centered representations based on the integration of body posture, tactile information and vision, we believe its mechanism is important not only for self-perception but also for any kind of sensorimotor transformation such as those during social interaction like imitation or joint attention. Based on these considerations, we think it is highly probable that the GF mechanism contributes to the functioning of the Mirror Neurons System (MNS).

Their modeling corresponds to multiplicative Radial Basis Functions (RBFs) or sigma-pi networks [38], [39] to learn sensorimotor transformations. In image processing, these networks are known as gated networks, which have been recently re-investigated by [40], [41] for affine transformations and in developmental robotics [42], [43], [44] for multimodal integration. These multiplicative networks can serve to learn nonlinear transformations, which are common problems in robotics to compute direct mapping and inverse kinematics.

In recent researches, we proposed to exploit the properties of these GF neurons to construct neural networks that process spatial transformations in body-centered coordinates based on body posture, tactile information, sound and vision for self-perception. Sensorimotor coordination was done either in head-centered coordinates with the binding of audiovisual signals and of the camera motor position [42] or in arm-centered coordinates with a robotic arm from visual and tactile inputs [43], [45]. One result was for instance the construction of an ego-space around the body based on the integration of tactile, visual and motor activity. Another result was the learning of the visual transformation necessary for mapping the motion of one person in front of the robot camera with its most probable actions selected from its motor repertoire. These two results describe how self-other representations and the correspondence problem may be resolved based on the Alignment across the modalities.

Furthermore, it is interesting that a super-additive effect similar to GF mechanism has been found also in the multimodal neurons in the Superior Colliculus, which were more sensitive to the incoming signals of two types of information coming together rather than ones coming at different timing [46]. The Superior Colliculus combines temporal alignment as well as topological alignment of the unimodal maps (visual, tactile and auditive) to construct an egocentric representation with the head as reference [47], [48]. We proposed that the minimal Self for social development was done by this structure at the foetal stage for mimicry for instance. Simulations of the Superior Colliculus network with a baby face 3D simulation with tactile sensors permitted to make the system sensitive to face-like patterns without encoding this feature, and just by visual, tactile and motor integration [49]. Recent studies of human foetus sensitive to face-like patterns [50] and the study of the superior colliculus newborn monkeys sensitive to face-like patterns [51] are in line with our hypothesis.

IV. MEMORY ALIGNMENT

Previous sections emphasized the modeling of the present Self with candidate neural mechanisms that can support temporal binding and multimodal integration. We consider in this section auto-biographical memory[52] and incremental learning as an important component and complementary to the two previous ones.

Auto-biographical memory relies on the idea that we have the capability to scrutinize our own past actions and to judge them in comparison to current ones [53]. Based on our self-judgment, the human working memory (WM) has the ability to initiate flexible decision-making[54] and to incrementally learn to optimize its actions in order to perform better later. Stated like this, it is as if the Self brain was monitoring its own activity online with regard to its past performances.

One interesting framework that has emerged recently to describe this Self brain is the one of Predictive Coding (PC) [3] and of the related mechanism of Free-Energy Minimization (FEM) [55], [56]. According to PC, the brain is continuously attempting to minimize the discrepancy or prediction error between its inputs and its emerging models of the causes of these inputs via. This is done via neural computations approximating Bayesian inference[57]. Therefore, its architecture has to be at least hierarchical so that one neural circuit makes inferences about the causes of another. One network (the top layer) anticipates what is expected to be seen in another network (the bottom layer) and minimizes the prediction errors for controlling it. According to Seth, one such Self memory system may display the introspective capabilities of the human brain to learn interoceptive signals and to infer hidden causes (active inference) as well as errors (error-learning) when they can(not) be predicted [57]. Seth identified the Anterior Insular Cortex (AIC) as a comparator circuit to be engaged in interoceptive inference useful for error learning. In one neurocomputational simulation, we modeled also the AIC system for error learning [58]. The aim of the study was to describe how recursive and online learning could be done based on negative reinforcement learning. We attached the network behavior with the capability of learning-to-learn because the error detection served for interoceptive comparison of old memory and the indirect selection of new actions and therefore the indirect learning of new memories.

AIC is of course not the only place for interoceptive inference and several overlapping sub-networks appear to participate to the realization of the Predictive Brain [59] that could constitute the Self. In previous researches, we modeled the cortico-hippocampal system in order to investigate the development of predictive coding and of an autobiographical memory [60], [61], [62] with the rapid categorization of novel memories and the consolidation of old ones [63]. Based on previous developmental studies and neuro-functional analysis [64], [65], we simulated how the gradual activation of the neuromodulator Acetylcholine (ACh) activated the functional re-organization of the hippocampal system to start to detect novelty and to code sparsely old memories. We could show that a novelty detection mechanism in combination with habit learning could create a flexible working memory. The resulting

system was capable to solve the A-not-B problem, which is a marker during the first year of cognitive development and of flexible action selection.

We extended our research on predictive coding with a recent model based on the iterative free-energy optimization of recurrent neural networks, which is the acronym for INFERNO [66]. It consists on two learning systems coupled each other that attempt to diminish their mutual prediction errors. The result is the active control of one system on the other. In sensorimotor tasks, the coupled system is similar to a forward model and an inverse model, which attempt to dynamically optimize their models to reduce error prediction to better reach one goal and to better learn one body dynamics. In memory sequence tasks, we showed that INFERNO was capable to retrieve long-range sequences of spikes above 200 iterations which is above the state of art.

In the perspective of modeling one working memory, to learn and retrieve memory sequences, we believe that it encompasses also some important aspects behind designing the Self and autobiographical memories in one artificial system.

ACKNOWLEDGMENTS

Grants EQUIPEX-ROBOTEX (CNRS), chaire d'excellence CNRS-UCP and Labex MME-DII (ANR11-LBX-0023-01).

REFERENCES

- [1] R. Pfeifer and J. Bongard, *How the Body Shapes the Way We Think, A New View of Intelligence*. Bradford Books, 1999.
- [2] R. Pfeifer and A. Pitti, *La Revolution de L'Intelligence Du Corps*. Manuella Editions, 2012.
- [3] A. Clark, *Surfing Uncertainty Prediction, Action, and the Embodied Mind*. Oxford University Press, 2015.
- [4] P. Rochat, "Self-perception and action in infancy," *Exp. Brain Res.*, vol. 123, pp. 102–109, 1998.
- [5] P. Rochat and T. Striano, "Perceived self in infancy," *Infant Behavior and Development*, vol. 23, pp. 513–530, 2000.
- [6] A. Meltzoff, "like me a foundation for social cognition," *Developmental Science*, vol. 10, no. 1, pp. 126–134, 2007.
- [7] P. Marshal and A. Meltzoff, "Body maps in the infant brain," *Trends in Cognitive Sciences*, vol. 19, no. 9, pp. 499–505, 2015.
- [8] J. Watson, "The development and generalization of 'contingency awareness' in early infancy some hypotheses," *Merrill Palmer Quarterly*, vol. 12, pp. 123–135, 1966.
- [9] —, "Detection of self the perfect algorithm," In S. Parker, R. Mitchell and M. Boccia (Eds.), *Self-awareness in animals and humans Developmental perspectives*. Cambridge University Press, 1994.
- [10] T. Heed and B. Roder, "Common anatomical and external coding for hands and feet in tactile attention evidence from event-related potentials," *J. Cogn. Neurosci.*, vol. 22, pp. 184–202, 2010.
- [11] T. Heed and E. Azanon, "Using time to investigate space a review of tactile temporal order judgments as a window onto spatial processing in touch," *Frontiers in Psychology*, vol. 5, no. 00076, pp. 184–202, 2014.
- [12] T. Heed, V. Buchholz, A. Engel, and B. Roder, "Tactile remapping from coordinate transformation to integration in sensorimotor processing," *Trends in Cogn. Sci.*, vol. 19, no. 5, pp. 251–258, 2015.
- [13] K. Adolph and A. Joh, *Learning to Learn in the Development of Action*. In J. Lockman, J. Reiser, & C. A. Nelson (Eds.), *Action as an organizer of perception and cognition during learning and development Minnesota Symposium on Child Development*, 2005, vol. 33.
- [14] —, *Multiple learning mechanisms in the development of action*. New York Oxford University Press, 2009.
- [15] A. Diamond, "Development of the ability to use recall to guide action, as indicated by infants' performance on a-not-b," *Child Development*, vol. 74, pp. 24–40, 1985.
- [16] L. Smith, E. Thelen, R. Titzer, and D. McLin, "Knowing in the context of acting the task dynamics of the a-not-b error," *Psychological Review*, vol. 106, pp. 235–260, 1999.
- [17] P. Rochat, "Five levels of self-awareness as they unfold early in life," *Consciousness and Cognition*, vol. 12, pp. 717–731, 2003.
- [18] L. Smith and E. Thelen, "Development as a dynamic system," *Trends in Cognitive Sciences*, vol. 7, no. 8, pp. 343–348, 2003.
- [19] G. Bi and M. Poo, "Activity-induced synaptic modifications in hippocampal culture, dependence of spike timing, synaptic strength and cell type," *J. Neuroscience*, vol. 18, pp. 10464–10472, 1998.
- [20] L. Abbott and S. Nelson, "Synaptic plasticity: taming the beast," *Nature neuroscience*, vol. 3, pp. 1178–1182, 2000.
- [21] C. Keysers, "Demystifying social cognition: Hebbian perspective," *Trends in Cognitive Sciences*, no. 8, pp. 501–507, 2004.
- [22] V. Lestou, F. Pollick, and Z. Kourtzi, "Neural substrates for action understanding at different description levels in the human brain," *Journal of Cognitive Neuroscience*, vol. 20, no. 2, pp. 324–341, 2008.
- [23] G. Rizzolatti, L. Fadiga, L. Fogassi, and V. Gallese, "Premotor cortex and the recognition of motor actions," *Cognitive Brain Research*, vol. 3, pp. 131–141, 1996.
- [24] P. Rochat and T. Striano, "Perceived self in infancy," *Infant Behavior and Development*, vol. 23, pp. 513–530, 2000.
- [25] S. Shimada, K. Hiraki, and I. Oda, "The parietal role in the sense of self-ownership with temporal discrepancy between visual and proprioceptive feedbacks," *Neuroimage*, no. 24, pp. 1225–1232, 2005.
- [26] A. Pitti, H. Alirezaei, and Y. Kuniyoshi, "Cross-modal and scale-free action representations through enaction," *Neural Networks*, vol. 22, no. 2, pp. 144–154, 2009.
- [27] A. Pitti, H. Mori, S. Kouzuma, and Y. Kuniyoshi, "Contingency perception and agency measure in visuo-motor spiking neural networks," *IEEE Trans. on Aut. Ment. Dev.*, vol. 1, no. 1, p. 8697, 2009.
- [28] A. Pitti, G. Pugach, P. Gaussier, and S. Shimada, "Spatio-temporal tolerance of visuo-tactile illusions in artificial skin by recurrent neural network with spike-timing-dependent plasticity," *Scientific Reports*, vol. 7, p. 41056, 2017.
- [29] D. Watts and S. Strogatz, "Collective dynamics of 'small-world' networks," *Nature*, vol. 393, pp. 440–442, 1998.
- [30] D. Bassett and E. Bullmore, "Small-world brain networks," *The Neuroscientist*, vol. 12, no. 6, pp. 512–523, 2006.
- [31] R. Andersen and V. Mountcastle, "The influence of the angle of gaze upon the excitability of the light-sensitive neurons of the posterior parietal cortex," *J. Neuroscience*, vol. 3, pp. 532–548, 1983.
- [32] M. Graziano and C. Gross, "Spatial maps for the control of movement," *Current Opinion in Neurobiology*, vol. 8, pp. 195–201, 1998.
- [33] A. Iriki, M. Tanaka, S. Obayashi, and Y. Iwamura, "Self-images in the video monitor coded by monkey intraparietal neurons," *Neuroscience Research*, vol. 40, pp. 163–173, 2001.
- [34] G. Blohm, A. Khan, and J. Crawford, "Spatial transformations for eyehand coordination," *Encyclopedia of Neuroscience*, p. 203211, 2009.
- [35] A. Georgopoulos, H. Merchant, T. Naselaris, and B. Amirikian, "Mapping of the preferred direction in the motor cortex," *Proc Natl Acad Sci USA*, vol. 104, no. 26, pp. 11068–72, 2007.
- [36] S. Kakei, D. Hoffman, and P. Strick, "Sensorimotor transformations in cortical motor areas," *Neuroscience Research*, vol. 46, pp. 1–10, 2003.
- [37] P. Baraduc, E. Guigon, and Y. Burnod, "Recording arm position to learn visuomotor transformations," *Cerebral Cortex*, vol. 11, no. 10, pp. 906–917, 2001.
- [38] A. Pouget and L. Snyder, "Spatial transformations in the parietal cortex using basis functions," *J. of Cog. Neuro.*, vol. 3, pp. 1192–1198, 1997.
- [39] D. Bullock, S. Grossberg, and F. Guenther, "A self-organizing neural model of motor equivalent reaching and tool use by multijoint arm," *Journal of Cognitive Neuroscience*, vol. 5, no. 4, pp. 408–435, 1993.
- [40] R. Memisevic, "Learning to represent spatial transformations with factored higher-order boltzmann machines," *Neural Computation*, vol. 22, pp. 1473–1493, 2010.
- [41] O. Sigaud, C. Masson, D. Filliat, and F. Stulp, "Gated networks: an inventory," *arXiv:1512.03201v1*, 2016.
- [42] A. Pitti, A. Blanchard, M. Cardinaux, and P. Gaussier, "Gain-field modulation mechanism in multimodal networks for spatial perception," *12th IEEE-RAS Int. Conf. on Humanoid Robots*, pp. 297–302, 2012.
- [43] S. Mahe, P. Braud, R. Gaussier, M. Quoy, and A. Pitti, "Exploiting the gain-modulation mechanism in parieto-motor neurons application to visuomotor transformations and embodied simulation," *Neural Networks*, vol. 62, pp. 102–111, 2015.
- [44] A. Droniou, I. Serena, and O. Sigaud, "A deep unsupervised network for multimodal perception, representation and classification," *Robotics and Autonomous Systems*, vol. 71, p. 8398, 2015.
- [45] J. Abrossimov, A. Pitti, G. Pugach, and P. Gaussier, "Visuo-tactile learning for reaching and body schema with gain-field networks," *IEEE Conference on Humanoids*, p. submitted, 2017.

- [46] B. Stein and M. Meredith, *The Merging of the Senses*. A Bradford Book, Cambridge, MA, 1993.
- [47] B. Stein, B. Magalhães Castro, and L. Kruger, "Superior colliculus: Visuotopic-somatotopic overlap," *Science*, vol. 189, pp. 224–226, 1975.
- [48] B. Stein, "Development of the superior colliculus," *Ann. Rev. Neurosci.*, vol. 7, no. 22, pp. 95–125, 1984.
- [49] A. Pitti, Y. Kuniyoshi, M. Quoy, and P. Gaussier, "Modeling the minimal newborn's intersubjective mind: The visuotopic-somatotopic alignment hypothesis in the superior colliculus," *PLoS ONE*, vol. 8, no. 7, p. e69474, 2013.
- [50] V. Reid, K. Dunn, R. Young, J. Amu, T. Donovan, and N. Reissland, "The human fetus preferentially engages with face-like visual stimuli," *Current Biology*, vol. 27, no. 12, p. 18251828.e3, 2017.
- [51] M. Nguyen, J. Matsumoto, E. Hori, R. Souto Maior, C. Tomaz, A. Tran, T. Ono, and H. Nishijo, "Neuronal responses to face-like and facial stimuli in the monkey superior colliculus," *Frontiers in Behavioral Neuroscience*, vol. 8, no. 85, p. 10.3389/fnbeh.2014.00085, 2014.
- [52] G. Pointeau and P. Dominey, "The role of autobiographical memory in the development of a robot self," *Front. Neurobot.*, vol. 27, no. 11, p. 10.3389/fnbot.2017.00027, 2017.
- [53] U. Neisser, "Five kinds of self-knowledge," *Philos. Psychol.*, vol. 1, p. 3559, 2017.
- [54] E. Miller, "The "working" of working memory," *Dialogues Clin Neurosci.*, vol. 15, no. 4, pp. 411–418, 2015.
- [55] K. Friston and S. Kiebel, "Predictive coding under the free-energy principle," *Philosophical Transactions of the Royal Society of London. Series B, Biological Sciences*, vol. 364, pp. 1211–21, 2009.
- [56] M. Apps and M. Tsakiris, "The free-energy self: a predictive coding account of self-recognition," *Neurosci Biobehav Rev.*, no. 41, pp. 85–97, 2014.
- [57] A. K. Seth, "Interoceptive inference, emotion, and the embodied self," *Trends Cogn. Sci.*, no. 17, p. 565573, 2013.
- [58] A. Pitti, R. Braud, S. Mah, M. Quoy, and P. Gaussier, "Neural model for learning-to-learn of novel task sets in the motor domain," *Frontiers in Psychology*, vol. 4, no. 771, 2013.
- [59] A. Clark, "Whatever next? predictive brains, situated agents, and the future of cognitive science," *Behavioral and Brain Sciences*, vol. 36, no. 3, p. 181204, 2013.
- [60] K. Norman and R. O'Reilly, "Modeling hippocampal and neocortical contributions to recognition memory: a complementary learning systems approach," *Psychological Review*, vol. 110, pp. 611–646, 2003.
- [61] R. O'Reilly and K. Norman, "Hippocampal and neocortical contributions to memory advances in the complementary learning systems framework," *Trends in Cognitive Sciences*, vol. 6, no. 12, pp. 505–510, 2002.
- [62] Y. Munakata and J. McClelland, "Connectionist models of development," *Developmental Science*, vol. 6, no. 4, pp. 413–429, 2003.
- [63] A. Pitti and Y. Kuniyoshi, "Modeling the cholinergic innervation in the infant cortico-hippocampal system and its contribution to early memory development and attention," *Proc. of the International Joint Conference on Neural Networks (IJCNN11)*, pp. 1 – 8, 2011.
- [64] Z. Kaldy and N. Sigala, "The neural mechanisms of object working memory: what is where in the infant brain?" *Neuroscience and Biobehavioral Reviews*, vol. 28, pp. 113–121, 2004.
- [65] M. Hasselmo and C. Stern, "Mechanisms underlying working memory for novel information," *Trends in Cognitive Sciences*, vol. 10, no. 11, pp. 487–493, 2006.
- [66] A. Pitti, P. Gaussier, and M. Quoy, "Iterative free-energy optimization for recurrent neural networks (inferno)," *PLoS One*, p. 0173684, 2017.