



Modeling sensory preference in speech motor planning

Jean-François Patri, Julien Diard, Pascal Perrier

► To cite this version:

Jean-François Patri, Julien Diard, Pascal Perrier. Modeling sensory preference in speech motor planning. NCM 2017 - 27th Annual Meeting of the Society for Neural Control of Movement, May 2017, Dublin, Ireland. hal-01614559

HAL Id: hal-01614559


<https://hal.science/hal-01614559>

Submitted on 11 Oct 2017


HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

1. Context & Framework



Bayesian Model



Activation / Deactivation of 2 sensory constraints

$$C_A, C_S \in \{0; 1\}$$

OFF ON

Auditory pathway	$P(M \Phi [C_A = 1] [C_S = 0])$
Somatosensory pathway	$P(M \Phi [C_A = 0] [C_S = 1])$
Fusion of pathway	$P(M \Phi [C_A = 1] [C_S = 1])$

Outcome of motor planning

$$P([M = m] | \Phi [C_A = 1] [C_S = 1]) \propto \Xi_A(\rho_A(m)) \Xi_S(\rho_S(m))$$

$$\Xi_A(\rho_A(m)) = \int_{A_\Phi} P(A_\Phi | \Phi) P([C_A = 1] | [A_M = \rho_A(m)] A_\Phi)$$

$$\Xi_S(\rho_S(m)) = \int_{S_\Phi} P(S_\Phi | \Phi) P([C_S = 1] | [S_M = \rho_S(m)] S_\Phi)$$

Sensory Characterizations Activated Sensory Constraints

3. Weighting of sensory pathways

1st approach: Hard constraint

$$P([C_A = 1] | [A_M = a_m] [A_\Phi = a_\phi]) \propto \begin{cases} 1 & \text{if } a_m = a_\phi \\ 0 & \text{otherwise} \end{cases}$$

2nd approach: Soft constraint

$$P([C_A = 1] | [A_M = a_m] [A_\Phi = a_\phi]) \propto e^{-\frac{D_A(a_m, a_\phi)^2}{2\eta_A}}$$

$$P([M = m] | \Phi [C_A = 1] [C_S = 1])$$

$$\propto P([A_\Phi = \rho_A(m)] | \Phi) \times P([S_\Phi = \rho_S(m)] | \Phi)$$

$$\propto \mathcal{N}(\rho_A(m); \mu_A^\Phi, \kappa_A \cdot \Sigma_A^\Phi) \times \mathcal{N}(\rho_S(m); \mu_S^\Phi, \kappa_S \cdot \Sigma_S^\Phi)$$




Outcome of motor planning

Weighting of pathways


$$P([M = m] | \Phi [C_A = 1] [C_S = 1])$$

$$\propto \int_a P([A_\Phi = a] | \Phi) e^{-\frac{D_A(a - \rho_A(m))^2}{2\eta_A^2}} \times \int_s P([S_\Phi = s] | \Phi) e^{-\frac{D_S(s - \rho_S(m))^2}{2\eta_S^2}}$$

$$\propto \mathcal{N}(\rho_A(m); \mu_A^\Phi, \Sigma_A^\Phi + \eta_A) \times \mathcal{N}(\rho_S(m); \mu_S^\Phi, \Sigma_S^\Phi + \eta_S)$$



4. Implementation: Adaptation to an auditory perturbation




Biomechanical model

6 muscles activated via 6 λ parameters (Feldman, 1986)

Internal models: Radial Basis Functions $\rho_A(m)$ $\rho_S(m)$



Vowels characterized in:
 • 3-D Formant space
 • 6-D Muscle length space



$$P(A_\Phi | \Phi)$$

$$P(S_\Phi | \Phi)$$

Outcome of productions in auditory space



Result of motor adaptation


Update of auditory-motor internal model

$$P(A_M | M)$$

$$\rho_A^{(a)}(m) = \rho_A^{(u)}(m) + \delta_A$$

Adapted = Unperturbed + Perturbation

1st approach Hard constraint



2nd approach Soft constraint

