



HAL
open science

Asymptotic stability of the linearised Euler equations with long-memory impedance boundary condition

Florian Monteghetti, Denis Matignon, Estelle Piot, Lucas Pascal

► **To cite this version:**

Florian Monteghetti, Denis Matignon, Estelle Piot, Lucas Pascal. Asymptotic stability of the linearised Euler equations with long-memory impedance boundary condition. 13th International Conference on Mathematical and Numerical Aspects of Wave Propagation (WAVES 2017), May 2017, Minneapolis, United States. hal-01618060

HAL Id: hal-01618060

<https://hal.science/hal-01618060v1>

Submitted on 17 Oct 2017

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Asymptotic stability of the linearised Euler equations with long-memory impedance boundary condition

Florian Monteghetti^{1,*}, Denis Matignon², Estelle Piot¹, Lucas Pascal¹

¹ONERA – The French Aerospace Lab, Toulouse, France

²Department of Applied Mathematics, ISAE-SUPAERO, Toulouse, France

*Email: florian.monteghetti@onera.fr

Abstract

This work focuses on the well-posedness and stability of the linearised Euler equations (1) with impedance boundary condition (2,3). The first part covers the *acoustical* case ($\mathbf{u}_0 = \mathbf{0}$), where the complexity lies solely in the chosen impedance model. The existence of an asymptotically stable C_0 -semigroup of contractions is shown when the passive impedance admits a dissipative realisation; the only source of instability is the time-delay τ . The second part discusses the more challenging *aeroacoustical* case ($\mathbf{u}_0 \neq \mathbf{0}$), which is the subject of ongoing research. A discontinuous Galerkin discretisation is used to investigate both cases.

Keywords: impedance boundary condition, diffusive representation, stability, discontinuous Galerkin

Introduction

This work focuses on the (dimensionless) homentropic linearised Euler equations (LEEs)

$$\begin{cases} \partial_t p + \nabla \cdot \mathbf{u} + \mathbf{u}_0 \cdot \nabla p + \gamma p \nabla \cdot \mathbf{u}_0 = 0 \\ \partial_t \mathbf{u} + \nabla p + [\mathbf{u}_0 \cdot \nabla] \mathbf{u} + [\mathbf{u} \cdot \nabla] \mathbf{u}_0 + p [\mathbf{u}_0 \cdot \nabla] \mathbf{u}_0 = \mathbf{0}, \end{cases} \quad (1)$$

defined on $(0, \infty) \times \Omega$, where $\Omega \subset \mathbb{R}^n$ is a bounded Lipschitz open subset, $p(\mathbf{u})$ is the acoustical pressure (velocity), $\mathbf{u}_0 \in C^\infty(\overline{\Omega})^n$ is the (given) base flow, and $\gamma > 1$ is the specific heat ratio. On the boundary $\Gamma := \partial\Omega$ (with outward normal \mathbf{n}), a so-called acoustical *impedance boundary condition* is prescribed :

$$p(t, x) = [z \star_t \mathbf{u} \cdot \mathbf{n}(\cdot, x)](t) \quad (x \in \Gamma := \partial\Omega), \quad (2)$$

where the *impedance* ($z \in \mathcal{D}'_+(\mathbb{R}) \cap \mathcal{S}'(\mathbb{R})$, causal convolution kernel) models a mono-dimensional medium as a continuous linear time-invariant system.

A recent analysis of acoustical models in the time domain [6] has shown that a wide range of sound absorbing materials and ground layers, assumed locally-reacting, can be modelled by kernels such as (“’” is the weak derivative, $a_0, a_1 \geq 0$):

$$z = a_0 \delta + a_1 \delta' + D'_2 + D_3(\cdot - \tau), \quad (3)$$

where $\tau \geq 0$ and $D_i \in L^1_{\text{loc}}(0, \infty)$ is a causal *oscillatory-diffusive* kernel ($I_i \subset \mathbb{Z}$ countable, poles $\Re[s_{n,i}] < 0$, $r_{n,i} > 0$, μ_i positive Borel measure):

$$D_i(t) = \underbrace{\sum_{n \in I_i} r_{n,i} e^{s_{n,i} t}}_{\text{oscillatory}} + \underbrace{\int_0^\infty e^{-\xi t} d\mu_i(\xi)}_{\text{diffusive}}, \quad (4)$$

which models resonances and visco-thermal losses (e.g. fractional kernel $D_2 \propto t^{-1/2}$). A key feature of such *positive real* kernels is that they can be realised (in the sense of systems theory) by a *diagonal, dissipative*, infinite-dimensional dynamical system. Note that, if $\tau > 0$ in (3), then (2) is a *delayed* boundary condition, which models wave reflections. The two sources of instability in (1,2) are the base flow \mathbf{u}_0 and the impedance z .

1 Acoustical case

The acoustical assumption ($\mathbf{u}_0 = 0$) removes hydrodynamic instabilities, but leaves room for purely acoustical ones triggered by the impedance boundary condition (2,3). Below, the delayed ($\tau = 0$) and undelayed ($\tau > 0$) cases are successively investigated by recasting the PDE (1,2) into a Cauchy problem on a Hilbert space \mathcal{H} :

$$\dot{X}(t) = \mathcal{A} X(t), \quad X(0) = X_0 \in \mathcal{D}(\mathcal{A}). \quad (5)$$

To express \mathcal{A} , a time-domain realisation of z in a state-space Θ is needed. The given asymptotic stability results (see Thms. 3 and 5), crucially rely on the *dissipativity* of this realisation.

1.1 Undelayed impedance ($\tau = 0$)

Impedances z of increasing complexity can be considered, with Θ either finite or infinite-dimensional: proportional ($z = a_0 \delta$), for which no realisation is required; derivative ($z = a_1 \delta'$), for which $\Theta = \mathbb{C}$. For the sake of brevity and clarity, only two simplified examples (compared with (3)) are given below before the statement of the general result.

Example 1. Let $\hat{z}(s)$ be a real rational function, bounded for $\Re[s] \geq 0$. If $\Re[\hat{z}(s)] \geq 0$ (passivity), then it can be realised by a dissipative ODE

in $\Theta = \mathbb{R}^N$, with a suitable energy norm (positive real lemma, see [4, § 3.1]). Eq. (5) is then defined on $\mathcal{H} = L^2(\Omega) \times (L^2(\Omega))^n \times L^2(\Gamma; \Theta)$.

Example 2. Let $z = a_0\delta + D_2$ (not D_2'), and define the weighted spaces $\Phi_{\alpha(\xi)} = L^2(0, \infty; \alpha(\xi) d\mu_2)$. The diagonal, dissipative, infinite-dimensional realisation of D_2 in $\Theta = \Phi_1$ leads to $\mathcal{H} = L^2(\Omega) \times (L^2(\Omega))^n \times L^2(\Gamma; \Phi_1)$, and (5) then reads:

$$\mathcal{A}X = \mathcal{A} \begin{pmatrix} p \\ \mathbf{u} \\ \varphi \end{pmatrix} = \begin{pmatrix} -\nabla \cdot \mathbf{u} \\ -\nabla p \\ A\varphi + B\mathbf{u} \cdot \mathbf{n} \end{pmatrix}$$

$$V = H^1 \times (H^1(\text{div}) \cap (H^{1/2})^n) \times L^2(\Gamma; \Phi_{1+\xi})$$

$$\mathcal{D}(\mathcal{A}) = \left\{ X \in V \left| \begin{array}{l} [A\varphi + B\mathbf{u} \cdot \mathbf{n}] \in L^2(\Gamma; \Phi_1) \\ p|_{\Gamma} = a_0\mathbf{u} \cdot \mathbf{n} + C\varphi \text{ (in } L^2(\Gamma)) \end{array} \right. \right\},$$

where, formally, $(A\varphi)(x, \xi) = -\xi\varphi(x, \xi)$ (state operator), $(B\mathbf{u} \cdot \mathbf{n})(x, \xi) = \mathbb{1}(\xi)\mathbf{u} \cdot \mathbf{n}(x)$ (control), and $(C\varphi)(x) = \int_0^\infty \varphi(x, \xi) d\mu_2(\xi)$ (observation).

Theorem 3. Assume that $\tau = 0$ in (3). If $\Re[a_0] > 0$, $a_1 \geq 0$, $\Re[s_{n,i}] < 0$, $r_{n,i} > 0$ and μ_i is a positive Borel measure, then z admits a dissipative realisation, and (5) has a unique strong solution X , such that $\|X(t)\| \leq \|X_0\|$ for $t \geq 0$ and $\|X(t)\| \xrightarrow{t} 0$.

Proof (Sketch). We follow [4]. The dissipativity of the realisation of z implies that of \mathcal{A} . Well-posedness follows from the m -dissipativity of \mathcal{A} . With the Fredholm alternative, we show that $\rho(\mathcal{A}) \supset i\mathbb{R}^*$ (we use that $H^s(\Omega) \subset L^2(\Omega)$, $s > 0$, is a compact embedding). Since $0 \notin \sigma_p(\mathcal{A})$, asymptotic stability then follows from the Arendt-Batty theorem. \square

Remark 4. With an infinite-dimensional realisation of z , the embedding $\mathcal{D}(\mathcal{A}) \subset \mathcal{H}$ may not be compact, hence the need to finely inspect $\rho(\mathcal{A})$, as the pre-compactness condition of LaSalle's invariance principle is not straightforward to verify.

1.2 Delayed impedance ($\tau > 0$)

The delayed case ($\tau > 0$) can also be recast into (5) using a hyperbolic realisation of the delay through a transport equation, which leads to an additional extension: $\tilde{\mathcal{H}} = \mathcal{H} \times L^2(\Gamma; L^2(0, \tau; \Theta))$. Asymptotic stability then becomes delay-dependent, which is typical of time-delayed linear systems (see [5] and references therein). The energy method of Thm. 3 leads to a sufficient stability condition for the pure delay case (i.e. $D_3 = a_\tau\delta$, not a diffusive kernel).

Theorem 5. Let $a_\tau \in \mathbb{C}$ and $a_1 > 0$. If $\Re[a_0] > |a_\tau|$, then the result of theorem 3 extends to the case $z = a_0\delta + a_1\delta' + D_2' + a_\tau\delta(\cdot - \tau)$.

Proof (Sketch). Similar to Thm. 3. The energy norm on the hyperbolic variables, $\|\cdot\|_{L^2(\Gamma; L^2(0, \tau; \mathbb{C}))}$ (here, $\Theta = \mathbb{C}$), is tuned so that \mathcal{A} is dissipative. [5] \square

2 Aeroacoustical case

The aeroacoustical assumption is $\mathbf{u}_0 \neq 0$ in (1). In the case of a subsonic base flow ($|\mathbf{u}_0| < 1$), and under stringent assumptions on \mathbf{u} and \mathbf{u}_0 (which must be, in particular, potential), the energy functional of Cantrell and Hart [1, Eq. (64)] can be used to construct a contraction C_0 -semigroup. Without these assumptions, however, there is no energy balance, and the dissipativity of \mathcal{A} is lost: well-posedness can only be achieved in a space like “ $e^{-\mu t} L^2(\Omega)$ ”, for some $\mu > \omega_0(\mathcal{A}) > 0$, where $\omega_0(\mathcal{A})$ is the growth rate of \mathcal{A} . (This constitutes a difficulty of the LEEs, compared to e.g. the Galbrun equation, see [1].) Current research focuses on the identification of instabilities with (2,3), see e.g. [3].

3 Numerical method

Insights into the stability of (5) can be gained by a numerical approximation of the temporal growth rate $\omega_0(\mathcal{A})$. A nodal discontinuous Galerkin method [2] is used to formulate $\dot{X}^h = \mathcal{A}^h X^h + \mathcal{B}^h X(\cdot - \tau)$, with $X^h = (p^h, \mathbf{u}^h, \varphi^h)$. The time-domain impedance boundary condition (2,3) is enforced through a centred numerical flux that couples the acoustical unknowns (p^h, \mathbf{u}^h) with the memory variables φ^h . If $\tau > 0$, finite-dimensional criteria, which rely on e.g. linear matrix inequalities (LMIs) or spectral conditions, are used to assess stability.

Acknowledgment This research is supported jointly by ONERA and DGA.

References

- [1] J.-Ph. Brazier. “Derivation of an exact energy balance for Galbrun equation in linear acoustics”. In: *J. Sound Vibration* 330.12 (2011).
- [2] J. S. Hesthaven and T. Warburton. *Nodal discontinuous Galerkin methods*. Springer, 2008.
- [3] D. Khamis and E. J. Brambley. “Acoustic boundary conditions at an impedance lining in inviscid shear flow”. In: *J. Fluid Mech.* 796 (June 2016).
- [4] D. Matignon and C. Prieur. “Asymptotic stability of Webster-Lokshin equation”. In: *Math. Control Relat. F.* 4.4 (2014).
- [5] F. Monteghetti, G. Haine and D. Matignon. “Stability of Linear Fractional Differential Equations with Delays: a coupled Parabolic-Hyperbolic PDEs formulation”. In: *IFAC 20th World Congress*.
- [6] F. Monteghetti, D. Matignon, E. Piot and L. Pascal. “Design of broadband time-domain impedance boundary conditions using the oscillatory-diffusive representation of acoustical models”. In: *J. Acoust. Soc. Am.* 140.3 (2016).