



HAL
open science

A stochastic hybrid systems based framework for modeling dependent failure processes

Mengfei Fan, Zhiguo Zeng, Enrico Zio, Rui Kang, Ying Chen

► **To cite this version:**

Mengfei Fan, Zhiguo Zeng, Enrico Zio, Rui Kang, Ying Chen. A stochastic hybrid systems based framework for modeling dependent failure processes. PLoS ONE, 2017, 10.1371/journal.pone.0172680 . hal-01633052

HAL Id: hal-01633052

<https://hal.science/hal-01633052>

Submitted on 11 Nov 2017

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27

A stochastic hybrid systems based framework for modeling dependent failure processes

Mengfei Fan ¹, Zhiguo Zeng ^{2*}, Enrico Zio ^{2,3}, Rui Kang ¹ and Ying Chen ¹

¹ School of Reliability and Systems Engineering, Beihang University, Beijing, China

² Chair System Science and the Energy Challenge, Fondation Electricité de France (EDF), CentraleSupélec,
Université Paris Saclay, Chatenay-Malabry, France

³ Energy Department, Politecnico di Milano, Italy

* Corresponding author

E-mail: zhiguo.zeng@centralesupelec.fr (ZZ)

Author contributions

Conceptualization: MF ZZ.

Methodology: MF.

Software: MF.

Validation: ZZ EZ.

Formal Analysis: MF ZZ.

Investigation: MF ZZ.

Resources: RK YC.

Data Curation: MF.

Writing – original draft: MF ZZ.

Writing – review & editing: EZ.

Supervision: RK EZ.

Project Administration: YC.

Funding Acquisition: RK EZ YC.

1 **Abstract**

2 In this paper, we develop a framework to model and analyze systems that are subject to dependent, competing
3 degradation processes and random shocks. The degradation processes are described by stochastic differential
4 equations, whereas transitions between the system discrete states are triggered by random shocks. The modeling is,
5 then, based on Stochastic Hybrid Systems (SHS), whose state space is comprised of a continuous state determined
6 by stochastic differential equations and a discrete state driven by stochastic transitions and reset maps. A set of
7 differential equations are derived to characterize the conditional moments of the state variables. System reliability
8 and its lower bounds are estimated from these conditional moments, using the First Order Second Moment (FOSM)
9 method and Markov inequality, respectively. The developed framework is applied to model three dependent failure
10 processes from literature and a comparison is made to Monte Carlo simulations. The results demonstrate that the
11 developed framework is able to yield an accurate estimation of reliability with less computational costs compared to
12 traditional Monte Carlo-based methods.

14 **Introduction**

15 Failure of industrial components, systems and products may be caused by multiple failure processes, e.g. wear,
16 corrosion, erosion, creep, fatigue, etc. [1]. In general, the failure processes are categorized as degradation processes
17 (or soft failures) and catastrophic failure processes (or hard failures) [2]. Soft failure is caused by continuous
18 degradation and is often modeled by a continuous-state random process, e.g., Wiener process [3,4], Gamma process
19 [5-7], inverse Gaussian process [8-10], continuous-time semi Markov process [11], etc. Hard failure is caused by
20 traumatic shocks in various patterns and is often modeled by a discrete-state random process, e.g., Homogeneous
21 Poisson Process (HPP) [11-13], Nonhomogeneous Poisson Process (NHPP) [14-16], etc. Often, complex
22 dependencies exist among the failure processes [17]. For example, [18] presents experimental data to show that
23 erosion and corrosion can enhance each other and therefore accelerate the failure process. Also, it is observed in [19]
24 that the dependency between creep and fatigue severely reduces the Time-To-Failure (TTF) of the specimens that are
25 exposed to high temperatures and heavy loads. To accurately describe the failure behavior affected by multiple failure
26 processes, the possible dependencies among the failure processes need to be properly addressed.

27 In literature, various methods have been developed to model the dependencies among degradation processes

1 and random shocks. Peng et al. [20] develop a dependency model where the arrived shocks lead to an abrupt increase
2 of the degradation process. Wang and Pham [21] investigate systems subject to dependent competing risk, which
3 suffer failures due to degradations and random shocks: the model is proposed of shocks that can cause immediate
4 failure of the system, with a time-dependent probability $p(t)$, or can increase the degradation level with probability
5 $1 - p(t)$. Cha and Finklstein [22] assume that a shock can lead to a hard failure with probability $p(t)$, or can increase
6 the degradation rate with probability $1 - p(t)$. Jiang et al. [23] develop a model that considers that the threshold of
7 hard failures can be shifted by random shocks. Rafiee et al. [24] consider that the degradation rate is increased by a
8 series of shocks. Jiang et al. [1] categorize shocks into different shock zones based on their magnitudes and consider
9 that shocks in different zones have different effects on the degradation process. Bagdonavicius et al. [25], Fan et al.
10 [26] and Ye et al. [27] develop models that consider that the probability of hard failures is increased as the degradation
11 process progresses. Huynh et al. [14,15] investigate maintenance strategies for a dependence model, where the
12 intensity of the NHPP for random shock is a piecewise function of the degradation magnitude. Fan et al. [16] present
13 a reliability model for sliding spools considering that the intensity of the NHPP describing the random shock process
14 is a linear function of the degradation level.

15 For models that consider the dependencies between degradation and random shock processes, like these above,
16 it is often too complicated, if not intractable, to evaluate system reliability analytically. Then, simulation methods,
17 such as Monte Carlo methods [28], are used, often with limitations due to heavy computational burden. In this respect,
18 Stochastic Hybrid Systems (SHS) [29] offer a new way to model the stochastic behavior of systems that involve both
19 discrete and continuous states [30-33]. SHS describe the system's behavior by a set of differential equations and
20 therefore, whose solution avoids the computational burdens of simulation methods. Various forms of SHS exist in
21 literature (see Pola et al. [29] for a comparison). In this paper, we adopt the models recently developed by Hespanha
22 in [34-36], which is similar to the Piecewise Deterministic Markov Process (PDMP) [37] but differs from it in that
23 the continuous state variable follow Stochastic Differential Equations (SDEs), rather than Ordinary differential
24 equations (ODEs). To the best of our knowledge, it is the first attempt to use SHS for modeling dependent failure
25 processes.

26 It should be mentioned that SHS is similar to Stochastic Hybrid Automata (SHA), which is also applied in
27 Dynamic Reliability (DR) assessment or Dynamic Probabilistic Risk Assessment (DPRA) [38,39]. Both methods
28 model dynamic hybrid system behaviors that involve stochastic factors. SHA introduces less assumptions than SHS

1 and resorts to Monte Carlo simulation for the calculations [40,41]; SHS, on the other hand, is able to describe the
 2 hybrid dynamics analytically or semi-analytically, by solving a set of Differential Equations (DEs) on the expense of
 3 introducing more assumptions [36]. The computational cost of SHS is, in general, less than that of SHA, but on the
 4 expense of more assumptions in particular with respect to the degradation models, whereby epistemic uncertainty
 5 (specifically model uncertainty) [42-44] is introduced. When applying the SHS in practice, then, care should be taken
 6 to ensure that the assumptions are consistent with the actual situation, in particular in case of systems characterized
 7 by complex and numerous dependencies among physical processes and failure behaviors. In this paper, we choose
 8 SHS because the type of dependent degradation and shock processes allows for modeling by SHS and, in general,
 9 SHS has a better computational performance than SHA.

10

11 **Methods**

12 **SHS model**

13 The state space of a SHS model is a combination of discrete and continuous states. Let us denote the discrete
 14 states by $q(t), q(t) \in Q$, where Q is a finite set containing all the possible discrete modes of the system. The
 15 continuous states are denoted by $x(t), x(t) \in \mathbb{R}^l$. A SHS model is defined based on the following assumptions [34-
 16 36]:

17 (1) The evolution of the continuous states is governed by a set of SDEs:

$$18 \quad dx(t) = f(q(t), x(t))dt + g(q(t), x(t))dw_t, \quad (1)$$

19 where $w_t : \mathbb{R}^+ \rightarrow \mathbb{R}^k$ is a k-dimensional Wiener process; $f : Q \times \mathbb{R}^l \rightarrow \mathbb{R}^l$ and $g : Q \times \mathbb{R}^l \rightarrow \mathbb{R}^{l \times k}$, respectively.

20 (2) At any time t , if the system is in state $(q(t), x(t))$, it undergoes a transition with a rate
 21 $\lambda_{ij}(q(t), x(t)) : Q \times \mathbb{R}^l \rightarrow \mathbb{R}^+$, $i, j \in Q$. That is, the probability that the system undergoes a transition from state i
 22 to state j within the interval $[t, t + \Delta t)$ is:

$$23 \quad \lambda_{ij}(q(t), x(t))\Delta t + o(\Delta t), \quad (2)$$

24 (3) Whenever the system undergoes a state transition from state i to state j , it instantaneously applies the
 25 map $\phi_{ij}(q(t), x(t))$ to the current values of $q(t)$ and $x(t)$, so that their values are reset:

$$(q(t), x(t)) = \phi_{ij}(q(t^-), x(t^-)), \quad (3)$$

where the notation $a(t^-)$ represents the left-hand limit of the function a at time t .

Fig 1 depicts the state transition and evolution of the SHS.

Fig 1. State-transition diagram for the SHS model

SHS formulism for dependent failure processes

The modeling framework for dependent failure processes involves three elements, i.e., a model for the degradation process, a model for the shock process and a model for the dependency between the two processes. The following assumptions are made in order to model a dependent failure process in the framework of SHS:

Assumption (1): The degradation processes are characterized by $x(t) = (x_1(t), x_2(t), \dots, x_l(t)) \in \mathbb{R}^l$. The elements in $x(t)$, $x_i(t), 1 \leq i \leq l$, are performance parameters for the degradation processes and are independent from one another. Soft failure occurs whenever

$$\exists i \in \{1, 2, \dots, l\}, x_i(t) > H_i, \quad (4)$$

where H_i is the failure threshold for the performance parameter $x_i(t)$.

Assumption (2): The system has n potential health states, i.e., $q(t) \in Q$ where $q(t)$ is a discrete-state variable that quantifies the system's health state at time t , and $Q = \{1, 2, \dots, n\}$ is a set containing all the possible system states. When $q(t) = n$, a hard failure occurs.

Assumption (3): Transitions between system health states are triggered by the arrival of random shocks with the transition rate $\lambda_{ij}(q(t), x(t))$, $i, j \in Q$, where the probability that the system jumps from state i to state j in the interval $[t, t + \Delta t)$ is given by (2).

Assumption (4): Between the transitions, the degradation of $x(t)$ is characterized by the SDEs in (1) for $q(t) = 1, 2, \dots, n-1$. When $q(t)$ takes different values, the form of $f(\cdot)$ and $g(\cdot)$ can be changed to reflect the dependency behavior. When $q(t) = n$, which indicates that the system fails due to hard failure, we impose that $x(t) = 0$.

1 Assumption (5): An arrival random shock resets the current values of $q(t)$ and $x(t)$, using the reset map
2 defined in (3).

3 Assumption (6): System failure is caused by both soft and hard failures, whichever occurs first.

4 Given a dependent failure process, the following steps show how to model it in the framework of SHS:

5 Step 1: Modeling degradation. In this step, the performance parameters $x(t)$ are identified to characterize the
6 degradation processes. For the performance parameters, the SDEs in (1) are developed to describe their degradation,
7 considering both deterministic and stochastic characteristics. The deterministic characteristics are often described
8 based on the physical knowledge on the degradation processes (e.g., using the Physics-of-Failure (PoF) models [19]),
9 while the stochastic characteristics are modeled by a Wiener process, as shown in (1).

10 Step 2: Modeling random shocks. In SHS, random shocks are considered as transitions among the system health
11 states. The transition rates, $\lambda_{ij}(q(t), x(t))$, $i, j \in Q$, need to be determined based on historical data or expert
12 judgments.

13 Step 3: Modeling dependencies. Finally, the dependencies between the degradation processes and random
14 shocks need to be considered. The dependencies can be modeled in various ways in SHS. For instance, by resetting
15 the values for $x(t)$, the reset map in (3) can capture the influence of the random shock on the degradation process.
16 Further, the functions f, g and even λ itself, as shown in **Fig 1**, are dependent on the current values of $x(t)$
17 and $q(t)$, which provides a versatile way to model the dependencies.

18 Note that in order to make sure that the developed SHS model is solvable in case that truncations techniques
19 [36] are needed, for example Case 3 in this paper, the $f_i, g_i, \lambda_{ij}, \phi_{ij}, i, j \in Q$ in the SHS model have to be polynomial
20 functions of $x(t)$.

21

22 **Conditional moments estimation**

23 In this section, we derive the conditional expectations for the continuous state variables, i.e.,
24 $E[x_j^p(t) | q(t) = i]$, $p \in \mathbb{N}, i \in Q, j = 1, 2, \dots, l$, where $x_j(t)$ represent the j th element of $x(t)$. The conditional
25 expectations will be used in the next section for reliability analysis. Let us define a test function to be

$$\psi_i^{(m)}(q, x) = \begin{cases} x^m & q = i \\ 0 & q \neq i \end{cases}, \quad (5)$$

where $m := (m_1, m_2, \dots, m_l), m \in \mathbb{N}^l$, and $x^m := x_1^{m_1} x_2^{m_2} \cdots x_l^{m_l}$, and let the m -order conditional moment of the continuous state x be

$$\begin{aligned} \mu_i^{(m)}(t) &:= E[\psi_i^{(m)}(q, x)] \\ &= E[x^m(t) | q(t) = i] \cdot \Pr\{q(t) = i\}. \end{aligned} \quad (6)$$

For a general test function $\psi(q(t), x(t))$, $\psi: Q \times \mathbb{R}^l \rightarrow \mathbb{R}$, which is twice continuously differentiable with respect to x , the evolution of its expected value is governed by Dynkin's formula [36]:

$$\frac{dE[\psi(q(t), x(t))]}{dt} = E[(L\psi)(q(t), x(t))], \quad (7)$$

where $(L\psi)(q, x)$ is the extended generator of SHS and $\forall (q, x) \in Q \times \mathbb{R}^l$, $(L\psi)(q, x)$ is given by

$$\begin{aligned} (L\psi)(q, x) &:= \frac{\partial \psi(q, x)}{\partial x} f(q, x) \\ &+ \frac{1}{2} \text{trace} \left(\frac{\partial^2 \psi(q, x)}{\partial x^2} g(q, x) g(q, x)' \right) \\ &+ \sum_{i, j \in Q} \lambda_{ij}(q, x) (\psi(\phi_{ij}(q, x)) - \psi(q, x)), \end{aligned} \quad (8)$$

where $\partial \psi / \partial x$ and $\partial^2 \psi / \partial x^2$ denote the gradient and Hessian matrix of $\psi(q, x)$ with respect to x , respectively;

$\text{trace}(A)$ is the trace of the matrix A , i.e., the sum of elements on its main diagonal.

Substituting (5) into (7), we get a group of differential equations with respect to $\mu_i^{(m)}(t), i \in Q, m \in \mathbb{N}^l$:

$$d\mu_i^{(m)}(t) = E[L(\psi_i^{(m)})(q(t), x(t))] \cdot dt. \quad (9)$$

The evolution of $\mu_i^{(m)}(t)$ can be depicted by solving (9). The conditional moments can, then, be obtained by

assigning proper values for m : if we let $m = (0, 0, \dots, 0)$, we have

$$\mu_i^{(0, 0, \dots, 0)}(t) = \Pr\{q(t) = i\}, i \in Q. \quad (10)$$

If we let

$$m = [m_1, m_2, \dots, m_l]: \begin{cases} m_j = p, & \text{if } j = k, k \in \{1, 2, \dots, l\}, \\ m_j = 0, & \text{if } j \neq k, \end{cases}$$

1 where m_j denotes the j th element in m and p is a natural number, we have

$$2 \quad \mu_i^{(m)}(t) = E[x_k^p(t) | q(t) = i] \cdot \Pr\{q(t) = i\}, i \in Q. \quad (11)$$

3 The conditional expectations, $E[x_j^p(t) | q(t) = i]$, $p \in \mathbb{N}, i \in Q, j = 1, 2, \dots, l$, can, then, be calculated by combining
4 (10) and (11).
5

6 Reliability analysis

7 From Assumption 6, system reliability can be expressed as:

$$8 \quad R(t) = \Pr(q(t) < n, x_1(t) < H_1, x_2(t) < H_2, \dots, x_l(t) < H_l). \quad (12)$$

9 From the law of total probability, we have

$$10 \quad \begin{aligned} R(t) &= \Pr(q(t) < n, x_1(t) < H_1, x_2(t) < H_2, \dots, x_l(t) < H_l) \\ &= \sum_{i=1}^{n-1} \Pr(q(t) = i) \cdot \Pr(x_1(t) < H_1, x_2(t) < H_2, \dots, x_l(t) < H_l | q(t) = i). \end{aligned} \quad (13)$$

11 Since we assume that the degradation processes are independent from one another, (13) becomes

$$12 \quad R(t) = \sum_{i=1}^{n-1} \left(\prod_{j=1}^l \Pr(x_j(t) < H_j | q(t) = i) \right) \cdot \Pr(q(t) = i) \quad (14)$$

13 In (14), $\Pr(q(t) = i)$ can be calculated by (10), $\Pr(x_j(t) < H_j | q(t) = i)$, $i = 1, 2, \dots, n-1, j = 1, 2, \dots, l$ can,
14 instead, be approximated using the First Order Second Moment (FOSM) method [45], since we have the conditional
15 moments for $x_j(t)$. Let $\mu_{x_j|q=i}(t)$ and $\sigma_{x_j|q=i}(t)$ denote the expected value and standard deviation of the random
16 variable $x_j(t)$ conditioned on $q = i$, respectively. Then, $\mu_{x_j|q=i}(t)$ and $\sigma_{x_j|q=i}(t)$ can be calculated by

$$17 \quad \begin{aligned} \hat{\mu}_{x_j|q=i}(t) &= E[x_j(t) | q(t) = i] = \frac{\mu_i^{(m^*,j)}(t)}{\Pr(q(t) = i)} = \frac{\mu_i^{(m^*,j)}(t)}{\mu_i^{(0,0,\dots,0)}(t)}, \\ \hat{\sigma}_{x_j|q=i}(t) &= \sqrt{E(x_j(t)^2 | q(t) = i) - (E(x_j(t) | q(t) = i))^2} \\ &= \sqrt{\frac{\mu_i^{(m^{**},j)}(t)}{\mu_i^{(0,0,\dots,0)}(t)} - \left(\frac{\mu_i^{(m^*,j)}(t)}{\mu_i^{(0,0,\dots,0)}(t)} \right)^2}, i \in \{1, 2, \dots, n-1\}, \end{aligned} \quad (15)$$

18 where $m^{*,j}$ and $m^{**,j}$ are given by

$$\begin{aligned}
m^{*,j} &= [m_1, m_2, \dots, m_l]: m_k = 1, \text{ if } k = j; m_k = 0, \text{ if } k \neq j, \\
m^{**,j} &= [m_1, m_2, \dots, m_l]: m_k = 2, \text{ if } k = j; m_k = 0, \text{ if } k \neq j.
\end{aligned} \tag{16}$$

Based on FOSM [45], $\Pr(x_j(t) < H_j | q(t) = i)$ can be approximated by

$$\Pr(x_j(t) < H_j | q(t) = i) \approx \Phi\left(\frac{H_j - \hat{\mu}_{x_j|q=i}(t)}{\hat{\sigma}_{x_j|q=i}(t)}\right). \tag{17}$$

Substituting (17) into (14), the reliability of the system is approximated by

$$R(t) \approx R_e(t) = \sum_{i=1}^{n-1} \mu_i^{(0,0,\dots,0)}(t) \cdot \left(\prod_{j=1}^l \Phi\left(\frac{H_j - \hat{\mu}_{x_j|q=i}(t)}{\hat{\sigma}_{x_j|q=i}(t)}\right) \right), \tag{18}$$

where $\hat{\mu}_{x_j|q=i}(t)$, $\hat{\sigma}_{x_j|q=i}(t)$ are calculated by (15).

The accuracy of the approximation by FOSM relies on the normality assumption: the random variables $x_j(t) | q(t) = i, i \in 1, 2, \dots, n-1, j = 1, 2, \dots, l$ are normally distributed with mean value $\mu_{x_j|q=i}(t)$ and standard deviation $\sigma_{x_j|q=i}(t)$. In practice, the assumption does not always hold. Therefore, we also present an estimation method for the lower bound of the system reliability, using Markov inequality.

According to Markov inequality [46], if X is a nonnegative random variable and $a > 0$, then

$$\Pr(X \geq a) \leq \frac{E(X)}{a}. \tag{19}$$

Using (19), we obtain

$$\Pr(x_j(t) \geq H_j | q = i) \leq \frac{E(x_j(t) | q = i)}{H_j}, j \in \{1, 2, \dots, l\}, i \in \{1, 2, \dots, n-1\}. \tag{20}$$

From (14) and (20), the lower bound of system reliability can, then, be derived:

$$\begin{aligned}
R(t) &= \sum_{i=1}^{n-1} \Pr(q(t) = i) \cdot \prod_{j=1}^l \Pr(x_j(t) < H_j | q(t) = i) \\
&= \sum_{i=1}^{n-1} \Pr(q(t) = i) \cdot \prod_{j=1}^l \left[1 - \Pr(x_j(t) \geq H_j | q(t) = i) \right] \\
&\geq \sum_{i=1}^{n-1} \Pr(q(t) = i) \cdot \prod_{j=1}^l \left[1 - \frac{E(x_j(t) | q(t) = i)}{H_j} \right] \\
&= \sum_{i=1}^{n-1} \mu_i^{(0,0,\dots,0)}(t) \cdot \prod_{j=1}^l \left[1 - \frac{\mu_i^{(m^{*j})}(t)}{H_j} \right], \\
R_i(t) &= \sum_{i=1}^{n-1} \mu_i^{(0,0,\dots,0)}(t) \cdot \prod_{j=1}^l \left[1 - \frac{\mu_i^{(m^{*j})}(t)}{H_j} \right],
\end{aligned} \tag{21}$$

where m^{*j} has the same meaning as in (16).

Results and Discussion

Case 1

System description

The first case study to demonstrate the developed framework is adapted from [20]. A MEMS device is subject to two dependent failure processes, i.e., soft failures caused by wear and debris from shock loads, and hard failures due to spring fracture caused by shock loads [20]. The soft failure is modeled by a continuous degradation process and the hard failure is modeled by a random shock process. Dependence exists among the two processes: the arrival of a shock brings an additional contribution to the degradation process. Failures occur whenever one of the following two events happens:

- the degradation process reaches its threshold, denoted by H ;
- a shock whose magnitude exceeds a critical level, denoted by D , occurs.

Additional assumptions include:

(1) The continuous degradation process follows an SDE.

$$dx(t) = \mu_\beta dt + \sigma_\beta dw_t, x(t) \in \mathbb{R}, \tag{22}$$

where $w_t \in \mathbb{R}$ is a standard Wiener process, μ_β, σ_β are constants and the initial degradation level at $t = 0$ is null.

1 (2) The random shock process is a HPP with intensity λ .

2 (3) The magnitudes of shock loads, denoted by W_i , are i.i.d. random variables following a normal distribution,

3
$$W_i \sim N(\mu_w, \sigma_w^2).$$

4 (4) The arrival of each shock brings a degradation increment d , which is a random variable following a normal
5 distribution $d \sim N(\mu_d, \sigma_d^2)$.

6 SHS formulation

7 A SHS model is constructed in **Fig 2** to describe the behavior of the system. The system has two health states,
8 $q(t) \in \{1, 2\}$. When $q(t) = 1$, the system is subject to the degradation process according to (22). When $q(t) = 2$,
9 the system fails due to hard failure and the degradation level is set to zero, i.e. $x(t) = 0$.

10

11 **Fig 2. State-transition diagram of the SHS for case 1**

12

13 As shown in Fig 2, the initial health state of the system is state 1. The transition rates and reset maps of the SHS
14 are defined as follows:

15
$$\lambda_{11}(q) := \begin{cases} \Phi\left(\frac{D - \mu_w}{\sigma_w}\right) \cdot \lambda & q = 1, \\ 0 & q = 2, \end{cases} \quad (23)$$
$$\lambda_{12}(q) := \begin{cases} \left(1 - \Phi\left(\frac{D - \mu_w}{\sigma_w}\right)\right) \cdot \lambda & q = 1, \\ 0 & q = 2. \end{cases}$$

16

$$\begin{aligned} \phi_{11}(q, x) &:= (1, x + d), \\ \phi_{12}(q, x) &:= (2, 0). \end{aligned} \quad (24)$$

17 In (24), the reset map $\phi_{11}(q, x)$ models the dependency in Assumption (4).

18 Reliability analysis

19 We define the test functions $\psi_i^{(m)}(q, x), i \in \{1, 2\}, m \in \mathbb{R}$, to be:

$$\begin{aligned}\psi_1^{(m)}(q, x) &= \begin{cases} x^m & q=1 \\ 0 & q \neq 1, \end{cases} \\ \psi_2^{(0)}(q, x) &= \begin{cases} 1 & q=2 \\ 0 & q \neq 2. \end{cases}\end{aligned}\quad (25)$$

Since $x(t)=0$ when $q(t)=2$, we only consider the 0-order conditional moment of the degradation at state 2, i.e. $\psi_2^{(0)}(q, x)$. By substituting (22)(23)(24) into (8), the extended generator of the SHS model is:

$$\begin{aligned}(L\psi_1)^{(m)}(q, x) &= \mu_\beta \frac{\partial \psi_1^{(m)}(q, x)}{\partial x} + \frac{1}{2} \sigma_\beta^2 \frac{\partial^2 \psi_1^{(m)}(q, x)}{\partial x^2} \\ &\quad + \lambda_{11}(q) \left(\psi_1^{(1)}(q, x) + d \cdot \psi_1^{(0)}(q, x) \right)^{(m)} \\ &\quad - (\lambda_{11}(q) + \lambda_{12}(q)) \psi_1^{(m)}(q, x), \\ (L\psi_2)^{(0)}(q, x) &= \lambda_{12}(q) \cdot \psi_1^{(0)}(q, x).\end{aligned}\quad (26)$$

According to (7) and (26), the differential equations governing the conditional moments are:

$$\begin{aligned}\frac{d}{dt} \mu_1^{(m)}(t) &= \mu_\beta m \mu_1^{(m-1)}(t) + \frac{1}{2} \sigma_\beta^2 m(m-1) \mu_1^{(m-2)}(t) \\ &\quad + \lambda_{11} \left(\sum_{k=0}^m \binom{m}{k} \mu_1^{(m-k)}(t) E(d^k) \right) - (\lambda_{11} + \lambda_{12}) \mu_1^{(m)}(t), \\ \frac{d}{dt} \mu_2^{(0)}(t) &= \lambda_{12} \mu_1^{(0)}(t),\end{aligned}\quad (27)$$

where $E(d) = \mu_d, E(d^2) = \mu_d^2 + \sigma_d^2$. From (27), we can obtain the following set of differential equations:

$$\begin{bmatrix} \dot{\mu}_1^{(0)} \\ \dot{\mu}_1^{(1)} \\ \dot{\mu}_1^{(2)} \end{bmatrix} = \begin{bmatrix} -\lambda_{12} & 0 & 0 \\ \mu_\beta + \lambda_{11} \mu_d & -\lambda_{12} & 0 \\ \sigma_\beta^2 + \lambda_{11} (\mu_d^2 + \sigma_d^2) & 2\mu_\beta + 2\lambda_{11} \mu_d & -\lambda_{12} \end{bmatrix} \begin{bmatrix} \mu_1^{(0)} \\ \mu_1^{(1)} \\ \mu_1^{(2)} \end{bmatrix}.\quad (28)$$

Since the system must belong to one of the two health modes, it is obvious that

$$\mu_1^{(0)}(t) + \mu_2^{(0)}(t) = 1.\quad (29)$$

From (18) and (21), the estimated system reliability $R_e(t)$ and the lower bound $R_l(t)$ are calculated by

$$R_e(t) = \mu_1^{(0)}(t) \cdot \Phi \left(\frac{H - \mu_1^{(1)}(t) / \mu_1^{(0)}(t)}{\sqrt{\mu_1^{(2)}(t) / \mu_1^{(0)}(t) + (\mu_1^{(1)}(t) / \mu_1^{(0)}(t))^2}} \right),\quad (30)$$

$$R_l(t) = \mu_1^{(0)}(t) \cdot \left[1 - \frac{\mu_1^{(1)}(t)}{H} \right],\quad (31)$$

1 where the conditional moments $\mu_1^{(0)}(t), \mu_1^{(1)}(t), \mu_1^{(2)}(t)$ are obtained by solving the differential equations in (28)
 2 and (29).

3 Numerical calculation

4 A numerical example is conducted with the parameters in Table 1, taken from [20]. To solve the differential
 5 equations in (28) and (29), the solver based on Runge Kutta method in Matlab R2013a is used. In [20], the original
 6 model is simulated using Monte Carlo methods to analyze system reliability. A comparison is made between the
 7 results obtained by the developed methods in this paper and those obtained by Monte Carlo simulation. The sample
 8 size of the Monte Carlo simulation is 10^4 . In Fig 3 (A)-(C), the moments with order 0, 1 and 2 are compared with
 9 simulation results. In Fig 3 (D), the estimated reliability and its lower bound are compared to the results of Monte
 10 Carlo simulation.

11 **Table 1. Parameter values for case 1**

Parameters	Value
H	$0.00125 \mu m^3$
μ_β	$8.4823 \times 10^{-9} \mu m^3$
σ_β	$6.0016 \times 10^{-10} \mu m^3$
μ_d	$1 \times 10^{-4} \mu m^3$
σ_d	$2 \times 10^{-5} \mu m^3$
D	$1.5 GPa$
λ	5×10^{-3}
μ_w	$1.2 GPa$
σ_w	$0.2 GPa$

12
 13 **Fig 3. Comparison of results for case 1.** (A) Comparison on the order 0 moment: $\Pr\{q \neq 2\} = \mu_1^{(0)}(t)$. (B)
 14 Comparison on the order 1 moment: $E(x(t)) = \mu_1^{(1)}(t) + \mu_2^{(1)}(t)$. (C) Comparison on the order 2 moment:
 15 $E(x^2(t)) = \mu_1^{(2)}(t) + \mu_2^{(2)}(t)$. (D) Comparison on the estimated reliability and lower bound for reliability

16
 17 The comparisons show that the moments are accurately predicted by the SHS model. The estimated reliability
 18 by FOSM is consistent with the result by Monte Carlo simulation. The estimated lower bound provides a relatively
 19 conservative reliability estimation. The running time of Monte Carlo simulation is 5788.2 times more than that of the
 20 developed SHS-based approach.

21

1 Case 2

2 System description

3 The second case study to demonstrate the developed framework is adapted from [24]. A MEMS device is subject
4 to two dependent failure processes, i.e., soft failures and hard failures. The soft failure is modeled by a continuous
5 degradation process and the hard failure is modeled by a random shock process. Dependences between the two failure
6 processes exist in the following two aspects: (1) the arrival of each shock brings a degradation increment; (2) the
7 degradation rate increases when the system undergoes a series of shocks. The second type of dependence has been
8 investigated based on four different shock models in [24]: extreme shock, δ shock, m shock, and run shock
9 models. In this section, we apply our framework by considering the first dependence and the second dependence
10 triggered by the extreme shock model. Failure occurs whenever one of the following two events happens:

- 11 ● the degradation process reaches its threshold, denoted by H ;
- 12 ● a shock whose magnitude exceeds a critical level, denoted by D_1 , occurs.

13 Additional assumptions include:

14 (1) Random shocks arrive according to a HPP with intensity λ .

15 (2) The magnitudes of shock loads, denoted by W_i , are i.i.d. random variables following a normal distribution

16 $W_i \sim N(\mu_w, \sigma_w^2)$.

17 (3) The arrival of a shock whose magnitude is less than D_0 would bring a degradation increment d , which is
18 a random variable following a normal distribution $d \sim N(\mu_d, \sigma_d^2)$.

19 (4) The arrival of a shock whose magnitude belongs to $[D_0, D_1)$ would trigger the change of degradation rate.

20 Let J denote the total number of arrival shocks when the trigger shock occurs, and T_j denote the time when
21 the J th shock arrives. Then, the continuous degradation process is modeled by the following SDEs,

22
$$dx(t) = \begin{cases} \mu_{\beta_1} dt + \sigma_{\beta_1} dw_t & \text{for } t < T_j \\ \mu_{\beta_2} dt + \sigma_{\beta_2} dw_t & \text{for } t \geq T_j \end{cases}, x(t) \in \mathbb{R}, \quad (32)$$

23 where $w_t \in \mathbb{R}$ is a standard Wiener process, $\mu_{\beta_1}, \mu_{\beta_2}, \sigma_{\beta_1}, \sigma_{\beta_2}, \mu_{\beta_2} > \mu_{\beta_1}$ are constants, and the initial
24 degradation level at $t = 0$ is null.

1 SHS formulation

2 The SHS concerning this case is described by the state-transition diagram in Fig 4. The system has three health
 3 states, $q(t) \in \{1, 2, 3\}$. When $q(t) = 1$, the system is subject to the degradation at a low-level degradation rate. By
 4 contrast, when $q(t) = 2$, the system degrades at a high-level degradation rate. System's degradation under the first
 5 two health states evolves according to the following SDEs:

$$6 \quad dx(t) = \begin{cases} \mu_{\beta_1} dt + \sigma_{\beta_1} dw_t & \text{if } q(t) = 1 \\ \mu_{\beta_2} dt + \sigma_{\beta_2} dw_t & \text{if } q(t) = 2 \end{cases}, x(t) \in \mathbb{R}. \quad (33)$$

7 When $q(t) = 3$, the system fails due to a hard failure and the degradation level is set to zero, i.e. $x(t) = 0$.

8
 9 **Fig 4. State-transition diagram for the SHS in case 2.**

10
 11 As shown in Fig 4, the initial health state of the system is state 1. The transition rates and reset maps of the
 12 SHS are defined as follows:

$$13 \quad \begin{aligned} \lambda_{11}(q) &:= \begin{cases} P_1 \cdot \lambda & q = 1, \\ 0 & q \neq 1, \end{cases} \\ \lambda_{12}(q) &:= \begin{cases} P_2 \cdot \lambda & q = 1, \\ 0 & q \neq 1, \end{cases} \\ \lambda_{13}(q) &:= \begin{cases} P_3 \cdot \lambda & q = 1, \\ 0 & q \neq 1, \end{cases} \\ \lambda_{22}(q) &:= \begin{cases} (P_1 + P_2) \cdot \lambda & q = 2, \\ 0 & q \neq 2, \end{cases} \\ \lambda_{23}(q) &:= \begin{cases} P_3 \cdot \lambda & q = 2, \\ 0 & q \neq 2. \end{cases} \end{aligned} \quad (34)$$

$$14 \quad \begin{aligned} \phi_{11}(q, x) &:= (1, x + d), \\ \phi_{12}(q, x) &:= (2, x + d), \\ \phi_{13}(q, x) &:= (3, 0), \\ \phi_{22}(q, x) &:= (2, x + d), \\ \phi_{23}(q, x) &:= (3, 0), \end{aligned} \quad (35)$$

15 where P_1, P_2, P_3 are calculated by

$$16 \quad P_1 = \Phi\left(\frac{D_0 - \mu_w}{\sigma_w}\right), P_2 = \Phi\left(\frac{D_1 - \mu_w}{\sigma_w}\right) - \Phi\left(\frac{D_0 - \mu_w}{\sigma_w}\right), P_3 = 1 - \Phi\left(\frac{D_1 - \mu_w}{\sigma_w}\right). \quad (36)$$

1 In (35), the reset maps $\phi_{11}(q, x), \phi_{22}(q, x)$ model the dependency in assumption (3) and the change of system
 2 degradation rate along with the transition from health state $q=1$ to health state $q=2$ model the dependency in
 3 assumption (4).

4 Reliability analysis

5 We define the test functions $\psi_i^{(m)}(q, x), i \in \{1, 2, 3\}, m \in \mathbb{R}$, to be:

$$\begin{aligned} \psi_1^{(m)}(q, x) &= \begin{cases} x^m & q = 1, \\ 0 & q \neq 1, \end{cases} \\ \psi_2^{(m)}(q, x) &= \begin{cases} x^m & q = 2, \\ 0 & q \neq 2, \end{cases} \\ \psi_3^{(0)}(q, x) &= \begin{cases} 1 & q = 3, \\ 0 & q \neq 3. \end{cases} \end{aligned} \quad (37)$$

7 Since $x(t) = 0$ when $q(t) = 3$, we only consider the 0-order conditional moment of the degradation at state 3, i.e.
 8 $\psi_3^{(0)}(q, x)$. By substituting (33)(34)(35) into (8), the extended generator of the SHS is:

$$\begin{aligned} (L\psi_1)^{(m)}(q, x) &= \mu_{\beta_1} \frac{\partial \psi_1^{(m)}(q, x)}{\partial x} + \frac{1}{2} \sigma_{\beta_1}^2 \frac{\partial^2 \psi_1^{(m)}(q, x)}{\partial x^2} + \lambda_{11} (\psi_1^{(1)}(q, x) + d \cdot \psi_1^{(0)}(q, x))^{(m)} \\ &\quad - (\lambda_{11} + \lambda_{12} + \lambda_{13}) \psi_1^{(m)}(q, x), \\ (L\psi_2)^{(m)}(q, x) &= \mu_{\beta_2} \frac{\partial \psi_2^{(m)}(q, x)}{\partial x} + \frac{1}{2} \sigma_{\beta_2}^2 \frac{\partial^2 \psi_2^{(m)}(q, x)}{\partial x^2} + \lambda_{22} (\psi_2^{(1)}(q, x) + d \cdot \psi_2^{(0)}(q, x))^{(m)} \\ &\quad + \lambda_{12} (\psi_1^{(1)}(q, x) + d \cdot \psi_1^{(0)}(q, x))^{(m)} - (\lambda_{22} + \lambda_{23}) \psi_2^{(m)}(q, x), \\ (L\psi_3)^{(0)}(q, x) &= \lambda_{13} \cdot \psi_1^{(0)}(q, x) + \lambda_{23} \cdot \psi_2^{(0)}(q, x). \end{aligned} \quad (38)$$

10 According to (7) and (38), the differential equations governing the conditional moments are:

$$\begin{aligned} \frac{d}{dt} \mu_1^{(m)}(t) &= \mu_{\beta_1} m \mu_1^{(m-1)}(t) + \frac{1}{2} \sigma_{\beta_1}^2 m(m-1) \mu_1^{(m-2)}(t) \\ &\quad + \lambda_{11} \left(\sum_{k=0}^m \binom{m}{k} \mu_1^{(m-k)}(t) E(d^k) \right) - (\lambda_{11} + \lambda_{12} + \lambda_{13}) \mu_1^{(m)}(t), \\ \frac{d}{dt} \mu_2^{(m)}(t) &= \mu_{\beta_2} m \mu_2^{(m-1)}(t) + \frac{1}{2} \sigma_{\beta_2}^2 m(m-1) \mu_2^{(m-2)}(t) + \lambda_{22} \left(\sum_{k=0}^m \binom{m}{k} \mu_2^{(m-k)}(t) E(d^k) \right) \\ &\quad + \lambda_{12} \left(\sum_{k=0}^m \binom{m}{k} \mu_1^{(m-k)}(t) E(d^k) \right) - (\lambda_{22} + \lambda_{23}) \mu_2^{(m)}(t), \\ \frac{d}{dt} \mu_3^{(0)}(t) &= \lambda_{13} \mu_1^{(0)}(t) + \lambda_{23} \mu_2^{(0)}(t), \end{aligned} \quad (39)$$

12 where $E(d) = \mu_d, E(d^2) = \mu_d^2 + \sigma_d^2$. From (39), we can obtain the following set of differential equations:

$$\begin{matrix} 1 \\ 2 \\ 3 \\ 4 \\ 5 \\ 6 \\ 7 \\ 8 \\ 9 \\ 10 \\ 11 \\ 12 \\ 13 \\ 14 \\ 15 \\ 16 \end{matrix}
\begin{matrix} \dot{\mu}_1^{(0)} \\ \dot{\mu}_2^{(0)} \\ \dot{\mu}_1^{(1)} \\ \dot{\mu}_2^{(1)} \\ \dot{\mu}_1^{(2)} \\ \dot{\mu}_2^{(2)} \end{matrix}
=
\begin{bmatrix}
-\lambda_{12} - \lambda_{13} & 0 & 0 & 0 & 0 & 0 \\
\lambda_{12} & -\lambda_{23} & 0 & 0 & 0 & 0 \\
\mu_{\beta_1} + \lambda_{11}\mu_d & 0 & -\lambda_{12} - \lambda_{13} & 0 & 0 & 0 \\
\lambda_{12}\mu_d & \mu_{\beta_2} + \lambda_{22}\mu_d & \lambda_{12} & -\lambda_{23} & 0 & 0 \\
\sigma_{\beta_1}^2 + \lambda_{11}(\mu_d^2 + \sigma_d^2) & 0 & 2\mu_{\beta_1} + 2\lambda_{11}\mu_d & 0 & -\lambda_{12} - \lambda_{13} & 0 \\
\lambda_{12}(\mu_d^2 + \sigma_d^2) & \sigma_{\beta_2}^2 + \lambda_{22}(\mu_d^2 + \sigma_d^2) & 2\lambda_{12}\mu_d & 2\mu_{\beta_2} + 2\lambda_{22}\mu_d & \lambda_{12} & -\lambda_{23}
\end{bmatrix}
\begin{bmatrix} \mu_1^{(0)} \\ \mu_2^{(0)} \\ \mu_1^{(1)} \\ \mu_2^{(1)} \\ \mu_1^{(2)} \\ \mu_2^{(2)} \end{bmatrix}. \quad (40)$$

Since the system must belong to one of the three health modes, it is clear that

$$\mu_1^{(0)}(t) + \mu_2^{(0)}(t) + \mu_3^{(0)}(t) = 1. \quad (41)$$

From (18) and (21), the estimated system reliability $R_e(t)$ and the lower boundary $R_l(t)$ are calculated by

$$R_e(t) = \sum_{i=1}^2 \mu_i^{(0)}(t) \cdot \Phi \left(\frac{H - \mu_i^{(1)}(t) / \mu_i^{(0)}(t)}{\sqrt{\mu_i^{(2)}(t) / \mu_i^{(0)}(t) + (\mu_i^{(1)}(t) / \mu_i^{(0)}(t))^2}} \right), \quad (42)$$

$$R_l(t) = \sum_{i=1}^2 \mu_i^{(0)}(t) \cdot \left[1 - \frac{\mu_i^{(1)}(t)}{H} \right]. \quad (43)$$

where the conditional moments $\mu_1^{(0)}(t), \mu_1^{(1)}(t), \mu_1^{(2)}(t), \mu_2^{(0)}(t), \mu_2^{(1)}(t), \mu_2^{(2)}(t)$ are obtained by solving the differential equations (40) and (41).

Numerical calculation

A numerical example is conducted using the parameters in Table 2, taken from [24]. To solve the differential equations (40) and (41), the solver based on Runge Kutta method in Matlab R2013a is used. In [24], the original model is simulated by Monte Carlo to compute system reliability. A comparison is made between the results obtained by the developed methods in this paper and those obtained by Monte Carlo simulation. The sample size of the Monte Carlo simulation is 10^4 . In Fig 5 (A)-(C), the moments with order 0,1 and 2 are compared with the simulation results. In Fig 5 (D), the estimated reliability and its lower bound are compared to the results of Monte Carlo simulation.

Table 2. Parameter values for case 2

Parameters	Value
H	$0.00125 \mu m^3$
μ_{β_1}	$8.4823 \times 10^{-9} \mu m^3$
μ_{β_2}	$10.9646 \times 10^{-9} \mu m^3$
σ_{β_1}	$6.0016 \times 10^{-10} \mu m^3$
σ_{β_2}	$6.0846 \times 10^{-10} \mu m^3$
μ_d	$1 \times 10^{-4} \mu m^3$

σ_d	$2 \times 10^{-5} \mu m^3$
D_1	$1.5 GPa$
D_0	$1.2 GPa$
λ	5×10^{-3}
μ_w	$1.2 GPa$
σ_w	$0.2 GPa$

1

2 **Fig 5. Comparison of results obtained by the SHS model and those by Monte Carlo simulation for case 2.** (A)

3 Comparison on the order 0 moment: $\Pr\{q \neq 3\} = \mu_1^{(0)}(t) + \mu_2^{(0)}(t)$. (B) Comparison on the order 1 moment:

4 $E(x(t)) = \mu_1^{(1)}(t) + \mu_2^{(1)}(t) + \mu_3^{(1)}(t)$. (C) Comparison on the order 2 moment:

5 $E(x^2(t)) = \mu_1^{(2)}(t) + \mu_2^{(2)}(t) + \mu_3^{(2)}(t)$. (D) Comparison on the estimated reliability and lower bound for reliability.

6

7 The comparisons show that the moments are accurately predicted by the SHS model. The estimated reliability
8 by FOSM is consistent with the result by Monte Carlo simulation. The estimated lower bound provides a relatively
9 conservative reliability estimation. Besides, the running time of Monte Carlo simulation is 1203.8 times more than
10 that of the developed SHS-based approach.

11

12 **Case 3**

13 **System descriptions**

14 The third case study to demonstrate the developed framework is adapted from [25]. The failure behavior of bus
15 tires is modeled by two dependent failure processes, i.e. soft failures caused by wear and hard failures of seven modes
16 due to traumatic shocks. The soft failure is modeled by a continuous degradation process and the hard failure is
17 modeled by a random shock process. Dependence exists among the two processes, that is, the probability that a
18 traumatic shock occurs depends on the degradation level. Failures occur whenever one of the following two events
19 happens:

- 20 ● the degradation process reaches its threshold, denoted by H ;
- 21 ● a traumatic shock following a Cox process [47] with intensity $\lambda(x)$ occurs.

22 Additional assumptions include:

- 23 (1) The continuous degradation process is modeled by an SDE.

$$dx(t) = \mu_\beta dt + \sigma_\beta dw_t, x(t) \in \mathbb{R}, \quad (44)$$

where $w_t \in \mathbb{R}$ is a standard Wiener process, μ_β, σ_β are constants and the initial degradation at $t = 0$ is denoted by x_0 .

(2) Random shocks arrive according to a Cox process with intensity function $\lambda(x) = \delta + \alpha x^k, k \in \mathbb{R}$, where δ and α are constants. In this paper, we let $k = 1$. Then, the intensity function is determined by

$$\lambda(x) = \delta + \alpha x. \quad (45)$$

SHS formulation

A SHS model is constructed in Fig 6 to describe the behavior of the system. The system has two health states, $q(t) \in \{1, 2\}$. When $q(t) = 1$, the system is subject to the degradation process and degrades according to (44). When $q(t) = 2$, the system fails due to a hard failure, and the degradation level is set to zero, i.e. $x(t) = 0$.

Fig 6. State-transition diagram for the SHS in case 3.

As shown in Fig 6, the initial state of the system is state 1. The transition rates and reset maps of the SHS are defined as follows:

$$\lambda_{12}(q, x) := \begin{cases} \delta + \alpha x & q = 1, \\ 0 & q \neq 1, \end{cases} \quad (46)$$

$$\phi_{12}(q, x) := (2, 0). \quad (47)$$

Reliability analysis

We define the test functions $\psi_i^{(m)}(q, x), i \in \{1, 2\}, m \in \mathbb{R}$, to be:

$$\begin{aligned} \psi_1^{(m)}(q, x) &= \begin{cases} x^m & q = 1, \\ 0 & q \neq 1, \end{cases} \\ \psi_2^{(0)}(q, x) &= \begin{cases} 1 & q = 2, \\ 0 & q \neq 2. \end{cases} \end{aligned} \quad (48)$$

Since $x(t) = 0$ when $q(t) = 2$, we only consider the 0-order conditional moment of the degradation at state 2, i.e.

$\psi_2^{(0)}(q, x)$. By substituting (44)(46)(47) into (8), the extended generator of the SHS is:

$$\begin{aligned}
(L\psi_1)^{(m)}(q, x) &= \mu_\beta \frac{\partial \psi_1^{(m)}(q, x)}{\partial x} + \frac{1}{2} \sigma_\beta^2 \frac{\partial^2 \psi_1^{(m)}(q, x)}{\partial x^2} - (\delta + \alpha x) \cdot \psi_1^{(m)}(q, x), \\
(L\psi_2)^{(0)}(q, x) &= (\delta + \alpha x) \cdot \psi_1^{(0)}(q, x).
\end{aligned} \tag{49}$$

According to (7) and (49), the differential equations governing the conditional moments are:

$$\begin{aligned}
\frac{d}{dt} \mu_1^{(m)}(t) &= \mu_\beta m \mu_1^{(m-1)}(t) + \frac{1}{2} \sigma_\beta^2 m(m-1) \mu_1^{(m-2)}(t) - \delta \mu_1^{(m)}(t) - \alpha \mu_1^{(m+1)}(t), \\
\frac{d}{dt} \mu_2^{(0)}(t) &= \delta \mu_1^{(0)}(t) + \alpha \mu_1^{(1)}(t).
\end{aligned} \tag{50}$$

From (50), we can obtain the following set of differential equations:

$$\begin{bmatrix} \dot{\mu}_1^{(0)} \\ \dot{\mu}_1^{(1)} \\ \dot{\mu}_1^{(2)} \end{bmatrix} = \begin{bmatrix} -\delta & -\alpha & 0 \\ \mu_\beta & -\delta & -\alpha \\ \sigma_\beta^2 & 2\mu_\beta & -\delta \end{bmatrix} \begin{bmatrix} \mu_1^{(0)} \\ \mu_1^{(1)} \\ \mu_1^{(2)} \end{bmatrix} + \begin{bmatrix} 0 \\ 0 \\ -\alpha \end{bmatrix} \cdot \mu_1^{(3)}. \tag{51}$$

Since the system must belong to one of the two health modes, it is obvious that

$$\mu_1^{(0)}(t) + \mu_2^{(0)}(t) = 1. \tag{52}$$

Unlike the differential equations obtained in case 1 and case 2, the dynamics of $\mu_1^{(0)}, \mu_1^{(1)}, \mu_1^{(2)}$ in this case is related to a high-order conditional moment $\mu_1^{(3)}$, so that (51) cannot be solved directly. To deal with this situation, an approximate truncation method is developed in [36] to provide an approximate function of the involved high-order conditional moments using the low-order conditional moments. Adopting the truncation method, we have the approximate function of $\mu_1^{(3)}$ in the following form:

$$\mu_1^{(3)} \approx \varphi(\mu_1^{(0)}, \mu_1^{(1)}, \mu_1^{(2)}) = \frac{\mu_1^{(0)} \cdot (\mu_1^{(2)})^3}{(\mu_1^{(1)})^3}. \tag{53}$$

Thus, (51) is approximated by:

$$\begin{bmatrix} \dot{\mu}_1^{(0)} \\ \dot{\mu}_1^{(1)} \\ \dot{\mu}_1^{(2)} \end{bmatrix} = \begin{bmatrix} -\delta & -\alpha & 0 \\ \mu_\beta & -\delta & -\alpha \\ \sigma_\beta^2 & 2\mu_\beta & -\delta \end{bmatrix} \begin{bmatrix} \mu_1^{(0)} \\ \mu_1^{(1)} \\ \mu_1^{(2)} \end{bmatrix} + \begin{bmatrix} 0 \\ 0 \\ -\alpha \end{bmatrix} \cdot \frac{\mu_1^{(0)} \cdot (\mu_1^{(2)})^3}{(\mu_1^{(1)})^3}. \tag{54}$$

From (18) and (21), the estimated system reliability $R_e(t)$ and the lower bound $R_l(t)$ are calculated by

$$R_e(t) = \mu_1^{(0)}(t) \cdot \Phi \left(\frac{H - \mu_1^{(1)}(t)/\mu_1^{(0)}(t)}{\sqrt{\mu_1^{(2)}(t)/\mu_1^{(0)}(t) + (\mu_1^{(1)}(t)/\mu_1^{(0)}(t))^2}} \right), \tag{55}$$

$$R_t(t) = \mu_1^{(0)}(t) \cdot \left[1 - \frac{\mu_1^{(1)}(t)}{H} \right]. \quad (56)$$

where the conditional moments $\mu_1^{(0)}(t), \mu_1^{(1)}(t), \mu_1^{(2)}(t)$ are obtained by solving the differential equations (52) and (54).

Numerical calculation

A numerical example is conducted using the parameters in Table 3, assumed arbitrarily by hypothesis for the purpose of illustration. To solve the differential equations in (52) and (54), the solver based on Runge Kutta method in Matlab 2013a is used. On the other hand, based on the properties of Cox process, the conditional moments can also be written as (57)-(58) below:

$$\begin{aligned} \mu_1^{(0)}(t) &= P\{q=1\} \\ &= E \exp\left(-\int_0^t \lambda(x(\tau)) d\tau\right) \\ &= E \exp\left(-\int_0^t (\delta + \alpha x(\tau)) d\tau\right), \end{aligned}$$

$$\begin{aligned} \mu_1^{(1)}(t) &= E(x|q=1) \cdot P\{q=1\} \\ &= (x_0 + \mu_\beta t) \cdot E \exp\left(-\int_0^t (\delta + \alpha x(\tau)) d\tau\right), \end{aligned} \quad (57)$$

$$\begin{aligned} \mu_1^{(2)}(t) &= E(x^2|q=1) \cdot P\{q=1\} \\ &= \left[(x_0 + \mu_\beta t)^2 + \sigma_\beta^2 t \right] \cdot E \exp\left(-\int_0^t (\delta + \alpha x(\tau)) d\tau\right). \end{aligned}$$

$$\begin{aligned} R(t) &= P\{x < H | q=1\} \cdot P\{q=1\} \\ &= \Phi\left(\frac{H - (x_0 + \mu_\beta t)}{\sigma_\beta \sqrt{t}}\right) \cdot E \exp\left(-\int_0^t (\delta + \alpha x(\tau)) d\tau\right), \end{aligned} \quad (58)$$

where x_0 denotes the initial degradation magnitude and $\Phi(\cdot)$ represents the standard normal distribution function.

A comparison is made between the results obtained by the developed methods in this paper and those obtained by solving (57)-(58) through Monte Carlo simulation. The sample size of the Monte Carlo simulation is 10^3 . In Fig 7 (A)-(C), the moments with order 0,1 and 2 are compared with those obtained by (57). In Fig 7 (D), the estimated reliability and its lower bound are compared to the results calculated by (58). The comparisons show that the moments and system reliability are accurately predicted by the SHS model.

1 **Table 3. Parameter values for case 3**

Parameters	Value
H	$7.5 \mu m^3$
μ_β	$1 \times 10^{-4} \mu m^3$
σ_β	$1 \times 10^{-5} \mu m^3$
δ	2.5×10^{-5}
α	1×10^{-4}
x_0	$1 \times 10^{-4} \mu m^3$

2
3 **Fig 7. Comparison of results obtained by the SHS model and those by analytic expressions for case 3. (A)**

4 Comparison on the order 0 moment: $\Pr\{q \neq 2\} = \mu_1^{(0)}(t)$. (B) Comparison on the order 1 moment:

5 $E(x(t)) = \mu_1^{(1)}(t) + \mu_2^{(1)}(t)$. (C) Comparison on the order 2 moment: $E(x^2(t)) = \mu_1^{(2)}(t) + \mu_2^{(2)}(t)$. (D)

6 Comparison on the estimated reliability and lower bound for reliability.

7
8 **Conclusions**

9 In this paper, a SHS-based modeling framework is developed for the reliability modeling and analysis of
10 dependent failure processes, where degradation processes and random shock processes compete to cause system
11 failure and dependencies exist among these processes. In the developed model, the degradation process is modeled
12 by SDEs and the shock process is characterized by transitions among the system health states. The dependencies
13 among the two processes are modeled within the structure of the SHS model by the reset map, transition rates etc.
14 The conditional moments for the state variables in the developed SHS model are calculated by deriving and solving
15 a set of differential equations based on Dynkin's formula. Using these conditional moments, a reliability analysis
16 method is developed to estimate the system reliability and its lower bound. Three case studies are conducted to
17 demonstrate the developed methods. Comparisons to Monte Carlo simulations show that the developed method can
18 achieve accurate reliability analysis results, while requiring much less computations than Monte Carlo simulations.

19 To apply the developed model in practice, the parameter values, such as the parameters in the SDEs that model
20 the degradation processes, the transition rates that model the random shock processes, and the parameters in the reset
21 maps that describe the dependency, need to be set based on historical data or expert judgments. Epistemic uncertainty
22 might present when setting values for the parameters. Another source of epistemic (model) uncertainty is derived
23 from the assumptions made for the present model. Treatment and calculation of epistemic uncertainty is an interesting

1 problem that deserves further investigations.

2

3 **Acknowledgements**

4 This work has been performed within the initiative of the Center for Resilience and Safety of Critical
5 Infrastructures (CRESCI, <http://cresci.cn>).

6

7 **References**

- 8 1. Jiang L, Feng Q, Coit DW (2015) Modeling zoned shock effects on stochastic degradation in dependent failure
9 processes. *IIE Transactions* 47: 460-470.
- 10 2. Li W, Pham H (2005) Reliability modeling of multi-state degraded systems with multi-competing failures and random
11 shocks. *IEEE Transactions on Reliability* 54: 297-303.
- 12 3. Guo C, Wang W, Guo B, Si X (2013) A maintenance optimization model for mission-oriented systems based on
13 Wiener degradation. *Reliability Engineering & System Safety* 111: 183-194.
- 14 4. Wang W, Carr M, Xu W, Kobbacy K (2011) A model for residual life prediction based on Brownian motion with an
15 adaptive drift. *Microelectronics Reliability* 51: 285-293.
- 16 5. Lawless J, Crowder M (2004) Covariates and Random Effects in a Gamma Process Model with Application to
17 Degradation and Failure. *Lifetime Data Analysis* 10: 213-227.
- 18 6. Kuniewski SP, van der Weide JAM, van Noortwijk JM (2009) Sampling inspection for the evaluation of time-
19 dependent reliability of deteriorating systems under imperfect defect detection. *Reliability Engineering & System Safety*
20 94: 1480-1490.
- 21 7. Castro IT, Barros A, Grall A (2011) Age-based preventive maintenance for passive components submitted to stress
22 corrosion cracking. *Mathematical and Computer Modelling* 54: 598-609.
- 23 8. Pan D, Liu J-B, Cao J (2016) Remaining useful life estimation using an inverse Gaussian degradation model.
24 *Neurocomputing* 185: 64-72.
- 25 9. Peng W, Li YF, Yang YJ, Mi J, Huang HZ (2015) Leveraging Degradation Testing and Condition Monitoring for Field
26 Reliability Analysis With Time-Varying Operating Missions. *IEEE Transactions on Reliability* 64: 1367-1382.
- 27 10. Ye Z, Chen N (2014) The Inverse Gaussian Process as a Degradation Model. *Technometrics* 56: 302-311.
- 28 11. Lin YH, Li YF, Zio E (2015) Integrating Random Shocks Into Multi-State Physics Models of Degradation Processes
29 for Component Reliability Assessment. *IEEE Transactions on Reliability* 64: 154-166.
- 30 12. Lemoine AJ, Wenocur ML (1985) On failure modeling. *Naval Research Logistics Quarterly* 32: 497-508.
- 31 13. Klutke GA, Yoonjung Y (2002) The availability of inspected systems subject to shocks and graceful degradation.
32 *IEEE Transactions on Reliability* 51: 371-374.
- 33 14. Huynh KT, Barros A, B érenguer C, Castro IT (2011) A periodic inspection and replacement policy for systems
34 subject to competing failure modes due to degradation and traumatic events. *Reliability Engineering & System Safety* 96:
35 497-508.
- 36 15. Huynh KT, Castro IT, Barros A, B érenguer C (2012) Modeling age-based maintenance strategies with minimal
37 repairs for systems subject to competing failure modes due to degradation and shocks. *European Journal of Operational*
38 *Research* 218: 140-151.
- 39 16. Fan M, Zeng Z, Kang R, Zio E (2015) Reliability modeling of a spool valve considering dependencies among failure
40 mechanisms. *Safety and Reliability of Complex Engineered Systems - Proceedings of the 25th European Safety and*
41 *Reliability Conference, ESREL 2015*. pp. 4407-4411.
- 42 17. Zeng Z, Kang R, Chen Y (2016) Using PoF models to predict system reliability considering failure collaboration.
43 *Chinese Journal of Aeronautics* 29: 1294-1301.
- 44 18. Jin G, Matthews D, Fan Y, Liu Q (2013) Physics of failure-based degradation modeling and lifetime prediction of the
45 momentum wheel in a dynamic covariate environment. *Engineering Failure Analysis* 28: 222-240.
- 46 19. McPherson JW (2013) *Reliability physics and engineering: time-to-failure modeling*: Springer Science & Business
47 Media.
- 48 20. Peng H, Feng Q, Coit DW (2010) *Reliability and maintenance modeling for systems subject to multiple dependent*

- 1 competing failure processes. IIE Transactions 43: 12-22.
- 2 21. Wang YP, Pham H (2011) A Multi-Objective Optimization of Imperfect Preventive Maintenance Policy for
3 Dependent Competing Risk Systems With Hidden Failure. IEEE Transactions on Reliability 60: 770-781.
- 4 22. Cha JI, Finkelstein M (2011) On new classes of extreme shock models and some generalizations. Journal of Applied
5 Probability 48: 258-270.
- 6 23. Jiang L, Feng Q, Coit DW (2012) Reliability and Maintenance Modeling for Dependent Competing Failure Processes
7 With Shifting Failure Thresholds. IEEE Transactions on Reliability 61: 932-948.
- 8 24. Rafiee K, Feng Q, Coit DW (2014) Reliability modeling for dependent competing failure processes with changing
9 degradation rate. IIE Transactions 46: 483-496.
- 10 25. Bagdonavicius V, Bikelis A, Kazakevicius V (2004) Statistical analysis of linear degradation and failure time data
11 with multiple failure modes. Lifetime Data Analysis 10: 65-81.
- 12 26. Fan J, Ghurye SG, Levine RA (2000) Multicomponent lifetime distributions in the presence of ageing. Journal of
13 Applied Probability 37: 521-533.
- 14 27. Ye ZS, Tang LC, Xu HY (2011) A Distribution-Based Systems Reliability Model Under Extreme Shocks and Natural
15 Degradation. IEEE Transactions on Reliability 60: 246-256.
- 16 28. Zio E (2013) The Monte Carlo Simulation Method for System Reliability and Risk Analysis: Springer London.
- 17 29. Pola G, Bujorianu M, Lygeros J, Benedetto M. Stochastic hybrid models: An overview; 2003. pp. 45-50.
- 18 30. Abate A, Prandini M, Lygeros J, Sastry S (2008) Probabilistic reachability and safety for controlled discrete time
19 stochastic hybrid systems. Automatica 44: 2724-2734.
- 20 31. Yang H, Shu H, Wang Z, Alsaadi FE, Hayat T (2016) Almost sure state estimation with -type performance constraints
21 for nonlinear hybrid stochastic systems. Nonlinear Analysis: Hybrid Systems 19: 26-37.
- 22 32. Teel AR, Subbaraman A, Sferlazza A (2014) Stability analysis for stochastic hybrid systems: A survey. Automatica
23 50: 2435-2456.
- 24 33. Dhople SV, DeVille L, Dom ínguez-Garc ía AD (2014) A Stochastic Hybrid Systems framework for analysis of
25 Markov reward models. Reliability Engineering & System Safety 123: 158-170.
- 26 34. Hespanha JP (2004) Stochastic Hybrid Systems: Application to Communication Networks. In: Alur R, Pappas GJ,
27 editors. Hybrid Systems: Computation and Control. Berlin, Heidelberg: Springer Berlin Heidelberg. pp. 387-401.
- 28 35. Hespanha JP (2005) A model for stochastic hybrid systems with application to communication networks. Nonlinear
29 Analysis: Theory, Methods & Applications 62: 1353-1383.
- 30 36. Hespanha JP (2006) Modelling and analysis of stochastic hybrid systems. IEE Proceedings - Control Theory and
31 Applications 153: 520-535.
- 32 37. Lin YH, Li YF, Zio E (2015) Fuzzy Reliability Assessment of Systems With Multiple-Dependent Competing
33 Degradation Processes. Ieee Transactions on Fuzzy Systems 23: 1428-1438.
- 34 38. Castañeda GAP, Aubry J-F, Brnzei N (2011) Stochastic hybrid automata model for dynamic reliability assessment.
35 Proceedings of the Institution of Mechanical Engineers, Part O: Journal of Risk and Reliability 225: 28-41.
- 36 39. Chiacchio F, D'Urso D, Manno G, Compagno L (2016) Stochastic hybrid automaton model of a multi-state system
37 with aging: Reliability assessment and design consequences. Reliability Engineering & System Safety 149: 1-13.
- 38 40. Siu N (1994) Risk assessment for dynamic systems: An overview. Reliability Engineering & System Safety 43: 43-
39 73.
- 40 41. Labeau PE, Smidts C, Swaminathan S (2000) Dynamic reliability: towards an integrated platform for probabilistic
41 risk assessment. Reliability Engineering & System Safety 68: 219-254.
- 42 42. Nilsen T, Aven T (2003) Models and model uncertainty in the context of risk analysis. Reliability Engineering &
43 System Safety 79: 309-317.
- 44 43. Bjerga T, Aven T, Zio E (2014) An illustration of the use of an approach for treating model uncertainties in risk
45 assessment. Reliability Engineering & System Safety 125: 46-53.
- 46 44. Kang R, Zhang Q, Zeng Z, Zio E, Li X (2016) Measuring reliability under epistemic uncertainty: Review on non-
47 probabilistic reliability metrics. Chinese Journal of Aeronautics 29: 571-579.
- 48 45. Zhao YG, Ono T (2001) Moment methods for structural reliability. Structural Safety 23: 47-75.
- 49 46. Pishro-Nik H (2014) Introduction to Probability, Statistics, and Random Processes: Kappa Research, LLC.
- 50 47. Lando D (1998) On cox processes and credit risky securities. Review of Derivatives Research 2: 99-120.
- 51