

Design of an Industrial Wooden Robot

Lila Kaci, Clément Boudaud, Sébastien Briot, Philippe Martinet

▶ To cite this version:

Lila Kaci, Clément Boudaud, Sébastien Briot, Philippe Martinet. Design of an Industrial Wooden Robot. 6èmes Journées scientifiques du GDR Sciences du Bois, Nov 2017, Nantes, France. 2017. hal-01646725

HAL Id: hal-01646725 https://hal.science/hal-01646725

Submitted on 24 Jun 2019

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

LS2N/ESN – LIMBHA/ESB

Design of an Industrial Wooden Robot


Lila KACI^{1,2}, Clément BOUDAUD³, Sébastien BRIOT¹ and Philippe MARTINET^{1,2}

¹ Laboratoire des Sciences du Numérique de Nantes (LS2N), UMR CNRS 6004 ² École Centrale de Nantes (ECN), France ³ École Supérieure du Bois (ESB), France

Why a project on the design of an industrial wooden robot?

This idea comes from the actual contest of climate change. The *Climate* **Change Mitigation (CCM)** has become a priority in Europe. To deal with this huge challenge, the European Council adopted new environmental targets for EU in 2008, the so-called « 20-20-20» targets, in which the first two targets are :


- To reduce emissions of Greenhouse Gases y 20% by 2020, and Ο
- **To increase energy efficiency** to save 20% energy consumption by Ο



RobEcolo

in France is due to nuclear power plants (releasing much less CO₂ than other types of plants)

Fig. 1 Environmental impact of a Kuka KR 270 robot during is total life







Fig. 3 Bending tests to define the mechanical properties of acetylated wood [3]




Passive Revolute Joint

- **Deterministic Elastostatic and Elastodynamic** 3. Models of a Five-bar Mechanism
- Sensitivity Analysis [3] => Monte-Carlo 4. Method


Fig. 4 Experimental setups to validate the theoretical models

using a wooden five-bar mechanism mockup



15 configurations in the workspace


def [mm]



6 configurations in the workspace

software


Good Correlation between models and experiments => Error < 10% **Design Process and Final Prototype**



Reliable Topology Optimization

- $E(\|\mathbf{u}_{e}\|) + k \sigma(\|\mathbf{u}_{e}\|) \le u_{max}$
- E(.): expectation operator
- $\sigma(.)$: Standard deviation operator
- k: a positive real
- **u**_e: deformation vector at given nodes, for a fixed nodal loading **f**

CAD Model of a Wooden Parallel Robot



Final Prototype



[1] Fizians Environnement "Eco-design of two types of robots: KUKA 270 and IRSbot-2", 2014 [2] L. Kaci et al. "Control-based Design of a Five-bar Mechanism". (EuCoMeS2016), September 2016 Nantes, France. [3] L. Kaci et al. "Elastostatic Modelling of a Wooden Parallel Robot," (CK2017), May 22-24, 2017 Futuroscope-Poitiers, France.

