

# A Branch&Cut algorithm for the Multi-Trip Vehicle Routing Problem with Time Windows

Diego Cattaruzza, Paolo Gianessi

## ▶ To cite this version:

Diego Cattaruzza, Paolo Gianessi. A Branch&Cut algorithm for the Multi-Trip Vehicle Routing Problem with Time Windows. ROADEF2017 - 18ème Conférence de la Société Française de Recherche Opérationnelle et d'Aide à la Décision, Feb 2017, Metz, France. hal-01651581

# HAL Id: hal-01651581 https://hal.science/hal-01651581v1

Submitted on 29 Nov 2017

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

# A Branch&Cut algorithm for the Multi-Trip Vehicle Routing Problem with Time Windows

Diego Cattaruzza<sup>1</sup>, Paolo Gianessi<sup>2</sup>

 <sup>1</sup> Université Lille, CNRS, Centrale Lille, Inria, UMR 9189 - CRIStAL Centre de Recherche en Informatique Signal et Automatique de Lille F-59000 Lille, France diego.cattaruzza@ec-lille.fr
<sup>2</sup> Mines Saint-Étienne, FAYOL-EMSE, LIMOS, UMR CNRS 6158, France paolo.gianessi@emse.fr

Keywords : Multi-Trip VRP, Time Windows, Branch & Cut, Exact Methods

### 1 Introduction

The Vehicle Routing Problem with Time Windows (VRPTW) deals with the determination of the trips of a homogeneous fleet of capacitated vehicles based at a central depot to deliver a set of customers, while complying delivery time intervals imposed by these latter. The Multi-Trip VRP with Time Windows (MTVRPTW) goes one step further by allowing vehicles to perform not one but a sequence of trips, called a journey, under a maximum overall shift length constraint. Moreover, the time to load a vehicle is service-dependent, i.e. proportional to the total service time of the subsequent trip. Hence, the MTVRPTW consists in finding a set of back-to-depot delivery trips and assigning them to vehicles so that the total travelled distance is minimized and :

▶ each customer is visited exactly once and service starts within the associated time window;

▶ vehicle capacity is respected;

▶ trips assigned to one vehicle do not overlap in time and do not exceed a maximum duration.

#### 2 Short literature review

Recently, MTVRPTW has got the attention of scholars mostly due to its application to city logistics (see [4]). However, as far as we are aware of, the literature of exact methods is still scarce. In [6], an algorithm based on the Branch & Price paradigm is proposed which can solve most of the adapted Solomon instances (derived from the benchmark VRPTW instances first proposed in [8]) with 25 customers and 2 vehicles. In [5], the same authors study a variant where the length of a trip is limited. Another Branch & Price algorithm is proposed in [1], where another variant of the problem is tackled where the visit of customers is not mandatory but rewarded with a profit. Finally, [7] proposes an exact algorithm for a variant with both profits and limited trip duration.

### 3 Solution method

We propose a two-index MILP formulation for the MTVRPTW that makes use of base and replenishment arcs. The former model the direct connection between two nodes, whereas the latter imply a reload operation between two client nodes. Replenishment arcs, which have been used e.g. in [3], allow to represent a journey as an elementary path with both endpoints in the

| instance      | $\%_r$ | $T_r$ | $T_t$ |
|---------------|--------|-------|-------|
| C201_2_25     | 1.41   | 1.8   | 7.5   |
| $C202\_2\_25$ | 2.30   | 6.5   | 616.8 |
| $C203\_2\_25$ | 0.91   | 7.3   | 930.1 |
| $C204\_2\_25$ | 0.22   | 9.3   | 100.6 |
| $C205\_2\_25$ | 4.35   | 2.7   | 71.3  |
| $C206_2_{25}$ | 2.22   | 4.1   | 221.3 |
| $C207_2_25$   | 0.08   | 4.5   | 3.2   |
| $C208\_2\_25$ | 0.73   | 3.9   | 379.9 |
| average       | 1.53   | 5.0   | 291.3 |

TAB. 1 – Results on clustered instances with 25 customers and 2 vehicles.

depot. This ensures the connectivity of journeys by separating Subtour Elimination Constraints on a transformation of the graph. Further sets of two-indexed variables impose time windows, shift length, and service-dependent loading time constraints. The use of classical capacity constraints to enforce the load limit on vehicles leads to a Branch & Cut algorithm. In order to tighten the lower bound obtained from the linear relaxation of the proposed MILP model, we consider connectivity and path valid inequalities. The latter are an adaptation to our case of those found in [2] : an exact procedure based on LP is proposed to efficiently separate them.

#### 4 Computational results

Tests have been conducted on a set of 54 adapted Solomon instances with 25 to 50 customers and a fleet of 2 to 4 vehicles. The algorithm is coded in C++ and makes use of CPLEX 12.6.1. Experiments are run on a Intel Core i7-5500U 2.4 Ghz machine with 15.56Gb RAM. We allocate 30s to solve the root node and extra 1200s after branching on it.

Table 1 shows the results on the class C (clustered) instances of of [4] with 25 customers. For these instances, the optimal value (which is known from [6]) is always found.  $T_r$  and  $\mathcal{N}_r$  report the root computation time and the gap of the root lower bound with respect to the optimal value, while  $T_t$  is the additional running time to explore the Branch & Bound tree.

### References

- [1] N.Azi, M.Gendreau, J.-Y.Potvin, An exact algorithm for a vehicle routing problem with time windows and multiple use of vehicles. European Journal of Operational Research, 202(3):756–763, 2010.
- J.F.Bard, G.Kontoravdis, G.Yu, A Branch-and-Cut Procedure for the Vehicle Routing Problem with Time Windows. Transportation Science, 36(2): 250–269, 2002.
- [3] O.J.Smith, N.Boland, H.Waterer, Solving shortest path problems with a weight constraint and replenishment arcs. Computers & Operations Research, 39(5): 964–984, 2012.
- [4] D.Cattaruzza, N.Absi, D.Feillet, Vehicle routing problems with multiple trips. 4OR A quarterly Journal of Operations Research, 14(3): 223–259, 2016.
- [5] F.Hernandez, D.Feillet, R.Giroudeau, O.Naud, A new exact algorithm to solve the multi-trip vehicle routing problem with time windows and limited duration.. 4OR A quarterly Journal of Operations Research, 12(3): 235–259, 2014.
- [6] F.Hernandez, D.Feillet, R.Giroudeau, O.Naud, Branch-and-price algorithms for the solution of the multitrip vehicle routing problem with time windows. European Journal of Operational Research, 249(2):551– 559, 2016.
- [7] R.Macedo, C.Alves, J.M.Valério de Carvalho, F.Clautiaux, S.Hanafi, Solving the vehicle routing problem with time windows and multiple routes exactly using a pseudo-polynomial model. European Journal of Operational Research, 214(3): 536–545, 2011.
- [8] M.Solomon, Algorithms for the vehicle routing and scheduling problem with time window constraints.. Operations Research, 35(2): 254–265, 1987.