

A new approach of experimental and modelling study of mixed gas hydrates under non-equilibrium conditions

Saheb Maghsoodloo, Baptiste Bouillot, Jean - Michel Herri

▶ To cite this version:

Saheb Maghsoodloo, Baptiste Bouillot, Jean - Michel Herri. A new approach of experimental and modelling study of mixed gas hydrates under non-equilibrium conditions. 16ème Congrès de la Société Française de Génie des Procédés (SFGP 2017 NANCY), Jul 2017, Nancy, France. Ed. SFGP, Paris, France, Livres des résumés, 110, 2017, Récents Progrès en Génie des Procédés. hal-01655059

HAL Id: hal-01655059 https://hal.science/hal-01655059

Submitted on 4 Dec 2017


HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

A new approach of experimental and modelling study of mixed gas hydrates under non-equilibrium conditions




MAGHSOODLOO Saheb*, **BOUILLOT Baptiste**, **HERRI Jean-Michel**

Ecole des Mines de Saint-Etienne, SPIN, CNRS 5307, LGF, F-42023 Saint-Etienne, France * Corresponding author: saheb.m@emse.fr



Introduction

Gas hydrates are crystalline solids composed of water and gas. The gas molecules (guests) are trapped in water cavities (host) that are composed of hydrogen-bonded water molecules.







Two different gas mixture including propane were studied. For each mixture, we performed two different experiments based on two different crystallization rates at the same initial conditions.

- - ---Quick crystallization rate
- **Slow crystallization rate**


The results of two different crystallization rates show that:

Gas hydrates are a crucial issue in many fields, from oil & gas industry, to carbon capture and storage, air conditioning, or even planetary science. They also have an enormous potential as an energy resource





Objectives

Effects of crystallization rate




A thermodynamic model, implementing classic van der Waals and Platteuw model, was used. The Kihara parameters for methane were taken from the previous works of our team and the Kihara parameters for propane have been investigated in this work.





- Studying the thermodynamics of mixed clathrate hydrates
- Determination of the gas composition in hydrate phase
- Volume of clathrate hydrate and water conversion
- Developing a reliable thermodynamic model based on classical van der Waals and Platteeuw model by implementing Kihara parameters.

Experimental section



 $\Delta \mu_w^{\beta-L} = \mu_w^L - \mu_w^\beta$

 $\Delta \mu_w^{\beta} \vdash \mu_w^H - \mu_w^\beta$

Classical thermodynamic


Parameters from Handa and Tse

Statistical thermodynamic


Kihara parameters

$$\Delta \mu_{w}^{L-\beta} = T \frac{\Delta \mu_{w}^{L-\beta} \Big|_{T^{0},P^{0}}}{T^{0}} - T \int_{T^{0}}^{T} \frac{\Delta h_{w}^{L-\beta} \Big|_{P^{0}}}{T^{2}} dT + \int_{P^{0}}^{P} \Delta v_{w}^{L-\beta} \Big|_{T} dP - RT \ln a_{w}^{L} \Big|_{T,P} \qquad w(r) = 2z\varepsilon \left[\frac{\sigma^{12}}{R^{11}r} \left(\delta^{10} + \frac{a}{R} \delta^{11} \right) - \frac{\sigma^{6}}{R^{5}r} \left(\delta^{4} + \frac{a}{R} \delta^{5} \right) \right]$$

Based on our results of slow crystallization and also some equilibrium data from literature, a new set of Kihara parameters for propane was obtained. The simulation based on the new Kihara parameters was compared with the other Kihara parameters in the open literature.







1. Cryostat 2. Reactor 2L. 100bar 3. Windows 12 * 2cm 4. Gas bottles 5. Agitator 6. Temperature sensors Pt 100 7. Sampling liquid 8. HPLC pump 9. Granulometric sensors LASENTECH 10. Sampling gas ROLSI 11. Gas chromatograph 12. Air supply, He **13. Display pressure and temperature** 14. Computer recording data



Conclusions

- >The equilibrium pressure for a given temperature is slightly different for different crystallization rates.
- > The Volume of hydrate and also water conversion in quick crystallization process is larger than slow crystallization rate.
- > Moreover, in a hydrocarbon mixture at slow crystallization rate, enclathration of heavier hydrocarbon is more important.
- >A New set of Kihara parameters of propane was obtained and it has a good accordance to predict the hydrate equilibrium pressure for a wide range of temperature from literature.

