

# A comprehensive study of layer-specific morphological changes in the microstructure of carotid arteries under uniaxial load

Witold Krasny, Claire Morin, Hélène Magoariec, Stéphane Avril

## ▶ To cite this version:

Witold Krasny, Claire Morin, Hélène Magoariec, Stéphane Avril. A comprehensive study of layer-specific morphological changes in the microstructure of carotid arteries under uniaxial load. Acta Biomaterialia, 2017, 10.1016/j.actbio.2017.04.033. hal-01671719

HAL Id: hal-01671719

 $\rm https://hal.science/hal-01671719$ 

Submitted on 22 Dec 2017

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

(will be inserted by the editor)

A comprehensive study of layer-specific morphological changes in the microstructure of carotid arteries under uniaxial load

Witold Krasny $^{1,2,3,4}$  · Claire Morin $^{1,2,3}$  · Hélène Magoariec $^4$  · Stéphane Avril $^{1,2,3*}$ 

Received: date / Accepted: date

Abstract The load bearing properties of large blood vessels are principally conferred by collagen and elastin networks and their microstructural organization plays an important role in the outcomes of various arterial pathologies. In particular, these fibrous networks are able to rearrange and reorient spatially during mechanical deformations. In this study, we investigate for the first time whether these well-known morphological rearrangements are the same across the whole thickness of blood vessels, and subsequently if the underlying mechanisms that govern these rearrangements can be predicted using affine kinematics. To this aim, we submitted rabbit carotid samples to uniaxial load in three distinct deformation directions, while recording live images of the 3D microstructure using multiphoton microscopy. Our results show that the observed realignment of collagen and elastin in the media layer, along with elastin of the adventitia layer, remained limited to small angles that can be predicted by affine kinematics. We show also that collagen bundles of fibers in the adventitia layer behaved in significantly different fashion. They showed a remarkable capacity to realign in the direction of the load,

<sup>1.</sup> Ecole Nationale Suprieure des Mines de Saint-Etienne, CIS-EMSE, SAINBIOSE, F-42023 Saint Etienne. France

<sup>2.</sup> INSERM, U1059, F-42000 Saint Etienne, France

<sup>3.</sup> Université de Lyon, SAINBIOSE, F-42000 Saint Etienne, France

<sup>4.</sup> Laboratoire de Tribologie et Dynamique des Systèmes, CNRS UMR 5513, Université de Lyon, Ecole Centrale Lyon, France

<sup>\*</sup>correspondance to: avril@emse.fr

whatever the loading direction. Measured reorientation angles of the fibers were significantly higher than affine predictions. This remarkable property of collagen bundles in the adventitia was never observed before, it shows that the medium surrounding collagen in the adventitia undergoes complex deformations challenging traditional hyperelastic models based on mixture theories.

Keywords Carotid artery · microstructure · adventitia · media · uniaxial load

#### 1 Introduction

Cardiovascular disorders are a significant public health issue affecting ageing populations globally and causing considerable public health expenses (31% of total mortality in 2012 - source: World Health Organization). In numerous cases, the disorder involves significant changes in the vascular mechanical properties, generating extensive studies about arterial biomechanics and mechanobiology. In this respect, a common approach to vascular biomechanics consists in submitting samples of arterial tissue to mechanical bench tests in order to characterize their macroscopic mechanical properties. Existing investigations [4,37,14] consisted in applying a tensile loading on flat samples of arterial material, revealing in particular the material's ability to undergo large strains and a characteristic stiffening 11 occurring above a given tensile stress. In order to capture this complex mechanical behavior and a potential anisotropy of the response, uniaxial tensile tests have been performed independently in the axial and circumferential directions [32,8], 14 and separately to the different layers of the composite structure of the arterial 15 wall [22,46]. In parallel to this macroscopic characterization of the mechanical 16 properties, the microstructure of the vascular wall has been extensively analyzed 17 by different microscopy techniques. In particular scanning electron microscopy allowed a morphological analysis of the arterial microstructure at the micron scale [20,55,12,35]. As for dynamic 2nd harmonic microscopy, it enabled simultaneous image acquisition and optical analysis of collagen fiber orientation, by means of 21 the collagen's optical property of second harmonic generation in the presence of

an intense laser beam coupled to a polarizer [43,48,26]. Confocal microscopy and multiphoton microscopy enabled live imaging with independent emissions signals corresponding to elastin and collagen [50] providing a 3D point of view on morpho-25 logical characteristics of the vascular wall, and allowing the evaluation of volume fractions of the different components of the microstructure [31]. These techniques revealed the morphology of each concentric layer (intima, media, adventitia). Concerning the intima, it is composed of endothelial cells, oriented longitudinally [37]. As for the media, it is composed principally of circumferentially oriented smooth 30 muscle cells and collagen fibers embedded in an elastin network [56, 10, 53, 13, 16]. 31 Finally, the adventitia is composed of thick collagen bundles and of a net of helically oriented elastic fibers [6]. Recently, a special attention has been dedicated to further characterize collagen and elastin fibers, for instance by measuring the waviness of adventitial collagen [36], fiber segment length and the radially-connecting 35 fiber density in the media [49,29]. Also, several studies started investigating the link between the arterial tissue's macroscopic mechanical response and the associ-37 ated rearrangements of its microstructure, by coupling mechanical testing with live microscopy. The latter studies confirmed the load-bearing properties of collagen fibers and revealed a progressive morphological rearrangement under load, namely 40 decrimping and reorientation of the collagen fibers in the direction of the load, as well as the subsequent stiffening of the material's response [48,45,18,54]. Those tests consisted in the application of uniaxial tension on flat samples [52, 21, 38], biaxial tension on flat samples [39, 23, 47, 27, 28, 7], or tension-inflation on cylindrical samples [19,58,17]. The observed morphological rearrangements concerned in particular bundle waviness and orientation [6, 40, 28, 54].

As a conclusion, extensive characterizations of both the mechanical layerspecific anisotropic behavior of the arterial wall, and the load-free microstructure
morphology exist. Moreover, studies aiming at the characterization of load-induced
microstructure rearrangements also exist and come up with advanced insights into
the coupling between macro-mechanical response and tissue microstructure rear-

rangements. However neither the underlying microscopic mechanisms governing
the load-induced microstructure rearrangements nor the inter-layer differences in
the rearrangements of the collagen and elastin networks have been characterized.
This paper is devoted to bridge these gaps in knowledge, by answering the following questions: are the well-known morphological changes of the vascular tissue
under load (uncrimping, realignment) dependent on the direction of the load, on
the vascular layer, and on the constituent under consideration? Are these morphological changes governed exclusively by the rule of affine transformations [5,
25]?

#### 2 Materials and methods

## 62 2.1 Sample preparation


Seven carotid arteries (Fig. 1(a)) were harvested from healthy male New Zealand White rabbits, weighing 3 kg approximately. Excisions were realized at the Veterinary Campus of the Université de Lyon (VetAgro Sup, Marcy l'Étoile, FR). Rabbit cadavers, previously sacrificed under compliance with the NIH Guide for Care and Use of Laboratory Animals, were kindly provided by Centre Lago (Vonnas, 67 FR). The length of each carotid was measured in vivo and ex vivo, i.e. immediately after harvesting (Table 1 - columns 2 and 3), in order to evaluate the in vivo pre-stretch condition (computed as the ratio of the ex vivo length to the in vivo length, Table 1 - column 4). The arteries were immediately frozen at -20 °C until the day of the experimental tests and unfrozen in a bath of phosphate-buffered 72 saline (10x PBS, pH 7.1) at ambient temperature (24 °C). 10 mm long cylindrical portions were excised from the arteries and longitudinally cut open, with a resulting width of approximately 5 mm. For each artery, a 0.5 mm long ring (Fig. 1(b)) was also extracted for optical measurement of the arterial thickness (Table 1 - last column). This resulted in a cross-sectional area of  $0.5\pm0.1~\mathrm{mm}^2$ . The rectangular 77 strips were cut into dogbone shapes [21] aligned along the three following in-plane

directions: circumferential, longitudinal, and an intermediate direction making a
45° angle with respect to the longitudinal direction (see Fig. 2(a) for a sketch of
the sample preparation). In the following, this intermediate direction will be referred to as the diagonal direction. Twelve samples (four in each orientation group)
were dedicated to mechanical testing coupled to multiphoton microscopy, while 6
additional samples (two in each orientation group) were dedicated to mechanical
testing alone.

#### 6 2.2 Tensile test

A screw-driven high precision tensile machine (Deben® Microtest tensile/compression stage) was used for uniaxial tensile tests, with a 150 N capacity load cell (Fig. 1(c)). The load cell signal provided a 0.01 N precision with satisfactory stability. The two heads of the tensile device moved in opposite directions, while the force and 90 the displacement were recorded. Particular care was taken to ensure that the protocol for sample fixation limited the risk of inducing any pre-strain or pre-stress in the sample. Each sample underwent quasi static triangular preconditionning. 93 According to the choice made by Hill et al. [21], a displacement-speed control was applied a rate of 0.5 mm·min<sup>-1</sup>, corresponding to a relative elongation speed of 95 0.2 min<sup>-1</sup>, with fixed target tensile force equal to 1N. During the mechanical test, the sample was continuously immerged in PBS at a constant ambient temperature of 24 °C. After preconditioning, four measures of the sample width in the unloaded configuration were recorded using a caliper and averaged [21]. An image of the harvested ring of the artery was taken using a macro optic objective (Nikon 100 D7200<sup>®</sup> optical camera equipped with Nikon AF-S VR Micro-Nikkor<sup>®</sup> optical 101 105 mm f/2.8G IF-ED lens). The caliper in 0.5 mm opening position was placed 102 next to the sample ring in order to caliber the pixel size and subsequently measure the thickness of the arterial wall. The measures of the sample width and thick-104 ness allowed the computation of the reference cross-sectional area  $A_0$  (under zero 105 load, after preconditioning) and of the first Piola-Kirchhoff (engineering) stress 106

[21]  $\sigma_{PK} = F/A_0$ , where F is the displacement-dependent measure of the tensile force. The stretch was computed from the actual and reference inter-clamp length of the strip (respectively l and  $l_0$ ) as:  $\lambda = l/l_0$ . The reference length of the strip was defined as the interclamp length of the strip after preconditioning.



 $\textbf{Fig. 1} \ \, \textbf{(a)} \,\, \textbf{Excised carotid artery from a New Zealand White rabbit; (b)} \,\, \textbf{Cross-sectional ring of the artery for optical thickness measurement; (c)} \,\, \textbf{Tensile machine.}$ 




Fig. 2 (a) Schematic representation of the vascular tissue samples, prepared from cut-open cylindrical portions of New Zealand White rabbit carotid arteries; (b) Schematic representation of the experimental setup composed of a tensile machine coupled to a multiphoton microscope.

## 2.3 Multiphoton Microscopy

- A multiphoton microscope (NIKON, A1R MP PLUS) of the IVTV platform (En-
- 113 gineering and Ageing of Living Tissues Platform, ANR-10-EQPX-06-01) was used

to image the collagen and elastin networks of the samples (Fig. 2(b)). Setting the 114 excitation wavelength to 870 nm [21] allowed collecting autofluorescence and col-115 lagen second harmonic generation (SHG) signals through 500-550 nm and 400-492 116 nm band-pass filters respectively [25], without any staining or fixation. The imag-117 ing resolution was set to 0.5 μm in all directions [21,40] with a 512 μm<sup>2</sup> imaging 118 window. This setting resulted in stacks of images characterized by 60 to 90 µm 119 thicknesses, depending on the quality of the signal at in-depth focal position. In 120 order to achieve an optimal compromise between image quality and acquisition 121 time, the scan speed was set to 0.25 frames per second, with two-frame averaging. 122 This setting resulted in acquisition times of approximately 20 to 30 minutes for a 123 given elongation configuration. Each arterial tissue sample underwent two imaging sequences: one sequence with the adventitial side facing the objective of the 125 microscope after five preconditioning cycles [21]; and the other sequence with the 126 intimal side facing the objective after two additional stabilizing preconditioning 127 cycles. Images were taken in the unloaded configuration and in three gradually 128 loaded configurations, respectively at 0.2 N, 0.5 N, and 0.8 N. Before imaging, a period of 10 to 15 minutes was observed in order to stabilize the tissue after initial 130 material creep. Creep dynamics were previously analyzed and it was shown that 10 131 minutes were sufficient to avoid an important creeping. It was also observed by live 132 imaging that possible further creep did not modify noticeably the microstructure 133 morphology.

## 5 2.4 Image analysis

The image stacks representing collagen and elastin were analyzed in terms of spatial orientation of the fibrous networks. Previous studies have investigated the transmural angle (radial direction) of the fibers and showed that it is negligible in comparison to the in-plane angle [38, 36, 40]. They have also showed that the most relevant morphological changes in the microstructure occur in the circumferential and longitudinal directions. Subsequently, we focused in the following on the anal-

ysis of the in-plane angles of the fibrous networks. Prior to the analysis of relative angle densities, the image stacks were pre-processed so that they could represent the true tissue morphology on two-dimensional images while enabling liable angle density extraction. To this aim, the stack portion representing the adventitial layer of the vascular wall was subdivided into three equally thick sublayers (20-30 μm) and each sublayer was projected orthogonally onto a single image using a maximum intensity projection algorithm. The choice of three sublayers allowed to achieve an optimum between image pixel density and fiber trans-mural continuity (due to non-zero transmural angles which could cause bias in the angle density analysis). Pre-processing of the media stack consisted in a projection in the thickness of one representative lamella (5-10 µm), after verification of the equivalent morphologies of the different lamellae. The resulting set of 2D images used for the analysis of the fiber angle density consisted in three images of the adventitial collagen, three images of the adventitial elastin, one image of the medial collagen and one image of the medial elastin (Fig. 3(a)). The relative angle densities of the fibrous networks seen on each of these images were analyzed by combining wedge-shape integration of the Fourier power spectrum [2,42,41] (Fig. 3(b)) and a custom method for the extraction of local density maxima with their associated dispersions (Fig. 3(c)). Local density maxima were determined by a standard peak detection algorithm. The associated dispersions were evaluated by first determining an arbitrary density threshold that represented a cumulative percentile of total fiber angles extracted from the image, and secondly by reading out angle values corresponding to this threshold. Explicitly, let  $\theta$  represent a local orientation angle, and  $d(\theta)$  the angle density of the analyzed image; the angle density threshold p is the angle density below which the fraction  $\alpha_p = 0.8$  of the total fibers is counted, i.e. the solution of the following equation:

$$\alpha_p = \frac{\int_0^\pi \min(d(\theta), p) d\theta}{\int_0^\pi d(\theta) d\theta} = 0.8.$$
 (1)

We evaluated corresponding angles about each detected local maximum in order to extract related relative dispersions (Fig. 3(c)).

#### 2.5 Predicting the amplitude of fiber rotation by affine reorientation

The assumption of affine reorientation considers that the fibers are continuously embedded in their surrounding matrix and are therefore constrained to the same deformation gradient as the matrix [3,5,25]. For a uniaxial tensile loading, the fiber orientations  $\theta$  can be computed as a function of the initial angle  $\theta_0$  and deformation stretch  $\lambda$  (Fig. 3(d)) by:

$$\theta = \arctan(\lambda \tan \theta_0). \tag{2}$$

The angle values predicted by Equation (2) are compared to the experimentally 139 measured angles in order to analyze to which extent this affine reorientation can 140 predict true fiber network reorientations. In particular, the adventitial collagen 141 bundles showed, in the load-free state, a dense crimped configuration for which it 142 was difficult to extract global orientations of the bundles using traditional image 143 processing techniques (Fourier analysis, local gradients, ...). In order to avoid a subsequent imprecision of the analysis, a specific method was designed to isolate the global fiber rotation mechanism from the uncrimping mechanism, and to test the hypothesis of affine kinematics only on the global reorientation of the fibers. To 147 this aim, we considered a deformation scenario which starts in the diagonally de-148 formed state and reaches the circumferentially and longitudinally deformed states 149 in two sequenced steps: diagonal unloading followed by circumferential or longitudinal loading. Accordingly, only deformed configurations with straight collagen 151 bundles needed to be processed for fiber angle analysis. Prediction errors were com-152 puted by dividing the difference between experimental and predicted fiber angles 153 by the experimental fiber angle. 154




Fig. 3 Summary of the image analysis method. (a) Partial z-projections of adventitial and medial microstructure image stacks; (b) Fast Fourier 2D analysis of microstructure images; (c) Local maxima dectection and associated relative dispersions evaluation on smoothed fiber angles density function; (d) Analytical computation of affine fiber reorientation.

#### 55 3 Results

Specimen	Ex vivo	In vivo	In vivo	Thickness
	[mm]	[mm]	[-]	[mm]
1	4.3	7.1	1.6	0.18
2	4.1	6.9	1.6	0.17
3	4.3	7.0	1.6	0.19
4	4.2	6.9	1.6	0.16
5	4.3	7.5	1.7	0.18
6	4.0	6.5	1.6	0.18
7	3.9	6.6	1.7	0.19

Table 1 Geometrical measurements of the harvested carotid arteries.

## 3.1 Macromechanical response of the arterial tissue

Engineering stress evaluated against stretch revealed a macroscopic anisotropy of the material's mechanical response, as shown by (i) the characteristic stiffening

of the samples starting at different stretch values depending on the direction of

the load (Fig. 4(a)); (ii) the estimated elastic moduli in the final loading regime

(Figure 4(b)-middle), and (iii) the stretch values when reaching 0.5 MPa (Figure 161 4(b)-right). In particular, the mean estimated elastic moduli in the final loading 162 regime was 50% higher in the circumferential direction than in the longitudinal 163 direction; and 20% higher in the circumferential direction than in the diagonal 164 direction. Accordingly, the mean stretch when reaching 0.5 MPa was 20% lower 165 in the circumferential direction than in the longitudinal direction; and 15% lower 166 than in the diagonal direction. Concerning the estimated elastic moduli in the 167 initial loading regime (Figure 4(b)-left), the comparison of mean values showed 168 lower differences between the sample families as their standard deviation amounts 169 to 8%. Comparing the measured in vivo stretches to the longitudinal mechanical 170 response (Table 1), the carotid were subjected in vivo to a longitudinal stress of about 0.1 MPa, in the soft region of the curve (Fig. 4 - red curves). 172

### 173 3.2 Microstructure morphological rearrangements under uniaxial load

Fibrous networks of the arterial microstructure revealed varying morphologies depending on the biological constituent (elastin, collagen), on the considered arterial 175 layer (adventitia, media), and on the direction of the applied uniaxial load (Fig. 176 5). Fig. 5(a) shows the microstructure of the unloaded arterial tissue, and Fig. 177 5(b)(c)(d) show the microstructure under the three considered loading conditions, 178 which corresponded to the same uniaxial force of 0.8 N. For each constituent of the imaged microstructure, we provide on Fig. 6 a polar representation of fiber 180 orientations (local maxima of angle density with associated dispersions, see section 181 2.4 for more details) with the relative elongation  $\lambda$  and the fiber angle  $\theta$  as polar 182 coordinates. The angles  $\pi/2$ ,  $3\pi/4$ , and  $\pi$  represent the circumferential, diagonal, 183 and longitudinal directions respectively. 184


Adventitial collagen was organized in thick bundles showing a crimped morphology in the load-free state (Fig. 5(a) - upper left). The analysis of in-plane fiber angles (Fig. 6(a)) suggested a preferred direction close to the longitudinal direction, with an important dispersion ( $\pm \pi/6$ ) due to bundle direction variabil-

185


186

187

188



**Fig. 4** (a) Macroscopic mechanical response: engineering stress PK v.s. stretch plotted for the three loading directions (blue: circumferential, black: diagonal, red: longitudinal); (b) Statistical representations of the stiffness before (left) and after (middle) collagen engagement, and stretch when reaching 0.5 MPa (right); n stands for the number of investigated samples



**Fig. 5** Arterial microstructure imaged under multiphoton microscope. (a) Load-free state, (b) circumferential load (F = 0.8 N,  $\lambda$  = 1.7), (c) longitudinal load (F = 0.8 N,  $\lambda$  = 2.1), and (d) diagonal load (F = 0.8 N,  $\lambda$  = 1.9). The upper row of each image represents the adventitia; the lower row represents the media. Collagen network is represented in grey (left), elastin network is represented in red (right).

ity and to the influence of crimping, which limited the liability of interpretation. These collagen bundles underwent an uncrimping process and all appeared to align close to the direction of the load, whether its direction was circumferential (Fig. 5(b) - upper left), longitudinal (Fig. 5(c) - upper left) or diagonal (Fig. 5(d) - upper left). In the three deformed states, in-plane fiber orientations (Fig. 6(a)) showed identically limited dispersions ( $\pm \pi/12$ ) around their respective local angle maximum.




Fig. 6 Orientations of fiber networks represented with local angle density maxima and associated dispersions, for each constituent, layer, and load direction, under 0 and 0.8 N tensile load: (a) and (e) correspond to adventitial collagen, (b) and (f) to adventitial elastin, (c) and (g) to medial collagen, and (d) and (h) to medial elastin. The blue, black, and red colors correspond to the circumferential ( $\lambda=1.7$ ), diagonal ( $\lambda=1.9$ ), and longitudinal ( $\lambda=2.1$ ) directions respectively. Represented network orientations correspond to the mechanical deformations of samples 1-3, tested respectively in the circumferential, diagonal and longitudinal directions.

Adventitial elastin took the form of a low-density meshwork, composed of thin fiber segments showing a preferred longitudinal direction with variously oriented transverse segments (Fig. 5(a) - upper right). The analysis of in-plane fiber angles at rest (Fig. 6(b)) confirmed the longitudinal orientation, with an important dispersion ( $\pm \pi/6$ ) due to the variously oriented transverse fiber segments. Under load, the longitudinally oriented fiber segments underwent limited morphological changes: when the loading direction was circumferential (Fig. 5(b) - upper right), the global orientation of the meshwork did not change significantly (a maximum of  $\pi/6$  rotation - Fig. 6(b)), although a spreading of the meshwork was noticeable (compare Fig. 5(a) - upper right and 5(b) - upper right). Almost unchanged dispersions around local density maxima (Fig. 6(b)) confirmed this limited morphological

change. When the load was applied longitudinally (Fig. 5(c) - upper right), trans-verse segments aligned in the direction of the load, while the fibrous meshwork remained oriented in the longitudinal direction, which led to an unchanged angle density (Fig. 6(b)). When the load was applied in the diagonal direction (Fig. 5(d) - upper right), the meshwork underwent a limited reorientation towards the loading direction (a maximum rotation of  $\pi/6$  and angle dispersions reduced by a factor 2 - Fig. 6(b)), with transverse segments aligning with the principal segments orientations. 

Medial collagen did not agglomerate into variously oriented bundles as in the adventitia, but took the form of thin parallel fibers distinctively oriented in the circumferential direction (Fig. 5(a) - lower left) and showed a higher crimping frequency. Its morphology underwent limited changes under uniaxial load: when the loading direction was circumferential (Fig. 5(b) - lower left), the fibers uncrimped and remained aligned in the circumferential direction (Fig. 6(c)). When the loading direction was diagonal (Fig. 5(d) - lower left), the fibers uncrimped - with a decrease of the dispersion of local angles by a factor 2 (Fig. 6(c)) - and underwent a limited realignment in the loading direction - below  $\pi/6$  rotation for the density maximum of local angles (Fig. 6(c)). When the load was longitudinal (Fig. 5(c) - lower left), i.e. perpendicular to the network direction, the fibers did not align in the loading direction and their crimping increased, as shown by the angular dispersion increased by a factor 2 (Fig. 6(c)).

The medial elastin morphology was different from the one of adventitial elastin:
at rest (Fig. 5(a) - lower right), it took the form of a dense, structured meshwork
preferentially oriented in the circumferential direction. Under load, it underwent
limited morphology changes, namely partial alignment of transverse fiber segments
in the loading direction, when the loading direction was circumferential (Fig. 5(b)
- lower right) or longitudinal (Fig. 5(c) - lower right); the maxima of angle density
remained unchanged, while the angular density dispersion decreased by a factor

<sup>235</sup> 2 (Fig. 6(d)); and a limited global reorientation when the loading direction was diagonal, with rotation of the angle density maximum below  $\pi/6$ .

237 3.3 Prediction of reorientations using an affine model

Table 2 presents the experimental values of local angle density maxima with the 238 upper and lower angle bounds corresponding to the evaluated dispersions, together 239 with the theoretical angles computed by applying the affine reorientation (Equation (2)) to the local angle maxima. The represented results in Table 2 refer to the 241 testing of samples 1 to 3, respectively in the circumferential, diagonal and longitu-242 dinal directions. Fig. 7 presents a statistical synthesis of fiber angles under uniaxial 243 load, together with the theoretical angles computed by applying the affine reorientation (Equation (2)) to the local angle maxima. The represented results refer to the four sample groups tested in the three aforementioned directions (samples 246 1 to 12). Results show that the affine model predicted well the reorientation of the 247 medial microstructure (collagen and elastin) as well as of the adventitial elastin, 248 with prediction errors ranging from 1 to 7% (see Table 2 and compare black and 249 white symbols in Fig. 7) and a limited variability of fiber orientation between the 250 analogous samples (Fig. 7). Concerning adventitial collagen, for which we illus-251 trated the ability to reorient along the different tested loading directions (Fig. 5, 252 Fig. 6), the affine model largely under-predicted the fiber reorientation, as proven 253 by the high prediction error (12 to 25%, see Table 2), observed independently on 254 the analogous samples (Fig. 7, upper left). 255

#### 56 4 Discussion

Our results represent an original insight into the morphological changes that occur in the arterial tissue microstructure under variously oriented uniaxial loads. The experiments were performed on rabbit carotid arteries and focused on collagen and elastin networks of the media and of the adventitia. Our results suggest that

		(a) Initial	(b) Final 1	(c) Final 2
Group 1 : samples 1-3		$\lambda_{diag} = 1.9 \pm 0.1$	$\lambda_{circ} = 1.7 \pm 0.05$	$\lambda_{long} = 2.1 \pm 0.2$
Collagen - adv.	Experimental $[\pi]$	$0.76^{+0.07}_{-0.02}$	$0.55^{+0.07}_{-0.06}$	$0.97^{+0.03}_{-0.05}$
	Affine prediction $[\pi]$	-	0.69	0.85
	Prediction error $[\pi]$	-	25%	12%
Elastin - adv.	Experimental $[\pi]$	$0.86^{+0.04}_{-0.09}$	$0.83^{+0.12}_{-0.13}$	$0.98^{+0.02}_{-0.01}$
	Affine prediction $[\pi]$	-	0.89	0.97
	Prediction error	-	7%	1%
Collagen - med.	Experimental $[\pi]$	$0.61^{+0.04}_{-0.03}$	$0.51^{+0.02}_{-0.02}$	$0.52^{+0.16}_{-0.17}$
	Affine prediction $[\pi]$	-	0.52	0.54
	Prediction error	-	2%	4%
Elastin - med.	Experimental $[\pi]$	$0.60^{+0.07}_{-0.06}$	$0.53^{+0.03}_{-0.08}$	$0.53^{+0.22}_{-0.21}$
	Affine prediction $[\pi]$	-	0.50	0.51
	Prediction error	-	6%	4%

**Table 2** Evaluation of the predictive accuracy of affine reorientation. Fiber angles are provided for initial and final states of two deformation scenarii (Samples 1-3): (a) to (b) and (a) to (c)




Fig. 7 Synthesis of the predictive accuracy analysis of affine reorientation. Final network orientations (Final state 1 and Final state 2) are averaged on n=4 samples under analogous deformation. Affine prediction errors in the case of adventitial collagen reorientation amount to  $0.12\pi$  and  $0.13\pi$  when reaching final states 1 and 2 respectively, corresponding to 22% and 14% error.

the arterial tissue is more compliant in the longitudinal direction, as seen by a

delayed stiffening phase. This result is consistent with previous studies performed

262

by pressurizing and axially elongating dog carotids [34,11], rat and rabbit carotids

265

266

267

268

269

270

271

272

273

275

276

277

278

279

280

281

282

284

285

286

287

290

291

292

[11] and by applying uniaxial tension on flat samples of human ascending aortas [8]. Conversely, this anisotropy has been shown contrary (stiffer tissue in the longitudinal direction) for human coronary arteries [33] and dog coronary arteries [34]. Indeed, no consensus has been gained up to now as regards the anisotropy of arteries, evidencing the complex interplay of load bearing contributions between the media and the adventitia. Recent results [22] show clearly that the media is stiffer in the circumferential direction, while the adventitia is stiffer in the longitudinal direction. These results are in good agreement with the orientation of the fiber networks in each layer, but do not permit to draw any conclusion on the overall anisotropy of the tissue. In order to further understand the origin of this complex anisotropy, the distribution of load bearing properties between the media and adventitia should be further characterized along with the study of microstructure rearrangements.

Concerning the arterial microstructure in the load-free state, our results illustrate the layer-specific morphologies of the collagen and elastin networks which are similar to previous investigations [31,36]. In the deformed configuration however, our results bring a novel comprehensive understanding of morphological changes occurring within the arterial microstructure. Under uniaxial tensile loadings, affine kinematics [3,5] explain the reorientations of adventitial elastin, medial elastin, and medial collagen. This kinematically limited reorientation corresponds to a tight embedding of the fibers in their surrounding matrix, which could correspond to near-equivalent shear moduli of the fibers and of their surrounding matrix, or to the existence of molecular links which hinder further rotation of the inclusions within the matrix. Besides, these fibrous networks are unable to fully align in any of the presently applied uniaxial loading directions. Conversely, the adventitial collagen showed a remarkable potential to reorient in any of the applied loading directions (circumferential, longitudinal, diagonal). This reorientation is characterized by significant rotation amplitudes, that remain underestimated by affine reorientations. Although the protocols employed in the literature vary both

303

304

305

306

307

308

309

311

312

314

317

321

in terms of characterization techniques (focusing on fiber decrimping [30] or on 293 global fiber reorientation [24]) and in terms of applied mechanical loadings (uni-294 axial, equi-biaxial [30]), our result is consistent with previous studies investigating 295 collagen fiber kinematics in other tissues like porcine aortic leaflets [3], bovine 296 pericardium [3], tissue constructs [5] or human liver capsule [24] and suggests that 297 other mechanisms are activated in the reorientation of adventitial collagen under 298 load. 299

Several limitations stem from the differences existing between our testing pro-300 tocol and the real in vivo conditions. First of all, we should comment on the fact that we have considered temperature conditions lower than in vivo conditions. Zemanek et al. [57] studied the influence of the testing temperature on the mechanical response of the arterial wall and showed that samples are stiffer at ambient temperature than at in vivo temperature. There is no consensus on the impact of sample freezing on the change in the mechanical response of the sample [57, 1, 51, 9]. However in the present study, test temperature and preservation conditions were identical for all experiments, and allowed to perform an inter sample comparison of the stiffness change during loading or among diverse load directions. Also, to our best knowledge, there is no study on the influence of the temperature on the 310 fiber rotation. Secondly, we have applied a quasi-static elongation speed, which cannot render the dynamic conditions of the pulsatile hemodynamic load seen in large vessels. However, given the small variations in the arterial pressure and the 313 preferred helical orientation of the adventitial collagen bundles, the orientations of the latter are believed not to vary significantly during a cardiac cycle. The choice 315 of a quasi-static loading was made so as to ensure that the mechanical response 316 was independent of the strain rate, as well as to limit the relaxation effects that would impair repeatability of the results. We should also comment on the choice of directions and ranges of load that go beyond the physiological load directions 319 and ranges. While tension-inflation or equi-biaxial protocols allow the simulation 320 of near physiological loadings, the present protocol was applied to reach our objec-

323

324

325

326

327

328

329

330

332

333

334

335

336

337

338

339

342

343

344

345

349

350

tive of comparing inter-layer and inter-constituent changes of the fiber networks within the microstructure subjected to diversified loading scenarii. Besides, the high stretches reached successively during preconditioning and imaging may have induced damage in the tissue, enhancing non-affine fiber rotation. However it is assumed that in this case, the increase of fiber rotation would have affected all imaged fibrous networks, not only adventitial collagen. Accordingly, we did not observe any sign of damage within the imaged tissue, on any fibrous network of the arterial wall.

Furthermore, it should be mentioned that what we call arterial microstructure in this work is incomplete from the biological point of view, as our multiphoton microscopy provided only images of elastin and collagen fibers, with a spatial resolution of the order of 1 µm. The analysis could be complemented by the characterization of the deformations and reorientations of non-cellular components under varying levels of smooth muscle tones, as the latter mechanism is known to play an active role in arterial adaptive plasticity during the in vivo pressure cycle. At a lower scale, our analysis could also be complemented by the description of collagen fibrils rearrangements within bundles during decrimping and during postdecrimping stretching. Moreover, the observed morphology changes during uniaxial tension in carotid samples should be compared to morphology changes occurring in identically deformed carotids from other species, with different smooth muscle, collagen and elastin content. To the authors' knowledge, identical deformation protocol has not been yet applied to samples of other arteries or other species carotids. However, and to engage the discussion, the recent studies of Keyes et al. [27] on mouse aortas, showed that adventitial collagen could undergo high amplitude rotations under pressurization (up to  $\pi/3$ ), while medial networks kept their orientation unchanged. On the contrary, the results of Chen et al. [7], performed on porcine coronary arteries, illustrated under flat biaxial tension the adventitial collagen's decrimping mechanism but a limited rotation potential. Nevertheless, our analysis was intended as a first step, focusing on the major load-bearing com-

ponents of the arterial wall. Furthermore, a nano-scale imaging resolution could investigate the influence of nanoscale aldehyde cross-links on the observed morphology rearrangements. Such an analysis would give biological foundations to the observed reorientations, explaining why several fibers can encounter large rotations whilst others are restricted to small rotations.

Finally, the level of representativeness of the microscopy images with associated angle distributions of collagenous and elastic networks should be commented. In particular concerning automated angles extraction, the Fast Fourier Transform algorithm applied on adventitial collagen at rest (high density crimped bundles) provided information about local angles but did not allow the extraction of global collagen bundle orientation. In order to capture full morphological rearrangements of adventitial collagen under load, a specific method should be developed so as to analyze collagen orientation at different scales: crimping scale (10 µm) and global bundle scale (100 µm). With the objective of comparing true reorientations with affine predictions, we here overcame this image processing issue by comparing only deformed configurations, for which the orientations at crimping scale and at global bundle scale are identical.

#### 5 Conclusion and outlooks

We have shown that arterial microstructure presents inter-layer differences between collagen network and elastin network morphologies. These inter-layer differences concern in particular the ability to rearrange under variously oriented uniaxial loads. We have shown that even though the fibers of the vascular microstructure undergo the same macroscopic deformation, they rearrange in their own specific way, and differently from one vascular layer to the other. This finding brings additional insight for current multi-scale model formulations which take into account specific kinematics of arterial collagen and its relation to the surrounding matrix [44,15]. It also confirms the need to consider the arterial wall as a composite struc-ture composed of different mechanically relevant layers with different mechanical 

properties [22]. Our results also suggest the need to further investigate the underlying mechanisms that govern adventitial collagen rearrangement, in particular 380 uncrimping and post-uncrimping fiber rotation. Given that the affine reorientation 381 underestimates real fiber rotation of adventitial collagen, it appears interesting 382 to propose a micromechanical origin to collagen fiber rotation. In particular, we 383 hypothesize that the macroscopic strain concentrated in a highly heterogeneous 384 microstructure induces a heterogeneous field of displacement gradients, itself gen-385 erating microscopic spin that can be important if the shear moduli of the fibers 386 and of the matrix are significantly different. These spins may induce material ro-387 tation within the structure which superimposes with affine reorientation. Future 388 multi-scale models could test this hypothesis by accounting for the existence of local spin vectors, promoting fiber rotations. 390

Acknowledgements This work was supported by the ARC 2 "Bien-être et vieillissement" 391 research program of the Auvergne-Rhône-Alpes region (FR), with financial contributions from 392 ERC consolidator grant "Biolochanics" and CNRS UMR 5513 research group. The authors 393 thank Prof. Eric Viguier (VetAgro Sup, Université de Lyon, FR), Dr. Caroline Boulocher (VetAgro Sup, Université de Lyon, FR) and Mr. Fabrice Desplanches (Centre Lago, Vonnas, 395 FR) for their help in provision and excision of arterial specimen. Authors also thank the IVTV (ANR-10-EQPX-06-01) team and especially Ing. Ophélie Pollet for her support during the 397 imaging process, as well as Dr. Damien Constant (Ecole Centrale Lyon, FR) and Mr. Lionel Charles (Ecole Centrale Lyon, FR) for their technical contribution in the preparation of the 399 mechanical setup. 400

### 401 References

- Adham, M., Gournier, J.P., Favre, J.P., De La Roche, E., Ducerf, C., Baulieux, J., Barral,
   X., Pouyet, M.: Mechanical characteristics of fresh and frozen human descending thoracic
   aorta. Journal of Surgical Research 64(1), 32–34 (1996)
- Ayres, C., Jha, B.S., Meredith, H., Bowman, J.R., Bowlin, G.L., Henderson, S.C., Simpson,
   D.G.: Measuring fiber alignment in electrospun scaffolds: a user's guide to the 2D Fast
   Fourier Transform approach. Journal of Biomaterials Science, Polymer Edition 19(5),
   603–621 (2008)

- 3. Billiar, K., Sacks, M.: A method to quantify the fiber kinematics of planar tissues under 409 biaxial stretch. Journal of Biomechanics 30(7), 753-756 (1997) 410
- 4. Burton, A.C.: Relation of structure to function of the tissues of the wall of blood vessels. 411 Physiological Reviews **34**(4), 619–642 (1954) 412
- 5. Chandran, P.L., Barocas, V.H.: Affine versus non-affine fibril kinematics in collagen net-413 works: theoretical studies of network behavior. Journal of Biomechanical Engineering 414
- **128**(2), 259–70 (2006) 415
- 6. Chen, H., Liu, Y., Slipchenko, M.N., Zhao, X., Cheng, J.X., Kassab, G.S.: The layered 416 structure of coronary adventitia under mechanical load. Biophysical Journal 101(11), 417
- 2555-2562 (2011) 418
- 7. Chen, H., Slipchenko, M.N., Liu, Y., Zhao, X., Cheng, J.X., Lanir, Y., Kassab, G.S.: 419
- Biaxial deformation of collagen and elastin fibers in coronary adventitia. Journal of Applied 420
- Physiology **115**(11), 1683–1693 (2013) 421
- 8. Choudhury, N., Bouchot, O., Rouleau, L., Tremblay, D., Cartier, R., Butany, J., Mongrain, 422
- R., Leask, R.L.: Local mechanical and structural properties of healthy and diseased human 423
- ascending aorta tissue. Cardiovascular Pathology 18(2), 83-91 (2009) 424
- 9. Chow, M.J., Zhang, Y.: Changes in the mechanical and biochemical properties of aortic 425
- tissue due to cold storage. Journal of Surgical Research 171(2), 434-442 (2011) 426
- 10. Clark, J.M., Glagov, S.: Transmural organization of the arterial media. The lamellar unit revisited. Arteriosclerosis, Thrombosis, and Vascular Biology 5(1), 19-34 (1985) 428
- 11. Cox, R.: Anisotropic properties of the canine carotid artery in vitro. Journal of biomechanics 8(5), 293-300 (1975) 430
- 12. Denk, W., Horstmann, H.: Serial block-face scanning electron microscopy to reconstruct 431 three-dimensional tissue nanostructure. PLoS Biology 2(11) (2004)
- 13. Dingemans, K.P., Teeling, P., Lagendijk, J.H., Becker, A.E.: Extracellular matrix of the 433
- human aortic media: an ultrastructural histochemical and immunohistochemical study of 434
- the adult aortic media. The Anatomical Record 258(1), 1-14 (2000) 435
- 14. Duprey, A., Khanafer, K., Schlicht, M., Avril, S., Williams, D., Berguer, R.: In vitro 436
- characterisation of physiological and maximum elastic modulus of ascending thoracic aortic 437
- aneurysms using uniaxial tensile testing. European Journal of Vascular and Endovascular
- Surgery 39(6), 700 707 (2010) 439
- 15. Fan, R., Sacks, M.S.: Simulation of planar soft tissues using a structural constitutive model:
- finite element implementation and validation. Journal of biomechanics 47(9), 2043-2054 441
- (2014)442

- 16. Farand, P., Garon, A., Plante, G.E.: Structure of large arteries: Orientation of elastin in 443
- rabbit aortic internal elastic lamina and in the elastic lamellae of aortic media. Microvas-444
- cular Research 73(2), 95-99 (2007) 445

- 446 17. Ferruzzi, J., Vorp, D., Humphrey, J.D.: On constitutive descriptors of the biaxial mechanical behaviour of human abdominal aorta and aneurysms. Journal of the Royal Society,
   448 Interface 8(56), 435–450 (2011)
- 449 18. Genovese, K., Lee, Y.U., Lee, a.Y., Humphrey, J.D.: An improved panoramic digital image
   450 correlation method for vascular strain analysis and material characterization. Journal of
   451 the Mechanical Behavior of Biomedical Materials 27, 132–42 (2013)
- 452 19. Gleason, R.L., Gray, S.P., Wilson, E., Humphrey, J.D.: A multiaxial computer-controlled
   453 organ culture and biomechanical device for mouse carotid arteries. Journal of Biomechan 454 ical Engineering 126(6), 787–795 (2004)
- 20. Gross, J.: The structure of elastic tissue as studied with the electron microscope. The

  Journal of Experimental Medicine 89(6), 699–708 (1949)
- 457 21. Hill, M.R., Duan, X., Gibson, G.A., Watkins, S., Robertson, A.M.: A theoretical and non destructive experimental approach for direct inclusion of measured collagen orientation and
   recruitment into mechanical models of the artery wall. Journal of Biomechanics 45(5),
   762–771 (2012)
- 461 22. Holzapfel, G.A., Sommer, G., Gasser, C.T., Regitnig, P.: Determination of layer-specific
   462 mechanical properties of human coronary arteries with nonatherosclerotic intimal thick 463 ening and related constitutive modeling. American Journal of Physiology-Heart and Cir 464 culatory Physiology 289(5), H2048-H2058 (2005)
- 465 23. Humphrey, J.D., Wells, P.B., Baek, S., Hu, J.J., McLeroy, K., Yeh, A.T.: A theoretically 466 motivated biaxial tissue culture system with intravital microscopy. Biomechanics and
   467 Modeling in Mechanobiology 7(4), 323–334 (2008)
- 24. Jayyosi, C.: Caractérisation mécanique et microstructurale du comportement à rupture de
   la capsule de glisson pour la prédiction du risque de lésions des tissus hépatiques humains.
   Ph.D. thesis, Université de Lyon 1 (2015)
- 25. Jayyosi, C., Coret, M., Bruyere-Garnier, K.: Characterizing liver capsule microstructure
   via in situ bulge test coupled with multiphoton imaging. Journal of the Mechanical Be havior of Biomedical Materials 54, 229–243 (2016)
- 474 26. Kabir, M.M., Inavalli, V.K., Lau, T.Y., Toussaint, K.C.: Application of quantitative
   475 second-harmonic generation microscopy to dynamic conditions. Biomedical optics express
   476 4(11), 2546–2554 (2013)
- 477 27. Keyes, J.T., Borowicz, S.M., Rader, J.H., Utzinger, U., Azhar, M., Geest, J.P.V.: Design
   478 and demonstration of a microbiaxial optomechanical device for multiscale characteriza 479 tion of soft biological tissues with two-photon microscopy. Microscopy and Microanalysis
   480 17(02), 167–175 (2011)

- 481 28. Keyes, J.T., Lockwood, D.R., Utzinger, U., Montilla, L.G., Witte, R.S., Geest, J.P.V.:
   Comparisons of planar and tubular biaxial tensile testing protocols of the same porcine
   coronary arteries. Annals of Biomedical Engineering 41(7), 1579–1591 (2013)
- 29. Koch, R.G., Tsamis, A., D'Amore, A., Wagner, W.R., Watkins, S.C., Gleason, T.G., Vorp,
- D.A.: A custom image-based analysis tool for quantifying elastin and collagen micro-
- architecture in the wall of the human aorta from multi-photon microscopy. Journal of
- 487 Biomechanics **47**(5), 935–943 (2014)
- 488 30. Lee, C.H., Zhang, W., Liao, J., Carruthers, C.A., Sacks, J.I., Sacks, M.S.: On the presence
- of affine fibril and fiber kinematics in the mitral valve anterior leaflet. Biophysical journal
- 490 **108**(8), 2074–2087 (2015)
- 491 31. O'Connell, M.K., Murthy, S., Phan, S., Xu, C., Buchanan, J., Spilker, R., Dalman, R.L.,
- Zarins, C.K., Denk, W., Taylor, C.A.: The three-dimensional micro- and nanostructure
- of the aortic medial lamellar unit measured using 3D confocal and electron microscopy
- imaging. Matrix Biology **27**(3), 171–181 (2008)
- 495 32. Okamoto, R.J., Wagenseil, J.E., DeLong, W.R., Peterson, S.J., Kouchoukos, N.T.,
- Sundt III, T.M.: Mechanical properties of dilated human ascending aorta. Annals of
- 497 Biomedical Engineering **30**(5), 624–635 (2002)
- 498 33. Papageorgiou, G., Jones, N.: Circumferential and longitudinal viscoelasticity of human
- iliac arterial segments in vitro. Journal of biomedical engineering 10(1), 82–90 (1988)
- 500 34. Patel, D.J., Janicki, J.S.: Static elastic properties of the left coronary circumflex artery
- and the common carotid artery in dogs. Circulation Research 27(2), 149–158 (1970)
- 35. Raspanti, M., Protasoni, M., Manelli, A., Guizzardi, S., Mantovani, V., Sala, A.: The
- extracellular matrix of the human aortic wall: ultrastructural observations by FEG-SEM
- and by tapping-mode AFM. Micron 37(1), 81–86 (2006)
- ${\it 36. Rezakhaniha, R., Agianniotis, A., Schrauwen, J.T.C., Griffa, A., Sage, D., Bouten, C.V.C., Agianniotis, A., Schrauwen, J.T.C., Griffa, A., Sage, D., Bouten, C.V.C., Griffa, A., Sage, D., Sage, D.$
- Van De Vosse, F.N., Unser, M., Stergiopulos, N.: Experimental investigation of colla-
- gen waviness and orientation in the arterial adventitia using confocal laser scanning mi-
- croscopy. Biomechanics and Modeling in Mechanobiology  $\mathbf{11}(3\text{-}4),\ 461\text{-}473\ (2012)$
- 509 37. Richardson, P.D., Keeny, S.: Anisotropy of human coronary artery intima. In: Bioengineer-
- ing Conference, 1989., Proceedings of the 1989 Fifteenth Annual Northeast, pp. 205–206.
- 511 IEEE (1989)
- 512 38. Roy, S., Boss, C., Rezakhaniha, R., Stergiopulos, N.: Experimental characterization of the
- distribution of collagen fiber recruitment. Journal of Biorheology 24(2), 84–93 (2011)
- $_{514}$  39. Sacks, M.S.: Incorporation of experimentally-derived fiber orientation into a structural
- constitutive model for planar collagenous tissues. Journal of Biomechanical Engineering
- **125**(2), 280–287 (2003)

- 40. Schrauwen, J.T.C., Vilanova, A., Rezakhaniha, R., Stergiopulos, N., van de Vosse, F.N.,
  Bovendeerd, P.H.M.: A method for the quantification of the pressure dependent 3D collagen configuration in the arterial adventitia. Journal of Structural Biology **180**(2), 335–342
  (2012)
- 41. Schriefl, A.J., Wolinski, H., Regitnig, P., Kohlwein, S.D., Holzapfel, G.A.: An automated
   approach for three-dimensional quantification of fibrillar structures in optically cleared
   soft biological tissues. Journal of The Royal Society Interface 10(80), 20120,760 (2013)
- 42. Schriefl, J., Reinisch, J., Sankaran, S., Pierce, D.M., Holzapfel, G.A.: Quantitative assessment of collagen fibre orientations from two-dimensional images of soft biological tissues.
   Journal of The Royal Society Interface 9, 3081–3093 (2012)
- 43. Stoller, P., Reiser, K.M., Celliers, P.M., Rubenchik, A.M.: Polarization-modulated second
   harmonic generation in collagen. Biophysical journal 82(6), 3330–3342 (2002)
- 44. Stylianopoulos, T., Barocas, V.H.: Multiscale, structure-based modeling for the elastic
   mechanical behavior of arterial walls. Journal of biomechanical engineering 129(4), 611–
   618 (2007)
- 45. Sutton, M., Ke, X., Lessner, S., Goldbach, M., Yost, M., Zhao, F., Schreier, H.: Strain
   field measurements on mouse carotid arteries using microscopic three-dimensional digital
   image correlation. Journal of Biomedical Materials Research Part A 84(1), 178–190 (2008)
- 46. Teng, Z., Tang, D., Zheng, J., Woodard, P.K., Hoffman, A.H.: An experimental study on
   the ultimate strength of the adventitia and media of human atherosclerotic carotid arteries
   in circumferential and axial directions. Journal of Biomechanics 42(15), 2535–2539 (2009)
- 47. Timmins, L.H., Wu, Q., Yeh, A.T., Moore, J.E., Greenwald, S.E.: Structural inhomogeneity and fiber orientation in the inner arterial media. American Journal of Physiology-Heart
   and Circulatory Physiology 298(5), H1537–H1545 (2010)
- 48. Tower, T.T., Neidert, M.R., Tranquillo, R.T.: Fiber alignment imaging during mechanical
   testing of soft tissues. Annals of Biomedical Engineering 30(10), 1221–1233 (2002)
- 49. Tsamis, A., Phillippi, J.A., Koch, R.G., Pasta, S., Amore, A.D., Watkins, S.C., Wagner,
   W.R., Gleason, T.G., Vorp, D.A.: Fiber micro-architecture in the longitudinal-radial and
   circumferential-radial planes of ascending thoracic aortic aneurysm media. Journal of
   Biomechanics 46(16), 2787–2794 (2013)
- 50. Van Zandvoort, M., Engels, W., Douma, K., Beckers, L., Oude Egbrink, M., Daemen, M.,
   Slaaf, D.W.: Two-photon microscopy for imaging of the (atherosclerotic) vascular wall: A
   proof of concept study. Journal of Vascular Research 41(1), 54–63 (2004)
- 550 51. Venkatasubramanian, R.T., Grassl, E.D., Barocas, V.H., Lafontaine, D., Bischof, J.C.:
   551 Effects of freezing and cryopreservation on the mechanical properties of arteries. Annals
   552 of Biomedical engineering 34(5), 823–832 (2006)

- 52. Voytik-Harbin, S.L., Roeder, B.A., Sturgis, J.E., Kokini, K., Robinson, J.P.: Simultaneous
   mechanical loading and confocal reflection microscopy for three-dimensional microbiome-
- chanical analysis of biomaterials and tissue constructs. Microscopy and Microanalysis  $\mathbf{9}$ ,
- 556 74-85 (2003)
- 53. Walker-Caprioglio, H., Trotter, J., Little, S., McGuffee, L.: Organization of cells and extra-
- celluar matrix in mesenteric arteries of spontaneously hypertensive rats. Cell and Tissue
- Research **269**(1), 141–149 (1992)
- 560 54. Wang, R., Brewster, L.P., Gleason, R.L.: In-situ characterization of the uncrimping pro-
- cess of arterial collagen fibers using two-photon confocal microscopy and digital image
- correlation. Journal of Biomechanics  $\mathbf{46}(15)$ , 2726-2729 (2013)
- 55. Wasano, K., Yamamota, T.: Tridimensional architecture of elastic tissue in the rat aorta
- and femoral arterya scanning electron microscope study. Journal of Electron Microscopy
- **32**(1), 33–44 (1983)
- $_{566}$   $_{56}$   $_{56}$  Wolinsky, H., Daly, M.M.: A method for the isolation of intima-media samples from ar-
- teries. Experimental Biology and Medicine 135(2), 364–368 (1970)
- 568 57. Zemánek, M., Burša, J., Děták, M.: Biaxial tension tests with soft tissues of arterial wall.
- 569 Engineering Mechanics **16**(1), 3–11 (2009)
- 570 58. Zoumi, A., Lu, X., Kassab, G.S., Tromberg, B.J.: Imaging coronary artery microstruc-
- ture using second-harmonic and two-photon fluorescence microscopy. Biophysical Journal
- **87**(4), 2778–2786 (2004)