

Low Mach number limit of some staggered schemes for compressible barotropic flows

R. Herbin, J.-C Latché, Khaled Saleh

▶ To cite this version:

R. Herbin, J.-C Latché, Khaled Saleh. Low Mach number limit of some staggered schemes for compressible barotropic flows. Mathematics of Computation, 2021, 90, pp.1039-1087. 10.1090/mcom/3604. hal-01672909v1

HAL Id: hal-01672909 https://hal.science/hal-01672909v1

Submitted on 27 Dec 2017 (v1), last revised 29 Mar 2018 (v2)

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



LOW MACH NUMBER LIMIT OF SOME STAGGERED SCHEMES FOR COMPRESSIBLE BAROTROPIC FLOWS

R. HERBIN *, J.-C. LATCHÉ † , AND K. SALEH ‡

December 27, 2017

Abstract. In this paper, we study the behaviour at low Mach number of numerical schemes based on staggered discretizations for the barotropic Navier-Stokes equations. Three time discretizations are considered: the implicit-in-time scheme and two non-iterative pressure correction schemes. The last two schemes differ by the discretization of the convection term: linearly implicit for the first one, so the resulting scheme is unconditionnally stable, and explicit for the second one, so the scheme is stable under a CFL condition involving the material velocity only. We rigorously prove that these three variants are asymptotic preserving in the following sense: for a given mesh and a given time step, a sequence of solutions obtained with a sequence of vanishing Mach numbers tend to a solution of a standard scheme for incompressible flows. This convergence result is obtained by mimicking the proof already known in the continuous case.

Key words. Compressible Navier-Stokes equations, low Mach number flows, finite volumes, Crouzeix-Raviart scheme, Ranacher-Turek scheme, finite elements, staggered discretizations.

AMS subject classifications. 35Q31,65N12,76M10,76M12

1. Introduction. We consider the non-dimensionalized system of time-dependent barotropic compressible Navier-Stokes equations, parametrized by the Mach number denoted thereafter by ε , and posed for $(x,t) \in \Omega \times (0,T)$:

$$\partial_t \rho^{\varepsilon} + \operatorname{div}(\rho^{\varepsilon} \mathbf{u}^{\varepsilon}) = 0, \tag{1.1a}$$

$$\partial_t(\rho^{\varepsilon} \mathbf{u}^{\varepsilon}) + \operatorname{div}(\rho^{\varepsilon} \mathbf{u}^{\varepsilon} \otimes \mathbf{u}^{\varepsilon}) - \operatorname{div}(\boldsymbol{\tau}(\mathbf{u}^{\varepsilon})) + \frac{1}{\varepsilon^2} \boldsymbol{\nabla} \wp(\rho^{\varepsilon}) = 0, \tag{1.1b}$$

where T is a finite positive real number, and Ω is an open bounded connected subset of \mathbb{R}^d , with $d \in \{2,3\}$, which is polygonal if d=2 and polyhedral if d=3. The quantities $\rho^{\varepsilon}>0$ and $\mathbf{u}^{\varepsilon}=(u_1^{\varepsilon},...,u_d^{\varepsilon})^T$ are the density and velocity of the fluid. The pressure satisfies the ideal gas law $\wp(\rho^{\varepsilon})=(\rho^{\varepsilon})^{\gamma}$, with $\gamma\geq 1$, the heat capacity ratio, a coefficient which is specific to the considered fluid. Equation (1.1a) expresses the local conservation of the mass of the fluid while equation (1.1b) expresses the local balance between momentum and forces. We consider Newtonian fluids so that the shear stress tensor $\tau(\mathbf{u}^{\varepsilon})$ satisfies:

$$\operatorname{div}(\boldsymbol{\tau}(\boldsymbol{u})) = \mu \Delta \boldsymbol{u} + (\mu + \lambda) \boldsymbol{\nabla}(\operatorname{div} \boldsymbol{u}),$$

where μ and λ are two parameters with $\mu > 0$ and $\mu + \lambda > 0$. System (1.1) is complemented with the following boundary and initial conditions:

$$\rho^{\varepsilon}|_{t=0} = \rho_0^{\varepsilon}, \qquad \mathbf{u}^{\varepsilon}|_{t=0} = \mathbf{u}_0^{\varepsilon}, \qquad \mathbf{u}^{\varepsilon}|_{\partial\Omega} = 0.$$
(1.2)

At the continuous level, when ε tends to zero, the density ρ^{ε} tends to a constant and the velocity tends, in a sense to be defined, to a solution of the incompressible Navier-Stokes equations [41]. Heuristically, the momentum equation (1.1b) indicates that ρ^{ε} behaves like $\bar{\rho}(t) + \mathcal{O}(\varepsilon^{\frac{2}{\gamma}})$ where $\bar{\rho}(t)$ is a function only dependent on the time variable. Integrating the mass conservation equation (1.1a) over Ω and using the homogeneous Dirichlet boundary condition (1.2) (homogeneous Neumann condition suffice) then implies that $\bar{\rho}$ is actually a constant. For such a result to hold, some assumptions need to be made on the initial data; in particular, the initial density ρ_0^{ε} must be assumed to be close to $\bar{\rho}$ in a certain sense. These assumptions will be specified below. Setting $\bar{\rho} = 1$ (here and throughout the paper) without loss of generality, passing to the limit in the mass conservation equation (1.1a) and in the momentum balance (1.1b), the limit velocity \bar{u} is formally seen to solve the system of incompressible Navier-Stokes equations:

$$div(\bar{\boldsymbol{u}}) = 0,$$

$$\partial_t \bar{\boldsymbol{u}} + div(\bar{\boldsymbol{u}} \otimes \bar{\boldsymbol{u}}) - \mu \Delta \bar{\boldsymbol{u}} + \nabla \pi = 0,$$

^{*}I2M UMR 7373, Aix-Marseille Université, CNRS, École Centrale de Marseille. 39 rue Joliot Curie. 13453, Marseille, France. (raphaele.herbin@univ-amu.fr)

[†]Institut de Radioprotection et de Sûreté Nucléaire (IRSN) (jean-claude.latche@irsn.fr)

[‡]Université de Lyon, CNRS UMR 5208, Université Lyon 1, Institut Camille Jordan. 43 bd 11 novembre 1918; F-69622 Villeurbanne cedex, France. (saleh@math.univ-lyon1.fr)

where π is the formal limit of $(\wp(\rho^{\varepsilon}) - 1)/\varepsilon^2$. This formal computation has been justified by rigorous studies [41, 15, 16]. Actually, the mathematical analysis of the low Mach number limit begins with works [37, 17]. See also [44, 12, 20, 1, 19] for related works.

For numerical schemes, the issue is not so clear. Indeed, in the general case, schemes designed for computing compressible flows do not boil down, when $\varepsilon \to 0$, to standard schemes for incompressible flows, for essentially two reasons. First, the numerical dissipation introduced to stabilize the scheme depends on the celerity of acoustic waves, which blows up when $\varepsilon \to 0$; a reasonable approximation of the incompressible solution thus may need a very small space step, depending not only on the regularity of the continuous solution but also on ε . Second, these schemes are usually explicit in time (with a sophisticated derivation of fluxes, for instance through solutions of Riemann problems at interfaces, which lead to a nonlinear expression with respect to the unknowns), which is not compatible with a wave celerity blowing up in the incompressible limit; to cope with the low Mach number situation, an implicitation of some terms in the equations, usually the pressure gradient in the momentum balance equation and the mass fluxes divergence in the mass balance, is thus necessary, and this makes implicit-in-time discrete analogues of the wave equation for the pressure appear. Unfortunately, the schemes for the compressible case usually use a collocated arrangement of the unknowns (specially if one intends to compute the numerical fluxes on the basis of the solution of a Riemann problem at faces, which is well suited to a cell by cell piecewise constant approximation), and the diffusion operator appearing in this wave equation (obtained by a discrete composition of the pressure gradient and the velocity divergence operators) is unstable, since collocated approximations do not satisfy a form of the so-called discrete *inf-sup* condition. At the incompressible limit, the scheme thus will need an additional stabilization mechanism [45]. These phenomena have been widely studied and corrections have been proposed [49, 26, 25, 24, 14, 13, 10, 27, 46, 7, 57]. To obtain a scheme accurate for all Mach number flows, an alternative route consists in starting from technologies initially designed for incompressible Navier-Stokes equations and extending them to compressible flows. This approach may be traced back to the late sixties, when first attempts were done to build "all flow velocity" schemes [28, 29]; these algorithms may be seen as an extension to the compressible case of the celebrated MAC scheme, introduced some years before [30, 3]. These seminal papers have been the starting point for the development of numerous schemes falling in the class of pressure correction algorithms (see e.g. [8, 48, 23] for a presentation in the incompressible case), possibly iterative, in the spirit of the SIMPLE method, some of them based on staggered finite volume space discretizations [6, 34, 35, 52, 36, 43, 4, 56, 9, 50, 55, 54, 51, 53, 38]; a bibliography extended to the schemes using other space discretizations may be found in [32].

In this paper, we address, besides a purely implicit scheme, variants of schemes falling in this latter class, namely non-iterative pressure correction schemes based on staggered discretizations. These schemes have been developed in the last ten years, first for barotropic Euler and Navier-Stokes equations [31, 32] and then for the non-barotropic case [32, 22], and have been shown both theoretically and numerically to be consistent and accurate for Navier-Stokes and Euler equations and Mach number in the range of unity (including shock solutions in the inviscid cases). In addition, some numerical experiments [22] suggest that, when the Mach number tends to zero, the numerical solution tends to the solution of a standard scheme for incompressible or, in non-isothermal situations, quasi-incompressible (in the sense of the classical asymptotic model for low Mach numbers [42]) flows. Our aim here is to rigorously prove that, in the barotropic case, these schemes indeed are asymptotic preserving: for a given discretization (i.e. mesh and time step), when the Mach number tends to zero, the solution tends to the solution of a standard (stable and accurate) scheme for incompressible flows. To this purpose, we reproduce at the discrete level the analysis performed in the continuous case in [41] (of course, with heavy simplifications on compactness arguments, especially for the compactness of the sequence of discrete solutions for the velocity, since we work in a finite dimensional setting); to our knowledge, this is the first presentation of such a proof.

We address three different time-discretizations: first, a fully implicit scheme, because the convergence proof in this case is simpler and necessitates less restrictive assumptions on the initial data; then we turn to two variants which are more efficient in practice, namely two pressure correction schemes, which differ by the discretization of the convection term in the momentum balance equation, linearly implicit for the first one (so the corresponding scheme is unconditionally stable) and fully explicit for the second one (so the corresponding scheme is stable under a CFL condition based on the material velocity). This paper is organized as follows. First, for the reader convenience, we recall the (part of) the continuous analysis which is mimicked at the discrete level (Section 2). Then we define the meshes and unknowns used by the schemes (Section 3) and the space discretization of the operators involved in the balance equations (Section 4). The last three sections are devoted to the convergence analysis for the time-discretization

variants: the implicit scheme (Section 5) and the two pressure corrections schemes (Sections 6 and 7).

2. Incompressible limit in the continuous setting. The convergence when ε tends to zero of $(\rho^{\varepsilon}, \boldsymbol{u}^{\varepsilon})$, a weak solution to the initial value problem (1.1)-(1.2), is the purpose of various papers published in the late 90' [41, 15, 16]. In this section, we wish to recall some of the key arguments used in these works to pass to the limit when the Mach number vanishes, in the global weak solutions of (1.1)-(1.2).

The results proven in the above-mentioned papers on the convergence of $(\rho^{\varepsilon}, \boldsymbol{u}^{\varepsilon})$ towards a weak solution of the incompressible Navier-Stokes equations follow a two-step argument. The first step consists in deriving a priori bounds on the quantities $\rho^{\varepsilon} - 1$ and $\boldsymbol{u}^{\varepsilon}$ which are uniform with respect to ε . These bounds imply the strong convergence of ρ^{ε} towards $\bar{\rho} = 1$ in $L^{\infty}(L^{\gamma})$, and up to the extraction of a subsequence, the weak convergence in $L^{2}(H^{1})$ of $\boldsymbol{u}^{\varepsilon}$ towards some function $\bar{\boldsymbol{u}}$. The second step consists in passing to the limit in the weak formulation of problem (1.1)-(1.2) thanks to these convergence properties. The main difficulty in this passage to the limit lies within the term $\operatorname{div}(\rho^{\varepsilon}\boldsymbol{u}^{\varepsilon}\otimes\boldsymbol{u}^{\varepsilon})$ with only weak convergence of the velocity.

Subsequently, we describe the main arguments for obtaining the estimates on $\rho^{\varepsilon} - 1$ and \mathbf{u}^{ε} , which we will mimic at the discrete level in order to prove the asymptotic preserving feature of the staggered schemes in the low Mach number limit. However, we do not need a careful study of the nonlinear term since at the discrete level, *i.e.* for a fixed mesh, all the norms are equivalent and the boundedness of $(\mathbf{u}^{\varepsilon})_{\varepsilon>0}$ is enough to obtain convergence in any finite dimensional norm up to the extraction of a subsequence, and then to pass to the limit in the numerical scheme.

2.1. A priori estimates. We begin with recalling some key identities satisfied by the smooth solutions of (1.1), which are then incorporated in the definition of weak solutions.

PROPOSITION 2.1. Let ψ_{γ} be the function defined for $\rho > 0$ as $\psi_{\gamma}(\rho) = \rho \log \rho$ if $\gamma = 1$, and $\psi_{\gamma}(\rho) = \rho^{\gamma}/(\gamma - 1)$ if $\gamma > 1$ and define $\Pi_{\gamma}(\rho) = \psi_{\gamma}(\rho) - \psi_{\gamma}(1) - \psi_{\gamma}'(1)(\rho - 1)$. The smooth solutions of (1.1)-(1.2) satisfy the following identities:

• A kinetic energy balance:

$$\partial_t (\frac{1}{2} \rho^{\varepsilon} |\boldsymbol{u}^{\varepsilon}|^2) + \operatorname{div}(\frac{1}{2} \rho^{\varepsilon} |\boldsymbol{u}^{\varepsilon}|^2 |\boldsymbol{u}^{\varepsilon}|^2 |\boldsymbol{u}^{\varepsilon}) - \operatorname{div}(\boldsymbol{\tau}(\boldsymbol{u}^{\varepsilon})) \cdot \boldsymbol{u}^{\varepsilon} + \frac{1}{\varepsilon^2} |\boldsymbol{\nabla} \wp(\rho^{\varepsilon}) \cdot \boldsymbol{u}^{\varepsilon} = 0.$$
 (2.1)

• A renormalization identity

$$\partial_t \psi_{\gamma}(\rho^{\varepsilon}) + \operatorname{div}(\psi_{\gamma}(\rho^{\varepsilon}) \, \boldsymbol{u}^{\varepsilon}) + \wp(\rho^{\varepsilon}) \operatorname{div} \boldsymbol{u}^{\varepsilon} = 0. \tag{2.2}$$

• A "positive" renormalization identity:

$$\partial_t \Pi_\gamma(\rho^\varepsilon) + \operatorname{div}(\psi_\gamma(\rho^\varepsilon) \, \boldsymbol{u}^\varepsilon - \psi_\gamma'(1)\rho^\varepsilon \boldsymbol{u}^\varepsilon) + \wp(\rho^\varepsilon) \operatorname{div} \boldsymbol{u}^\varepsilon = 0. \tag{2.3}$$

• An entropy identity:

$$\partial_{t} \left(\frac{1}{2} \rho^{\varepsilon} |\boldsymbol{u}^{\varepsilon}|^{2}\right) + \frac{1}{\varepsilon^{2}} \partial_{t} \Pi_{\gamma}(\rho^{\varepsilon}) + \operatorname{div}\left(\left(\frac{1}{2} \rho^{\varepsilon} |\boldsymbol{u}^{\varepsilon}|^{2} + \frac{1}{\varepsilon^{2}} \psi_{\gamma}(\rho^{\varepsilon})\right) - \frac{1}{\varepsilon^{2}} \psi_{\gamma}'(1) \rho^{\varepsilon} + \frac{1}{\varepsilon^{2}} \wp(\rho^{\varepsilon})\right) \boldsymbol{u}^{\varepsilon} - \operatorname{div}(\boldsymbol{\tau}(\boldsymbol{u}^{\varepsilon})) \cdot \boldsymbol{u}^{\varepsilon} = 0. \quad (2.4)$$

Proof. The proof of (2.1) and (2.2) are classical. Multiplying the mass conservation equation (1.1a) by $-\psi'_{\gamma}(1)$ and summing with (2.2) yields (2.3). Summing (2.1) and $\varepsilon^{-2} \times (2.3)$ yields (2.4). \square

Remark 2.1. We call (2.3) a "positive" renormalization identity because the function Π_{γ} is positive thanks to the convexity of ψ_{γ} .

Integrating (2.4) over $\Omega \times (0, t)$ and recalling the homogeneous Dirichlet boundary conditions on the velocity, we obtain the following estimate on the solution pair $(\rho^{\varepsilon}, \mathbf{u}^{\varepsilon})$. For all $t \in (0, T)$:

$$\frac{1}{2} \int_{\Omega} \rho^{\varepsilon}(t) |\boldsymbol{u}^{\varepsilon}(t)|^{2} + \frac{1}{\varepsilon^{2}} \int_{\Omega} \Pi_{\gamma}(\rho^{\varepsilon}(t)) + \mu \int_{0}^{t} \|\boldsymbol{\nabla}\boldsymbol{u}^{\varepsilon}(s)\|_{L^{2}(\Omega)^{d \times d}}^{2} ds \\
+ (\mu + \lambda) \int_{0}^{t} \|\operatorname{div}(\boldsymbol{u}^{\varepsilon}(s))\|_{L^{2}(\Omega)}^{2} ds = \frac{1}{2} \int_{\Omega} \rho_{0}^{\varepsilon} |\boldsymbol{u}_{0}^{\varepsilon}|^{2} + \frac{1}{\varepsilon^{2}} \int_{\Omega} \Pi_{\gamma}(\rho_{0}^{\varepsilon}). \quad (2.5)$$

2.2. Asymptotic behavior of the density and velocity in the zero Mach limit. The global entropy estimate (2.5) is thus proven for any strong solution of the boundary and initial value problem (1.1)-(1.2). In the following, we always assume the existence of a weak solution $(\rho^{\varepsilon}, \mathbf{u}^{\varepsilon})$ to problem (1.1)-(1.2) satisfying the following inequality:

$$\frac{1}{2} \int_{\Omega} \rho^{\varepsilon}(t) |\boldsymbol{u}^{\varepsilon}(t)|^{2} + \frac{1}{\varepsilon^{2}} \int_{\Omega} \Pi_{\gamma}(\rho^{\varepsilon}(t)) + \mu \int_{0}^{t} ||\boldsymbol{\nabla}\boldsymbol{u}^{\varepsilon}(s)||_{\mathbf{L}^{2}(\Omega)^{d \times d}}^{2} \mathrm{d}s \leq \frac{1}{2} \int_{\Omega} \rho_{0}^{\varepsilon} ||\boldsymbol{u}_{0}^{\varepsilon}|^{2} + \frac{1}{\varepsilon^{2}} \int_{\Omega} \Pi_{\gamma}(\rho_{0}^{\varepsilon}). \quad (2.6)$$

In particular, we assume that all the integrals involved in (2.6) are convergent.

Estimate (2.6) allows to prove the convergence of ρ^{ε} towards 1 in $L^{\infty}((0,T);L^{\gamma}(\Omega))$ provided that the right hand side, which depends on the initial conditions is uniformly bounded with respect to ε . We show in the following that it is indeed the case provided some assumptions on the initial data.

We begin with proving the following lemma, which states crucial properties of the function Π_{γ} . LEMMA 2.2. The function Π_{γ} has the following lower bounds:

• For all
$$\gamma \ge 1$$
 and $\delta > 0$, there exists $C_{\gamma,\delta} > 0$ such that:

$$\Pi_{\gamma}(\rho) \ge C_{\gamma,\delta} |\rho - 1|^{\gamma}, \quad \forall \rho > 0 \text{ with } |\rho - 1| \ge \delta,$$
(2.7a)

• If
$$\gamma \ge 2$$
 then $\Pi_{\gamma}(\rho) \ge |\rho - 1|^2$, $\forall \rho > 0$. (2.7b)

• If
$$\gamma \in [1,2)$$
 then for all $R \in (2,+\infty)$, there exists $C_{\gamma,R}$ such that:

$$\Pi_{\gamma}(\rho) \geq C_{\gamma,R} |\rho - 1|^2, \quad \forall \rho \in (0,R),$$

$$\Pi_{\gamma}(\rho) \geq C_{\gamma,R} |\rho - 1|^{\gamma}, \quad \forall \rho \in [R,\infty).$$
(2.7c)

Moreover, the function Π_{γ} has the following upper bound (for small densities): For all $\gamma \geq 1$ there exists C_{γ} such that:

$$\Pi_{\gamma}(\rho) \le C_{\gamma} |\rho - 1|^2, \ \forall \rho \in (0, 2). \tag{2.8}$$

Proof. For $\gamma=1$, we have $\Pi_1=\rho\log\rho-\rho$. Hence $\Pi_1\sim\rho\log\rho$ for large values of ρ which implies (2.7a). Similarly, for $\gamma>1$, we have $\Pi_{\gamma}(\rho)=\psi_{\gamma}(\rho)-\psi_{\gamma}(1)-\psi_{\gamma}'(1)(\rho-1)=(\gamma-1)^{-1}(\rho^{\gamma}-1-\gamma(\rho-1))$, thus $\Pi_{\gamma}(\rho)\sim(\gamma-1)^{-1}\rho^{\gamma}$ for large values of ρ which proves (2.7a). The second order Taylor expansion of ψ_{γ} yields, for all $\gamma\geq 1$:

$$\Pi_{\gamma}(\rho) = |\rho - 1|^2 \gamma \int_0^1 (1 + s(\rho - 1))^{\gamma - 2} (1 - s) ds, \quad \text{for all} \quad \rho \in (0, +\infty).$$

The case $\gamma \geq 2$ is straightforward and we obtain $|\rho-1|^2 \leq \Pi_{\gamma}(\rho)$ for all $\rho \in (0, +\infty)$ and $\Pi_{\gamma}(\rho) \leq C_{\gamma}|\rho-1|^2$ for all $\rho \leq 2$ with $C_{\gamma} = \gamma \int_0^1 (1+s)^{\gamma-2} (1-s) ds$. For $1 \leq \gamma < 2$, we easily get $\Pi_{\gamma}(\rho) \leq |\rho-1|^2$ for all $\rho \in (0, +\infty)$ and the lower bound is obtained by separating the case $\rho < R$ and $\rho \geq R$. We obtain the expected lower bound (2.7c) with

$$C_{\gamma,R} = \gamma \int_0^1 \frac{1-s}{(1+s(R-1))^{2-\gamma}} ds.$$

П

Let us now assume that the initial data is "ill-prepared": $\rho_0^{\varepsilon} \in L^{\infty}(\Omega)$ with $\rho_0^{\varepsilon} > 0$ for a.e. $\boldsymbol{x} \in \Omega$, $\boldsymbol{u}_0^{\varepsilon} \in L^2(\Omega)^d$ and there exists C independent of ε such that:

$$\|\boldsymbol{u}_0^{\varepsilon}\|_{\mathrm{L}^2(\Omega)^d} + \frac{1}{\varepsilon} \|\rho_0^{\varepsilon} - 1\|_{\mathrm{L}^{\infty}(\Omega)} \leq C.$$
 (2.9)

This relation implies that ρ_0^{ε} tends to 1 in $L^{\infty}(\Omega)$ when $\varepsilon \to 0$; moreover, we suppose that $\boldsymbol{u}_0^{\varepsilon}$ weakly converges in $L^2(\Omega)^d$ towards a function $\bar{\boldsymbol{u}}_0 \in L^2(\Omega)^d$. The initial data is said to be "ill-prepared" since $\rho_0^{\varepsilon} - 1$ behaves like ε and not like $\varepsilon^{\frac{2}{\gamma}}$ (or ε^2) as suggested by the momentum equation, and the initial velocity is *not required* to be close to a diverge free velocity.

Under assumption (2.9), an easy consequence of the upper bound (2.8) on Π_{γ} is that the right-hand side of the estimate (2.6) is bounded independently of the Mach number ε . We then obtain that for any weak solution $(\rho^{\varepsilon}, \boldsymbol{u}^{\varepsilon})$ to (1.1)-(1.2) that satisfies the global entropy estimate (2.6), the velocity $\boldsymbol{u}^{\varepsilon}$ is bounded in $L^{2}((0,T); H_{0}^{1}(\Omega)^{d})$ uniformly with respect to ε .

A further consequence of the lower bound (2.7a) on Π_{γ} is the convergence of ρ^{ε} towards 1 as $\varepsilon \to 0$ in $L^{\infty}(L^{\gamma}(\Omega))$ as stated in the following proposition.

PROPOSITION 2.3. Let, $(\rho_0^{\varepsilon}, \mathbf{u}_0^{\varepsilon})$ be a family of ill-prepared initial data and let $(\rho^{\varepsilon}, \mathbf{u}^{\varepsilon})$ be a corresponding family of weak solutions of (1.1)-(1.2) that satisfy the global entropy estimate (2.6). Then, ρ^{ε} converges towards 1 as $\varepsilon \to 0$ in $L^{\infty}(L^{\gamma}(\Omega))$.

Proof. By (2.7a) and estimate (2.6), we have for all $\delta > 0$, and t > 0:

$$\|\rho^{\varepsilon}(t) - 1\|_{\mathcal{L}^{\gamma}(\Omega)}^{\gamma} \le |\Omega| \, \delta^{\gamma} + \int_{\Omega} |\rho^{\varepsilon}(t) - 1|^{\gamma} \, \mathcal{X}_{\{|\rho^{\varepsilon} - 1| \ge \delta\}} \le |\Omega| \, \delta^{\gamma} + \frac{C \, \varepsilon^{2}}{C_{\gamma, \delta}}.$$

Hence, $\limsup_{\varepsilon \to 0} \|\rho^{\varepsilon} - 1\|_{L^{\infty}((0,T);L^{\gamma}(\Omega))} \le |\Omega|^{\frac{1}{\gamma}} \delta$ for all $\delta > 0$, which concludes the proof. \square

The following proposition provides a rate of convergence in $L^{\infty}(L^{q}(\Omega))$ for ρ^{ε} towards 1 as soon as $q \in [1, \min(2, \gamma)]$.

PROPOSITION 2.4. Let, $(\rho_0^{\varepsilon}, \mathbf{u}_0^{\varepsilon})$ be a family of ill-prepared initial data and let $(\rho^{\varepsilon}, \mathbf{u}^{\varepsilon})$ be a corresponding family of weak solutions of (1.1)-(1.2) that satisfy the global entropy estimate (2.6). Then, the following estimates hold.

• If $\gamma \geq 2$, then there exists C > 0 such that, for ε small enough:

$$\|\rho^{\varepsilon} - 1\|_{\mathcal{L}^{\infty}((0,T);\mathcal{L}^{2}(\Omega))} \le C\varepsilon.$$

• If $1 \le \gamma \le 2$, then for ε small enough, for all $R \in (2, +\infty)$, there exists $C_R > 0$ such that:

$$\varepsilon^{-1} \| (\rho^{\varepsilon} - 1) \mathcal{X}_{\{\rho^{\varepsilon} < R\}} \|_{L^{\infty}((0,T);L^{2}(\Omega))} + \varepsilon^{-\frac{2}{\gamma}} \| (\rho^{\varepsilon} - 1) \mathcal{X}_{\{\rho^{\varepsilon} \geq R\}} \|_{L^{\infty}((0,T);L^{\gamma}(\Omega))} \le C_{R}.$$

As a consequence, for all $q \in [1, \min(2, \gamma)]$, there exists C > 0 such that for ε small enough:

$$\|\rho^{\varepsilon} - 1\|_{L^{\infty}((0,T);L^{q}(\Omega))} \le C\varepsilon.$$

Proof. As already stated, thanks to (2.9) and using the upper bound on $\Pi_{\gamma}(\rho)$ for small values of ρ , for ε small enough, the right hand side of (2.6) is bounded by some constant C_0 , independent of ε . We now use the lower bounds on $\Pi_{\gamma}(\rho)$. For $\gamma \geq 2$, by Lemma 2.2 combined with estimate (2.6), we have for all $t \in (0,T)$:

$$\|\rho^{\varepsilon}(t) - 1\|_{\mathrm{L}^{2}(\Omega)}^{2} \le \int_{\Omega} \Pi_{\gamma}(\rho^{\varepsilon}(t)) \le C_{0} \varepsilon^{2}.$$

For $1 \le \gamma < 2$, invoking once again Lemma 2.2 and estimate (2.6), we obtain for all $t \in (0,T)$ and for all $R \in (2,+\infty)$:

$$(i) \qquad \|(\rho^{\varepsilon}(t) - 1)\mathcal{X}_{\{\rho^{\varepsilon}(t) \leq R\}}\|_{\mathrm{L}^{2}(\Omega)}^{2} \leq \frac{1}{C_{\gamma,R}} \int_{\Omega} \Pi_{\gamma}(\rho^{\varepsilon}(t)) \leq C \varepsilon^{2},$$

$$(ii) \qquad \|(\rho^{\varepsilon}(t) - 1)\mathcal{X}_{\{\rho^{\varepsilon}(t) \geq R\}}\|_{L^{\gamma}(\Omega)}^{\gamma} \leq \frac{1}{C_{\gamma,R}} \int_{\Omega} \Pi_{\gamma}(\rho^{\varepsilon}(t)) \leq C \varepsilon^{2},$$

which concludes the proof. \square

- 3. Meshes and unknowns. Definition 3.1 (Staggered mesh). A staggered discretization of Ω , denoted by \mathcal{T} , is given by a couple $\mathcal{T} = (\mathcal{M}, \mathcal{E})$, where:
 - \mathcal{M} , the primal mesh, is a finite family composed of non empty triangles and convex quadrilaterals for d=2 or non empty tetrahedra and convex hexahedra for d=3. The primal mesh \mathcal{M} is assumed to form a partition of $\Omega:\overline{\Omega}=\cup_{K\in\mathcal{M}}\overline{K}$. For any $K\in\mathcal{M}$, let $\partial K=\overline{K}\setminus K$ be the boundary of K, which is the union of cell faces. We denote by \mathcal{E} the set of faces of the mesh, and we suppose that two neighbouring cells share a whole face: for all $\sigma\in\mathcal{E}$, either $\sigma\subset\partial\Omega$ or there exists $(K,L)\in\mathcal{M}^2$ with $K\neq L$ such that $\overline{K}\cap\overline{L}=\overline{\sigma}$; we denote in the latter case $\sigma=K|L$. We denote by $\mathcal{E}_{\rm ext}$ and $\mathcal{E}_{\rm int}$ the set of external and internal faces: $\mathcal{E}_{\rm ext}=\{\sigma\in\mathcal{E},\sigma\subset\partial\Omega\}$ and $\mathcal{E}_{\rm int}=\mathcal{E}\setminus\mathcal{E}_{\rm ext}$. For $K\in\mathcal{M}$, $\mathcal{E}(K)$ stands for the set of faces of K. The unit vector normal to $\sigma\in\mathcal{E}(K)$ outward K is denoted by $\mathbf{n}_{K,\sigma}$. In the following, the notation |K| or $|\sigma|$ stands indifferently for the d-dimensional or the (d-1)-dimensional measure of the subset K of \mathbb{R}^d or σ of \mathbb{R}^{d-1} respectively.

• We define a dual mesh associated with the faces $\sigma \in \mathcal{E}$ as follows. When $K \in \mathcal{M}$ is a simplex, a rectangle or a cuboid, for $\sigma \in \mathcal{E}(K)$, we define $D_{K,\sigma}$ as the cone with basis σ and with vertex the mass center of K (see Figure 3.1). We thus obtain a partition of K in m sub-volumes, where m is the number of faces of K, each sub-volume having the same measure $|D_{K,\sigma}| = |K|/m$. We extend this definition to general quadrangles and hexahedra, by supposing that we have built a partition still of equal-volume sub-cells, and with the same connectivities. The volume $D_{K,\sigma}$ is referred to as the half-diamond cell associated with K and σ . For $\sigma \in \mathcal{E}_{int}$, $\sigma = K|L$, we now define the diamond cell D_{σ} associated with σ by $D_{\sigma} = D_{K,\sigma} \cup D_{L,\sigma}$. We denote by $\bar{\mathcal{E}}(D_{\sigma})$ the set of faces of D_{σ} , and by $\varepsilon = D_{\sigma}|D_{\sigma'}$ the face separating two diamond cells D_{σ} and $D_{\sigma'}$. As for the primal mesh, we denote by $\bar{\mathcal{E}}_{int}$ the set of dual faces included in the domain and by $\bar{\mathcal{E}}_{ext}$ the set of dual faces lying on the boundary $\partial \Omega$. In this latter case, there exists $\sigma \in \mathcal{E}_{ext}$ such that $\varepsilon = \sigma$.

Relying on this definition, we now define a staggered space discretization. The degrees of freedom for the density (*i.e.* the discrete density unknowns) are associated with the cells of the mesh \mathcal{M} , and are denoted by:

$$\{\rho_K, K \in \mathcal{M}\},\$$

while the degrees of freedom for the velocity are located at the center of the faces of the mesh \mathcal{M} and are therefore associated with the cells of the dual mesh D_{σ} , $\sigma \in \mathcal{E}$ (as in the low-degree nonconforming finite-element discretizations proposed in [11, 47]). The Dirichlet boundary conditions are taken into account by setting the velocity unknowns associated with an external face to zero, so the set of discrete velocity unknowns reads:

$$\{\boldsymbol{u}_{\sigma} \in \mathbb{R}^d, \ \sigma \in \mathcal{E}_{\mathrm{int}}\}.$$

We associate functions with the discrete unknowns of the schemes described hereinafter. To this purpose, we define the following sets of discrete functions of the space variable.

DEFINITION 3.2 (Discrete functional spaces). Let $\mathcal{T} = (\mathcal{M}, \mathcal{E})$ be a staggered discretization of Ω as defined in Definition 3.1.

• We denote by $L_{\mathcal{M}}(\Omega) \subset L^{\infty}(\Omega)$ the space of scalar functions which are piecewise constant on each primal mesh cell $K \in \mathcal{M}$. For all $w \in L_{\mathcal{M}}(\Omega)$ and for all $K \in \mathcal{M}$, we denote by w_K the constant value of w in K, so the function w reads:

$$w(x) = \sum_{K \in \mathcal{M}} w_K \mathcal{X}_K(x)$$
 for a.e. $x \in \Omega$,

where \mathcal{X}_K stands for the characteristic function of K.

• We denote by $H_{\mathcal{E}}(\Omega) \subset L^{\infty}(\Omega)$ the space of scalar functions which are piecewise constant on each diamond cell of the dual mesh D_{σ} , $\sigma \in \mathcal{E}$. For all $u \in H_{\mathcal{E}}(\Omega)$ and for all $\sigma \in \mathcal{E}$, we denote by u_{σ} the constant value of u in D_{σ} , so the function u reads:

$$u(\boldsymbol{x}) = \sum_{\sigma \in \mathcal{E}} u_{\sigma} \, \mathcal{X}_{D_{\sigma}}(\boldsymbol{x}) \quad \text{for a.e. } \boldsymbol{x} \in \Omega,$$

where $\mathcal{X}_{D_{\sigma}}(\boldsymbol{x})$ stands for the characteristic function of D_{σ} . We denote by $\mathbf{H}_{\mathcal{E}}(\Omega) = \mathrm{H}_{\mathcal{E}}(\Omega)^d$ the space of vector valued (in \mathbb{R}^d) functions that are constant on each diamond cell D_{σ} . Finally, we denote $\mathrm{H}_{\mathcal{E},0}(\Omega) = \{u \in \mathrm{H}_{\mathcal{E}}(\Omega), u_{\sigma} = 0 \text{ for all } \sigma \in \mathcal{E}_{\mathrm{ext}}\}$ and $\mathbf{H}_{\mathcal{E},0}(\Omega) = \mathrm{H}_{\mathcal{E},0}(\Omega)^d$.

- **4. Space discretization.** This section is devoted to the construction of the discrete space differential operators that approximate the differential operators in (1.1). As already said, the discretization is staggered. The discrete operators involved in the discretization of the mass equation (1.1a) are thus associated with the cells of the primal mesh $K, K \in \mathcal{M}$, while the discrete operators involved in the discretization of the momentum equation (1.1b) are associated with the cells of the dual mesh $D_{\sigma}, \sigma \in \mathcal{E}_{int}$.
- **4.1.** Mass convection flux. The discretization of the convection term $\operatorname{div}(\rho u)$ in the mass conservation equation is defined as follows. Given a discrete density field $\rho \in L_{\mathcal{M}}(\Omega)$ and a velocity field $u \in H_{\mathcal{E},0}(\Omega)$, it is a piecewise constant function on each primal cell $K \in \mathcal{M}$ given by:

$$\operatorname{div}(\rho \boldsymbol{u})_{K} = \frac{1}{|K|} \sum_{\sigma \in \mathcal{E}(K)} F_{K,\sigma}(\rho, \boldsymbol{u}), \qquad \forall K \in \mathcal{M}.$$
(4.1)




Fig. 3.1. Notations for control volumes and dual cells.

The quantity $F_{K,\sigma}(\rho, \mathbf{u})$ stands for the mass flux across σ outward K. By the impermeability boundary conditions, it vanishes on external faces and is given on internal faces by:

$$F_{K,\sigma}(\rho, \mathbf{u}) = |\sigma| \ \rho_{\sigma} \ \mathbf{u}_{\sigma} \cdot \mathbf{n}_{K,\sigma}, \qquad \forall \sigma \in \mathcal{E}_{\text{int}}, \ \sigma = K|L.$$

$$(4.2)$$

The density at the face $\sigma = K|L$ is approximated by the upwind technique, i.e. $\rho_{\sigma} = \rho_{K}$ if $\mathbf{u}_{\sigma} \cdot \mathbf{n}_{K,\sigma} \geq 0$ and $\rho_{\sigma} = \rho_{L}$ otherwise.

4.2. Velocity convection operator. We now describe the approximation of the convection operator $\partial_t(\rho \boldsymbol{u}) + \operatorname{div}(\rho \boldsymbol{u} \otimes \boldsymbol{u})$ appearing in the momentum balance equation. The approximation of the time derivative part $\partial_t(\rho \boldsymbol{u})$ is naturally discretized at the dual cells D_{σ} , $\sigma \in \mathcal{E}_{\text{int}}$ and an approximation $\rho_{D_{\sigma}}$ of the density on these dual cells D_{σ} is thus needed. Given a density field $\rho \in L_{\mathcal{M}}(\Omega)$, this approximation is built as follows:

$$|D_{\sigma}| \rho_{D_{\sigma}} = |D_{K,\sigma}| \rho_K + |D_{L,\sigma}| \rho_L, \qquad \forall \sigma \in \mathcal{E}_{int}, \ \sigma = K|L. \tag{4.3}$$

In order to consider different time discretizations, we build a space discretization of a more general divergence part of the velocity convection operator, $\operatorname{div}(\rho \boldsymbol{u} \otimes \boldsymbol{v})$. Given a discrete density field $\rho \in L_{\mathcal{M}}(\Omega)$, and two discrete velocity fields $\boldsymbol{u} \in \mathbf{H}_{\mathcal{E},0}(\Omega)$ and $\boldsymbol{v} \in \mathbf{H}_{\mathcal{E},0}(\Omega)$, this approximation is built as follows:

$$\operatorname{\mathbf{div}}(\rho \boldsymbol{u} \otimes \boldsymbol{v})_{\sigma} = \frac{1}{|D_{\sigma}|} \sum_{\varepsilon \in \bar{\mathcal{E}}(D_{\sigma})} F_{\sigma,\varepsilon}(\rho, \boldsymbol{u}) \ \boldsymbol{v}_{\varepsilon}, \qquad \forall \sigma \in \mathcal{E}_{\mathrm{int}}.$$

$$(4.4)$$

 $F_{\sigma,\varepsilon}(\rho, \boldsymbol{u})$ is the mass flux across the edge ε of the dual cell D_{σ} . Its value is zero if $\varepsilon \in \bar{\mathcal{E}}_{\mathrm{ext}}$. Otherwise, it is defined as a linear combination, with constant coefficients, of the primal mass fluxes at the neighboring faces. For $K \in \mathcal{M}$ and $\sigma \in \mathcal{E}(K)$, let ξ_K^{σ} be given by:

$$\xi_K^{\sigma} = \frac{|D_{K,\sigma}|}{|K|},$$

so that $\sum_{\sigma \in \mathcal{E}(K)} \xi_K^{\sigma} = 1$. With the definition of the dual mesh adopted here, the value of the coefficients ξ_K^{σ} only depend on the type of the cell K (simplicial or quandrangular/hexahedral). For the quadrangular and hexahedral elements, we have $\xi_K^{\sigma} = 1/(2d)$ and, for the simplicial elements, $\xi_K^{\sigma} = 1/(d+1)$. We suppose first that the flux through the external dual faces, which are also faces of the primal mesh, is equal to zero. Then the mass fluxes through the inner dual faces are supposed to satisfy the following properties.

(H1) The discrete mass balance over the half-diamond cells is satisfied, in the following sense. For all primal cell K in \mathcal{M} , the set $(F_{\sigma,\varepsilon}(\rho, \boldsymbol{u}))_{\varepsilon \subset K}$ of dual fluxes included in K solves the following linear system

$$F_{K,\sigma}(\rho, \boldsymbol{u}) + \sum_{\varepsilon \in \bar{\mathcal{E}}(D_{\sigma}), \ \varepsilon \subset K} F_{\sigma,\varepsilon}(\rho, \boldsymbol{u}) = \xi_K^{\sigma} \sum_{\sigma' \in \mathcal{E}(K)} F_{K,\sigma'}(\rho, \boldsymbol{u}), \quad \sigma \in \mathcal{E}(K).$$
 (4.5)

- (H2) The dual fluxes are conservative, *i.e.* for any dual face $\varepsilon = D_{\sigma}|D'_{\sigma}$, we have $F_{\sigma,\varepsilon}(\rho, \mathbf{u}) = -F_{\sigma',\varepsilon}(\rho, \mathbf{u})$.
- (H3) The dual fluxes are bounded with respect to the primal fluxes $(F_{K,\sigma}(\rho, \boldsymbol{u}))_{\sigma \in \mathcal{E}(K)}$, in the sense that

$$|F_{\sigma,\epsilon}(\rho, \boldsymbol{u})| \le \max\{|F_{K,\sigma'}(\rho, \boldsymbol{u})|, \ \sigma' \in \mathcal{E}(K)\},$$
 (4.6)

for
$$K \in \mathcal{M}$$
, $\sigma \in \mathcal{E}(K)$, $\epsilon \in \bar{\mathcal{E}}(D_{\sigma})$ with $\varepsilon \subset K$.

The system of equations (4.5) only depends on the type of the cell K (since it only depends on the coefficient ξ_K^{σ} , which is chosen as the inverse of the number of cell faces, and sub-cell connectivities) but has an infinite number of solutions, which makes necessary to impose in addition the constraint (4.6); however, assumptions (H1)-(H3) are sufficient for the subsequent developments, in the sense that any choice for the expression of the fluxes satisfying these assumptions yields stable and consistent schemes (see [40, 39]).

To complete the definition of the convective flux, we just have now to give the expression of the velocity v_{ε} at the dual face. As already said, a dual face lying on the boundary is also a primal face, and the flux across that face is zero. Therefore, the values v_{ε} are only needed at the internal dual faces; we choose them to be centered:

$$v_{\varepsilon} = \frac{1}{2}(v_{\sigma} + v_{\sigma'}), \quad \text{for } \varepsilon = D_{\sigma}|D'_{\sigma}.$$

4.3. Diffusion term. The space discretization of the diffusion term $\operatorname{\mathbf{div}}(u)$ in the momentum equation relies on the Crouzeix-Raviart element for the simplicial cells K and on the *parametric* Rannacher-Turek (or rotated bilinear) element for quadrangular or hexahedral cells (see [47]). Let \mathbb{P}_K be the affine transformation between the reference unit simplex and the simplicial cell K. The space of discrete functions over a simplicial cell K is

$$P_1(K) = \{ f \circ \mathbb{P}_K^{-1}, \text{ with } f \in \text{span } \{1, (x_i)_{i=1,\dots,d} \} \}.$$

Let \mathbb{Q}_K be the standard Q_1 mapping between the reference unit cuboid and the quadrangular or hexahedral cell K. The space of discrete functions over such a cell is

$$\tilde{Q}_1(K) = \left\{ f \circ \mathbb{Q}_K^{-1}, \text{ with } f \in \text{span} \left\{ 1, (x_i)_{i=1,\dots,d}, (x_i^2 - x_{i+1}^2)_{i=1,\dots,d-1} \right\} \right\}.$$

The shape functions are the functions ζ_{σ} , $\sigma \in \mathcal{E}$ such that for all $K \in \mathcal{M}$, $\zeta_{\sigma}|_{K} \in P_{1}(K)$ if K is a simplicial cell and $\zeta_{\sigma}|_{K} \in \tilde{Q}_{1}(K)$ if K is a quadrangular or hexahedral cell and which satisfy the following two conditions:

(i)
$$\int_{\sigma} [\zeta]_{\sigma}(\boldsymbol{x}) = 0, \text{ where } [\zeta]_{\sigma}(\boldsymbol{x}) = \lim_{\substack{\boldsymbol{y} \to \boldsymbol{x} \\ \boldsymbol{y} \in L}} \zeta(\boldsymbol{y}) - \lim_{\substack{\boldsymbol{y} \to \boldsymbol{x} \\ \boldsymbol{y} \in K}} \zeta(\boldsymbol{y}), \forall \boldsymbol{x} \in \sigma, \forall \sigma \in \mathcal{E}_{\text{int}}, \sigma = K|L.$$
 (4.7a)

(ii)
$$\frac{1}{|\sigma'|} \int_{\sigma'} \zeta_{\sigma}(\boldsymbol{x}) = \delta_{\sigma}^{\sigma'}, \quad \forall \sigma, \sigma' \in \mathcal{E},$$
 (4.7b)

with $\delta_{\sigma}^{\sigma'} = 1$ if $\sigma = \sigma'$ and $\delta_{\sigma}^{\sigma'} = 0$ otherwise. Note that condition (i) is consistent with a location of the degrees of freedom at the faces.

Now, with a discrete velocity field $\boldsymbol{u} \in \mathbf{H}_{\mathcal{E},0}(\Omega)$, one classically associates, in the finite element context, the function $\hat{\boldsymbol{u}}(\boldsymbol{x}) = \sum_{\sigma \in \mathcal{E}} \boldsymbol{u}_{\sigma} \zeta_{\sigma}(\boldsymbol{x})$. The discretization of the diffusion term is a piecewise constant function on each diamond cell D_{σ} , the value of which reads

$$\operatorname{div}\boldsymbol{\tau}(\boldsymbol{u})_{\sigma} = -\mu \left(\frac{1}{|D_{\sigma}|} \sum_{K \in \mathcal{M}} \int_{K} \boldsymbol{\nabla} \hat{\boldsymbol{u}} \cdot \boldsymbol{\nabla} \zeta_{\sigma}\right) - (\mu + \lambda) \left(\frac{1}{|D_{\sigma}|} \sum_{K \in \mathcal{M}} \int_{K} \operatorname{div}(\hat{\boldsymbol{u}}) \boldsymbol{\nabla} \zeta_{\sigma}\right). \tag{4.8}$$

The identification between $\mathbf{u} \in \mathbf{H}_{\mathcal{E},0}(\Omega)$ and $\hat{\mathbf{u}}$ allows to introduce the broken Sobolev H¹ semi-norm $\|.\|_{1,\mathcal{T}}$, given for any $\mathbf{u} \in \mathbf{H}_{\mathcal{E}}(\Omega)$ by:

$$\|\boldsymbol{u}\|_{1,\mathcal{T}}^2 = \sum_{K\in\mathcal{M}} \int_K \boldsymbol{\nabla} \hat{\boldsymbol{u}} : \boldsymbol{\nabla} \hat{\boldsymbol{u}} : \boldsymbol{\nabla} \hat{\boldsymbol{u}}.$$

The semi-norm $\|u\|_{1,\mathcal{T}}$ is in fact a norm on the space $\mathbf{H}_{\mathcal{E},0}(\Omega)$, thanks to a classical discrete Poincaré inequality.

As in the continuous setting, it is easily seen that the bilinear form derived from the discretization of the diffusion term controls the discrete H^1 -norm of the velocity as stated in the following lemma:

LEMMA 4.1 (Coercivity of the diffusion operator). For every discrete velocity field $\mathbf{u} \in \mathbf{H}_{\mathcal{E},0}(\Omega)$, one has:

$$\sum_{\mathcal{E} \in \mathcal{E}_{\mathrm{int}}} |D_{\sigma}| \ \boldsymbol{u}_{\sigma} \cdot \left(-\operatorname{\mathbf{div}} \boldsymbol{\tau}(\boldsymbol{u})_{\sigma} \right) \geq \mu \ \|\boldsymbol{u}\|_{1,\mathcal{T}}^{2}.$$

4.4. Pressure gradient term. The discretization of the pressure gradient term $\nabla \wp(\rho)$ is a piecewise constant function on each diamond cell D_{σ} , the value of which is denoted $(\nabla p)_{\sigma}$. For $\rho \in L_{\mathcal{M}}(\Omega)$, this term is defined as:

$$(\nabla p)_{\sigma} = \frac{|\sigma|}{|D_{\sigma}|} \left(\wp(\rho_L) - \wp(\rho_K) \right) \, \boldsymbol{n}_{K,\sigma}, \qquad \forall \sigma = K | L \in \mathcal{E}_{\text{int}}. \tag{4.9}$$

This pressure gradient is only defined at internal faces since, thanks to the impermeability boundary conditions, no momentum balance equation is written at the external faces.

The following discrete duality relation holds for all $\rho \in L_{\mathcal{M}}(\Omega)$ and $\mathbf{u} \in \mathbf{H}_{\mathcal{E},0}(\Omega)$:

$$\sum_{K \in \mathcal{M}} |K| \wp(\rho_K) \operatorname{div}(\boldsymbol{u})_K + \sum_{\sigma \in \mathcal{E}_{int}} |D_{\sigma}| \boldsymbol{u}_{\sigma} \cdot (\boldsymbol{\nabla} p)_{\sigma} = 0, \tag{4.10}$$

where we have set for all $K \in \mathcal{M}$, $\operatorname{div}(\boldsymbol{u})_K = |K|^{-1} \sum_{\sigma \in \mathcal{E}(K)} |\sigma| \boldsymbol{u}_{\sigma} \cdot \boldsymbol{n}_{K,\sigma}$ (consistently with (4.1) for $\rho \equiv 1$).

We finish this section with the following lemma which states that the staggered approximation is inf-sup stable.

LEMMA 4.2. There exists $\beta > 0$, depending only on Ω and on the mesh, such that for all $p = \{p_K, K \in \mathcal{M}\} \in L_{\mathcal{M}}(\Omega)$, there exists $\mathbf{u} \in \mathbf{H}_{\mathcal{E},0}$ satisfying:

$$\|u\|_{1,\mathcal{T}} = 1 \text{ and } \sum_{K \in \mathcal{M}} |K| \ p_K \operatorname{div}(u)_K \ge \beta \|p - m(p)\|_{L^2(\Omega)},$$

where $m(p) = |\Omega|^{-1} \sum_{K \in \mathcal{M}} |K| p_K$ is the mean value of p over Ω .

The *inf-sup* property is crucial when passing to the limit $\varepsilon \to 0$ in the various schemes presented thereafter. It indeed provides an L² control on the discrete (zero-mean) pressure through the control of its gradient.

In fact, the actual inf-sup stability condition states that the constant β only depends on the regularity of the mesh (in a sense to be defined), and not on the space step; this property, which is satisfied by low-order staggered discretizations, is inherited by the limit incompressible scheme and guarantees its stability and the fact that error estimates do not blow up when the mesh is refined. In this paper, since we work on a fixed discretization, the dependency of β with respect to the mesh does not need to be precisely stated.

5. Asymptotic analysis of the zero Mach limit for an implicit scheme. We begin with the analysis of the zero Mach limit for a fully implicit scheme. Let $\delta t > 0$ be a constant time step. The approximate solution $(\rho^n, \boldsymbol{u}^n) \in L_{\mathcal{M}}(\Omega) \times \mathbf{H}_{\mathcal{E},0}(\Omega)$ at time $t_n = n\delta t$ for $1 \leq n \leq N = \lfloor T/\delta t \rfloor$ is computed by induction through the following implicit scheme.

Knowing $(\rho^n, \boldsymbol{u}^n) \in L_{\mathcal{M}}(\Omega) \times \mathbf{H}_{\mathcal{E},0}(\Omega)$, solve for $\rho^{n+1} \in L_{\mathcal{M}}(\Omega)$ and $\boldsymbol{u}^{n+1} \in \mathbf{H}_{\mathcal{E},0}(\Omega)$:

$$\frac{1}{\delta t}(\rho_K^{n+1} - \rho_K^n) + \operatorname{div}(\rho^{n+1} \boldsymbol{u}^{n+1})_K = 0, \qquad \forall K \in \mathcal{M}, \qquad (5.1a)$$

$$\frac{1}{\delta t} \left(\rho_{D_{\sigma}}^{n+1} \boldsymbol{u}_{\sigma}^{n+1} - \rho_{D_{\sigma}}^{n} \boldsymbol{u}_{\sigma}^{n} \right) + \operatorname{\mathbf{div}}(\rho^{n+1} \boldsymbol{u}^{n+1} \otimes \boldsymbol{u}^{n+1})_{\sigma} \\
- \operatorname{\mathbf{div}} \boldsymbol{\tau}(\boldsymbol{u}^{n+1})_{\sigma} + \frac{1}{\varepsilon^{2}} (\boldsymbol{\nabla} p^{n+1})_{\sigma} = 0, \quad \forall \sigma \in \mathcal{E}_{\text{int}}. \tag{5.1b}$$

5.1. Initialization of the scheme. The initial approximations are given by the average of the initial density ρ_0^{ε} on the primal cells and the initial velocity u_0^{ε} on the dual cells:

$$\rho_K^0 = \frac{1}{|K|} \int_K \rho_0^{\varepsilon}, \qquad \forall K \in \mathcal{M},
\mathbf{u}_{\sigma}^0 = \frac{1}{|D_{\sigma}|} \int_{D_{\sigma}} \mathbf{u}_0^{\varepsilon}, \qquad \forall \sigma \in \mathcal{E}_{\text{int}}. \tag{5.2}$$

Thereafter, we prove that for every $\varepsilon > 0$, there exists a solution $(\rho^{\varepsilon}, \mathbf{u}^{\varepsilon})$ to the implicit scheme (5.1)-(5.2) and that for a fixed discretization, *i.e.* for a fixed mesh and a fixed time step δt , the solution $(\rho^{\varepsilon}, \mathbf{u}^{\varepsilon})$ converges as $\varepsilon \to 0$ towards the solution of an implicit scheme for the incompressible Navier-Stokes equations, which is stable thanks to the inf-sup condition.

Assumption on the initial data – For the convergence study performed in this section, it is sufficient to assume that the initial data is ill-prepared, in the sense of Inequality (2.9).

5.2. A priori estimates. We begin with a first lemma which states that the velocity convection operator defined in Section 4.2 is built so that if a discrete mass conservation equation is satisfied on the cells of the primal mesh (as in (5.1a)) - which is consistent with the staggered discretization - then a discrete mass conservation equation is also satisfied on each cell of the dual mesh (see [2] for a proof). Lemma 5.1. Let two density fields ρ^n , $\rho^{n+1} \in L_{\mathcal{M}}(\Omega)$ and a velocity field $\boldsymbol{u}^{n+1} \in \mathbf{H}_{\mathcal{E},0}(\Omega)$ satisfying

LEMMA 5.1. Let two density fields ρ^n , $\rho^{n+1} \in L_{\mathcal{M}}(\Omega)$ and a velocity field $\mathbf{u}^{n+1} \in \mathbf{H}_{\mathcal{E},0}(\Omega)$ satisfying the discrete mass conservation equation (5.1a) on every cell of the primal mesh be given. Then, the dual quantities $\{\rho_{D_{\sigma}}^{n}, \rho_{D_{\sigma}}^{n+1}, \sigma \in \mathcal{E}\}$ and the dual fluxes $\{F_{\sigma,\varepsilon}(\rho^{n+1}, \mathbf{u}^{n+1}), \sigma \in \mathcal{E}_{int}, \varepsilon \in \bar{\mathcal{E}}(D_{\sigma})\}$ satisfy a finite volume discretization of the mass balance (1.1a) over the internal dual cells:

$$\frac{|D_{\sigma}|}{\delta t} \left(\rho_{D_{\sigma}}^{n+1} - \rho_{D_{\sigma}}^{n} \right) + \sum_{\varepsilon \in \bar{\mathcal{E}}(D_{\sigma})} F_{\sigma,\varepsilon}(\rho^{n+1}, \boldsymbol{u}^{n+1}) = 0, \quad \forall \sigma \in \mathcal{E}_{\text{int}}.$$
 (5.3)

The following result states that any solution of the implicit scheme satisfies a discrete counterpart to the kinetic energy balance (2.1); its derivation relies on the previous relation, namely the dual mass balance (5.3).

LEMMA 5.2 (Discrete kinetic energy balance). Any solution to the implicit scheme (5.1) satisfies the following equality, for all $\sigma \in \mathcal{E}_{int}$, and $0 \le n \le N-1$:

$$\frac{1}{2\delta t} \left(\rho_{D_{\sigma}}^{n+1} |\boldsymbol{u}_{\sigma}^{n+1}|^{2} - \rho_{D_{\sigma}}^{n} |\boldsymbol{u}_{\sigma}^{n}|^{2} \right) + \frac{1}{2|D_{\sigma}|} \sum_{\varepsilon = D_{\sigma}|D_{\sigma}'} F_{\sigma,\varepsilon}(\rho^{n+1}, \boldsymbol{u}^{n+1}) \boldsymbol{u}_{\sigma}^{n+1} \cdot \boldsymbol{u}_{\sigma'}^{n+1} - \operatorname{div}\boldsymbol{\tau}(\boldsymbol{u}^{n+1})_{\sigma} \cdot \boldsymbol{u}_{\sigma}^{n+1} + \frac{1}{\varepsilon^{2}} (\boldsymbol{\nabla} p^{n+1})_{\sigma} \cdot \boldsymbol{u}_{\sigma}^{n+1} + R_{\sigma}^{n+1} = 0, \quad (5.4)$$

where $R_{\sigma}^{n+1} = \frac{1}{2\delta t} \rho_{D_{\sigma}}^{n} |\boldsymbol{u}_{\sigma}^{n+1} - \boldsymbol{u}_{\sigma}^{n}|^{2}$.

Proof. Let us take the scalar product of the discrete momentum balance equation (5.1b) by the corresponding velocity unknown $\boldsymbol{u}_{\sigma}^{n+1}$, which gives the relation $T_{\sigma}^{\text{conv}} - \operatorname{div} \boldsymbol{\tau}(\boldsymbol{u}^{n+1})_{\sigma} \cdot \boldsymbol{u}_{\sigma}^{n+1} + \frac{1}{\varepsilon^2} (\nabla p^{n+1})_{\sigma} \cdot \boldsymbol{u}_{\sigma}^{n+1} = 0$, with:

$$T_{\sigma}^{\text{conv}} = \left(\frac{1}{\delta t} \left(\rho_{D_{\sigma}}^{n+1} \boldsymbol{u}_{\sigma}^{n+1} - \rho_{D_{\sigma}}^{n} \boldsymbol{u}_{\sigma}^{n}\right) + \frac{1}{2|D_{\sigma}|} \sum_{\substack{\varepsilon \in \bar{\mathcal{E}}(D_{\sigma}) \\ \varepsilon = D_{\sigma}|D_{\sigma'}}} F_{\sigma,\varepsilon}(\rho^{n+1}, \boldsymbol{u}^{n+1}) \left(\boldsymbol{u}_{\sigma}^{n+1} + \boldsymbol{u}_{\sigma'}^{n+1}\right)\right) \cdot \boldsymbol{u}_{\sigma}^{n+1}.$$

Now, using the identity $2(\rho |\boldsymbol{a}|^2 - \rho^* \boldsymbol{a} \cdot \boldsymbol{b}) = \rho |\boldsymbol{a}|^2 - \rho^* |\boldsymbol{b}|^2 + \rho^* |\boldsymbol{a} - \boldsymbol{b}|^2 + (\rho - \rho^*) |\boldsymbol{a}|^2$ with $\rho = \rho_{D_{\sigma}}^{n+1}$, $\rho^* = \rho_{D_{\sigma}}^n$, $\boldsymbol{a} = \boldsymbol{u}_{\sigma}^{n+1}$ and $\boldsymbol{b} = \boldsymbol{u}_{\sigma}^n$, we obtain

$$\begin{split} T_{\sigma}^{\text{conv}} &= \frac{1}{2\delta t} \Big(\rho_{D_{\sigma}}^{n+1} |\boldsymbol{u}_{\sigma}^{n+1}|^2 - \rho_{D_{\sigma}}^{n} |\boldsymbol{u}_{\sigma}^{n}|^2 \Big) + \frac{1}{2|D_{\sigma}|} \sum_{\varepsilon = D_{\sigma}|D_{\sigma'}} F_{\sigma,\varepsilon}(\rho^{n+1}, \boldsymbol{u}^{n+1}) \; \boldsymbol{u}_{\sigma}^{n+1} \cdot \boldsymbol{u}_{\sigma'}^{n+1} \\ &+ \frac{1}{2\delta t} \; \rho_{D_{\sigma}}^{n} \; |\boldsymbol{u}_{\sigma}^{n+1} - \boldsymbol{u}_{\sigma}^{n}|^2 + \Big(\frac{1}{\delta t} \; (\rho_{D_{\sigma}}^{n+1} - \rho_{D_{\sigma}}^{n}) + |D_{\sigma}|^{-1} \sum_{\varepsilon \in \mathcal{E}(D_{\sigma})} F_{\sigma,\varepsilon}(\rho^{n+1}, \boldsymbol{u}^{n+1}) \Big) \; \frac{|\boldsymbol{u}_{\sigma}^{n+1}|^2}{2}. \end{split}$$

The last term is equal to zero thanks to (5.3), which concludes the proof. \square

We then prove that any solution of the implicit scheme satisfies a discrete counterpart of the renormalization identities (2.2) and (2.3) satisfied by any smooth solution of (1.1). To state this result, we need to extend the notation for divergence operators on the primal cells as follows. For $K \in \mathcal{M}$ and a smooth function φ ,

$$\operatorname{div}(\varphi(\rho) \mathbf{u})_{K} = \frac{1}{|K|} \sum_{\sigma \in \mathcal{E}(K)} |\sigma| \ \varphi(\rho_{\sigma}) \mathbf{u}_{\sigma} \cdot \mathbf{n}_{K,\sigma},$$

where ρ_{σ} stands for the upwind value of the density at the face.

LEMMA 5.3 (Discrete renormalization identities). Let ψ_{γ} be the function defined as $\psi_{\gamma}(\rho) = \rho \log \rho$ if $\gamma = 1$, and $\psi_{\gamma}(\rho) = \rho^{\gamma}/(\gamma - 1)$ if $\gamma > 1$ and define $\Pi_{\gamma}(\rho) = \psi_{\gamma}(\rho) - \psi_{\gamma}(1) - \psi_{\gamma}'(1)(\rho - 1)$. Then, any solution to the implicit scheme (5.1) satisfies the following two identities, for all $K \in \mathcal{M}$ and $0 \le n \le N-1$:

$$\frac{1}{\delta t} \left(\psi_{\gamma}(\rho_K^{n+1}) - \psi_{\gamma}(\rho_K^n) \right) + \operatorname{div}(\psi_{\gamma}(\rho^{n+1})\boldsymbol{u}^{n+1})_K + \wp(\rho_K^{n+1}) \operatorname{div}(\boldsymbol{u}^{n+1})_K + R_K^{n+1} = 0, \tag{5.5}$$

$$\frac{1}{\delta t} \left(\Pi_{\gamma}(\rho_K^{n+1}) - \Pi_{\gamma}(\rho_K^n) \right) + \operatorname{div} \left(\left(\psi_{\gamma}(\rho^{n+1}) - \psi_{\gamma}'(1) \rho^{n+1} \right) \boldsymbol{u}^{n+1} \right)_K + \wp(\rho_K^{n+1}) \operatorname{div} (\boldsymbol{u}^{n+1})_K + R_K^{n+1} = 0, \quad (5.6)$$

with:

$$R_K^{n+1} = \frac{1}{2\delta t} \psi_{\gamma}''(\bar{\rho}_K^{n+\frac{1}{2}}) \left(\rho_K^{n+1} - \rho_K^n\right)^2 + \frac{1}{2|K|} \sum_{\sigma = K|L} |\sigma| \left(\boldsymbol{u}_{\sigma}^{n+1} \cdot \boldsymbol{n}_{K,\sigma}\right)^- \psi_{\gamma}''(\bar{\rho}_{\sigma}^{n+1}) \left(\rho_L^{n+1} - \rho_K^{n+1}\right)^2,$$

where $\bar{\rho}_K^{n+\frac{1}{2}} \in [\min(\rho_K^{n+1}, \rho_K^n), \max(\rho_K^{n+1}, \rho_K^n)], \ \bar{\rho}_\sigma^{n+1} \in [\min(\rho_\sigma^{n+1}, \rho_K^{n+1}), \max(\rho_\sigma^{n+1}, \rho_K^{n+1})]$ for all $\sigma \in \mathcal{E}(K)$, and for $a \in \mathbb{R}$, $a^- \ge 0$ is defined by $a^- = -\min(a, 0)$. Since ψ_γ is a convex function, R_K^{n+1} is non-negative.

Proof. The proof of (5.5) is the same as that of [32, Lemma 3.2]. The equality (5.6) is obtained after multiplying the discrete mass equation (5.1a) by $-\psi'_{\gamma}(1)$ and summing with (5.5). \square

As a consequence of Lemmas 5.2 and 5.3, the implicit scheme satisfies a discrete counterpart of the local-in-time entropy identity (2.4).

LEMMA 5.4 (Local-in-time discrete entropy inequality, existence of a solution). Let $\varepsilon > 0$ and assume that the initial density ρ_0^{ε} is positive. Then, there exists a solution $(\rho^n, \mathbf{u}^n)_{0 \leq n \leq N}$ to the scheme (5.1), $\rho^n > 0$ for $0 \le n \le N$, and the following inequality holds for $0 \le n \le N-1$:

$$\frac{1}{2} \sum_{\sigma \in \mathcal{E}_{int}} |D_{\sigma}| \left(\rho_{D_{\sigma}}^{n+1} |\boldsymbol{u}_{\sigma}^{n+1}|^{2} - \rho_{D_{\sigma}}^{n} |\boldsymbol{u}_{\sigma}^{n}|^{2} \right) + \frac{1}{\varepsilon^{2}} \sum_{K \in \mathcal{M}} |K| \left(\Pi_{\gamma}(\rho_{K}^{n+1}) - \Pi_{\gamma}(\rho_{K}^{n}) \right) + \mu \, \delta t \, \|\boldsymbol{u}^{n+1}\|_{1,\mathcal{T}}^{2} + \mathcal{R}^{n+1} \leq 0, \tag{5.7}$$

where $\mathcal{R}^{n+1} = \sum_{\sigma \in \mathcal{E}_{int}} R_{\sigma}^{n+1} + \varepsilon^{-2} \sum_{K \in \mathcal{M}} R_K^{n+1} \ge 0$. Proof. The positivity of the density is a consequence of the properties of the upwind choice (4.2) for ρ [21, Lemma 2.1]. Let us then sum equation (5.4) over the faces $\sigma \in \mathcal{E}_{int}$, $\varepsilon^{-2} \times$ (5.6) over $K \in \mathcal{M}$, and, finally, the two obtained relations. Since the discrete gradient and divergence operators are dual with respect to the L^2 inner product (see (4.10)), noting that the conservative dual fluxes vanish in the summation and that the diffusion term is coercive (see Lemma 4.1), we get (5.7).

Given discrete density and velocity fields (ρ^n, u^n) , the existence of a solution (ρ^{n+1}, u^{n+1}) to the implicit scheme at the time step n+1 may be inferred by the Brouwer fixed point theorem, by an easy adaptation of the proof of [18, Proposition 5.2]. This proof relies on the following set of mesh-dependent estimates: the conservativity of the mass balance discretization, together with the fact that the density is positive, yields an estimate for ρ in the L¹-norm, and so, by a norm equivalence argument, of the pressure in any norm; then, for a given density ρ , the discrete global kinetic energy inequality (i.e. (5.4) summed over the control volumes) provides a control on the velocity. Therefore, computing ρ from the mass balance for fixed u, then p from ρ by the equation of state $\wp(\rho)$, and finally u from the momentum balance equation with fixed ρ , yields an iteration in a bounded convex subset of a finite dimensional

We may now prove that the solution of the implicit scheme satisfies a discrete counterpart of the global estimate (2.6).

LEMMA 5.5 (Global discrete entropy inequality). Let $\varepsilon > 0$ and assume that the initial data $(\rho_0^{\varepsilon}, \mathbf{u}_0^{\varepsilon})$ is ill-prepared in the sense of (2.9). By Lemma 5.4, there exists a solution $(\rho^n, \mathbf{u}^n)_{0 \le n \le N}$ to the scheme (5.1). In addition, there exists C>0 independent of ε such that, for ε small enough and for all $1\leq n\leq N$

$$\frac{1}{2} \sum_{\sigma \in \mathcal{E}_{int}} |D_{\sigma}| \ \rho_{D_{\sigma}}^{n} \ |\boldsymbol{u}_{\sigma}^{n}|^{2} + \mu \sum_{k=1}^{n} \delta t \ \|\boldsymbol{u}^{k}\|_{1,\mathcal{T}}^{2} + \frac{1}{\varepsilon^{2}} \sum_{K \in \mathcal{M}} |K| \Pi_{\gamma}(\rho_{K}^{n}) \leq C.$$
 (5.8)

Proof. Multiplying equation (5.7) by δt and summing over the time steps yields for $1 \leq n \leq N$:

$$\frac{1}{2} \sum_{\sigma \in \mathcal{E}_{int}} |D_{\sigma}| \; \rho_{D_{\sigma}}^{n} \; |\boldsymbol{u}_{\sigma}^{n}|^{2} + \mu \sum_{k=1}^{n} \delta t \; \|\boldsymbol{u}^{k}\|_{1,\mathcal{T}}^{2} + \frac{1}{\varepsilon^{2}} \sum_{K \in \mathcal{M}} |K| \, \Pi_{\gamma}(\rho_{K}^{n}) + \mathcal{R}^{n}$$

$$\leq \frac{1}{2} \sum_{\sigma \in \mathcal{E}_{int}} |D_{\sigma}| \; \rho_{D_{\sigma}}^{0} \; |\boldsymbol{u}_{\sigma}^{0}|^{2} + \frac{1}{\varepsilon^{2}} \sum_{K \in \mathcal{M}} |K| \, \Pi_{\gamma}(\rho_{K}^{0}), \quad (5.9)$$

with
$$\mathcal{R}^n = \sum_{k=0}^{n-1} \left(\sum_{\sigma \in \mathcal{E}_{int}} R_{\sigma}^{k+1} + \varepsilon^{-2} \sum_{K \in \mathcal{M}} R_K^{k+1} \right) \ge 0$$

with $\mathcal{R}^n = \sum_{k=0}^{n-1} \left(\sum_{\sigma \in \mathcal{E}_{int}} R_{\sigma}^{k+1} + \varepsilon^{-2} \sum_{K \in \mathcal{M}} R_K^{k+1} \right) \ge 0$. Let us prove that the right hand side of (5.9) is uniformly bounded for all ε small enough. By (2.9) and (5.2), for ε small enough, one has $\rho_K^0 \leq 2$ for all $K \in \mathcal{M}$ and therefore $\rho_{D_{\sigma}}^0 \leq 2$ for all $\sigma \in \mathcal{E}_{int}$, since the dual densities are convex combinations of the primal density unknowns. Hence, one has:

$$\frac{1}{2} \sum_{\sigma \in \mathcal{E}_{\mathrm{int}}} |D_{\sigma}| \; \rho_{D_{\sigma}}^{0} \; |\boldsymbol{u}_{\sigma}^{0}|^{2} \leq \sum_{\sigma \in \mathcal{E}_{\mathrm{int}}} |D_{\sigma}|^{-1} \Big| \int_{D_{\sigma}} \boldsymbol{u}_{0}^{\varepsilon} \Big|^{2} \leq \|\boldsymbol{u}_{0}^{\varepsilon}\|_{\mathrm{L}^{2}(\Omega)^{d}}^{2},$$

which by (2.9) is uniformly bounded with respect to ε . Then, using the upper bound on $\Pi_{\gamma}(\rho)$ for small values of ρ (see Lemma 2.2), we can see that the second term of the right hand side of (5.9) is uniformly bounded with respect to ε , for ε small enough. \square

LEMMA 5.6 (Control of the pressure). Let $\varepsilon > 0$ and assume that the initial density ρ_0^{ε} is positive and that the initial data $(\rho_0^{\varepsilon}, \mathbf{u}_0^{\varepsilon})$ is ill-prepared in the sense of (2.9). Then, there exists a solution $(\rho^n, \boldsymbol{u}^n)_{0 \leq n \leq N}$ to the scheme (5.1). Let $p^n = \wp(\rho^n)$ and define $\delta p^n = \{\delta p_K^n, K \in \mathcal{M}\}$ where $\delta p_K^n = (p_K^n - m(p^n))/\varepsilon^2$ with $m(p^n)$ the mean value of p^n over Ω (i.e. $m(p^n) = |\Omega|^{-1} \sum_{K \in \mathcal{M}} |K| p_K^n$). Then, one has, for all $1 \le n \le N$:

$$\|\delta p^n\| \le C_{\mathcal{T},\delta t},\tag{5.10}$$

where the real number $C_{\mathcal{T},\delta t}$ depends on the mesh and the time step but not on ε , and $\|\cdot\|$ stands for any norm on the space of discrete functions.

Proof. The staggered discretization satisfies the *inf-sup* condition (see Lemma 4.2), which implies that for $\delta p^n = (p^n - m(p^n))/\varepsilon^2$ there exists a discrete velocity field \mathbf{v} , with $\|\mathbf{v}\|_{1,\mathcal{T}} = 1$ and a positive real number β , depending only on Ω and on the mesh, such that:

$$\beta \|\delta p^n\|_{L^2(\Omega)} \le \sum_{K \in \mathcal{M}} |K| p_K^n \operatorname{div}(\boldsymbol{v})_K.$$

Hence by the gradient-divergence duality property (4.10), taking the scalar product of (5.1b) with $|D_{\sigma}| v_{\sigma}$ and summing over σ in \mathcal{E}_{int} , we get $\beta \|\delta p^n\|_{L^2(\Omega)} \leq T_1^n + T_2^n + T_3^n$ with:

$$T_1^n = rac{1}{\delta t} \sum_{\sigma \in \mathcal{E}_{\mathrm{int}}} |D_{\sigma}| \left(
ho_{D_{\sigma}}^n oldsymbol{u}_{\sigma}^n -
ho_{D_{\sigma}}^{n-1} oldsymbol{u}_{\sigma}^{n-1}
ight) \cdot oldsymbol{v}_{\sigma}, \ T_2^n = \sum_{\sigma \in \mathcal{E}_{\mathrm{int}}} |D_{\sigma}| \operatorname{\mathbf{div}}(
ho^n oldsymbol{u}^n \otimes oldsymbol{u}^n)_{\sigma} \cdot oldsymbol{v}_{\sigma}, \ T_3^n = -\sum_{\sigma \in \mathcal{E}_{\mathrm{int}}} |D_{\sigma}| \operatorname{\mathbf{div}} oldsymbol{ au}(oldsymbol{u}^n)_{\sigma} \cdot oldsymbol{v}_{\sigma}.$$

The proof of (5.10) follows if one is able to control each of these terms T_1^n , T_2^n and T_3^n independently of ε . Since the mesh and the time step δt are fixed, a norm equivalence argument in a finite dimensional space yields the existence of a positive function $C_{\mathcal{T},\delta t}$ depending on the discretization, which is non-decreasing in each of its variables, such that:

$$|T_1^n + T_2^n + T_3^n| \le C_{\mathcal{T},\delta t}(\|\rho^n\|_{L^1}, \|\rho^{n-1}\|_{L^1}, \|u^n\|_{1,\mathcal{T}}, \|u^{n-1}\|_{1,\mathcal{T}}, \|v\|_{1,\mathcal{T}}).$$

We have $\|\boldsymbol{v}\|_{1,\mathcal{T}} = 1$ and by the estimate (5.8), $\|\boldsymbol{u}^n\|_{1,\mathcal{T}}$ and $\|\boldsymbol{u}^{n-1}\|_{1,\mathcal{T}}$ are controlled independently of ε . In addition ρ^n and ρ^{n-1} are controlled in L¹ by conservativity of the discrete mass balance equation. \square

5.3. Incompressible limit of the implicit scheme. We may now state the main result of this section which is the convergence, up to a subsequence, of the compressible scheme (5.1) towards an implicit inf-sup stable incompressible scheme when the Mach number tends to zero.

THEOREM 5.7 (Asymptotic behavior of the implicit scheme). Let $(\varepsilon^{(m)})_{m\in\mathbb{N}}$ be a sequence of real numbers tending to zero, and let $(\rho^{(m)}, \mathbf{u}^{(m)})_{m\in\mathbb{N}}$ be a corresponding sequence of solutions of the scheme (5.1). Let us assume that the initial data $(\rho_0^{\varepsilon^{(m)}}, \mathbf{u}_0^{\varepsilon^{(m)}})$ is ill-prepared, i.e. satisfies Relation (2.9) for $m \in \mathbb{N}$. Then the sequence $(\rho^{(m)})_{m\in\mathbb{N}}$ tends to the constant function $\rho = 1$ when m tends to $+\infty$ in $L^{\infty}((0,T),L^{\gamma}(\Omega))$. Moreover, for all $q \in [1,\min(2,\gamma)]$, there exists C > 0 such that:

$$\|\rho^{(m)} - 1\|_{L^{\infty}((0,T);L^{q}(\Omega))} \le C\varepsilon^{(m)}, \quad \text{for } m \text{ large enough.}$$

In addition, the sequences $(\boldsymbol{u}^{(m)})_{m\in\mathbb{N}}$ and $(\delta p^{(m)})_{m\in\mathbb{N}}$ are bounded in any discrete norm which may depend on the fixed discretization. If a subsequence of $(\boldsymbol{u}^{(m)}, \delta p^{(m)})_{m\in\mathbb{N}}$ tends, in any discrete norm, to a limit $(\boldsymbol{u}, \delta p)$, then $(\boldsymbol{u}, \delta p)$ is a solution to the standard (Rannacher-Turek or Crouzeix-Raviart) implicit scheme for the barotropic incompressible Navier-Stokes equations:

Knowing $\delta p^n \in L_{\mathcal{M}}(\Omega)$ and $\mathbf{u}^n \in \mathbf{H}_{\mathcal{E},0}(\Omega)$, solve for $\delta p^{n+1} \in L_{\mathcal{M}}(\Omega)$ and $\mathbf{u}^{n+1} \in \mathbf{H}_{\mathcal{E},0}(\Omega)$:

$$\operatorname{div}(\boldsymbol{u}^{n+1})_K = 0, \qquad \forall K \in \mathcal{M}, \qquad (5.11a)$$

$$\frac{1}{\delta t} (\boldsymbol{u}_{\sigma}^{n+1} - \boldsymbol{u}_{\sigma}^{n}) + \operatorname{div}(\boldsymbol{u}^{n+1} \otimes \boldsymbol{u}^{n+1})_{\sigma} - \operatorname{div}\boldsymbol{\tau}(\boldsymbol{u}^{n+1})_{\sigma} + (\boldsymbol{\nabla} \delta p^{n+1})_{\sigma} = 0, \quad \forall \sigma \in \mathcal{E}_{\text{int}}.$$
 (5.11b)

At the limit, the scheme uses as initial condition only the L²-projection of \mathbf{u}_0 (the limit of $\mathbf{u}_0^{\varepsilon}$) on the space $E_{\mathcal{T}}(\Omega)$ of the discrete divergence-free functions: $E_{\mathcal{T}}(\Omega) = \{ \mathbf{v} \in \mathbf{H}_{\mathcal{E},0}(\Omega), \operatorname{div}(\mathbf{v})_K = 0, \forall K \in \mathcal{M} \}.$

Proof. The proof of the convergence of $(\rho^{(m)})_{m\in\mathbb{N}}$ towards $\rho=1$ when m tends to $+\infty$ is the same as in the continuous setting. It follows from the combination of the lower bounds on $\Pi_{\gamma}(\rho)$ proven in Lemma 2.2 and the discrete global entropy estimate (5.8).

Using again estimate (5.8), one can see that the sequence $(\boldsymbol{u}^{(m)})_{m\in\mathbb{N}}$ is bounded in any discrete norm and the same holds for the sequence $(\delta p^{(m)})_{m\in\mathbb{N}}$ by Lemma 5.6. By the Bolzano-Weierstrass Theorem and a norm equivalence argument for finite dimensional spaces, there exists a subsequence of $(\boldsymbol{u}^{(m)}, \delta p^{(m)})_{m\in\mathbb{N}}$ which tends, in any discrete norm, to a limit $(\boldsymbol{u}, \delta p)$. Passing to the limit cell-by-cell in the implicit scheme (5.1), one obtains that $(\boldsymbol{u}, \delta p)$ is a solution of the standard implicit scheme (5.11) for the incompressible Navier-Stokes equations.

If \mathbf{u}^1 is a solution of the first time-step of (5.11) then $\mathbf{u}^1 \in E_{\mathcal{T}}(\Omega)$, and for all $\varphi \in E_{\mathcal{T}}(\Omega)$, taking the scalar product of (5.11b) with $|D_{\sigma}|\varphi_{\sigma}$ and summing over $\sigma \in \mathcal{E}_{int}$, one gets that \mathbf{u}^1 satisfies:

$$\frac{1}{\delta t} (\boldsymbol{u}^{1}, \boldsymbol{\varphi})_{L^{2}} + \sum_{\sigma \in \mathcal{E}_{int}} |D_{\sigma}| \operatorname{div}(\rho^{1} \boldsymbol{u}^{1} \otimes \boldsymbol{u}^{1})_{\sigma} \cdot \boldsymbol{\varphi}_{\sigma} + \sum_{K \in \mathcal{M}} \int_{K} \boldsymbol{\tau}(\hat{\boldsymbol{u}}^{1}) : \boldsymbol{\tau}(\hat{\boldsymbol{\varphi}}) = \frac{1}{\delta t} (\boldsymbol{u}^{0}, \boldsymbol{\varphi})_{L^{2}}.$$
 (5.12)

This system is known to be the part of the algebraic system associated with one time step of the scheme determining the velocity (even if the uniqueness of this unknown is guaranteed only for small time steps), in the sense that the velocity may be computed from (5.12), the remaining equations yielding the pressure. Observing that in the right hand side of (5.12), \boldsymbol{u}^0 can be replaced by its L²-projection $\mathcal{P}(\boldsymbol{u}^0)$ onto $E_{\mathcal{T}}(\Omega)$ (since $(\boldsymbol{u}^0 - \mathcal{P}(\boldsymbol{u}^0), \boldsymbol{\varphi})_{L^2} = 0$ for all $\boldsymbol{\varphi} \in E_{\mathcal{T}}(\Omega)$ by definition of $\mathcal{P}(\boldsymbol{u}^0)$), we obtain that only the divergence-free part of the initial velocity is seen by the implicit scheme. \square

6. Asymptotic analysis of the zero Mach limit for a pressure correction scheme. Since the scheme (5.1) is fully implicit, the implementation of the algorithm implies to find the solution of a fully non-linear coupled system which is difficult in a real computational context due to the computational cost and lack of robustness. This is why we also perform the analysis of the low Mach number limit for a semi-implicit scheme which is implemented in the software (CALIF³S [5]). This scheme is obtained thanks to a partial decoupling of the discrete equations, and falls in the family of pressure correction schemes. It consists (after a rescaling step for the pressure gradient) in two main steps. A prediction step, where a tentative velocity field is obtained by solving a linearized momentum balance in which the mass convection flux and the pressure gradient are explicit. A correction step where a nonlinear problem on the pressure is solved, and the velocity is updated in such a way to recover the discrete mass conservation equation.

Let $\delta t > 0$ be a constant time step. The approximate solution at time $t_n = n\delta t$ for $1 \le n \le N = \lfloor T/\delta t \rfloor$ is denoted $(\rho^n, \mathbf{u}^n) \in L_{\mathcal{M}}(\Omega) \times \mathbf{H}_{\mathcal{E},0}(\Omega)$.

Knowing $(\rho^{n-1}, \rho^n, \boldsymbol{u}^n) \in L_{\mathcal{M}}(\Omega) \times L_{\mathcal{M}}(\Omega) \times \boldsymbol{H}_{\mathcal{E},0}(\Omega)$, the considered algorithm consists in computing $\rho^{n+1} \in L_{\mathcal{M}}(\Omega)$ and $\boldsymbol{u}^{n+1} \in \boldsymbol{H}_{\mathcal{E},0}(\Omega)$ through the following steps:

Pressure gradient scaling step:

$$(\overline{\nabla p})_{\sigma}^{n} = \left(\frac{\rho_{D_{\sigma}}^{n}}{\rho_{D_{\sigma}}^{n-1}}\right)^{1/2} (\nabla p^{n})_{\sigma}, \qquad \forall \sigma \in \mathcal{E}_{\text{int}}. \quad (6.1a)$$

Prediction step – Solve for $\tilde{\boldsymbol{u}}^{n+1} \in \mathbf{H}_{\mathcal{E},0}(\Omega)$:

$$\frac{1}{\delta t} \left(\rho_{D_{\sigma}}^{n} \tilde{\boldsymbol{u}}_{\sigma}^{n+1} - \rho_{D_{\sigma}}^{n-1} \boldsymbol{u}_{\sigma}^{n} \right) + \operatorname{\mathbf{div}}(\rho^{n} \boldsymbol{u}^{n} \otimes \tilde{\boldsymbol{u}}^{n+1})_{\sigma} - \operatorname{\mathbf{div}} \boldsymbol{\tau} (\tilde{\boldsymbol{u}}^{n+1})_{\sigma} + \frac{1}{\varepsilon^{2}} \left(\overline{\boldsymbol{\nabla} p} \right)_{\sigma}^{n} = 0, \quad \forall \sigma \in \mathcal{E}_{\text{int}}. \quad (6.1b)$$

Correction step – Solve for $\rho^{n+1} \in L_{\mathcal{M}}(\Omega)$ and $\mathbf{u}^{n+1} \in \mathbf{H}_{\mathcal{E},0}(\Omega)$:

$$\frac{1}{\delta t} \rho_{D_{\sigma}}^{n} \left(\boldsymbol{u}_{\sigma}^{n+1} - \tilde{\boldsymbol{u}}_{\sigma}^{n+1} \right) + \frac{1}{\varepsilon^{2}} \left(\boldsymbol{\nabla} p^{n+1} \right)_{\sigma} - \frac{1}{\varepsilon^{2}} \left(\overline{\boldsymbol{\nabla} p} \right)_{\sigma}^{n} = 0, \qquad \forall \sigma \in \mathcal{E}_{\text{int}}. \quad (6.1c)$$

$$\frac{1}{\delta t}(\rho_K^{n+1} - \rho_K^n) + \operatorname{div}(\rho^{n+1}\boldsymbol{u}^{n+1})_K = 0, \qquad \forall K \in \mathcal{M}. \quad (6.1d)$$

6.1. Initial data and initialization of the scheme. As mentioned in the introduction, for the pressure correction scheme, it is not sufficient to assume "ill-prepared" initial data. In this section, the initial data $(\rho_0^{\varepsilon}, u_0^{\varepsilon})$ are assumed to be well-prepared in the sense of the following definition:

DEFINITION 6.1. The initial data $(\rho_0^{\varepsilon}, \mathbf{u}_0^{\varepsilon})$ is said to be well-prepared if $\rho_0^{\varepsilon} > 0$, $\rho_0^{\varepsilon} \in L^{\infty}(\Omega)$, $\mathbf{u}_0^{\varepsilon} \in H_0^1(\Omega)^d$ for all $\varepsilon > 0$ and if there exists C independent of ε such that:

$$\|\boldsymbol{u}_{0}^{\varepsilon}\|_{\mathrm{H}^{1}(\Omega)^{d}} + \frac{1}{\varepsilon} \|\operatorname{div}\boldsymbol{u}_{0}^{\varepsilon}\|_{\mathrm{L}^{2}(\Omega)} + \frac{1}{\varepsilon^{2}} \|\rho_{0}^{\varepsilon} - 1\|_{\mathrm{L}^{\infty}(\Omega)} \le C.$$
 (6.2)

Consequently, ρ_0^{ε} tends to 1 when $\varepsilon \to 0$; moreover, we suppose that $\mathbf{u}_0^{\varepsilon}$ converges in $L^2(\Omega)^d$ towards a function $\mathbf{u}_0 \in L^2(\Omega)^d$ (the uniform boundedness of the sequence in the $H^1(\Omega)^d$ norm already implies this convergence up to a subsequence).

The initial velocities $\boldsymbol{u}_0^{\varepsilon}$ are in $\mathrm{H}_0^1(\Omega)^d$. In particular, their trace is thus well defined as an L² function on any smooth (or Lipschitz-continuous) hypersurface of Ω . The initialization of the pressure correction scheme (6.1) is performed as follows. First, ρ^0 and \boldsymbol{u}^0 are given by the average of the initial conditions ρ_0^{ε} and $\boldsymbol{u}_0^{\varepsilon}$ respectively on the primal cells and on the faces of the primal cells:

$$\rho_K^0 = \frac{1}{|K|} \int_K \rho_0^{\varepsilon}, \qquad \forall K \in \mathcal{M},
\mathbf{u}_{\sigma}^0 = \frac{1}{|\sigma|} \int_{\sigma} \mathbf{u}_0^{\varepsilon}, \qquad \forall \sigma \in \mathcal{E}_{\text{int}}.$$
(6.3)

Finally, we compute ρ^{-1} by solving the mass balance equation (6.1d) for n=-1, where the unknown is ρ^{-1} and not ρ^0 . This procedure allows to perform the first prediction step with $(\rho_{D_{\sigma}}^{-1})_{\sigma \in \mathcal{E}}$, $(\rho_{D_{\sigma}}^0)_{\sigma \in \mathcal{E}}$ and the dual mass fluxes satisfying the mass balance:

$$\frac{|D_{\sigma}|}{\delta t} \left(\rho_{D_{\sigma}}^{0} - \rho_{D_{\sigma}}^{-1} \right) + \sum_{\varepsilon \in \overline{\mathcal{E}}(D_{\sigma})} F_{\sigma,\varepsilon}(\rho^{0}, \boldsymbol{u}^{0}) = 0, \quad \forall \sigma \in \mathcal{E}_{\text{int}}.$$
 (6.4)

In this section, we prove that for every $\varepsilon > 0$, there exists a solution $(\rho^{\varepsilon}, \boldsymbol{u}^{\varepsilon})$ to the pressure correction scheme (6.1) with the aforementioned initialization, and that for a fixed discretization, *i.e.* for a fixed mesh and a fixed time step δt , the solution $(\rho^{\varepsilon}, \boldsymbol{u}^{\varepsilon})$ converges as $\varepsilon \to 0$ towards the solution of a pressure correction scheme for the incompressible Navier-Stokes equations, which is inf-sup stable.

A first property must be checked so that the scheme is well defined, which is the positivity of the density at the fictitious time step n=-1. Indeed, since ρ_0^{ε} is assumed to be positive on Ω and by definition of the discrete density ρ^0 (6.3), one clearly has $\rho_K^0 > 0$ for all $K \in \mathcal{M}$. This positivity property is not clear for ρ^{-1} . It is a consequence of the following result.

LEMMA 6.2. If the initial conditions $(\rho_0^{\varepsilon}, \mathbf{u}_0^{\varepsilon})$ are assumed to be well-prepared in the sense of Definition 6.1, then there exists a constant C independent of ε such that:

$$\frac{1}{\varepsilon^2} \max_{K \in \mathcal{M}} |\rho_K^0 - 1| + \frac{1}{\varepsilon^2} \max_{\sigma \in \mathcal{E}_{int}} |(\nabla p^0)_{\sigma}| + \frac{1}{\varepsilon} \max_{K \in \mathcal{M}} |\rho_K^{-1} - 1| \le C.$$
 (6.5)

Proof. Since the initial conditions $(\rho_0^{\varepsilon}, \mathbf{u}_0^{\varepsilon})$ are well-prepared, the discrete density at the time step n = 0 satisfies for all $K \in \mathcal{M}$:

$$|\rho_K^0 - 1| \le \frac{1}{|K|} \int_K |\rho_0^{\varepsilon} - 1| \le \|\rho_0^{\varepsilon} - 1\|_{L^{\infty}(K)} \le C\varepsilon^2.$$

Then, using the definition of the pressure gradient, we also obtain $|(\nabla p^0)_{\sigma}| \leq C\varepsilon^2$ for all $\sigma \in \mathcal{E}_{\rm int}$, where the constant C may depend on the (fixed) mesh and on γ but is independent of ε . Let us then verify that for ε small enough the discrete density at time step n=-1 is close to 1. This density is computed in such a manner that, for all $K \in \mathcal{M}$:

$$\rho_{K}^{-1} - 1 = \rho_{K}^{0} - 1 + \delta t \sum_{\sigma \in \mathcal{E}(K)} \frac{|\sigma|}{|K|} \rho_{\sigma}^{0} \mathbf{u}_{\sigma}^{0} \cdot \mathbf{n}_{K,\sigma}$$

$$= \rho_{K}^{0} - 1 + \delta t \rho_{K}^{0} \sum_{\sigma \in \mathcal{E}(K)} \frac{|\sigma|}{|K|} \mathbf{u}_{\sigma}^{0} \cdot \mathbf{n}_{K,\sigma} + \delta t \sum_{\sigma \in \mathcal{E}(K)} \frac{|\sigma|}{|K|} (\rho_{\sigma}^{0} - \rho_{K}^{0}) \mathbf{u}_{\sigma}^{0} \cdot \mathbf{n}_{K,\sigma}$$

$$= \rho_{K}^{0} - 1 + \delta t \rho_{K}^{0} \frac{1}{|K|} \sum_{\sigma \in \mathcal{E}(K)} \int_{\sigma} \mathbf{u}_{0}^{\varepsilon} \cdot \mathbf{n}_{K,\sigma} + \delta t \sum_{\sigma \in \mathcal{E}(K)} \frac{|\sigma|}{|K|} (\rho_{\sigma}^{0} - \rho_{K}^{0}) \mathbf{u}_{\sigma}^{0} \cdot \mathbf{n}_{K,\sigma}$$

$$= \rho_{K}^{0} - 1 + \delta t \rho_{K}^{0} \frac{1}{|K|} \int_{K} \operatorname{div} \mathbf{u}_{0}^{\varepsilon} + \delta t \sum_{\sigma \in \mathcal{E}(K)} \frac{|\sigma|}{|K|} (\rho_{\sigma}^{0} - \rho_{K}^{0}) \mathbf{u}_{\sigma}^{0} \cdot \mathbf{n}_{K,\sigma}.$$

We have already proven that the first term and thus the third term (using, for this latter, a trace inequality to bound the face velocity) in the right-hand side of the above equality are bounded by $C\varepsilon^2$ for some constant C independent of ε (but dependent on the mesh). The second term is bounded by $C\varepsilon$ for some constant C since the divergence of the initial velocity satisfies (6.2). The expected bound on $|\rho_K^{-1} - 1|$ follows. \square

Remark 6.1. All the developments below are still valid under the slightly less restrictive condition on the divergence of the initial velocities:

$$\|\operatorname{div} \boldsymbol{u}_0^{\varepsilon}\|_{L^2(\Omega)} \to 0 \quad as \ \varepsilon \to 0.$$

6.2. A priori estimates. Let us now derive the estimates satisfied by any solution of the pressure correction scheme. As for the implicit scheme, any solution of the pressure correction scheme satisfies a discrete counterpart to the kinetic energy balance (2.1).

LEMMA 6.3 (Discrete kinetic energy balance). Any solution to the pressure correction scheme (6.1) satisfies the following equality, for all $\sigma \in \mathcal{E}_{int}$ and $0 \le n \le N-1$:

$$\frac{1}{2\delta t} \left(\rho_{D_{\sigma}}^{n} |\boldsymbol{u}_{\sigma}^{n+1}|^{2} - \rho_{D_{\sigma}}^{n-1} |\boldsymbol{u}_{\sigma}^{n}|^{2} \right) + \frac{1}{2|D_{\sigma}|} \sum_{\varepsilon = D_{\sigma}|D_{\sigma}'} F_{\sigma,\varepsilon}(\rho^{n}, \boldsymbol{u}^{n}) \, \tilde{\boldsymbol{u}}_{\sigma}^{n+1} \cdot \tilde{\boldsymbol{u}}_{\sigma'}^{n+1} - \operatorname{div}\boldsymbol{\tau}(\tilde{\boldsymbol{u}}^{n+1})_{\sigma} \cdot \tilde{\boldsymbol{u}}_{\sigma}^{n+1} \\
+ \frac{1}{\varepsilon^{2}} (\boldsymbol{\nabla} p^{n+1})_{\sigma} \cdot \boldsymbol{u}_{\sigma}^{n+1} + \frac{\delta t}{2 \, \varepsilon^{4}} \left(\frac{\left| (\boldsymbol{\nabla} p^{n+1})_{\sigma} \right|^{2}}{\rho_{D_{\sigma}}^{n}} - \frac{\left| (\boldsymbol{\nabla} p^{n})_{\sigma} \right|^{2}}{\rho_{D_{\sigma}}^{n-1}} \right) + R_{\sigma}^{n+1} = 0, \quad (6.6)$$

where
$$R_{\sigma}^{n+1} = \frac{1}{2\delta t} \rho_{D_{\sigma}}^{n-1} |\tilde{\boldsymbol{u}}_{\sigma}^{n+1} - \boldsymbol{u}_{\sigma}^{n}|^{2}$$
.

Proof. Let us take the scalar product of the velocity prediction equation (6.1b) with the corresponding velocity unknown $\tilde{\boldsymbol{u}}_{\sigma}^{n+1}$. Thanks to the time shift in the dual densities and the dual mass fluxes in the velocity prediction equation (6.1b), together with the dual mass balance (at the previous time step)

$$\frac{1}{\delta t} \left(\rho_{D_{\sigma}}^{n} - \rho_{D_{\sigma}}^{n-1} \right) + |D_{\sigma}|^{-1} \sum_{\varepsilon \in \mathcal{E}(D_{\sigma})} F_{\sigma,\varepsilon}(\rho^{n}, \tilde{\boldsymbol{u}}^{n}) = 0, \quad \forall \sigma \in \mathcal{E}_{\text{int}},$$

we obtain, by a similar computation to that in the proof of Lemma 5.2:

$$\frac{1}{2\delta t} \left(\rho_{D_{\sigma}}^{n} |\tilde{u}_{\sigma}^{n+1}|^{2} - \rho_{D_{\sigma}}^{n-1} |\boldsymbol{u}_{\sigma}^{n}|^{2} \right) + \frac{1}{2|D_{\sigma}|} \sum_{\varepsilon = D_{\sigma}|D_{\sigma'}} F_{\sigma,\varepsilon}(\rho^{n}, \tilde{\boldsymbol{u}}^{n}) \; \tilde{\boldsymbol{u}}_{\sigma}^{n+1} \cdot \tilde{\boldsymbol{u}}_{\sigma'}^{n+1} \\
- \operatorname{div} \boldsymbol{\tau}(\tilde{\boldsymbol{u}}^{n+1})_{\sigma} \cdot \tilde{\boldsymbol{u}}_{\sigma}^{n+1} + \frac{1}{\varepsilon^{2}} (\overline{\nabla p})_{\sigma}^{n} \cdot \tilde{\boldsymbol{u}}_{\sigma}^{n+1} + R_{\sigma}^{n+1} = 0. \quad (6.7)$$

where $R_{\sigma}^{n+1} = \frac{1}{2\delta t} \rho_{D_{\sigma}}^{n-1} |\tilde{\boldsymbol{u}}_{\sigma}^{n+1} - \boldsymbol{u}_{\sigma}^{n}|^{2}$. Dividing the velocity correction equation (6.1c) by $\left(\frac{\rho_{D_{\sigma}}^{n}}{\delta t}\right)^{\frac{1}{2}}$, we

$$\left(\frac{\rho_{D_{\sigma}}^{n}}{\delta t}\right)^{1/2}\boldsymbol{u}_{\sigma}^{n+1} + \left(\frac{\delta t}{\rho_{D_{\sigma}}^{n}}\right)^{1/2}\frac{1}{\varepsilon^{2}}(\boldsymbol{\nabla}p^{n+1})_{\sigma} = \left(\frac{\rho_{D_{\sigma}}^{n}}{\delta t}\right)^{1/2}\tilde{\boldsymbol{u}}_{\sigma}^{n+1} + \left(\frac{\delta t}{\rho_{D_{\sigma}}^{n}}\right)^{1/2}\frac{1}{\varepsilon^{2}}(\overline{\boldsymbol{\nabla}p})_{\sigma}^{n}.$$

Squaring this relation and summing it with (6.7) yields

$$\begin{split} \frac{1}{2\delta t} \Big(\rho_{D_{\sigma}}^{n} \, |\boldsymbol{u}_{\sigma}^{n+1}|^{2} - \rho_{D_{\sigma}}^{n-1} \, |\boldsymbol{u}_{\sigma}^{n}|^{2} \Big) + \frac{1}{2|D_{\sigma}|} \sum_{\varepsilon = D_{\sigma}|D_{\sigma}'} F_{\sigma,\varepsilon}(\rho^{n}, \boldsymbol{u}^{n}) \, \tilde{\boldsymbol{u}}_{\sigma}^{n+1} \cdot \tilde{\boldsymbol{u}}_{\sigma'}^{n+1} \\ - \operatorname{\mathbf{div}} \boldsymbol{\tau}(\tilde{\boldsymbol{u}}^{n+1})_{\sigma} \cdot \tilde{\boldsymbol{u}}_{\sigma}^{n+1} + \frac{1}{\varepsilon^{2}} (\boldsymbol{\nabla} p^{n+1})_{\sigma} \cdot \boldsymbol{u}_{\sigma}^{n+1} + R_{\sigma}^{n+1} + \frac{1}{\varepsilon^{4}} P_{\sigma}^{n+1} = 0, \end{split}$$

where $P_{\sigma}^{n+1} = \frac{\delta t}{2 \rho_{\sigma}^{n}} \left(\left| (\nabla p^{n+1})_{\sigma} \right|^{2} - \left| (\overline{\nabla p})_{\sigma}^{n} \right|^{2} \right)$. Recalling that the rescaled pressure is defined as

$$(\overline{\nabla p})_{\sigma}^{n} = \left(\frac{\rho_{D_{\sigma}}^{n}}{\rho_{D_{\sigma}}^{n-1}}\right)^{1/2} (\nabla p^{n})_{\sigma}$$

for all $\sigma \in \mathcal{E}_{int}$, we obtain (6.6). \square

The discrete renormalization identities are again valid for the pressure correction algorithm, thanks to the fact that the mass balance (6.1d) is satisfied. The proof is identical to that of Lemma 5.3 given for the implicit scheme.

LEMMA 6.4 (Discrete renormalization identities). A solution to the system (6.1) satisfies for all $K \in \mathcal{M}$ and $0 \le n \le N-1$ the two following identities:

$$\frac{1}{\delta t} \Big(\psi_{\gamma}(\rho_{K}^{n+1}) - \psi_{\gamma}(\rho_{K}^{n}) \Big) + \operatorname{div}(\psi_{\gamma}(\rho^{n+1})\boldsymbol{u}^{n+1})_{K} + \wp(\rho_{K}^{n+1}) \operatorname{div}(\boldsymbol{u}^{n+1})_{K} + R_{K}^{n+1} = 0,$$

$$\frac{1}{\delta t} \Big(\Pi_{\gamma}(\rho_{K}^{n+1}) - \Pi_{\gamma}(\rho_{K}^{n}) \Big) + \operatorname{div}\Big((\psi_{\gamma}(\rho^{n+1}) - \psi_{\gamma}'(1) \rho^{n+1}) \boldsymbol{u}^{n+1} \Big)_{K}$$

$$+ \wp(\rho_{K}^{n+1}) \operatorname{div}(\boldsymbol{u}^{n+1})_{K} + R_{K}^{n+1} = 0,$$
(6.8)

where R_K^{n+1} has the same expression as in Lemma 5.3.

LEMMA 6.5 (Local-in-time discrete entropy inequality, existence of a solution). Let $\varepsilon > 0$ and assume that the initial data $(\rho_0^{\varepsilon}, \mathbf{u}_0^{\varepsilon})$ is well-prepared in the sense of Definition 6.1, i.e. satisfies (6.2). Then, for ε small enough, there exists a solution $(\rho^n, \mathbf{u}^n)_{0 \le n \le N}$ to the scheme (6.1), $\rho^n > 0$ for $1 \le n \le N$ and the following inequality holds for $1 \le n \le N-1$:

$$\frac{1}{2} \sum_{\sigma \in \mathcal{E}_{int}} |D_{\sigma}| \left(\rho_{D_{\sigma}}^{n} |\boldsymbol{u}_{\sigma}^{n+1}|^{2} - \rho_{D_{\sigma}}^{n-1} |\boldsymbol{u}_{\sigma}^{n}|^{2} \right) + \frac{1}{\varepsilon^{2}} \sum_{K \in \mathcal{M}} |K| \left(\Pi_{\gamma}(\rho_{K}^{n+1}) - \Pi_{\gamma}(\rho_{K}^{n}) \right) \\
+ \mu \delta t \|\tilde{\boldsymbol{u}}^{n+1}\|_{1,\mathcal{T}}^{2} + \frac{\delta t^{2}}{2\varepsilon^{4}} \sum_{\sigma \in \mathcal{E}_{int}} |D_{\sigma}| \left(\frac{\left| (\boldsymbol{\nabla} p^{n+1})_{\sigma} \right|^{2}}{\rho_{D_{\sigma}}^{n}} - \frac{\left| (\boldsymbol{\nabla} p^{n})_{\sigma} \right|^{2}}{\rho_{D_{\sigma}}^{n-1}} \right) + \mathcal{R}^{n+1} \leq 0, \quad (6.10)$$

where $\mathcal{R}^{n+1} = \sum_{\sigma \in \mathcal{E}_{int}} R_{\sigma}^{n+1} + \varepsilon^{-2} \sum_{K \in \mathcal{M}} R_K^{n+1} \ge 0$. Proof. For ε small enough, by Lemma 6.2, both ρ^{-1} and ρ^0 are positive. The positivity of ρ^n , for $1 \le n \le N$, is a consequence of the properties of the upwind choice (4.2) for ρ in the mass balance of the correction step (6.1d).

After multiplication by $|D_{\sigma}|$, we sum the kinetic energy balance equation (6.6) over the faces, and after multiplication by $\varepsilon^{-2}|K|$, we sum the relative entropy balance (6.9) over the primal cells, and finally sum the two obtained relations. Since the discrete gradient and divergence operators are dual with respect to the L^2 inner product (see (4.10)), noting that the conservative fluxes vanish in the summation and that the diffusion term is coercive (see Lemma 4.1), we get (6.10).

Given discrete density and velocity fields $(\rho^{n-1}, \rho^n, \boldsymbol{u}^n)$, the predicted velocity $\tilde{\boldsymbol{u}}^{n+1}$ is the solution of the linear system (6.1b). Multiplying (6.7) by $|D_{\sigma}|$, summing over the faces and using Young's inequality, yields the following inequality, which is valid for all $\alpha > 0$:

$$\frac{1}{2\delta t} \|\sqrt{\underline{\rho}^n} \tilde{\boldsymbol{u}}^{n+1}\|_{\mathrm{L}^2}^2 - \frac{\alpha}{2\varepsilon^2} \|\tilde{\boldsymbol{u}}^{n+1}\|_{\mathrm{L}^2}^2 + \mu \|\tilde{\boldsymbol{u}}^{n+1}\|_{1,\mathcal{T}}^2 \leq \frac{1}{2\delta t} \|\sqrt{\underline{\rho}^{n-1}} \boldsymbol{u}^n\|_{\mathrm{L}^2}^2 + \frac{1}{2\alpha\varepsilon^2} \|(\overline{\boldsymbol{\nabla}p})^n\|_{\mathrm{L}^2}^2.$$

In this inequality, $\underline{\rho}^n$ and $\underline{\rho}^{n-1}$ are the piecewise constant fields equal to $\rho_{D_{\sigma}}^n$ and $\rho_{D_{\sigma}}^{n-1}$ on each dual face D_{σ} . Choosing $\alpha > 0$ small enough yields the coercivity of the linear system (6.1b) and therefore the existence of a unique solution $\tilde{\boldsymbol{u}}^{n+1}$ to the prediction step. The existence of a solution $(\rho^{n+1}, \boldsymbol{u}^{n+1})$ to the correction step (6.1c)-(6.1d) follows from the Brouwer fixed point theorem, by an easy adaptation of the proof of [18, Proposition 5.2]. \square

Let us now turn to the global entropy inequality.

LEMMA 6.6 (Global discrete entropy inequality). Let $\varepsilon > 0$ and assume that the initial data $(\rho_0^{\varepsilon}, \mathbf{u}_0^{\varepsilon})$ is well-prepared in the sense of Definition 6.1, i.e. satisfies (6.2). By Lemma 6.5, there exists a solution $(\rho^n, \mathbf{u}^n)_{0 \le n \le N}$ to the scheme (5.1). In addition, there exists C > 0 independent of ε such that, for ε small enough and for all $1 \le n \le N$:

$$\frac{1}{2} \sum_{\sigma \in \mathcal{E}_{int}} |D_{\sigma}| \; \rho_{D_{\sigma}}^{n-1} \; |\boldsymbol{u}_{\sigma}^{n}|^{2} + \mu \sum_{k=1}^{n} \delta t \; \|\tilde{\boldsymbol{u}}^{k}\|_{1,\mathcal{T}}^{2} + \frac{1}{\varepsilon^{2}} \sum_{K \in \mathcal{M}} |K| \, \Pi_{\gamma}(\rho_{K}^{n}) + \frac{\delta t^{2}}{2\varepsilon^{4}} \sum_{\sigma \in \mathcal{E}_{int}} \frac{|D_{\sigma}|}{\rho_{D_{\sigma}}^{n-1}} \; |(\boldsymbol{\nabla} p^{n})_{\sigma}|^{2} \leq C. \quad (6.11)$$

Proof. Summing (6.10) over n yields the expected inequality (6.11) with

$$C = \frac{1}{2} \sum_{\sigma \in \mathcal{E}_{\text{int}}} |D_{\sigma}| \ \rho_{D_{\sigma}}^{-1} \ |\boldsymbol{u}_{\sigma}^{0}|^{2} + \frac{1}{\varepsilon^{2}} \sum_{K \in \mathcal{M}} |K| \prod_{\gamma} (\rho_{K}^{0}) + \frac{\delta t^{2}}{2\varepsilon^{4}} \sum_{\sigma \in \mathcal{E}_{\text{int}}} \frac{|D_{\sigma}|}{\rho_{D_{\sigma}}^{-1}} \ |(\boldsymbol{\nabla} p^{0})_{\sigma}|^{2}.$$

Let us prove that if the initial data is well-prepared in the sense of (6.2), then for ε small enough, C is uniformly bounded independently of ε . By Lemma 6.2, ρ_K^{-1} is bounded for all $K \in \mathcal{M}$ for ε small enough and therefore so is $\rho_{D_{\tau}}^{-1}$ for all $\sigma \in \mathcal{E}_{int}$. Hence, since $\mathbf{u}_0^{\varepsilon}$ is uniformly bounded in $\mathrm{H}^1(\Omega)^d$ by (6.2), a classical trace inequality yields the boundedness of the first term. By (6.5), one has $|\rho_K^0 - 1| \leq C\varepsilon^2$ for all $K \in \mathcal{M}$. Hence, by (2.8), the second term vanishes as $\varepsilon \to 0$. The third term is also uniformly bounded with respect to ε thanks to (6.5). \square

LEMMA 6.7 (Control of the pressure). Let $\varepsilon > 0$ and assume that the initial data $(\rho_0^{\varepsilon}, \boldsymbol{u}_0^{\varepsilon})$ is well-prepared in the sense of Definition 6.1, i.e. satisfies (6.2). By Lemma 6.5, for ε small enough, there exists a solution $(\rho^n, \boldsymbol{u}^n)_{0 \le n \le N}$ to the scheme (5.1). Let $p^n = \wp(\rho^n)$ and define $\delta p^n = \{\delta p_K^n, K \in \mathcal{M}\}$ where $\delta p_K^n = (p_K^n - m(p^n))/\varepsilon^2$ with $m(p^n)$ the mean value of p^n over Ω (i.e. $m(p^n) = |\Omega|^{-1} \sum_{K \in \mathcal{M}} |K| p_K^n$). Then, one has, for $1 \le n \le N$:

$$\|\delta p^n\| \le C_{\mathcal{T},\delta t},\tag{6.12}$$

where the real number $C_{\mathcal{T},\delta t}$ depends on the mesh and the time step but not on ε , and $\|\cdot\|$ stands for any norm on the space of discrete functions.

Proof. According to (6.11), the pressure gradient is controlled in L^{∞} by $C_{\mathcal{T},\delta t}$ ε^2 where $C_{\mathcal{T},\delta t}$ is a mesh-dependent constant independent of ε . Hence, by a finite-dimensional argument $\nabla(\delta p^n)$ is controlled in any norm by some constant independent of ε . In particular, on has $\|\nabla(\delta p^n)\|_{-1,\mathcal{T}} \leq C_{\mathcal{T},\delta t}$, where $\|\cdot\|_{-1,\mathcal{T}}$ is the discrete $(H^{-1})^d$ -norm defined for $\mathbf{v} \in \mathbf{H}_{\mathcal{E},0}(\Omega)$ by:

$$\|\boldsymbol{v}\|_{-1,\mathcal{T}} = \sup \Big\{ \sum_{\sigma \in \mathcal{E}} |D_{\sigma}| \ \boldsymbol{v}_{\sigma} \cdot \boldsymbol{w}_{\sigma}, \quad \text{with } \boldsymbol{w} \in \mathbf{H}_{\mathcal{E},0}(\Omega) \text{ such that } \|\boldsymbol{w}\|_{1,\mathcal{T}} \le 1 \Big\}.$$

Invoking the gradient divergence duality (4.10) and the *inf-sup* stability of the scheme (see Lemma 4.2), $\|\nabla(\delta p^n)\|_{-1,\mathcal{T}} \leq C_{\mathcal{T},\delta t}$ implies that $\|\delta p^n\|_{L^2} \leq \beta^{-1}C_{\mathcal{T},\delta t}$. \square

6.3. Incompressible limit of the pressure correction scheme. We may now state the main result of this section which is the convergence, up to a subsequence, of the compressible scheme (6.1) towards a pressure correction *inf-sup* stable scheme when the Mach number tends to zero.

THEOREM 6.8 (Incompressible limit of the pressure correction scheme). Let $(\varepsilon^{(m)})_{m\in\mathbb{N}}$ be a sequence of positive real numbers tending to zero, and let $(\rho^{(m)}, \boldsymbol{u}^{(m)})$ be a corresponding sequence of solutions of the scheme (6.1). Let us assume that the initial data $(\rho_0^{\varepsilon^{(m)}}, \boldsymbol{u}_0^{\varepsilon^{(m)}})$ is well-prepared in the sense of Definition 6.1, i.e. satisfies (6.2) for $m \in \mathbb{N}$. Then the sequence $(\rho^{(m)})_{m \in \mathbb{N}}$ tends to the constant function $\rho = 1$ when m tends to $+\infty$ in $L^{\infty}((0,T),L^{\gamma}(\Omega))$. Moreover, for all $q \in [1, \min(2, \gamma)]$, there exists C > 0 such that:

$$\|\rho^{(m)} - 1\|_{L^{\infty}((0,T);L^{q}(\Omega))} \le C\varepsilon^{(m)}, \quad \text{for } m \text{ large enough.}$$

In addition, the sequence $(\mathbf{u}^{(m)}, \delta p^{(m)})_{m \in \mathbb{N}}$ tends, in any discrete norm, to the solution $(\mathbf{u}, \delta p)$ of the usual (Rannacher-Turek or Crouzeix-Raviart) pressure correction scheme for the incompressible Navier-Stokes equations, which reads:

Knowing $\delta p^n \in L_{\mathcal{M}}(\Omega)$ and $\mathbf{u}^n \in \mathbf{H}_{\mathcal{E},0}(\Omega)$, compute $\delta p^{n+1} \in L_{\mathcal{M}}(\Omega)$ and $\mathbf{u}^{n+1} \in \mathbf{H}_{\mathcal{E},0}(\Omega)$ through the following steps:

Prediction step – Solve for $\tilde{\boldsymbol{u}}^{n+1} \in \mathbf{H}_{\mathcal{E},0}(\Omega)$:

$$\frac{1}{\delta t} \left(\tilde{\boldsymbol{u}}_{\sigma}^{n+1} - \boldsymbol{u}_{\sigma}^{n} \right) + \operatorname{div}(\boldsymbol{u}^{n} \otimes \tilde{\boldsymbol{u}}^{n+1})_{\sigma} - \operatorname{div}\boldsymbol{\tau}(\tilde{\boldsymbol{u}}^{n+1})_{\sigma} + (\boldsymbol{\nabla} \delta p^{n})_{\sigma} = 0, \qquad \forall \sigma \in \mathcal{E}_{\text{int}}.$$
 (6.13a)

Correction step – Solve for $\delta p^{n+1} \in L_{\mathcal{M}}(\Omega)$ and $\mathbf{u}^{n+1} \in \mathbf{H}_{\mathcal{E},0}(\Omega)$:

$$\frac{1}{\delta t} \left(\boldsymbol{u}_{\sigma}^{n+1} - \tilde{\boldsymbol{u}}_{\sigma}^{n+1} \right) + (\boldsymbol{\nabla} \delta p^{n+1})_{\sigma} - (\boldsymbol{\nabla} \delta p^{n})_{\sigma} = 0, \qquad \forall \sigma \in \mathcal{E}_{\text{int}}. \tag{6.13b}$$

$$\operatorname{div}(\boldsymbol{u}^{n+1})_K = 0, \qquad \forall K \in \mathcal{M}. \tag{6.13c}$$

Proof. The proof of the convergence of $(\rho^{(m)})_{m\in\mathbb{N}}$ towards $\rho=1$ when m tends to $+\infty$ is the same as in the continuous case. It follows from the combination of the lower bounds on $\Pi_{\gamma}(\rho)$ proven in Lemma 2.2 and the global entropy estimate (6.11).

Using again (6.11), the sequence $(\boldsymbol{u}^{(m)})_{m\in\mathbb{N}}$ is bounded in any discrete norm and the same holds for the sequence $(\delta p^{(m)})_{m\in\mathbb{N}}$ by Lemma 6.7. By the Bolzano-Weierstrass theorem and a norm equivalence argument, there exists a subsequence of $(\boldsymbol{u}^{(m)}, \delta p^{(m)})_{m\in\mathbb{N}}$ which tends, in any discrete norm, to a limit $(\boldsymbol{u}, \delta p)$. Passing to the limit cell-by-cell in (6.1), one obtains that $(\boldsymbol{u}, \delta p)$ is a solution to (6.13). Since this solution is unique, the whole sequence converges, which concludes the proof. \square

7. Asymptotic analysis of the zero Mach limit for a semi-implicit scheme. Another interesting semi-implicit scheme for low viscosity flows (typically a viscosity μ which is of the same order as the space step $h_{\mathcal{T}}$) is a scheme, where in the momentum equation, only the pressure is treated in an implicit way (which is mandatory for stability reasons).

Let $\delta t > 0$ be a constant time step. The approximate solution $(\rho^n, \mathbf{u}^n) \in L_{\mathcal{M}}(\Omega) \times \mathbf{H}_{\mathcal{E},0}(\Omega)$ at time $t_n = n\delta t$ for $1 \leq n \leq N = \lfloor T/\delta t \rfloor$ is computed through the following algorithm:

Knowing $(\rho^n, \mathbf{u}^n) \in L_{\mathcal{M}}(\Omega) \times \mathbf{H}_{\mathcal{E},0}(\Omega)$, solve for $\rho^{n+1} \in L_{\mathcal{M}}(\Omega)$ and $\mathbf{u}^{n+1} \in \mathbf{H}_{\mathcal{E},0}(\Omega)$:

$$\frac{1}{\delta t}(\rho_K^{n+1} - \rho_K^n) + \operatorname{div}(\rho^{n+1} \boldsymbol{u}^{n+1})_K = 0, \qquad \forall K \in \mathcal{M}, \quad (7.1a)$$

$$\frac{1}{\delta t} \left(\rho_{D_{\sigma}}^{n} \boldsymbol{u}_{\sigma}^{n+1} - \rho_{D_{\sigma}}^{n-1} \boldsymbol{u}_{\sigma}^{n} \right) + \operatorname{div}(\rho^{n} \boldsymbol{u}^{n} \otimes \boldsymbol{u}^{n})_{\sigma}^{\operatorname{up}} - \operatorname{div} \boldsymbol{\tau}(\boldsymbol{u}^{n})_{\sigma} + \frac{1}{\varepsilon^{2}} (\boldsymbol{\nabla} p^{n+1})_{\sigma} = 0, \quad \forall \sigma \in \mathcal{E}_{\operatorname{int}}.$$
 (7.1b)

Computing u_{σ}^{n+1} from the second equation and inserting in the first one yields a nonlinear diffusion-convection-reaction problem on the density ρ^{n+1} or the pressure p^{n+1} . This algorithm may also equiva-

lently be set under the form of a pressure-correction scheme:

Prediction step – Compute $\tilde{\boldsymbol{u}}^{n+1} \in \mathbf{H}_{\mathcal{E},0}(\Omega)$ by:

$$\frac{1}{\delta t} \left(\rho_{D_{\sigma}}^{n} \tilde{\boldsymbol{u}}_{\sigma}^{n+1} - \rho_{D_{\sigma}}^{n-1} \boldsymbol{u}_{\sigma}^{n} \right) + \operatorname{div}(\rho^{n} \boldsymbol{u}^{n} \otimes \boldsymbol{u}^{n})_{\sigma}^{\operatorname{up}} - \operatorname{div} \boldsymbol{\tau}(\boldsymbol{u}^{n})_{\sigma} = 0, \qquad \forall \sigma \in \mathcal{E}_{\operatorname{int}}.$$
 (7.2a)

Correction step – Solve for $\rho^{n+1} \in L_{\mathcal{M}}(\Omega)$ and $\boldsymbol{u}^{n+1} \in \mathbf{H}_{\mathcal{E},0}(\Omega)$:

$$\frac{1}{\delta t} \rho_{D_{\sigma}}^{n} (\boldsymbol{u}_{\sigma}^{n+1} - \tilde{\boldsymbol{u}}_{\sigma}^{n+1}) + \frac{1}{\varepsilon^{2}} (\boldsymbol{\nabla} p^{n+1})_{\sigma} = 0, \qquad \forall \sigma \in \mathcal{E}_{\text{int}}.$$
 (7.2b)

$$\frac{1}{\delta t}(\rho_K^{n+1} - \rho_K^n) + \operatorname{div}(\rho^{n+1} \boldsymbol{u}^{n+1})_K = 0, \qquad \forall K \in \mathcal{M}.$$
 (7.2c)

The L²-stability of this scheme is expected to be ensured under a CFL restriction on the time step of the form $\delta t \leq c(h_T/|\mathbf{u}| + h_T^2/\mu)$, provided that an upwind space discretization be used in the convection term of the momentum balance equation. Hence, for the semi-implicit scheme (7.1), this convection term is defined as:

$$\operatorname{div}(\rho \boldsymbol{u} \otimes \boldsymbol{v})_{\sigma}^{\operatorname{up}} = \sum_{\varepsilon \in \bar{\mathcal{E}}(D_{\sigma})} F_{\sigma,\varepsilon}(\rho, \boldsymbol{u}) \ \boldsymbol{v}_{\varepsilon}, \qquad \forall \sigma \in \mathcal{E}_{\operatorname{int}}. \tag{7.3}$$

where the dual mass fluxes $F_{\sigma,\varepsilon}(\rho, \boldsymbol{u})$ are defined as previously in Section 4.2, and where the approximation of the convected velocity on a dual face $\varepsilon = D_{\sigma}|D'_{\sigma}$ is computed with the upwind technique: $\boldsymbol{v}_{\varepsilon} = \boldsymbol{v}_{\sigma}$ if $F_{\sigma,\varepsilon}(\rho, \boldsymbol{u}) \geq 0$, $\boldsymbol{v}_{\varepsilon} = \boldsymbol{v}_{\sigma'}$ otherwise.

The initial data $(\rho_0^{\varepsilon}, \boldsymbol{u}_0^{\varepsilon})$ is assumed to satisfy:

$$\rho_0^{\varepsilon} > 0, \ \rho_0^{\varepsilon} \in \mathcal{L}^{\infty}(\Omega), \ \boldsymbol{u}_0^{\varepsilon} \in \mathcal{H}_0^1(\Omega)^d \text{ and } \|\boldsymbol{u}_0^{\varepsilon}\|_{\mathcal{H}^1(\Omega)^d} + \frac{1}{\varepsilon} \|\operatorname{div}\boldsymbol{u}_0^{\varepsilon}\|_{\mathcal{L}^2(\Omega)} + \frac{1}{\varepsilon} \|\rho_0^{\varepsilon} - 1\|_{\mathcal{L}^{\infty}(\Omega)} \leq C, \ (7.4)$$

for a real number C independent of ε . Moreover, we suppose that u_0^{ε} converges in $L^2(\Omega)^d$ towards a function $u_0 \in L^2(\Omega)^d$. Note that these hypotheses are less restrictive than assuming well-prepared initial data since the density is here assumed to be close to 1 with an ε rate (and not ε^2).

The initialization of the scheme (7.1) is performed similarly to that of the pressure-correction scheme. First, ρ^0 and \boldsymbol{u}^0 are given by the average of the initial conditions ρ_0^ε and $\boldsymbol{u}_0^\varepsilon$ respectively on the primal cells and on the faces of the primal cells; then we compute ρ^{-1} by solving the mass balance equation (7.1a) for n=-1, where the unknown is ρ^{-1} and not ρ^0 . As in the case of the pressure correction scheme, one may prove that the discrete densities ρ_K^{-1} , $K \in \mathcal{M}$, are close to 1 for ε small enough and therefore positive and bounded.

7.1. A priori estimates. The discrete renormalization identities are again valid for the scheme (7.1), thanks to the fact that the mass balance (7.1a) is satisfied. The proof is identical to that of Lemmas 5.3 and 6.4.

LEMMA 7.1 (Discrete renormalization property). A solution to the system (6.1) satisfies for all $K \in \mathcal{M}$ and $0 \le n \le N-1$ the two following identities:

$$\frac{1}{\delta t} \left(\psi_{\gamma}(\rho_K^{n+1}) - \psi_{\gamma}(\rho_K^n) \right) + \operatorname{div}(\psi_{\gamma}(\rho^{n+1})\boldsymbol{u}^{n+1})_K + \wp(\rho_K^{n+1}) \operatorname{div}(\boldsymbol{u}^{n+1})_K + R_K^{n+1} = 0, \tag{7.5}$$

$$\frac{1}{\delta t} \left(\Pi_{\gamma}(\rho_K^{n+1}) - \Pi_{\gamma}(\rho_K^n) \right) + \operatorname{div} \left(\left(\psi_{\gamma}(\rho^{n+1}) - \psi_{\gamma}'(1) \rho^{n+1} \right) \boldsymbol{u}^{n+1} \right)_K + \wp(\rho_K^{n+1}) \operatorname{div} (\boldsymbol{u}^{n+1})_K + R_K^{n+1} = 0, \quad (7.6)$$

where R_K^{n+1} has the same expression as in Lemma 5.3.

Let us now turn to the discrete kinetic energy balance which leads to the L^2 stability of the scheme. We begin with the following proposition which characterizes the rigidity matrix associated with the discretization of the diffusion term in the momentum equation.

PROPOSITION 7.2. Let \mathcal{A} be the $d\sharp \mathcal{E}_{\mathrm{int}} \times d\sharp \mathcal{E}_{\mathrm{int}}$ rigidity matrix associated with the finite element discretization of the diffusion term. The matrix \mathcal{A} is the block matrix $\mathcal{A} = (\mathcal{A}_{\sigma,\sigma'})_{\sigma,\sigma' \in \mathcal{E}_{\mathrm{int}}}$, where for $\sigma, \sigma' \in \mathcal{E}_{\mathrm{int}}$, $\mathcal{A}_{\sigma,\sigma'}$ is the $d \times d$ matrix defined by:

$$\mathcal{A}_{\sigma,\sigma'} = \sum_{K \in \mathcal{M}} \left(\mu \int_{K} \nabla \zeta_{\sigma} \cdot \nabla \zeta_{\sigma'} \mathbf{I} + (\mu + \lambda) \int_{K} \nabla \zeta_{\sigma} \otimes \nabla \zeta_{\sigma'} \right), \tag{7.7}$$

and A is a symmetric positive-definite matrix.

Proof. Let us identify $\boldsymbol{u} = (\boldsymbol{u}_{\sigma})_{\sigma \in \mathcal{E}_{int}}$ and $\boldsymbol{v} = (\boldsymbol{v}_{\sigma})_{\sigma \in \mathcal{E}_{int}}$ with vectors in $\mathbb{R}^{d\sharp \mathcal{E}_{int}}$ and denote (.,.) the canonical scalar product in $\mathbb{R}^{d\sharp \mathcal{E}_{int}}$. The result follows from the elementary computation:

$$\begin{split} (\mathcal{A}\boldsymbol{u},\boldsymbol{v}) &= \sum_{\sigma \in \mathcal{E}_{\mathrm{int}}} \sum_{\sigma' \in \mathcal{E}_{\mathrm{int}}} \mathcal{A}_{\sigma,\sigma'} \boldsymbol{u}_{\sigma'} \cdot \boldsymbol{v}_{\sigma} \\ &= \sum_{\sigma \in \mathcal{E}_{\mathrm{int}}} |D_{\sigma}| \left(-\operatorname{div} \boldsymbol{\tau}(\boldsymbol{u})_{\sigma} \right) \cdot \boldsymbol{v}_{\sigma} \\ &= \sum_{K \in \mathcal{M}} \mu \int_{K} \boldsymbol{\nabla} \hat{\boldsymbol{u}} : \boldsymbol{\nabla} \hat{\boldsymbol{v}} + (\mu + \lambda) \int_{K} (\operatorname{div} \hat{\boldsymbol{u}}) (\operatorname{div} \hat{\boldsymbol{v}}). \end{split}$$

The expression (7.7) of the block-entries of the matrix \mathcal{A} then follows by developing the expression of \hat{u} and \hat{v} on the basis of the shape functions and identifying the terms. \square

The following lemma states the L²-stability of an explicit upwind scheme for the convection-diffusion equation (7.2a), under some CFL restriction on the time step.

LEMMA 7.3 (L²-stability of the prediction step). Any solution to (7.2a), and thus to the explicit scheme (7.1), satisfies the following inequality, for all $0 \le n \le N-1$:

$$\frac{1}{2\delta t} \sum_{\sigma \in \mathcal{E}_{int}} |D_{\sigma}| \left(\rho_{D_{\sigma}}^{n} |\tilde{\boldsymbol{u}}_{\sigma}^{n+1}|^{2} - \rho_{D_{\sigma}}^{n-1} |\boldsymbol{u}_{\sigma}^{n}|^{2} \right) + R_{\mathcal{E}}^{n+1} \le 0, \tag{7.8}$$

where, denoting $\varrho(A)$ the spectral radius of the matrix A, the remainder term R_{ε}^{n+1} is given by:

$$R_{\mathcal{E}}^{n+1} = \sum_{\sigma \in \mathcal{E}_{int}} \left(\frac{\rho_{D_{\sigma}}^{n} |D_{\sigma}|}{2\delta t} - \frac{1}{2} \sum_{\varepsilon \in \bar{\mathcal{E}}(D_{\sigma})} \left(F_{\sigma,\varepsilon}(\rho^{n}, \boldsymbol{u}^{n}) \right)^{-} - \frac{1}{4} \varrho(\mathcal{A}) \right) |\tilde{\boldsymbol{u}}_{\sigma}^{n+1} - \boldsymbol{u}_{\sigma}^{n}|^{2}.$$
 (7.9)

Proof. Taking the scalar product of the momentum equation (7.2a) with $|D_{\sigma}| \tilde{\boldsymbol{u}}_{\sigma}^{n+1}$, we obtain $T_{\sigma}^{\text{conv}} + T_{\sigma}^{\text{diff}} = 0$, with:

$$T_{\sigma}^{\text{conv}} = \left(\frac{|D_{\sigma}|}{\delta t} \left(\rho_{D_{\sigma}}^{n} \tilde{\boldsymbol{u}}_{\sigma}^{n+1} - \rho_{D_{\sigma}}^{n-1} \boldsymbol{u}_{\sigma}^{n}\right) + \sum_{\varepsilon \in \mathcal{E}(D_{\sigma})} F_{\sigma,\varepsilon}(\rho^{n}, \boldsymbol{u}^{n}) \boldsymbol{u}_{\varepsilon}^{n}\right) \cdot \tilde{\boldsymbol{u}}_{\sigma}^{n+1},$$

$$T_{\sigma}^{\text{diff}} = -|D_{\sigma}|\operatorname{div}\boldsymbol{\tau}(\boldsymbol{u}^n)_{\sigma}\cdot\tilde{\boldsymbol{u}}_{\sigma}^{n+1}.$$

For the convection term, the dual density unknowns and mass fluxes are chosen so as to have:

$$\frac{|D_{\sigma}|}{\delta t} \left(\rho_{D_{\sigma}}^{n} - \rho_{D_{\sigma}}^{n-1} \right) + \sum_{\varepsilon \in \mathcal{E}(D_{\sigma})} F_{\sigma,\varepsilon}(\rho^{n}, \boldsymbol{u}^{n}) = 0, \quad \forall \sigma \in \mathcal{E}_{\text{int}},$$

which necessitates a time-shift in order to exploit the mass balance at the previous time step. Hence, following the proof of [33, Lemma A.2], we obtain:

$$T_{\sigma}^{\text{conv}} = \frac{|D_{\sigma}|}{2\delta t} \left(\rho_{D_{\sigma}}^{n} |\tilde{\boldsymbol{u}}_{\sigma}^{n+1}|^{2} - \rho_{D_{\sigma}}^{n-1} |\boldsymbol{u}_{\sigma}^{n}|^{2} \right) + \frac{1}{2} \sum_{\varepsilon \in \mathcal{E}(D_{\sigma})} F_{\sigma,\varepsilon}(\rho^{n}, \boldsymbol{u}^{n}) |\boldsymbol{u}_{\varepsilon}^{n}|^{2} + \frac{|D_{\sigma}|}{2\delta t} \rho_{D_{\sigma}}^{n} |\tilde{\boldsymbol{u}}_{\sigma}^{n+1} - \boldsymbol{u}_{\sigma}^{n}|^{2}$$
$$- \frac{1}{2} \sum_{\varepsilon \in \mathcal{E}(D_{\sigma})} F_{\sigma,\varepsilon}(\rho^{n}, \boldsymbol{u}^{n}) |\boldsymbol{u}_{\varepsilon}^{n} - \boldsymbol{u}_{\sigma}^{n}|^{2} + \sum_{\varepsilon \in \mathcal{E}(D_{\sigma})} F_{\sigma,\varepsilon}(\rho^{n}, \boldsymbol{u}^{n}) (\boldsymbol{u}_{\varepsilon}^{n} - \boldsymbol{u}_{\sigma}^{n}) \cdot (\tilde{\boldsymbol{u}}_{\sigma}^{n+1} - \boldsymbol{u}_{\sigma}^{n}).$$

Thanks to the upwind choice for $\boldsymbol{u}_{\varepsilon}^{n}$, the term $\boldsymbol{u}_{\varepsilon}^{n}-\boldsymbol{u}_{\sigma}^{n}$ vanishes whenever the dual flux $F_{\sigma,\varepsilon}(\rho^{n},\boldsymbol{u}^{n})$ is non-negative. Applying Young's inequality to the product in the last term yields:

$$T_{\sigma}^{\text{conv}} \geq \frac{|D_{\sigma}|}{2\delta t} \left(\rho_{D_{\sigma}}^{n} |\tilde{\boldsymbol{u}}_{\sigma}^{n+1}|^{2} - \rho_{D_{\sigma}}^{n-1} |\boldsymbol{u}_{\sigma}^{n}|^{2} \right) + \frac{1}{2} \sum_{\varepsilon \in \mathcal{E}(D_{\sigma})} F_{\sigma,\varepsilon}(\rho^{n}, \boldsymbol{u}^{n}) |\boldsymbol{u}_{\varepsilon}^{n}|^{2} + \frac{|D_{\sigma}|}{2\delta t} \rho_{D_{\sigma}}^{n} |\tilde{\boldsymbol{u}}_{\sigma}^{n+1} - \boldsymbol{u}_{\sigma}^{n}|^{2}$$

$$- \frac{1}{2} \sum_{\varepsilon \in \mathcal{E}(D_{\sigma})} F_{\sigma,\varepsilon}(\rho^{n}, \boldsymbol{u}^{n})^{-} |\tilde{\boldsymbol{u}}_{\sigma}^{n+1} - \boldsymbol{u}_{\sigma}^{n}|^{2}. \quad (7.10)$$

For the diffusion term, we observe that:

$$\sum_{\sigma \in \mathcal{E}_{r}} T_{\sigma}^{\text{diff}} = (\mathcal{A}\boldsymbol{u}^{n}, \tilde{\boldsymbol{u}}^{n+1}) = (\mathcal{A}\boldsymbol{u}^{n}, \tilde{\boldsymbol{u}}^{n+1} - \boldsymbol{u}^{n}) + (\mathcal{A}\boldsymbol{u}^{n}, \boldsymbol{u}^{n}).$$

The Cauchy-Schwarz inequality for the scalar product associated with the real positive symmetric matrix \mathcal{A} yields

$$(\mathcal{A}u^n, \tilde{u}^{n+1} - u^n) \ge -(\mathcal{A}u^n, u^n)^{\frac{1}{2}} (\mathcal{A}(\tilde{u}^{n+1} - u^n), \tilde{u}^{n+1} - u^n)^{\frac{1}{2}}.$$

Applying Young's inequality yields:

$$\sum_{\sigma \in \mathcal{E}_{int}} T_{\sigma}^{\text{diff}} \ge -\frac{1}{4} (\mathcal{A}(\tilde{\boldsymbol{u}}^{n+1} - \boldsymbol{u}^n), \tilde{\boldsymbol{u}}^{n+1} - \boldsymbol{u}^n) \ge -\frac{1}{4} \varrho(\mathcal{A}) \sum_{\sigma \in \mathcal{E}_{int}} |\tilde{\boldsymbol{u}}_{\sigma}^{n+1} - \boldsymbol{u}_{\sigma}^n|^2.$$
 (7.11)

By the conservativity of the dual fluxes, taking the sum of (7.10) over $\sigma \in \mathcal{E}_{int}$ and summing the result with (7.11) yields the expected inequality (7.8).

We are now in position to state the following local-in-time kinetic energy balance.

LEMMA 7.4 (Discrete kinetic energy balance). Any solution to the explicit scheme (7.1) satisfies the following inequality, for all $0 \le n \le N-1$:

$$\frac{1}{2\delta t} \sum_{\sigma \in \mathcal{E}_{int}} |D_{\sigma}| \left(\rho_{D_{\sigma}}^{n} |\tilde{\boldsymbol{u}}_{\sigma}^{n+1}|^{2} - \rho_{D_{\sigma}}^{n-1} |\boldsymbol{u}_{\sigma}^{n}|^{2} \right) + \frac{1}{\varepsilon^{2}} \sum_{\sigma \in \mathcal{E}_{int}} |D_{\sigma}| (\boldsymbol{\nabla} p^{n+1})_{\sigma} \cdot \boldsymbol{u}_{\sigma}^{n+1} \\
+ \frac{\delta t}{2\varepsilon^{4}} \sum_{\sigma \in \mathcal{E}_{int}} \frac{|D_{\sigma}|}{\rho_{D_{\sigma}}^{n}} \left| (\boldsymbol{\nabla} p^{n+1})_{\sigma} \right|^{2} + R_{\varepsilon}^{n+1} \leq 0, \quad (7.12)$$

where $R_{\mathcal{E}}^{n+1}$ is defined in Lemma 7.3.

Proof. As for the first pressure correction scheme, we write the velocity correction equation as:

$$\left(\frac{\rho_{D_{\sigma}}^{n}}{\delta t}\right)^{1/2}\boldsymbol{u}_{\sigma}^{n+1} + \left(\frac{\delta t}{\rho_{D}^{n}}\right)^{1/2}\frac{1}{\varepsilon^{2}}(\boldsymbol{\nabla}p^{n+1})_{\sigma} = \left(\frac{\rho_{D_{\sigma}}^{n}}{\delta t}\right)^{1/2}\tilde{\boldsymbol{u}}_{\sigma}^{n+1},$$

square this relation and sum it with (7.8), which yields the desired inequality. \square

We may now state the following result.

LEMMA 7.5 (Local-in-time discrete entropy inequality, existence of a solution). Let $\varepsilon > 0$ and assume that the initial data satisfies (7.4). Then, for ε small enough to ensure that ρ^{-1} is positive, there exists a solution $(\rho^n, \mathbf{u}^n)_{0 \le n \le N}$ to the scheme (7.1), and for $1 \le n \le N$, the density ρ^n is positive. Moreover, assuming that the time-step satisfies the following CFL restriction:

$$\delta t \le \min_{\sigma \in \mathcal{E}_{int}} \frac{4 \,\rho_{D_{\sigma}}^{n} |D_{\sigma}|}{2 \sum_{\varepsilon \in \bar{\mathcal{E}}(D_{\sigma})} \left(F_{\sigma,\varepsilon}(\rho^{n}, \boldsymbol{u}^{n}) \right)^{-} + \varrho(\mathcal{A})},\tag{7.13}$$

the following inequality holds:

$$\frac{1}{2} \sum_{\sigma \in \mathcal{E}_{int}} |D_{\sigma}| \left(\rho_{D_{\sigma}}^{n} |\boldsymbol{u}_{\sigma}^{n+1}|^{2} - \rho_{D_{\sigma}}^{n-1} |\boldsymbol{u}_{\sigma}^{n}|^{2} \right) + \frac{1}{\varepsilon^{2}} \sum_{K \in \mathcal{M}} |K| \left(\Pi_{\gamma} (\rho_{K}^{n+1}) - \Pi_{\gamma} (\rho_{K}^{n}) \right) + \frac{\delta t^{2}}{2 \varepsilon^{4}} \sum_{\sigma \in \mathcal{E}_{int}} \frac{|D_{\sigma}|}{\rho_{D_{\sigma}}^{n}} \left| (\boldsymbol{\nabla} p^{n+1})_{\sigma} \right|^{2} + \mathcal{R}^{n+1} \leq 0, \quad (7.14)$$

where $\mathcal{R}^{n+1} = R_{\mathcal{E}}^{n+1} + \varepsilon^{-2} \sum_{K \in \mathcal{M}} R_K^{n+1} \ge 0$. Proof. The positivity of the density is a consequence of the properties of the upwind choice (4.2) for ρ in the mass balance of the correction step (7.1a). After multiplication by $\varepsilon^{-2}|K|$, we sum the relative entropy balance (7.6) over the primal cells, and sum the obtained relation with the kinetic energy balance (7.12). Since the discrete gradient and divergence operators are dual with respect to the L² inner product (see (4.10)), we get (7.14). Under the CFL condition (7.13), the remainder term $R_{\mathcal{E}}^{n+1}$ defined in (7.9) is non-negative. The existence of a solution $(\rho^{n+1}, \boldsymbol{u}^{n+1})$ to the scheme (7.1) follows form the Brouwer fixed point theorem, by an easy adaptation of the proof of [18, Proposition 5.2].

The restriction (7.13) on the time-step is a convective-diffusive CFL condition. In particular, it is satisfied if the time step simultaneously satisfies the following two conditions:

$$\delta t \leq \min_{\sigma \in \mathcal{E}_{\mathrm{int}}} \frac{\rho_{D_{\sigma}}^{n} |D_{\sigma}|}{\sum_{\varepsilon \in \mathcal{E}(D_{\sigma})} \left(F_{\sigma,\varepsilon}(\rho^{n}, \boldsymbol{u}^{n}) \right)^{-}} \quad \text{and} \quad \delta t \leq \min_{\sigma \in \mathcal{E}_{\mathrm{int}}} \frac{2 \, \rho_{D_{\sigma}}^{n} |D_{\sigma}|}{\varrho(\mathcal{A})}.$$

The first condition is a convective CFL restriction associated with the velocity of the fluid, which is classical for explicit schemes. As for the second condition, it is also a classical diffusive CFL restriction for explicit schemes. Indeed, if the Lamé coefficients μ and λ are of the same order, usual regularity assumptions on the mesh imply that:

$$\varrho(\mathcal{A}) \propto \mu \, h_{\mathcal{T}}^{d-2},$$

where $h_{\mathcal{T}}$ is a characteristic length of the mesh cells. Therefore, if the viscosity μ is small, typically $\mu \approx h_{\mathcal{T}}$, the diffusive CFL restriction is comparable to the convective CFL restriction.

Lemma 7.6 (Global discrete entropy inequality). Let $\varepsilon > 0$ and assume that the initial data $(\rho_0^{\varepsilon}, \mathbf{u}_0^{\varepsilon})$ satisfies (7.4). By Lemma 7.5, for ε small enough, there exists a solution $(\rho^n, \mathbf{u}^n)_{0 \le n \le N}$ to the scheme (7.1). Moreover, if the time-step satisfies the CFL restriction (7.13) for all $1 \le n \le N$, then there exists C > 0 independent of ε such that, for ε small enough and for all $1 \le n \le N$:

$$\frac{1}{2} \sum_{\sigma \in \mathcal{E}_{int}} |D_{\sigma}| \ \rho_{D_{\sigma}}^{n-1} \ |\boldsymbol{u}_{\sigma}^{n}|^{2} + \frac{1}{\varepsilon^{2}} \sum_{K \in \mathcal{M}} |K| \Pi_{\gamma}(\rho_{K}^{n}) + \frac{\delta t^{2}}{2 \varepsilon^{4}} \sum_{k=1}^{n} \sum_{\sigma \in \mathcal{E}_{int}} \frac{|D_{\sigma}|}{\rho_{D_{\sigma}}^{k-1}} \left| (\boldsymbol{\nabla} p^{k})_{\sigma} \right|^{2} \le C.$$
 (7.15)

Proof. Multiplying equation (7.14) by δt and summing over the time steps yields for $1 \leq n \leq N$:

$$\frac{1}{2} \sum_{\sigma \in \mathcal{E}_{int}} |D_{\sigma}| \; \rho_{D_{\sigma}}^{n-1} \; |\boldsymbol{u}_{\sigma}^{n}|^{2} + \frac{1}{\varepsilon^{2}} \sum_{K \in \mathcal{M}} |K| \, \Pi_{\gamma}(\rho_{K}^{n}) + \frac{\delta t^{2}}{2 \, \varepsilon^{4}} \sum_{k=1}^{n} \sum_{\sigma \in \mathcal{E}_{int}} \frac{|D_{\sigma}|}{\rho_{D_{\sigma}}^{k-1}} \left| (\boldsymbol{\nabla} p^{k})_{\sigma} \right|^{2} + \mathcal{R}^{n}$$

$$\leq \frac{1}{2} \sum_{\sigma \in \mathcal{E}_{int}} |D_{\sigma}| \; \rho_{D_{\sigma}}^{-1} \; |\boldsymbol{u}_{\sigma}^{0}|^{2} + \frac{1}{\varepsilon^{2}} \sum_{K \in \mathcal{M}} |K| \; \Pi_{\gamma}(\rho_{K}^{0}), \quad (7.16)^{n}$$

with
$$\mathcal{R}^n = \sum_{k=0}^{n-1} \left(R_{\mathcal{E}}^{k+1} + \varepsilon^{-2} \sum_{K \in \mathcal{M}} R_K^{k+1} \right) \ge 0.$$

Let us prove that the right hand side of (7.16) is uniformly bounded for all ε small enough. As in Lemma 6.2, one may prove that under (7.4), ρ_K^{-1} is bounded for all $K \in \mathcal{M}$ for ε small enough and therefore so is $\rho_{D_{\sigma}}^{-1}$ for all $\sigma \in \mathcal{E}_{int}$. Hence, since u_0^{ε} is uniformly bounded in $H^1(\Omega)^d$ by (7.4), a classical trace inequality yields the boundedness of the first term. By (7.4), one has $|\rho_K^0 - 1| \leq C\varepsilon$ for all $K \in \mathcal{M}$. Hence, by (2.8), the second term is also uniformly bounded with respect to ε . \square

From now on, we need to assume that we use a time step independent of the Mach number and satisfying the constraint (7.13) (which involves the velocity field, which itself depends on ε). The existence of such a time step is proven in Appendix A.

Under this assumption, by the same arguments as for the pressure correction scheme, we get that the dynamic pressure is controlled independently of ε ; this is stated in the following lemma.

LEMMA 7.7 (Control of the pressure). Let $\varepsilon > 0$ and assume that the initial data $(\rho_0^{\varepsilon}, \mathbf{u}_0^{\varepsilon})$ satisfies (7.4). Then, there exists a solution $(\rho^n, \mathbf{u}^n)_{0 \le n \le N}$ to the scheme (7.1). Let $p^n = \wp(\rho^n)$ and define $\delta p^n = \{\delta p_K^n, K \in \mathcal{M}\}$ where $\delta p_K^n = (p_K^n - m(p^n))/\varepsilon^2$ with $m(p^n)$ the mean value of p^n over Ω . If the time step δt satisfies the CFL condition (7.13) for all $1 \le n \le N$ independently of the Mach number ε , then, one has, for all $1 \le n \le N$:

$$\|\delta p^n\| \le C_{\mathcal{T},\delta t},\tag{7.17}$$

where the real number $C_{\mathcal{T},\delta t}$ depends on the mesh and the time step but not on ε , and $\|\cdot\|$ stands for any norm on the space of discrete functions.

7.2. Incompressible limit of the scheme. By the same proof as for the previous pressure correction scheme, we have the following convergence result.

THEOREM 7.8 (Incompressible limit of the semi-implicit scheme (7.1)).

Let $(\varepsilon^{(m)})_{m\in\mathbb{N}}$ be a sequence of positive real numbers tending to zero. Let the associated sequence of initial data $(\rho_0^{\varepsilon^{(m)}}, \mathbf{u}_0^{\varepsilon^{(m)}})$ satisfy (7.4), and the time step satisfy the CFL condition (7.13) for all $1 \le n \le N$ independently of m. Let $(\rho^{(m)}, \mathbf{u}^{(m)})$ be a corresponding sequence of solutions of the scheme (7.1). Then the sequence $(\rho^{(m)})_{m\in\mathbb{N}}$ tends to the constant function $\rho = 1$ when m tends to $+\infty$ in $L^{\infty}((0,T), L^{\gamma}(\Omega))$. Moreover, for all $q \in [1, \min(2, \gamma)]$, there exists C > 0 such that:

$$\|\rho^{(m)} - 1\|_{\mathrm{L}^{\infty}((0,T);\mathrm{L}^q(\Omega))} \le C\varepsilon^{(m)}, \quad \text{for } m \text{ large enough.}$$

In addition, the sequence $(\mathbf{u}^{(m)}, \delta p^{(m)})_{m \in \mathbb{N}}$ tends, in any discrete norm, to a limit $(\mathbf{u}, \delta p)$ which is the solution to the following inf-sup stable semi-implicit scheme for the incompressible Navier-Stokes equations:

Knowing $\delta p^n \in L_{\mathcal{M}}(\Omega)$ and $\mathbf{u}^n \in \mathbf{H}_{\mathcal{E},0}(\Omega)$, solve for $\delta p^{n+1} \in L_{\mathcal{M}}(\Omega)$ and $\mathbf{u}^{n+1} \in \mathbf{H}_{\mathcal{E},0}(\Omega)$:

$$\operatorname{div}(\boldsymbol{u}^{n+1})_K = 0, \qquad \forall K \in \mathcal{M}, \qquad (7.18a)$$

$$\frac{1}{\delta t} \left(\boldsymbol{u}_{\sigma}^{n+1} - \boldsymbol{u}_{\sigma}^{n} \right) + \operatorname{div}(\boldsymbol{u}^{n} \otimes \boldsymbol{u}^{n})_{\sigma}^{\operatorname{up}} - \operatorname{div}\boldsymbol{\tau}(\boldsymbol{u}^{n})_{\sigma} + (\boldsymbol{\nabla} \delta p^{n+1})_{\sigma} = 0, \qquad \forall \sigma \in \mathcal{E}_{\operatorname{int}}.$$
 (7.18b)

Appendix A. Existence of a time step verifying the CFL condition (7.13) for all Mach numbers.

In this appendix, we prove that for the semi-implicit scheme (7.1), it is possible to define a time-step δt which satisfies the CFL condition (7.13) independently of the Mach number ε . This allows to prove the discrete global entropy estimate (7.15) independently of the Mach number. More precisely, we prove that under a convective CFL condition which is more restrictive than expected ($\delta t \leq C h_T^{1+\frac{d}{2}}$ instead of $\delta t \leq C h_T$ with C independent of ε), the discrete global entropy estimate (7.15) holds true.

Let $\theta_{\mathcal{T}}$ be a measure of the regularity of the mesh in the classical finite element sense (see for instance [40]). Then for all $K \in \mathcal{M}$ and $\sigma, \sigma' \in \mathcal{E}(K)$, we have $|\sigma'|/|D_{\sigma}| \leq C_1(\theta_{\mathcal{T}}) h_{\mathcal{T}}^{-1}$ for some nondecreasing function C_1 . Moreover, thanks to classical inverse inequalities, there exists a nondecreasing function C_2 such that $\|\boldsymbol{u}\|_{L^{\infty}(\Omega)^d} \leq C_2(\theta_{\mathcal{T}}) h_{\mathcal{T}}^{-\frac{d}{2}} \|\boldsymbol{u}\|_{L^2(\Omega)^d}$ for all $\boldsymbol{u} \in \mathbf{H}_{\mathcal{E}}(\Omega)$.

Since the initial data satisfies (7.4), the initial total energy is uniformly bounded with respect to ε . We denote by C_0 a uniform upper bound (which depends on the constant C in (7.4) and on the spatial discretization \mathcal{T}), which thus satisfies for all $\varepsilon > 0$:

$$\frac{1}{2} \sum_{\sigma \in \mathcal{E}_{\text{int}}} |D_{\sigma}| \; \rho_{D_{\sigma}}^{-1} \; |\boldsymbol{u}_{\sigma}^{0}|^{2} + \frac{1}{\varepsilon^{2}} \sum_{K \in \mathcal{M}} |K| \, \Pi_{\gamma}(\rho_{K}^{0}) \leq C_{0}.$$

We define:

$$C(d, \theta_{\mathcal{T}}, C_0) := \frac{1}{2\sqrt{2}d C_1(\theta_{\mathcal{T}}) C_2(\theta_{\mathcal{T}}) C_0^{\frac{1}{2}}}.$$

We have the following result.

PROPOSITION A.1. Let η be a fixed small parameter in (0,1). If the time step δt satisfies the following CFL condition, which is independent of the Mach number:

$$\delta t \le (1 - \eta) \min \left(C(d, \theta_{\mathcal{T}}, C_0) h_{\mathcal{T}}^{1 + \frac{d}{2}}, \min_{\sigma \in \mathcal{E}_{int}} \frac{2|D_{\sigma}|}{\varrho(\mathcal{A})} \right), \tag{A.1}$$

then there exists $\bar{\varepsilon}$ (depending on γ , the spatial discretization \mathcal{T} , the constant C in (7.4) and on η) such that for all $\varepsilon \in (0, \bar{\varepsilon})$:

$$\max_{n=0..N} \left\{ \frac{1}{2} \sum_{\sigma \in \mathcal{E}_{\text{int}}} |D_{\sigma}| \ \rho_{D_{\sigma}}^{n-1} \ |\boldsymbol{u}_{\sigma}^{n}|^{2} + \frac{1}{\varepsilon^{2}} \sum_{K \in \mathcal{M}} |K| \Pi_{\gamma}(\rho_{K}^{n}) \right\} \le C_{0}.$$
(A.2)

Remark A.1. As a by-product of the proof, we can see that, if the time step δt satisfies the CFL condition (A.1), then it satisfies the classical CFL condition (7.13) independently of the Mach number ε , and this also allows to prove (A.2). Actually the proof given hereunder consists in proving (7.13) and (A.2) simultaneously, thanks to an induction process.

Proof. Let δt satisfy the CFL condition (A.1). Let $(\alpha_{\varepsilon}^n)_{n=0..N}$ and $(\beta_{\varepsilon}^n)_{n=0..N}$ be the two sequences defined by:

$$\alpha_{\varepsilon}^{n} := \min \left(\min_{\sigma \in \mathcal{E}_{int}} \frac{\rho_{D_{\sigma}}^{n}}{|D_{\sigma}|^{-1} \sum_{\varepsilon \in \bar{\mathcal{E}}(D_{\sigma})} \left(F_{\sigma,\varepsilon}(\rho^{n}, \boldsymbol{u}^{n}) \right)^{-}} \right., \ \min_{\sigma \in \mathcal{E}_{int}} \frac{2 \, \rho_{D_{\sigma}}^{n}}{|D_{\sigma}|^{-1} \varrho(\mathcal{A})} \right),$$

$$\beta_{\varepsilon}^{n} := \frac{1}{2} \sum_{\sigma \in \mathcal{E}_{\text{int}}} |D_{\sigma}| \ \rho_{D_{\sigma}}^{n-1} \ |\boldsymbol{u}_{\sigma}^{n}|^{2} + \frac{1}{\varepsilon^{2}} \sum_{K \in \mathcal{M}} |K| \Pi_{\gamma}(\rho_{K}^{n}).$$

By Lemma 7.5, we know that for all $0 \le n \le N-1$ and for all $\varepsilon > 0$, $\delta t \le \alpha_{\varepsilon}^n \Longrightarrow \beta_{\varepsilon}^{n+1} \le \beta_{\varepsilon}^n$. Let us prove that for all $0 \le n \le N-1$:

$$\left(\exists \, \varepsilon^n > 0 \text{ such that } \beta_{\varepsilon}^{n+1} \leq \beta_{\varepsilon}^n \leq ... \leq \beta_{\varepsilon}^0 \leq C_0 \text{ for all } \varepsilon \in (0, \varepsilon^n)\right)$$

$$\Longrightarrow \left(\exists \, \varepsilon^{n+1} > 0 \text{ with } \varepsilon^{n+1} \leq \varepsilon^n \text{ such that } \delta t \leq \alpha_{\varepsilon}^{n+1} \text{ for all } \varepsilon \in (0, \varepsilon^{n+1})\right). \quad (A.3)$$

Let us assume that the left-hand side of the above implication holds true for some n such that $0 \le n \le N-1$. Then, for every $\sigma = K|L \in \mathcal{E}_{int}$, we have the following inequalities:

$$|D_{\sigma}|^{-1} \sum_{\varepsilon \in \bar{\mathcal{E}}(D_{\sigma})} \left(F_{\sigma,\varepsilon}(\rho^{n+1}, \boldsymbol{u}^{n+1}) \right)^{-} \leq 2d \max_{\sigma' \in \mathcal{E}(K) \cup \mathcal{E}(L)} |D_{\sigma}|^{-1} |F_{K,\sigma'}(\rho^{n+1}, \boldsymbol{u}^{n+1})|$$

$$\leq 2d \max_{\sigma' \in \mathcal{E}(K) \cup \mathcal{E}(L)} \frac{|\sigma'|}{|D_{\sigma}|} |\rho_{\sigma'}^{n+1}| |\boldsymbol{u}_{\sigma'}^{n+1}|$$

$$\leq 2d C_{1}(\theta_{\mathcal{T}}) h_{\mathcal{T}}^{-1} \left(\max_{K \in \mathcal{M}} |\rho_{K}^{n+1}| \right) \left(\max_{\sigma \in \mathcal{E}_{\text{int}}} |\boldsymbol{u}_{\sigma}^{n+1}| \right).$$
(A.4)

The first inequality in (A.4) follows from hypothesis (H3) in (4.6). We then remark that $\max_{\sigma \in \mathcal{E}_{int}} |\boldsymbol{u}_{\sigma}^{n+1}| = \|\boldsymbol{u}^{n+1}\|_{L^{\infty}(\Omega)^d} \leq C_2(\theta_{\mathcal{T}})h_{\mathcal{T}}^{-\frac{d}{2}}\|\boldsymbol{u}^{n+1}\|_{L^2(\Omega)^d}$ with

$$\|\boldsymbol{u}^{n+1}\|_{\mathrm{L}^2(\Omega)^d} \leq \left(\frac{2}{\min\limits_{K \in \mathcal{M}} \rho_K^n}\right)^{\frac{1}{2}} \left(\frac{1}{2} \sum_{\sigma \in \mathcal{E}_{\mathrm{int}}} |D_{\sigma}| \; \rho_{D_{\sigma}}^n \; |\boldsymbol{u}_{\sigma}^{n+1}|^2 + \frac{1}{\varepsilon^2} \sum_{K \in \mathcal{M}} |K| \, \Pi_{\gamma}(\rho_K^{n+1})\right)^{\frac{1}{2}}.$$

Hence, since the left-hand side of (A.3) is assumed to hold true, we obtain that

$$\|u^{n+1}\|_{L^2(\Omega)^d} \le \left(\frac{2}{\min\limits_{K \in \mathcal{M}} \rho_K^n}\right)^{\frac{1}{2}} C_0^{\frac{1}{2}}.$$

Injecting in (A.4), we obtain:

$$\min_{\sigma \in \mathcal{E}_{\mathrm{int}}} \frac{\rho_{D_{\sigma}}^{n+1}}{|D_{\sigma}|^{-1} \sum_{\varepsilon \in \bar{\mathcal{E}}(D_{\sigma})} \left(F_{\sigma,\varepsilon}(\rho^{n+1}, \boldsymbol{u}^{n+1})\right)^{-}} \geq C(d, \theta_{\mathcal{T}}, C_0) \, h_{\mathcal{T}}^{1+\frac{d}{2}} \, \frac{\min_{K \in \mathcal{M}} \rho_K^{n+1}}{\max_{K \in \mathcal{M}} \rho_K^{n+1}} \left(\min_{K \in \mathcal{M}} \rho_K^n\right)^{\frac{1}{2}}.$$

Invoking once again the left hand side of (A.3), we have $\beta_{\varepsilon}^{n+1} \leq \beta_{\varepsilon}^{n} \leq C_{0}$ for all $\varepsilon \in (0, \varepsilon^{n})$, which implies that $\|\Pi_{\gamma}(\rho^{n+1})\|_{L^{1}(\Omega)} \leq C_{0}\varepsilon^{2}$ and $\|\Pi_{\gamma}(\rho^{n})\|_{L^{1}(\Omega)} \leq C_{0}\varepsilon^{2}$ for all $\varepsilon \in (0, \varepsilon^{n})$. By the results of Lemma 2.2, this implies that for all $K \in \mathcal{M}$, $\rho_{K}^{n} \to 1$ and $\rho_{K}^{n+1} \to 1$ as $\varepsilon \to 0$. Hence, there exists $0 < \varepsilon^{n+1} \leq \varepsilon^{n}$ such that for all $\varepsilon \in (0, \varepsilon^{n+1})$:

$$\min_{\sigma \in \mathcal{E}_{int}} \frac{\rho_{D_{\sigma}}^{n+1}}{|D_{\sigma}|^{-1} \sum_{\varepsilon \in \bar{\mathcal{F}}(D_{\sigma})} \left(F_{\sigma,\varepsilon}(\rho^{n+1}, \boldsymbol{u}^{n+1})\right)^{-}} \ge (1 - \eta)C(d, \theta_{\mathcal{T}}, C_0) h_{\mathcal{T}}^{1 + \frac{d}{2}}.$$
(A.5)

Obviously, ε^{n+1} depends on η . It also depends on γ and on the spatial discretization (namely $\theta_{\mathcal{T}}$ and $h_{\mathcal{T}}$) since one has to bound the L^{\infty}-norm of ρ^n-1 (resp. of $\rho^{n+1}-1$) by the L^{\infty}-norm of ρ^n-1 (resp. of $\rho^{n+1}-1$) thanks to an inverse inequality, combined with the estimates of Lemma 2.2. Upon diminishing ε^{n+1} , we can also prove that for all $\varepsilon \in (0, \varepsilon^{n+1})$:

$$\min_{\sigma \in \mathcal{E}_{int}} \frac{2 \rho_{D_{\sigma}}^{n+1}}{|D_{\sigma}|^{-1} \varrho(\mathcal{A})} \ge \left(\min_{\sigma \in \mathcal{E}_{int}} \frac{2 |D_{\sigma}|}{\varrho(\mathcal{A})} \right) \left(\min_{K \in \mathcal{M}} \rho_{K}^{n+1} \right) \ge (1 - \eta) \min_{\sigma \in \mathcal{E}_{int}} \frac{2 |D_{\sigma}|}{\varrho(\mathcal{A})}. \tag{A.6}$$

Combining (A.5) and (A.6), we obtain that $\delta t \leq \alpha_{\varepsilon}^{n+1}$ for all $\varepsilon \in (0, \varepsilon^{n+1})$. Hence, by a straightforward induction process, the proposition is proved with $\bar{\varepsilon} := \varepsilon^{N-1}$ provided that there exists ε^0 such that $\beta_{\varepsilon}^1 \leq \beta_{\varepsilon}^0$ for all $\varepsilon \in (0, \varepsilon^0)$. It is sufficient to prove that for some $\varepsilon^0 > 0$, $\delta t \leq \alpha_{\varepsilon}^0$ for all $\varepsilon \in (0, \varepsilon^0)$. Following similar steps as above, this is easily proved with ε^0 only depending on the constant C in (7.4) and on the discretization. \square

REFERENCES

- [1] T. Alazard. Low Mach number limit of the full navier-stokes equations. Archive for Rational Mechanics and Analysis, 180(1):1–73, 2006.
- [2] G. Ansanay-Alex, F. Babik, J.-C. Latché, and D. Vola. An L²-stable approximation of the Navier-Stokes convection operator for low-order non-conforming finite elements. *International Journal for Numerical Methods in Fluids*, 66:555-580, 2011
- [3] A. Arakawa and V. Lamb. A potential enstrophy and energy conserving scheme for the shallow water equations. Monthly Weather Review, 109:18–36, 1981.
- [4] H. Bijl and P. Wesseling. A unified method for computing incompressible and compressible flows in boundary-fitted coordinates. *Journal of Computational Physics*, 141:153–173, 1998.
- [5] CALIF³S. A software components library for the computation of reactive turbulent flows. https://gforge.irsn.fr/gf/project/isis.
- V. Casulli and D. Greenspan. Pressure method for the numerical solution of transient, compressible fluid flows. *International Journal for Numerical Methods in Fluids*, 4:1001–1012, 1984.
- [7] C. Chalons, M. Girardin, and S. Kokh. An all-regime Lagrange-projection like scheme for the gas dynamics equations on unstructured meshes. *Communications in Computational Physics*, 20(1):188?233, 2016.
- [8] A.J. Chorin. Numerical solution of the Navier-Stokes equations. Mathematics of Computation, 22:745–762, 1968.
- [9] P. Colella and K. Pao. A projection method for low speed flows. *Journal of Computational Physics*, 149:245–269, 1999.
- [10] F. Cordier, P. Degond, and A. Kumbaro. An asymptotic-preserving all-speed scheme for the Euler and Navier-Stokes equations. *Journal of Computational Physics*, 231:5685–5704, 2012.
- [11] M. Crouzeix and P.A. Raviart. Conforming and nonconforming finite element methods for solving the stationary Stokes equations. *RAIRO Série Rouge*, 7:33–75, 1973.
- [12] R. Danchin. Zero Mach number limit in critical spaces for compressible Navier? Stokes equations. Annales Scientifiques de l?cole Normale Suprieure, 35(1):27 75, 2002.
- [13] P. Degond and M. Tang. All speed scheme for the low Mach number limit of the isentropic Euler equations. *Communications in Computational Physics*, 10:1–31, 2011.
- [14] S. Dellacherie. Analysis of Godunov type schemes applied to the compressible Euler system at low Mach number. Journal of Computational Physics, 229:978–1016, 2010.
- [15] B. Desjardins and E. Grenier. Low Mach number limit of viscous compressible flows in the whole space. *Proceedings of the Royal Society of London A: Mathematical, Physical and Engineering Sciences*, 455:2271–2279, 1999.
- [16] B. Desjardins, E. Grenier, P.-L. Lions, and N. Masmoudi. Incompressible limit for solutions of the isentropic Navier-Stokes equations with dirichlet boundary conditions. *Journal de Mathématiques Pures et Appliquées*, 78:461–471, 1999.
- [17] D. G. Ebin. Motion of slightly compressible fluids in a bounded domain. i. Communications on Pure and Applied Mathematics, 35(4):451–485, 1982.
- [18] R. Eymard, T. Gallouët, R. Herbin, and J.-C. Latché. Convergence of the MAC Scheme for the Compressible Stokes Equations. SIAM Journal on Numerical Analysis, 48:2218–2246, 2010.
- [19] E. Feireisl. Asymptotic analysis of the full Navier-Stokes-Fourier system: From compressible to incompressible fluid flows. Russian Mathematical Surveys, 62(3):511, 2007.
- [20] I. Gallagher. Résultats récents sur la limite incompressible. Séminaire Bourbaki 2003-2004, 926, 2003.
- [21] L. Gastaldo, R. Herbin, and J.-C. Latché. A discretization of phase mass balance in fractional step algorithms for the drift-flux model. *IMA Journal of Numerical Analysis*, 31:116–146, 2011.
- [22] D. Grapsas, R. Herbin, W. Kheriji, and J.-C. Latché. An unconditionally stable staggered pressure correction scheme for the compressible Navier-Stokes equations. SMAI Journal of Computational Mathematics, 2:51–97, 2016.
- [23] J.L. Guermond, P. Minev, and J. Shen. An overview of projection methods for incompressible flows. Computer Methods in Applied Mechanics and Engineering, 195:6011–6045, 2006.
- [24] H. Guillard. Recent developments in the computation of compressible low Mach flows. Flow, Turbulence and Combustion, 76:363–369, 2006.
- [25] H. Guillard and A. Murrone. On the behaviour of upwind schemes in the low Mach number limit: II. Godunov type schemes. Computers & Fluids, 33:655–675, 2004.
- [26] H. Guillard and C. Viozat. On the behaviour of upwind schemes in the low Mach number limit. Computers & Fluids, 28:63–86, 1999.
- [27] J. Haack, S. Jin, and J.-G. Liu. An all-speed asymptotic-preserving method for the isentropic Euler and Navier-Stokes equations. Communications in Computational Physics, 12:955–980, 2012.
- [28] F.H. Harlow and A.A. Amsden. Numerical calculation of almost incompressible flow. Journal of Computational Physics, 3:80–93, 1968.
- [29] F.H. Harlow and A.A. Amsden. A numerical fluid dynamics calculation method for all flow speeds. *Journal of Computational Physics*, 8:197–213, 1971.
- [30] F.H. Harlow and J.E. Welsh. Numerical calculation of time-dependent viscous incompressible flow of fluid with free surface. *Physics of Fluids*, 8:2182–2189, 1965.
- [31] R. Herbin, W. Kheriji, and J.-C. Latché. Pressure correction staggered schemes for barotropic one-phase and two-phase flows. *Computers and Fluids*, 88:524–542, 2013.
- [32] R. Herbin, W. Kheriji, and J.-C. Latché. On some implicit and semi-implicit staggered schemes for the shallow water and Euler equations. *Mathematical Modelling and Numerical Analysis*, 48:1807–1857, 2014.
- [33] R. Herbin, J.-C. Latché, and T.T. Nguyen. Consistent segregated staggered schemes with explicit steps for the isentropic and full Euler equations. *Mathematical Modelling and Numerical Analysis, to appear,* 2017.
- [34] R.I. Issa. Solution of the implicitly discretised fluid flow equations by operator splitting. Journal of Computational Physics, 62:40–65, 1985.
- [35] R.I. Issa, A.D. Gosman, and A.P. Watkins. The computation of compressible and incompressible recirculating flows by a non-iterative implicit scheme. *Journal of Computational Physics*, 62:66–82, 1986.
- [36] K.C. Karki and S.V. Patankar. Pressure based calculation procedure for viscous flows at all speeds in arbitrary configurations. AIAA Journal, 27:1167–1174, 1989.
- [37] S. Klainerman and A. Majda. Singular limits of quasilinear hyperbolic systems with large parameters and the incompressible limit of compressible fluids. Communications on Pure and Applied Mathematics, 34(4):481–524,

- 1981.
- [38] N. Kwatra, J. Su, J.T. Grétarsson, and R. Fedkiw. A method for avoiding the acoustic time step restriction in compressible flow. *Journal of Computational Physics*, 228:4146–4161, 2009.
- [39] J.-C. Latché, B. Piar, and K. Saleh. A discrete kinetic energy preserving convection operator for variable density flows on locally refined staggered meshes. *in preparation*, 2018.
- [40] J.-C. Latché and K. Saleh. A convergent staggered scheme for variable density incompressible Navier-Stokes equations. Mathematics of Computation, to appear, 2018.
- [41] P.-L. Lions and N. Masmoudi. Incompressible limit for a viscous compressible fluid. *Journal de Mathmatiques Pures et Appliquées*, 77:585–627, 1998.
- [42] A. Majda and J. Sethian. The derivation and numerical solution of the equations for zero Mach number solution. Combustion Science and Techniques, 42:185–205, 1985.
- [43] J.J. McGuirk and G.J. Page. Shock capturing using a pressure-correction method. AIAA Journal, 28:1751–1757, 1990.
- [44] G. Métivier and S. Schochet. The incompressible limit of the non-isentropic Euler equations. Archive for Rational Mechanics and Analysis, 158(1):61–90, 2001.
- [45] Y. Moguen, T. Kouksou, P. Bruel, J. Vierendeels, and E. Dick. Pressure-velocity coupling allowing acoustic calculation in low Mach number flow. *Journal of Computational Physics*, 231:5522–5541, 2012.
- [46] S. Noelle, G. Bispen, K.R. Arun, M Lukáčová-Medviďová, and C.-D. Munz. A weakly asymptotic preserving low Mach number scheme for the Euler equations of gas dynamics. SIAM Journal of Scientific Computing, 36:989–1024, 2014.
- [47] R. Rannacher and S. Turek. Simple nonconforming quadrilateral Stokes element. Numerical Methods for Partial Differential Equations, 8:97–111, 1992.
- [48] R. Temam. Sur l'approximation de la solution des équations de Navier-Stokes par la méthode des pas fractionnaires II. Arch. Rat. Mech. Anal., 33:377–385, 1969.
- [49] E. Turkel. Preconditionning techniques in computational fluid dynamics. Annual Review of Fluid Mechanics, 31:385–416, 1999.
- [50] D.R. Van der Heul, C. Vuik, and P. Wesseling. Stability analysis of segregated solution methods for compressible flow. Applied Numerical Mathematics, 38:257–274, 2001.
- [51] D.R. Van der Heul, C. Vuik, and P. Wesseling. A conservative pressure-correction method for flow at all speeds. Computers & Fluids, 32:1113–1132, 2003.
- [52] J.P. Van Dormaal, G.D. Raithby, and B.H. McDonald. The segregated approach to predicting viscous compressible fluid flows. Transactions of the ASME, 109:268–277, 1987.
- [53] D. Vidović, A. Segal, and P. Wesseling. A superlinearly convergent Mach-uniform finite volume method for the Euler equations on staggered unstructured grids. *Journal of Computational Physics*, 217:277–294, 2006.
- [54] C. Wall, C.D. Pierce, and P. Moin. A semi-implicit method for resolution of acoustic waves in low Mach number flows. Journal of Computational Physics, 181:545–563, 2002.
- [55] I. Wenneker, A. Segal, and P. Wesseling. A Mach-uniform unstructured staggered grid method. International Journal for Numerical Methods in Fluids, 40:1209–1235, 2002.
- [56] S.Y. Yoon and T. Yabe. The unified simulation for incompressible and compressible flow by the predictor-corrector scheme based on the CIP method. Computer Physics Communications, 119:149–158, 1999.
- [57] Zakerzadeh, H. On the Mach-uniformity of the Lagrange-projection scheme. ESAIM: M2AN, 51(4):1343-1366, 2017.