



Spectral Element Method and Discontinuous Galerkin approximation for elasto-acoustic problems

Hélène Barucq, Henri Calandra, Aurélien Citrain, Julien Diaz, Christian Gout

► To cite this version:

Hélène Barucq, Henri Calandra, Aurélien Citrain, Julien Diaz, Christian Gout. Spectral Element Method and Discontinuous Galerkin approximation for elasto-acoustic problems. MATHIAS – TOTAL Symposium on Mathematics, Oct 2017, Paris, France. hal-01690670

HAL Id: hal-01690670

<https://hal.science/hal-01690670>

Submitted on 23 Jan 2018

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

On the coupling of Spectral Element Method with Discontinuous Galerkin approximation for elasto-acoustic problems.

Hélène Barucq¹, Henri Calandra², Aurélien Citrain^{1,3}, Julien Diaz¹ and Christian Gout³

¹ Team project Magique.3D, INRIA.UPPA.CNRS, Pau, France.



² TOTAL SA, CSTJS, Pau, France.

³ INSA Rouen-Normandie Université, LMI EA 3226, 76000, Rouen.

MATHIAS 2017 October 25-27



Why using hybrid meshes?



- Useful when the use of unstructured grid is non-sense (e.g. medium with a layer of water)
- Allows the coupling of numerical methods in order to reduce the computational cost

Elastodynamic system

$x \in \Omega \subset \mathbb{R}^d$, $t \in [0, T]$, $T > 0$:

$$\begin{cases} \rho(x) \frac{\partial \nu}{\partial t}(x, t) = \nabla \cdot \underline{\underline{\sigma}}(x, t) \\ \frac{\partial \underline{\underline{\sigma}}}{\partial t}(x, t) = \underline{\underline{C}}(x) \underline{\underline{\epsilon}}(\nu(x, t)) \end{cases}$$

With :

- $\rho(x)$ the density
- $C(x)$ the elasticity tensor
- $\epsilon(x, t)$ the deformation tensor
- $\nu(x, t)$, the wavespeed
- $\underline{\underline{\sigma}}(x, t)$ the strain tensor

Software written in **Fortran 90** for wave propagation simulation in the **time domain**

Features

Simulation:

- on various types of meshes (**unstructured triangle, structured quadrangle, hybrid**)
 - on **heterogeneous media** (**acoustic, elastic and elasto-acoustic**)
-
- **Discontinuous Galerkin (DG)** on **quadrangle, triangle and hybrid mesh**
 - **Spectral Element Method (SEM)** only on **quadrangle mesh**
 - with various time-schemes : **Runge-Kutta (2 or 4), Leap-Frog**
 - with **p-adaptivity, multi-order computation...**

Table of contents

- 1 Numerical Methods
- 2 Comparison DG/SEM on structured quadrangle mesh
- 3 DG/SEM coupling

1 Numerical Methods

- Discontinuous Galerkin Method (DG)
- Spectral Element Method (SEM)
- Advantages of each method

Discontinuous Galerkin Method

Use discontinuous functions :



mesh



continuous




discontinuous




h adaptivity :



p adaptivity :




Degrees of freedom necessary on each cell :



General principle

- Finite Element Method (FEM) discretization + Gauss-Lobatto quadrature
- Gauss-Lobatto points as degrees of freedom (gives us exponential convergence on L^2 -norm)



- $\int f(x)dx \approx \sum_{j=1}^{N+1} \omega_j f(\xi_j)$
- $\varphi_i(\xi_j) = \delta_{ij}$

Main change with DG

- DG discontinuous, SEM continuous
- Need to define local to global numbering
- Global matrices needed for SEM
- Basis functions computed differently

DG

- Element per element computation (*hp*-adaptivity)
- Time discretization quasi explicit (block diagonal mass matrix)
- Simple to parallelize


SEM

- Couples the flexibility of FEM with the accuracy of the pseudo-spectral method
- Reduces the computational cost when you use structured meshes in comparison with DG
- Simplifies the mass and stiff matrices (mass matrix diagonal)

- 2 Comparison DG/SEM on structured quadrangle mesh
- Description of the test cases
 - Comparative tables

Description of the test cases

Physical parameters



P wavespeed	1000 m.s^{-1}
Density	1 kg.m^{-3}

Second order Ricker Source in P wave
($f_{peak} = 10\text{Hz}$)

General context

- Acoustic homogeneous medium
- Four different meshes : 10000 cells, 22500 cells, 90000 cells, 250000 cells
- CFL computed using power iteration method
- Leap-Frog time scheme
- Four threads parallel execution with OpenMP

Comparative tables

- Comparison between numerical solution and analytical solution obtained using the software Gar6more

Quadrangle mesh 10000 elements:

	CFL	L2-error	CPU-time	Nb of time steps
DG	1.99e-3	2.5e-2	61.96	500
SEM	4.9e-3	1.3e-1	0.73	204
SEM(DG CFL)	1.99e-3	4.8e-2	1.48	502

Quadrangle mesh 22500 elements:

	CFL	L2-error	CPU-time	Nb of time steps
DG	1.33e-3	1.8e-2	252.20	750
SEM	3.26e-3	7e-2	2.42	306
SEM(DG CFL)	1.33e-3	1.2e-2	4.70	751

SEM fifty times faster on a mesh with 22500 cells than DG



3 DG/SEM coupling


- Hybrid meshes structures
- Variationnal formulation
- Space discretization

Hybrid meshes structures

- Need to couple P_k and Q_k structures.
- Need to extend or split some of the structures (e.g. neighbour indexes)
- Necessity to define new face matrices


$$M_{ij}^{K,L} = \int_{K \cap L} \phi_i^K \phi_j^L, \quad M_{ij}^{K,L} = \int_{K \cap L} \psi_i^K \psi_j^L, \quad M_{ij}^{K,L} = \int_{K \cap L} \phi_i^K \psi_j^L$$





Global context

- Domain in two parts : $\Omega_{h,1}$ (**structured quadrangle + SEM**), $\Omega_{h,2}$ (**unstructured triangle + DG**)
- w_1, w_2 the tests-function and ξ_1, ξ_2 the tests-tensors



Variational formulation

SEM variationnal formulation :

$$\begin{cases} \int_{\Omega_{h,1}} \rho \partial_t v_1 \cdot w_1 = - \int_{\Omega_{h,1}} \sigma_1 \cdot \nabla w_1 + \int_{\Gamma_{out}} (\sigma_1 n_1) \cdot w_1 \\ \int_{\Omega_{h,1}} \partial_t \sigma_1 : \xi_1 = - \int_{\Omega_{h,1}} (\nabla(C\xi_1)) \cdot v_1 + \int_{\Gamma_{out}} (C\xi_1 n_1) \cdot v_1 \end{cases}$$

DG variationnal formulation :

$$\begin{cases} \int_{\Omega_{h,2}} \rho \partial_t v_2 \cdot w_2 = - \int_{\Omega_{h,2}} \sigma_2 \cdot \nabla w_2 + \int_{\Gamma_{out}} (\sigma_2 n_2) \cdot w_2 + \int_{\Gamma_{int}} \{\{\sigma_2\}\} [[w_2]] \cdot n_2 \\ \int_{\Omega_{h,2}} \partial_t \sigma_2 : \xi_2 = - \int_{\Omega_{h,2}} (\nabla(C\xi_2)) \cdot v_2 + \int_{\Gamma_{out}} (C\xi_2 n_2) \cdot v_2 + \int_{\Gamma_{int}} \{\{v_2\}\} [[C\xi_2]] \cdot n_2 \end{cases}$$

Variational formulation

SEM variational formulation :

$$\begin{cases} \int_{\Omega_{h,1}} \rho \partial_t v_1 \cdot w_1 = - \int_{\Omega_{h,1}} \sigma_1 \cdot \nabla w_1 + \int_{\Gamma_{out}} (\sigma_1 n_1) \cdot w_1 + \int_{\Gamma_{DG/SEM}} (\sigma_1 n_1) \cdot w_1 \\ \int_{\Omega_{h,1}} \partial_t \sigma_1 : \xi_1 = - \int_{\Omega_{h,1}} (\nabla(C\xi_1)) \cdot v_1 + \int_{\Gamma_{out}} (C\xi_1 n_1) \cdot v_1 + \int_{\Gamma_{DG/SEM}} (C\xi_1 n_1) \cdot v_1 \end{cases}$$

DG variational formulation :

$$\begin{cases} \int_{\Omega_{h,2}} \rho \partial_t v_2 \cdot w_2 = - \int_{\Omega_{h,2}} \sigma_2 \cdot \nabla w_2 + \int_{\Gamma_{out}} (\sigma_2 n_2) \cdot w_2 + \int_{\Gamma_{int}} \{\{\sigma_2\}\} [[w_2]] \cdot n_2 + \int_{\Gamma_{DG/SEM}} (\sigma_2 n_2) \cdot w_2 \\ \int_{\Omega_{h,2}} \partial_t \sigma_2 : \xi_2 = - \int_{\Omega_{h,2}} (\nabla(C\xi_2)) \cdot v_2 + \int_{\Gamma_{out}} (C\xi_2 n_2) \cdot v_2 + \int_{\Gamma_{int}} \{\{v_2\}\} [[C\xi_2]] \cdot n_2 + \int_{\Gamma_{DG/SEM}} (C\xi_2 n_2) \cdot v_2 \end{cases}$$

Computation steps

- ① Simplify the coupling terms and separates the two parts + put $\sigma \cdot n = 0$

$$\begin{cases} \int_{\Omega_{h,1}} \rho \partial_t v_1 \cdot w_1 = - \int_{\Omega_{h,1}} \sigma_1 \cdot \nabla w_1 + \frac{1}{2} \int_{\Gamma_{DG/SEM}} (\sigma_1 + \sigma_2) n_1 \cdot w_1 \\ \int_{\Omega_{h,1}} \partial_t \sigma_1 : \xi_1 = - \int_{\Omega_{h,1}} (\nabla(C\xi_1)) \cdot v_1 + \frac{1}{2} \int_{\Gamma_{DG/SEM}} (C\xi_1 n_1) \cdot (v_1 + v_2) \end{cases}$$

$$\begin{cases} \int_{\Omega_{h,2}} \rho \partial_t v_2 \cdot w_2 = - \int_{\Omega_{h,2}} \sigma_2 \cdot \nabla w_2 + \int_{\Gamma_{int}} \{\{\sigma_2\}\} [[w_2]] \cdot n_2 - \frac{1}{2} \int_{\Gamma_{DG/SEM}} (\sigma_1 + \sigma_2) n_1 \cdot w_2 \\ \int_{\Omega_{h,2}} \partial_t \sigma_2 : \xi_2 = - \int_{\Omega_{h,2}} (\nabla(C\xi_2)) \cdot v_2 + \int_{\Gamma_{int}} \{\{v_2\}\} [[C\xi_2]] \cdot n_2 - \frac{1}{2} \int_{\Gamma_{DG/SEM}} (C\xi_2 n_1) \cdot (v_1 + v_2) \end{cases}$$

Space discretization : SEM part

- φ_i : SEM basis functions
- ψ_i : DG basis functions

$$\begin{cases} M_{\boldsymbol{\nu}_1} \partial_t \boldsymbol{\nu}_{h,1} + R_{\boldsymbol{\sigma}_1} \boldsymbol{\sigma}_{h,1} + R_{\boldsymbol{\sigma}_2}^{2,1} \boldsymbol{\sigma}_{h,2} = 0 \\ M_{\boldsymbol{\sigma}_1} \partial_t \boldsymbol{\sigma}_{h,1} + R_{\boldsymbol{\nu}_1} \boldsymbol{\nu}_{h,1} + R_{\boldsymbol{\nu}_2}^{2,1} \boldsymbol{\nu}_{h,2} = 0 \end{cases}$$

- $M_{ij} = \int_{\Omega} \varphi_i \varphi_j \approx \sum_{e \in \text{supp}(\varphi_i) \cap \text{supp}(\varphi_j)} \sum_{k=1}^{(r+1)^d} \omega_k \varphi_i(\xi_k) \varphi_j(\xi_k) = \sum_{e \in \text{supp}(\varphi_i) \cap \text{supp}(\varphi_j)} \omega_i \delta_{i,j}$ the mass matrix
- $R_{\rho_{ij}} = \int_{\Omega} \varphi_i \frac{\partial \varphi_j}{\partial \rho}$ stiffness matrix

Matrix of DG/SEM coupling :

$$R_{\sigma_2, ij}^{2,1} = \int_{\partial\Omega_1 \cap \partial\Omega_2} \psi_i \varphi_j$$

Space discretization : DG part

$$\begin{cases} \rho M_{\mathbf{v}_2} \partial_t \mathbf{v}_{h,2} + R_{\sigma_2} \boldsymbol{\sigma}_{h,2} - R_{\sigma_1}^{1,2} \boldsymbol{\sigma}_{h,1} = 0 \\ M_{\sigma_2} \partial_t \boldsymbol{\sigma}_{h,2} + R_{\mathbf{v}_2} \mathbf{v}_{h,2} - R_{\mathbf{v}_1}^{1,2} \mathbf{v}_{h,1} = 0 \end{cases}$$

- $M_{ij}^K = \int_K \psi_i^K \psi_j^K$ mass matrix,
- $R_{p_{ij}}^K = \int_K \psi_i^K \frac{\partial \psi_j^K}{\partial p}$ stiffness matrix,
- $R_{p_{ij}}^{K,L} = \int_{\partial K \cap \partial L} \psi_i^K \psi_j^L n_K \cdot \mathbf{e}_p$ the mass-face matrices

Two new matrices which come from the DG/SEM hybridation $R_*^{1,2}$. Block composed :

$$R_{\mathbf{v}_1}^{1,2} = R_{\sigma_1}^{1,2} = -\frac{1}{2} \int_{\partial \Omega_2 \cap \partial K_1} \psi_j^{K_2} \varphi_i \quad \forall i, j = 1..N_m \quad (1)$$

Conclusion

- ① As expected, SEM is more efficient on structured quadrangle mesh than DG
- ② Show the utility on the use of hybrid meshes and method coupling (reduce computational cost,...)
- ③ Build a variationnal formulation for DG/SEM coupling and find a CFL condition that ensures stability

Perspectives

- Implement DG/SEM coupling on the code (2D)
- Develop h-adaptivity for the structured part
- Develop DG/SEM coupling in 3D

Thank you for your attention !

Questions?