



Macroscopic behavior of gas flow with adsorption through a fractured porous medium

Pascale Royer, Jean-Louis Auriault, T. Strzelecki

► To cite this version:

Pascale Royer, Jean-Louis Auriault, T. Strzelecki. Macroscopic behavior of gas flow with adsorption through a fractured porous medium. *Mechanics Research Communications*, 1996, 23 (1), pp.67 - 73. <10.1016/0093-6413(95)00079-8>. <hal-01713983>

HAL Id: hal-01713983

<https://hal.science/hal-01713983v1>

Submitted on 21 Feb 2018

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



HAL Authorization

MACROSCOPIC BEHAVIOR OF GAS FLOW WITH ADSORPTION THROUGH A FRACTURED POROUS MEDIUM

P. Royer¹, J.L. Auriault¹ and T. Strzelecki²

1. Laboratoire "Sols, Solides, Structures", UJF, INPG, CNRS URA 1511, BP 53X 38041 Grenoble cedex 9, France.

2. Institute of Geotechnics and Hydrotechnics of the Technical University of Wrocław, Wybrzeże Wypiańskiego 27, 50-370 Wrocław, Poland.

Introduction

A fractured porous medium is a double-porosity medium, i.e. it consists of two interacting porous systems whose permeabilities are very different. One of the two porous structures is associated with the fractures and the other one with the porous matrix. Thus, when looking for a macroscopic equivalent description, three separated scales whose characteristic lengths are very different may be under consideration: the pore-scale, the fracture-scale and the macroscopic scale. Modeling gas flow with adsorption through double-porosity media is of particular interest in mining engineering. Indeed, coal is a multiple-porosity system that naturally contains gas. Gas adsorption within coal skeleton is strongly connected to the occurrence of a coal-outburst. To prevent outbursts and also to draw up reliable safety measures, an accurate knowledge of coal-gas system behavior is required. A three-scale homogenization method has been first used in [1] and [2] for the investigation of incompressible fluid flow in a deformable fractured porous medium. The local descriptions at both pore-scale and fracture-scale are expressed by Navier-Stokes equations. This upscaling method allows to convey the influence of the local effects to the macroscopic level. This technique has been taken up again for modeling gas flow through a rigid fractured porous matrix while considering the strong compressibility of the fluid [3], [4], [5], [6]. Here, the adsorption phenomenon is implemented to gas-flow equations at both local scales through additional boundary conditions. Then, the macroscopic behavior is derived via the same three-scale homogenization method.

Medium under Consideration

To fit the homogenization method for periodic structures to three-scales problems, the medium is assumed to be doubly periodic. There is no loss of generality by introducing the assumption of periodicity [7]. At the pore scale, consider the medium to be Ω -periodic and its characteristic length to be l . The solid and the pores occupy the domains Ω_s and Ω_p , respectively, and their common boundary is Γ (figure 1). A second periodic porous structure exists at the fracture level, whose period is Ω' and whose characteristic length is l' , such that $l' \gg l$. The porous matrix and the fractures occupy the domains Ω'_{sp} and Ω'_f , respectively, and their common boundary is noted Γ' (figure 2). As for the macroscopic characteristic length l'' , it must be chosen such that: $l'' \gg l'$. Therefore, the double-porosity medium shows two separations of scales instead of one in the single-porosity case:

- $\frac{l'}{l''} \ll 1$ between the fracture scale and the macroscopic level,
- $\frac{l}{l'} \ll 1$ between the pore scale and the fracture scale.

The macroscopic behavior of such a medium under fluid flow depends upon the relative order of magnitude between these two scale ratios [1], [2]. The largest coupling effects between the pore-flow and the fracture-flow appear when the scales are equally separated, i.e. when $\frac{l}{l'} = O(\frac{l'}{l''}) = O(\varepsilon)$ [1], [2], [3], [4], [5], [6]. This is the case under consideration hereafter for the investigation of gas flow with adsorption in a rigid fractured porous medium.




Figure 1: Pore-scale period.




Figure 2: Fracture-scale period.

Governing Equations

In the pores (Ω_p) and in the fractures (Ω'_f), gas flow is expressed by Navier-Stokes equations. The inertial and transient terms of Navier-Stokes equations can be neglected for the first order equivalent macroscopic description [8]. For the sake of simplicity, assume the fluid to be linear. Thus, the gas state equation is a linear relationship between the fluid pressure and the fluid density. As for the adsorption phenomenon, consider the following isotherm linear adsorption law:

$$(\rho \vec{v}) \cdot \vec{n} = \theta \frac{\partial \rho}{\partial t} \quad \text{on the solid/fluid boundaries,} \quad (1)$$

where $\theta > 0$ and \vec{n} is the exterior normal unit vector of the fluid domain. θ is the ratio of the adsorbed flux to the time-variation of the density in the neighborhood of the solid/fluid boundary. Therefore, this coefficient is different in the pores and in the fractures. Consequently, two constant coefficients θ_p and θ_f are distinguished. This adsorption law is similar to those used in [9], [10] in the context of diffusion with adsorption so as to model pollutant transport in porous media.

Let us assume the system to be initially at rest: fluid velocity is zero-valued and pressure and density are constant (P_0 and ρ_0 , respectively). Thus, the problem is governed by the following set of equations with $k = p$ in the pores (Ω_p) and $k = f$ in the fractures (Ω'_f). Fluid pressure and density are $P_0 + P_k$ and $\rho_0 + \rho_k$, respectively, where P_k and ρ_k are increments.

$$\mu \Delta \vec{v}_k + (\lambda + \mu) \vec{\nabla} (\vec{\nabla} \cdot \vec{v}_k) - \vec{\nabla} P_k = \vec{0}, \quad (2)$$

$$\frac{\partial \rho_k}{\partial t} + \vec{\nabla} \cdot ((\rho_0 + \rho_k) \vec{v}_k) = 0, \quad (3)$$

$$\rho_k = A P_k \quad \text{where } \frac{\rho_0}{P_0} = A \text{ is a constant,} \quad (4)$$

$$((\rho_0 + \rho_p) \vec{v}_p) \cdot \vec{n} = \theta_p \frac{\partial \rho_p}{\partial t} \quad \text{on } \Gamma, \quad (5)$$

$$((\rho_0 + \rho_f) (\vec{v}_f - \langle \vec{v}_p \rangle_\Omega)) \cdot \vec{n}' = \theta_f \frac{\partial \rho_f}{\partial t} \quad \text{on } \Gamma', \quad (6)$$

$$P_f = P_p \quad \text{on } \Gamma' \quad (7)$$

Dimensionless Numbers

The momentum balance (equation (2)) introduces the following dimensionless number:

$$Q_k = \frac{|\vec{\nabla} P_k|}{|\mu \Delta \vec{v}_k + (\lambda + \mu) \vec{\nabla}(\vec{\nabla} \cdot \vec{v}_k)|}, \quad k = p, f.$$

It can be shown [4], [5], [6] that $Q = Q_p = Q_f = O((\frac{\ell}{\mu r})^{-2}) = O(\varepsilon^{-2})$.

The mass balance (equation (3)) shows the Strouhal number:

$$S_k = \frac{|\partial \rho_k / \partial t|}{|\vec{\nabla} \cdot ((\rho_0 + \rho_k) \vec{v}_k)|}, \quad k = p, f.$$

It has been shown [8] that the case of interest is those where $S_f = O(1)$, and that for equally separated scales we have $S_p = O(1)$ [5], [6].

The dimensionless number showing adsorption influence (equations (5) and (6)) is:

$$R_k = \frac{|\theta_k \frac{\partial \rho_k}{\partial t}|}{|(\rho_k \vec{v}_k) \cdot \vec{n}|}, \quad k = p, f.$$

The case of largest adsorption influence for which the homogenization method can be applied is those where $R_p = O(\varepsilon^2)$ and $R_f = O(\varepsilon)$ [6]. Hence, θ_p and θ_f are assumed to be such that the two above relationships are verified.

Thus, when cast in dimensionless form, the governing equations are written as follows, where all quantities are now dimensionless quantities:

$$\varepsilon^2 \mu \Delta \vec{v}_k + \varepsilon^2 (\lambda + \mu) \vec{\nabla}(\vec{\nabla} \cdot \vec{v}_k) - \vec{\nabla} P_k = \vec{0}, \quad (8)$$

$$\frac{\partial \rho_k}{\partial t} + \vec{\nabla} \cdot ((\rho_0 + \rho_k) \vec{v}_k) = 0, \quad (9)$$

$$\rho_k = A P_k, \quad (10)$$

$$((\rho_0 + \rho_p) \vec{v}_p) \cdot \vec{n} = \varepsilon^2 \theta_p \frac{\partial \rho_p}{\partial t} \quad \text{on } \Gamma, \quad (11)$$

$$((\rho_0 + \rho_f) (\vec{v}_f - \langle \vec{v}_p \rangle_\Omega)) \cdot \vec{n}' = \varepsilon \theta_f \frac{\partial \rho_f}{\partial t} \quad \text{on } \Gamma', \quad (12)$$

$$P_f = P_p \quad \text{on } \Gamma' \quad (13)$$

The upscaling process may now be performed. Density, pressure and velocity fields are looked for in the form of asymptotic expansions in power of ε . Once these expansions

have been introduced in the dimensionless set of equations (8-13), the successive boundary-value problems at the different orders of ε must be resolved so as to derive the macroscopic description. Application of homogenization theory to this problem and calculus are detailed in [6]. For a general introduction to the homogenization method for periodic structures, the reader is referred to [7].

Macroscopic Behavior

The derived macroscopic behavior is:

$$(n' + \theta_f a_f) \frac{\partial P_f}{\partial t} + (n + \theta_p a_p) \frac{\langle P_p \rangle_{eff}}{\partial t} - \vec{\nabla} \cdot [(P_0 + P_f) \tilde{K}_f \vec{\nabla} P_f] = 0. \quad (14)$$

- $a_f = \frac{|\Gamma'_f|}{|\Omega'|}$ and $a_p = \frac{|\Gamma_p|}{|\Omega|}$ are specific surfaces
(Γ'_f, Γ_p : solid total surfaces in Ω' and Ω , respectively),
- \tilde{K}_f is the fracture permeability,
- $\langle P_p \rangle_{eff} = \frac{1}{|\Omega|} \int_{\Omega_p} P_p d\Omega$,
- P_p is Ω -periodic and defined by the following boundary-value problem on Ω' :

$$(n + \theta_p a_p) \frac{\partial P_p}{\partial t} - \vec{\nabla} \cdot [(P_0 + P_p) \tilde{K}_p \vec{\nabla} P_p] = 0,$$

$$P_p = P_f \text{ on } \Gamma',$$

- $P_p = \mathcal{F}(P_f)$, where \mathcal{F} is a nonlinear time-dependent functional exhibiting memory effects.

Concluding Remarks

The macroscopic behavior is strongly influenced by the flow in the pores. It induces memory effects and strong non-linearities. This result highlights how the local effects may affect the macroscopic behavior. This macroscopic description is similar to those obtained in terms of concentrations in [9] to depict pollutant transfer. In this latter paper, the authors take up again some of the notations commonly used in the phenomenological diffusion-adsorption

investigations, in order to connect the result obtained through homogenization to the concerned literature. Here, two retardation coefficients similar to those used in Soils Mechanics can be defined:

$$r_p = n + \theta_p a_p \quad \text{in the pores} \qquad r_f = n' + \theta_f a_f \quad \text{in the fractures}$$

These coefficients display both filtration transient contribution (n and n') and adsorption influence (θ_p , a_p , θ_f , a_f).

In this investigation, only the case where $R_p = O(\varepsilon^2)$ and $R_f = O(\varepsilon)$ has been considered. This is the case where the homogenization can be applied for which the adsorption influence is the most important. For higher orders of magnitude of these dimensionless numbers, the seepage process is affected by gas adsorption and then the homogenization cannot be applied. Thus, for $R_p > O(\varepsilon^2)$ and $R_f > O(\varepsilon)$, there is no rigorous equivalent macroscopic description, i.e. independent from sample size and boundary conditions [6]. As for the case in which $R_p < O(\varepsilon^2)$ and $R_f < O(\varepsilon)$, the first-order macroscopic behavior is no longer influenced by adsorption.

The investigation of porous media with several porosities is of greatest importance in petroleum engineering and mining engineering. The latter concerns in particular the determination of setting of factors contributing to coal-gas outburst occurrence. Unless this also depends upon many others phenomena such as absorption and sorption-swelling, the introduction of adsorption in a double-porosity model is an important step in the modeling.

References

1. J.L. Auriault and C. Boutin, TIPM, **7**, 63 (1992)
2. J.L. Auriault and C. Boutin, TIPM, **10**, 153 (1993)
3. P. Royer and J.L. Auriault, *Studia Geotechnica et Mechanica*, **13**, 65 (1992)
4. J.L. Auriault and P. Royer, *C.R.A.S.,II*, 431 (1993)
5. P. Royer and J.L. Auriault, TIPM, **17**, 33 (1994)
6. P. Royer, PhD Diss., Un. J. Fourier, Grenoble, France (1994)
7. J.L. Auriault, *Int. J. Eng. Sci.*, **29**, 785 (1991)
8. J.L. Auriault, T. Strzelecki, J. Bauer and S. He, *Eur. J. Mech. A/Solids*, **9**, 373 (1990)
9. J.L. Auriault and J. Lewandowska, *J.Geot.*, **43**, 457, (1993)
10. J.L. Auriault and J. Lewandowska, *Arch. mech.*, **45**, 51 (1993)

Acknowledgement

This work has been sponsored by the Polish Scientific Research Committee in Warsaw (Grant KBN No.7S10304305).